

# Package ‘MeasurementError.cor’

September 24, 2012

**Title** Measurement Error model estimate for correlation coefficient

**Version** 1.28.0

**Author** Beiying Ding

**Description** Two-stage measurement error model for correlation estimation with smaller bias than the usual sample correlation

**Maintainer** Beiying Ding <bding@amgen.com>

**License** LGPL

**biocViews** Bioinformatics

## R topics documented:

cor.me.matrix	1
cor.me.vector	2

**Index** 4

---

cor.me.matrix	<i>A function to calculate measurement error estimates for all pairs of genes given by the matrix</i>
---------------	-------------------------------------------------------------------------------------------------------

---

## Description

Given a matrix (  $p \times n$  ) for observed values of  $p$  variables and a corresponding matrix for their standard errors, the all pairwise measurement error estimates for true correlations are returned

## Usage

```
cor.me.matrix(exp, se)
```

## Arguments

exp	observed value marix
se	standard error matrix

**Value**

The final estimates for true correlation (i.e. `cor.true`) from the measurement error model

**Note**

The function involves using quasi-newton for linear optimization, "BFGS" is the only implemented method now. Refer to `cor.me.vector` for more details.

**Author(s)**

Beiyong Ding

**References**

Ding, B. Y. and Gentleman, R. (2003) Measurement error model for correlation coefficient estimation and its application in microarray analysis

**See Also**

`cor.me.vector`

**Examples**

```
exp <- matrix(abs(rnorm(200, 1000, 20)), ncol=10)
se <- matrix(abs(rnorm(200, 50, 5)), ncol=10)
cor.me.matrix(exp, se)
```

---

`cor.me.vector`

*A function to calculate measurement error model estimates for correlation coefficient between two variables*

---

**Description**

Given the observed value of two variables and their respective standard error, the measurement error estimate for their correlation coefficient is returned

**Usage**

```
cor.me.vector(exp1, se1, exp2, se2)
```

**Arguments**

<code>exp1</code>	observed value for vector 1
<code>se1</code>	estimated standard error for vector 1
<code>exp2</code>	observed value for vector 2
<code>se2</code>	estimated standard error for vector 2

**Value**

estimate	Vecotr containing the estimates from the measurement error model, i.e. cor.me, cor.true, mu1, mu2, s1, s2 which are correlation for the measurement error distribution of the two variables, true correlation between the two variables, and true mean and standard deviation estimates for the two variables respectively
count	numer of function and gradient evaluation
convergence	0 if converged. See optim() for details

**Note**

Most applicable for microarray expression data where standard errors are readily estimated by most low level analysis softwares. Hence variables can be thought of as genes. One also need to differentiate between cor.me and cor.true: the first one being the correlation between the measurement error distributions of the two genes whereas the second one is the quantity of interest, i.e true correlation between the two gene expression profiles.\

The function involves using quasi-newton for linear optimization, "BFGS" is the only implemented method now.

**Author(s)**

Beiyong Ding

**References**

Ding, B.Y. and Gentleman, R. (2003) Measurement Error Model for correlation coefficient estimation and its application in microarray analysis

**See Also**

cor.me.matrix

**Examples**

```
exp <- matrix(abs(rnorm(200,1000,20)),ncol=10)
se <- matrix(abs(rnorm(200,50,5)),ncol=10)
cor.me.vector(exp[1,],se[1,],exp[2,],se[2,])
```

# Index

\*Topic **multivariate**

cor.me.matrix, [1](#)

cor.me.vector, [2](#)

cor.me.matrix, [1](#)

cor.me.vector, [2](#)