

Package ‘codelink’

September 24, 2012

Version 1.24.0

Date 2012/01/10

Title Manipulation of Codelink Bioarrays data.

Author Diego Diez <diego10ruiz@gmail.com>

Maintainer Diego Diez <diego10ruiz@gmail.com>

Depends R (>= 2.10), methods, Biobase (>= 2.5.5), limma

Imports annotate

Suggests genefilter

Enhances multicore

LazyLoad yes

Description This packages allow reading into R of Codelink bioarray data exported as text from the Codelink software. Also includes some functions to ease the manipulation and pre-processing of data, such in background correction and normalization.

License GPL-2

Collate Codelink-class.R file.R data.R norm.R plot.R
CodelinkSet-class.R CodelinkSet-methods.R CodelinkSet-tools.R
CodelinkSetUnique-class.R CodelinkSetUnique-methods.R filter.R cluster.R

URL <http://www.kuicr.kyoto-u.ac.jp/~diez>

R topics documented:

arrayNew	2
arraySize	3
as.matrix.Codelink	3
averageProbes	4
bkgdCorrect	5
Codelink-class	6
codelink.example	7
codelink.exprset	7
CodelinkSet-class	8

CodelinkSetUnique-class	8
createWeights	9
cutCV	10
decDetect	10
dim.Codelink	11
fc2Cond	12
imageCodelink	12
logCodelink	13
mergeArray	14
na2false	15
normalize	15
normalize.loess	16
plotCorrelation	17
plotCV	18
plotDensities	19
plotMA	19
printHead	21
readCodelink	21
readHeader	22
readHeaderXLS	23
reportCodelink	24
selCV	25
SNR	25
writeCodelink	26
Index	27

arrayNew

Create a new x11 device

Description

Create a new x11 device with dimensions suited to be used with imageCodelink().

Usage

```
arrayNew(f=2, chip="rwgcod")
```

Arguments

chip	character; Codelink chip to be used in imageCodelink.
f	numerical; scaling factor.

Author(s)

Diego Diez

Examples

```
## Not run:
  data(codelink.example)
  arrayNew()
  imageCodelink(codelink.example)

## End(Not run)
```

arraySize	<i>Determine the size of the array</i>
-----------	--

Description

When loading Codelink arrays in text format (as exported from the Codelink software) this function retrieves the correct size of the array. This is useful because those files contain an indetermined number of empty lines at the end. Thus, reading the entire data matrix don't work.

Note

Not meant to be used directly.

Author(s)

Diego Diez

as.matrix.Codelink	<i>Return a matrix of intensity values</i>
--------------------	--

Description

Takes a Codelink object and returns a matrix with the intensity values available.

Usage

```
## S3 method for class 'Codelink'
as.matrix(x, ...)
```

Arguments

x	an object of class "Codelink".
...	additional arguments added to generic as.matrix since R-2.5.x

Value

A matrix with the intensity values.

Author(s)

Diego Diez

See Also[as.matrix](#)**Examples**

```
## Not run:
data(codelink.example)
mat <- as.matrix(codelink.example)
is(mat)

## End(Not run)
```

`averageProbes`*averageProbes*

Description

Takes a CodelinkSet object and computes the average (mean) and sd of duplicated probes.

Usage

```
averageProbes(object, parallel = FALSE)
```

Arguments

<code>object</code>	an object of class "CodelinkSet".
<code>parallel</code>	whether to use a parallel version (requires package multicore).

Details

This function will compute the `mean()` and `sd()` on each duplicated probe (i.e. identical probe id as for `probeNames()`). CodelinkSet objects use the per-array index to enable unique identifiers needed for ExpressionSet derived objects. Although the method `probeNames()` provides access to Codelink probe ids, this is inconvenient when dealing with other packages that make use of `featureNames()` to obtain probe ids and feed them to the corresponding annotation package.

In such cases CodelinkSet objects are not compatible with methods working on ExpressionSet objects. To avoid this limitation it is possible to construct a CodelinkSet object containing unique identifiers (CodelinkSetUnique class) by averaging the intensities of all replicated probes. This is done by computing the `mean()`. The `sd()` is also computed and stored in the slot `sd`.

The current implementation takes a lot of time so a parallelized version of `lapply()` may be used through the package 'multicore'. This is controlled by the argument 'parallel' which is FALSE by default.

According to the authors it is not actually possible to use 'multicore' in a GUI environment like the R.app Cocoa application in R, because this interferes with the events loop. Therefore it is advised to use option 'parallel=TRUE' in an R session running in a shell.

Author(s)

Diego Diez

Examples

```
## Not run:
  data(codelink.example)
foo <- averageProbes(codelink.example)

## End(Not run)
```

bkgdCorrect	<i>Background correction of intensity values.</i>
-------------	---

Description

Takes a Codelink object with Spot mean and Bkgd median values and corrects applying one of the methods available.

Usage

```
bkgdCorrect(object, method = "half", preserve = FALSE, verbose = FALSE,
  offset = 0)
```

Arguments

object	character; an object of class "Codelink".
method	character; the correction method to use, one of "none", "subtract", "half" and "normexp".
preserve	logical; if Smean and Bmedian slots should be preserved.
verbose	logical; if TRUE print some information with method normexp.
offset	numeric; value to add to intensities.

Details

Available methods are: . none: left intensities untouched. . subtract: simple subtraction of Bkgd median from Spot mean. . half: the same as above but avoid negative values setting all intensity values below zero to 0.5. . normexp: apply normexp background adjustment from package limma.

Value

An object of class Codelink with corrected intensity values, that is Ri slot.

Author(s)

Diego Diez

Examples

```
## Not run:
  data(codelink.example)
  codelink.example <- bkgdCorrect(codelink.example, method = "half")

## End(Not run)
```

Codelink-class	<i>Class Codelink</i>
----------------	-----------------------

Description

This is the storage class for Codelink data

Objects from the Class

Object are created after reading text codelink files with readCodelink()

Description

Codelink objects contain a single "list", which contains the following elements:

sample Object of class "character" containing the sample names

file Object of class "character" containing the file names

name Object of class "character" containing the probe ID

method Object of class "list" containing log information

Smean Object of class "matrix" containing spot mean intensities

Bmedian Object of class "matrix" containing background median intensities

Ri Object of class "matrix" containing raw intensities

Ni Object of class "matrix" containing normalized intensities

snr Object of class "matrix" containing signal to noise ratio values

flag Object of class "character" containing assigned flags

Note

More details are in the package vignette

Author(s)

Diego Diez

Examples

```
## Not run:  
  data(codelink.example)
```

```
## End(Not run)
```

codelink.example *Dataset of class 'Codelink'*

Description

Dataset from a h20kcod (Codelink Human UniSet I 20k) array containing 2 samples and ~20000 probes.

Usage

```
data(codelink.example)
```

Format

A [Codelink](#) object containing 20469 probes and 2 samples.

Author(s)

Diego Diez

codelink.exprset *Dataset of class 'CodelinkSet'*

Description

Dataset from a h20kcod (Codelink Human UniSet I 20k) array containing 4 samples and ~20000 probes.

Usage

```
data(codelink.example)
```

Format

A [Codelink](#) object containing 20469 probes and 4 samples.

Author(s)

Diego Diez

CodelinkSet-class *Class CodelinkSet*

Description

This is the storage class for Codelink data

Objects from the Class

Object are created after reading text codelink files with readCodelink2()

Description

CodelinkSet objects are derived from ExpressionSet and therefore inherits all the methods.

Note

More details are in the package vignette

Author(s)

Diego Diez

Examples

```
## Not run:
  data(codelink.exprs)

## End(Not run)
```

CodelinkSetUnique-class
 Class CodelinkSetUnique

Description

This is the storage class for Codelink data– with unique probes

Objects from the Class

Object are created after applying averageProbes() on an object of the class CodelinkSet

Description

CodelinkSetUnique objects are derived from ExpressionSet and therefore inherits all the methods.

Note

More details are in the package vignette

Author(s)

Diego Diez

Examples

```
## Not run:  
  data(codelink.exprs)  
  foo <- averageProbes(codelink.exprs)  
  
## End(Not run)
```

`createWeights` *Create weight for Codelink chips*

Description

Create a weight matrix to be used in limma.

Usage

```
createWeights(object, type=NULL)
```

Arguments

`object` an object of class "Codelink".
`type` weight assigned to each Probe_type.

Author(s)

Diego Diez

Examples

```
## Not run:  
  data(codelink.example)  
  w <- createWeights(codelink.example, type = list(FIDUCIAL = 0.1))  
  
## End(Not run)
```

cutCV	<i>Calculate cutoff based in CV.</i>
-------	--------------------------------------

Description

Takes a Codelink object and calculate cutoff based in CV.

Usage

```
cutCV(object, subset=c(1:dim(object)[2]))
```

Arguments

object	an object of class "Codelink".
subset	subset of arrays to calculate cutoff with

Details

First it computes the median of CV for each gene over all arrays. Then it computes the mean and sd of all medians. Finally:

```
cutoff = mean + 3 * sd
```

Author(s)

Diego Diez

Examples

```
## Not run:  
# data: Normalized Codelink object merged.  
cutoff <- cutCV(data)  
  
## End(Not run)
```

decDetect	<i>Determine decimal type of Codelink files</i>
-----------	---

Description

Determine decimal type of Codelink files.

Usage

```
decDetect(file, nlines)
```

Arguments

file	the file to be read.
nlines	number of lines to skip.

Value

Decimal type.

Author(s)

Diego Diez

`dim.Codelink`

Return the dimension of a Codelink object.

Description

Takes a Codelink object and returns the dimension (genes x samples).

Usage

```
## S3 method for class 'Codelink'  
dim(x)
```

Arguments

`x` an object of class "Codelink".

Value

A numeric vector with the dimensions.

Author(s)

Diego Diez

Examples

```
## Not run:  
data(codelink.example)  
dim(codelink.example)  
  
## End(Not run)
```

fc2Cond	<i>Select probes based on fold change calculation</i>
---------	---

Description

Takes a Codelink object and calculate fold changes (M) between two conditions (samples). Then select genes based on those who pass the passed cutoff.

Usage

```
fc2Cond(object, cond1=NULL, cond2=NULL, fc=1.0, verbose=FALSE)
```

Arguments

object	an object of class "Codelink".
cond1	numeric or character; First condition to compute M.
cond2	numeric or character; Second condition to compute M.
fc	value of the fold change cutoff
verbose	logical; if some information is printed on the console.

Details

Conditions can be passed as characters or as numeric index from the sample slot. The intensities are internally transformed to log2 if needed. The M value is computed as:

$$M = \text{cond1} - \text{cond2}$$
Value

A logical vector indicating which genes pass the cutoff

Author(s)

Diego Diez

imageCodelink	<i>Image plot of Codelink arrays</i>
---------------	--------------------------------------

Description

Plot and image of a Codelink array if the layout information is found.

Usage

```
imageCodelink(object, array = 1, what = "bg",
  low="black", high="white", mar=c(1,1,1,1),
  gr=1, gc=1, log.it=FALSE, ...)
```

Arguments

object	an object of class "Codelink".
array	array to be used.
what	with data plot: bg, smean, ri, ni.
low	color used for low intensities.
high	color used for high intensities-
mar	character vector specifying margins.
gc	numerical; number of grid columns.
gr	numerical; number of grid rows.
log.it	logical; if TRUE data is log2 transformed (if not yet).
...	additional arguments passed to image.

Author(s)

Diego Diez

Examples

```
## Not run:  
  data(codelink.example)  
  imageCodelink(codelink.example)  
  
## End(Not run)
```

logCodelink

Application of logCodelink to Codelink object

Description

Takes a Codelink object and apply logCodelink to intensity values.

Usage

```
logCodelink(object)
```

Arguments

object	an object of class "Codelink" or a list of genes.
--------	---

Value

A Codelink object with logCodelink intensities.

Author(s)

Diego Diez

See Also

[log2](#)

Examples

```
## Not run:
  data(codelink.example)
  codelink.example <- logCodelink(codelink.example)

## End(Not run)
```

mergeArray

Merge Codelink Bioarrays Data

Description

Merge data in a Codelink Object corresponding to same samples. Need a vector indicating the classes and an optional vector indicating the labels of the merged samples.

Usage

```
mergeArray(object, class, names=NULL, method="mean",
           log.it=FALSE, merge.snr=TRUE)
```

Arguments

object	an object of class "Codelink".
class	a numeric vector indicating the classes.
names	an optional character vector indicating labels for each class.
method	the method used to summarize. Currently only "mean" supported.
log.it	logical; a logical indicating if log ₂ values should be returned.
merge.snr	logical; a logical indicating if SNR values should be merged.

Value

An object of class "Codelink".

Author(s)

Diego Diez

Examples

```
## Not run:
  data(codelink.example)
  codelink.example <- bkgdCorrect(codelink.example)
  codelink.example <- normalize(codelink.example, log.it = FALSE)
  codelink.example <- mergeArray(codelink.example, class = c(1,1),
  names = "SAMPLE", log.it = TRUE)

## End(Not run)
```

na2false	<i>Set NAs to FALSE</i>
----------	-------------------------

Description

Takes a logical vector as input and set all NAs to FALSE. This may happens when comparison is done on NA values.

Usage

```
na2false(x)
```

Arguments

x a logical vector.

Value

A logical vector without NAs.

Author(s)

Diego Diez

Examples

```
## Not run:  
a <- c(1, 2, 3, NA, 5)  
b <- c(5, 4, NA, 2, 1)  
sel <- a > b  
sel <- na2false(sel)  
  
## End(Not run)
```

normalize	<i>Normalization wrapper for Codelink objects.</i>
-----------	--

Description

Takes a Codelink object and applies normalization to intensity values.

Usage

```
normalize(object, method = "quantiles", log.it = TRUE, preserve = FALSE,  
weights = NULL, verbose = FALSE)
```

Arguments

object	an object of class "Codelink".
method	method to use in normalization.
log.it	logical; if data should be log2.
preserve	logical; if Ri slot should be preserved.
weights	weights vector for method CyclicLoess.
verbose	should informative output be printed.

Details

Currently supported methods include "loess", "quantiles" and "median". Median normalization is analogous to the default method applied for the manufacturer in the Codelink software. Loess is a modified version of CyclicLoess implemented in the affy package, allowing missing values and weights. Quantile normalization uses the normalizeQuantiles() function in the limma package.

Value

A Codelink object with normalized intensity values.

Author(s)

Diego Diez

Examples

```
## Not run:
data(codelink.example)
# Background correction.
codelink.example <- bkgdCorrect(codelink.example,
  method = "half")
# Normalization.
codelink.example <- normalize(codelink.example,
  method = "quantile")

## End(Not run)
```

normalize.loess

Normalized chips using cyclic loess.

Description

Takes a matrix and apply cyclic loess normalization. It is based in normalize.loess from package affy but supports NA.

Usage

```
normalize.loess(mat, subset = sample(1:(dim(mat)[1]),
  min(c(5000,nrow(mat))))), epsilon = 10^-2, maxit = 1, log.it = TRUE,
  verbose = FALSE, span = 2/3, family.loess = "symmetric", weights = NULL)
```


Arguments

mat	a matrix with columns containing the values of the chips to normalize.
subset	a subset of the data to fit a loess to.
epsilon	a tolerance value (supposed to be a small value - used as a stopping criterium).
maxit	maximum number of iterations.
log.it	logical. If TRUE it takes the log2 of mat
verbose	logical. If TRUE displays current pair of chip being worked on.
span	parameter to be passed the function loess
family.loess	parameter to be passed the function loess . "gaussian" or "symmetric" are acceptable values for this parameter.
weights	a vector of weights for the individual measurements.

Value

A matrix of normalized values.

Author(s)

Diego Diez

Examples

```
## Not run:
mat <- matrix(sample(500), 100, 5)
mat <- normalize.loess(mat)

## End(Not run)
```

plotCorrelation	<i>Plot correlation scatterplot between two arrays</i>
-----------------	--

Description

Takes a Codelink object as argument and plot Correlation scatterplot of two arrays.

Usage

```
plotCorrelation(object, x=1, y=2, cutoff=FALSE, label="type", title=NULL, xlim=NULL, ylim=NULL)
```

Arguments

object	an object of class "Codelink".
x	array to be used in x axis.
y	array to be used in y axis.
cutoff	cutoff used to show fold change.
label	labels to shown.
title	The title of the plot.
xlim	range for the X axis.
ylim	range for the Y axis.

Author(s)

Diego Diez

See Also[plot](#)**Examples**

```
## Not run:
  data(codelink.example)
  plotCorrelation(codelink.example)

## End(Not run)
```

`plotCV`*Plot of CV*

Description

Takes a Codelink object and plot de distribution of CV after applying mergeCodelink.

Usage

```
plotCV(object, subset=c(1:dim(object)[2]), cutoff=NULL, title=NULL, legend.cex=1)
```

Arguments

<code>object</code>	an object of class "Codelink".
<code>subset</code>	subset of arrays to plot
<code>cutoff</code>	cutoff of CV to be shown.
<code>title</code>	title of the plot.
<code>legend.cex</code>	factor to apply to the fonts in the legend to fit.

Author(s)

Diego Diez

plotDensities	<i>Plot Densities</i>
---------------	-----------------------

Description

Takes a Codelink object and plot the distributions of intensities.

Usage

```
plotDensities(object, subset=1:dim(object)[2], title=NULL,
              legend.cex=1, what=NULL)
```

Arguments

object	an object of class "Codelink".
subset	subset of arrays to be plotted (default: all).
title	title of the plot.
legend.cex	font factor use in legend to fit.
what	what data to plot, may be "bg", "smean", "snr", "ri" or "ni"

Author(s)

Diego Diez

Examples

```
## Not run:
  data(codelink.example)
  plotDensities(codelink.example)

## End(Not run)
```

plotMA	<i>MA plot</i>
--------	----------------

Description

Takes a Codelink object and plot M vs A.

Usage

```
plotMA(object, array1 = 1, array2 = NULL, cutoff = c(-1, 1), label = NULL,
        type = NULL, high.list = NULL, high.col = "blue", high.pch = 21,
        high.bg = "cyan", snr = NULL, snr.cutoff = 1, legend.x = NULL, pch = ".",
        subset = NULL, title = NULL, xlim = NULL, ylim = NULL)
```

Arguments

object	an object of class "Codelink" or "MAarrayLM".
array1	first array to be used.
array2	second array to be used.
cutoff	cutoff to be used as fold change marker.
label	type of labeling used in legend.
type	spot type information.
high.list	list of genes highlighted.
high.col	color used for high genes.
high.pch	pch used for high genes.
high.bg	background color used for high genes.
snr	vector with SNR values, usually, taking rowMeans() from a SNR matrix.
snr.cutoff	SNR cutoff used for label spots.
legend.x	relative position of the legend.
pch	pch style used to main spots.
subset	subset of spots used to plot based on 'type' slot.
title	title of the plot.
xlim	range for the X axis.
ylim	range for the Y axis.

Details

This function has suffered recent re-working, to increase the usability and to clean a little bit the code.

If array2 is NULL a median array is computed using all available arrays. Then the values of M and A are computed using the following formula:

$$M = \text{array2} - \text{array1}$$

$$A = (\text{array2} + \text{array1}) / 2$$

If type information is available in the Codelink object, or provided through the 'type' argument, spots are colored based on that. DISCOVERY spots are plotted black with pch = "." whereas the other classes are plotted with different background colors, using gray as border to increase contrasts. For that pch = 21 is used. If snr is specified as label option, the SNR is used to label spots, if available in the Codelink object. In this case, the mean SNR across all arrays is used when array2 = NULL.

Some parameters may not be working right now, as the new function is using a different method to labels spots.

The legend is 'automagically' located, but this can be overridden with the legend.x argument.

In addition, a subset of the spots can be plotted based on type information when available. This allows, for example, to plot only DISCOVERY spots.

Author(s)

Diego Diez

Examples

```
## Not run:  
  data(codelink.example)  
  plotMA(codelink.example)  
  
## End(Not run)
```

printHead

Print briefly a Codelink object

Description

Takes a Codelink object and print a summary information of the data estored. It is based on printHead() from package limma.

Usage

```
printHead(x)
```

Arguments

x an object of class "Codelink".

Author(s)

Diego Diez

readCodelink

Read Codelink Bioarrays Data

Description

Read data exported as text by Codelink Software. It reads values (normalized by Codelink Software or not) flags and information about probes.

Usage

```
readCodelink(files=list.files(pattern="TXT"), sample.name=NULL,  
flag, dec=NULL, type="Spot",preserve=FALSE,verbose=2,  
file.type="Codelink", check=TRUE, fix=FALSE)
```

Arguments

files	list of files to read.
sample.name	vector of same length as files with sample names.
flag	list with values to assign based on Flag quality values.
dec	character indicating the decimal character used in the files.
type	character indicating which base value to read from files.
preserve	logical, if TRUE Bkgd_stdev slot is not removed (if present).
verbose	numerical, set the level of information. Level 2 set as old behaviour. Level > 2 output some debug info.
file.type	exported file type, currently Codelink or XLS file formats supported.
check	logical, check for probe order consistency.
fix	logical, try to fix probe order consistency.

Value

An object of class "Codelink".

Author(s)

Diego Diez

See Also

[read.table](#)

Examples

```
## Not run:
# reading default extension (TXT).
data <- readCodelink()

# specify a different one.
files <- list.files(pattern = "txt")
data <- readCodelink(files = files)

# example.
data(codelink.example)

## End(Not run)
```

readHeader

Read Header from Codelink Bioarrays Files

Description

Read the header of Codelink files and obtain usefull information.

Usage

```
readHeader(file, dec=FALSE)
```

Arguments

file File to read.
dec logical; If TRUE determine decimal point.

Value

A list with header and other usefull information.

Author(s)

Diego Diez

Examples

```
## Not run:  
files <- list.files(pattern = "TXT")  
head <- readHeader(files[1])  
  
## End(Not run)
```

readHeaderXLS

Read Header from XLS exported Codelink Bioarrays Files

Description

Read the header of Codelink files and obtain useful information.

Usage

```
readHeaderXLS(file, dec=FALSE)
```

Arguments

file File to read.
dec logical; If TRUE determine decimal point.

Details

This function is not meant to be used by normal users.

Value

A list with header and other usefull information.

Author(s)

Diego Diez

Examples

```
## Not run:
  files <- list.files(pattern = "TXT")
  head <- readHeaderHeader(files[1])

## End(Not run)
```

reportCodelink	<i>Write a report of genes selected in HTML</i>
----------------	---

Description

Takes a list of genes as argument and writes an HTML page containing information about these genes: Unigene, Genbank, Entrez Gene, etc.

Usage

```
reportCodelink(object, chip, filename = NULL, title = "Main title",
               probe.type = FALSE, other = NULL, other.ord = NULL)
```

Arguments

object	an object of class "Codelink" or a list of genes.
chip	the chip description package.
filename	file name used in the report.
title	title used in the report.
probe.type	logical; if TRUE Probe type information is written.
other	list of vectors containing additional values to add to the report.
other.ord	slot name in other to order genes by.

Value

Nothing, only the HTML file generated.

Author(s)

Diego Diez

See Also

[htmlpage](#)

selCV	<i>Select based on CV cutoff.</i>
-------	-----------------------------------

Description

Takes a Codelink object and select genes based on CV cutoff.

Usage

```
selCV(object, cutoff)
```

Arguments

object	an object of class "Codelink".
cutoff	cutoff normally calculated with cutCV()

Value

A logical vector.

Author(s)

Diego Diez

SNR	<i>Calculate SNR</i>
-----	----------------------

Description

Compute SNR inside read.Codelink.

Usage

```
SNR(Smean, Bmedian, Bstdev)
```

Arguments

Smean	matrix of Smean intensities.
Bmedian	matrix of background median intensities.
Bstdev	matrix of background standard deviation.

Author(s)

Diego Diez

writeCodelink	<i>Write a Codelink object to file.</i>
---------------	---

Description

Export of the data from a codelink object to a text file.

Usage

```
writeCodelink(object, file, dec = ".", sep = "\t", flag = FALSE, chip)
```

Arguments

object	an object of class "Codelink".
file	filename to write object to.
dec	decimal character to use.
sep	delimiter character to use.
flag	should the Codelink flags be written.
chip	chip package to use, normally guessed.

Details

By default, intensities and SNR are wrote to the file. If set, the flag are also output. The header have "INTENSITY_", "SNR_" and "FLAG_" respectibely appendend to the sample name for those values. The default delimiter is the tab character, but that can be set with the sep argument. The default decimal character is the point.

Author(s)

Diego Diez

Examples

```
## Not run:  
  data(codelink.example)  
  writeCodelink(codelink.example, file = "foo.txt")  
  
## End(Not run)
```

Index

*Topic **classes**

- Codelink-class, 6
- CodelinkSet-class, 8
- CodelinkSetUnique-class, 8

*Topic **datasets**

- codelink.example, 7
- codelink.exprset, 7

*Topic **documentation**

- arrayNew, 2
- arraySize, 3
- as.matrix.Codelink, 3
- averageProbes, 4
- bkgdCorrect, 5
- createWeights, 9
- cutCV, 10
- decDetect, 10
- dim.Codelink, 11
- fc2Cond, 12
- imageCodelink, 12
- logCodelink, 13
- mergeArray, 14
- na2false, 15
- normalize, 15
- normalize.loess, 16
- plotCorrelation, 17
- plotCV, 18
- plotDensities, 19
- plotMA, 19
- printHead, 21
- readCodelink, 21
- readHeader, 22
- readHeaderXLS, 23
- reportCodelink, 24
- selCV, 25
- SNR, 25
- writeCodelink, 26

*Topic **utilities**

- arrayNew, 2
- arraySize, 3
- as.matrix.Codelink, 3
- averageProbes, 4
- bkgdCorrect, 5
- createWeights, 9

- cutCV, 10
- decDetect, 10
- dim.Codelink, 11
- fc2Cond, 12
- imageCodelink, 12
- logCodelink, 13
- mergeArray, 14
- na2false, 15
- normalize, 15
- normalize.loess, 16
- plotCorrelation, 17
- plotCV, 18
- plotDensities, 19
- plotMA, 19
- printHead, 21
- readCodelink, 21
- readHeader, 22
- readHeaderXLS, 23
- reportCodelink, 24
- selCV, 25
- SNR, 25
- writeCodelink, 26

[,Codelink-method (Codelink-class), 6

- arrayNew, 2
- arraySize, 3
- as.matrix, 4
- as.matrix.Codelink, 3
- averageProbes, 4
- averageProbes, CodelinkSet-method
(averageProbes), 4

bkgdCorrect, 5

class::CodelinkSet (CodelinkSet-class), 8

class::CodelinkSetUnique
(CodelinkSetUnique-class), 8

class:Codelink (Codelink-class), 6

Codelink, 7

Codelink (Codelink-class), 6

Codelink-class, 6

codelink.example, 7

codelink.exprset, 7

CodelinkSet (CodelinkSet-class), 8
CodelinkSet-class, 8
CodelinkSetUnique
 (CodelinkSetUnique-class), 8
CodelinkSetUnique-class, 8
createWeights, 9
cutCV, 10

decDetect, 10
dim.Codelink, 11

fc2Cond, 12

htmlpage, 24

imageCodelink, 12

loess, 17
log2, 13
logCodelink, 13

mergeArray, 14

na2false, 15
normalize, 15
normalize.loess, 16

plot, 18
plotCorrelation, 17
plotCV, 18
plotDensities, 19
plotDensities,Codelink-method
 (plotDensities), 19
plotMA, 19
printHead, 21

read.table, 22
readCodelink, 21
readHeader, 22
readHeaderXLS, 23
reportCodelink, 24

selCV, 25
show,Codelink-method (Codelink-class), 6
SNR, 25

writeCodelink, 26
writeCodelink,CodelinkSet-method
 (writeCodelink), 26