

# Package ‘rrvgo’

October 17, 2020

**Type** Package

**Title** Reduce + Visualize GO

**Version** 1.0.2

**Author** Sergi Sayols

**Maintainer** Sergi Sayols <sergisayolspuig@gmail.com>

**Description** Reduce and visualize lists of Gene Ontology terms by identifying redudance based on semantic similarity.

**URL** <https://www.bioconductor.org/packages/rrvgo>,  
<https://ssayols.github.io/rrvgo/index.html>

**License** GPL-3

**Encoding** UTF-8

**Imports** GOSemSim, AnnotationDbi, GO.db, pheatmap, ggplot2, ggrepel,  
treemap, tm, wordcloud, shiny, grDevices, grid, stats, methods

**Suggests** knitr, rmarkdown, BiocStyle, testthat (>= 2.1.0),  
shinydashboard, DT, plotly, heatmaply, magrittr, utils,  
clusterProfiler, DOSE, slam, org.Ag.eg.db, org.At.tair.db,  
org.Bt.eg.db, org.Ce.eg.db, org.Cf.eg.db, org.Dm.eg.db,  
org.Dr.eg.db, org.EcK12.eg.db, org.EcSakai.eg.db, org.Gg.eg.db,  
org.Hs.eg.db, org.Mm.eg.db, org.Mmu.eg.db, org.Pf.plasmo.db,  
org.Pt.eg.db, org.Rn.eg.db, org.Sc.sgd.db, org.Ss.eg.db,  
org.Xl.eg.db

**VignetteBuilder** knitr

**RoxygenNote** 7.0.2

**biocViews** Annotation, Clustering, GO, Network, Pathways, Software

**NeedsCompilation** no

**git\_url** <https://git.bioconductor.org/packages/rrvgo>

**git\_branch** RELEASE\_3\_11

**git\_last\_commit** 291fb2d

**git\_last\_commit\_date** 2020-10-05

**Date/Publication** 2020-10-16

## R topics documented:

calculateSimMatrix . . . . .	2
getGoSize . . . . .	3
getGoTerm . . . . .	3
gg_color_hue . . . . .	4
heatmapPlot . . . . .	4
loadOrgdb . . . . .	5
reduceSimMatrix . . . . .	6
scatterPlot . . . . .	7
shiny_rrvgo . . . . .	8
treemapPlot . . . . .	8
wordcloudPlot . . . . .	9

<b>Index</b>	<b>10</b>
--------------	-----------

---

calculateSimMatrix	<i>calculateSimMatrix Calculate the score similarity matrix between terms</i>
--------------------	---

---

### Description

calculateSimMatrix Calculate the score similarity matrix between terms

### Usage

```
calculateSimMatrix(
  x,
  orgdb,
  semdata = GOSemSim::godata(orgdb, ont = ont),
  ont = c("BP", "MF", "CC"),
  method = c("Resnik", "Lin", "Rel", "Jiang", "Wang")
)
```

### Arguments

x	vector of GO terms
orgdb	one of org.* Bioconductor packages (the package name, or the package itself)
semdata	object with prepared GO DATA for measuring semantic similarity
ont	ontology. One of c("BP", "MF", "CC")
method	distance method. One of the supported methods by GOSemSim: c("Resnik", "Lin", "Rel", "Jiang", "Wang")

### Details

All similarity measures available are those implemented in the [GOSemSim package](<https://www.bioconductor.org/packages/release/bioc/vignettes/GOSemSim/inst/doc/GOSemSim-similarity-measurement-based-on-go>) namely the Resnik, Lin, Relevance, Jiang and Wang methods. See the [Semantic Similarity Measurement Based on GO](<https://www.bioconductor.org/packages/release/bioc/vignettes/GOSemSim/inst/doc/GOSemSim-similarity-measurement-based-on-go>) section from the GOSemSim documentation for more details.

**Value**

a square matrix with similarity scores between terms

**Examples**

```
go_analysis <- read.delim(system.file("extdata/example.txt", package="rrvgo"))
simMatrix <- calculateSimMatrix(go_analysis$ID, orgdb="org.Hs.eg.db", ont="BP", method="Rel")
```

---

getGoSize	<i>getGoSize</i> Get GO term size (# of genes)
-----------	--

---

**Description**

getGoSize Get GO term size (# of genes)

**Usage**

```
getGoSize(terms, orgdb)
```

**Arguments**

terms	GO terms
orgdb	one of org.* Bioconductor packages (the package name, or the package itself)

**Value**

number of genes associated with each term

---

getGoTerm	<i>getGoTerm</i> Get the description of a GO term
-----------	---

---

**Description**

getGoTerm Get the description of a GO term

**Usage**

```
getGoTerm(x)
```

**Arguments**

x	GO terms
---	----------

**Value**

the Term slot in GO.db::GOTERM[[x]]

gg\_color\_hue                    *gg\_color\_hue Emulate ggplot2 color palette.*

---

### Description

gg\_color\_hue Emulate ggplot2 color palette.

### Usage

```
gg_color_hue(n)
```

### Arguments

n                    number of colors

### Details

It is just equally spaced hues around the color wheel, starting from 15:

### Value

a vector with colors (alphanumeric)

### Examples

```
## Not run:
plot(1:10, pch=16, cex=2, col=gg_color_hue(10))

## End(Not run)
```

---

heatmapPlot                    *heatmapPlot Plot similarity matrix as a heatmap*

---

### Description

heatmapPlot Plot similarity matrix as a heatmap

### Usage

```
heatmapPlot(
  simMatrix,
  reducedTerms = NULL,
  annotateParent = TRUE,
  annotationLabel = "parentTerm",
  ...
)
```

**Arguments**

`simMatrix` a (square) similarity matrix.  
`reducedTerms` a data.frame with the reduced terms from `reduceSimMatrix()`  
`annotateParent` whether to add annotation of the parent  
`annotationLabel` display "parent" ids or "parentTerm" string  
`...` other parameters sent to `pheatmap::pheatmap()`

**Details**

Matrix with similarity scores between terms is represented as a heatmap.

**Value**

Invisibly a pheatmap object that is a list with components

**Examples**

```

go_analysis <- read.delim(system.file("extdata/example.txt", package="rrvgo"))
simMatrix <- calculateSimMatrix(go_analysis$ID, orgdb="org.Hs.eg.db", ont="BP", method="Rel")
scores <- setNames(-log10(go_analysis$qvalue), go_analysis$ID)
reducedTerms <- reduceSimMatrix(simMatrix, scores, threshold=0.7, orgdb="org.Hs.eg.db")
heatmapPlot(simMatrix, reducedTerms, annotateParent=TRUE, annotationLabel="parentTerm", fontsize=6)

```

---

loadOrgdb

*loadOrgdb Load an orgdb object*


---

**Description**

loadOrgdb Load an orgdb object

**Usage**

```
loadOrgdb(orgdb)
```

**Arguments**

`orgdb` one of org.\* Bioconductor packages

**Value**

the loaded orgdb

---

reduceSimMatrix	<i>reduceSimMatrix</i> Reduce a set of GO terms based on their semantic similarity and scores.
-----------------	--

---

### Description

reduceSimMatrix Reduce a set of GO terms based on their semantic similarity and scores.

### Usage

```
reduceSimMatrix(simMatrix, scores = NULL, threshold = 0.7, orgdb)
```

### Arguments

simMatrix	a (square) similarity matrix
scores	*named* vector with scores (weights) assigned to each term. Higher is better. Can be NULL (default, means no scores. In this case, a default score based on set size is assigned, thus favoring larger sets). Note: if you have p-values as scores, consider $-1 \cdot \log(p)$ -transforming them ( $-\log(p)$ )
threshold	similarity threshold (0-1). Some guidance: Large (allowed similarity=0.9), Medium (0.7), Small (0.5), Tiny (0.4) Defaults to Medium (0.7)
orgdb	one of org.* Bioconductor packages (the package name, or the orgdb object itself)

### Details

Currently, rrvgo uses the similarity between pairs of terms to compute a distance matrix, defined as  $(1 - \text{simMatrix})$ . The terms are then hierarchically clustered using complete linkage, and the tree is cut at the desired threshold, picking the term with the highest score as the representative of each group.

Therefore, higher thresholds lead to fewer groups, and the threshold should be read as the expected similarity of terms within a group (though this is not entirely correct, and you'll see similarities below this threshold being put in the same group).

### Value

a data.frame with all terms and it's "reducer" (NA if the term was not reduced)

### Examples

```
go_analysis <- read.delim(system.file("extdata/example.txt", package="rrvgo"))
simMatrix <- calculateSimMatrix(go_analysis$ID, orgdb="org.Hs.eg.db", ont="BP", method="Rel")
scores <- setNames(-log10(go_analysis$qvalue), go_analysis$ID)
reducedTerms <- reduceSimMatrix(simMatrix, scores, threshold=0.7, orgdb="org.Hs.eg.db")
```

---

scatterPlot	<i>scatterPlot Plot GO terms as scattered points.</i>
-------------	---

---

## Description

scatterPlot Plot GO terms as scattered points.

## Usage

```
scatterPlot(  
  simMatrix,  
  reducedTerms,  
  size = "score",  
  addLabel = TRUE,  
  labelSize = 3  
)
```

## Arguments

simMatrix	a (square) similarity matrix.
reducedTerms	a data.frame with the reduced terms from reduceSimMatrix()
size	what to use as point size. Can be either GO term's "size" or "score"
addLabel	add labels with the most representative term of the group.
labelSize	text size in the label.

## Details

Distances between points represent the similarity between terms. Axes are the first 2 components of applying a PCoA to the (di)similarity matrix. Size of the point represents the provided scores or, in its absence, the number of genes the GO term contains.

## Value

ggplot2 object ready to be printed (or manipulated)

## Examples

```
go_analysis <- read.delim(system.file("extdata/example.txt", package="rrvgo"))  
simMatrix <- calculateSimMatrix(go_analysis$ID, orgdb="org.Hs.eg.db", ont="BP", method="Rel")  
scores <- setNames(-log10(go_analysis$qvalue), go_analysis$ID)  
reducedTerms <- reduceSimMatrix(simMatrix, scores, threshold=0.7, orgdb="org.Hs.eg.db")  
scatterPlot(simMatrix, reducedTerms)
```

---

shiny_rrvgo	<i>shiny_rrvgo Launch an interactive web interface.</i>
-------------	---

---

**Description**

shiny\_rrvgo Launch an interactive web interface.

**Usage**

```
shiny_rrvgo(...)
```

**Arguments**

... other params sent to shiny::runApp().

**Value**

Nothing

---

treemapPlot	<i>treemapPlot Plot GO terms as a treemap.</i>
-------------	--

---

**Description**

treemapPlot Plot GO terms as a treemap.

**Usage**

```
treemapPlot(reducedTerms, size = "score", ...)
```

**Arguments**

reducedTerms	a data.frame with the reduced terms from reduceSimMatrix()
size	what to use as point size. Can be either GO term's "size" or "score"
...	other parameters sent to treemap::treemap()

**Value**

A list from the call to the 'treemap()' function is silently returned

**Examples**

```
go_analysis <- read.delim(system.file("extdata/example.txt", package="rrvgo"))
simMatrix <- calculateSimMatrix(go_analysis$ID, orgdb="org.Hs.eg.db", ont="BP", method="Rel")
scores <- setNames(-log10(go_analysis$qvalue), go_analysis$ID)
reducedTerms <- reduceSimMatrix(simMatrix, scores, threshold=0.7, orgdb="org.Hs.eg.db")
treemapPlot(reducedTerms)
```



---

wordcloudPlot	<i>wordcloudPlot Plot GO reduced terms as a wordcloud.</i>
---------------	--

---

**Description**

wordcloudPlot Plot GO reduced terms as a wordcloud.

**Usage**

```
wordcloudPlot(reducedTerms, onlyParents = TRUE, ...)
```

**Arguments**

reducedTerms	a data.frame with the reduced terms from reduceSimMatrix().
onlyParents	use only parent terms to calculate frequencies.
...	other parameters sent to wordcloud::wordcloud()

**Value**

Nothing

**Examples**

```
go_analysis <- read.delim(system.file("extdata/example.txt", package="rrvgo"))
simMatrix <- calculateSimMatrix(go_analysis$ID, orgdb="org.Hs.eg.db", ont="BP", method="Rel")
scores <- setNames(-log10(go_analysis$qvalue), go_analysis$ID)
reducedTerms <- reduceSimMatrix(simMatrix, scores, threshold=0.7, orgdb="org.Hs.eg.db")
wordcloudPlot(reducedTerms, min.freq=1, colors="black")
```

# Index

[calculateSimMatrix](#), 2

[getGoSize](#), 3

[getGoTerm](#), 3

[gg\\_color\\_hue](#), 4

[heatmapPlot](#), 4

[loadOrgdb](#), 5

[reduceSimMatrix](#), 6

[scatterPlot](#), 7

[shiny\\_rrvgo](#), 8

[treemapPlot](#), 8

[wordcloudPlot](#), 9