

Introduction to antiProfiles

Héctor Corrada Bravo hcorrada@gmail.com

Modified: March 13, 2013. Compiled: April 27, 2020

Introduction

This package implements the gene expression anti-profiles method in [1]. Anti-profiles are a new approach for developing cancer genomic signatures that specifically takes advantage of gene expression heterogeneity. They explicitly model increased gene expression variability in cancer to define robust and reproducible gene expression signatures capable of accurately distinguishing tumor samples from healthy controls.

In this vignette we will use the companion `antiProfilesData` package to illustrate some of the analysis in that paper.

```
> # these are libraries used by this vignette
> require(antiProfiles)
> require(antiProfilesData)
> require(RColorBrewer)
```

Colon cancer expression data

The `antiProfilesData` package contains expression data from normal colon tissue samples and colon cancer samples from two datasets in the Gene Expression Omnibus, <http://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE8671> and <http://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE4183>. Probesets annotated to genes within blocks of hypo-methylation in colon cancer defined in [2]. Let's load the data and take a look at its contents.

```
> data(apColonData)
> show(apColonData)
```

```
ExpressionSet (storageMode: lockedEnvironment)
assayData: 5339 features, 68 samples
  element names: exprs
protocolData: none
phenoData
  sampleNames: GSM95473 GSM95474 ... GSM215114 (68 total)
  varLabels: filename DB_ID ... Status (7 total)
  varMetadata: labelDescription
featureData: none
experimentData: use 'experimentData(object)'
Annotation: hgu133plus2
```

```
> # look at sample types by experiment and status
> table(apColonData$Status, apColonData$SubType, apColonData$ExperimentID)
```

```
, , = GSE4183
```

	adenoma	colorectal_cancer	normal	tumor
0	0	0	8	0
1	15	15	0	0

```
, , = GSE8671
```

	adenoma	colorectal_cancer	normal	tumor
0	0	0	7	0
1	0	0	0	23

The data is stored as an **ExpressionSet**. This dataset contains colon adenomas, benign but hyperplastic growths along with the normal and tumor tissues. Let's remove these from the remaining analysis.

```
> drop=apColonData$SubType=="adenoma"
> apColonData=apColonData[,!drop]
```

Building antiprofiles

The general anti-profile idea is to find genes with hyper-variable expression in cancer with respect to normal samples and classify new samples as normal vs. cancer based on deviation from a normal expression profile built from normal training samples. Anti-profiles are built using the following general algorithm:

1. Find candidate differentially variable genes (anti-profile genes): rank by ratio of cancer to normal variance
2. Define region of normal expression for each anti-profile gene: normal median ± 5 * normal MAD
3. For each sample to classify:
 - (a) count number of antiProfile genes outside normal expression region (anti-profile score)
 - (b) if score is above threshold, then classify as cancer

We will use data from one of the experiments to train the anti-profile (steps 1 and 2 above) and test it on the data from the other experiment (step 3).

Computing variance ratios

The first step in building an antiprofile is to calculate the ratio of normal variance to cancer variance. This is done with the `apStats` function.


```
> trainSamples=pData(apColonData)$ExperimentID=="GSE4183"  
> colonStats=apStats(exprs(apColonData)[,trainSamples],  
+                      pData(apColonData)$Status[trainSamples],minL=5)  
> head(getProbeStats(colonStats))
```

	affyid	SD0	SD1	stat	meds0	mads0
4895	214974_x_at	0.23369554	7.777167	5.056543	-1.5182409	0.20537749
10	210118_s_at	0.12684950	3.991524	4.975750	-0.7449072	0.08599552
1318	205719_s_at	0.09529811	2.817550	4.885850	-0.8532822	0.08670758
2707	205863_at	0.12430282	3.431335	4.786839	-0.5508941	0.15574925
4896	215101_s_at	0.24540888	6.578072	4.744406	-0.9257671	0.15043660
2272	227140_at	0.24976921	5.718607	4.516996	-1.8026488	0.13726594

We can see how that ratio is distributed for these probesets:

```
> hist(getProbeStats(colonStats)$stat, nc=100,  
+      main="Histogram of log variance ratio", xlab="log2 variance ratio")
```

Histogram of log variance ratio



Building the anti-profile

Now we construct the anti-profile by selecting the 100 probesets most hyper-variable probesets

```
> ap=buildAntiProfile(colonStats, tissueSpec=FALSE, sigsize=100)  
> show(ap)
```

```
AntiProfile object with 100 probes
Normal medians
  Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
-1.8026 -0.8542 -0.5102  0.6835 -0.1187 23.6885
Using cutoff 5
```

Computing the anti-profile score

Given the estimated anti-profile, we can get anti-profile scores for a set of testing samples.

```
> counts=apCount(ap, exprs(apColonData)[,!trainSamples])
> palette(brewer.pal(8,"Dark2"))
> # plot in score order
> o=order(counts)
> dotchart(counts[o],col=pData(apColonData)$Status[!trainSamples][o]+1,
+          labels="",pch=19,xlab="anti-profile score",
+          ylab="samples",cex=1.3)
> legend("bottomright", legend=c("Cancer","Normal"),pch=19,col=2:1)
```


SessionInfo

- R version 4.0.0 (2020-04-24), x86_64-pc-linux-gnu
- Locale: LC_CTYPE=en_US.UTF-8, LC_NUMERIC=C, LC_TIME=en_US.UTF-8, LC_COLLATE=C, LC_MONETARY=en_US.UTF-8, LC_MESSAGES=en_US.UTF-8, LC_PAPER=en_US.UTF-8, LC_NAME=C, LC_ADDRESS=C, LC_TELEPHONE=C, LC_MEASUREMENT=en_US.UTF-8, LC_IDENTIFICATION=C
- Running under: Ubuntu 18.04.4 LTS
- Matrix products: default
- BLAS: /home/biocbuild/bbs-3.11-bioc/R/lib/libRblas.so
- LAPACK: /home/biocbuild/bbs-3.11-bioc/R/lib/libRlapack.so
- Base packages: base, datasets, grDevices, graphics, methods, parallel, stats, utils
- Other packages: Biobase 2.48.0, BiocGenerics 0.34.0, RColorBrewer 1.1-2, antiProfiles 1.28.0, antiProfilesData 1.23.0, locfit 1.5-9.4, matrixStats 0.56.0
- Loaded via a namespace (and not attached): compiler 4.0.0, grid 4.0.0, lattice 0.20-41, tools 4.0.0