

Package ‘cellbaseR’

October 18, 2022

Type Package

Date 2016-04-17

Title Querying annotation data from the high performance Cellbase web

Version 1.20.1

Author Mohammed OE Abdallah

Maintainer Mohammed OE Abdallah <melsiddieg@gmail.com>

URL <https://github.com/melsiddieg/cellbaseR>

Description This R package makes use of the exhaustive RESTful Web service API that has been implemented for the Cellbase database. It enable researchers to query and obtain a wealth of biological information from a single database saving a lot of time. Another benefit is that researchers can easily make queries about different biological topics and link all this information together as all information is integrated.

License Apache License (== 2.0)

Depends R(>= 3.4)

Imports methods, jsonlite, httr, data.table, pbapply, tidyr, R.utils, Rsamtools, BiocParallel, foreach, utils, parallel, doParallel

Suggests BiocStyle, knitr, rmarkdown, Gviz, VariantAnnotation

RoxygenNote 7.2.0

biocViews Annotation, VariantAnnotation

Lazy TRUE

LazyData TRUE

Collate 'commons.R' 'AllClasses.R' 'AllGenerics.R'
'AnnotateVcf-methods.R' 'CellBaseParam-methods.R'
'CellBaseR-methods.R' 'cellbase.R' 'getCellbase-methods.R'
'getChromosomeInfo-methods.R' 'getClinical-methods.R'
'getGene-methods.R' 'getMeta-methods.R' 'getProtein-methods.R'
'getRegion-methods.R' 'getSnp-methods.R' 'getTf-methods.R'
'getTranscript-methods.R' 'getVariant-methods.R'
'getXref-methods.R' 'show-methods.R' 'tools.R' 'user.R'

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/cellbaseR>

git_branch RELEASE_3_15

git_last_commit 2f86a12

git_last_commit_date 2022-06-21

Date/Publication 2022-10-18

R topics documented:

cellbaseR-package	3
AnnotateVcf,CellBaseR-method	3
CellBaseParam	4
CellBaseParam-class	6
CellBaseR	7
CellBaseR-class	8
createGeneModel	8
getCaddScores	9
getCellBase,CellBaseR-method	10
getCellBaseResourceHelp	11
getChromosomeInfo,CellBaseR-method	11
getClinical,CellBaseR-method	12
getClinicalByGene	13
getClinicalByRegion	13
getConservationByRegion	14
getGene,CellBaseR-method	15
getGeneInfo	16
getMeta,CellBaseR-method	16
getProtein,CellBaseR-method	17
getProteinInfo	18
getRegion,CellBaseR-method	18
getRegulatoryByRegion	19
getSnp,CellBaseR-method	20
getSnpByGene	21
getTf,CellBaseR-method	21
getTfbsByRegion	22
getTranscript,CellBaseR-method	23
getTranscriptByGene	24
getVariant,CellBaseR-method	24
getVariantAnnotation	25
getXref,CellBaseR-method	26
Index	27

cellbaseR-package *cellbaseR*

Description

Querying annotation data from the high performance Cellbase web services

Details

Documentation for the cellbaseR package

This R package makes use of the exhaustive RESTful Web service API that has been implemented for the Cellbase database. It enables researchers to query and obtain a wealth of biological information from a single database saving a lot of time. Another benefit is that researchers can easily make queries about different biological topics and link all this information together as all information is integrated. Currently *Homo sapiens*, *Mus musculus* and other 20 species are available and many others will be included soon. Results returned from the cellbase queries are parsed into R data.frames and other common R data structures so users can readily get into downstream analysis.

Author(s)

Mohammed OE Abdallah

See Also

Useful links:

- <https://github.com/melsiddieg/cellbaseR>

AnnotateVcf, CellBaseR-method
AnnotateVcf

Description

This method is a convenience method to annotate bgzipped tabix-indexed vcf files. It should be ideal for annotating small to medium sized vcf files.

Usage

```
## S4 method for signature 'CellBaseR'  
AnnotateVcf(object, file, batch_size, num_threads, BPPARAM = bpparam())
```

Arguments

object	an object of class CellBaseR
file	Path to a bgzipped and tabix indexed vcf file
batch_size	integer if multiple queries are raised by a single method call, e.g. getting annotation info for several genes, queries will be sent to the server in batches. This slot indicates the size of each batch, e.g. 200
num_threads	number of asynchronous batches to be sent to the server
BPPARAM	a BiocParallel class object

Value

a dataframe with the results of the query

See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

Examples

```
cb <- CellBaseR()
fl <- system.file("extdata", "hapmap_exome_chr22_200.vcf.gz",
                 package = "cellbaseR" )
res <- AnnotateVcf(object=cb, file=fl, BPPARAM = bpparam(workers=2),batch_size=100)
```

CellBaseParam

A Constructor for the CellBaseParam Object

Description

CellBaseParam object is used to control what results are returned from the CellBaseR methods

Usage

```
CellBaseParam(
  assembly = character(),
  feature = character(),
  region = character(),
  rsid = character(),
  accession = character(),
  type = character(),
  mode_inheritance_labels = character(),
  clinsig_labels = character(),
  alleleOrigin = character(),
  consistency_labels = character(),
  so = character(),
```

```

    source = character(),
    trait = character(),
    include = character(),
    exclude = character(),
    limit = character()
)

```

Arguments

assembly	A character the assembly build to query, e.g.GRCh37(default)
feature	A character vector denoting the feature/s to be queried
region	A character vector denoting the region/s to be queried must be in the form 1:100000-1500000
rsid	A character vector denoting the rs ids to be queried
accession	A caharcter vector of Cinvar accessions
type	A caharcter vector of Variant types
mode_inheritance_labels	A character vector
clinsig_labels	A character vector
alleleOrigin	A character vector
consistency_labels	A character vector
so	A character vector denoting sequence ontology to be queried
source	A character vector
trait	A character vector denoting the trait to be queried
include	A character vector denoting the fields to be returned
exclude	A character vector denoting the fields to be excluded
limit	A number limiting the number of results to be returned

Value

an object of class CellBaseParam

See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

Examples

```

cbParam <- CellBaseParam(assembly="GRCh38",feature=c("TP73","TET1"))
print(cbParam)

```

CellBaseParam-class *CellBaseParam Class*

Description

This class defines a CellBaseParam object to hold filtering parameters.

Details

This class stores parameters used for filtering the CellBaseR query and is available for all query methods. CellBaseParam object is used to control what results are returned from the 'CellBaseR' methods

Slots

assembly A character the assembly build to query, e.g.GRCh37(default)

feature A character vector denoting the feature/s to be queried

region A character vector denoting the region/s to be queried must be in the form 1:100000-1500000

rsid A character vector denoting the rs ids to be queried

accession A character vector of CInvar accessions

type A character vector of Variant types

mode_inheritance_labels A character vector

clinsig_labels A character vector

alleleOrigin A character vector

consistency_labels A character vector

so A character vector denoting sequence ontology to be queried

source A character vector

trait A character vector denoting the trait to be queried

include A character vector denoting the fields to be returned

exclude A character vector denoting the fields to be excluded

limit A number limiting the number of results to be returned

See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

 CellBaseR

CellBaseR

Description

This is a constructor function for the CellBaseR object

Usage

```
CellBaseR(
  host = "https://ws.opencb.org/cellbase-4.8.2/webservices/rest/",
  version = "v4",
  species = "hsapiens",
  batch_size = 200L,
  num_threads = 8L
)
```

Arguments

host	A character the default host url for cellbase webservices, e.g. "http://bioinfo.hpc.cam.ac.uk/cellbase/webservices"
version	A character the cellbae API version, e.g. "V4"
species	a character specifying the species to be queried, e.g. "hsapiens"
batch_size	intger if multiple queries are raised by a single method call, e.g. getting annotation info for several genes, queries will be sent to the server in batches. This slot indicates the size of each batch, e.g. 200
num_threads	integer number of batches to be sent to the server

Details

CellbaseR constructor function

This class defines the CellBaseR object. It holds the default configuration required by CellBaseR methods to connect to the cellbase web services. By default it is configured to query human data based on the GRCh37 genome assembly.

Value

An object of class CellBaseR

See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

Examples

```
cb <- CellBaseR()
print(cb)
```

CellBaseR-class	<i>CellBaseR Class</i>
-----------------	------------------------

Description

This is an S4 class which defines the CellBaseR object

Details

This S4 class holds the default configuration required by CellBaseR methods to connect to the cellbase web services. By default it is configured to query human data based on the GRCh37 assembly assembly.

Slots

host a character specifying the host url. Default "http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/rest/"

version a character specifying the API version. Default "v4"

species a character specifying the species to be queried. Default "hsapiens"

batch_size if multiple queries are raised by a single method call, e.g. getting annotation info for several features, queries will be sent to the server in batches. This slot indicates the size of these batches. Default 200

num_threads the number of threads. Default 8

See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

createGeneModel	<i>createGeneModel</i>
-----------------	------------------------

Description

A convenience function to construct a genemodel

Usage

```
createGeneModel(object, region = NULL)
```

Arguments

object an object of class CellbaseResponse

region a character

Details

This function create a gene model data frame, which can be then turned into a `GeneRegionTrack` for visualiaztion by [GeneRegionTrack](#)

Value

A `geneModel`

See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

Examples

```
cb <- CellBaseR()
test <- createGeneModel(object = cb, region = "17:1500000-1550000")
```

<code>getCaddScores</code>	<i>getCaddScores</i>
----------------------------	----------------------

Description

A convienice method to fetch Cadd scores for specific variant/s

Usage

```
getCaddScores(object, id, param = NULL)
```

Arguments

<code>object</code>	an object of class <code>CellBaseR</code>
<code>id</code>	a charcter vector of genomic variants, eg 19:45411941:T:C
<code>param</code>	an object of class <code>CellBaseParam</code>

Value

a dataframe of the query result

Examples

```
cb <- CellBaseR()
res <- getCaddScores(cb, "19:45411941:T:C")
```

getCellBase, CellBaseR-method
getCellBase

Description

The generic method for querying CellBase web services.

Usage

```
## S4 method for signature 'CellBaseR'  
getCellBase(object, category, subcategory, ids, resource, param = NULL)
```

Arguments

object	an object of class CellBaseR
category	character to specify the category to be queried.
subcategory	character to specify the subcategory to be queried
ids	a character vector of the ids to be queried
resource	a character to specify the resource to be queried
param	an object of class CellBaseParam specifying additional param for the CellBaseR

Details

This method allows the user to query the cellbase web services without any predefined categories, subcategories, or resources.

Value

a dataframe holding the results of the query

See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

Examples

```
cb <- CellBaseR()  
res <- getCellBase(object=cb, category="feature", subcategory="gene",  
ids="TET1", resource="info")
```

```
getCellBaseResourceHelp
      getCellBaseResourceHelp
```

Description

A function to get help about available cellbase resources

Usage

```
getCellBaseResourceHelp(object, subcategory)
```

Arguments

object	a cellBase class object
subcategory	a character the subcategory to be queried

Details

This function retrieves available resources for each generic method like getGene, getRegion, get-protein, etc. It help the user see all possible resources to use with the getGeneric methods

Value

character vector of the available resources to that particular subcategory

Examples

```
cb <- CellBaseR()
# Get help about what resources are available to the getGene method
getCellBaseResourceHelp(cb, subcategory="gene")
# Get help about what resources are available to the getRegion method
getCellBaseResourceHelp(cb, subcategory="region")
# Get help about what resources are available to the getXref method
getCellBaseResourceHelp(cb, subcategory="id")
```

```
getChromosomeInfo, CellBaseR-method
      getChromosomeInfo
```

Description

A method to query sequence data from Cellbase web services.

Usage

```
## S4 method for signature 'CellBaseR'
getChromosomeInfo(object, ids, resource, param = NULL)
```

Arguments

object	an object of class CellBaseR
ids	a character vector of chromosome ids to be queried
resource	a character vector to specify the resource to be queried
param	a object of class CellBaseParam specifying additional param for the query

Details

A method to query sequence data from Cellbase web services. This method retrieves information about chromosomes, including its size and detailed information about its different cytobands

Value

a dataframe with the results of the query

See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

Examples

```
cb <- CellBaseR()
res <- getChromosomeInfo(object=cb, ids="22", resource="info")
```

getClinical,CellBaseR-method

getClinical

Description

A method to query Clinical data from Cellbase web services.

Usage

```
## S4 method for signature 'CellBaseR'
getClinical(object, param = NULL)
```

Arguments

object	an object of class CellBaseR
param	a object of class CellBaseParam specifying the parameters limiting the Cell-BaseR

Details

This method retrieves clinically relevant variants annotations from multiple resources including clinvar, cosmic and gwas catalog. Furthermore, the user can filter these data in many ways including trait, features, rs, etc.,

Value

a dataframe with the results of the query

See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

Examples

```
cb <- CellBaseR()
cbParam <- CellBaseParam(feature=c("TP73", "TET1"), limit=100)
res <- getClinical(object=cb,param=cbParam)
```

getClinicalByGene *getClinicalByGene*

Description

A convenience method to fetch clinical variants for specific gene/s

Usage

```
getClinicalByGene()
```

getClinicalByRegion *getClinicalByRegion*

Description

A convenience method to fetch clinical variants for specific region/s

Usage

```
getClinicalByRegion(object, id, param = NULL)
```

Arguments

object	an object of class CellBaseR
id	a character vector of genomic regions, eg 17:1000000-1100000
param	an object of class CellBaseParam

Value

a dataframe of the query result

Examples

```
cb <- CellBaseR()
res <- getClinicalByRegion(cb, "17:1000000-1189811")
```

```
getConservationByRegion
      getConservationByRegion
```

Description

A convenience method to fetch conservation data for specific region/s

Usage

```
getConservationByRegion(object, id, param = NULL)
```

Arguments

object	an object of class CellBaseR
id	a character vector of genomic regions, eg 17:1000000-1100000
param	an object of class CellBaseParam

Value

a dataframe of the query result

Examples

```
cb <- CellBaseR()
res <- getConservationByRegion(cb, "17:1000000-1189811")
```

getGene, CellBaseR-method
getGene

Description

A method to query gene data from Cellbase web services.

Usage

```
## S4 method for signature 'CellBaseR'  
getGene(object, ids, resource, param = NULL)
```

Arguments

object	an object of class CellBaseR
ids	a character vector of gene ids to be queried
resource	a character vector to specify the resource to be queried
param	an object of class CellBaseParam specifying additional param for the CellBaseR

Details

This method retrieves various gene annotations including transcripts and exons data as well as gene expression and clinical data

Value

a dataframe with the results of the query

See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

Examples

```
cb <- CellBaseR()  
res <- getGene(object=cb, ids=c("TP73", "TET1"), resource="info")
```

```
getGeneInfo          getGeneInfo
```

Description

A convenience method to fetch gene annotations specific gene/s

Usage

```
getGeneInfo(object, id, param = NULL)
```

Arguments

object	an object of class CellBaseR
id	a character vector of HUGO symbol (gene names)
param	an object of class CellBaseParam

Value

a dataframe of the query result

Examples

```
cb <- CellBaseR()
res <- getGeneInfo(cb, "TET1")
```

```
getMeta,CellBaseR-method
      getMeta
```

Description

A method for getting the available metadata from the cellbase web services

Usage

```
## S4 method for signature 'CellBaseR'
getMeta(object, resource)
```

Arguments

object	an object of class CellBaseR
resource	the resource you want to query its metadata

Details

This method is for getting information about the available species and available annotation, assembly for each species from the cellbase web services.

Value

a dataframe with the results of the query

See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

Examples

```
cb <- CellBaseR()
res <- getMeta(object=cb, resource="species")
```

getProtein, CellBaseR-method

getProtein

Description

A method to query protein data from Cellbase web services.

Usage

```
## S4 method for signature 'CellBaseR'
getProtein(object, ids, resource, param = NULL)
```

Arguments

object	an object of class CellBaseR
ids	a character vector of uniprot ids to be queried, should be one or more of uniprot ids, for example O15350.
resource	a character vector to specify the resource to be queried
param	a object of class CellBaseParam specifying additional param for the query

Details

This method retrieves various protein annotations including protein description, features, sequence, substitution scores, evidence, etc.

Value

an object of class CellBaseResponse which holds a dataframe with the results of the query

Examples

```
cb <- CellBaseR()
res <- getProtein(object=cb, ids="015350", resource="info")
```

getProteinInfo	<i>getProteinInfo</i>
----------------	-----------------------

Description

A convenience method to fetch annotations for specific protein/s

Usage

```
getProteinInfo(object, id, param = NULL)
```

Arguments

object	an object of class CellBaseR
id	a character vector of Uniprot Ids
param	an object of class CellBaseParam

Value

a dataframe of the query result

Examples

```
cb <- CellBaseR()
res <- getProteinInfo(cb, "015350")
```

getRegion,CellBaseR-method	<i>getRegion</i>
----------------------------	------------------

Description

A method to query features within a genomic region from Cellbase web services.

Usage

```
## S4 method for signature 'CellBaseR'
getRegion(object, ids, resource, param = NULL)
```

Arguments

object	an object of class CellBaseR
ids	a character vector of the regions to be queried, for example, "1:1000000-1200000" should always be in the form 'chr:start-end'
resource	a character vector to specify the resource to be queried
param	a object of class CellBaseParam specifying additional param for the query

Details

This method retrieves various genomic features from a given region including genes, snps, clinically relevant variants, proteins, etc.

Value

a dataframe with the results of the query

See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

Examples

```
cb <- CellBaseR()
res <- getRegion(object=cb, ids="17:1000000-1200000", resource="gene")
```

getRegulatoryByRegion *getRegulatoryByRegion*

Description

A convenience method to fetch regulatory data for specific region/s

Usage

```
getRegulatoryByRegion(object, id, param = NULL)
```

Arguments

object	an object of class CellBaseR
id	a character vector of genomic regions, eg 17:1000000-1100000
param	an object of class CellBaseParam

Value

a dataframe of the query result

Examples

```
cb <- CellBaseR()
res <- getRegulatoryByRegion(cb, "17:1000000-1189811")
```

getSnp,CellBaseR-method

getSnp

Description

A method to query genomic variation data from Cellbase web services.

Usage

```
## S4 method for signature 'CellBaseR'
getSnp(object, ids, resource, param = NULL)
```

Arguments

object	an object of class CellBaseR
ids	a character vector of the ids to be queried, must be a valid rsid, for example 'rs6025'
resource	a character vector to specify the resource to be queried
param	a object of class CellBaseParam specifying additional param for the query

Details

.

This method retrieves known genomic variants (snps) and their annotations including population frequencies from 1k genomes and Exac projects as well as clinical data and various other annotations

Value

a dataframe with the results of the query

See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

Examples

```
cb <- CellBaseR()
res <- getSnp(object=cb, ids="rs6025", resource="info")
```

getSnpByGene	<i>getSnpByGene</i>
--------------	---------------------

Description

A convenience method to fetch known variants (snps) for specific gene/s

Usage

```
getSnpByGene(object, id, param = NULL)
```

Arguments

object	an object of class CellBaseR
id	a character vector of HUGO symbol (gene names)
param	an object of class CellBaseParam

Value

a dataframe of the query result

Examples

```
cb <- CellBaseR()
param <- CellBaseParam(limit = 10)
res <- getSnpByGene(cb, "TET1", param = param)
```

getTf,CellBaseR-method	<i>getTf</i>
------------------------	--------------

Description

A method to query transcription factors binding sites data from Cellbase web services.

Usage

```
## S4 method for signature 'CellBaseR'
getTf(object, ids, resource, param = NULL)
```

Arguments

object	an object of class CellBaseR
ids	a character vector of the ids to be queried, must be a valid transcription factor name, for example, eg, CTCF
resource	a character vector to specify the resource to be queried
param	a object of class CellBaseParam specifying additional param for the query

Details

This method retrieves various transcription factors binding sites data

Value

a dataframe with the results of the query

See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

Examples

```
cb <- CellBaseR()
param <- CellBaseParam(limit = 12)
res <- getTf(object=cb, ids="CTCF", resource="tfbs", param=param)
```

<code>getTfbsByRegion</code>	<i>getTfbsByRegion</i>
------------------------------	------------------------

Description

A convenience method to fetch Transcription factors data for specific region/s

Usage

```
getTfbsByRegion(object, id, param = NULL)
```

Arguments

<code>object</code>	an object of class <code>CellBaseR</code>
<code>id</code>	a character vector of genomic regions, eg <code>17:1000000-1100000</code>
<code>param</code>	an object of class <code>CellBaseParam</code>

Value

a dataframe of the query result

Examples

```
cb <- CellBaseR()
res <- getTfbsByRegion(cb, "17:1000000-1189811")
```

getTranscript, CellBaseR-method
getTranscript

Description

A method to query transcript data from Cellbase web services.

Usage

```
## S4 method for signature 'CellBaseR'  
getTranscript(object, ids, resource, param = NULL)
```

Arguments

object	an object of class CellBaseR
ids	a character vector of the transcript ids to be queried, use ensemble transcript IDs eq, ENST00000380152
resource	a character vector to specify the resource to be queried
param	an object of class CellBaseParam specifying additional params for the query

Details

This method retrieves various genomic annotations for transcripts including exons, cDNA sequence, annotations flags, and cross references, etc.

Value

a dataframe with the results of the query

See Also

<https://github.com/openCB/cellbase/wiki> and the RESTful API documentation <http://bioinformatics.cam.ac.uk/cellbase/webservices/>

Examples

```
cb <- CellBaseR()  
res <- getTranscript(object=cb, ids="ENST00000373644", resource="info")
```

```
getTranscriptByGene    getTranscriptByGene
```

Description

A convenience method to fetch transcripts for specific gene/s

Usage

```
getTranscriptByGene(object, id, param = NULL)
```

Arguments

object	an object of class CellBaseR
id	a character vector of HUGO symbol (gene names)
param	an object of class CellBaseParam

Value

a dataframe of the query result

Examples

```
cb <- CellBaseR()
res <- getTranscriptByGene(cb, "TET1")
```

```
getVariant,CellBaseR-method
                          getVariant
```

Description

A method to query variant annotation data from Cellbase web services from Cellbase web services.

Usage

```
## S4 method for signature 'CellBaseR'
getVariant(object, ids, resource, param = NULL)
```

Arguments

object	an object of class CellBaseR
ids	a character vector of the ids to be queried, must be in the following format 'chr:start:ref:alt', for example, '1:128546:A:T'
resource	a character vector to specify the resource to be queried
param	a object of class CellBaseParam specifying additional param for the query

Details

This method retrieves extensive genomic annotations for variants including consequence types, conservation data, population frequencies from 1k genomes and Exac projects, etc. as well as clinical data and various other annotations

Value

a dataframe with the results of the query

See Also

<https://github.com/openCB/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

Examples

```
cb <- CellBaseR()
res <- getVariant(object=cb, ids="19:45411941:T:C", resource="annotation")
```

getVariantAnnotation *getVariantAnnotation*

Description

A convenience method to fetch variant annotation for specific variant/s

Usage

```
getVariantAnnotation(object, id, param = NULL)
```

Arguments

object	an object of class CellBaseR
id	a character vector of length < 200 of genomic variants, eg 19:45411941:T:C
param	an object of class CellBaseParam

Value

a dataframe of the query result

Examples

```
cb <- CellBaseR()
res <- getVariantAnnotation(cb, "19:45411941:T:C")
```

getXref,CellBaseR-method
getXref

Description

A method to query cross reference data from Cellbase web services.

Usage

```
## S4 method for signature 'CellBaseR'  
getXref(object, ids, resource, param = NULL)
```

Arguments

object	an object of class CellBaseR
ids	a character vector of the ids to be queried, any crossreferenceable ID, gene names, transcript ids, uniprot ids,etc.
resource	a character vector to specify the resource to be queried
param	a object of class CellBaseParam specifying additional param for the query

Details

This method retrieves cross references for genomic identifiers, eg ENSEMBL ids, it also provide starts_with service that is useful for autocomplete services.

Value

a dataframe with the results of the query

See Also

<https://github.com/openCB/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

Examples

```
cb <- CellBaseR()  
res <- getXref(object=cb, ids="ENST00000373644", resource="xref")
```

Index

AnnotateVcf
 (AnnotateVcf, CellBaseR-method),
 3
AnnotateVcf, CellBaseR-method, 3

CellBaseParam, 4
CellBaseParam-class, 6
CellBaseR, 7
cellbaseR (cellbaseR-package), 3
CellBaseR-class, 8
cellbaseR-package, 3
createGeneModel, 8

GeneRegionTrack, 9
getCaddScores, 9
getCellBase
 (getCellBase, CellBaseR-method),
 10
getCellBase, CellBaseR-method, 10
getCellBaseResourceHelp, 11
getChromosomeInfo
 (getChromosomeInfo, CellBaseR-method),
 11
getChromosomeInfo, CellBaseR-method, 11
getClinical
 (getClinical, CellBaseR-method),
 12
getClinical, CellBaseR-method, 12
getClinicalByGene, 13
getClinicalByRegion, 13
getConservationByRegion, 14
getGene (getGene, CellBaseR-method), 15
getGene, CellBaseR-method, 15
getGeneInfo, 16
getMeta (getMeta, CellBaseR-method), 16
getMeta, CellBaseR-method, 16
getProtein
 (getProtein, CellBaseR-method),
 17
getProtein, CellBaseR-method, 17
getProteinInfo, 18
getRegion (getRegion, CellBaseR-method),
 18
getRegion, CellBaseR-method, 18
getRegulatoryByRegion, 19
getSnp (getSnp, CellBaseR-method), 20
getSnp, CellBaseR-method, 20
getSnpByGene, 21
getTf (getTf, CellBaseR-method), 21
getTf, CellBaseR-method, 21
getTfbsByRegion, 22
getTranscript
 (getTranscript, CellBaseR-method),
 23
getTranscript, CellBaseR-method, 23
getTranscriptByGene, 24
getVariant
 (getVariant, CellBaseR-method),
 24
getVariant, CellBaseR-method, 24
getVariantAnnotation, 25
getXref (getXref, CellBaseR-method), 26
getXref, CellBaseR-method, 26