

Package ‘fennr’

April 8, 2024

Title Fast functional enrichment for interactive applications

Version 1.0.5

Description Perform fast functional enrichment on feature lists (like genes or proteins) using the hypergeometric distribution. Tailored for speed, this package is ideal for interactive platforms such as Shiny. It supports the retrieval of functional data from sources like GO, KEGG, Reactome, Bioplanet and WikiPathways. By downloading and preparing data first, it allows for rapid successive tests on various feature selections without the need for repetitive, time-consuming preparatory steps typical of other packages.

URL <https://github.com/bartongroup/fennr>

BugReports <https://github.com/bartongroup/fennr/issues>

Depends R (>= 4.3.0)

License MIT + file LICENSE

Encoding UTF-8

biocViews FunctionalPrediction, DifferentialExpression, GeneSetEnrichment, GO, KEGG, Reactome, Proteomics

Imports tools, methods, assertthat, rlang, dplyr, tidyr, tidyselect, tibble, purrr, readr, stringr, httr2, rvest, progress, biomaRt, BiocFileCache, shiny, ggplot2

Suggests BiocStyle, testthat, knitr, rmarkdown, topGO

RoxygenNote 7.2.3

VignetteBuilder knitr

LazyData false

git_url <https://git.bioconductor.org/packages/fennr>

git_branch RELEASE_3_18

git_last_commit f29fc4c

git_last_commit_date 2024-01-25

Repository Bioconductor 3.18

Date/Publication 2024-04-08

Author Marek Gierlinski [aut, cre] (<<https://orcid.org/0000-0001-9149-3514>>)

Maintainer Marek Gierlinski <M.Gierlinski@dundee.ac.uk>

R topics documented:

fennr-package	2
enrichment_interactive	3
exmpl_all	4
exmpl_sel	4
fetch_bp	5
fetch_go	5
fetch_go_species	6
fetch_kegg	7
fetch_kegg_species	8
fetch_reactome	9
fetch_reactome_species	10
fetch_terms_for_example	10
fetch_wiki	11
fetch_wiki_species	12
functional_enrichment	12
get_feature_terms	14
get_term_features	14
prepare_for_enrichment	15
yeast_de	16
Index	17

fennr-package

fennr: Fast functional enrichment for interactive applications

Description

This R package provides a fast and efficient method for functional enrichment analysis, optimized for speed and designed for use in interactive applications, such as **Shiny** apps.

To learn more about fennr, start with the vignette: `vignette("fennr")`.

Value

Package fennr.

Author(s)

Maintainer: Marek Gierlinski <M.Gierlinski@dundee.ac.uk> ([ORCID](https://orcid.org/0000-0001-9149-3514))

See Also

Useful links:

- <https://github.com/bartongroup/fenr>
- Report bugs at <https://github.com/bartongroup/fenr/issues>

enrichment_interactive

Small Shiny app serving as example for fast enrichment

Description

Small Shiny app serving as example for fast enrichment

Usage

```
enrichment_interactive(de, term_data)
```

Arguments

de	Differential expression results, yeast_de attached to this package can be used.
term_data	A list of fenr_terms objects containing functional data for various ontologies. fetch_terms_for_example can be used to create this object.

Value

An interactive Shiny app

Examples

```
data(yeast_de)
term_data <- fetch_terms_for_example(yeast_de)
if(interactive()) {
  enrichment_interactive(yeast_de, term_data)
}
```

exmpl_all	<i>Example set of background genes.</i>
-----------	---

Description

A set of gene names for proteins that could be detected in a typical proteomics experiment on yeast samples.

Usage

```
data(exmpl_all)
```

Format

A character vector with 6985 elements.

Value

A vector with background gene names.

exmpl_sel	<i>Example set of selected genes.</i>
-----------	---------------------------------------

Description

A set of gene names manually selected to illustrate functional enrichment.

Usage

```
data(exmpl_sel)
```

Format

A character vector with 21 elements.

Value

A vector with selected gene names.

fetch_bp	<i>Get functional term data from BioPlanet</i>
----------	--

Description

Download term information (term ID and name) and gene-pathway mapping (NCBI gene ID, gene symbol and pathway ID) from BioPlanet.

Usage

```
fetch_bp(use_cache = TRUE, on_error = c("stop", "warn"))
```

Arguments

use_cache	Logical, if TRUE, the remote file will be cached locally.
on_error	A character vector specifying the error handling method. It can take values "stop" or "warn". The default is "stop". "stop" will halt the function execution and throw an error, while "warn" will issue a warning and return 'NULL'.

Value

A list with terms and mapping tibbles.

Examples

```
bioplanet_data <- fetch_bp(on_error = "warn")
```

fetch_go	<i>Get Gene Ontology (GO) data</i>
----------	------------------------------------

Description

This function downloads term information (GO term ID and name) and gene-term mapping (gene ID, symbol, and GO term ID) from either the Ensembl database (using BioMart) or the Gene Ontology database (using GAF files), depending on the provided argument.

Usage

```
fetch_go(  
  species = NULL,  
  mart = NULL,  
  use_cache = TRUE,  
  on_error = c("stop", "warn")  
)
```

Arguments

species	(Optional) Species designation. Examples are goa_human for human, mgi for mouse, or sgd for yeast. Full list of available species can be obtained using <code>fetch_go_species - column designation</code> . This argument is used when fetching data from the Gene Ontology database.
mart	(Optional) Object class Mart representing connection to BioMart database, created with, e.g., <code>useEnsembl</code> . This argument is used when fetching data from the Ensembl database.
use_cache	Logical, if TRUE, the remote data will be cached locally.
on_error	A character vector specifying the error handling method. It can take values "stop" or "warn". The default is "stop". "stop" will halt the function execution and throw an error, while "warn" will issue a warning and return 'NULL'.

Details

If `species` is provided, mapping from a Gene Ontology GAF file will be downloaded. GAF files contain more generic information than gene symbols. In this function, the third column of the GAF file (DB Object Symbol) is returned as `gene_symbol`, but, depending on the `species` argument it can contain other entities, e.g. RNA or protein complex names. Similarly, the eleventh column of the GAF file (DB Object Synonym) is returned as `gene_synonym`. It is up to the user to select the appropriate database.

Alternatively, if `mart` is provided, mapping will be downloaded from Ensembl database. It will gene symbol and Ensembl gene ID.

Value

A list with terms and mapping tibbles.

Examples

```
# Fetch GO data from Ensembl
## Not run:
mart <- biomaRt::useEnsembl(biomart = "ensembl", dataset = "scerevisiae_gene_ensembl")
go_data_ensembl <- fetch_go(mart = mart, on_error = "warn")

## End(Not run)
# Fetch GO data from Gene Ontology
go_data_go <- fetch_go(species = "sgd", on_error = "warn")
```

Description

This function attempts to scrape HTML web page containing a table of available species and corresponding file names. If the structure of the page changes one day and the function stops working, go to <http://current.geneontology.org/products/pages/downloads.html> and check file names. The species designation used in this package is the GAF file name without extension (e.g. for a file 'goa_chicken.gaf' the designation is 'goa_chicken').

Usage

```
fetch_go_species(on_error = c("stop", "warn"))
```

Arguments

on_error A character vector specifying the error handling method. It can take values "stop" or "warn". The default is "stop". "stop" will halt the function execution and throw an error, while "warn" will issue a warning and return 'NULL'.

Value

A tibble with columns species and designation.

Examples

```
go_species <- fetch_go_species(on_error = "warn")
```

fetch_kegg

Get functional term data from KEGG

Description

Download information (pathway ID and name) and gene-pathway mapping (entrez gene ID, gene symbol and pathway ID) from KEGG. Gene symbols are extracted from gene descriptions. For some species (e.g. yeast), gene symbols are returned instead of entrez IDs and not in gene description.

Usage

```
fetch_kegg(species, batch_size = 10, on_error = c("stop", "warn"))
```

Arguments

species KEGG species code, for example "hsa" for human. The full list of available KEGG species can be found by using `fetch_kegg_species`.

batch_size Number of pathways sent to KEGG database in one query. The maximum allowed is 10.

`on_error` A character vector specifying the error handling method. It can take values "stop" or "warn". The default is "stop". "stop" will halt the function execution and throw an error, while "warn" will issue a warning and return 'NULL'.

Value

A list with terms and mapping tibbles.

Examples

```
kegg_data <- fetch_kegg("mge", on_error = "warn")
```

`fetch_kegg_species` *Find all species available from KEGG*

Description

Find all species available from KEGG

Usage

```
fetch_kegg_species(on_error = c("stop", "warn"))
```

Arguments

`on_error` A character vector specifying the error handling method. It can take values "stop" or "warn". The default is "stop". "stop" will halt the function execution and throw an error, while "warn" will issue a warning and return 'NULL'.

Value

A tibble, in which column `designation` contains species designations used in function `fetch_kegg`.

Examples

```
spe <- fetch_kegg_species(on_error = "warn")
```

fetch_reactome	<i>Get functional term data from Reactome</i>
----------------	---

Description

Download term information (pathway ID and name) and gene-pathway mapping (Ensembl gene ID or gene symbol and pathway ID) from Reactome.

Usage

```
fetch_reactome(  
  species,  
  source = c("ensembl", "api", "gene_association"),  
  use_cache = TRUE,  
  on_error = c("stop", "warn")  
)
```

Arguments

species	Reactome species designation, for example "Homo sapiens" for human. Full list of available species can be found using <code>fetch_reactome_species()</code> .
source	How to download the mapping. If 'ensembl' or 'gene_association', one mapping file provided by Reactome will be downloaded, if 'api', then Reactome API will be used. See details.
use_cache	Logical, if TRUE, the remote file will be cached locally.
on_error	A character vector specifying the error handling method. It can take values "stop" or "warn". The default is "stop". "stop" will halt the function execution and throw an error, while "warn" will issue a warning and return 'NULL'.

Details

Reactome makes mapping between Ensembl ID and pathway ID available in form of one downloadable file. Also, a gene association file with mapping between UniProt accession number, gene symbol and Reactome term is available. If `source = "ensembl"` or `source = "gene_association"` is set, one large file will be downloaded and parsed. If `source = "api"` is set, then Reactome APIs will be interrogated for each pathway available. This method is considerably slower, especially for large genomes. However, gene association file contains far fewer mappings than can be extracted using API.

Value

A list with terms and mapping tibbles

Examples

```
reactome_data <- fetch_reactome("Saccharomyces cerevisiae", on_error = "warn")
```

`fetch_reactome_species`*List of available Reactome species*

Description

List of available Reactome species

Usage

```
fetch_reactome_species(on_error = c("stop", "warn"))
```

Arguments

`on_error` A character vector specifying the error handling method. It can take values "stop" or "warn". The default is "stop". "stop" will halt the function execution and throw an error, while "warn" will issue a warning and return 'NULL'.

Value

A tibble with species names used by Reactome.

Examples

```
re <- fetch_reactome_species(on_error = "warn")
```

`fetch_terms_for_example`*Create term data for interactive example*

Description

Create term data for interactive example

Usage

```
fetch_terms_for_example(de)
```

Arguments

`de` Differential expression results, use yeast_de data attached to this package.

Value

A list of objects containing functional terms for GO and Reactome.

Examples

```
data(yeast_de)
term_data <- fetch_terms_for_example(yeast_de)
```

fetch_wiki

*Get functional term data from WikiPathways***Description**

Download term information (pathway ID and name) and gene-pathway mapping (gene symbol and pathway ID) from WikiPathways.

Usage

```
fetch_wiki(
  species,
  databases = c("Ensembl", "Entrez Gene", "HGNC", "HGNC Accession number",
    "Uniprot-TrEMBL"),
  types = c("GeneProduct", "Protein", "Rna", "RNA"),
  on_error = c("stop", "warn")
)
```

Arguments

species	WikiPathways species designation, for example "Homo sapiens" for human. Full list of available species can be found using <code>fetch_wiki_species()</code> .
databases	A character vector with database names to pre-filter mapping data. See details. Full result will be returned if NULL.
types	A character vector with types of entities to pre-filter mapping data. See details. Full result will be returned if NULL.
on_error	A character vector specifying the error handling method. It can take values "stop" or "warn". The default is "stop". "stop" will halt the function execution and throw an error, while "warn" will issue a warning and return 'NULL'.

Details

WikiPathways contain mapping between pathways and a variety of entities from various databases. Typically a gene symbol is returned in column `text_label` and some sort of ID in column `id`, but this depends on the species and databases used. For gene/protein enrichment, these should be filtered to contain gene symbols only. This can be done by selecting a desired databases and types. The default values for parameters `databases` and `types` attempt to select information from generic databases, but there are organism-specific databases not included in the selection. We suggest to run this function with `databases = NULL`, `types = NULL` to see what types and databases are available before making selection.

Value

A list with terms and mapping tibbles.

Examples

```
wiki_data <- fetch_wiki("Bacillus subtilis", on_error = "warn")
```

```
fetch_wiki_species    List of available WikiPathways species
```

Description

List of available WikiPathways species

Usage

```
fetch_wiki_species(on_error = c("stop", "warn"))
```

Arguments

`on_error` A character vector specifying the error handling method. It can take values "stop" or "warn". The default is "stop". "stop" will halt the function execution and throw an error, while "warn" will issue a warning and return 'NULL'.

Value

A character vector with species names used by WikiPathways.

Examples

```
spec <- fetch_wiki_species(on_error = "warn")
```

```
functional_enrichment Fast Functional Enrichment
```

Description

Perform fast functional enrichment analysis based on the hypergeometric distribution. Designed for use in interactive applications.

Usage

```
functional_enrichment(feats_all, feats_sel, term_data, feat2name = NULL)
```

Arguments

feat_all	A character vector with all feature identifiers, serving as the background for enrichment.
feat_sel	A character vector with feature identifiers in the selection.
term_data	An object of class <code>fenr_terms</code> , created by <code>prepare_for_enrichment</code> .
feat2name	An optional named list to convert feature IDs into feature names.

Details

This function carries out functional enrichment analysis on a selection of features (e.g., differentially expressed genes) using the hypergeometric probability distribution (Fisher's exact test). Features can be genes, proteins, etc. The `term_data` object contains functional term information and feature-term mapping.

Value

A tibble with enrichment results, providing the following information for each term:

- `N_with` - number of features with this term among all features
- `n_with_sel` - number of features with this term in the selection
- `n_expect` - expected number of features with this term in the selection, under the null hypothesis that terms are mapped to features randomly
- `enrichment` - ratio of `n_with_sel` / `n_expect`
- `odds_ratio` - odds ratio for enrichment; is infinite when all features with the given term are in the selection
- `p_value` - p-value from a single hypergeometric test
- `p_adjust` - p-value adjusted for multiple tests using the Benjamini-Hochberg approach

Examples

```
data(exmpl_all, exempl_sel)
go <- fetch_go(species = "sgd")
go_terms <- prepare_for_enrichment(go$terms, go$mapping, exempl_all, feature_name = "gene_symbol")
enr <- functional_enrichment(exmpl_all, exempl_sel, go_terms)
```

get_feature_terms *Get terms annotating a given feature.*

Description

Get terms annotating a given feature.

Usage

```
get_feature_terms(term_data, feature_id)
```

Arguments

term_data An object class fenr_terms, created by prepare_for_enrichment.
feature_id A string with a feature ID

Value

A character vector containing functional term IDs annotating given feature.

Examples

```
go_data <- fetch_go(species = "sgd")  
go_terms <- prepare_for_enrichment(go_data$terms, go_data$mapping, feature = "gene_symbol")  
trms <- get_feature_terms(go_terms, "GEM1")
```

get_term_features *Get features annotated with a given term.*

Description

Get features annotated with a given term.

Usage

```
get_term_features(term_data, term_id)
```

Arguments

term_data An object class fenr_terms, created by prepare_for_enrichment.
term_id A string with a functional term ID.

Value

A character vector containing feature IDs annotated with the term ID.

Examples

```
go_data <- fetch_go(species = "sgd")
go_terms <- prepare_for_enrichment(go_data$terms, go_data$mapping, feature = "gene_symbol")
feats <- get_term_features(go_terms, "GO:0000001")
```

prepare_for_enrichment

Prepare Term Data for Enrichment Analysis

Description

Process term data downloaded with the `fetch_*` functions, preparing it for fast enrichment analysis using `functional_enrichment`.

Usage

```
prepare_for_enrichment(
  terms,
  mapping,
  all_features = NULL,
  feature_name = "gene_id"
)
```

Arguments

terms	A tibble with at least two columns: <code>term_id</code> and <code>term_name</code> . This tibble contains information about functional term names and descriptions.
mapping	A tibble with at least two columns, containing the mapping between functional terms and features. One column must be named <code>term_id</code> , while the other column should have a name specified by the <code>feature_name</code> argument. For example, if <code>mapping</code> contains columns <code>term_id</code> , <code>accession_number</code> , and <code>gene_symbol</code> , setting <code>feature_name = "gene_symbol"</code> indicates that gene symbols will be used for enrichment analysis.
all_features	A vector with all feature IDs used as the background for enrichment. If not specified, all features found in <code>mapping</code> will be used, resulting in a larger object size.
feature_name	The name of the column in the <code>mapping</code> tibble to be used as the feature identifier. For example, if <code>mapping</code> contains columns <code>term_id</code> , <code>accession_number</code> , and <code>gene_symbol</code> , setting <code>feature_name = "gene_symbol"</code> indicates that gene symbols will be used for enrichment analysis.

Details

This function takes two tibbles containing functional term information (`terms`) and feature mapping (`mapping`), and converts them into an object required by `functional_enrichment` for efficient analysis. Terms and mapping can be generated with the database access functions included in this package, such as `fetch_reactome` or `fetch_go_from_go`.

Value

An object of class `fenr_terms` required by `functional_enrichment`.

Examples

```
data(exmpl_all)
go <- fetch_go(species = "sgd")
go_terms <- prepare_for_enrichment(go$terms, go$mapping, expl_all,
                                  feature_name = "gene_symbol")
```

yeast_de

Differential expression results for yeast RNA-seq.

Description

A subset of 6 + 6 replicates was selected from data set reported in <https://doi.org/10.1093/bioinformatics/btv425>

Usage

```
data(yeast_de)
```

Format

A tibble with 5 columns

Value

Results for differential expression for yeast RNA-seq.

Index

* datasets

- [exmpl_all](#), 4
- [exmpl_sel](#), 4
- [yeast_de](#), 16

* internal

- [fenr-package](#), 2

[enrichment_interactive](#), 3

[exmpl_all](#), 4

[exmpl_sel](#), 4

[fenr \(fenr-package\)](#), 2

[fenr-package](#), 2

[fetch_bp](#), 5

[fetch_go](#), 5

[fetch_go_species](#), 6

[fetch_kegg](#), 7

[fetch_kegg_species](#), 8

[fetch_reactome](#), 9

[fetch_reactome_species](#), 10

[fetch_terms_for_example](#), 10

[fetch_wiki](#), 11

[fetch_wiki_species](#), 12

[functional_enrichment](#), 12

[get_feature_terms](#), 14

[get_term_features](#), 14

[prepare_for_enrichment](#), 15

[yeast_de](#), 16