

Package ‘OncoScore’

January 10, 2025

Version 1.34.0

Date 2024-09-20

Title A tool to identify potentially oncogenic genes

Depends R (>= 4.1.0),

Imports biomaRt, grDevices, graphics, utils, methods,

Suggests BiocGenerics, BiocStyle, knitr, testthat,

Description OncoScore is a tool to measure the association of genes to cancer based on citation frequencies in biomedical literature. The score is evaluated from PubMed literature by dynamically updatable web queries.

Encoding UTF-8

License file LICENSE

URL <https://github.com/danro9685/OncoScore>

BugReports <https://github.com/danro9685/OncoScore>

biocViews BiomedicalInformatics

RoxygenNote 7.3.2

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/OncoScore>

git_branch RELEASE_3_20

git_last_commit 3994272

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2025-01-09

Author Luca De Sano [cre, aut] (<<https://orcid.org/0000-0002-9618-3774>>),
Carlo Gambacorti Passerini [ctb],
Rocco Piazza [ctb],
Daniele Ramazzotti [aut] (<<https://orcid.org/0000-0002-6087-2666>>),
Roberta Spinelli [ctb]

Maintainer Luca De Sano <luca.desano@gmail.com>

Contents

combine.query.results	2
combine.single.matrix	3
compute.frequencies.scores	3
compute.oncoscore	4
compute.oncoscore.from.region	4
compute.oncoscore.timeseries	5
estimate.oncogenes	6
genes	7
get.genes.from.biomart	7
get.list.from.xml	8
get.pubmed.driver.analysis	8
perform.query	9
perform.query.from.region	9
perform.query.timeseries	10
plot.oncoscore	11
plot.oncoscore.timeseries	12
query	13
query.timepoints	13
timepoints	14
try.scan	14
Index	15

combine.query.results *combine.query.results*

Description

Merge a set of genes in a unique one in order to account for possible aliases

Usage

```
combine.query.results(query, genes, new.name)
```

Arguments

query	The result of perform.query, perform.query.timeseries or perform.query.from.region
genes	A list of genes to be merged
new.name	A string containing the new name to be used for the new genes

Value

The frequencies of the genes in the cancer related documents and in all the documents retrieved on PubMed

Examples

```
data(query)
combine.query.results(query, c('IDH1', 'IDH2'), 'new_gene')
```

`combine.single.matrix` *combine.single.matrix*

Description

Perform merge procedure on a matrix

Usage

```
combine.single.matrix(query, genes, new.name)
```

Arguments

<code>query</code>	The result of <code>perform.query</code> , <code>perform.query.timeseries</code> or <code>perform.query.from.region</code>
<code>genes</code>	A list of genes to be merged
<code>new.name</code>	A string containing the new name to be used for the new genes

Value

a merged matrix

`compute.frequencies.scores`
compute.frequencies.scores

Description

compute the logarithmic scores based on the frequencies of the genes

Usage

```
compute.frequencies.scores(data, filter.threshold = 1, analysis.mode = "Log2")
```

Arguments

<code>data</code>	input data as result of the function <code>perform.query</code>
<code>filter.threshold</code>	threshold to filter for a minimum number of citations for the genes
<code>analysis.mode</code>	logarithmic scores to be computed, i.e., log10, log2, natural log or log5

Value

the computed scores

```
compute.oncoscore      compute.oncoscore
```

Description

compute the OncoScore for a list of genes

Usage

```
compute.oncoscore(  
  data,  
  filter.threshold = 0,  
  analysis.mode = "Log2",  
  cutoff.threshold = 21.09,  
  file = NULL,  
  filter.invalid = TRUE  
)
```

Arguments

```
data          input data as result of the function perform.query  
filter.threshold  threshold to filter for a minimum number of citations for the genes  
analysis.mode  logarithmic scores to be computed, i.e., log10, log2, natural log or log5  
cutoff.threshold  threshold to be used to asses the oncogenes  
file          should I save the results to text files?  
filter.invalid auto-remove genes with invalid count
```

Value

the computed OncoScores and the clusters for the genes

Examples

```
data(query)  
compute.oncoscore(query)
```

```
compute.oncoscore.from.region  
      compute.oncoscore.from.region
```

Description

Perform OncoScore analysis on a given chromosomal region

Usage

```
compute.oncoscore.from.region(  
  chromosome,  
  start = NA,  
  end = NA,  
  gene.num.limit = 100,  
  filter.threshold = NA,  
  analysis.mode = "Log2",  
  cutoff.threshold = 21.09,  
  file = NULL  
)
```

Arguments

chromosome	chromosome to be retrieved
start	initial position to be used
end	final position to be used
gene.num.limit	A limit to the genes to be considered in the analysis; this is done to limit the number of queries to PubMed
filter.threshold	threshold to filter for a minimum number of citations for the genes
analysis.mode	logarithmic scores to be computed, i.e., log10, log2, natural log or log5
cutoff.threshold	threshold to be used to assess the oncogenes
file	should I save the results to text files?

Value

the computed scores

Examples

```
chromosome = 15  
start = 200000  
end = 300000
```

```
compute.oncoscore.timeseries  
compute.oncoscore.timeseries
```

Description

perform the OncoScore time series analysis for a list of genes and data times

Usage

```
compute.oncoscore.timeseries(
  data,
  filter.threshold = 0,
  analysis.mode = "Log2",
  cutoff.threshold = 21.09,
  file = NULL
)
```

Arguments

`data` input data as result of the function `perform.query.timeseries`

`filter.threshold` threshold to filter for a minimum number of citations for the genes

`analysis.mode` logarithmic scores to be computed, i.e., log10, log2, natural log or log5

`cutoff.threshold` threshold to be used to asses the oncogenes

`file` should I save the results to text files?

Value

the performed OncoScores time series analysis

Examples

```
data(query.timepoints)
compute.oncoscore.timeseries(query.timepoints)
```

<code>estimate.oncogenes</code>	<i>estimate.oncogenes</i>
---------------------------------	---------------------------

Description

estimate the oncoscore for the genes

Usage

```
estimate.oncogenes(data, cutoff.threshold = 21.09)
```

Arguments

`data` input data as result of the function `compute.frequencies.scores`

`cutoff.threshold` threshold to be used to asses the oncogenes

Value

the computed scores and oncogenes

genes

A list of genes

Description

This dataset contains a list of genes to be used in the analysis as an example

Usage

```
data(genes)
```

Format

rdata

Value

list of 5 elements

Source

example data

```
get.genes.from.biomart
```

get.genes.from.biomart

Description

Get a gene list from biomart

Usage

```
get.genes.from.biomart(chromosome, start = NA, end = NA)
```

Arguments

chromosome	chromosome to be retrieved
start	initial position to be used
end	final position to be used

Value

A list of genes

Examples

```
chromosome = 15  
start = 200000  
end = 300000
```

`get.list.from.xml` *get.list.from.xml*

Description

process the result of the query

Usage

`get.list.from.xml(webget)`

Arguments

`webget` The result from the query to PubMed

Value

Processed result obtained from the query to PubMed

`get.pubmed.driver.analysis`
get.pubmed.driver.analysis

Description

query PubMed for a list of genes

Usage

`get.pubmed.driver.analysis(keywords, gene)`

Arguments

`keywords` The set of keywords to be used for the query to PubMed

`gene` The name of a gene to be used for the query to PubMed

Value

The frequency for the current gene retrieved with the query on the provided set of keywords

`perform.query` *perform.query*

Description

perform the query to PubMed

Usage

```
perform.query(list.of.genes, gene.num.limit = 100, custom.search = NA)
```

Arguments

- `list.of.genes` The list of genes to be used in the queries to PubMed
- `gene.num.limit` A limit to the genes to be considered in the analysis; this is done to limit the number of queries to PubMed
- `custom.search` A custom set of keywords to be used when querying PubMed

Value

The frequencies of the genes in the cancer related documents and in all the documents retrieved on PubMed

Examples

```
data(genes)
```

`perform.query.from.region`
perform.query.from.region

Description

Perform the query to PubMed on a given chromosomal region

Usage

```
perform.query.from.region(  
  chromosome,  
  start = NA,  
  end = NA,  
  gene.num.limit = 100  
)
```

Arguments

chromosome	chromosome to be retrieved
start	initial position to be used
end	final position to be used
gene.num.limit	A limit to the genes to be considered in the analysis; this is done to limit the number of queries to PubMed

Value

The frequencies of the genes in the cancer related documents and in all the documents retrieved on PubMed

Examples

```
chromosome = 15
start = 200000
end = 300000
```

```
perform.query.timeseries
```

```
perform.query.timeseries
```

Description

perform the query to PubMed for the time series analysis

Usage

```
perform.query.timeseries(
  list.of.genes,
  list.of.datatimes,
  gene.num.limit = 100,
  timepoints.limit = 10,
  custom.search = NA
)
```

Arguments

list.of.genes	The list of genes to be used in the queries to PubMed
list.of.datatimes	The list of time points to be used in the queries to PubMed
gene.num.limit	A limit to the genes to be considered in the analysis; this is done to limit the number of queries to PubMed
timepoints.limit	A limit to the time points to be considered in the analysis; this is done to limit the number of queries to PubMed
custom.search	A custom set of keywords to be used when querying PubMed

Value

The frequencies of the genes in the cancer related documents and in all the documents retrieved on PubMed at the specified time points

Examples

```
data(genes)
data(timepoints)
```

plot.oncoscore	<i>plot.oncoscore</i>
----------------	-----------------------

Description

plot the OncoScore for a list of genes

Usage

```
## S3 method for class 'oncoscore'
plot(
  x,
  gene.number = 5,
  main = "OncoScore",
  xlab = "score",
  ylab = "genes",
  file = NA,
  ...
)
```

Arguments

x	input data as result of the function compute.OncoScore
gene.number	number of genes to print
main	the title
xlab	description of x axis (default score)
ylab	description of y axis (default genes)
file	where to save the plot
...	additional parameter to pass to the barplot function

Value

A plot

Examples

```
data(query)
result = compute.oncoscore(query)
plot.oncoscore(result)
```

```
plot.oncoscore.timeseries
      plot.oncoscore.timeseries
```

Description

plot the OncoScore for a list of genes

Usage

```
## S3 method for class 'oncoscore.timeseries'
plot(
  x,
  gene.number = 5,
  incremental = FALSE,
  relative = FALSE,
  main = "OncoScore",
  xlab = "timepoints",
  ylab = "score",
  legend.pos = "top",
  file = NA,
  ...
)
```

Arguments

<code>x</code>	input data as result of the function <code>compute.OncoScore</code>
<code>gene.number</code>	number of genes to print
<code>incremental</code>	display the OncoScore increment
<code>relative</code>	display the incrementa as relative value
<code>main</code>	the title
<code>xlab</code>	description of x asix (default score)
<code>ylab</code>	description of y asix (default genes)
<code>legend.pos</code>	Position of the legend
<code>file</code>	where to save the plot
<code>...</code>	additional parameter to pass to the lines function

Value

A plot

Examples

```
data(query.timepoints)
result = compute.oncoscore.timeseries(query.timepoints)
plot.oncoscore.timeseries(result)
```

query

The result of perform.web.query on genes

Description

This dataset contains the result of perform.web.query on genes

Usage

```
data(query)
```

Format

rdata

Value

matrix 5 x 2

Source

example data

query.timepoints

The result of perform.time.series.query on genes and timepoints

Description

This dataset contains the result of perform.time.series.query on genes and timepoints

Usage

```
data(query.timepoints)
```

Format

rdata

Value

list of 5 matrix 5 x 2

Source

example data

timepoints *A list of timepoints*

Description

This dataset contains a list of time points to be used in the analysis as an example

Usage

```
data(timepoints)
```

Format

rdata

Value

list of 5 elements

Source

example data

try.scan *try.scan*

Description

try to query the given URL

Usage

```
try.scan(getURL)
```

Arguments

getURL The given URL

Value

Result obtained from PubMed

Index

`combine.query.results`, [2](#)
`combine.single.matrix`, [3](#)
`compute.frequencies.scores`, [3](#)
`compute.oncoscore`, [4](#)
`compute.oncoscore.from.region`, [4](#)
`compute.oncoscore.timeseries`, [5](#)

`estimate.oncogenes`, [6](#)

`genes`, [7](#)
`get.genes.from.biomart`, [7](#)
`get.list.from.xml`, [8](#)
`get.pubmed.driver.analysis`, [8](#)

`perform.query`, [9](#)
`perform.query.from.region`, [9](#)
`perform.query.timeseries`, [10](#)
`plot.oncoscore`, [11](#)
`plot.oncoscore.timeseries`, [12](#)

`query`, [13](#)
`query.timepoints`, [13](#)

`timepoints`, [14](#)
`try.scan`, [14](#)