

# Package ‘Rhdf5lib’

January 10, 2025

**Type** Package

**Title** hdf5 library as an R package

**Version** 1.28.0

**Description** Provides C and C++ hdf5 libraries.

**License** Artistic-2.0

**Copyright** src/hdf5/COPYING

**LazyLoad** true

**VignetteBuilder** knitr

**Depends** R (>= 4.2.0)

**Suggests** BiocStyle, knitr, rmarkdown, tinytest, mockery

**URL** <https://github.com/grimbough/Rhdf5lib>

**BugReports** <https://github.com/grimbough/Rhdf5lib>

**SystemRequirements** GNU make

**Encoding** UTF-8

**biocViews** Infrastructure

**RoxygenNote** 7.1.2

**git\_url** <https://git.bioconductor.org/packages/Rhdf5lib>

**git\_branch** RELEASE\_3\_20

**git\_last\_commit** f37cb76

**git\_last\_commit\_date** 2024-10-29

**Repository** Bioconductor 3.20

**Date/Publication** 2025-01-09

**Author** Mike Smith [ctb, cre] (<<https://orcid.org/0000-0002-7800-3848>>),  
The HDF Group [cph]

**Maintainer** Mike Smith <[grimbough@gmail.com](mailto:grimbough@gmail.com)>

## Contents

.getDynamicLinks . . . . .	2
.getSzipLoc . . . . .	2
getHdf5Version . . . . .	2
pkgconfig . . . . .	3
Rhdf5lib . . . . .	3

**Index****4**


---

<code>.getDynamicLinks</code>	<i>Return the link flags determined when HDF5 was configured</i>
-------------------------------	--

---

**Description**

Return the link flags determined when HDF5 was configured

**Usage**

```
.getDynamicLinks()
```

---

<code>.getSzipLoc</code>	<i>If we compiled our own version of SZIP this returns the link path Otherwise it returns an empty string.</i>
--------------------------	--

---

**Description**

If we compiled our own version of SZIP this returns the link path Otherwise it returns an empty string.

**Usage**

```
.getSzipLoc(path)
```

---

<code>getHdf5Version</code>	<i>Report the version of HDF5 distributed with this package</i>
-----------------------------	---

---

**Description**

This function returns the version number of the HDF5 library that is distributed with this package.

**Usage**

```
getHdf5Version()
```

**Value**

Returns a character vector of length 1 containing the version number.

**Examples**

```
getHdf5Version()
```

---

pkgconfig

*Compiler arguments for using Rhdf5lib*

---

### Description

This function returns values for PKG\_LIBS variables for use in Makevars files.

### Usage

```
pkgconfig(  
  opt = c("PKG_CXX_LIBS", "PKG_C_LIBS", "PKG_CXX_HL_LIBS", "PKG_C_HL_LIBS")  
)
```

### Arguments

`opt` A scalar character from the list of available options; default is PKG\_CXX\_LIBS. Valid options are PKG\_C\_LIBS, PKG\_CXX\_LIBS, PKG\_C\_HL\_LIBS and PKG\_CXX\_HL\_LIBS, where HL indicates that you want to include the HDF5 'high-level' API and CXX denotes including the C++ interface.

### Value

NULL; prints the corresponding value to stdout.

### Examples

```
pkgconfig("PKG_C_LIBS")  
pkgconfig("PKG_CXX_LIBS")  
pkgconfig("PKG_C_HL_LIBS")  
pkgconfig("PKG_CXX_HL_LIBS")
```

---

Rhdf5lib

*Rhdf5lib: A version of the HDF5 library built into an R package.*

---

### Description

This package provides a compiled version of the HDF5 library bundled within the R package structure. It is primarily useful to developers of other R packages who want to make use of the capabilities of the HDF5 library directly in the C or C++ code of their own packages, rather than using a higher level interface.

# Index

## \* **internal**

[.getDynamicLinks, 2](#)

[.getSzipLoc, 2](#)

[.getDynamicLinks, 2](#)

[.getSzipLoc, 2](#)

[getHdf5Version, 2](#)

[pkgconfig, 3](#)

[Rhdf5lib, 3](#)