

Package ‘Summix’

January 10, 2025

Title Summix2: A suite of methods to estimate, adjust, and leverage substructure in genetic summary data

Version 2.12.0

Description This package contains the Summix2 method for estimating and adjusting for substructure in genetic summary allele frequency data. The function `summix()` estimates reference group proportions using a mixture model. The `adjAF()` function produces adjusted allele frequencies for an observed group with reference group proportions matching a target individual or sample. The `summix_local()` function estimates local ancestry mixture proportions and performs selection scans in genetic summary data.

License MIT + file LICENSE

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

Suggests rmarkdown, markdown, knitr, testthat (>= 3.0.0)

biocViews StatisticalMethod, WholeGenome, Genetics

VignetteBuilder knitr

Encoding UTF-8

Depends R (>= 4.3)

Imports dplyr, nloptr, magrittr, methods, tibble, tidyselect, BEDASSLE, scales, visNetwork, randomcolor

LazyData true

BugReports <https://github.com/Bioconductor/Summix/issues>

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/Summix>

git_branch RELEASE_3_20

git_last_commit b6a1b50

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2025-01-09

Author Audrey Hendricks [cre],
Price Adelle [aut],
Stoneman Haley [aut]

Maintainer Audrey Hendricks <audrey.hendricks@cuanschutz.edu>

Contents

| | |
|----------------------|----|
| adjAF | 2 |
| adjAF_calc | 4 |
| ancestryData | 4 |
| calc_effective_N | 5 |
| calc_scaledObj | 6 |
| doInternalSimulation | 6 |
| getNextEndPoint | 7 |
| getNextStartPoint | 7 |
| saveBlock | 8 |
| sizeGetNext | 8 |
| summix | 9 |
| summix_calc | 11 |
| summix_local | 11 |
| summix_network | 14 |
| testDiff | 15 |
| variantGetNext | 15 |

| | |
|--------------|-----------|
| Index | 16 |
|--------------|-----------|

| | |
|-------|--------------|
| adjAF | <i>adjAF</i> |
|-------|--------------|

Description

Adjusts allele frequencies for heterogeneous populations in genetic data given proportion of reference groups

Usage

```
adjAF(
  data,
  reference,
  observed,
  pi.target,
  pi.observed,
  adj_method = "average",
  N_reference = NULL,
  N_observed = NULL,
  filter = TRUE
)
```

Arguments

| | |
|-----------|--|
| data | dataframe of unadjusted allele frequency for observed group, K reference group allele frequencies for N SNPs |
| reference | character vector of the column names for K reference groups. |
| observed | character value for the column name of observed data group |
| pi.target | numeric vector of the mixture proportions for K reference groups in the target individual or group. |

| | |
|-------------|--|
| pi.observed | numeric vector of the mixture proportions for K reference groups in the observed group. |
| adj_method | user choice of method for the allele frequency adjustment: options "average" and "leave_one_out" are available. Defaults to "average". |
| N_reference | numeric vector of the sample sizes for each of the K reference groups. |
| N_observed | numeric value of the sample size of the observed group. |
| filter | sets adjusted allele frequencies equal to 1 if > 1 , to 0 if $> -.005$ and < 0 , and removes adjusted allele frequencies $< -.005$. |

Value

pi: table of input reference groups, pi.observed, and pi.target

observed.data: name of the data column for the observed group from which adjusted allele frequency is estimated

Nsnps: number of SNPs for which adjusted AF is estimated

adjusted.AF: data frame of original data with an appended column of adjusted allele frequencies

effective.sample.size: The sample size of individuals effectively represented by the adjusted allele frequencies

Author(s)

Adelle Price, <adelle.price@cuanschutz.edu>

Hayley Wolff, <hayley.wolff@cuanschutz.edu>

Audrey Hendricks, <audrey.hendricks@cuanschutz.edu>

References

<https://github.com/hendriau/Summix2>

See Also

<https://github.com/hendriau/Summix2> for further documentation.

Examples

```
data(ancestryData)
adjusted_data<-adjAF(data = ancestryData,
  reference = c("reference_AF_afr", "reference_AF_eur"),
  observed = "gnomad_AF_afr",
  pi.target = c(1, 0),
  pi.observed = c(.85, .15),
  adj_method = 'average',
  N_reference = c(704, 741),
  N_observed = 20744,
  filter = TRUE)
adjusted_data$adjusted.AF[1:5,]
```

adjAF_calc

adjAF_calc

Description

Helper function for calculating allele frequencies for heterogeneous populations in genetic data given proportion of reference groups

Usage

```
adjAF_calc(data, reference, observed, pi.target, pi.observed)
```

Arguments

| | |
|-------------|---|
| data | dataframe of unadjusted allele frequency for observed group, K-1 reference group allele frequencies for N SNPs |
| reference | character vector of the column names for K-1 reference groups. The name of the last reference group is not included as that group is not used to estimate the adjusted allele frequencies. |
| observed | character value for the column name of observed data group |
| pi.target | numeric vector of the mixture proportions for K reference groups in the target sample or subject. The order must match the order of the reference columns with the last entry matching the missing reference group. |
| pi.observed | numeric vector of the mixture proportions for K reference groups for the observed group. The order must match the order of the reference columns with the last entry matching the missing reference group. |

Value

pi: table of input reference groups, pi.observed, and pi.target
observed.data: name of the data column for the observed group from which adjusted allele frequency is estimated
Nsnps: number of SNPs for which adjusted AF is estimated
adjusted.AF: data frame of original data with an appended column of adjusted allele frequencies

ancestryData

ancestryData

Description

Sample dataset containing reference and observed allele frequencies to be used for examples within the Summix package.

Usage

```
ancestryData
```

Format

A data frame with 1000 rows (representing individual SNPs) and 10 columns:

POS Position of SNP on given chromosome.

REF Reference allele

ALT Alternate allele

CHROM Chromosome

reference_AF_afr Allele frequency column of the African reference ancestry.

reference_AF_eas Allele frequency column of the East Asian reference ancestry.

reference_AF_eur Allele frequency column of the European reference ancestry.

reference_AF_iam Allele frequency column of the Indigenous American reference ancestry.

reference_AF_sas Allele frequency column of the South Asian reference ancestry.

gnomad_AF_afr Allele frequency column of the observed gnomAD v3.1.2 African/African American population.

Source

<https://gnomad.broadinstitute.org/downloads#v3>

| | |
|------------------|-------------------------|
| calc_effective_N | <i>calc_effective_N</i> |
|------------------|-------------------------|

Description

Helper function to calculate effective sample size for the group that is left out when estimating the adjusted allele frequencies in each adjAF function iteration.

Usage

```
calc_effective_N(N_reference, N_observed, pi.target, pi.observed)
```

Arguments

| | |
|-------------|---|
| N_reference | numeric vector of the sample sizes of each K reference groups. |
| N_observed | numeric value of the sample size of the observed group. |
| pi.target | numeric vector of the mixture proportions for K reference groups in the target sample or subject. The order must match the order of the reference columns with the last entry matching the missing reference group. |
| pi.observed | numeric vector of the mixture proportions for K reference groups for the observed group. The order must match the order of the reference columns with the last entry matching the missing reference group. |

Value

N_effective: effective sample size for the group that is left out when estimating the adjusted allele frequencies in each adjAF function iteration.

| | |
|----------------|-----------------------|
| calc_scaledObj | <i>calc_scaledObj</i> |
|----------------|-----------------------|

Description

Helper function to calculate new scaled loss function using weighted AF bin objectives

Usage

```
calc_scaledObj(data, reference, observed, pi.start)
```

Arguments

| | |
|-----------|--|
| data | a dataframe of the observed and reference allele frequencies for N genetic variants. See data formatting document at https://github.com/hendriau/Summix for more information. Uses the same input data as summix. |
| reference | a character vector of the column names for the reference groups. |
| observed | a string that is the column name for the observed group. |
| pi.start | Length K numeric vector of the starting guess for the reference group proportions. If not specified, this defaults to 1/K where K is the number of reference groups. |

Value

numeric value that is the scaled objective per 1000 SNPs

| | |
|----------------------|-----------------------------|
| doInternalSimulation | <i>doInternalSimulation</i> |
|----------------------|-----------------------------|

Description

Helper function to get the within block se using re-simulation

Usage

```
doInternalSimulation(windows, data, reference, observed, nRefs)
```

Arguments

| | |
|-----------|---|
| windows | is a dataframe with the Start_Pos and End_Pos |
| data | is the original chromosome data |
| reference | is a list with the names of the columns with references |
| observed | a character value that is the column name for the observed group |
| nRefs | is a vector the same lengths as reference with the number of individuals in each reference population |

| | |
|-----------------|------------------------|
| getNextEndPoint | <i>getNextEndPoint</i> |
|-----------------|------------------------|

Description

Helper function: algorithm to get next end point in basic window algorithm; will find first point that is at least window size away from start

Usage

```
getNextEndPoint(data, start, windowSize)
```

Arguments

| | |
|------------|--|
| data | the input dataframe subset to the chromosome |
| start | index of the current start point |
| windowSize | the window size (in bp or variants) |

Value

index of end point of window

| | |
|-------------------|--------------------------|
| getNextStartPoint | <i>getNextStartPoint</i> |
|-------------------|--------------------------|

Description

Helper function: algorithm to get next start point; will pick the point that provides approx. the specified amount of overlap, but not more; if there are only two variants in the previous block, will jump new start point to the previous end point

Usage

```
getNextStartPoint(data, start, end, overlap)
```

Arguments

| | |
|---------|--|
| data | the input dataframe subset to the chromosome |
| start | the current index of start point |
| end | the current index of end point |
| overlap | the desired amount of window overlap (in bp or variants) |

Value

returns index of new start point

| | |
|-----------|------------------|
| saveBlock | <i>saveBlock</i> |
|-----------|------------------|

Description

Helper function to save one block to results

Usage

```
saveBlock(data, start, end, props, results)
```

Arguments

| | |
|---------|---|
| data | the input dataframe subsetting to just the chromosome |
| start | index of start of block |
| end | index of the end of block |
| props | substructure proportions for the block returned from summix |
| results | current results dataframe |

| | |
|-------------|--------------------|
| sizeGetNext | <i>sizeGetNext</i> |
|-------------|--------------------|

Description

Helper function to get starting end point that is a minimum distance (in bases) from start point; uses indices NOT position numbers

Usage

```
sizeGetNext(positions, start, minSize)
```

Arguments

| | |
|-----------|---|
| positions | list of positions of variants |
| start | index of the current start position |
| minSize | integer defining the minimum size in bp of the window |

Value

the new end point index

summix *summix*

Description

Estimating mixture proportions of reference groups from large (N SNPs>10,000) genetic AF data.

Usage

```
summix(
  data,
  reference,
  observed,
  pi.start = NA,
  goodness.of.fit = TRUE,
  override_removeSmallRef = FALSE,
  network = FALSE,
  N_reference = NA,
  reference_colors = NA
)
```

Arguments

| | |
|--------------------------------------|--|
| <code>data</code> | A dataframe of the observed and reference allele frequencies for N genetic variants. See data formatting document at https://github.com/hendriau/Summix for more information. |
| <code>reference</code> | A character vector of the column names for the reference groups. |
| <code>observed</code> | A character value that is the column name for the observed group. |
| <code>pi.start</code> | Length K numeric vector of the starting guess for the reference group proportions. If not specified, this defaults to 1/K where K is the number of reference groups. |
| <code>goodness.of.fit</code> | Default value is TRUE. If set as FALSE, the user will override the default goodness of fit measure and return the raw objective loss from slsqp. |
| <code>override_removeSmallRef</code> | Default value is FALSE. If set as TRUE, the user will override the automatic removal of reference groups with <1% global proportions - this is not recommended. |
| <code>network</code> | Default value is FALSE. If set as TRUE, function will return a network diagram with nodes as estimated substructure proportions and edges as degree of similarity between the given node pair. |
| <code>N_reference</code> | numeric vector of the sample sizes for each of the K reference groups; must be specified if <code>network = "TRUE"</code> . |
| <code>reference_colors</code> | A character vector of length K that specifies the color each reference group node in the network plot. If not specified, this defaults to K random colors. |

Value

A data frame with the following columns:

goodness.of.fit: scaled objective loss from `slsqp()` reflecting the fit of the reference data. Values between 0.5-1.5 are considered moderate fit and should be used with caution. Values greater than 1.5 indicate poor fit, and users should not perform further analyses using Summix.

iterations: number of iterations for SLSQP algorithm

time: time in seconds of SLSQP algorithm

filtered: number of genetic variants not used in the reference group mixture proportion estimation due to missing values.

K columns of mixture proportions of reference groups input into the function

Author(s)

Adelle Price, <adelle.price@cuanschutz.edu>

Hayley Wolff, <hayley.wolff@cuanschutz.edu>

Audrey Hendricks, <audrey.hendricks@cuanschutz.edu>

References

<https://github.com/hendriau/Summix2>

See Also

<https://github.com/hendriau/Summix2> for further documentation. `slsqp` function in the `nloptr` package for further details on Sequential Quadratic Programming <https://www.rdocumentation.org/packages/nloptr/versions/1.2.2.2/topics/slsqp>

Examples

```
# load the data
data("ancestryData")

# Estimate 5 reference ancestry proportion values for the gnomAD African/African American group
# using a starting guess of .2 for each ancestry proportion.
summix(data = ancestryData,
       reference=c("reference_AF_afr",
                  "reference_AF_eas",
                  "reference_AF_eur",
                  "reference_AF_iam",
                  "reference_AF_sas"),
       observed="gnomad_AF_afr",
       pi.start = c(.2, .2, .2, .2, .2),
       goodness.of.fit=TRUE)
```

| | |
|-------------|--------------------|
| summix_calc | <i>summix_calc</i> |
|-------------|--------------------|

Description

Helper function for estimating mixture proportions of reference groups from large (N SNPs>10,000) genetic AF data, using slsqp to solve for least square difference

Usage

```
summix_calc(data, reference, observed, pi.start = NA)
```

Arguments

| | |
|-----------|--|
| data | A dataframe of the observed and reference allele frequencies for N genetic variants. See data formatting document at https://github.com/hendriau/Summix for more information. |
| reference | A character vector of the column names for the reference groups. |
| observed | A character value that is the column name for the observed group. |
| pi.start | Length K numeric vector of the starting guess for the reference group proportions. If not specified, this defaults to 1/K where K is the number of reference groups. |

Value

data frame with the following columns

- objective: least square value at solution
- iterations: number of iterations for SLSQP algorithm
- time: time in seconds of SLSQP algorithm
- filtered: number of SNPs not used in estimation due to missing values
- K columns of mixture proportions of reference groups input into the function

| | |
|--------------|---------------------|
| summix_local | <i>summix_local</i> |
|--------------|---------------------|

Description

Estimates local substructure mixture proportions in genetic summary data; Also performs a selection scan (optional) that identifies potential regions of selection along the given chromosome.

Usage

```
summix_local(
  data,
  reference,
  observed,
  goodness.of.fit = TRUE,
  type = "variants",
  algorithm = "fastcatch",
  minVariants = 0,
  maxVariants = 0,
  maxWindowSize = 0,
  minWindowSize = 0,
  windowOverlap = 200,
  maxStepSize = 1000,
  diffThreshold = 0.02,
  NSimRef = NULL,
  override_fit = FALSE,
  override_removeSmallAnc = FALSE,
  selection_scan = FALSE,
  position_col = "POS"
)
```

Arguments

| | |
|------------------------------|--|
| <code>data</code> | a data frame of the observed group and reference group allele frequencies for N genetic variants on a single chromosome. Must contain a column specifying the genetic variant positions. |
| <code>reference</code> | a character vector of the column names for K reference groups. |
| <code>observed</code> | a character value that is the column name for the observed group. |
| <code>goodness.of.fit</code> | an option to override the default scaled objective to return the raw loss from slsqp |
| <code>type</code> | user choice of how to define window size; options "variants" and "bp" are available where "variants" defines window size as the number of variants in a given window and "bp" defines window size as the number of base pairs in a given window. Default is "variants". |
| <code>algorithm</code> | user choice of algorithm to define local substructure blocks; options "fastcatch" and "windows" are available. "windows" uses a fixed window in a sliding windows algorithm. "fastcatch" allows dynamic window sizes. The "fastcatch" algorithm is recommended- though it is computationally slower. Default is "fastcatch". |
| <code>minVariants</code> | Used if <code>algorithm = "fastcatch"</code> and <code>type = "variants"</code> . A numeric value that specifies the minimum number of genetic variants allowed to define a given window. |
| <code>maxVariants</code> | Used if <code>type = "variants"</code> . A numeric value that specifies the maximum number of genetic variants allowed to define a given window. |
| <code>maxWindowSize</code> | Used if <code>type = "bp"</code> . A numeric value that defines the maximum allowed window size by the number of base pairs in a given window. |
| <code>minWindowSize</code> | Used if <code>algorithm = "fastcatch"</code> and <code>type = "bp"</code> . A numeric value that specifies the minimum number of base pairs allowed to define a given window. |

| | |
|-------------------------|---|
| windowOverlap | Used if algorithm = "windows". A numeric value that defines the number of variants or the number of base pairs that overlap between the given sliding windows. Default is 200. |
| maxStepSize | a numeric value that defines the maximum gap in base pairs between two consecutive genetic variants within a given window. Default is 1000. |
| diffThreshold | Used if algorithm = "fastcatch". A numeric value that defines the percent difference threshold to mark the end of a local substructure block. Default is 0.02. |
| NSimRef | Used if f selection_scan = TRUE. A numeric vector of the sample sizes for each of the K reference groups that is in the same order as the reference parameter. This is used in a simulation framework that calculates within local substructure block standard error. |
| override_fit | default is FALSE. If set as TRUE, the user will override the auto-stop of summix_local() that occurs if the global goodness of fit value is greater than 1.5 (indicating a poor fit of the reference data to the observed data). |
| override_removeSmallAnc | default is FALSE. If set as TRUE, the user will override the automatic removal of reference ancestries with <2% global proportions – this is not recommended. |
| selection_scan | user option to perform a selection scan on the given chromosome. Default is FALSE. If set as TRUE, a test statistic will be calculated for each local substructure block. Note: the user can expect extended computation time if this option is set as TRUE. |
| position_col | a character value that is the column name for the genetic variants positions. Default is "POS". |

Value

data frame with a row for each local substructure block and the following columns:

goodness.of.fit: scaled objective reflecting the fit of the reference data. Values between 0.5-1.5 are considered moderate fit and should be used with caution. Values greater than 1.5 indicate poor fit, and users should not perform further analyses using summix

iterations: number of iterations for SLSQP algorithm

time: time in seconds of SLSQP algorithm

filtered: number of SNPs not used in estimation due to missing values

K columns of mixture proportions of reference groups input into the function

nSNPs: number of SNPs in the given local substructure block

Author(s)

Hayley Wolff (Stoneman), <hayley.wolff@cuanschutz.edu>

Audrey Hendricks, <audrey.hendricks@cuanschutz.edu>

References

<https://github.com/hendriau/Summix2>

See Also

<https://github.com/hendriau/Summix2> for further documentation.

Examples

```

data(ancestryData)
results <- summix_local(data = ancestryData,
                       reference = c("reference_AF_afr",
                                      "reference_AF_eas",
                                      "reference_AF_eur",
                                      "reference_AF_iam",
                                      "reference_AF_sas"),
                       NSimRef = c(704,787,741,47,545),
                       observed="gnomad_AF_afr",
                       goodness.of.fit = TRUE,
                       type = "variants",
                       algorithm = "fastcatch",
                       minVariants = 150,
                       maxVariants = 250,
                       maxStepSize = 1000,
                       diffThreshold = .02,
                       override_fit = FALSE,
                       override_removeSmallAnc = TRUE,
                       selection_scan = FALSE,
                       position_col = "POS")
print(results$results)

```

summix_network

*summix_network***Description**

Helper function to plot the network diagram of estimated substructure proportions and similarity between reference groups

Usage

```

summix_network(
  data = data,
  sum_res = sum_res,
  reference = reference,
  N_reference = N_reference,
  reference_colors = reference_colors
)

```

Arguments

| | |
|------------------|--|
| data | A dataframe of the observed and reference allele frequencies for N genetic variants. See data formatting document at https://github.com/hendriau/Summix for more information. |
| sum_res | The resulting data frame from the summix function |
| reference | A character vector of the column names for the reference groups. |
| N_reference | numeric vector of the sample sizes for each of the K reference groups. |
| reference_colors | A character vector of length K that specifies the color each reference group node in the network plot. If not specified, this defaults to K random colors. |

Value

network diagram with nodes as estimated substructure proportions and edges as degree of similarity between the given node pair

| | |
|----------|-----------------|
| testDiff | <i>testDiff</i> |
|----------|-----------------|

Description

Helper function to determine whether reference group has changed for fast/catchup window algorithm

Usage

```
testDiff(last, current, threshold = 0.01)
```

Arguments

| | |
|-----------|--|
| last | substructure proportions of block returned from summix |
| current | substructure proportions of block returned from summix |
| threshold | if applicable the threshold for determining change point |

Value

true if passes threshold, false if not

| | |
|----------------|-----------------------|
| variantGetNext | <i>variantGetNext</i> |
|----------------|-----------------------|

Description

Helper function to get starting end point that is a minimum distance (in variants) from start point; uses indices NOT position numbers

Usage

```
variantGetNext(positions, start, minVariants)
```

Arguments

| | |
|-------------|---|
| positions | list of positions of variants |
| start | index of the current start position |
| minVariants | integer defining the minimum size in number of variants of the window |

Value

the new end point index

Index

- * **admixture**,
 - adjAF, 2
 - summix, 9
 - summix_local, 11
- * **ancestry**
 - summix_local, 11
- * **datasets**
 - ancestryData, 4
- * **distribution**,
 - adjAF, 2
 - summix, 9
 - summix_local, 11
- * **genetics**,
 - adjAF, 2
 - summix, 9
 - summix_local, 11
- * **local**
 - summix_local, 11
- * **mixture**
 - adjAF, 2
 - summix, 9
 - summix_local, 11
- * **population**
 - adjAF, 2
 - summix, 9
 - summix_local, 11
- * **stratification**,
 - summix_local, 11
- * **stratification**
 - adjAF, 2
 - summix, 9

adjAF, 2

adjAF_calc, 4

ancestryData, 4

calc_effective_N, 5

calc_scaledObj, 6

doInternalSimulation, 6

getNextEndPoint, 7

getNextStartPoint, 7

saveBlock, 8

sizeGetNext, 8

slsqp, 10

summix, 9

summix_calc, 11

summix_local, 11

summix_network, 14

testDiff, 15

variantGetNext, 15