

Package ‘VaSP’

January 10, 2025

Type Package

Version 1.18.0

Title Quantification and Visualization of Variations of Splicing in Population

Description Discovery of genome-wide variable alternative splicing events from short-read RNA-seq data and visualizations of gene splicing information for publication-quality multi-panel figures in a population. (Warning: The visualizing function is removed due to the dependent package Sushi deprecated. If you want to use it, please change back to an older version.)

URL <https://github.com/yuhuihui2011/VaSP>

BugReports <https://github.com/yuhuihui2011/VaSP/issues>

License GPL (>= 2.0)

Depends R (>= 4.0), ballgown

Imports IRanges, GenomicRanges, S4Vectors, parallel, matrixStats, GenomicAlignments, GenomeInfoDb, Rsamtools, cluster, stats, graphics, methods

Suggests knitr, rmarkdown

VignetteBuilder knitr

biocViews RNASeq, AlternativeSplicing, DifferentialSplicing, StatisticalMethod, Visualization, Preprocessing, Clustering, DifferentialExpression, KEGG, ImmunoOncology

Encoding UTF-8

LazyData false

RoxygenNote 7.1.1

git_url <https://git.bioconductor.org/packages/VaSP>

git_branch RELEASE_3_20

git_last_commit a50d9a5

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2025-01-09

Author Huihui Yu [aut, cre] (<<https://orcid.org/0000-0003-2725-1937>>),
Qian Du [aut] (<<https://orcid.org/0000-0003-3864-8745>>),
Chi Zhang [aut] (<<https://orcid.org/0000-0002-1827-8137>>)

Maintainer Huihui Yu <yuhuihui2011@foxmail.com>

Contents

| | |
|------------------------|---|
| BMfinder | 2 |
| getDepth | 3 |
| getGeneinfo | 3 |
| rice.bg | 4 |
| spliceGene | 5 |
| spliceGenome | 6 |

| | |
|--------------|----------|
| Index | 8 |
|--------------|----------|

| | |
|----------|---|
| BMfinder | <i>Discover bimodal distribution features</i> |
|----------|---|

Description

Find bimodal distribution features and divide the samples into 2 groups by k-means clustering.

Usage

```
BMfinder(x, p.value = 0.01, maf = 0.05, miss = 0.05, fold = 2, log = FALSE,
         cores = detectCores() - 1)
```

Arguments

| | |
|---------|--|
| x | a numeric matrix with feature rows and sample columns, e.g., splicing score matrix from spliceGenome or spliceGene function. |
| p.value | p.value threshold for bimodal distribution test |
| maf | minor allele frequency threshold in k-means clustering |
| miss | missing grouping rate threshold in k-means clustering |
| fold | fold change threshold between the two groups |
| log | whether the scores are to be logarithmic. If TRUE, all the scores are log2 transformed before k-means clustering: $x = \log_2(x+1)$. |
| cores | threads to be used. This value is passed to ?mclapply in parallel package |

Details

The matrix contains 1, 2 and NA, and values of 'x' in group 2 are larger than group 1.

Value

a matrix with feature rows and sample columns.

Examples

```
data(rice.bg)
score<-spliceGene(rice.bg, 'MSTRG.183', junc.type='score')
score<-round(score,2)
as<-BMfinder(score,cores=1) # 4 bimodal distribution features found

##compare
as
score[rownames(score)%in%rownames(as),]
```

getDepth

Get Read Depth

Description

Get read depth from a BAM file (in bedgraph format)

Usage

```
getDepth(x, chrom, start, end)
```

Arguments

| | |
|-------|---------------------------------------|
| x | path to a BAM file |
| chrom | chromosome of a region to be searched |
| start | start position |
| end | end position |

Value

a data.frame in bedgraph file format.

Examples

```
path <- system.file('extdata', package='VaSP')
bam_files<-list.files(path, 'bam$')
bam_files

depth<-getDepth(file.path(path, bam_files[1]), 'Chr1',
                 start=1171800, end=1179400)
head(depth)

# library(Sushi)
# plotBedgraph(depth, 'Chr1', chromstart=1171800, chromend=1179400, yaxt='s')
# mtext('Depth', side=2, line=2.5, cex=1.2, font=2)
# labelgenome('Chr1', 1171800, 1179400, side=1, scipen=20, n=5, scale='Kb')
```

getGeneinfo

Get Gene Informaton from a ballgown object

Description

Get gene informaton from a ballgown object by genes or by genomic regions

Usage

```
getGeneinfo(genes = NA, bg, chrom, start, end, samples = sampleNames(bg),
            trans.select = NA)
```

Arguments

| | |
|--------------|---|
| genes | a character vector specifying gene IDs in 'bg'. Any values other than NA override genomic region (chrom, start, stop) |
| bg | ballgown object |
| chrom | chromosome of a region |
| start | start position |
| end | stop position |
| samples | names of samples. The transcripts in these samples are subjected to 'trans.select' |
| trans.select | logical expression-like string, indicating transcript rows to select from a matrix of transcript coverages: NA value keeps all transcripts. |

Value

a data.frame in bed-like file format

Examples

```
data(rice.bg)
unique(geneIDs(rice.bg))

gene_id <- c('MSTRG.181', 'MSTRG.182', 'MSTRG.183')
geneinfo <- getGeneinfo(genes=gene_id, rice.bg)
trans <- table(geneinfo$name) # show how many exons each transcript has
trans

# library(Sushi)
# chrom = geneinfo$chrom[1]
# chromstart = min(geneinfo$start) - 1e3
# chromend = max(geneinfo$stop) + 1e3
# color = rep(SushiColors(2)(length(trans)), trans)

# par(mar=c(3,1,1,1))
# plotGenes(geneinfo, chrom, chromstart, chromend, col = color, bheight = 0.2,
#           bentline = FALSE, plotgenetype = 'arrow', labeloffset = 0.5)
# labelgenome(chrom, chromstart, chromend, side = 1, n = 5, scale = 'Kb')
```

rice.bg

Rice ballgown object

Description

Small ballgown object created with a subset of rice RNAseq data, for demonstration purposes

Format

a ballgown object with 33 transcripts and 6 samples

Details

The raw RNA-seq data were screened and trimmed using Trimmomatic (Bolger et al., 2014) and RNA-seq mapping, transcript assembly, and quantification were conducted with HISAT, StringTie, and Ballgown by following the method described by Pertea et al. (Pertea et al., 2016). The rice.bg is a subset ballgown object with 33 transcripts and 6 samples (Yu et al., 2021).

Source

The raw RNA-seq data were from the project of variation in transcriptional responses to salt stress in rice (SRA Accession: [SRP106054](https://www.ncbi.nlm.nih.gov/sra/SRP106054))

References

Yu, H., Du, Q., Campbell, M., Yu, B., Walia, H. and Zhang, C. (2021), Genome-wide discovery of natural variation in pre-mRNA splicing and prioritising causal alternative splicing to salt stress response in rice. *New Phytol.* <https://doi.org/10.1111/nph.17189>

Bolger, A.M., Lohse, M., and Usadel, B. (2014). Trimmomatic: a flexible trimmer for Illumina sequence data. *Bioinformatics* 30, 2114-2120.

Pertea, M., Kim, D., Pertea, G.M., Leek, J.T., and Salzberg, S.L. (2016). Transcript-level expression analysis of RNA-seq experiments with HISAT, StringTie and Ballgown. *Nat Protoc* 11, 1650-1667.

Examples

```
data(rice.bg)
rice.bg
# ballgown instance with 33 transcripts and 6 samples
```

spliceGene

Calculate Splicing Scores for One Gene

Description

Calculate splicing Scores from ballgown object for a given gene. This function can only calculate one gene. Please use function [spliceGenome](#) to obtain genome-wide splicing scores.

Usage

```
spliceGene(bg, gene, samples = sampleNames(bg), junc.type = c("score", "count"),
           trans.select = "rowMaxs(x)>=1", junc.select = "rowMaxs(x)>=5")
```

Arguments

| | |
|--------------|--|
| bg | ballgown object |
| gene | a character string specifying gene id |
| samples | names of samples |
| junc.type | type of junction estimate ('score' for junction score; 'count' for junction read count) |
| trans.select | logical expression-like string, indicating transcript rows to select from a matrix of transcript coverages: NA value keeps all transcripts. e.g. use trans.select='rowMaxs(x)>=1' to filter the transcripts with the maximum coverage among all the samples less than 1. |
| junc.select | logical expression-like string, indicating junction rows to select from a matrix of junction counts: NA value keeps all junctions. e.g. use junc.select='rowMaxs(x)>=5' to filter the junctions with the maximum read count among all the samples less than 5. |

Details

score = junction count/gene-level per base read coverage. Row functions for matrices are useful to select transcripts and junctions. See [matrixStats](#) package.

Value

a matrix of junction scores with intron rows and sample columns.

References

Yu, H., Du, Q., Campbell, M., Yu, B., Walia, H. and Zhang, C. (2021), Genome-wide discovery of natural variation in pre-mRNA splicing and prioritising causal alternative splicing to salt stress response in rice. *New Phytol.* <https://doi.org/10.1111/nph.17189>

See Also

[spliceGenome](#), which calculates splicing scores in whole genome.

Examples

```
data(rice.bg)
rice.bg
head(geneIDs(rice.bg))

score<-spliceGene(rice.bg, 'MSTRG.183',junc.type='score')
count<-spliceGene(rice.bg, 'MSTRG.183',junc.type='count')

## compare
tail(score)
tail(count)

## get intron structure
intron<-structure(rice.bg)$intron
intron[intron$id%in%rownames(score)]
```

spliceGenome

Calculate Genome-wide Splicing Scores

Description

Calculate splicing scores from ballgown objects for all genes.

Usage

```
spliceGenome(bg, gene.select = "rowQuantiles(x,probs = 0.05)>=1",
             intron.select = "rowQuantiles(x,probs = 0.95)>=5")
```

Arguments

| | |
|----------------------------|---|
| <code>bg</code> | ballgown object |
| <code>gene.select</code> | logical expression-like string, indicating genes to select from a matrix of gene-level coverages: NA value keeps all genes. e.g. <code>gene.select = 'rowQuantiles(x,probs = 0.05)>=1'</code> keeps the genes with the read coverage greater than or equal to 1 in at least 95 (0.05 quantile). Used to filter low expressed genes. |
| <code>intron.select</code> | logical expression-like string, indicating introns to select from a matrix of junction counts: NA value keeps all introns. e.g. <code>intron.select = 'rowQuantiles(x,probs = 0.95)>=5'</code> keeps the introns with the read count greater than or equal to 5 in at least 5 (0.95 quantile). Used to filter introns with very few junction reads supporting. |

Details

`score` = junction count/gene-level per base read coverage. Row functions for matrices in [matrixStats](#) package are useful to select genes and introns.

Value

a list of two elements: 'score' is matrix of intron splicing scores with intron rows and sample columns and 'intron' is a [GRanges](#) object of intron structure. See [structure](#) in [ballgown](#) package

References

Yu, H., Du, Q., Campbell, M., Yu, B., Walia, H. and Zhang, C. (2021), Genome-wide discovery of natural variation in pre-mRNA splicing and prioritising causal alternative splicing to salt stress response in rice. *New Phytol.* <https://doi.org/10.1111/nph.17189>

See Also

[spliceGene](#), which calculates splicing scores in one gene.

Examples

```
data(rice.bg)
rice.bg

splice<-spliceGenome(rice.bg,gene.select=NA,intron.select=NA)
names(splice)

head(splice$score)
splice$intron
```

Index

* datasets

rice.bg, 4

BMfinder, 2

getDepth, 3

getGeneinfo, 3

GRanges, 7

matrixStats, 6, 7

rice.bg, 4

spliceGene, 2, 5, 7

spliceGenome, 2, 5, 6, 6

structure, 7