

Package ‘geneLenDataBase’

January 28, 2025

Title Lengths of mRNA transcripts for a number of genomes

Version 1.42.0

Date 2024-06-08

Description Length of mRNA transcripts for a number of genomes and gene ID formats, largely based on UCSC table browser. Data objects are provided as individual pieces of information to be retrieved and loaded. A variety of different gene identifiers and genomes is supported to ensure wide applicability.

Depends R (>= 2.11.0)

Imports utils, rtracklayer, GenomicFeatures, txdbmaker

URL <https://github.com/federicomarini/geneLenDataBase>

BugReports <https://github.com/federicomarini/geneLenDataBase/issues>

License LGPL (>= 2)

biocViews ExperimentData, Genome

RoxygenNote 7.3.1

Encoding UTF-8

git_url <https://git.bioconductor.org/packages/geneLenDataBase>

git_branch RELEASE_3_20

git_last_commit 8eb2611

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2025-01-28

Author Matthew Young [aut],
Nadia Davidson [aut],
Federico Marini [ctb, cre] (<<https://orcid.org/0000-0003-3252-7758>>)

Maintainer Federico Marini <marinif@uni-mainz.de>

Contents

anoCar1.ensGene.LENGTH	8
anoCar1.genscan.LENGTH	9
anoCar1.xenoRefGene.LENGTH	9
anoGam1.ensGene.LENGTH	10

anoGam1.geneid.LENGTH	10
anoGam1.genscan.LENGTH	11
apiMel1.genscan.LENGTH	11
apiMel2.ensGene.LENGTH	12
apiMel2.geneid.LENGTH	12
apiMel2.genscan.LENGTH	13
aplCal1.xenoRefGene.LENGTH	13
bosTau2.geneid.LENGTH	14
bosTau2.geneSymbol.LENGTH	14
bosTau2.genscan.LENGTH	15
bosTau2.refGene.LENGTH	15
bosTau2.sgpGene.LENGTH	16
bosTau3.ensGene.LENGTH	16
bosTau3.geneid.LENGTH	17
bosTau3.geneSymbol.LENGTH	17
bosTau3.genscan.LENGTH	18
bosTau3.refGene.LENGTH	18
bosTau3.sgpGene.LENGTH	19
bosTau4.ensGene.LENGTH	19
bosTau4.geneSymbol.LENGTH	20
bosTau4.genscan.LENGTH	20
bosTau4.nscanGene.LENGTH	21
bosTau4.refGene.LENGTH	21
braFlo1.xenoRefGene.LENGTH	22
caeJap1.xenoRefGene.LENGTH	22
caePb1.xenoRefGene.LENGTH	23
caePb2.xenoRefGene.LENGTH	23
caeRem2.xenoRefGene.LENGTH	24
caeRem3.xenoRefGene.LENGTH	24
calJac1.genscan.LENGTH	25
calJac1.nscanGene.LENGTH	25
calJac1.xenoRefGene.LENGTH	26
canFam1.ensGene.LENGTH	26
canFam1.geneSymbol.LENGTH	27
canFam1.genscan.LENGTH	27
canFam1.nscanGene.LENGTH	28
canFam1.refGene.LENGTH	28
canFam1.xenoRefGene.LENGTH	29
canFam2.ensGene.LENGTH	29
canFam2.geneSymbol.LENGTH	30
canFam2.genscan.LENGTH	30
canFam2.nscanGene.LENGTH	31
canFam2.refGene.LENGTH	31
canFam2.xenoRefGene.LENGTH	32
cavPor3.ensGene.LENGTH	32
cavPor3.genscan.LENGTH	33
cavPor3.nscanGene.LENGTH	33
cavPor3.xenoRefGene.LENGTH	34
cb1.xenoRefGene.LENGTH	34
cb3.xenoRefGene.LENGTH	35
ce2.geneid.LENGTH	35
ce2.geneSymbol.LENGTH	36

ce2.refGene.LENGTH	36
ce4.geneSymbol.LENGTH	37
ce4.refGene.LENGTH	37
ce4.xenoRefGene.LENGTH	38
ce6.ensGene.LENGTH	38
ce6.geneSymbol.LENGTH	39
ce6.refGene.LENGTH	39
ce6.xenoRefGene.LENGTH	40
ci1.geneSymbol.LENGTH	40
ci1.refGene.LENGTH	41
ci1.xenoRefGene.LENGTH	41
ci2.ensGene.LENGTH	42
ci2.geneSymbol.LENGTH	42
ci2.refGene.LENGTH	43
ci2.xenoRefGene.LENGTH	43
danRer3.ensGene.LENGTH	44
danRer3.geneSymbol.LENGTH	44
danRer3.refGene.LENGTH	45
danRer4.ensGene.LENGTH	45
danRer4.geneSymbol.LENGTH	46
danRer4.genscan.LENGTH	46
danRer4.nscanGene.LENGTH	47
danRer4.refGene.LENGTH	47
danRer5.ensGene.LENGTH	48
danRer5.geneSymbol.LENGTH	48
danRer5.refGene.LENGTH	49
danRer5.vegaGene.LENGTH	49
danRer5.vegaPseudoGene.LENGTH	50
danRer6.ensGene.LENGTH	50
danRer6.geneSymbol.LENGTH	51
danRer6.refGene.LENGTH	51
danRer6.xenoRefGene.LENGTH	52
dm1.geneSymbol.LENGTH	52
dm1.genscan.LENGTH	53
dm1.refGene.LENGTH	53
dm2.geneid.LENGTH	54
dm2.geneSymbol.LENGTH	54
dm2.genscan.LENGTH	55
dm2.nscanGene.LENGTH	55
dm2.refGene.LENGTH	56
dm3.geneSymbol.LENGTH	56
dm3.nscanPasaGene.LENGTH	57
dm3.refGene.LENGTH	57
downloadLengthFromUCSC	58
dp2.genscan.LENGTH	59
dp2.xenoRefGene.LENGTH	59
dp3.geneid.LENGTH	60
dp3.genscan.LENGTH	60
dp3.xenoRefGene.LENGTH	61
droAna1.geneid.LENGTH	61
droAna1.genscan.LENGTH	62
droAna1.xenoRefGene.LENGTH	62

droAna2.genscan.LENGTH	63
droAna2.xenoRefGene.LENGTH	63
droEre1.genscan.LENGTH	64
droEre1.xenoRefGene.LENGTH	64
droGri1.genscan.LENGTH	65
droGri1.xenoRefGene.LENGTH	65
droMoj1.geneid.LENGTH	66
droMoj1.genscan.LENGTH	66
droMoj1.xenoRefGene.LENGTH	67
droMoj2.genscan.LENGTH	67
droMoj2.xenoRefGene.LENGTH	68
droPer1.genscan.LENGTH	68
droPer1.xenoRefGene.LENGTH	69
droSec1.genscan.LENGTH	69
droSec1.xenoRefGene.LENGTH	70
droSim1.geneid.LENGTH	70
droSim1.genscan.LENGTH	71
droSim1.xenoRefGene.LENGTH	71
droVir1.geneid.LENGTH	72
droVir1.genscan.LENGTH	72
droVir1.xenoRefGene.LENGTH	73
droVir2.genscan.LENGTH	73
droVir2.xenoRefGene.LENGTH	74
droYak1.geneid.LENGTH	74
droYak1.genscan.LENGTH	75
droYak1.xenoRefGene.LENGTH	75
droYak2.genscan.LENGTH	76
droYak2.xenoRefGene.LENGTH	76
equCab1.geneid.LENGTH	77
equCab1.geneSymbol.LENGTH	77
equCab1.nscanGene.LENGTH	78
equCab1.refGene.LENGTH	78
equCab1.sgpGene.LENGTH	79
equCab2.ensGene.LENGTH	79
equCab2.geneSymbol.LENGTH	80
equCab2.nscanGene.LENGTH	80
equCab2.refGene.LENGTH	81
equCab2.xenoRefGene.LENGTH	81
felCat3.ensGene.LENGTH	82
felCat3.geneid.LENGTH	82
felCat3.geneSymbol.LENGTH	83
felCat3.genscan.LENGTH	83
felCat3.nscanGene.LENGTH	84
felCat3.refGene.LENGTH	84
felCat3.sgpGene.LENGTH	85
felCat3.xenoRefGene.LENGTH	85
fr1.ensGene.LENGTH	86
fr1.genscan.LENGTH	86
fr2.ensGene.LENGTH	87
galGal2.ensGene.LENGTH	87
galGal2.geneid.LENGTH	88
galGal2.geneSymbol.LENGTH	88

galGal2.genscan.LENGTH	89
galGal2.refGene.LENGTH	89
galGal2.sgpGene.LENGTH	90
galGal3.ensGene.LENGTH	90
galGal3.geneSymbol.LENGTH	91
galGal3.genscan.LENGTH	91
galGal3.nscanGene.LENGTH	92
galGal3.refGene.LENGTH	92
galGal3.xenoRefGene.LENGTH	93
gasAcu1.ensGene.LENGTH	93
gasAcu1.nscanGene.LENGTH	94
geneLenDatabase-pkg	94
hg16.acembly.LENGTH	95
hg16.ensGene.LENGTH	95
hg16.exoniphy.LENGTH	96
hg16.geneid.LENGTH	96
hg16.geneSymbol.LENGTH	97
hg16.genscan.LENGTH	97
hg16.knownGene.LENGTH	98
hg16.refGene.LENGTH	98
hg16.sgpGene.LENGTH	99
hg17.acembly.LENGTH	99
hg17.acescan.LENGTH	100
hg17.ccdsGene.LENGTH	100
hg17.ensGene.LENGTH	101
hg17.exoniphy.LENGTH	101
hg17.geneid.LENGTH	102
hg17.geneSymbol.LENGTH	102
hg17.genscan.LENGTH	103
hg17.knownGene.LENGTH	103
hg17.refGene.LENGTH	104
hg17.sgpGene.LENGTH	104
hg17.vegaGene.LENGTH	105
hg17.vegaPseudoGene.LENGTH	105
hg17.xenoRefGene.LENGTH	106
hg18.acembly.LENGTH	106
hg18.acescan.LENGTH	107
hg18.ccdsGene.LENGTH	107
hg18.ensGene.LENGTH	108
hg18.exoniphy.LENGTH	108
hg18.geneid.LENGTH	109
hg18.geneSymbol.LENGTH	109
hg18.genscan.LENGTH	110
hg18.knownGene.LENGTH	110
hg18.knownGeneOld3.LENGTH	111
hg18.refGene.LENGTH	111
hg18.sgpGene.LENGTH	112
hg18.sibGene.LENGTH	112
hg18.xenoRefGene.LENGTH	113
hg19.ccdsGene.LENGTH	113
hg19.ensGene.LENGTH	114
hg19.exoniphy.LENGTH	114

hg19.geneSymbol.LENGTH	115
hg19.knownGene.LENGTH	115
hg19.nscanGene.LENGTH	116
hg19.refGene.LENGTH	116
hg19.xenoRefGene.LENGTH	117
loxAfr3.xenoRefGene.LENGTH	117
mm7.ensGene.LENGTH	118
mm7.geneid.LENGTH	118
mm7.geneSymbol.LENGTH	119
mm7.genscan.LENGTH	119
mm7.knownGene.LENGTH	120
mm7.refGene.LENGTH	120
mm7.sgpGene.LENGTH	121
mm7.xenoRefGene.LENGTH	121
mm8.ccdsGene.LENGTH	122
mm8.ensGene.LENGTH	122
mm8.geneid.LENGTH	123
mm8.geneSymbol.LENGTH	123
mm8.genscan.LENGTH	124
mm8.knownGene.LENGTH	124
mm8.nscanGene.LENGTH	125
mm8.refGene.LENGTH	125
mm8.sgpGene.LENGTH	126
mm8.sibGene.LENGTH	126
mm8.xenoRefGene.LENGTH	127
mm9.acembly.LENGTH	127
mm9.ccdsGene.LENGTH	128
mm9.ensGene.LENGTH	128
mm9.exoniphy.LENGTH	129
mm9.geneid.LENGTH	129
mm9.geneSymbol.LENGTH	130
mm9.genscan.LENGTH	130
mm9.knownGene.LENGTH	131
mm9.nscanGene.LENGTH	131
mm9.refGene.LENGTH	132
mm9.sgpGene.LENGTH	132
mm9.xenoRefGene.LENGTH	133
monDom1.genscan.LENGTH	133
monDom4.ensGene.LENGTH	134
monDom4.geneSymbol.LENGTH	134
monDom4.genscan.LENGTH	135
monDom4.nscanGene.LENGTH	135
monDom4.refGene.LENGTH	136
monDom4.xenoRefGene.LENGTH	136
monDom5.ensGene.LENGTH	137
monDom5.geneSymbol.LENGTH	137
monDom5.genscan.LENGTH	138
monDom5.nscanGene.LENGTH	138
monDom5.refGene.LENGTH	139
monDom5.xenoRefGene.LENGTH	139
ornAna1.ensGene.LENGTH	140
ornAna1.geneSymbol.LENGTH	140

ornAna1.refGene.LENGTH	141
ornAna1.xenoRefGene.LENGTH	141
oryLat2.ensGene.LENGTH	142
oryLat2.geneSymbol.LENGTH	142
oryLat2.refGene.LENGTH	143
oryLat2.xenoRefGene.LENGTH	143
panTro1.ensGene.LENGTH	144
panTro1.geneid.LENGTH	144
panTro1.genscan.LENGTH	145
panTro1.xenoRefGene.LENGTH	145
panTro2.ensGene.LENGTH	146
panTro2.geneSymbol.LENGTH	146
panTro2.genscan.LENGTH	147
panTro2.nscanGene.LENGTH	147
panTro2.refGene.LENGTH	148
panTro2.xenoRefGene.LENGTH	148
petMar1.xenoRefGene.LENGTH	149
ponAbe2.ensGene.LENGTH	149
ponAbe2.geneSymbol.LENGTH	150
ponAbe2.genscan.LENGTH	150
ponAbe2.nscanGene.LENGTH	151
ponAbe2.refGene.LENGTH	151
ponAbe2.xenoRefGene.LENGTH	152
priPac1.xenoRefGene.LENGTH	152
rheMac2.ensGene.LENGTH	153
rheMac2.geneid.LENGTH	153
rheMac2.geneSymbol.LENGTH	154
rheMac2.nscanGene.LENGTH	154
rheMac2.refGene.LENGTH	155
rheMac2.sgpGene.LENGTH	155
rheMac2.xenoRefGene.LENGTH	156
rn3.ensGene.LENGTH	156
rn3.geneid.LENGTH	157
rn3.geneSymbol.LENGTH	157
rn3.genscan.LENGTH	158
rn3.knownGene.LENGTH	158
rn3.nscanGene.LENGTH	159
rn3.refGene.LENGTH	159
rn3.sgpGene.LENGTH	160
rn3.xenoRefGene.LENGTH	160
rn4.ensGene.LENGTH	161
rn4.geneid.LENGTH	161
rn4.geneSymbol.LENGTH	162
rn4.genscan.LENGTH	162
rn4.knownGene.LENGTH	163
rn4.nscanGene.LENGTH	163
rn4.refGene.LENGTH	164
rn4.sgpGene.LENGTH	164
rn4.xenoRefGene.LENGTH	165
sacCer1.ensGene.LENGTH	165
sacCer2.ensGene.LENGTH	166
strPur1.geneSymbol.LENGTH	166

strPur1.genscan.LENGTH	167
strPur1.refGene.LENGTH	167
strPur1.xenoRefGene.LENGTH	168
strPur2.geneSymbol.LENGTH	168
strPur2.genscan.LENGTH	169
strPur2.refGene.LENGTH	169
strPur2.xenoRefGene.LENGTH	170
supportedGeneIDs	170
supportedGenomes	171
taeGut1.ensGene.LENGTH	171
taeGut1.geneSymbol.LENGTH	172
taeGut1.genscan.LENGTH	172
taeGut1.nscanGene.LENGTH	173
taeGut1.refGene.LENGTH	173
taeGut1.xenoRefGene.LENGTH	174
tetNig1.ensGene.LENGTH	174
tetNig1.geneid.LENGTH	175
tetNig1.genscan.LENGTH	175
tetNig1.nscanGene.LENGTH	176
tetNig2.ensGene.LENGTH	176
unfactor	177
xenTro1.genscan.LENGTH	178
xenTro2.ensGene.LENGTH	178
xenTro2.geneSymbol.LENGTH	179
xenTro2.genscan.LENGTH	179
xenTro2.refGene.LENGTH	180

Index 181

anoCar1.ensGene.LENGTH

Transcript length data for the organism anoCar

Description

anoCar1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(anoCar1, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(anoCar1.ensGene.LENGTH)
head(anoCar1.ensGene.LENGTH)
```

`anoCar1.genscan.LENGTH`*Transcript length data for the organism anoCar*

Description

`anoCar1.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(anoCar1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(anoCar1.genscan.LENGTH)
head(anoCar1.genscan.LENGTH)
```

`anoCar1.xenoRefGene.LENGTH`*Transcript length data for the organism anoCar*

Description

`anoCar1.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(anoCar1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(anoCar1.xenoRefGene.LENGTH)
head(anoCar1.xenoRefGene.LENGTH)
```

```
anoGam1.ensGene.LENGTH
```

Transcript length data for the organism anoGam

Description

anoGam1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(anoGam1, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(anoGam1.ensGene.LENGTH)
head(anoGam1.ensGene.LENGTH)
```

```
anoGam1.geneid.LENGTH
```

Transcript length data for the organism anoGam

Description

anoGam1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(anoGam1, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(anoGam1.geneid.LENGTH)
head(anoGam1.geneid.LENGTH)
```

```
anoGam1.genscan.LENGTH
```

Transcript length data for the organism anoGam

Description

anoGam1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(anoGam1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(anoGam1.genscan.LENGTH)
head(anoGam1.genscan.LENGTH)
```

```
apiMel1.genscan.LENGTH
```

Transcript length data for the organism apiMel

Description

apiMel1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(apiMel1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(apiMel1.genscan.LENGTH)
head(apiMel1.genscan.LENGTH)
```

```
apiMel2.ensGene.LENGTH
```

Transcript length data for the organism apiMel

Description

apiMel2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(apiMel2, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(apiMel2.ensGene.LENGTH)
head(apiMel2.ensGene.LENGTH)
```

```
apiMel2.geneid.LENGTH
```

Transcript length data for the organism apiMel

Description

apiMel2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(apiMel2, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(apiMel2.geneid.LENGTH)
head(apiMel2.geneid.LENGTH)
```

```
apiMel2.genscan.LENGTH
```

Transcript length data for the organism apiMel

Description

apiMel2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(apiMel2, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(apiMel2.genscan.LENGTH)
head(apiMel2.genscan.LENGTH)
```

```
aplCal1.xenoRefGene.LENGTH
```

Transcript length data for the organism aplCal

Description

aplCal1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(aplCal1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(aplCal1.xenoRefGene.LENGTH)
head(aplCal1.xenoRefGene.LENGTH)
```

bosTau2.geneid.LENGTH *Transcript length data for the organism bosTau*

Description

bosTau2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(bosTau2.geneid.LENGTH)
head(bosTau2.geneid.LENGTH)
```

bosTau2.geneSymbol.LENGTH
Transcript length data for the organism bosTau

Description

bosTau2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(bosTau2.geneSymbol.LENGTH)
head(bosTau2.geneSymbol.LENGTH)
```

`bosTau2.genscan.LENGTH`*Transcript length data for the organism bosTau*

Description

`bosTau2.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, genscan)` on the date on which the package was last updated.

See Also[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau2.genscan.LENGTH)
head(bosTau2.genscan.LENGTH)
```

`bosTau2.refGene.LENGTH`*Transcript length data for the organism bosTau*

Description

`bosTau2.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, refGene)` on the date on which the package was last updated.

See Also[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau2.refGene.LENGTH)
head(bosTau2.refGene.LENGTH)
```

```
bosTau2.sgpGene.LENGTH
```

Transcript length data for the organism bosTau

Description

bosTau2.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, sgpGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(bosTau2.sgpGene.LENGTH)
head(bosTau2.sgpGene.LENGTH)
```

```
bosTau3.ensGene.LENGTH
```

Transcript length data for the organism bosTau

Description

bosTau3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(bosTau3.ensGene.LENGTH)
head(bosTau3.ensGene.LENGTH)
```

bosTau3.geneid.LENGTH *Transcript length data for the organism bosTau*

Description

bosTau3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(bosTau3.geneid.LENGTH)
head(bosTau3.geneid.LENGTH)
```

bosTau3.geneSymbol.LENGTH
Transcript length data for the organism bosTau

Description

bosTau3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(bosTau3.geneSymbol.LENGTH)
head(bosTau3.geneSymbol.LENGTH)
```

```
bosTau3.genscan.LENGTH
```

Transcript length data for the organism bosTau

Description

bosTau3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(bosTau3.genscan.LENGTH)
head(bosTau3.genscan.LENGTH)
```

```
bosTau3.refGene.LENGTH
```

Transcript length data for the organism bosTau

Description

bosTau3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(bosTau3.refGene.LENGTH)
head(bosTau3.refGene.LENGTH)
```

`bosTau3.sgpGene.LENGTH`*Transcript length data for the organism bosTau*

Description

`bosTau3.sgpGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `sgpGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, sgpGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(bosTau3.sgpGene.LENGTH)
head(bosTau3.sgpGene.LENGTH)
```

`bosTau4.ensGene.LENGTH`*Transcript length data for the organism bosTau*

Description

`bosTau4.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(bosTau4.ensGene.LENGTH)
head(bosTau4.ensGene.LENGTH)
```

```
bosTau4.geneSymbol.LENGTH
```

Transcript length data for the organism bosTau

Description

bosTau4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(bosTau4.geneSymbol.LENGTH)
head(bosTau4.geneSymbol.LENGTH)
```

```
bosTau4.genscan.LENGTH
```

Transcript length data for the organism bosTau

Description

bosTau4.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(bosTau4.genscan.LENGTH)
head(bosTau4.genscan.LENGTH)
```

```
bosTau4.nscanGene.LENGTH
```

Transcript length data for the organism bosTau

Description

bosTau4.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(bosTau4.nscanGene.LENGTH)
head(bosTau4.nscanGene.LENGTH)
```

```
bosTau4.refGene.LENGTH
```

Transcript length data for the organism bosTau

Description

bosTau4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(bosTau4.refGene.LENGTH)
head(bosTau4.refGene.LENGTH)
```

```
braFlo1.xenoRefGene.LENGTH
```

Transcript length data for the organism braFlo

Description

braFlo1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(braFlo1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(braFlo1.xenoRefGene.LENGTH)
head(braFlo1.xenoRefGene.LENGTH)
```

```
caeJap1.xenoRefGene.LENGTH
```

Transcript length data for the organism caeJap

Description

caeJap1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caeJap1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(caeJap1.xenoRefGene.LENGTH)
head(caeJap1.xenoRefGene.LENGTH)
```

```
caePb1.xenoRefGene.LENGTH
```

Transcript length data for the organism caePb

Description

caePb1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caePb1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(caePb1.xenoRefGene.LENGTH)
head(caePb1.xenoRefGene.LENGTH)
```

```
caePb2.xenoRefGene.LENGTH
```

Transcript length data for the organism caePb

Description

caePb2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caePb2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(caePb2.xenoRefGene.LENGTH)
head(caePb2.xenoRefGene.LENGTH)
```

```
caeRem2.xenoRefGene.LENGTH
```

Transcript length data for the organism caeRem

Description

caeRem2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caeRem2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(caeRem2.xenoRefGene.LENGTH)
head(caeRem2.xenoRefGene.LENGTH)
```

```
caeRem3.xenoRefGene.LENGTH
```

Transcript length data for the organism caeRem

Description

caeRem3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caeRem3, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(caeRem3.xenoRefGene.LENGTH)
head(caeRem3.xenoRefGene.LENGTH)
```

`calJac1.genscan.LENGTH`*Transcript length data for the organism calJac*

Description

calJac1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(calJac1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(calJac1.genscan.LENGTH)
head(calJac1.genscan.LENGTH)
```

`calJac1.nscanGene.LENGTH`*Transcript length data for the organism calJac*

Description

calJac1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(calJac1, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(calJac1.nscanGene.LENGTH)
head(calJac1.nscanGene.LENGTH)
```

```
calJac1.xenoRefGene.LENGTH
```

Transcript length data for the organism calJac

Description

calJac1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(calJac1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(calJac1.xenoRefGene.LENGTH)
head(calJac1.xenoRefGene.LENGTH)
```

```
canFam1.ensGene.LENGTH
```

Transcript length data for the organism canFam

Description

canFam1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(canFam1.ensGene.LENGTH)
head(canFam1.ensGene.LENGTH)
```

`canFam1.geneSymbol.LENGTH`*Transcript length data for the organism canFam*

Description

canFam1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(canFam1.geneSymbol.LENGTH)
head(canFam1.geneSymbol.LENGTH)
```

`canFam1.genscan.LENGTH`*Transcript length data for the organism canFam*

Description

canFam1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(canFam1.genscan.LENGTH)
head(canFam1.genscan.LENGTH)
```

canFam1.nscanGene.LENGTH

Transcript length data for the organism canFam

Description

canFam1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(canFam1.nscanGene.LENGTH)
head(canFam1.nscanGene.LENGTH)
```

canFam1.refGene.LENGTH

Transcript length data for the organism canFam

Description

canFam1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(canFam1.refGene.LENGTH)
head(canFam1.refGene.LENGTH)
```

```
canFam1.xenoRefGene.LENGTH
```

Transcript length data for the organism canFam

Description

canFam1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(canFam1.xenoRefGene.LENGTH)
head(canFam1.xenoRefGene.LENGTH)
```

```
canFam2.ensGene.LENGTH
```

Transcript length data for the organism canFam

Description

canFam2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(canFam2.ensGene.LENGTH)
head(canFam2.ensGene.LENGTH)
```

```
canFam2.geneSymbol.LENGTH
```

Transcript length data for the organism canFam

Description

canFam2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(canFam2.geneSymbol.LENGTH)
head(canFam2.geneSymbol.LENGTH)
```

```
canFam2.genscan.LENGTH
```

Transcript length data for the organism canFam

Description

canFam2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(canFam2.genscan.LENGTH)
head(canFam2.genscan.LENGTH)
```

```
canFam2.nscanGene.LENGTH
```

Transcript length data for the organism canFam

Description

canFam2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(canFam2.nscanGene.LENGTH)
head(canFam2.nscanGene.LENGTH)
```

```
canFam2.refGene.LENGTH
```

Transcript length data for the organism canFam

Description

canFam2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(canFam2.refGene.LENGTH)
head(canFam2.refGene.LENGTH)
```

```
canFam2.xenoRefGene.LENGTH
```

Transcript length data for the organism canFam

Description

canFam2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(canFam2.xenoRefGene.LENGTH)
head(canFam2.xenoRefGene.LENGTH)
```

```
cavPor3.ensGene.LENGTH
```

Transcript length data for the organism cavPor

Description

cavPor3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(cavPor3.ensGene.LENGTH)
head(cavPor3.ensGene.LENGTH)
```

```
cavPor3.genscan.LENGTH
```

Transcript length data for the organism cavPor

Description

cavPor3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(cavPor3.genscan.LENGTH)
head(cavPor3.genscan.LENGTH)
```

```
cavPor3.nscanGene.LENGTH
```

Transcript length data for the organism cavPor

Description

cavPor3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(cavPor3.nscanGene.LENGTH)
head(cavPor3.nscanGene.LENGTH)
```

```
cavPor3.xenoRefGene.LENGTH
```

Transcript length data for the organism cavPor

Description

cavPor3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(cavPor3.xenoRefGene.LENGTH)
head(cavPor3.xenoRefGene.LENGTH)
```

```
cb1.xenoRefGene.LENGTH
```

Transcript length data for the organism cb

Description

cb1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(cb1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(cb1.xenoRefGene.LENGTH)
head(cb1.xenoRefGene.LENGTH)
```

`cb3.xenoRefGene.LENGTH`*Transcript length data for the organism cb*

Description

`cb3.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(cb3, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(cb3.xenoRefGene.LENGTH)
head(cb3.xenoRefGene.LENGTH)
```

`ce2.geneid.LENGTH`*Transcript length data for the organism ce*

Description

`ce2.geneid.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneid` table.

The data file was made by calling `downloadLengthFromUCSC(ce2, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ce2.geneid.LENGTH)
head(ce2.geneid.LENGTH)
```

ce2.geneSymbol1.LENGTH *Transcript length data for the organism ce*

Description

ce2.geneSymbol1.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ce2, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ce2.geneSymbol1.LENGTH)
head(ce2.geneSymbol1.LENGTH)
```

ce2.refGene.LENGTH *Transcript length data for the organism ce*

Description

ce2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ce2, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ce2.refGene.LENGTH)
head(ce2.refGene.LENGTH)
```

ce4.geneSymbol.LENGTH *Transcript length data for the organism ce*

Description

ce4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ce4, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ce4.geneSymbol.LENGTH)
head(ce4.geneSymbol.LENGTH)
```

ce4.refGene.LENGTH *Transcript length data for the organism ce*

Description

ce4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ce4, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ce4.refGene.LENGTH)
head(ce4.refGene.LENGTH)
```

```
ce4.xenoRefGene.LENGTH
```

Transcript length data for the organism ce

Description

ce4.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ce4, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ce4.xenoRefGene.LENGTH)
head(ce4.xenoRefGene.LENGTH)
```

```
ce6.ensGene.LENGTH
```

Transcript length data for the organism ce

Description

ce6.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(ce6, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ce6.ensGene.LENGTH)
head(ce6.ensGene.LENGTH)
```

ce6.geneSymbol.LENGTH *Transcript length data for the organism ce*

Description

ce6.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ce6, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ce6.geneSymbol.LENGTH)
head(ce6.geneSymbol.LENGTH)
```

ce6.refGene.LENGTH *Transcript length data for the organism ce*

Description

ce6.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ce6, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ce6.refGene.LENGTH)
head(ce6.refGene.LENGTH)
```

ce6.xenoRefGene.LENGTH

Transcript length data for the organism ce

Description

ce6.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ce6, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ce6.xenoRefGene.LENGTH)
head(ce6.xenoRefGene.LENGTH)
```

ci1.geneSymbol.LENGTH *Transcript length data for the organism ci*

Description

ci1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ci1, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ci1.geneSymbol.LENGTH)
head(ci1.geneSymbol.LENGTH)
```

ci1.refGene.LENGTH *Transcript length data for the organism ci*

Description

ci1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ci1, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ci1.refGene.LENGTH)
head(ci1.refGene.LENGTH)
```

ci1.xenoRefGene.LENGTH *Transcript length data for the organism ci*

Description

ci1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ci1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ci1.xenoRefGene.LENGTH)
head(ci1.xenoRefGene.LENGTH)
```

ci2.ensGene.LENGTH *Transcript length data for the organism ci*

Description

ci2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(ci2, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ci2.ensGene.LENGTH)
head(ci2.ensGene.LENGTH)
```

ci2.geneSymbol.LENGTH *Transcript length data for the organism ci*

Description

ci2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ci2, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ci2.geneSymbol.LENGTH)
head(ci2.geneSymbol.LENGTH)
```

ci2.refGene.LENGTH *Transcript length data for the organism ci*

Description

ci2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ci2, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ci2.refGene.LENGTH)
head(ci2.refGene.LENGTH)
```

ci2.xenoRefGene.LENGTH *Transcript length data for the organism ci*

Description

ci2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ci2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ci2.xenoRefGene.LENGTH)
head(ci2.xenoRefGene.LENGTH)
```

danRer3.ensGene.LENGTH

Transcript length data for the organism danRer

Description

danRer3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer3, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer3.ensGene.LENGTH)
head(danRer3.ensGene.LENGTH)
```

danRer3.geneSymbol.LENGTH

Transcript length data for the organism danRer

Description

danRer3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(danRer3, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer3.geneSymbol.LENGTH)
head(danRer3.geneSymbol.LENGTH)
```

```
danRer3.refGene.LENGTH
```

Transcript length data for the organism danRer

Description

danRer3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer3, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer3.refGene.LENGTH)
head(danRer3.refGene.LENGTH)
```

```
danRer4.ensGene.LENGTH
```

Transcript length data for the organism danRer

Description

danRer4.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer4.ensGene.LENGTH)
head(danRer4.ensGene.LENGTH)
```

```
danRer4.geneSymbol.LENGTH
```

Transcript length data for the organism danRer

Description

danRer4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer4.geneSymbol.LENGTH)
head(danRer4.geneSymbol.LENGTH)
```

```
danRer4.genscan.LENGTH
```

Transcript length data for the organism danRer

Description

danRer4.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer4.genscan.LENGTH)
head(danRer4.genscan.LENGTH)
```

`danRer4.nscanGene.LENGTH`*Transcript length data for the organism danRer*

Description

`danRer4.nscanGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `nscanGene` table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, nscanGene)` on the date on which the package was last updated.

See Also[downloadLengthFromUCSC](#)**Examples**

```
data(danRer4.nscanGene.LENGTH)
head(danRer4.nscanGene.LENGTH)
```

`danRer4.refGene.LENGTH`*Transcript length data for the organism danRer*

Description

`danRer4.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, refGene)` on the date on which the package was last updated.

See Also[downloadLengthFromUCSC](#)**Examples**

```
data(danRer4.refGene.LENGTH)
head(danRer4.refGene.LENGTH)
```

```
danRer5.ensGene.LENGTH
```

Transcript length data for the organism danRer

Description

danRer5.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer5.ensGene.LENGTH)
head(danRer5.ensGene.LENGTH)
```

```
danRer5.geneSymbol.LENGTH
```

Transcript length data for the organism danRer

Description

danRer5.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer5.geneSymbol.LENGTH)
head(danRer5.geneSymbol.LENGTH)
```

```
danRer5.refGene.LENGTH
```

Transcript length data for the organism danRer

Description

danRer5.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer5.refGene.LENGTH)
head(danRer5.refGene.LENGTH)
```

```
danRer5.vegaGene.LENGTH
```

Transcript length data for the organism danRer

Description

danRer5.vegaGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, vegaGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer5.vegaGene.LENGTH)
head(danRer5.vegaGene.LENGTH)
```

```
danRer5.vegaPseudoGene.LENGTH
```

Transcript length data for the organism danRer

Description

danRer5.vegaPseudoGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaPseudoGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, vegaPseudoGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer5.vegaPseudoGene.LENGTH)
head(danRer5.vegaPseudoGene.LENGTH)
```

```
danRer6.ensGene.LENGTH
```

Transcript length data for the organism danRer

Description

danRer6.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer6.ensGene.LENGTH)
head(danRer6.ensGene.LENGTH)
```

```
danRer6.geneSymbol.LENGTH
```

Transcript length data for the organism danRer

Description

danRer6.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer6.geneSymbol.LENGTH)
head(danRer6.geneSymbol.LENGTH)
```

```
danRer6.refGene.LENGTH
```

Transcript length data for the organism danRer

Description

danRer6.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer6.refGene.LENGTH)
head(danRer6.refGene.LENGTH)
```

```
danRer6.xenoRefGene.LENGTH
```

Transcript length data for the organism danRer

Description

danRer6.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(danRer6.xenoRefGene.LENGTH)
head(danRer6.xenoRefGene.LENGTH)
```

```
dm1.geneSymbol.LENGTH
```

Transcript length data for the organism dm

Description

dm1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(dm1, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dm1.geneSymbol.LENGTH)
head(dm1.geneSymbol.LENGTH)
```

dm1.genscan.LENGTH *Transcript length data for the organism dm*

Description

dm1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dm1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dm1.genscan.LENGTH)
head(dm1.genscan.LENGTH)
```

dm1.refGene.LENGTH *Transcript length data for the organism dm*

Description

dm1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(dm1, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dm1.refGene.LENGTH)
head(dm1.refGene.LENGTH)
```

dm2.geneid.LENGTH *Transcript length data for the organism dm*

Description

dm2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(dm2, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dm2.geneid.LENGTH)
head(dm2.geneid.LENGTH)
```

dm2.geneSymbol.LENGTH *Transcript length data for the organism dm*

Description

dm2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(dm2, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dm2.geneSymbol.LENGTH)
head(dm2.geneSymbol.LENGTH)
```

dm2.genscan.LENGTH *Transcript length data for the organism dm*

Description

dm2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dm2, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dm2.genscan.LENGTH)
head(dm2.genscan.LENGTH)
```

dm2.nscanGene.LENGTH *Transcript length data for the organism dm*

Description

dm2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(dm2, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dm2.nscanGene.LENGTH)
head(dm2.nscanGene.LENGTH)
```

dm2.refGene.LENGTH *Transcript length data for the organism dm*

Description

dm2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(dm2, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dm2.refGene.LENGTH)
head(dm2.refGene.LENGTH)
```

dm3.geneSymbol.LENGTH *Transcript length data for the organism dm*

Description

dm3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(dm3, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dm3.geneSymbol.LENGTH)
head(dm3.geneSymbol.LENGTH)
```

`dm3.nscanPasaGene.LENGTH`*Transcript length data for the organism dm*

Description

dm3.nscanPasaGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanPasaGene table.

The data file was made by calling `downloadLengthFromUCSC(dm3, nscanPasaGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dm3.nscanPasaGene.LENGTH)
head(dm3.nscanPasaGene.LENGTH)
```

`dm3.refGene.LENGTH`*Transcript length data for the organism dm*

Description

dm3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(dm3, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dm3.refGene.LENGTH)
head(dm3.refGene.LENGTH)
```

`downloadLengthFromUCSC`*Download Transcript Length Data*

Description

Attempts to download the length of each transcript for the genome and gene ID specified from the UCSC genome browser.

Usage

```
downloadLengthFromUCSC(genome, id)
```

Arguments

<code>genome</code>	A string identifying the genome that genes refer to. For a list of supported organisms see supportedGenomes .
<code>id</code>	A string identifying the gene identifier used by genes. For a list of supported gene identifiers see supportedGeneIDs .

Details

For each transcript, the UCSC genome browser is used to obtain the exon boundaries. The length of each transcript is then taken to be the sum of the lengths of all its exons. Each transcript is then associated with a gene.

The UCSC does not contain length information for all combinations of genome and gene ID listed by [supportedGeneIDs](#) and [supportedGenomes](#). If `downloadLengthFromUCSC` fails because your gene ID format is not supported for the genome you specified, a list of possible ID formats for the specified genome will be listed.

Value

A data.frame containing with three columns, the gene name, transcript identifier and the length of the transcript. Each row represents one transcript.

Note

For some genome / gene ID combinations, no gene ID will be provided by UCSC. In this case, the gene name column is set to NA. However, the transcript ID column will always be populated.

Author(s)

Matthew D. Young <myoung@wehi.edu.au>

See Also

[supportedGenomes](#), [supportedGeneIDs](#)

Examples

```
## Not run:
flat_length <- downloadLengthFromUCSC('hg19', 'ensGene')

## End(Not run)
```

dp2.genscan.LENGTH *Transcript length data for the organism dp*

Description

dp2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dp2, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dp2.genscan.LENGTH)
head(dp2.genscan.LENGTH)
```

dp2.xenoRefGene.LENGTH *Transcript length data for the organism dp*

Description

dp2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(dp2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dp2.xenoRefGene.LENGTH)
head(dp2.xenoRefGene.LENGTH)
```

dp3.geneid.LENGTH *Transcript length data for the organism dp*

Description

dp3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(dp3, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dp3.geneid.LENGTH)
head(dp3.geneid.LENGTH)
```

dp3.genscan.LENGTH *Transcript length data for the organism dp*

Description

dp3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dp3, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dp3.genscan.LENGTH)
head(dp3.genscan.LENGTH)
```

```
dp3.xenoRefGene.LENGTH
```

Transcript length data for the organism dp

Description

dp3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(dp3, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(dp3.xenoRefGene.LENGTH)
head(dp3.xenoRefGene.LENGTH)
```

```
droAna1.geneid.LENGTH
```

Transcript length data for the organism droAna

Description

droAna1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droAna1, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droAna1.geneid.LENGTH)
head(droAna1.geneid.LENGTH)
```

droAna1.genscan.LENGTH

Transcript length data for the organism droAna

Description

droAna1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droAna1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droAna1.genscan.LENGTH)
head(droAna1.genscan.LENGTH)
```

droAna1.xenoRefGene.LENGTH

Transcript length data for the organism droAna

Description

droAna1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droAna1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droAna1.xenoRefGene.LENGTH)
head(droAna1.xenoRefGene.LENGTH)
```

`droAna2.genscan.LENGTH`*Transcript length data for the organism droAna*

Description

droAna2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droAna2, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droAna2.genscan.LENGTH)
head(droAna2.genscan.LENGTH)
```

`droAna2.xenoRefGene.LENGTH`*Transcript length data for the organism droAna*

Description

droAna2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droAna2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droAna2.xenoRefGene.LENGTH)
head(droAna2.xenoRefGene.LENGTH)
```

```
droEre1.genscan.LENGTH
```

Transcript length data for the organism droEre

Description

droEre1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droEre1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droEre1.genscan.LENGTH)
head(droEre1.genscan.LENGTH)
```

```
droEre1.xenoRefGene.LENGTH
```

Transcript length data for the organism droEre

Description

droEre1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droEre1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droEre1.xenoRefGene.LENGTH)
head(droEre1.xenoRefGene.LENGTH)
```

`droGri1.genscan.LENGTH`*Transcript length data for the organism droGri*

Description

droGri1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droGri1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droGri1.genscan.LENGTH)
head(droGri1.genscan.LENGTH)
```

`droGri1.xenoRefGene.LENGTH`*Transcript length data for the organism droGri*

Description

droGri1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droGri1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droGri1.xenoRefGene.LENGTH)
head(droGri1.xenoRefGene.LENGTH)
```

droMoj1.geneid.LENGTH *Transcript length data for the organism droMoj*

Description

droMoj1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droMoj1, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droMoj1.geneid.LENGTH)
head(droMoj1.geneid.LENGTH)
```

droMoj1.genscan.LENGTH
Transcript length data for the organism droMoj

Description

droMoj1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droMoj1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droMoj1.genscan.LENGTH)
head(droMoj1.genscan.LENGTH)
```

```
droMoj1.xenoRefGene.LENGTH
```

Transcript length data for the organism droMoj

Description

droMoj1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droMoj1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droMoj1.xenoRefGene.LENGTH)
head(droMoj1.xenoRefGene.LENGTH)
```

```
droMoj2.genscan.LENGTH
```

Transcript length data for the organism droMoj

Description

droMoj2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droMoj2, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droMoj2.genscan.LENGTH)
head(droMoj2.genscan.LENGTH)
```

```
droMoj2.xenoRefGene.LENGTH
```

Transcript length data for the organism droMoj

Description

droMoj2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droMoj2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droMoj2.xenoRefGene.LENGTH)
head(droMoj2.xenoRefGene.LENGTH)
```

```
droPer1.genscan.LENGTH
```

Transcript length data for the organism droPer

Description

droPer1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droPer1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droPer1.genscan.LENGTH)
head(droPer1.genscan.LENGTH)
```

```
droPer1.xenoRefGene.LENGTH
```

Transcript length data for the organism droPer

Description

droPer1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droPer1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droPer1.xenoRefGene.LENGTH)
head(droPer1.xenoRefGene.LENGTH)
```

```
droSec1.genscan.LENGTH
```

Transcript length data for the organism droSec

Description

droSec1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droSec1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droSec1.genscan.LENGTH)
head(droSec1.genscan.LENGTH)
```

```
droSec1.xenoRefGene.LENGTH
```

Transcript length data for the organism droSec

Description

droSec1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droSec1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droSec1.xenoRefGene.LENGTH)
head(droSec1.xenoRefGene.LENGTH)
```

```
droSim1.geneid.LENGTH
```

Transcript length data for the organism droSim

Description

droSim1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droSim1, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droSim1.geneid.LENGTH)
head(droSim1.geneid.LENGTH)
```

```
droSim1.genscan.LENGTH
```

Transcript length data for the organism droSim

Description

droSim1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droSim1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droSim1.genscan.LENGTH)
head(droSim1.genscan.LENGTH)
```

```
droSim1.xenoRefGene.LENGTH
```

Transcript length data for the organism droSim

Description

droSim1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droSim1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droSim1.xenoRefGene.LENGTH)
head(droSim1.xenoRefGene.LENGTH)
```

droVir1.geneid.LENGTH *Transcript length data for the organism droVir*

Description

droVir1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droVir1, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droVir1.geneid.LENGTH)
head(droVir1.geneid.LENGTH)
```

droVir1.genscan.LENGTH
Transcript length data for the organism droVir

Description

droVir1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droVir1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droVir1.genscan.LENGTH)
head(droVir1.genscan.LENGTH)
```

```
droVir1.xenoRefGene.LENGTH
```

Transcript length data for the organism droVir

Description

droVir1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droVir1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droVir1.xenoRefGene.LENGTH)
head(droVir1.xenoRefGene.LENGTH)
```

```
droVir2.genscan.LENGTH
```

Transcript length data for the organism droVir

Description

droVir2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droVir2, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droVir2.genscan.LENGTH)
head(droVir2.genscan.LENGTH)
```

```
droVir2.xenoRefGene.LENGTH
```

Transcript length data for the organism droVir

Description

droVir2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droVir2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droVir2.xenoRefGene.LENGTH)
head(droVir2.xenoRefGene.LENGTH)
```

```
droYak1.geneid.LENGTH
```

Transcript length data for the organism droYak

Description

droYak1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droYak1, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droYak1.geneid.LENGTH)
head(droYak1.geneid.LENGTH)
```

```
droYak1.genscan.LENGTH
```

Transcript length data for the organism droYak

Description

droYak1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droYak1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droYak1.genscan.LENGTH)
head(droYak1.genscan.LENGTH)
```

```
droYak1.xenoRefGene.LENGTH
```

Transcript length data for the organism droYak

Description

droYak1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droYak1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droYak1.xenoRefGene.LENGTH)
head(droYak1.xenoRefGene.LENGTH)
```

```
droYak2.genscan.LENGTH
```

Transcript length data for the organism droYak

Description

droYak2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droYak2, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droYak2.genscan.LENGTH)
head(droYak2.genscan.LENGTH)
```

```
droYak2.xenoRefGene.LENGTH
```

Transcript length data for the organism droYak

Description

droYak2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droYak2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(droYak2.xenoRefGene.LENGTH)
head(droYak2.xenoRefGene.LENGTH)
```

equCab1.geneid.LENGTH *Transcript length data for the organism equCab*

Description

equCab1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(equCab1.geneid.LENGTH)
head(equCab1.geneid.LENGTH)
```

equCab1.geneSymbol.LENGTH
Transcript length data for the organism equCab

Description

equCab1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(equCab1.geneSymbol.LENGTH)
head(equCab1.geneSymbol.LENGTH)
```

equCab1.nscanGene.LENGTH

Transcript length data for the organism equCab

Description

equCab1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(equCab1.nscanGene.LENGTH)
head(equCab1.nscanGene.LENGTH)
```

equCab1.refGene.LENGTH

Transcript length data for the organism equCab

Description

equCab1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(equCab1.refGene.LENGTH)
head(equCab1.refGene.LENGTH)
```

```
equCab1 . sgpGene . LENGTH
```

Transcript length data for the organism equCab

Description

equCab1.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, sgpGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(equCab1 . sgpGene . LENGTH)
head(equCab1 . sgpGene . LENGTH)
```

```
equCab2 . ensGene . LENGTH
```

Transcript length data for the organism equCab

Description

equCab2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(equCab2 . ensGene . LENGTH)
head(equCab2 . ensGene . LENGTH)
```

```
equCab2.geneSymbol.LENGTH
```

Transcript length data for the organism equCab

Description

equCab2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(equCab2.geneSymbol.LENGTH)
head(equCab2.geneSymbol.LENGTH)
```

```
equCab2.nscanGene.LENGTH
```

Transcript length data for the organism equCab

Description

equCab2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(equCab2.nscanGene.LENGTH)
head(equCab2.nscanGene.LENGTH)
```

```
equCab2.refGene.LENGTH
```

Transcript length data for the organism equCab

Description

equCab2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(equCab2.refGene.LENGTH)
head(equCab2.refGene.LENGTH)
```

```
equCab2.xenoRefGene.LENGTH
```

Transcript length data for the organism equCab

Description

equCab2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(equCab2.xenoRefGene.LENGTH)
head(equCab2.xenoRefGene.LENGTH)
```

```
felCat3.ensGene.LENGTH
```

Transcript length data for the organism felCat

Description

felCat3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(felCat3.ensGene.LENGTH)
head(felCat3.ensGene.LENGTH)
```

```
felCat3.geneid.LENGTH
```

Transcript length data for the organism felCat

Description

felCat3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(felCat3.geneid.LENGTH)
head(felCat3.geneid.LENGTH)
```

```
felCat3.geneSymbol.LENGTH
```

Transcript length data for the organism felCat

Description

felCat3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(felCat3.geneSymbol.LENGTH)
head(felCat3.geneSymbol.LENGTH)
```

```
felCat3.genscan.LENGTH
```

Transcript length data for the organism felCat

Description

felCat3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(felCat3.genscan.LENGTH)
head(felCat3.genscan.LENGTH)
```

```
felCat3.nscanGene.LENGTH
```

Transcript length data for the organism felCat

Description

felCat3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(felCat3.nscanGene.LENGTH)
head(felCat3.nscanGene.LENGTH)
```

```
felCat3.refGene.LENGTH
```

Transcript length data for the organism felCat

Description

felCat3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(felCat3.refGene.LENGTH)
head(felCat3.refGene.LENGTH)
```

```
felCat3.sgpGene.LENGTH
```

Transcript length data for the organism felCat

Description

felCat3.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, sgpGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(felCat3.sgpGene.LENGTH)
head(felCat3.sgpGene.LENGTH)
```

```
felCat3.xenoRefGene.LENGTH
```

Transcript length data for the organism felCat

Description

felCat3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(felCat3.xenoRefGene.LENGTH)
head(felCat3.xenoRefGene.LENGTH)
```

fr1.ensGene.LENGTH *Transcript length data for the organism fr*

Description

fr1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(fr1, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(fr1.ensGene.LENGTH)
head(fr1.ensGene.LENGTH)
```

fr1.genscan.LENGTH *Transcript length data for the organism fr*

Description

fr1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(fr1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(fr1.genscan.LENGTH)
head(fr1.genscan.LENGTH)
```

fr2.ensGene.LENGTH *Transcript length data for the organism fr*

Description

fr2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(fr2, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(fr2.ensGene.LENGTH)
head(fr2.ensGene.LENGTH)
```

galGal2.ensGene.LENGTH
Transcript length data for the organism galGal

Description

galGal2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(galGal2.ensGene.LENGTH)
head(galGal2.ensGene.LENGTH)
```

galGal2.geneid.LENGTH *Transcript length data for the organism galGal*

Description

galGal2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(galGal2.geneid.LENGTH)
head(galGal2.geneid.LENGTH)
```

galGal2.geneSymbol.LENGTH
Transcript length data for the organism galGal

Description

galGal2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(galGal2.geneSymbol.LENGTH)
head(galGal2.geneSymbol.LENGTH)
```

```
galGal2.genscan.LENGTH
```

Transcript length data for the organism galGal

Description

galGal2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(galGal2.genscan.LENGTH)
head(galGal2.genscan.LENGTH)
```

```
galGal2.refGene.LENGTH
```

Transcript length data for the organism galGal

Description

galGal2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(galGal2.refGene.LENGTH)
head(galGal2.refGene.LENGTH)
```

```
galGal2.sgpGene.LENGTH
```

Transcript length data for the organism galGal

Description

galGal2.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, sgpGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(galGal2.sgpGene.LENGTH)
head(galGal2.sgpGene.LENGTH)
```

```
galGal3.ensGene.LENGTH
```

Transcript length data for the organism galGal

Description

galGal3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(galGal3.ensGene.LENGTH)
head(galGal3.ensGene.LENGTH)
```

```
galGal3.geneSymbol.LENGTH
```

Transcript length data for the organism galGal

Description

galGal3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(galGal3.geneSymbol.LENGTH)
head(galGal3.geneSymbol.LENGTH)
```

```
galGal3.genscan.LENGTH
```

Transcript length data for the organism galGal

Description

galGal3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(galGal3.genscan.LENGTH)
head(galGal3.genscan.LENGTH)
```

```
galGal3.nscanGene.LENGTH
```

Transcript length data for the organism galGal

Description

galGal3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(galGal3.nscanGene.LENGTH)
head(galGal3.nscanGene.LENGTH)
```

```
galGal3.refGene.LENGTH
```

Transcript length data for the organism galGal

Description

galGal3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(galGal3.refGene.LENGTH)
head(galGal3.refGene.LENGTH)
```

```
galGal3.xenoRefGene.LENGTH
```

Transcript length data for the organism galGal

Description

galGal3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(galGal3.xenoRefGene.LENGTH)
head(galGal3.xenoRefGene.LENGTH)
```

```
gasAcu1.ensGene.LENGTH
```

Transcript length data for the organism gasAcu

Description

gasAcu1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(gasAcu1, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(gasAcu1.ensGene.LENGTH)
head(gasAcu1.ensGene.LENGTH)
```

gasAcu1.nscanGene.LENGTH

Transcript length data for the organism gasAcu

Description

gasAcu1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(gasAcu1, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(gasAcu1.nscanGene.LENGTH)
head(gasAcu1.nscanGene.LENGTH)
```

geneLenDatabase-pkg *geneLenDatabase:*

Description

Lengths of mRNA transcripts for a number of genomes

Details

Length of mRNA transcripts for a number of genomes and gene ID formats, largely based on UCSC table browser. Data objects are provided as individual pieces of information to be retrieved and loaded. A variety of different gene identifiers and genomes is supported to ensure wide applicability.

Author(s)

Maintainer: Federico Marini <marinif@uni-mainz.de> ([ORCID](#)) [contributor]

Authors:

- Matthew Young <my4@sanger.ac.uk>
- Nadia Davidson <nadia.davidson@mcri.edu.au>

See Also

Useful links:

- <https://github.com/federicomarini/geneLenDataBase>
- Report bugs at <https://github.com/federicomarini/geneLenDataBase/issues>

hg16.acembly.LENGTH *Transcript length data for the organism hg*

Description

hg16.acembly.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acembly table.

The data file was made by calling `downloadLengthFromUCSC(hg16, acembly)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg16.acembly.LENGTH)
head(hg16.acembly.LENGTH)
```

hg16.ensGene.LENGTH *Transcript length data for the organism hg*

Description

hg16.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg16.ensGene.LENGTH)
head(hg16.ensGene.LENGTH)
```

hg16.exoniphy.LENGTH *Transcript length data for the organism hg*

Description

hg16.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg16, exoniphy)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg16.exoniphy.LENGTH)
head(hg16.exoniphy.LENGTH)
```

hg16.geneid.LENGTH *Transcript length data for the organism hg*

Description

hg16.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(hg16, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg16.geneid.LENGTH)
head(hg16.geneid.LENGTH)
```

```
hg16.geneSymbol.LENGTH
```

Transcript length data for the organism hg

Description

hg16.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg16, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg16.geneSymbol.LENGTH)
head(hg16.geneSymbol.LENGTH)
```

```
hg16.genscan.LENGTH
```

Transcript length data for the organism hg

Description

hg16.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(hg16, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg16.genscan.LENGTH)
head(hg16.genscan.LENGTH)
```

hg16.knownGene.LENGTH *Transcript length data for the organism hg*

Description

hg16.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, knownGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg16.knownGene.LENGTH)
head(hg16.knownGene.LENGTH)
```

hg16.refGene.LENGTH *Transcript length data for the organism hg*

Description

hg16.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg16.refGene.LENGTH)
head(hg16.refGene.LENGTH)
```

hg16.sgpGene.LENGTH *Transcript length data for the organism hg*

Description

hg16.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, sgpGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg16.sgpGene.LENGTH)
head(hg16.sgpGene.LENGTH)
```

hg17.acembly.LENGTH *Transcript length data for the organism hg*

Description

hg17.acembly.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acembly table.

The data file was made by calling `downloadLengthFromUCSC(hg17, acembly)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg17.acembly.LENGTH)
head(hg17.acembly.LENGTH)
```

hg17.acescan.LENGTH *Transcript length data for the organism hg*

Description

hg17.acescan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acescan table.

The data file was made by calling `downloadLengthFromUCSC(hg17, acescan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg17.acescan.LENGTH)
head(hg17.acescan.LENGTH)
```

hg17.ccdsGene.LENGTH *Transcript length data for the organism hg*

Description

hg17.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, ccdsGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg17.ccdsGene.LENGTH)
head(hg17.ccdsGene.LENGTH)
```

hg17.ensGene.LENGTH *Transcript length data for the organism hg*

Description

hg17.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg17.ensGene.LENGTH)
head(hg17.ensGene.LENGTH)
```

hg17.exoniphy.LENGTH *Transcript length data for the organism hg*

Description

hg17.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg17, exoniphy)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg17.exoniphy.LENGTH)
head(hg17.exoniphy.LENGTH)
```

hg17.geneid.LENGTH *Transcript length data for the organism hg*

Description

hg17.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(hg17, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg17.geneid.LENGTH)
head(hg17.geneid.LENGTH)
```

hg17.geneSymbol.LENGTH *Transcript length data for the organism hg*

Description

hg17.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg17, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg17.geneSymbol.LENGTH)
head(hg17.geneSymbol.LENGTH)
```

hg17.genscan.LENGTH *Transcript length data for the organism hg*

Description

hg17.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(hg17, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg17.genscan.LENGTH)
head(hg17.genscan.LENGTH)
```

hg17.knownGene.LENGTH *Transcript length data for the organism hg*

Description

hg17.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, knownGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg17.knownGene.LENGTH)
head(hg17.knownGene.LENGTH)
```

hg17.refGene.LENGTH *Transcript length data for the organism hg*

Description

hg17.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg17.refGene.LENGTH)
head(hg17.refGene.LENGTH)
```

hg17.sgpGene.LENGTH *Transcript length data for the organism hg*

Description

hg17.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, sgpGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg17.sgpGene.LENGTH)
head(hg17.sgpGene.LENGTH)
```

hg17.vegaGene.LENGTH *Transcript length data for the organism hg*

Description

hg17.vegaGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, vegaGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg17.vegaGene.LENGTH)
head(hg17.vegaGene.LENGTH)
```

hg17.vegaPseudoGene.LENGTH
Transcript length data for the organism hg

Description

hg17.vegaPseudoGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaPseudoGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, vegaPseudoGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg17.vegaPseudoGene.LENGTH)
head(hg17.vegaPseudoGene.LENGTH)
```

hg17.xenoRefGene.LENGTH

Transcript length data for the organism hg

Description

hg17.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg17.xenoRefGene.LENGTH)
head(hg17.xenoRefGene.LENGTH)
```

hg18.acembly.LENGTH

Transcript length data for the organism hg

Description

hg18.acembly.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acembly table.

The data file was made by calling `downloadLengthFromUCSC(hg18, acembly)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg18.acembly.LENGTH)
head(hg18.acembly.LENGTH)
```

hg18.acescan.LENGTH *Transcript length data for the organism hg*

Description

hg18.acescan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acescan table.

The data file was made by calling `downloadLengthFromUCSC(hg18, acescan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg18.acescan.LENGTH)
head(hg18.acescan.LENGTH)
```

hg18.ccdsGene.LENGTH *Transcript length data for the organism hg*

Description

hg18.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, ccdsGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg18.ccdsGene.LENGTH)
head(hg18.ccdsGene.LENGTH)
```

hg18.ensGene.LENGTH *Transcript length data for the organism hg*

Description

hg18.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg18.ensGene.LENGTH)
head(hg18.ensGene.LENGTH)
```

hg18.exoniphy.LENGTH *Transcript length data for the organism hg*

Description

hg18.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg18, exoniphy)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg18.exoniphy.LENGTH)
head(hg18.exoniphy.LENGTH)
```

hg18.geneid.LENGTH *Transcript length data for the organism hg*

Description

hg18.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(hg18, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg18.geneid.LENGTH)
head(hg18.geneid.LENGTH)
```

hg18.geneSymbol.LENGTH *Transcript length data for the organism hg*

Description

hg18.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg18, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg18.geneSymbol.LENGTH)
head(hg18.geneSymbol.LENGTH)
```

hg18.genscan.LENGTH *Transcript length data for the organism hg*

Description

hg18.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(hg18, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg18.genscan.LENGTH)
head(hg18.genscan.LENGTH)
```

hg18.knownGene.LENGTH *Transcript length data for the organism hg*

Description

hg18.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, knownGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg18.knownGene.LENGTH)
head(hg18.knownGene.LENGTH)
```

`hg18.knownGeneOld3.LENGTH`*Transcript length data for the organism hg*

Description

hg18.knownGeneOld3.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGeneOld3 table.

The data file was made by calling `downloadLengthFromUCSC(hg18, knownGeneOld3)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg18.knownGeneOld3.LENGTH)
head(hg18.knownGeneOld3.LENGTH)
```

`hg18.refGene.LENGTH` *Transcript length data for the organism hg*

Description

hg18.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg18.refGene.LENGTH)
head(hg18.refGene.LENGTH)
```

hg18.sgpGene.LENGTH *Transcript length data for the organism hg*

Description

hg18.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, sgpGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg18.sgpGene.LENGTH)
head(hg18.sgpGene.LENGTH)
```

hg18.sibGene.LENGTH *Transcript length data for the organism hg*

Description

hg18.sibGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sibGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, sibGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg18.sibGene.LENGTH)
head(hg18.sibGene.LENGTH)
```

`hg18.xenoRefGene.LENGTH`*Transcript length data for the organism hg*

Description

hg18.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg18.xenoRefGene.LENGTH)
head(hg18.xenoRefGene.LENGTH)
```

`hg19.ccdsGene.LENGTH` *Transcript length data for the organism hg*

Description

hg19.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, ccdsGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg19.ccdsGene.LENGTH)
head(hg19.ccdsGene.LENGTH)
```

hg19.ensGene.LENGTH *Transcript length data for the organism hg*

Description

hg19.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg19.ensGene.LENGTH)
head(hg19.ensGene.LENGTH)
```

hg19.exoniphy.LENGTH *Transcript length data for the organism hg*

Description

hg19.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg19, exoniphy)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg19.exoniphy.LENGTH)
head(hg19.exoniphy.LENGTH)
```

```
hg19.geneSymbol.LENGTH
```

Transcript length data for the organism hg

Description

hg19.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg19, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg19.geneSymbol.LENGTH)
head(hg19.geneSymbol.LENGTH)
```

```
hg19.knownGene.LENGTH
```

Transcript length data for the organism hg

Description

hg19.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, knownGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg19.knownGene.LENGTH)
head(hg19.knownGene.LENGTH)
```

hg19.nscanGene.LENGTH *Transcript length data for the organism hg*

Description

hg19.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg19.nscanGene.LENGTH)
head(hg19.nscanGene.LENGTH)
```

hg19.refGene.LENGTH *Transcript length data for the organism hg*

Description

hg19.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg19.refGene.LENGTH)
head(hg19.refGene.LENGTH)
```

`hg19.xenoRefGene.LENGTH`*Transcript length data for the organism hg*

Description

hg19.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(hg19.xenoRefGene.LENGTH)
head(hg19.xenoRefGene.LENGTH)
```

`loxAfr3.xenoRefGene.LENGTH`*Transcript length data for the organism loxAfr*

Description

loxAfr3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(loxAfr3, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(loxAfr3.xenoRefGene.LENGTH)
head(loxAfr3.xenoRefGene.LENGTH)
```

mm7.ensGene.LENGTH *Transcript length data for the organism mm*

Description

mm7.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm7.ensGene.LENGTH)
head(mm7.ensGene.LENGTH)
```

mm7.geneid.LENGTH *Transcript length data for the organism mm*

Description

mm7.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(mm7, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm7.geneid.LENGTH)
head(mm7.geneid.LENGTH)
```

mm7.geneSymbol.LENGTH *Transcript length data for the organism mm*

Description

mm7.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(mm7, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm7.geneSymbol.LENGTH)
head(mm7.geneSymbol.LENGTH)
```

mm7.genscan.LENGTH *Transcript length data for the organism mm*

Description

mm7.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(mm7, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm7.genscan.LENGTH)
head(mm7.genscan.LENGTH)
```

mm7.knownGene.LENGTH *Transcript length data for the organism mm*

Description

mm7.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, knownGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm7.knownGene.LENGTH)
head(mm7.knownGene.LENGTH)
```

mm7.refGene.LENGTH *Transcript length data for the organism mm*

Description

mm7.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm7.refGene.LENGTH)
head(mm7.refGene.LENGTH)
```

mm7.sgpGene.LENGTH *Transcript length data for the organism mm*

Description

mm7.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, sgpGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm7.sgpGene.LENGTH)
head(mm7.sgpGene.LENGTH)
```

mm7.xenoRefGene.LENGTH *Transcript length data for the organism mm*

Description

mm7.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm7.xenoRefGene.LENGTH)
head(mm7.xenoRefGene.LENGTH)
```

mm8.ccdsGene.LENGTH *Transcript length data for the organism mm*

Description

mm8.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, ccdsGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm8.ccdsGene.LENGTH)
head(mm8.ccdsGene.LENGTH)
```

mm8.ensGene.LENGTH *Transcript length data for the organism mm*

Description

mm8.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm8.ensGene.LENGTH)
head(mm8.ensGene.LENGTH)
```

mm8.geneid.LENGTH *Transcript length data for the organism mm*

Description

mm8.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(mm8, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm8.geneid.LENGTH)
head(mm8.geneid.LENGTH)
```

mm8.geneSymbol.LENGTH *Transcript length data for the organism mm*

Description

mm8.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(mm8, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm8.geneSymbol.LENGTH)
head(mm8.geneSymbol.LENGTH)
```

mm8.genscan.LENGTH *Transcript length data for the organism mm*

Description

mm8.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(mm8, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm8.genscan.LENGTH)
head(mm8.genscan.LENGTH)
```

mm8.knownGene.LENGTH *Transcript length data for the organism mm*

Description

mm8.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, knownGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm8.knownGene.LENGTH)
head(mm8.knownGene.LENGTH)
```

mm8.nscanGene.LENGTH *Transcript length data for the organism mm*

Description

mm8.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm8.nscanGene.LENGTH)
head(mm8.nscanGene.LENGTH)
```

mm8.refGene.LENGTH *Transcript length data for the organism mm*

Description

mm8.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm8.refGene.LENGTH)
head(mm8.refGene.LENGTH)
```

mm8.sgpGene.LENGTH *Transcript length data for the organism mm*

Description

mm8.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, sgpGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm8.sgpGene.LENGTH)
head(mm8.sgpGene.LENGTH)
```

mm8.sibGene.LENGTH *Transcript length data for the organism mm*

Description

mm8.sibGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sibGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, sibGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm8.sibGene.LENGTH)
head(mm8.sibGene.LENGTH)
```

`mm8.xenoRefGene.LENGTH`*Transcript length data for the organism mm*

Description

`mm8.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(mm8, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm8.xenoRefGene.LENGTH)
head(mm8.xenoRefGene.LENGTH)
```

`mm9.acembly.LENGTH`*Transcript length data for the organism mm*

Description

`mm9.acembly.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `acembly` table.

The data file was made by calling `downloadLengthFromUCSC(mm9, acembly)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm9.acembly.LENGTH)
head(mm9.acembly.LENGTH)
```

mm9.ccdsGene.LENGTH *Transcript length data for the organism mm*

Description

mm9.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, ccdsGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm9.ccdsGene.LENGTH)
head(mm9.ccdsGene.LENGTH)
```

mm9.ensGene.LENGTH *Transcript length data for the organism mm*

Description

mm9.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm9.ensGene.LENGTH)
head(mm9.ensGene.LENGTH)
```

mm9.exoniphy.LENGTH *Transcript length data for the organism mm*

Description

mm9.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(mm9, exoniphy)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm9.exoniphy.LENGTH)
head(mm9.exoniphy.LENGTH)
```

mm9.geneid.LENGTH *Transcript length data for the organism mm*

Description

mm9.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(mm9, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm9.geneid.LENGTH)
head(mm9.geneid.LENGTH)
```

mm9.geneSymbol.LENGTH *Transcript length data for the organism mm*

Description

mm9.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(mm9, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm9.geneSymbol.LENGTH)
head(mm9.geneSymbol.LENGTH)
```

mm9.genscan.LENGTH *Transcript length data for the organism mm*

Description

mm9.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(mm9, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm9.genscan.LENGTH)
head(mm9.genscan.LENGTH)
```

mm9.knownGene.LENGTH *Transcript length data for the organism mm*

Description

mm9.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, knownGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm9.knownGene.LENGTH)
head(mm9.knownGene.LENGTH)
```

mm9.nscanGene.LENGTH *Transcript length data for the organism mm*

Description

mm9.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm9.nscanGene.LENGTH)
head(mm9.nscanGene.LENGTH)
```

mm9.refGene.LENGTH *Transcript length data for the organism mm*

Description

mm9.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm9.refGene.LENGTH)
head(mm9.refGene.LENGTH)
```

mm9.sgpGene.LENGTH *Transcript length data for the organism mm*

Description

mm9.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, sgpGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm9.sgpGene.LENGTH)
head(mm9.sgpGene.LENGTH)
```

```
mm9.xenoRefGene.LENGTH
```

Transcript length data for the organism mm

Description

mm9.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(mm9.xenoRefGene.LENGTH)
head(mm9.xenoRefGene.LENGTH)
```

```
monDom1.genscan.LENGTH
```

Transcript length data for the organism monDom

Description

monDom1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(monDom1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(monDom1.genscan.LENGTH)
head(monDom1.genscan.LENGTH)
```

```
monDom4.ensGene.LENGTH
```

Transcript length data for the organism monDom

Description

monDom4.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(monDom4.ensGene.LENGTH)
head(monDom4.ensGene.LENGTH)
```

```
monDom4.geneSymbol.LENGTH
```

Transcript length data for the organism monDom

Description

monDom4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(monDom4.geneSymbol.LENGTH)
head(monDom4.geneSymbol.LENGTH)
```

`monDom4.genscan.LENGTH`*Transcript length data for the organism monDom*

Description

`monDom4.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(monDom4.genscan.LENGTH)
head(monDom4.genscan.LENGTH)
```

`monDom4.nscanGene.LENGTH`*Transcript length data for the organism monDom*

Description

`monDom4.nscanGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `nscanGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(monDom4.nscanGene.LENGTH)
head(monDom4.nscanGene.LENGTH)
```

```
monDom4.refGene.LENGTH
```

Transcript length data for the organism monDom

Description

monDom4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(monDom4.refGene.LENGTH)
head(monDom4.refGene.LENGTH)
```

```
monDom4.xenoRefGene.LENGTH
```

Transcript length data for the organism monDom

Description

monDom4.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(monDom4.xenoRefGene.LENGTH)
head(monDom4.xenoRefGene.LENGTH)
```

`monDom5.ensGene.LENGTH`*Transcript length data for the organism monDom*

Description

`monDom5.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(monDom5.ensGene.LENGTH)
head(monDom5.ensGene.LENGTH)
```

`monDom5.geneSymbol.LENGTH`*Transcript length data for the organism monDom*

Description

`monDom5.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(monDom5.geneSymbol.LENGTH)
head(monDom5.geneSymbol.LENGTH)
```

monDom5.genscan.LENGTH

Transcript length data for the organism monDom

Description

monDom5.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(monDom5.genscan.LENGTH)
head(monDom5.genscan.LENGTH)
```

monDom5.nscanGene.LENGTH

Transcript length data for the organism monDom

Description

monDom5.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(monDom5.nscanGene.LENGTH)
head(monDom5.nscanGene.LENGTH)
```

```
monDom5.refGene.LENGTH
```

Transcript length data for the organism monDom

Description

monDom5.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(monDom5.refGene.LENGTH)
head(monDom5.refGene.LENGTH)
```

```
monDom5.xenoRefGene.LENGTH
```

Transcript length data for the organism monDom

Description

monDom5.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(monDom5.xenoRefGene.LENGTH)
head(monDom5.xenoRefGene.LENGTH)
```

```
ornAna1.ensGene.LENGTH
```

Transcript length data for the organism ornAna

Description

ornAna1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ornAna1.ensGene.LENGTH)
head(ornAna1.ensGene.LENGTH)
```

```
ornAna1.geneSymbol.LENGTH
```

Transcript length data for the organism ornAna

Description

ornAna1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ornAna1.geneSymbol.LENGTH)
head(ornAna1.geneSymbol.LENGTH)
```

```
ornAna1.refGene.LENGTH
```

Transcript length data for the organism ornAna

Description

ornAna1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ornAna1.refGene.LENGTH)
head(ornAna1.refGene.LENGTH)
```

```
ornAna1.xenoRefGene.LENGTH
```

Transcript length data for the organism ornAna

Description

ornAna1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ornAna1.xenoRefGene.LENGTH)
head(ornAna1.xenoRefGene.LENGTH)
```

```
oryLat2.ensGene.LENGTH
```

Transcript length data for the organism oryLat

Description

oryLat2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(oryLat2.ensGene.LENGTH)
head(oryLat2.ensGene.LENGTH)
```

```
oryLat2.geneSymbol.LENGTH
```

Transcript length data for the organism oryLat

Description

oryLat2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(oryLat2.geneSymbol.LENGTH)
head(oryLat2.geneSymbol.LENGTH)
```

```
oryLat2.refGene.LENGTH
```

Transcript length data for the organism oryLat

Description

oryLat2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(oryLat2.refGene.LENGTH)
head(oryLat2.refGene.LENGTH)
```

```
oryLat2.xenoRefGene.LENGTH
```

Transcript length data for the organism oryLat

Description

oryLat2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(oryLat2.xenoRefGene.LENGTH)
head(oryLat2.xenoRefGene.LENGTH)
```

```
panTro1.ensGene.LENGTH
```

Transcript length data for the organism panTro

Description

panTro1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(panTro1.ensGene.LENGTH)
head(panTro1.ensGene.LENGTH)
```

```
panTro1.geneid.LENGTH
```

Transcript length data for the organism panTro

Description

panTro1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(panTro1.geneid.LENGTH)
head(panTro1.geneid.LENGTH)
```

```
panTro1.genscan.LENGTH
```

Transcript length data for the organism panTro

Description

panTro1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(panTro1.genscan.LENGTH)
head(panTro1.genscan.LENGTH)
```

```
panTro1.xenoRefGene.LENGTH
```

Transcript length data for the organism panTro

Description

panTro1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(panTro1.xenoRefGene.LENGTH)
head(panTro1.xenoRefGene.LENGTH)
```

```
panTro2.ensGene.LENGTH
```

Transcript length data for the organism panTro

Description

panTro2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(panTro2.ensGene.LENGTH)
head(panTro2.ensGene.LENGTH)
```

```
panTro2.geneSymbol.LENGTH
```

Transcript length data for the organism panTro

Description

panTro2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(panTro2.geneSymbol.LENGTH)
head(panTro2.geneSymbol.LENGTH)
```

```
panTro2.genscan.LENGTH
```

Transcript length data for the organism panTro

Description

panTro2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(panTro2.genscan.LENGTH)
head(panTro2.genscan.LENGTH)
```

```
panTro2.nscanGene.LENGTH
```

Transcript length data for the organism panTro

Description

panTro2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(panTro2.nscanGene.LENGTH)
head(panTro2.nscanGene.LENGTH)
```

```
panTro2.refGene.LENGTH
```

Transcript length data for the organism panTro

Description

panTro2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(panTro2.refGene.LENGTH)
head(panTro2.refGene.LENGTH)
```

```
panTro2.xenoRefGene.LENGTH
```

Transcript length data for the organism panTro

Description

panTro2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(panTro2.xenoRefGene.LENGTH)
head(panTro2.xenoRefGene.LENGTH)
```

```
petMar1.xenoRefGene.LENGTH
```

Transcript length data for the organism petMar

Description

petMar1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(petMar1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(petMar1.xenoRefGene.LENGTH)
head(petMar1.xenoRefGene.LENGTH)
```

```
ponAbe2.ensGene.LENGTH
```

Transcript length data for the organism ponAbe

Description

ponAbe2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ponAbe2.ensGene.LENGTH)
head(ponAbe2.ensGene.LENGTH)
```

```
ponAbe2.geneSymbol.LENGTH
```

Transcript length data for the organism ponAbe

Description

ponAbe2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ponAbe2.geneSymbol.LENGTH)
head(ponAbe2.geneSymbol.LENGTH)
```

```
ponAbe2.genscan.LENGTH
```

Transcript length data for the organism ponAbe

Description

ponAbe2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ponAbe2.genscan.LENGTH)
head(ponAbe2.genscan.LENGTH)
```

```
ponAbe2.nscanGene.LENGTH
```

Transcript length data for the organism ponAbe

Description

ponAbe2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ponAbe2.nscanGene.LENGTH)
head(ponAbe2.nscanGene.LENGTH)
```

```
ponAbe2.refGene.LENGTH
```

Transcript length data for the organism ponAbe

Description

ponAbe2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ponAbe2.refGene.LENGTH)
head(ponAbe2.refGene.LENGTH)
```

```
ponAbe2.xenoRefGene.LENGTH
```

Transcript length data for the organism ponAbe

Description

ponAbe2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(ponAbe2.xenoRefGene.LENGTH)
head(ponAbe2.xenoRefGene.LENGTH)
```

```
priPac1.xenoRefGene.LENGTH
```

Transcript length data for the organism priPac

Description

priPac1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(priPac1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(priPac1.xenoRefGene.LENGTH)
head(priPac1.xenoRefGene.LENGTH)
```

```
rheMac2.ensGene.LENGTH
```

Transcript length data for the organism rheMac

Description

rheMac2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rheMac2.ensGene.LENGTH)
head(rheMac2.ensGene.LENGTH)
```

```
rheMac2.geneid.LENGTH
```

Transcript length data for the organism rheMac

Description

rheMac2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rheMac2.geneid.LENGTH)
head(rheMac2.geneid.LENGTH)
```

```
rheMac2.geneSymbol.LENGTH
```

Transcript length data for the organism rheMac

Description

rheMac2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rheMac2.geneSymbol.LENGTH)
head(rheMac2.geneSymbol.LENGTH)
```

```
rheMac2.nscanGene.LENGTH
```

Transcript length data for the organism rheMac

Description

rheMac2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rheMac2.nscanGene.LENGTH)
head(rheMac2.nscanGene.LENGTH)
```

`rheMac2.refGene.LENGTH`*Transcript length data for the organism rheMac*

Description

rheMac2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, refGene)` on the date on which the package was last updated.

See Also[downloadLengthFromUCSC](#)**Examples**

```
data(rheMac2.refGene.LENGTH)
head(rheMac2.refGene.LENGTH)
```

`rheMac2.sgpGene.LENGTH`*Transcript length data for the organism rheMac*

Description

rheMac2.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, sgpGene)` on the date on which the package was last updated.

See Also[downloadLengthFromUCSC](#)**Examples**

```
data(rheMac2.sgpGene.LENGTH)
head(rheMac2.sgpGene.LENGTH)
```

```
rheMac2.xenoRefGene.LENGTH
```

Transcript length data for the organism rheMac

Description

rheMac2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rheMac2.xenoRefGene.LENGTH)
head(rheMac2.xenoRefGene.LENGTH)
```

```
rn3.ensGene.LENGTH
```

Transcript length data for the organism rn

Description

rn3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn3.ensGene.LENGTH)
head(rn3.ensGene.LENGTH)
```

rn3.geneid.LENGTH *Transcript length data for the organism rn*

Description

rn3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(rn3, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn3.geneid.LENGTH)
head(rn3.geneid.LENGTH)
```

rn3.geneSymbol.LENGTH *Transcript length data for the organism rn*

Description

rn3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(rn3, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn3.geneSymbol.LENGTH)
head(rn3.geneSymbol.LENGTH)
```

rn3.genscan.LENGTH *Transcript length data for the organism rn*

Description

rn3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(rn3, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn3.genscan.LENGTH)
head(rn3.genscan.LENGTH)
```

rn3.knownGene.LENGTH *Transcript length data for the organism rn*

Description

rn3.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, knownGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn3.knownGene.LENGTH)
head(rn3.knownGene.LENGTH)
```

rn3.nscanGene.LENGTH *Transcript length data for the organism rn*

Description

rn3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn3.nscanGene.LENGTH)
head(rn3.nscanGene.LENGTH)
```

rn3.refGene.LENGTH *Transcript length data for the organism rn*

Description

rn3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn3.refGene.LENGTH)
head(rn3.refGene.LENGTH)
```

rn3.sgpGene.LENGTH *Transcript length data for the organism rn*

Description

rn3.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, sgpGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn3.sgpGene.LENGTH)
head(rn3.sgpGene.LENGTH)
```

rn3.xenoRefGene.LENGTH *Transcript length data for the organism rn*

Description

rn3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn3.xenoRefGene.LENGTH)
head(rn3.xenoRefGene.LENGTH)
```

rn4.ensGene.LENGTH *Transcript length data for the organism rn*

Description

rn4.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn4.ensGene.LENGTH)
head(rn4.ensGene.LENGTH)
```

rn4.geneid.LENGTH *Transcript length data for the organism rn*

Description

rn4.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(rn4, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn4.geneid.LENGTH)
head(rn4.geneid.LENGTH)
```

rn4.geneSymbol.LENGTH *Transcript length data for the organism rn*

Description

rn4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(rn4, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn4.geneSymbol.LENGTH)
head(rn4.geneSymbol.LENGTH)
```

rn4.genscan.LENGTH *Transcript length data for the organism rn*

Description

rn4.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(rn4, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn4.genscan.LENGTH)
head(rn4.genscan.LENGTH)
```

rn4.knownGene.LENGTH *Transcript length data for the organism rn*

Description

rn4.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, knownGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn4.knownGene.LENGTH)
head(rn4.knownGene.LENGTH)
```

rn4.nscanGene.LENGTH *Transcript length data for the organism rn*

Description

rn4.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn4.nscanGene.LENGTH)
head(rn4.nscanGene.LENGTH)
```

rn4.refGene.LENGTH *Transcript length data for the organism rn*

Description

rn4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn4.refGene.LENGTH)
head(rn4.refGene.LENGTH)
```

rn4.sgpGene.LENGTH *Transcript length data for the organism rn*

Description

rn4.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, sgpGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn4.sgpGene.LENGTH)
head(rn4.sgpGene.LENGTH)
```

`rn4.xenoRefGene.LENGTH`*Transcript length data for the organism rn*

Description

rn4.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(rn4.xenoRefGene.LENGTH)
head(rn4.xenoRefGene.LENGTH)
```

`sacCer1.ensGene.LENGTH`*Transcript length data for the organism sacCer*

Description

sacCer1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(sacCer1, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(sacCer1.ensGene.LENGTH)
head(sacCer1.ensGene.LENGTH)
```

sacCer2.ensGene.LENGTH

Transcript length data for the organism sacCer

Description

sacCer2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(sacCer2, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(sacCer2.ensGene.LENGTH)
head(sacCer2.ensGene.LENGTH)
```

strPur1.geneSymbol.LENGTH

Transcript length data for the organism strPur

Description

strPur1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(strPur1.geneSymbol.LENGTH)
head(strPur1.geneSymbol.LENGTH)
```

```
strPur1.genscan.LENGTH
```

Transcript length data for the organism strPur

Description

strPur1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(strPur1.genscan.LENGTH)
head(strPur1.genscan.LENGTH)
```

```
strPur1.refGene.LENGTH
```

Transcript length data for the organism strPur

Description

strPur1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(strPur1.refGene.LENGTH)
head(strPur1.refGene.LENGTH)
```

```
strPur1.xenoRefGene.LENGTH
```

Transcript length data for the organism strPur

Description

strPur1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(strPur1.xenoRefGene.LENGTH)
head(strPur1.xenoRefGene.LENGTH)
```

```
strPur2.geneSymbol.LENGTH
```

Transcript length data for the organism strPur

Description

strPur2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(strPur2.geneSymbol.LENGTH)
head(strPur2.geneSymbol.LENGTH)
```

`strPur2.genscan.LENGTH`*Transcript length data for the organism strPur*

Description

strPur2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, genscan)` on the date on which the package was last updated.

See Also[downloadLengthFromUCSC](#)**Examples**

```
data(strPur2.genscan.LENGTH)
head(strPur2.genscan.LENGTH)
```

`strPur2.refGene.LENGTH`*Transcript length data for the organism strPur*

Description

strPur2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, refGene)` on the date on which the package was last updated.

See Also[downloadLengthFromUCSC](#)**Examples**

```
data(strPur2.refGene.LENGTH)
head(strPur2.refGene.LENGTH)
```

```
strPur2.xenoRefGene.LENGTH
```

Transcript length data for the organism strPur

Description

strPur2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(strPur2.xenoRefGene.LENGTH)
head(strPur2.xenoRefGene.LENGTH)
```

```
supportedGeneIDs
```

Supported Gene IDs

Description

Lists supported gene ID formats

Usage

```
supportedGeneIDs()
```

Details

Uses the `supportedUCSCTables` function from the `GenomicFeatures` package to obtain a list of gene ID formats available from the UCSC genome browser. The `db` column gives the gene ID formats which are provided to the `id` argument of various functions. The `track` and `subtrack` columns are the names of the UCSC track/subtrack from which information is fetched.

The `GeneID` column lists the "full name" of the gene ID format where available.

The final column, headed `AvailableGenomes` lists the genomes for which there is a local copy of the length information available for the gene ID format listed in the `geneLenDataBase` package.

Value

A data.frame containing supported gene ID formats.

Author(s)

Matthew D. Young <myoung@wehi.edu.au>

Examples

```
supportedGeneIDs()
```

supportedGenomes	<i>Supported Genomes</i>
------------------	--------------------------

Description

Lists supported genomes

Usage

```
supportedGenomes()
```

Details

Uses the `ucscGenomes()` function from the `rtracklayer` package to obtain a list of genomes available from the UCSC genome browser. The `db` column lists genomes as they are provided to the genome argument of various functions.

The final column, headed `AvailableGeneIDs` lists the gene ID formats for which there is a local copy of the length information available for the genome listed in the `geneLenDataBase` package.

Value

A data.frame containing supported genomes.

Author(s)

Matthew D. Young <myoung@wehi.edu.au>

Examples

```
supportedGenomes()
```

<code>taeGut1.ensGene.LENGTH</code>	<i>Transcript length data for the organism taeGut</i>
-------------------------------------	---

Description

`taeGut1.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(taeGut1.ensGene.LENGTH)
head(taeGut1.ensGene.LENGTH)
```

```
taeGut1.geneSymbol.LENGTH
```

Transcript length data for the organism taeGut

Description

taeGut1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(taeGut1.geneSymbol.LENGTH)
head(taeGut1.geneSymbol.LENGTH)
```

```
taeGut1.genscan.LENGTH
```

Transcript length data for the organism taeGut

Description

taeGut1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(taeGut1.genscan.LENGTH)
head(taeGut1.genscan.LENGTH)
```

```
taeGut1.nscanGene.LENGTH
```

Transcript length data for the organism taeGut

Description

taeGut1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(taeGut1.nscanGene.LENGTH)
head(taeGut1.nscanGene.LENGTH)
```

```
taeGut1.refGene.LENGTH
```

Transcript length data for the organism taeGut

Description

taeGut1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(taeGut1.refGene.LENGTH)
head(taeGut1.refGene.LENGTH)
```

```
taeGut1.xenoRefGene.LENGTH
```

Transcript length data for the organism taeGut

Description

taeGut1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, xenoRefGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(taeGut1.xenoRefGene.LENGTH)
head(taeGut1.xenoRefGene.LENGTH)
```

```
tetNig1.ensGene.LENGTH
```

Transcript length data for the organism tetNig

Description

tetNig1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(tetNig1.ensGene.LENGTH)
head(tetNig1.ensGene.LENGTH)
```

tetNig1.geneid.LENGTH *Transcript length data for the organism tetNig*

Description

tetNig1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, geneid)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(tetNig1.geneid.LENGTH)
head(tetNig1.geneid.LENGTH)
```

tetNig1.genscan.LENGTH
Transcript length data for the organism tetNig

Description

tetNig1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(tetNig1.genscan.LENGTH)
head(tetNig1.genscan.LENGTH)
```

```
tetNig1.nscanGene.LENGTH
```

Transcript length data for the organism tetNig

Description

tetNig1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, nscanGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(tetNig1.nscanGene.LENGTH)
head(tetNig1.nscanGene.LENGTH)
```

```
tetNig2.ensGene.LENGTH
```

Transcript length data for the organism tetNig

Description

tetNig2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(tetNig2, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(tetNig2.ensGene.LENGTH)
head(tetNig2.ensGene.LENGTH)
```

unfactor	<i>Purge factors</i>
----------	----------------------

Description

Removes all factors from a variable in a sensible way.

Usage

```
unfactor(var)
```

Arguments

var The variable from which you want the factors removed.

Details

As factors are their own type, to remove factors we must convert each level into another type. This is currently done using "typeless" behaviour: a factor is converted to a numeric vector if this can be done without inducing NAs, otherwise it is coerced using `as.character`. Currently supported types are: `factor`, `data.frame` and `list`.

Value

The variable with all factors converted to characters or numbers (see details).

Author(s)

Matthew D. Young <myoung@wehi.edu.au>

Examples

```
# A named factor
x <- factor(sample(1:6, 100, replace=TRUE))
names(x) <- paste("Roll.No", 1:100, sep='.')
x
unfactor(x)

# A data.frame
x <- data.frame(player <- c("Alice", "Bob", "Mary", "Fred"),
               score <- factor(c(9, 7, 8, 9)), stringsAsFactors=TRUE)
x$player
x$score
y <- unfactor(x)
y$player
y$score
```

```
xenTro1.genscan.LENGTH
```

Transcript length data for the organism xenTro

Description

xenTro1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(xenTro1, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(xenTro1.genscan.LENGTH)
head(xenTro1.genscan.LENGTH)
```

```
xenTro2.ensGene.LENGTH
```

Transcript length data for the organism xenTro

Description

xenTro2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, ensGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(xenTro2.ensGene.LENGTH)
head(xenTro2.ensGene.LENGTH)
```

```
xenTro2.geneSymbol.LENGTH
```

Transcript length data for the organism xenTro

Description

xenTro2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, geneSymbol)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(xenTro2.geneSymbol.LENGTH)
head(xenTro2.geneSymbol.LENGTH)
```

```
xenTro2.genscan.LENGTH
```

Transcript length data for the organism xenTro

Description

xenTro2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, genscan)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(xenTro2.genscan.LENGTH)
head(xenTro2.genscan.LENGTH)
```

`xenTro2.refGene.LENGTH`*Transcript length data for the organism xenTro*

Description

`xenTro2.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, refGene)` on the date on which the package was last updated.

See Also

[downloadLengthFromUCSC](#)

Examples

```
data(xenTro2.refGene.LENGTH)
head(xenTro2.refGene.LENGTH)
```

Index

* datasets

anoCar1.ensGene.LENGTH, 8
anoCar1.genscan.LENGTH, 9
anoCar1.xenoRefGene.LENGTH, 9
anoGam1.ensGene.LENGTH, 10
anoGam1.geneid.LENGTH, 10
anoGam1.genscan.LENGTH, 11
apiMe11.genscan.LENGTH, 11
apiMe12.ensGene.LENGTH, 12
apiMe12.geneid.LENGTH, 12
apiMe12.genscan.LENGTH, 13
aplCa11.xenoRefGene.LENGTH, 13
bosTau2.geneid.LENGTH, 14
bosTau2.geneSymbol.LENGTH, 14
bosTau2.genscan.LENGTH, 15
bosTau2.refGene.LENGTH, 15
bosTau2.sgpGene.LENGTH, 16
bosTau3.ensGene.LENGTH, 16
bosTau3.geneid.LENGTH, 17
bosTau3.geneSymbol.LENGTH, 17
bosTau3.genscan.LENGTH, 18
bosTau3.refGene.LENGTH, 18
bosTau3.sgpGene.LENGTH, 19
bosTau4.ensGene.LENGTH, 19
bosTau4.geneSymbol.LENGTH, 20
bosTau4.genscan.LENGTH, 20
bosTau4.nscanGene.LENGTH, 21
bosTau4.refGene.LENGTH, 21
braFlo1.xenoRefGene.LENGTH, 22
caeJap1.xenoRefGene.LENGTH, 22
caePb1.xenoRefGene.LENGTH, 23
caePb2.xenoRefGene.LENGTH, 23
caeRem2.xenoRefGene.LENGTH, 24
caeRem3.xenoRefGene.LENGTH, 24
calJac1.genscan.LENGTH, 25
calJac1.nscanGene.LENGTH, 25
calJac1.xenoRefGene.LENGTH, 26
canFam1.ensGene.LENGTH, 26
canFam1.geneSymbol.LENGTH, 27
canFam1.genscan.LENGTH, 27
canFam1.nscanGene.LENGTH, 28
canFam1.refGene.LENGTH, 28
canFam1.xenoRefGene.LENGTH, 29
canFam2.ensGene.LENGTH, 29
canFam2.geneSymbol.LENGTH, 30
canFam2.genscan.LENGTH, 30
canFam2.nscanGene.LENGTH, 31
canFam2.refGene.LENGTH, 31
canFam2.xenoRefGene.LENGTH, 32
cavPor3.ensGene.LENGTH, 32
cavPor3.genscan.LENGTH, 33
cavPor3.nscanGene.LENGTH, 33
cavPor3.xenoRefGene.LENGTH, 34
cb1.xenoRefGene.LENGTH, 34
cb3.xenoRefGene.LENGTH, 35
ce2.geneid.LENGTH, 35
ce2.geneSymbol.LENGTH, 36
ce2.refGene.LENGTH, 36
ce4.geneSymbol.LENGTH, 37
ce4.refGene.LENGTH, 37
ce4.xenoRefGene.LENGTH, 38
ce6.ensGene.LENGTH, 38
ce6.geneSymbol.LENGTH, 39
ce6.refGene.LENGTH, 39
ce6.xenoRefGene.LENGTH, 40
ci1.geneSymbol.LENGTH, 40
ci1.refGene.LENGTH, 41
ci1.xenoRefGene.LENGTH, 41
ci2.ensGene.LENGTH, 42
ci2.geneSymbol.LENGTH, 42
ci2.refGene.LENGTH, 43
ci2.xenoRefGene.LENGTH, 43
danRer3.ensGene.LENGTH, 44
danRer3.geneSymbol.LENGTH, 44
danRer3.refGene.LENGTH, 45
danRer4.ensGene.LENGTH, 45
danRer4.geneSymbol.LENGTH, 46
danRer4.genscan.LENGTH, 46
danRer4.nscanGene.LENGTH, 47
danRer4.refGene.LENGTH, 47
danRer5.ensGene.LENGTH, 48
danRer5.geneSymbol.LENGTH, 48
danRer5.refGene.LENGTH, 49
danRer5.vegaGene.LENGTH, 49
danRer5.vegaPseudoGene.LENGTH, 50
danRer6.ensGene.LENGTH, 50

- danRer6.geneSymbol.LENGTH, 51
 danRer6.refGene.LENGTH, 51
 danRer6.xenoRefGene.LENGTH, 52
 dm1.geneSymbol.LENGTH, 52
 dm1.genscan.LENGTH, 53
 dm1.refGene.LENGTH, 53
 dm2.geneid.LENGTH, 54
 dm2.geneSymbol.LENGTH, 54
 dm2.genscan.LENGTH, 55
 dm2.nscanGene.LENGTH, 55
 dm2.refGene.LENGTH, 56
 dm3.geneSymbol.LENGTH, 56
 dm3.nscanPasaGene.LENGTH, 57
 dm3.refGene.LENGTH, 57
 dp2.genscan.LENGTH, 59
 dp2.xenoRefGene.LENGTH, 59
 dp3.geneid.LENGTH, 60
 dp3.genscan.LENGTH, 60
 dp3.xenoRefGene.LENGTH, 61
 droAna1.geneid.LENGTH, 61
 droAna1.genscan.LENGTH, 62
 droAna1.xenoRefGene.LENGTH, 62
 droAna2.genscan.LENGTH, 63
 droAna2.xenoRefGene.LENGTH, 63
 droEre1.genscan.LENGTH, 64
 droEre1.xenoRefGene.LENGTH, 64
 droGri1.genscan.LENGTH, 65
 droGri1.xenoRefGene.LENGTH, 65
 droMoj1.geneid.LENGTH, 66
 droMoj1.genscan.LENGTH, 66
 droMoj1.xenoRefGene.LENGTH, 67
 droMoj2.genscan.LENGTH, 67
 droMoj2.xenoRefGene.LENGTH, 68
 droPer1.genscan.LENGTH, 68
 droPer1.xenoRefGene.LENGTH, 69
 droSec1.genscan.LENGTH, 69
 droSec1.xenoRefGene.LENGTH, 70
 droSim1.geneid.LENGTH, 70
 droSim1.genscan.LENGTH, 71
 droSim1.xenoRefGene.LENGTH, 71
 droVir1.geneid.LENGTH, 72
 droVir1.genscan.LENGTH, 72
 droVir1.xenoRefGene.LENGTH, 73
 droVir2.genscan.LENGTH, 73
 droVir2.xenoRefGene.LENGTH, 74
 droYak1.geneid.LENGTH, 74
 droYak1.genscan.LENGTH, 75
 droYak1.xenoRefGene.LENGTH, 75
 droYak2.genscan.LENGTH, 76
 droYak2.xenoRefGene.LENGTH, 76
 equCab1.geneid.LENGTH, 77
 equCab1.geneSymbol.LENGTH, 77
 equCab1.nscanGene.LENGTH, 78
 equCab1.refGene.LENGTH, 78
 equCab1.sgpGene.LENGTH, 79
 equCab2.ensGene.LENGTH, 79
 equCab2.geneSymbol.LENGTH, 80
 equCab2.nscanGene.LENGTH, 80
 equCab2.refGene.LENGTH, 81
 equCab2.xenoRefGene.LENGTH, 81
 felCat3.ensGene.LENGTH, 82
 felCat3.geneid.LENGTH, 82
 felCat3.geneSymbol.LENGTH, 83
 felCat3.genscan.LENGTH, 83
 felCat3.nscanGene.LENGTH, 84
 felCat3.refGene.LENGTH, 84
 felCat3.sgpGene.LENGTH, 85
 felCat3.xenoRefGene.LENGTH, 85
 fr1.ensGene.LENGTH, 86
 fr1.genscan.LENGTH, 86
 fr2.ensGene.LENGTH, 87
 galGal2.ensGene.LENGTH, 87
 galGal2.geneid.LENGTH, 88
 galGal2.geneSymbol.LENGTH, 88
 galGal2.genscan.LENGTH, 89
 galGal2.refGene.LENGTH, 89
 galGal2.sgpGene.LENGTH, 90
 galGal3.ensGene.LENGTH, 90
 galGal3.geneSymbol.LENGTH, 91
 galGal3.genscan.LENGTH, 91
 galGal3.nscanGene.LENGTH, 92
 galGal3.refGene.LENGTH, 92
 galGal3.xenoRefGene.LENGTH, 93
 gasAcu1.ensGene.LENGTH, 93
 gasAcu1.nscanGene.LENGTH, 94
 hg16.acembly.LENGTH, 95
 hg16.ensGene.LENGTH, 95
 hg16.exoniphy.LENGTH, 96
 hg16.geneid.LENGTH, 96
 hg16.geneSymbol.LENGTH, 97
 hg16.genscan.LENGTH, 97
 hg16.knownGene.LENGTH, 98
 hg16.refGene.LENGTH, 98
 hg16.sgpGene.LENGTH, 99
 hg17.acembly.LENGTH, 99
 hg17.acescan.LENGTH, 100
 hg17.ccdsGene.LENGTH, 100
 hg17.ensGene.LENGTH, 101
 hg17.exoniphy.LENGTH, 101
 hg17.geneid.LENGTH, 102
 hg17.geneSymbol.LENGTH, 102
 hg17.genscan.LENGTH, 103
 hg17.knownGene.LENGTH, 103
 hg17.refGene.LENGTH, 104

- hg17.sgpGene.LENGTH, 104
- hg17.vegaGene.LENGTH, 105
- hg17.vegaPseudoGene.LENGTH, 105
- hg17.xenoRefGene.LENGTH, 106
- hg18.acembly.LENGTH, 106
- hg18.acescan.LENGTH, 107
- hg18.ccdsGene.LENGTH, 107
- hg18.ensGene.LENGTH, 108
- hg18.exoniphy.LENGTH, 108
- hg18.geneid.LENGTH, 109
- hg18.geneSymbol.LENGTH, 109
- hg18.genscan.LENGTH, 110
- hg18.knownGene.LENGTH, 110
- hg18.knownGeneOld3.LENGTH, 111
- hg18.refGene.LENGTH, 111
- hg18.sgpGene.LENGTH, 112
- hg18.sibGene.LENGTH, 112
- hg18.xenoRefGene.LENGTH, 113
- hg19.ccdsGene.LENGTH, 113
- hg19.ensGene.LENGTH, 114
- hg19.exoniphy.LENGTH, 114
- hg19.geneSymbol.LENGTH, 115
- hg19.knownGene.LENGTH, 115
- hg19.nscanGene.LENGTH, 116
- hg19.refGene.LENGTH, 116
- hg19.xenoRefGene.LENGTH, 117
- loxAfr3.xenoRefGene.LENGTH, 117
- mm7.ensGene.LENGTH, 118
- mm7.geneid.LENGTH, 118
- mm7.geneSymbol.LENGTH, 119
- mm7.genscan.LENGTH, 119
- mm7.knownGene.LENGTH, 120
- mm7.refGene.LENGTH, 120
- mm7.sgpGene.LENGTH, 121
- mm7.xenoRefGene.LENGTH, 121
- mm8.ccdsGene.LENGTH, 122
- mm8.ensGene.LENGTH, 122
- mm8.geneid.LENGTH, 123
- mm8.geneSymbol.LENGTH, 123
- mm8.genscan.LENGTH, 124
- mm8.knownGene.LENGTH, 124
- mm8.nscanGene.LENGTH, 125
- mm8.refGene.LENGTH, 125
- mm8.sgpGene.LENGTH, 126
- mm8.sibGene.LENGTH, 126
- mm8.xenoRefGene.LENGTH, 127
- mm9.acembly.LENGTH, 127
- mm9.ccdsGene.LENGTH, 128
- mm9.ensGene.LENGTH, 128
- mm9.exoniphy.LENGTH, 129
- mm9.geneid.LENGTH, 129
- mm9.geneSymbol.LENGTH, 130
- mm9.genscan.LENGTH, 130
- mm9.knownGene.LENGTH, 131
- mm9.nscanGene.LENGTH, 131
- mm9.refGene.LENGTH, 132
- mm9.sgpGene.LENGTH, 132
- mm9.xenoRefGene.LENGTH, 133
- monDom1.genscan.LENGTH, 133
- monDom4.ensGene.LENGTH, 134
- monDom4.geneSymbol.LENGTH, 134
- monDom4.genscan.LENGTH, 135
- monDom4.nscanGene.LENGTH, 135
- monDom4.refGene.LENGTH, 136
- monDom4.xenoRefGene.LENGTH, 136
- monDom5.ensGene.LENGTH, 137
- monDom5.geneSymbol.LENGTH, 137
- monDom5.genscan.LENGTH, 138
- monDom5.nscanGene.LENGTH, 138
- monDom5.refGene.LENGTH, 139
- monDom5.xenoRefGene.LENGTH, 139
- ornAna1.ensGene.LENGTH, 140
- ornAna1.geneSymbol.LENGTH, 140
- ornAna1.refGene.LENGTH, 141
- ornAna1.xenoRefGene.LENGTH, 141
- oryLat2.ensGene.LENGTH, 142
- oryLat2.geneSymbol.LENGTH, 142
- oryLat2.refGene.LENGTH, 143
- oryLat2.xenoRefGene.LENGTH, 143
- panTro1.ensGene.LENGTH, 144
- panTro1.geneid.LENGTH, 144
- panTro1.genscan.LENGTH, 145
- panTro1.xenoRefGene.LENGTH, 145
- panTro2.ensGene.LENGTH, 146
- panTro2.geneSymbol.LENGTH, 146
- panTro2.genscan.LENGTH, 147
- panTro2.nscanGene.LENGTH, 147
- panTro2.refGene.LENGTH, 148
- panTro2.xenoRefGene.LENGTH, 148
- petMar1.xenoRefGene.LENGTH, 149
- ponAbe2.ensGene.LENGTH, 149
- ponAbe2.geneSymbol.LENGTH, 150
- ponAbe2.genscan.LENGTH, 150
- ponAbe2.nscanGene.LENGTH, 151
- ponAbe2.refGene.LENGTH, 151
- ponAbe2.xenoRefGene.LENGTH, 152
- priPac1.xenoRefGene.LENGTH, 152
- rheMac2.ensGene.LENGTH, 153
- rheMac2.geneid.LENGTH, 153
- rheMac2.geneSymbol.LENGTH, 154
- rheMac2.nscanGene.LENGTH, 154
- rheMac2.refGene.LENGTH, 155
- rheMac2.sgpGene.LENGTH, 155
- rheMac2.xenoRefGene.LENGTH, 156

- rn3.ensGene.LENGTH, 156
 rn3.geneid.LENGTH, 157
 rn3.geneSymbol.LENGTH, 157
 rn3.genscan.LENGTH, 158
 rn3.knownGene.LENGTH, 158
 rn3.nscanGene.LENGTH, 159
 rn3.refGene.LENGTH, 159
 rn3.sgpGene.LENGTH, 160
 rn3.xenoRefGene.LENGTH, 160
 rn4.ensGene.LENGTH, 161
 rn4.geneid.LENGTH, 161
 rn4.geneSymbol.LENGTH, 162
 rn4.genscan.LENGTH, 162
 rn4.knownGene.LENGTH, 163
 rn4.nscanGene.LENGTH, 163
 rn4.refGene.LENGTH, 164
 rn4.sgpGene.LENGTH, 164
 rn4.xenoRefGene.LENGTH, 165
 sacCer1.ensGene.LENGTH, 165
 sacCer2.ensGene.LENGTH, 166
 strPur1.geneSymbol.LENGTH, 166
 strPur1.genscan.LENGTH, 167
 strPur1.refGene.LENGTH, 167
 strPur1.xenoRefGene.LENGTH, 168
 strPur2.geneSymbol.LENGTH, 168
 strPur2.genscan.LENGTH, 169
 strPur2.refGene.LENGTH, 169
 strPur2.xenoRefGene.LENGTH, 170
 taeGut1.ensGene.LENGTH, 171
 taeGut1.geneSymbol.LENGTH, 172
 taeGut1.genscan.LENGTH, 172
 taeGut1.nscanGene.LENGTH, 173
 taeGut1.refGene.LENGTH, 173
 taeGut1.xenoRefGene.LENGTH, 174
 tetNig1.ensGene.LENGTH, 174
 tetNig1.geneid.LENGTH, 175
 tetNig1.genscan.LENGTH, 175
 tetNig1.nscanGene.LENGTH, 176
 tetNig2.ensGene.LENGTH, 176
 xenTro1.genscan.LENGTH, 178
 xenTro2.ensGene.LENGTH, 178
 xenTro2.geneSymbol.LENGTH, 179
 xenTro2.genscan.LENGTH, 179
 xenTro2.refGene.LENGTH, 180
- * **internal**
 geneLenDatabase-pkg, 94
- anoCar1.ensGene.LENGTH, 8
 anoCar1.genscan.LENGTH, 9
 anoCar1.xenoRefGene.LENGTH, 9
 anoGam1.ensGene.LENGTH, 10
 anoGam1.geneid.LENGTH, 10
 anoGam1.genscan.LENGTH, 11
- apiMe11.genscan.LENGTH, 11
 apiMe12.ensGene.LENGTH, 12
 apiMe12.geneid.LENGTH, 12
 apiMe12.genscan.LENGTH, 13
 ap1Ca11.xenoRefGene.LENGTH, 13
- bosTau2.geneid.LENGTH, 14
 bosTau2.geneSymbol.LENGTH, 14
 bosTau2.genscan.LENGTH, 15
 bosTau2.refGene.LENGTH, 15
 bosTau2.sgpGene.LENGTH, 16
 bosTau3.ensGene.LENGTH, 16
 bosTau3.geneid.LENGTH, 17
 bosTau3.geneSymbol.LENGTH, 17
 bosTau3.genscan.LENGTH, 18
 bosTau3.refGene.LENGTH, 18
 bosTau3.sgpGene.LENGTH, 19
 bosTau4.ensGene.LENGTH, 19
 bosTau4.geneSymbol.LENGTH, 20
 bosTau4.genscan.LENGTH, 20
 bosTau4.nscanGene.LENGTH, 21
 bosTau4.refGene.LENGTH, 21
 braFlo1.xenoRefGene.LENGTH, 22
- caeJap1.xenoRefGene.LENGTH, 22
 caePb1.xenoRefGene.LENGTH, 23
 caePb2.xenoRefGene.LENGTH, 23
 caeRem2.xenoRefGene.LENGTH, 24
 caeRem3.xenoRefGene.LENGTH, 24
 calJac1.genscan.LENGTH, 25
 calJac1.nscanGene.LENGTH, 25
 calJac1.xenoRefGene.LENGTH, 26
 canFam1.ensGene.LENGTH, 26
 canFam1.geneSymbol.LENGTH, 27
 canFam1.genscan.LENGTH, 27
 canFam1.nscanGene.LENGTH, 28
 canFam1.refGene.LENGTH, 28
 canFam1.xenoRefGene.LENGTH, 29
 canFam2.ensGene.LENGTH, 29
 canFam2.geneSymbol.LENGTH, 30
 canFam2.genscan.LENGTH, 30
 canFam2.nscanGene.LENGTH, 31
 canFam2.refGene.LENGTH, 31
 canFam2.xenoRefGene.LENGTH, 32
 cavPor3.ensGene.LENGTH, 32
 cavPor3.genscan.LENGTH, 33
 cavPor3.nscanGene.LENGTH, 33
 cavPor3.xenoRefGene.LENGTH, 34
 cb1.xenoRefGene.LENGTH, 34
 cb3.xenoRefGene.LENGTH, 35
 ce2.geneid.LENGTH, 35
 ce2.geneSymbol.LENGTH, 36
 ce2.refGene.LENGTH, 36

- ce4.geneSymbol.LENGTH, 37
 ce4.refGene.LENGTH, 37
 ce4.xenoRefGene.LENGTH, 38
 ce6.ensGene.LENGTH, 38
 ce6.geneSymbol.LENGTH, 39
 ce6.refGene.LENGTH, 39
 ce6.xenoRefGene.LENGTH, 40
 ci1.geneSymbol.LENGTH, 40
 ci1.refGene.LENGTH, 41
 ci1.xenoRefGene.LENGTH, 41
 ci2.ensGene.LENGTH, 42
 ci2.geneSymbol.LENGTH, 42
 ci2.refGene.LENGTH, 43
 ci2.xenoRefGene.LENGTH, 43

 danRer3.ensGene.LENGTH, 44
 danRer3.geneSymbol.LENGTH, 44
 danRer3.refGene.LENGTH, 45
 danRer4.ensGene.LENGTH, 45
 danRer4.geneSymbol.LENGTH, 46
 danRer4.genscan.LENGTH, 46
 danRer4.nscanGene.LENGTH, 47
 danRer4.refGene.LENGTH, 47
 danRer5.ensGene.LENGTH, 48
 danRer5.geneSymbol.LENGTH, 48
 danRer5.refGene.LENGTH, 49
 danRer5.vegaGene.LENGTH, 49
 danRer5.vegaPseudoGene.LENGTH, 50
 danRer6.ensGene.LENGTH, 50
 danRer6.geneSymbol.LENGTH, 51
 danRer6.refGene.LENGTH, 51
 danRer6.xenoRefGene.LENGTH, 52
 dm1.geneSymbol.LENGTH, 52
 dm1.genscan.LENGTH, 53
 dm1.refGene.LENGTH, 53
 dm2.geneid.LENGTH, 54
 dm2.geneSymbol.LENGTH, 54
 dm2.genscan.LENGTH, 55
 dm2.nscanGene.LENGTH, 55
 dm2.refGene.LENGTH, 56
 dm3.geneSymbol.LENGTH, 56
 dm3.nscanPasaGene.LENGTH, 57
 dm3.refGene.LENGTH, 57
 downloadLengthFromUCSC, 8–57, 58, 59–170,
 172–176, 178–180
 dp2.genscan.LENGTH, 59
 dp2.xenoRefGene.LENGTH, 59
 dp3.geneid.LENGTH, 60
 dp3.genscan.LENGTH, 60
 dp3.xenoRefGene.LENGTH, 61
 droAna1.geneid.LENGTH, 61
 droAna1.genscan.LENGTH, 62
 droAna1.xenoRefGene.LENGTH, 62

 droAna2.genscan.LENGTH, 63
 droAna2.xenoRefGene.LENGTH, 63
 droEre1.genscan.LENGTH, 64
 droEre1.xenoRefGene.LENGTH, 64
 droGri1.genscan.LENGTH, 65
 droGri1.xenoRefGene.LENGTH, 65
 droMoj1.geneid.LENGTH, 66
 droMoj1.genscan.LENGTH, 66
 droMoj1.xenoRefGene.LENGTH, 67
 droMoj2.genscan.LENGTH, 67
 droMoj2.xenoRefGene.LENGTH, 68
 droPer1.genscan.LENGTH, 68
 droPer1.xenoRefGene.LENGTH, 69
 droSec1.genscan.LENGTH, 69
 droSec1.xenoRefGene.LENGTH, 70
 droSim1.geneid.LENGTH, 70
 droSim1.genscan.LENGTH, 71
 droSim1.xenoRefGene.LENGTH, 71
 droVir1.geneid.LENGTH, 72
 droVir1.genscan.LENGTH, 72
 droVir1.xenoRefGene.LENGTH, 73
 droVir2.genscan.LENGTH, 73
 droVir2.xenoRefGene.LENGTH, 74
 droYak1.geneid.LENGTH, 74
 droYak1.genscan.LENGTH, 75
 droYak1.xenoRefGene.LENGTH, 75
 droYak2.genscan.LENGTH, 76
 droYak2.xenoRefGene.LENGTH, 76

 equCab1.geneid.LENGTH, 77
 equCab1.geneSymbol.LENGTH, 77
 equCab1.nscanGene.LENGTH, 78
 equCab1.refGene.LENGTH, 78
 equCab1.sgpGene.LENGTH, 79
 equCab2.ensGene.LENGTH, 79
 equCab2.geneSymbol.LENGTH, 80
 equCab2.nscanGene.LENGTH, 80
 equCab2.refGene.LENGTH, 81
 equCab2.xenoRefGene.LENGTH, 81

 felCat3.ensGene.LENGTH, 82
 felCat3.geneid.LENGTH, 82
 felCat3.geneSymbol.LENGTH, 83
 felCat3.genscan.LENGTH, 83
 felCat3.nscanGene.LENGTH, 84
 felCat3.refGene.LENGTH, 84
 felCat3.sgpGene.LENGTH, 85
 felCat3.xenoRefGene.LENGTH, 85
 fr1.ensGene.LENGTH, 86
 fr1.genscan.LENGTH, 86
 fr2.ensGene.LENGTH, 87

 galGal2.ensGene.LENGTH, 87

- galGal2.geneid.LENGTH, 88
- galGal2.geneSymbol.LENGTH, 88
- galGal2.genscan.LENGTH, 89
- galGal2.refGene.LENGTH, 89
- galGal2.sgpGene.LENGTH, 90
- galGal3.geneid.LENGTH, 90
- galGal3.geneSymbol.LENGTH, 91
- galGal3.genscan.LENGTH, 91
- galGal3.nscanGene.LENGTH, 92
- galGal3.refGene.LENGTH, 92
- galGal3.xenoRefGene.LENGTH, 93
- gasAcu1.ensGene.LENGTH, 93
- gasAcu1.nscanGene.LENGTH, 94
- geneLenDataBase (geneLenDatabase-pkg), 94
- geneLenDataBase-package (geneLenDatabase-pkg), 94
- geneLenDatabase-pkg, 94
- hg16.acembly.LENGTH, 95
- hg16.ensGene.LENGTH, 95
- hg16.exoniphy.LENGTH, 96
- hg16.geneid.LENGTH, 96
- hg16.geneSymbol.LENGTH, 97
- hg16.genscan.LENGTH, 97
- hg16.knownGene.LENGTH, 98
- hg16.refGene.LENGTH, 98
- hg16.sgpGene.LENGTH, 99
- hg17.acembly.LENGTH, 99
- hg17.acescan.LENGTH, 100
- hg17.ccdsGene.LENGTH, 100
- hg17.ensGene.LENGTH, 101
- hg17.exoniphy.LENGTH, 101
- hg17.geneid.LENGTH, 102
- hg17.geneSymbol.LENGTH, 102
- hg17.genscan.LENGTH, 103
- hg17.knownGene.LENGTH, 103
- hg17.refGene.LENGTH, 104
- hg17.sgpGene.LENGTH, 104
- hg17.vegaGene.LENGTH, 105
- hg17.vegaPseudoGene.LENGTH, 105
- hg17.xenoRefGene.LENGTH, 106
- hg18.acembly.LENGTH, 106
- hg18.acescan.LENGTH, 107
- hg18.ccdsGene.LENGTH, 107
- hg18.ensGene.LENGTH, 108
- hg18.exoniphy.LENGTH, 108
- hg18.geneid.LENGTH, 109
- hg18.geneSymbol.LENGTH, 109
- hg18.genscan.LENGTH, 110
- hg18.knownGene.LENGTH, 110
- hg18.knownGeneOld3.LENGTH, 111
- hg18.refGene.LENGTH, 111
- hg18.sgpGene.LENGTH, 112
- hg18.sibGene.LENGTH, 112
- hg18.xenoRefGene.LENGTH, 113
- hg19.ccdsGene.LENGTH, 113
- hg19.ensGene.LENGTH, 114
- hg19.exoniphy.LENGTH, 114
- hg19.geneSymbol.LENGTH, 115
- hg19.knownGene.LENGTH, 115
- hg19.nscanGene.LENGTH, 116
- hg19.refGene.LENGTH, 116
- hg19.xenoRefGene.LENGTH, 117
- loxAfr3.xenoRefGene.LENGTH, 117
- mm7.ensGene.LENGTH, 118
- mm7.geneid.LENGTH, 118
- mm7.geneSymbol.LENGTH, 119
- mm7.genscan.LENGTH, 119
- mm7.knownGene.LENGTH, 120
- mm7.refGene.LENGTH, 120
- mm7.sgpGene.LENGTH, 121
- mm7.xenoRefGene.LENGTH, 121
- mm8.ccdsGene.LENGTH, 122
- mm8.ensGene.LENGTH, 122
- mm8.geneid.LENGTH, 123
- mm8.geneSymbol.LENGTH, 123
- mm8.genscan.LENGTH, 124
- mm8.knownGene.LENGTH, 124
- mm8.nscanGene.LENGTH, 125
- mm8.refGene.LENGTH, 125
- mm8.sgpGene.LENGTH, 126
- mm8.sibGene.LENGTH, 126
- mm8.xenoRefGene.LENGTH, 127
- mm9.acembly.LENGTH, 127
- mm9.ccdsGene.LENGTH, 128
- mm9.ensGene.LENGTH, 128
- mm9.exoniphy.LENGTH, 129
- mm9.geneid.LENGTH, 129
- mm9.geneSymbol.LENGTH, 130
- mm9.genscan.LENGTH, 130
- mm9.knownGene.LENGTH, 131
- mm9.nscanGene.LENGTH, 131
- mm9.refGene.LENGTH, 132
- mm9.sgpGene.LENGTH, 132
- mm9.xenoRefGene.LENGTH, 133
- monDom1.genscan.LENGTH, 133
- monDom4.ensGene.LENGTH, 134
- monDom4.geneSymbol.LENGTH, 134
- monDom4.genscan.LENGTH, 135
- monDom4.nscanGene.LENGTH, 135
- monDom4.refGene.LENGTH, 136
- monDom4.xenoRefGene.LENGTH, 136
- monDom5.ensGene.LENGTH, 137

- monDom5.geneSymbol.LENGTH, 137
- monDom5.genscan.LENGTH, 138
- monDom5.nscanGene.LENGTH, 138
- monDom5.refGene.LENGTH, 139
- monDom5.xenoRefGene.LENGTH, 139

- ornAna1.ensGene.LENGTH, 140
- ornAna1.geneSymbol.LENGTH, 140
- ornAna1.refGene.LENGTH, 141
- ornAna1.xenoRefGene.LENGTH, 141
- oryLat2.ensGene.LENGTH, 142
- oryLat2.geneSymbol.LENGTH, 142
- oryLat2.refGene.LENGTH, 143
- oryLat2.xenoRefGene.LENGTH, 143

- panTro1.ensGene.LENGTH, 144
- panTro1.geneid.LENGTH, 144
- panTro1.genscan.LENGTH, 145
- panTro1.xenoRefGene.LENGTH, 145
- panTro2.ensGene.LENGTH, 146
- panTro2.geneSymbol.LENGTH, 146
- panTro2.genscan.LENGTH, 147
- panTro2.nscanGene.LENGTH, 147
- panTro2.refGene.LENGTH, 148
- panTro2.xenoRefGene.LENGTH, 148
- petMar1.xenoRefGene.LENGTH, 149
- ponAbe2.ensGene.LENGTH, 149
- ponAbe2.geneSymbol.LENGTH, 150
- ponAbe2.genscan.LENGTH, 150
- ponAbe2.nscanGene.LENGTH, 151
- ponAbe2.refGene.LENGTH, 151
- ponAbe2.xenoRefGene.LENGTH, 152
- priPac1.xenoRefGene.LENGTH, 152

- rheMac2.ensGene.LENGTH, 153
- rheMac2.geneid.LENGTH, 153
- rheMac2.geneSymbol.LENGTH, 154
- rheMac2.nscanGene.LENGTH, 154
- rheMac2.refGene.LENGTH, 155
- rheMac2.sgpGene.LENGTH, 155
- rheMac2.xenoRefGene.LENGTH, 156
- rn3.ensGene.LENGTH, 156
- rn3.geneid.LENGTH, 157
- rn3.geneSymbol.LENGTH, 157
- rn3.genscan.LENGTH, 158
- rn3.knownGene.LENGTH, 158
- rn3.nscanGene.LENGTH, 159
- rn3.refGene.LENGTH, 159
- rn3.sgpGene.LENGTH, 160
- rn3.xenoRefGene.LENGTH, 160
- rn4.ensGene.LENGTH, 161
- rn4.geneid.LENGTH, 161
- rn4.geneSymbol.LENGTH, 162
- rn4.genscan.LENGTH, 162
- rn4.knownGene.LENGTH, 163
- rn4.nscanGene.LENGTH, 163
- rn4.refGene.LENGTH, 164
- rn4.sgpGene.LENGTH, 164
- rn4.xenoRefGene.LENGTH, 165

- sacCer1.ensGene.LENGTH, 165
- sacCer2.ensGene.LENGTH, 166
- strPur1.geneSymbol.LENGTH, 166
- strPur1.genscan.LENGTH, 167
- strPur1.refGene.LENGTH, 167
- strPur1.xenoRefGene.LENGTH, 168
- strPur2.geneSymbol.LENGTH, 168
- strPur2.genscan.LENGTH, 169
- strPur2.refGene.LENGTH, 169
- strPur2.xenoRefGene.LENGTH, 170
- supportedGeneIDs, 58, 170
- supportedGenomes, 58, 171

- taeGut1.ensGene.LENGTH, 171
- taeGut1.geneSymbol.LENGTH, 172
- taeGut1.genscan.LENGTH, 172
- taeGut1.nscanGene.LENGTH, 173
- taeGut1.refGene.LENGTH, 173
- taeGut1.xenoRefGene.LENGTH, 174
- tetNig1.ensGene.LENGTH, 174
- tetNig1.geneid.LENGTH, 175
- tetNig1.genscan.LENGTH, 175
- tetNig1.nscanGene.LENGTH, 176
- tetNig2.ensGene.LENGTH, 176

- unfactor, 177

- xenTro1.genscan.LENGTH, 178
- xenTro2.ensGene.LENGTH, 178
- xenTro2.geneSymbol.LENGTH, 179
- xenTro2.genscan.LENGTH, 179
- xenTro2.refGene.LENGTH, 180