

Package ‘seqsetvis’

April 10, 2025

Type Package

Title Set Based Visualizations for Next-Gen Sequencing Data

Version 1.27.2

Description seqsetvis enables the visualization and analysis of sets of genomic sites in next gen sequencing data. Although seqsetvis was designed for the comparison of multiple ChIP-seq samples, this package is domain-agnostic and allows the processing of multiple genomic coordinate files (bed-like files) and signal files (bigwig files pileups from bam file). seqsetvis has multiple functions for fetching data from regions into a tidy format for analysis in data.table or tidyverse and visualization via ggplot2.

License MIT + file LICENSE

Encoding UTF-8

Suggests BiocFileCache, BiocManager, BiocStyle, ChIPpeakAnno, covr, knitr, rmarkdown, testthat

Depends R (>= 4.3), ggplot2

Imports cowplot, data.table, eulerr, GenomeInfoDb, GenomicAlignments, GenomicRanges, ggplotify, grDevices, grid, IRanges, limma, methods, pbapply, pbmcapply, png, RColorBrewer, Rsamtools, rtracklayer, S4Vectors, scales, stats, UpSetR

RoxygenNote 7.3.1

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

NeedsCompilation no

biocViews Software, ChIPSeq, MultipleComparison, Sequencing, Visualization

git_url <https://git.bioconductor.org/packages/seqsetvis>

git_branch devel

git_last_commit ae10577

git_last_commit_date 2024-12-09

Repository Bioconductor 3.21

Date/Publication 2025-04-09

Author Joseph R Boyd [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-8969-9676>>)

Maintainer Joseph R Boyd <jrboyd@uvm.edu>

Contents

| | |
|--|----|
| seqsetvis-package | 4 |
| .expand_cigar_dt | 4 |
| .expand_cigar_dt_recursive | 5 |
| .rm_dupes | 5 |
| .rm_dupesPE | 6 |
| add_cluster_annotation | 6 |
| append_ynorm | 8 |
| applyMovingAverage | 9 |
| applySpline | 10 |
| assemble_heatmap_cluster_bars | 11 |
| Bcell_peaks | 12 |
| calc_norm_factors | 12 |
| centerAtMax | 13 |
| centerFixedSizeGRanges | 15 |
| centerGRangesAtMax | 16 |
| chromHMM_demo_bw_states_gr | 17 |
| chromHMM_demo_chain_url | 17 |
| chromHMM_demo_data | 18 |
| chromHMM_demo_overlaps_gr | 18 |
| chromHMM_demo_segmentation_url | 19 |
| chromHMM_demo_state_colors | 19 |
| chromHMM_demo_state_total_widths | 20 |
| clusteringKmeans | 20 |
| clusteringKmeansNestedHclust | 21 |
| col2hex | 22 |
| collapse_gr | 23 |
| convert_collapsed_coord | 24 |
| copy_clust_info | 25 |
| crossCorrByRle | 26 |
| CTCF_in_10a_bigWig_urls | 27 |
| CTCF_in_10a_data | 27 |
| CTCF_in_10a_narrowPeak_grs | 28 |
| CTCF_in_10a_narrowPeak_urls | 28 |
| CTCF_in_10a_overlaps_gr | 29 |
| CTCF_in_10a_profiles_dt | 29 |
| CTCF_in_10a_profiles_gr | 30 |
| easyLoad_bed | 30 |
| easyLoad_broadPeak | 31 |
| easyLoad_FUN | 32 |

| | |
|-----------------------------|----|
| easyLoad_IDRmerged | 33 |
| easyLoad_narrowPeak | 33 |
| easyLoad_seacr | 34 |
| expandCigar | 35 |
| fetchBam | 36 |
| findMaxPos | 37 |
| fragLen_calcStranded | 38 |
| fragLen_fromMacs2Xls | 39 |
| getReadLength | 39 |
| get_mapped_reads | 40 |
| ggellipse | 40 |
| harmonize_seqlengths | 42 |
| make_clustering_matrix | 43 |
| merge_clusters | 44 |
| prepare_fetch_GRanges | 45 |
| prepare_fetch_GRanges_names | 46 |
| prepare_fetch_GRanges_width | 47 |
| quantileGRangesWidth | 48 |
| reorder_clusters_hclust | 49 |
| reorder_clusters_manual | 50 |
| reorder_clusters_stepdown | 51 |
| reverse_clusters | 52 |
| safeBrew | 53 |
| set_list2memb | 54 |
| shift_anchor | 55 |
| split_cluster | 55 |
| ssvAnnotateSubjectGRanges | 56 |
| ssvConsensusIntervalSets | 58 |
| ssvFactorizeMembTable | 59 |
| ssvFeatureBars | 60 |
| ssvFeatureBinaryHeatmap | 61 |
| ssvFeatureEuler | 62 |
| ssvFeaturePie | 63 |
| ssvFeatureUpset | 64 |
| ssvFeatureVenn | 65 |
| ssvFetchBam | 66 |
| ssvFetchBam.single | 69 |
| ssvFetchBamPE | 70 |
| ssvFetchBamPE.RNA | 72 |
| ssvFetchBamPE.single | 74 |
| ssvFetchBigwig | 76 |
| ssvFetchBigwig.single | 77 |
| ssvFetchGRanges | 79 |
| ssvFetchSignal | 80 |
| ssvMakeMembTable | 82 |
| ssvOverlapIntervalSets | 84 |
| ssvSignalBandedQuantiles | 85 |
| ssvSignalClustering | 86 |

| | |
|--|-----|
| ssvSignalHeatmap | 88 |
| ssvSignalHeatmap.ClusterBars | 91 |
| ssvSignalLineplot | 93 |
| ssvSignalLineplotAgg | 95 |
| ssvSignalScatterplot | 96 |
| ssv_mclapply | 97 |
| test_peaks | 98 |
| viewGRangesWinSample_dt | 99 |
| viewGRangesWinSummary_dt | 100 |
| within_clust_sort | 102 |

Index 104

seqsetvis-package *easy awesome peak set vis TESTING seqsetvis allows you to...*

Description

2 steps [ssvOverlapIntervalSets](#). [ssvFetchBigwig](#). Otherwise refer to the vignettes to see

Author(s)

Maintainer: Joseph R Boyd <jrboyd@uvm.edu> ([ORCID](#))

.expand_cigar_dt *Expand intermediate bam fetch by cigar codes*

Description

see [sam specs](#) for cigar details

Usage

```
.expand_cigar_dt(cigar_dt, op_2count = c("M", "D", "=", "X"))
```

Arguments

| | |
|-----------|--|
| cigar_dt | data.table with 5 required named columns in any order. c("which_label", "seq-names", "strand", "start", "cigar") |
| op_2count | Cigar codes to count. Default is alignment (M), deletion (D), match (=), and mismatch (X). Other useful codes may be skipped regions for RNA splicing (N). The locations of any insterions (I) or clipping/padding (S, H, or P) will be a single bp immediately before the interval. |

Value

data.table with cigar entries expanded

.expand_cigar_dt_recursive

Expand intermediate bam fetch by cigar codes

Description

see [sam specs](#) for cigar details

Usage

```
.expand_cigar_dt_recursive(cigar_dt)
```

Arguments

cigar_dt data.table with 5 required named columns in any order. c("which_label", "seq-names", "strand", "start", "cigar")

Value

data.table with cigar entries expanded

.rm_dupes

Remove duplicate reads based on stranded start position. This is an over-simplification. For better duplicate handling, duplicates must be marked in bam and flag passed to fetchBam() ... for ScanBamParam

Description

flag = scanBamFlag(isDuplicate = FALSE)

Usage

```
.rm_dupes(reads_dt, max_dupes)
```

Arguments

reads_dt data.table of reads as loaded by fetchBam
max_dupes maximum allowed positional duplicates

Value

reads_dt with duplicated reads over max_dupes removed

| | |
|--------------------------|--|
| <code>.rm_dupesPE</code> | <i>Remove duplicate paired-end reads based on start and end position. This is an over-simplification. For better duplicate handling, duplicates must be marked in bam and flag passed to <code>fetchBamPE()</code> ... for <code>ScanBamParam</code></i> |
|--------------------------|--|

Description

```
flag = scanBamFlag(isDuplicate = FALSE)
```

Usage

```
.rm_dupesPE(reads_dt, max_dupes)
```

Arguments

| | |
|------------------------|--|
| <code>reads_dt</code> | data.table of reads as loaded by <code>fetchBamPE</code> |
| <code>max_dupes</code> | maximum allowed positional duplicates |

Value

`reads_dt` with duplicated reads over `max_dupes` removed

| | |
|-------------------------------------|-------------------------------|
| <code>add_cluster_annotation</code> | <i>add_cluster_annotation</i> |
|-------------------------------------|-------------------------------|

Description

adds rectangle boxes proportional to cluster sizes of heatmap with optional labels.

Usage

```
add_cluster_annotation(
  cluster_ids,
  p = NULL,
  xleft = 0,
  xright = 1,
  rect_colors = c("black", "gray"),
  text_colors = rev(rect_colors),
  show_labels = TRUE,
  label_angle = 0,
  row_ = "id",
  cluster_ = "cluster_id"
)
```

Arguments

| | |
|-------------|---|
| cluster_ids | Vector of cluster ids for each item in heatmap. Should be sorted by plot order for heatmap. |
| p | Optionally an existing ggplot to add annotation to. |
| xleft | left side of cluster annotation rectangles. Default is 0. |
| xright | right side of cluster annotation rectangles. Default is 1. |
| rect_colors | colors of rectangle fill, repeat to match number of clusters. Default is c("black", "gray"). |
| text_colors | colors of text, repeat to match number of clusters. Default is reverse of rect_colors. |
| show_labels | logical, should rectangles be labelled with cluster identity. Default is TRUE. |
| label_angle | angle to add clusters labels at. Default is 0, which is horizontal. |
| row_ | variable name mapped to row, likely id or gene name for ngs data. Default is "id" and works with ssvFetch* outputs. |
| cluster_ | variable name to use for cluster info. Default is "cluster_id". |

Value

A ggplot with cluster annotations added.

Examples

```

data(CTCF_in_10a_profiles_dt)
#simplest uses
add_cluster_annotation(factor(c(rep("A", 3), "B")))
p = ggplot() + coord_cartesian(xlim = c(0,10))
add_cluster_annotation(factor(c(rep("A", 3), "B")), p)

#intended use with ssvSignalHeatmap
clust_dt = ssvSignalClustering(CTCF_in_10a_profiles_dt, nclust = 3)
assign_dt = unique(clust_dt[, .(id, cluster_id)])[order(id)]
p_heat = ssvSignalHeatmap(clust_dt, show_clusterBars = FALSE)
add_cluster_annotation(assign_dt$cluster_id, p_heat,
  xleft = -500, xright = -360, rect_colors = rainbow(3), text_colors = "gray")

#when colors are named, the names are used rather than just the order
rect_colors = safeBrew(assign_dt$cluster_id)
text_colors = safeBrew(assign_dt$cluster_id, "greys")
p_clusters = add_cluster_annotation(assign_dt$cluster_id,
  rect_colors = rect_colors, text_colors = text_colors)
#specialized use as plot outside of heatmap
p1 = assemble_heatmap_clusterBars(plots = list(p_clusters, p_heat), rel_widths = c(1, 3))

#when colors are named, the names are used rather than just the order
#these plots will be identical even though order of colors changes.
rect_colors = rect_colors[c(2, 3, 1)]
text_colors = text_colors[c(3, 1, 2)]
p_clusters = add_cluster_annotation(assign_dt$cluster_id,
  rect_colors = rect_colors, text_colors = text_colors)

```

```
#specialized use as plot outside of heatmap
p2 = assemble_heatmap_cluster_bars(plots = list(p_clusters, p_heat), rel_widths = c(1, 3))

cowplot::plot_grid(p1, p2, ncol = 1)
```

 append_ynorm

append_ynorm

Description

see [calc_norm_factors](#) for normalization details.

Usage

```
append_ynorm(
  full_dt,
  value_ = "y",
  cap_value_ = "y_cap_value",
  norm_value_ = "y_norm",
  by1 = "id",
  by2 = "sample",
  aggFUN1 = max,
  aggFUN2 = function(x) quantile(x, 0.95),
  cap_dt = NULL,
  do_not_cap = FALSE,
  do_not_scaleTo1 = FALSE,
  force_append = FALSE
)
```

Arguments

| | |
|-----------------|--|
| full_dt | a data.table, as returned by <code>ssvFetch*(..., return_data.table = TRUE)</code> . |
| value_ | character, attribute in full_dt to normalzie. |
| cap_value_ | character, new attribute name specifying values to cap to. |
| norm_value_ | character, new attribute name specifying normalized values. |
| by1 | character vector, specifies attributes relevant to step 1. |
| by2 | character vector, specifies attributes relevant to step 1 and 2. |
| aggFUN1 | function called on value_ with by = c(by1, by2) in step 1. |
| aggFUN2 | function called on result of aggFUN1 with by = by2 in step 2. |
| cap_dt | optionally, provide user generated by2 to cap_value_ mapping |
| do_not_cap | if TRUE, normalized values are not capped to 1. Default is FALSE. |
| do_not_scaleTo1 | if TRUE, normalized values are not scaled to 1. Default is FALSE. |
| force_append | if TRUE, any previous cap_value or norm_value is overridden. Default is FALSE. |

Value

data.table, full_dt with cap_value_ and norm_value_ values appended.

Examples

```
data(CTCF_in_10a_profiles_dt)
append_ynorm(CTCF_in_10a_profiles_dt)
append_ynorm(CTCF_in_10a_profiles_dt,
  aggFUN1 = mean, aggFUN2 = function(x)quantile(x, .5))
```

applyMovingAverage *applyMovingAverage*

Description

http://www.cookbook-r.com/Manipulating_data/Calculating_a_moving_average/

Usage

```
applyMovingAverage(
  dt,
  n,
  centered = TRUE,
  x_ = "x",
  y_ = "y",
  by_ = c("id", "sample"),
  maFun = movingAverage
)
```

Arguments

| | |
|----------|--|
| dt | a tidy data.table containing two-dimensional data |
| n | the number of samples centered: if FALSE, then average |
| centered | current sample and previous (n-1) samples if TRUE, then average symmetrically in past and future. (If n is even, use one more sample from future.) |
| x_ | the variable name of the x-values |
| y_ | the variable name of the y-values |
| by_ | optionally, any variables that provide grouping to the data. default is none. see details. |
| maFun | a function that accepts x, y, and n as arguments and returns a list of length 2 with named elements x and y. |

Value

a newly derived data.table where a movingAverage has been applied.

Examples

```

data(CTCF_in_10a_profiles_dt)
agg_dt = CTCF_in_10a_profiles_dt[, list(y = mean(y)), by = list(sample, x)]
ggplot(agg_dt) +
  geom_line(aes(x = x, y = y, color = sample))

ma_smooth = applyMovingAverage(agg_dt, n = 5,
  y_ = 'y', by_ = c('sample'))
ggplot(ma_smooth) +
  geom_line(aes(x = x, y = y, color = sample))

ma_smooth$method = "moving_average"
agg_dt$method = "none"
ggplot(rbind(ma_smooth, agg_dt)) +
  geom_line(aes(x = x, y = y, color = method)) +
  facet_wrap(~sample)

```

| | |
|-------------|---|
| applySpline | <i>applies a spline smoothing to a tidy data.table containing x and y values.</i> |
|-------------|---|

Description

applySpline Is intended for two-dimensional tidy data.tables, as returned by ssvFetchBigwig

Usage

```

applySpline(
  dt,
  n,
  x_ = "x",
  y_ = "y",
  by_ = c("id", "sample"),
  splineFun = stats::spline
)

```

Arguments

| | |
|-----------|---|
| dt | a tidy data.table containing two-dimensional data |
| n | the number of interpolation points to use per input point, see ?spline. n must be > 1. |
| x_ | the variable name of the x-values |
| y_ | the variable name of the y-values |
| by_ | optionally, any variables that provide grouping to the data. default is none. see details. |
| splineFun | a function that accepts x, y, and n as arguments and returns a list of length 2 with named elements x and y. stats::spline by default. see stats::spline for details. |

Details

by_ is quite powerful. If by_ = c('gene_id', 'sample_id'), splines will be calculated individually for each gene in each sample. alternatively if by_ = c('gene_id')

Value

a newly derived data.table that is n times longer than original.

See Also

[ssvFetchBigwig](#)

Examples

```
data(CTCF_in_10a_profiles_dt)
#data may be blockier than we'd like
ggplot(CTCF_in_10a_profiles_dt[, list(y = mean(y)), by = list(sample, x)]) +
  geom_line(aes(x = x, y = y, color = sample))

#can be smoothed by applying a spline (think twice about doing so,
#it may look prettier but may also be deceptive or misleading)

splined_smooth = applySpline(CTCF_in_10a_profiles_dt, n = 10,
  y_ = 'y', by_ = c('id', 'sample'))
ggplot(splined_smooth[, list(y = mean(y)), by = list(sample, x)]) +
  geom_line(aes(x = x, y = y, color = sample))
```

```
assemble_heatmap_cluster_bars
      assemble_heatmap_cluster_bars
```

Description

assemble_heatmap_cluster_bars

Usage

```
assemble_heatmap_cluster_bars(plots, ...)
```

Arguments

| | |
|-------|--|
| plots | list of plots as returned from ssvSignalHeatmap.ClusterBars when return_unassembled_plots = TRUE |
| ... | arguments passed to cowplot::plot_grid |

Value

A grob produced by cowplot::plot_grid

Examples

```
data(CTCF_in_10a_profiles_gr)
plots = ssvSignalHeatmap.ClusterBars(CTCF_in_10a_profiles_gr, return_unassembled_plots = TRUE)
assemble_heatmap_cluster_bars(plots)
```

| | |
|-------------|---|
| Bcell_peaks | <i>4 random peaks for paired-end data</i> |
|-------------|---|

Description

matches `system.file("extdata/Bcell_PE.mm10.bam", package = "seqsetvis")`

Format

GRanges length 4

Details

this is included only for testing `ssvFetchBamPE` functions.

Value

GRanges length 4

| | |
|-------------------|--------------------------|
| calc_norm_factors | <i>calc_norm_factors</i> |
|-------------------|--------------------------|

Description

Calculate normalization factors in a two step process:

Usage

```
calc_norm_factors(
  full_dt,
  value_ = "y",
  cap_value_ = "y_cap_value",
  by1 = "id",
  by2 = "sample",
  aggFUN1 = max,
  aggFUN2 = function(x) quantile(x, 0.95)
)
```

Arguments

| | |
|------------|---|
| full_dt | a data.table, as returned by <code>ssvFetch*(..., return_data.table. = TRUE)</code> |
| value_ | character, attribute in full_dt to normalzie. |
| cap_value_ | character, new attribute name specifying values to cap to. |
| by1 | character vector, specifies attributes relevant to step 1. |
| by2 | character vector, specifies attributes relevant to step 1 and 2. |
| aggFUN1 | function called on value_ with by = c(by1, by2) in step 1. |
| aggFUN2 | function called on result of aggFUN1 with by = by2 in step 2. |

Details

1. summarize every region for each sample (default summary function is max)
2. caclulate a value to cap each sample to based on regions (default is 95th quantile).

The uderlying assumption here is that meaningful enrichment is present at the majority of regions provided. If prevalence varies by a specific factor, say ChIP-seq targets with different characteristics - ie. when analyzing TSSes for H3K4me3 and an infrequent transcription factor it is more appropriate to specify appropriate quantile cutoffs per factor.

Value

data.table mapping by2 to cap_value_.

Examples

```
data(CTCF_in_10a_profiles_dt)
calc_norm_factors(CTCF_in_10a_profiles_dt)
calc_norm_factors(CTCF_in_10a_profiles_dt,
  aggFUN1 = mean, aggFUN2 = function(x)quantile(x, .5))
```

| | |
|-------------|---|
| centerAtMax | <i>centers profile of x and y. default is to center by region but across all samples.</i> |
|-------------|---|

Description

centerAtMax locates the coordinate x of the maximum in y and shifts x such that it is zero at max y.

Usage

```
centerAtMax(
  dt,
  x_ = "x",
  y_ = "y",
  by_ = "id",
  view_size = NULL,
  trim_to_valid = TRUE,
  check_by_dupes = TRUE,
  x_precision = 3,
  replace_x = TRUE
)
```

Arguments

| | |
|----------------|--|
| dt | data.table |
| x_ | the variable name of the x-values. default is 'x' |
| y_ | the variable name of the y-values default is 'y' |
| by_ | optionally, any variables that provide grouping to the data. default is none. see details. |
| view_size | the size in x_ to consider for finding the max of y_. if length(view_size) == 1, range will be c(-view_size, view_size). if length(view_size) > 1, range will be range(view_size). default value of NULL uses complete range of x. |
| trim_to_valid | valid x_ values are those with a set y_ value in all by_ combinations |
| check_by_dupes | default assumption is that there should be on set of x_ for a by_ instance. if this is not the case and you want to disable warnings about set this to FALSE. |
| x_precision | numerical precision of x, default is 3. |
| replace_x | logical, default TRUE. if TRUE x_ will be replaced with position relative to summit. if FALSE x_ will be preserved and x_summitPosition added. |

Details

character. by_ controls at the level of the data centering is applied. If by_ is "" or NULL, a single max position will be determined for the entire dataset. If by_ is "id" (the default) then each region will be centered individually across all samples.

Value

data.table with x (or xnew if replace_x is FALSE) shifted such that x = 0 matches the maximum y-value define by by_ grouping

Examples

```
data(CTCF_in_10a_profiles_gr)
centerAtMax(CTCF_in_10a_profiles_gr, y_ = 'y', by_ = 'id',
  check_by_dupes = FALSE)
#it's a bit clearer what's happening with trimming disabled
```

```
#but results are less useful for heatmaps etc.
centerAtMax(CTCF_in_10a_profiles_gr, y_ = 'y', by_ = 'id',
  check_by_dupes = FALSE, trim_to_valid = FALSE)
#specify view_size to limit range of x values considered, prevents
#excessive data trimming.
centerAtMax(CTCF_in_10a_profiles_gr, y_ = 'y', view_size = 100, by_ = 'id',
  check_by_dupes = FALSE)
```

centerFixedSizeGRanges

Transforms set of GRanges to all have the same size.

Description

centerFixedSizeGRanges First calculates the central coordinate of each GRange in grs and extends in both direction by half of fixed_size

Usage

```
centerFixedSizeGRanges(grs, fixed_size = 2000)
```

Arguments

| | |
|------------|--|
| grs | Set of GRanges with inconsistent and/or incorrect size |
| fixed_size | The final width of each GRange returned. |

Value

Set of GRanges after resizing all input GRanges, either shortened or lengthened as required to match fixed_size

Examples

```
library(GenomicRanges)
grs = GRanges("chr1", IRanges(1:10+100, 1:10*3+100))
centered_grs = centerFixedSizeGRanges(grs, 10)
width(centered_grs)
```

centerGRangesAtMax *Centers query GRanges at maximum signal in prof_dt.*

Description

Centers query GRanges at maximum signal in prof_dt.

Usage

```
centerGRangesAtMax(
  prof_dt,
  qgr,
  x_ = "x",
  y_ = "y",
  by_ = "id",
  width = 1,
  view_size = NULL
)
```

Arguments

| | |
|-----------|--|
| prof_dt | a GRanges or data.table as returned by ssvFetch*. |
| qgr | the GRanges used to query ssvFetch* as the qgr argument. |
| x_ | positional variable. Should almost always be the default, "x". |
| y_ | the signal value variable. Likely the default value of "y" but could be "y_norm" if append_ynorm was applied to data. |
| by_ | region identifier variable. Should almost always be the default, "id". |
| width | Desired width of final regions. Default is 1. |
| view_size | the size in x_ to consider for finding the max of y_. if length(view_size) == 1, range will be c(-view_size, view_size). if length(view_size) > 1, range will be range(view_size). default value of NULL uses complete range of x. |

Value

a GRanges with same mcols as qgr that has been centered based on signal in prof_dt and with regions of specified width.

Examples

```
data(CTCF_in_10a_overlaps_gr)
data(CTCF_in_10a_profiles_gr)
data(CTCF_in_10a_profiles_dt)
centerGRangesAtMax(CTCF_in_10a_profiles_dt, CTCF_in_10a_overlaps_gr)
centerGRangesAtMax(CTCF_in_10a_profiles_gr, CTCF_in_10a_overlaps_gr)

centerGRangesAtMax(CTCF_in_10a_profiles_gr, CTCF_in_10a_overlaps_gr, view_size = 50)
```

chromHMM_demo_bw_states_gr

MCF10A CTCF profiles at 20 windows per chromHMM state, hg38.

Description

MCF10A CTCF profiles at 20 windows per chromHMM state, hg38.

Format

a GRanges object of length 4000 with 5 metadata columns sufficient for use with ggplot2

Details

part of [chromHMM_demo_data](#)

the result of `ssvFetchBigwig()` on the MCF10A_CTCF_FE.bw near 20 randomly selected windows per chromHMM state.

Value

a GRanges object of length 4000 with 5 metadata columns sufficient for use with ggplot2

chromHMM_demo_chain_url

URL to download hg19ToHg38 liftover chain from UCSC

Description

URL to download hg19ToHg38 liftover chain from UCSC

Format

a character containing a URL

Details

file is gzipped .txt

part of [chromHMM_demo_data](#)

Value

a character containing a URL

chromHMM_demo_data *chromHMM state segmentation in the MCF7 cell line*

Description

Vignette data for seqsetvis was downloaded directly from GEO series [GSE57498](#). This data is the state segmentation by chromHMM in the MCF7 cell line. chromHMM creates a hidden markov model by integrating several ChIP-seq samples, in this case:

- MCF7_H3K27ac_ChIP-Seq
- MCF7_H3K27me3_ChIP-Seq
- MCF7_H3K4me1_ChIP-Seq
- MCF7_H3K4me3_ChIP-Seq
- MCF7_RNApolIIp_ChIP-Seq

Data from GEO series [GSE57498](#) is from the publication [Taberlay PC et al. 2014](#)

Details

Contains:

- [chromHMM_demo_overlaps_gr](#)
- [chromHMM_demo_bw_states_gr](#)
- [chromHMM_demo_state_total_widths](#)
- [chromHMM_demo_state_colors](#)
- [chromHMM_demo_segmentation_url](#)
- [chromHMM_demo_chain_url](#)

chromHMM_demo_overlaps_gr
overlap of MCF10A CTCF with MCF7 chromHMM states, hg38.

Description

overlap of MCF10A CTCF with MCF7 chromHMM states, hg38.

Format

a GRanges object of length 98 with 10 logical metadata columns, 1 per state.

Details

part of [chromHMM_demo_data](#)

the result of `ssvOverlapIntervalSets()` on MCF10A CTCF peaks and MCF7 chromHMM states with `use_first = TRUE`

first (the MCF10A peaks) and `no_hit` columns have been removed each remaining column represents MCF10A peaks overlapping with a state.

Value

a GRanges object of length 98 with 10 logical metadata columns, 1 per state.

chromHMM_demo_segmentation_url

URL to download hg19 MCF7 chromHMM segmentation

Description

URL to download hg19 MCF7 chromHMM segmentation

Format

a character containing a URL

Details

file is gzipped bed with name, score, itemRgb and thick meta columns

part of [chromHMM_demo_data](#)

Value

a character containing a URL

chromHMM_demo_state_colors

original state name to color mappings stored in segmentation bed

Description

original state name to color mappings stored in segmentation bed

Format

a named character vector mapping states to hex colors

Details

part of [chromHMM_demo_data](#)

Value

a named character vector mapping states to hex colors

chromHMM_demo_state_total_widths
state name to total width mappings, hg38

Description

state name to total width mappings, hg38

Format

named numeric of total widths per state

Details

part of [chromHMM_demo_data](#)

Value

named numeric of total widths per state

clusteringKmeans *perform kmeans clustering on matrix rows and return reordered matrix along with order matched cluster assignments. clusters are sorted using hclust on centers*

Description

perform kmeans clustering on matrix rows and return reordered matrix along with order matched cluster assignments. clusters are sorted using hclust on centers

Usage

```
clusteringKmeans(mat, nclust, centroids = NULL, iter.max = 30)
```

Arguments

| | |
|-----------|--|
| mat | numeric matrix to cluster. |
| nclust | the number of clusters. |
| centroids | optional matrix with same columns as mat and one centroid per row to base clusters off of. Overrides any setting to nclust. Default of NULL results in randomly initialized k-means. |
| iter.max | Number of max iterations to allow for k-means. Default is 30. |

Value

data.table with group__ variable indicating cluster membership and id__ variable that is a factor indicating order based on within cluster similarity

Examples

```
data(CTCF_in_10a_profiles_dt)
dt = data.table::copy(CTCF_in_10a_profiles_dt)
mat = data.table::dcast(dt, id ~ sample + x, value.var = "y" )
rn = mat$id
mat = as.matrix(mat[,-1])
rownames(mat) = rn
clust_dt = clusteringKmeans(mat, nclust = 3)
dt = merge(dt, clust_dt[, .(id = id__, group = group__)])
dt$id = factor(dt$id, levels = clust_dt$id)
dt[order(id)]
```

clusteringKmeansNestedHclust

perform kmeans clustering on matrix rows and return reordered matrix along with order matched cluster assignments clusters are sorted using hclust on centers the contents of each cluster are sorted using hclust

Description

perform kmeans clustering on matrix rows and return reordered matrix along with order matched cluster assignments clusters are sorted using hclust on centers the contents of each cluster are sorted using hclust

Usage

```
clusteringKmeansNestedHclust(
  mat,
  nclust,
  within_order_strategy = valid_sort_strategies[2],
  centroids = NULL,
  manual_mapping = NULL,
  iter.max = 30
)
```

Arguments

| | |
|------------------------------------|--|
| <code>mat</code> | A wide format matrix |
| <code>nclust</code> | the number of clusters |
| <code>within_order_strategy</code> | one of "hclust", "sort", "right", "left", "reverse". If "hclust", hierarchical clustering will be used. If "sort", a simple decreasing sort of <code>rosSums</code> . If "left", will attempt to put high signal on left ("right" is opposite). If "reverse" reverses existing order (should only be used after meaningful order imposed). |
| <code>centroids</code> | optional matrix with same columns as <code>mat</code> and one centroid per row to base clusters off of. Overrides any setting to <code>nclust</code> . Default of <code>NULL</code> results in randomly initialized k-means. |
| <code>manual_mapping</code> | optional named vector manually specifying cluster assignments. names should be item ids and values should be cluster names the items are assigned to. Default of <code>NULL</code> allows clustering to proceed. |
| <code>iter.max</code> | Number of max iterations to allow for k-means. Default is 30. |

Value

data.table with 2 columns of cluster info. `id__` column corresponds with input matrix rownames and is sorted within each cluster using hierarchical clustering `group__` column indicates cluster assignment

Examples

```
data(CTCF_in_10a_profiles_dt)
dt = data.table::copy(CTCF_in_10a_profiles_dt)
mat = data.table::dcast(dt, id ~ sample + x, value.var = "y" )
rn = mat$id
mat = as.matrix(mat[,-1])
rownames(mat) = rn
clust_dt = clusteringKmeansNestedHclust(mat, nclust = 3)
clust_dt
```

| | |
|----------------------|---|
| <code>col2hex</code> | <i>converts a valid r color name ("black", "red", "white", etc.) to a hex value</i> |
|----------------------|---|

Description

converts a valid r color name ("black", "red", "white", etc.) to a hex value

Usage

```
col2hex(color_name)
```

Arguments

color_name character. one or more r color names.

Value

hex value of colors coded by colors()

Examples

```
col2hex(c("red", "green", "blue"))
col2hex(c("lightgray", "gray", "darkgray"))
```

| | |
|-------------|--------------------|
| collapse_gr | <i>collapse_gr</i> |
|-------------|--------------------|

Description

collapse non-contiguous regions (i.e. exons) into a contiguous coordinate starting at 1. this is strand sensitive and intended for use with all exons of a single gene.

Usage

```
collapse_gr(genome_gr)
```

Arguments

genome_gr a GRanges of regions on a single chromosome. Regions are intended to be non-contiguous and may even overlap.

Value

a new GRanges object with same mcols as input with all intervals starting at 1 and no empty space between syntenic regions.

Examples

```
library(data.table)
library(GenomicRanges)
dev_dat = data.table(seqnames = "chrTest",
                    transcript_id = c(1, 1, 2, 2, 3, 3, 3),
                    start = c(5, 30, 8, 30, 2, 30, 40),
                    end = c(10, 35, 15, 38, 7, 35, 45),
                    strand = "+")

genome_gr = GRanges(dev_dat)
collapse_gr(genome_gr)

neg_gr = genome_gr
strand(neg_gr) = "-"
collapse_gr(neg_gr)
```

convert_collapsed_coord
convert_collapsed_coord

Description

(preliminary implementation, sub-optimal)

Usage

```
convert_collapsed_coord(genome_gr, x)
```

Arguments

genome_gr non-contiguous regions to collapse a la [collapse_gr](#)
x numeric, positions within genome_gr to convert to collapsed coordinates.

Details

see [collapse_gr](#) for explanation of intended uses. this function translates all values of x from original genomic coordinates to new coordinate space created by [collapse_gr](#).

Value

numeric, positions of every value of x within collapse coordinates. values outside of collapsed regions (an intron or outside range) will be NA.

Examples

```
library(data.table)
library(GenomicRanges)
dev_dat = data.table(seqnames = "chrTest",
                    transcript_id = c(1, 1, 2, 2, 3, 3, 3),
                    start = c(5, 30, 8, 30, 2, 30, 40),
                    end = c(10, 35, 15, 38, 7, 35, 45),
                    strand = "+")

genome_gr = GRanges(dev_dat)
convert_collapsed_coord(genome_gr, start(genome_gr))
convert_collapsed_coord(genome_gr, end(genome_gr))
```

| | |
|-----------------|------------------------|
| copy_clust_info | <i>copy_clust_info</i> |
|-----------------|------------------------|

Description

copy_clust_info

Usage

```
copy_clust_info(target, to_copy, row_ = "id", cluster_ = "cluster_id")
```

Arguments

| | |
|----------|--|
| target | A data.table or GRanges returned from ssvFetch*, the target to which cluster info will be added. |
| to_copy | A data.table or GRanges returned from ssvSignalClustering, from which to copy cluster if. |
| row_ | variable name mapped to row, likely id or gene name for ngs data. Default is "id" and works with ssvFetch* output. |
| cluster_ | variable name to use for cluster info. Default is "cluster_id". |

Value

data.table or GRanges (whichever target is) containing row order and cluster assignment derived from to_copy. Suitable for ssvSignalHeatmap and related functions.

Examples

```
data(CTCF_in_10a_narrowPeak_grs)
data(CTCF_in_10a_overlaps_gr)
data(CTCF_in_10a_profiles_dt)
#this takes cluster info from signal and applies to peak hits to
#create a heatmap of peak hits clustered by signal.
clust_dt1 = ssvSignalClustering(CTCF_in_10a_profiles_dt)
peak_hit_gr = ssvFetchGRanges(
  CTCF_in_10a_narrowPeak_grs,
  qgr = CTCF_in_10a_overlaps_gr
)
peak_hit_gr.clust = copy_clust_info(peak_hit_gr, clust_dt1)
peak_hit_gr.clust$hit = peak_hit_gr.clust$y > 0
ssvSignalHeatmap(peak_hit_gr.clust, fill_ = "hit") +
  scale_fill_manual(values = c("FALSE" = "gray90", "TRUE" = "black"))
```

| | |
|----------------|---|
| crossCorrByRle | <i>Calculate cross correlation by using shiftApply on read coverage Rle</i> |
|----------------|---|

Description

Calculate cross correlation by using shiftApply on read coverage Rle

Usage

```
crossCorrByRle(
  bam_file,
  query_gr,
  max_dupes = 1,
  fragment_sizes = 50:300,
  read_length = NULL,
  flip_strand = FALSE,
  ...
)
```

Arguments

| | |
|----------------|--|
| bam_file | character. Path to .bam file, must have index at .bam.bai. |
| query_gr | GRanges. Regions to calculate cross correlation for. |
| max_dupes | integer. Duplicate reads above this value will be removed. |
| fragment_sizes | integer. fragment size range to search for maximum correlation. |
| read_length | integer. Any values outside fragment_range that must be searched. If not supplied will be determined from bam_file. Set as NA to disable this behavior. |
| flip_strand | boolean. if TRUE strands that reads align to are swapped. This is typically only necessary if there was a mismatch between library chemistry and aligner settings. Default is FALSE. |
| ... | arguments passed to ScanBamParam |

Value

named list of results

Examples

```
data(CTCF_in_10a_overlaps_gr)
bam_f = system.file("extdata/test.bam",
  package = "seqsetvis", mustWork = TRUE)
query_gr = CTCF_in_10a_overlaps_gr[1:2]
crossCorrByRle(bam_f, query_gr[1:2], fragment_sizes = seq(50, 300, 50))
```

CTCF_in_10a_bigWig_urls

FTP URL path for vignette data.

Description

FE bigWig tracks for CTCF ChIP-seq in a MCF10A progression model. See GEO series GSE98551 for details.

Format

named character vector of length 3

Details

part of [CTCF_in_10a_data](#)

CTCF_in_10a_data

CTCF ChIP-seq in breast cancer cell lines

Description

Vignette data for seqsetvis was downloaded directly from GEO series [GSE98551](#). This data is CTCF ChIP-seq from a model of breast cancer progression derived from the MCF10A cell line.

Data from GEO series [GSE98551](#) is from the publication [Fritz AJ et al. 2018](#)

Details

Contains:

- [CTCF_in_10a_overlaps_gr](#)
- [CTCF_in_10a_profiles_dt](#)
- [CTCF_in_10a_bigWig_urls](#)
- [CTCF_in_10a_narrowPeak_urls](#)

CTCF_in_10a_narrowPeak_grs

list of GRanges that results in 100 random subset when overlapped

Description

list of GRanges that results in 100 random subset when overlapped

Format

named list of GRanges of length 3

Details

part of [CTCF_in_10a_data](#)

Value

named list of GRanges of length 3

CTCF_in_10a_narrowPeak_urls

FTP URL path for vignette data. from

Description

macs2 peak calls for CTCF ChIP-seq in a MCF10A progression model. See GEO series GSE98551 for details.

Format

named character vector of length 3

Details

part of [CTCF_in_10a_data](#)

CTCF_in_10a_overlaps_gr

100 randomly selected regions from overlapping CTCF peaks in 10a cell ChIP-seq

Description

MACS2 narrowPeak calls on pooled biological replicates at pval 1e-5 and then 0.05 IDR filtered. IDR cutoffs determined by comparing top 150,000 pvalue sorted peak in replicates.

Format

GenomicRanges with 3 metadata columns of membership table

Details

See GEO series GSE98551 for details.

part of [CTCF_in_10a_data](#)

CTCF_in_10a_profiles_dt

Profiles for 100 randomly selected regions from overlapping CTCF peaks in 10a cell ChIP-seq Results from fetching bigwigs with CTCF_in_10a_overlaps_gr.

Description

A tidy data.table at window size 50 bp within 350 bp of peak center The variables are as follows:

Format

A tidy data.table of 2100 rows and 9 columns

Details

part of [CTCF_in_10a_data](#)

1. seqnames. chromosome for GRanges compatibility
2. start. start of interval
3. end. end of interval
4. width. width of interval
5. strand. leftover from GRanges.
6. id. unique identifier
7. y. fold-enrichment over input.
8. x. bp relative to center
9. sample. name of originating sample

CTCF_in_10a_profiles_gr

Profiles for 100 randomly selected regions from overlapping CTCF peaks in 10a cell ChIP-seq Results from CTCF_in_10a_overlaps_gr

Description

A tidy GRanges at window size 50 bp within 350 bp of peak center The variables are as follows:

Format

A tidy GRanges of 2100 rows and 4 metadata columns

Details

part of [CTCF_in_10a_data](#)

1. id. unique identifier
2. y. fold-enrichment over input.
3. x. bp relative to center
4. sample. name of originating sample

easyLoad_bed

easyLoad_bed takes a character vector of file paths to bed plus files and returning named list of GRanges.

Description

Mainly a utility function for loading MACS2 narrowPeak and broadPeak.

Usage

```
easyLoad_bed(
  file_paths,
  file_names = NULL,
  extraCols = character(),
  n_cores = getOption("mc.cores", 1)
)
```

Arguments

| | |
|------------|--|
| file_paths | character vector of paths to narrowPeak files. If named, those names will be used in output unless overridden by providing file_names. |
| file_names | character vector of names for output list. If not NULL will override any existing names for file_paths. Default is NULL. |
| extraCols | named character vector of classes. passed to rtracklayer::import for format = "BED". default is character(). |
| n_cores | number of cores to use, uses mc.cores option if set or 1. |

Value

a named list of GRanges loaded from file_paths

Examples

```
bed_f = system.file("extdata/test_loading.bed",
  package = "seqsetvis", mustWork = TRUE)
easyLoad_bed(bed_f, "my_bed")
```

easyLoad_broadPeak *easyLoad_broadPeak takes a character vector of file paths to narrow-Peak files from MACS2 and returns a named list of GRanges.*

Description

easyLoad_broadPeak takes a character vector of file paths to narrowPeak files from MACS2 and returns a named list of GRanges.

Usage

```
easyLoad_broadPeak(
  file_paths,
  file_names = NULL,
  n_cores = getOption("mc.cores", 1)
)
```

Arguments

| | |
|------------|--|
| file_paths | character vector of paths to narrowPeak files. If named, those names will be used in output unless overridden by providing file_names. |
| file_names | character vector of names for output list. If not NULL will override any existing names for file_paths. Default is NULL. |
| n_cores | number of cores to use, uses mc.cores option if set or 1. |

Value

a named list of GRanges loaded from file_paths

Examples

```
bp_f = system.file("extdata/test_loading.broadPeak",
  package = "seqsetvis", mustWork = TRUE)
easyLoad_broadPeak(bp_f, "my_broadPeak")
```

| | |
|--------------|--|
| easyLoad_FUN | <i>easyLoad_FUN takes a character vector of file paths run an arbitrary function defined in load_FUN</i> |
|--------------|--|

Description

easyLoad_FUN takes a character vector of file paths run an arbitrary function defined in load_FUN

Usage

```
easyLoad_FUN(
  file_paths,
  load_FUN,
  file_names = NULL,
  n_cores = getOption("mc.cores", 1),
  ...
)
```

Arguments

| | |
|------------|--|
| file_paths | character vector of paths to narrowPeak files. If named, those names will be used in output unless overridden by providing file_names. |
| load_FUN | Arbitrary function that takes at least a file path as argument. May take other arguments that should be set in call to easyLoad_FUN. |
| file_names | character vector of names for output list. If not NULL will override any existing names for file_paths. Default is NULL. |
| n_cores | number of cores to use, uses mc.cores option if set or 1. |
| ... | extra parameters passed to load_FUN |

Value

a named list of results from load_FUN

Examples

```
bed_f = system.file("extdata/test_loading.bed",
  package = "seqsetvis", mustWork = TRUE)
easyLoad_bed(bed_f, "my_bed")
```

easyLoad_IDRmerged *easyLoad_IDRmerged loads "overlapped-peaks.txt" from IDR.*

Description

easyLoad_IDRmerged loads "overlapped-peaks.txt" from IDR.

Usage

```
easyLoad_IDRmerged(
  file_paths,
  file_names = NULL,
  n_cores = getOption("mc.cores", 1),
  max_idr = 0.05
)
```

Arguments

`file_paths` character vector of paths to narrowPeak files. If named, those names will be used in output unless overridden by providing `file_names`.

`file_names` character vector of names for output list. If not NULL will override any existing names for `file_paths`. Default is NULL.

`n_cores` number of cores to use, uses `mc.cores` option if set or 1.

`max_idr` maximum IDR value allowed

Value

named list of GRanges

Examples

```
idr_file = system.file("extdata/test_idr.overlapped-peaks.txt",
  package = "seqsetvis", mustWork = TRUE)
easyLoad_IDRmerged(idr_file)
easyLoad_IDRmerged(idr_file, max_idr = .01)
```

easyLoad_narrowPeak *easyLoad_narrowPeak takes a character vector of file paths to narrowPeak files from MACS2 and returns a named list of GRanges.*

Description

easyLoad_narrowPeak takes a character vector of file paths to narrowPeak files from MACS2 and returns a named list of GRanges.

Usage

```
easyLoad_narrowPeak(
  file_paths,
  file_names = NULL,
  n_cores = getOption("mc.cores", 1)
)
```

Arguments

`file_paths` character vector of paths to narrowPeak files. If named, those names will be used in output unless overridden by providing `file_names`.

`file_names` character vector of names for output list. If not NULL will override any existing names for `file_paths`. Default is NULL.

`n_cores` number of cores to use, uses `mc.cores` option if set or 1.

Value

a named list of GRanges loaded from `file_paths`

Examples

```
np_f = system.file("extdata/test_loading.narrowPeak",
  package = "seqsetvis", mustWork = TRUE)
easyLoad_narrowPeak(np_f, "my_narrowPeak")
```

| | |
|-----------------------------|---|
| <code>easyLoad_seacr</code> | <i>easyLoad_seacr takes a character vector of file paths to seacr output bed files and returns a named list of GRanges.</i> |
|-----------------------------|---|

Description

`easyLoad_seacr` takes a character vector of file paths to seacr output bed files and returns a named list of GRanges.

Usage

```
easyLoad_seacr(
  file_paths,
  file_names = NULL,
  n_cores = getOption("mc.cores", 1)
)
```

Arguments

| | |
|------------|---|
| file_paths | character vector of paths to seacr bed files. If named, those names will be used in output unless overridden by providing file_names. |
| file_names | character vector of names for output list. If not NULL will override any existing names for file_paths. Default is NULL. |
| n_cores | number of cores to use, uses mc.cores option if set or 1. |

Value

a named list of GRanges loaded from file_paths

Examples

```
bed_f = system.file("extdata/test_loading.seacr.bed",
  package = "seqsetvis", mustWork = TRUE)
easyLoad_seacr(bed_f, "my_seacr")
```

| | |
|-------------|--------------------------------------|
| expandCigar | <i>Expand cigar codes to GRanges</i> |
|-------------|--------------------------------------|

Description

see [sam specs](#) for cigar details

Usage

```
expandCigar(
  cigar_dt,
  op_2count = c("M", "D", "=", "X"),
  return_data.table = FALSE
)
```

Arguments

| | |
|-------------------|--|
| cigar_dt | data.table with 5 required named columns in any order. c("which_label", "seq-names", "strand", "start", "cigar") |
| op_2count | Cigar codes to count. Default is alignment (M), deletion (D), match (=), and mismatch (X). Other useful codes may be skipped regions for RNA splicing (N). The locations of any insterions (I) or clipping/padding (S, H, or P) will be a single bp immediately before the interval. |
| return_data.table | if TRUE, a data.table is returned, else a GRanges. Default is FALSE. |

Value

data.table with cigar entries expanded

Examples

```

data(CTCF_in_10a_overlaps_gr)
qgr = CTCF_in_10a_overlaps_gr[1:5]
bam_file = system.file("extdata/test.bam", package = "seqsetvis", mustWork = TRUE)
raw_dt = ssvFetchBam(bam_file, qgr, return_unprocessed = TRUE)
expandCigar(raw_dt)

```

| | |
|----------|---|
| fetchBam | <i>fetch a bam file pileup with the ability to consider read extension to fragment size (fragLen)</i> |
|----------|---|

Description

fetch a bam file pileup with the ability to consider read extension to fragment size (fragLen)

Usage

```

fetchBam(
  bam_f,
  qgr,
  fragLen = NULL,
  target_strand = c("*", "+", "-")[1],
  max_dupes = Inf,
  splice_strategy = c("none", "ignore", "add", "only", "splice_count")[1],
  flip_strand = FALSE,
  return_unprocessed = FALSE,
  ...
)

```

Arguments

| | |
|-----------------|---|
| bam_f | character or BamFile to load |
| qgr | GRanges regions to fetchs |
| fragLen | numeric, NULL, or NA. if numeric, supplied value is used. if NULL, value is calculated with fragLen_calcStranded (default) if NA, raw bam pileup with no cross strand shift is returned. |
| target_strand | character. if one of "+" or "-", reads are filtered to match. ignored if any other value. |
| max_dupes | numeric >= 1. duplicate reads by strandd start position over this number are removed, Default is Inf. |
| splice_strategy | character, one of c("none", "ignore", "add", "only"). Default is "none" and split read alignments are assumed not present. fragLen must be NA for any other value to be valid. "ignore" will not count spliced regions. "add" counts spliced regions along with others, "only" will only count spliced regions and ignore others. |

flip_strand if TRUE, strand alignment is flipped prior to fragLen extension. Default is FALSE.

return_unprocessed boolean. if TRUE returns read alignment in data.table. Default is FALSE.

... passed to ScanBamParam(), can't be which or what.

Value

GRanges containing tag pileup values in score meta column. tags are optionally extended to fragment length (fragLen) prior to pile up.

| | |
|------------|-------------------|
| findMaxPos | <i>findMaxPos</i> |
|------------|-------------------|

Description

findMaxPos

Usage

```
findMaxPos(prof_dt, qgr, x_ = "x", y_ = "y", by_ = "id", width = 1)
```

Arguments

prof_dt a GRanges or data.table as returned by ssvFetch*.

qgr the GRanges used to query ssvFetch* as the qgr argument.

x_ positional variable. Should almost always be the default, "x".

y_ the signal value variable. Likely the default value of "y" but could be "y_norm" if append_ynorm was applied to data.

by_ region identifier variable. Should almost always be the default, "id".

width Desired width of final regions. Default is 1.

Value

data.table of relative x position from center per id

Examples

```
data(CTCF_in_10a_overlaps_gr)
data(CTCF_in_10a_profiles_gr)
data(CTCF_in_10a_profiles_dt)
findMaxPos(CTCF_in_10a_profiles_dt, CTCF_in_10a_overlaps_gr)
findMaxPos(CTCF_in_10a_profiles_gr, CTCF_in_10a_overlaps_gr)
```

fragLen_calcStranded *calculate fragLen from a bam file for specified regions*

Description

calculate fragLen from a bam file for specified regions

Usage

```
fragLen_calcStranded(
  bam_f,
  qgr,
  n_regions = 100,
  include_plot_in_output = FALSE,
  test_fragLen = seq(100, 400, 5),
  flip_strand = FALSE,
  ...
)
```

Arguments

| | |
|------------------------|--|
| bam_f | character or BamFile. bam file to read from. .bai index file must be in same directory |
| qgr | GRanges. used as which for ScanBamParam. Can be NULL if it's REALLY important to load the entire bam, force_no_which = TRUE also required. |
| n_regions | numeric (integer) it's generally overkill to pull all regions at this stage and will slow calculation down. Default is 100. |
| include_plot_in_output | if TRUE output is a list of fragLen and a ggplot showing values considered by calculation. Default is FALSE. |
| test_fragLen | numeric. The set of fragment lengths to gather strand cross correlation for. |
| flip_strand | boolean. if TRUE strands that reads align to are swapped. This is typically only necessary if there was a mismatch between library chemistry and aligner settings. Default is FALSE. |
| ... | passed to Rsamtools::ScanBamParam, can't be which or what. |

Value

numeric fragment length

Examples

```
data(CTCF_in_10a_overlaps_gr)
bam_file = system.file("extdata/test.bam",
  package = "seqsetvis")
qgr = CTCF_in_10a_overlaps_gr[1:5]
```

```
fragLen_calcStranded(bam_file, qgr)
#if plot is included, a list is returned, item 2 is the plot
fragLen_calcStranded(bam_file, qgr,
  include_plot_in_output = TRUE)[[2]]
```

fragLen_fromMacs2Xls *parse fragLen from MACS2 output*

Description

parse fragLen from MACS2 output

Usage

```
fragLen_fromMacs2Xls(macs2xls_file)
```

Arguments

macs2xls_file character. an xls file output by MACS2 to parse frag length from

Value

numeric fragment length

Examples

```
xls_file = system.file("extdata/test_peaks.xls",
  package = "seqsetvis")
fragLen_fromMacs2Xls(xls_file)
```

getReadLength *determine the most common read length for input bam_file. uses 50 randomly selected regions from query_gr. If fewer than 20 reads are present, loads all of query_gr.*

Description

determine the most common read length for input bam_file. uses 50 randomly selected regions from query_gr. If fewer than 20 reads are present, loads all of query_gr.

Usage

```
getReadLength(bam_file, query_gr)
```

Arguments

bam_file indexed bam file
 query_gr GRanges to read from bam file

Value

numeric of most common read length.

Examples

```
data(CTCF_in_10a_overlaps_gr)
qgr = CTCF_in_10a_overlaps_gr[1:5]
bam_file = system.file("extdata/test.bam", package = "seqsetvis", mustWork = TRUE)
getReadLength(bam_file, qgr)
```

| | |
|------------------|-------------------------|
| get_mapped_reads | <i>get_mapped_reads</i> |
|------------------|-------------------------|

Description

get_mapped_reads

Usage

```
get_mapped_reads(bam_files)
```

Arguments

bam_files Path to 1 or more bam files. Must be indexed.

Value

the total mapped reads in each bam file as a named numeric vector.

Examples

```
bam_file = system.file("extdata/test.bam", package = "seqsetvis", mustWork = TRUE)
get_mapped_reads(bam_file)
```

| | |
|-----------|------------------|
| ggellipse | <i>ggellipse</i> |
|-----------|------------------|

Description

returns a ggplot with ellipses drawn using specified parameters used by ssvFeatureVenn and ssvFeatureEuler

Usage

```
ggellipse(
  xcentres,
  ycentres,
  r,
  r2 = r,
  phi = rep(0, length(xcentres)),
  circle_colors = NULL,
  group_names = LETTERS[seq_along(xcentres)],
  line_alpha = 1,
  fill_alpha = 0.3,
  line_width = 2,
  n_points = 200
)
```

Arguments

| | |
|---------------|--|
| xcentres | numeric x-coord of centers of ellipses |
| ycentres | numeric y-coord of centers of ellipses, must have same length as xcentres |
| r | numeric radius1 of ellipse, must have length of 1 or match length of xcentres |
| r2 | numeric radius2 of ellipse, must have length of 1 or match length of xcentres. same as r by default. |
| phi | numeric phi of ellipse, must have length of 1 or match length of xcentres. 0 by default. |
| circle_colors | character of rcolors or hex colors or NULL. if null safeBrew of Dark2 is used |
| group_names | character/factor names of color/fill groups. capital letters by default. |
| line_alpha | numeric value from 0 to 1. alpha of lines, 1 by default |
| fill_alpha | numeric value from 0 to 1. alpha of fill, .3 by default. |
| line_width | numeric > 0. passed to size. 2 by default |
| n_points | integer > 1. number of points to approximate circle with. 200 by default |

Details

uses eulerr's non-exported ellipse drawing coordinate function

Value

a ggplot containing ellipses

Examples

```
ggellipse(xcentres = c(1, 1, 2),
          ycentres = c(2, 1, 1),
          r = c(1, 2, 1))
ggellipse(xcentres = c(1, 1, 2),
          ycentres = c(2, 1, 1),
```

```

    r = c(1, 2, 1),
    fill_alpha = 0,
    group_names = paste("set", 1:3))
ggellipse(xcentres = c(1, 1, 2),
          ycentres = c(2, 1, 1),
          r = c(1, 2, 1),
          circle_colors = c("red", "orange", "yellow"),
          line_alpha = 0,
          group_names = paste("set", 1:3))

```

harmonize_seqlengths *harmonize_seqlengths*

Description

ensures compatibility between seqlength of gr and bam_file based on header

Usage

```
harmonize_seqlengths(query_gr, bam_file, force_fix = FALSE)
```

Arguments

| | |
|-----------|---|
| query_gr | GRanges, object to harmonize seqlengths for |
| bam_file | character, a path to a valid bam file |
| force_fix | Logical, if TRUE incompatible seqnames are removed from the query_gr. Default is FALSE. |

Value

GRanges with seqlengths matching bam_file

Examples

```

library(GenomicRanges)
query_gr = GRanges("chr1", IRanges(1, 100))
#seqlengths has not been set
seqlengths(query_gr)
bam = system.file("extdata/test.bam", package = "seqsetvis")
gr2 = harmonize_seqlengths(query_gr, bam)
#seqlengths now set
seqlengths(gr2)

```

```
make_clustering_matrix
      make_clustering_matrix
```

Description

Create a wide matrix from a tidy data.table more suitable for clustering methods

Usage

```
make_clustering_matrix(
  tidy_dt,
  row_ = "id",
  column_ = "x",
  fill_ = "y",
  facet_ = "sample",
  max_rows = 500,
  max_cols = 100,
  clustering_col_min = -Inf,
  clustering_col_max = Inf,
  dcast_fill = NA,
  fun.aggregate = "mean"
)
```

Arguments

| | |
|--------------------|--|
| tidy_dt | the tidy data.table to covert to a wide matrix. Must have entries for variables specified by row_, column_, fill_, and facet_. |
| row_ | variable name mapped to row, likely peak id or gene name for ngs data |
| column_ | variable mapped to column, likely bp position for ngs data |
| fill_ | numeric variable to map to fill |
| facet_ | variable name to facet horizontally by |
| max_rows | for speed rows are sampled to 500 by default, use Inf to plot full data |
| max_cols | for speed columns are sampled to 100 by default, use Inf to plot full data |
| clustering_col_min | numeric minimum for col range considered when clustering, default in -Inf |
| clustering_col_max | numeric maximum for col range considered when clustering, default in Inf |
| dcast_fill | value to supply to dcast fill argument. default is NA. |
| fun.aggregate | Function to aggregate when multiple values present for facet_, row_, and column_. The function should accept a single vector argument or be a character string naming such a function. |

Value

A wide matrix version of input tidy data.table

Examples

```
data(CTCF_in_10a_profiles_dt)
mat = make_clustering_matrix(CTCF_in_10a_profiles_dt)
mat[1:5, 1:5]
```

| | |
|----------------|-----------------------|
| merge_clusters | <i>merge_clusters</i> |
|----------------|-----------------------|

Description

merge_clusters

Usage

```
merge_clusters(
  clust_dt,
  to_merge,
  row_ = "id",
  cluster_ = "cluster_id",
  reapply_cluster_names = TRUE
)
```

Arguments

| | |
|-----------------------|--|
| clust_dt | data.table output from ssvSignalClustering |
| to_merge | Clusters to merge. Must be items in clust_dt variable defined by cluster_ parameter. |
| row_ | variable name mapped to row, likely id or gene name for ngs data. Default is "id" and works with ssvFetch* output. |
| cluster_ | variable name to use for cluster info. Default is "cluster_id". |
| reapply_cluster_names | If TRUE, clusters will be renamed according to new order instead of their original names. Default is TRUE. |

Value

data.table as output from [ssvSignalClustering](#)

Examples

```

data(CTCF_in_10a_profiles_dt)
set.seed(0)
clust_dt = ssvSignalClustering(CTCF_in_10a_profiles_dt, nclust = 6)
ssvSignalHeatmap(clust_dt)
agg_dt = clust_dt[, list(y = mean(y)), list(x, cluster_id, sample)]
ggplot(agg_dt, aes(x = x, y = y, color = sample)) +
  geom_path() +
  facet_grid(cluster_id~.)

to_merge = c(2, 3, 5)
# debug(merge_clusters)
new_dt = merge_clusters(clust_dt, c(2, 3, 5), reapply_cluster_names = FALSE)
new_dt.relabel = merge_clusters(clust_dt, c(2, 3, 5), reapply_cluster_names = TRUE)
new_dt.relabel.sort = within_clust_sort(new_dt.relabel, within_order_strategy = "sort")

table(clust_dt$cluster_id)
table(new_dt$cluster_id)

cowplot::plot_grid(
  ssvSignalHeatmap(clust_dt) + labs(title = "original"),
  ssvSignalHeatmap(new_dt) + labs(title = "2,3,5 merged"),
  ssvSignalHeatmap(new_dt.relabel) + labs(title = "2,3,5 merged, renumbered"),
  ssvSignalHeatmap(new_dt.relabel.sort) + labs(title = "2,3,5 merged, renumbered and sorted")
)

```

prepare_fetch_GRanges *prepares GRanges for windowed fetching.*

Description

Deprecated and renamed as prepare_fetch_GRanges_width

Usage

```

prepare_fetch_GRanges(
  qgr,
  win_size,
  min_quantile = 0.75,
  target_size = NULL,
  skip_centerFix = FALSE
)

```

Arguments

| | |
|----------------|---|
| qgr | GRanges to prepare |
| win_size | numeric window size for fetch |
| min_quantile | numeric value from 0 to 1. Lowest possible quantile value. Only relevant if target_size is not specified. |
| target_size | numeric final width of qgr if known. Default of NULL leads to quantile based determination of target_size. |
| skip_centerFix | boolean, if FALSE (default) all regions will be resized GenomicRanges::resize(x, w, fix = "center") to a uniform size based on min_quantile to a width divisible by win_size. |

Details

output GRanges parallels input with consistent width evenly divisible by win_size. Has warning if GRanges needed resizing, otherwise no warning and input GRanges is returned unchanged.

Value

GRanges, either identical to qgr or with suitable consistent width applied.

Examples

```
data(CTCF_in_10a_overlaps_gr)
#use prepare_fetch_GRanges_width instead:
qgr = prepare_fetch_GRanges_width(CTCF_in_10a_overlaps_gr, win_size = 50)
#no warning if qgr is already valid for windowed fetching
prepare_fetch_GRanges_width(qgr, win_size = 50)
```

```
prepare_fetch_GRanges_names
```

Creates a named version of input GRanges using the same method seqsetvis uses internally to ensure consistency.

Description

If \$id is set, that value is used as name and duplicates are checked for.

Usage

```
prepare_fetch_GRanges_names(qgr, include_id = FALSE)
```

Arguments

| | |
|------------|--|
| qgr | input GRanges object the set/check names on |
| include_id | if TRUE, \$id is retained. Default is FALSE. |

Value

and named GRanges based on input qgr.

Examples

```
data(CTCF_in_10a_overlaps_gr)
qgr = CTCF_in_10a_overlaps_gr
names(qgr) = NULL
#default is to paste "region_" and iteration along length of qgr
prepare_fetch_GRanges_names(qgr)
#id gets used is already set
qgr$id = paste0("peak_", rev(seq_along(qgr)), "_of_", length(qgr))
prepare_fetch_GRanges_names(qgr)
```

```
prepare_fetch_GRanges_width
```

prepares GRanges for windowed fetching.

Description

output GRanges parallels input with consistent width evenly divisible by win_size. Has warning if GRanges needed resizing, otherwise no warning and input GRanges is returned unchanged.

Usage

```
prepare_fetch_GRanges_width(
  qgr,
  win_size,
  min_quantile = 0.75,
  target_size = NULL,
  skip_centerFix = FALSE
)
```

Arguments

| | |
|----------------|---|
| qgr | GRanges to prepare |
| win_size | numeric window size for fetch |
| min_quantile | numeric value from 0 to 1. Lowest possible quantile value. Only relevant if target_size is not specified. |
| target_size | numeric final width of qgr if known. Default of NULL leads to quantile based determination of target_size. |
| skip_centerFix | boolean, if FALSE (default) all regions will be resized GenomicRanges::resize(x, w, fix = "center") to a uniform size based on min_quantile to a width divisible by win_size. |

Value

GRanges, either identical to qgr or with suitable consistent width applied.

Examples

```
data(CTCF_in_10a_overlaps_gr)
qgr = prepare_fetch_GRanges_width(CTCF_in_10a_overlaps_gr, win_size = 50)
#no warning if qgr is already valid for windowed fetching
prepare_fetch_GRanges_width(qgr, win_size = 50)
```

quantileGRangesWidth *Quantile width determination strategy*

Description

Returns the lowest multiple of win_size greater than min_quantile quantile of width(qgr)

Usage

```
quantileGRangesWidth(qgr, min_quantile = 0.75, win_size = 1)
```

Arguments

| | |
|--------------|---|
| qgr | GRanges to calculate quantile width for |
| min_quantile | numeric value from 0 to 1. The minimum quantile of width in qgr |
| win_size | numeric/integer >=1, returned value will be a multiple of this |

Value

numeric that is >= min_quantile and evenly divisible by win_size

Examples

```
data(CTCF_in_10a_overlaps_gr)
gr = CTCF_in_10a_overlaps_gr
quantileGRangesWidth(gr)
quantileGRangesWidth(gr, min_quantile = .5, win_size = 100)
```

```
reorder_clusters_hclust
      reorder_clusters_hclust
```

Description

Applies hierarchical clustering to centroids of clusters to reorder.

Usage

```
reorder_clusters_hclust(
  clust_dt,
  hclust_result = NULL,
  row_ = "id",
  column_ = "x",
  fill_ = "y",
  facet_ = "sample",
  cluster_ = "cluster_id",
  reapply_cluster_names = TRUE,
  return_hclust = FALSE
)
```

Arguments

| | |
|------------------------------------|---|
| <code>clust_dt</code> | data.table output from ssvSignalClustering |
| <code>hclust_result</code> | hclust result returned by a previous call of this function with identical paramters when <code>return_hclust = TRUE</code> . |
| <code>row_</code> | variable name mapped to row, likely id or gene name for ngs data. Default is "id" and works with <code>ssvFetch*</code> output. |
| <code>column_</code> | variable mapped to column, likely bp position for ngs data. Default is "x" and works with <code>ssvFetch*</code> output. |
| <code>fill_</code> | numeric variable to map to fill. Default is "y" and works with <code>ssvFetch*</code> output. |
| <code>facet_</code> | variable name to facet horizontally by. Default is "sample" and works with <code>ssvFetch*</code> output. Set to "" if data is not faceted. |
| <code>cluster_</code> | variable name to use for cluster info. Default is "cluster_id". |
| <code>reapply_cluster_names</code> | If TRUE, clusters will be renamed according to new order instead of their original names. Default is TRUE. |
| <code>return_hclust</code> | If TRUE, return the result of hclust instead of the reordered clustering data.table. Default is FALSE. Ignored if <code>hclust_result</code> is supplied. |

Value

data.table as output from [ssvSignalClustering](#)

Examples

```

data(CTCF_in_10a_profiles_dt)
clust_dt = ssvSignalClustering(CTCF_in_10a_profiles_dt, nclust = 10)
new_dt = reorder_clusters_hclust(clust_dt)
cowplot::plot_grid(
  ssvSignalHeatmap(clust_dt),
  ssvSignalHeatmap(new_dt)
)

```

reorder_clusters_manual

reorder_clusters_manual

Description

Manually applies a new order (top to bottom) for cluster using the result of `ssvSignalClustering`.

Usage

```

reorder_clusters_manual(
  clust_dt,
  manual_order,
  row_ = "id",
  cluster_ = "cluster_id",
  reapply_cluster_names = TRUE
)

```

Arguments

| | |
|------------------------------------|--|
| <code>clust_dt</code> | data.table output from ssvSignalClustering |
| <code>manual_order</code> | New order for clusters Does not need to include all clusters. Any colors not included will be at the bottom in their original order. |
| <code>row_</code> | variable name mapped to row, likely id or gene name for ngs data. Default is "id" and works with <code>ssvFetch*</code> output. |
| <code>cluster_</code> | variable name to use for cluster info. Default is "cluster_id". |
| <code>reapply_cluster_names</code> | If TRUE, clusters will be renamed according to new order instead of their original names. Default is TRUE. |

Value

data.table as output from [ssvSignalClustering](#)

Examples

```

data(CTCF_in_10a_profiles_dt)
clust_dt = ssvSignalClustering(CTCF_in_10a_profiles_dt, nclust = 3)
new_dt = reorder_clusters_manual(clust_dt = clust_dt, manual_order = 2)
cowplot::plot_grid(
  ssvSignalHeatmap(clust_dt),
  ssvSignalHeatmap(new_dt)
)

```

```

reorder_clusters_stepdown
      reorder_clusters_stepdown

```

Description

Attempts to reorder clusters so that rows with highest signal on the left relative to the right appear at the top. Signal should have a roughly diagonal pattern in a "stepdown" pattern.

Usage

```

reorder_clusters_stepdown(
  clust_dt,
  row_ = "id",
  column_ = "x",
  fill_ = "y",
  facet_ = "sample",
  cluster_ = "cluster_id",
  reapply_cluster_names = TRUE,
  step_by_column = TRUE,
  step_by_facet = FALSE
)

```

Arguments

| | |
|------------------------------------|---|
| <code>clust_dt</code> | data.table output from ssvSignalClustering |
| <code>row_</code> | variable name mapped to row, likely id or gene name for ngs data. Default is "id" and works with <code>ssvFetch*</code> output. |
| <code>column_</code> | variable mapped to column, likely bp position for ngs data. Default is "x" and works with <code>ssvFetch*</code> output. |
| <code>fill_</code> | numeric variable to map to fill. Default is "y" and works with <code>ssvFetch*</code> output. |
| <code>facet_</code> | variable name to facet horizontally by. Default is "sample" and works with <code>ssvFetch*</code> output. Set to "" if data is not faceted. |
| <code>cluster_</code> | variable name to use for cluster info. Default is "cluster_id". |
| <code>reapply_cluster_names</code> | If TRUE, clusters will be renamed according to new order instead of their original names. Default is TRUE. |

step_by_column If TRUE, column is considered for left-right cluster balance. Default is TRUE.

step_by_facet If TRUE, facet is considered for left-right cluster balance. Default is FALSE.

Details

This can be done by column (`step_by_column = TRUE`) which averages across facets. By facet (`step_by_column = FALSE, step_by_facet = TRUE`) which averages all columns per facet. Or both column and facet (`step_by_column = TRUE, step_by_facet = TRUE`), which does no averaging so it looks at the full matrix as plotted.

Value

data.table as output from [ssvSignalClustering](#)

Examples

```
data(CTCF_in_10a_profiles_dt)
clust_dt = ssvSignalClustering(CTCF_in_10a_profiles_dt, nclust = 10)
new_dt = reorder_clusters_stepdown(clust_dt)
cowplot::plot_grid(
  ssvSignalHeatmap(clust_dt),
  ssvSignalHeatmap(new_dt)
)
```

| | |
|------------------|-------------------------|
| reverse_clusters | <i>reverse_clusters</i> |
|------------------|-------------------------|

Description

reverse_clusters

Usage

```
reverse_clusters(
  clust_dt,
  row_ = "id",
  column_ = "x",
  fill_ = "y",
  facet_ = "sample",
  cluster_ = "cluster_id",
  reverse_rows_within = TRUE,
  reapply_cluster_names = TRUE
)
```

Arguments

| | |
|------------------------------------|---|
| <code>clust_dt</code> | data.table output from ssvSignalClustering |
| <code>row_</code> | variable name mapped to row, likely id or gene name for ngs data. Default is "id" and works with <code>ssvFetch*</code> output. |
| <code>column_</code> | variable mapped to column, likely bp position for ngs data. Default is "x" and works with <code>ssvFetch*</code> output. |
| <code>fill_</code> | numeric variable to map to fill. Default is "y" and works with <code>ssvFetch*</code> output. |
| <code>facet_</code> | variable name to facet horizontally by. Default is "sample" and works with <code>ssvFetch*</code> output. Set to "" if data is not faceted. |
| <code>cluster_</code> | variable name to use for cluster info. Default is "cluster_id". |
| <code>reverse_rows_within</code> | If TRUE, rows within clusters will be reversed as well. Default is TRUE. |
| <code>reapply_cluster_names</code> | If TRUE, clusters will be renamed according to new order instead of their original names. Default is TRUE. |

Value

data.table as output from [ssvSignalClustering](#)

Examples

```
data(CTCF_in_10a_profiles_dt)
set.seed(0)
clust_dt = ssvSignalClustering(CTCF_in_10a_profiles_dt, nclust = 3)
rev_dt = reverse_clusters(clust_dt)
rev_dt.no_relabel = reverse_clusters(clust_dt, reapply_cluster_names = FALSE)
rev_dt.not_rows = reverse_clusters(clust_dt, reverse_rows_within = FALSE)
cowplot::plot_grid(nrow = 1,
  ssvSignalHeatmap(clust_dt) + labs(title = "original"),
  ssvSignalHeatmap(rev_dt) + labs(title = "reversed"),
  ssvSignalHeatmap(rev_dt.no_relabel) + labs(title = "reversed, no relabel"),
  ssvSignalHeatmap(rev_dt.not_rows) + labs(title = "reversed, not rows")
)
```

safeBrew

safeBrew

Description

Allows RColorBrew to handle n values less than 3 and greater than 8 without warnings and return expected number of colors.

Usage

```
safeBrew(n, pal = "Dark2")
```

Arguments

| | |
|-----|--|
| n | integer value of number of colors to make palette for. Alternatively a character or factor, in which case palette will be generated for each unique item or factor level respectively. |
| pal | palette recognized by RColorBrewer |

Details

For convenience, instead of the number n requested, n may be a character or factor vector and outputs will be appropriately named for use with `scale_color/fill_manual`.

Additionally, accepts pal as "gg", "ggplot", or "ggplot2" to reproduce default ggplot colors in the same way.

Value

a character vector of hex coded colors of length n from the color brewer palette pal. If n is supplied as character or factor, output will be named accordingly.

Examples

```
plot(1:2, rep(0, 2), col = safeBrew(2, "dark2"), pch = 16, cex = 6)
plot(1:12, rep(0, 12), col = safeBrew(12, "set1"), pch = 16, cex = 6)
plot(1:12, rep(0, 12), col = safeBrew(12, "set2"), pch = 16, cex = 6)
plot(1:12, rep(0, 12), col = safeBrew(12, "set3"), pch = 16, cex = 6)
```

| | |
|---------------|---|
| set_list2memb | <i>convert a list of sets, each list item should be a character vector denoting items in sets</i> |
|---------------|---|

Description

convert a list of sets, each list item should be a character vector denoting items in sets

Usage

```
set_list2memb(set_list)
```

Arguments

| | |
|----------|---|
| set_list | a list of character vectors. default names will be added if missing |
|----------|---|

Value

converts list of characters/numeric to membership table matrix

| | |
|--------------|--|
| shift_anchor | <i>orients the relative position of x's zero value and extends ranges to be contiguous</i> |
|--------------|--|

Description

orients the relative position of x's zero value and extends ranges to be contiguous

Usage

```
shift_anchor(score_dt, window_size, anchor)
```

Arguments

| | |
|-------------|---|
| score_dt | data.table, GRanges() sufficient |
| window_size | numeric, window size used to generate score_dt |
| anchor | character, one of c("center", "center_unstranded", "left", "left_unstranded") |

Value

score_dt with x values shifted appropriately and start and end extended to make ranges contiguous

| | |
|---------------|----------------------|
| split_cluster | <i>split_cluster</i> |
|---------------|----------------------|

Description

Splits one specified cluster in number of new clusters determined by nclust

Usage

```
split_cluster(
  clust_dt,
  to_split,
  nclust = 2,
  row_ = "id",
  column_ = "x",
  fill_ = "y",
  facet_ = "sample",
  cluster_ = "cluster_id",
  reapply_cluster_names = TRUE
)
```

Arguments

| | |
|------------------------------------|---|
| <code>clust_dt</code> | data.table output from ssvSignalClustering |
| <code>to_split</code> | Cluster to split. |
| <code>nclust</code> | Number of new clusters to create. |
| <code>row_</code> | variable name mapped to row, likely id or gene name for ngs data. Default is "id" and works with <code>ssvFetch*</code> output. |
| <code>column_</code> | variable mapped to column, likely bp position for ngs data. Default is "x" and works with <code>ssvFetch*</code> output. |
| <code>fill_</code> | numeric variable to map to fill. Default is "y" and works with <code>ssvFetch*</code> output. |
| <code>facet_</code> | variable name to facet horizontally by. Default is "sample" and works with <code>ssvFetch*</code> output. Set to "" if data is not faceted. |
| <code>cluster_</code> | variable name to use for cluster info. Default is "cluster_id". |
| <code>reapply_cluster_names</code> | If TRUE, clusters will be renamed according to new order instead of their original names. Default is TRUE. |

Value

data.table as output from [ssvSignalClustering](#)

Examples

```
data(CTCF_in_10a_profiles_dt)
set.seed(0)
clust_dt = ssvSignalClustering(CTCF_in_10a_profiles_dt, nclust = 3)
split_dt = split_cluster(clust_dt, to_split = 2, nclust = 3)
split_dt.no_rename = split_cluster(
  clust_dt,
  to_split = 2,
  nclust = 3,
  reapply_cluster_names = FALSE
)
cowplot::plot_grid(nrow = 1,
  ssvSignalHeatmap(clust_dt),
  ssvSignalHeatmap(split_dt),
  ssvSignalHeatmap(split_dt.no_rename)
)
```

ssvAnnotateSubjectGRanges

ssvAnnotateSubjectGRanges

Description

ssvAnnotateSubjectGRanges

Usage

```

ssvAnnotateSubjectGRanges(
  annotation_source,
  subject_gr,
  annotation_name = NULL,
  multi_resolver_FUN = "default"
)

## S4 method for signature 'GRanges'
ssvAnnotateSubjectGRanges(
  annotation_source,
  subject_gr,
  annotation_name = NULL,
  multi_resolver_FUN = "default"
)

## S4 method for signature 'list'
ssvAnnotateSubjectGRanges(
  annotation_source,
  subject_gr,
  annotation_name = NULL,
  multi_resolver_FUN = "default"
)

## S4 method for signature 'GRangesList'
ssvAnnotateSubjectGRanges(
  annotation_source,
  subject_gr,
  annotation_name = NULL,
  multi_resolver_FUN = "default"
)

```

Arguments

annotation_source
A single GRanges, a list of GRanges, or a GRangesList

subject_gr
The base GRanges to add annotation mcols to.

annotation_name
Optional name for single GRanges. Required for list inputs if list does not have names.

multi_resolver_FUN
Optional function to resolve multiple overlapping annotation source regions per subject region. This function must accept 2 arguments. `x` is the values in a single mcol attribute and `variable.name` is the name of variable. A single value must be returned or an error will be generated. The default of "default" can handle numeric, logical, character, and factor types.

Value

GRanges with the same regions as `subject_gr` but with additional `mcols` added from `annotation_source`.

Examples

```
library(GenomicRanges)
data(CTCF_in_10a_narrowPeak_grs)
np_grs = CTCF_in_10a_narrowPeak_grs
olap_gr = ssvOverlapIntervalSets(np_grs)
# annotating with a single GRanges is OK
ssvAnnotateSubjectGRanges(np_grs$MCF10A_CTCF, olap_gr)
# provide a name if that's useful
ssvAnnotateSubjectGRanges(np_grs$MCF10A_CTCF, olap_gr,
  annotation_name = "MCF10A")
# a named list adds each annotation
ssvAnnotateSubjectGRanges(np_grs, olap_gr)
# overriding list names is an option
ssvAnnotateSubjectGRanges(np_grs, olap_gr, LETTERS[1:3])
# GRangelist are handled like a standard list
ssvAnnotateSubjectGRanges(GRangesList(np_grs), olap_gr, LETTERS[1:3])
```

ssvConsensusIntervalSets

Intersect a list of GRanges to create a single GRanges object of merged ranges including metadata describing overlaps per input GRanges.

Description

In contrast to `ssvOverlapIntervalSets`, only regions where a consensus of input `grs` are present are preserved and annotated.

Usage

```
ssvConsensusIntervalSets(
  grs,
  ext = 0,
  min_number = 2,
  min_fraction = 0.5,
  preserve_mcols = FALSE,
  ...
)
```

Arguments

| | |
|------------------|---|
| <code>grs</code> | A list of GRanges |
| <code>ext</code> | An integer specifying how far to extend ranges before merging. In effect, ranges withing $2 * ext$ of one another will be joined during the merge |

| | |
|-----------------------------|--|
| <code>min_number</code> | An integer number specifying the absolute minimum of input grs that must overlap for a site to be considered consensus. |
| <code>min_fraction</code> | A numeric between 0 and 1 specifying the fraction of grs that must overlap to be considered consensus. |
| <code>preserve_mcols</code> | Controls carrying forward mcols metadata from input list of GRanges. If TRUE, all mcols will be carried forward with the item name appended. If a character vector, only those attributes will be carried and all must be present in all GRanges. The default of FALSE will carry nothing forward and only membership table will be generated. ssvAnnotateSubjectGRanges is used internally. |
| <code>...</code> | arguments passed to <code>IRanges::findOverlaps</code> , i.e. <code>maxgap</code> , <code>minoverlap</code> , <code>type</code> , <code>select</code> , <code>invert</code> . |

Details

Only the most stringent of `min_number` or `min_fraction` will be applied.

Value

GRanges with metadata columns describing consensus overlap of input grs.

Examples

```
library(GenomicRanges)
a = GRanges("chr1", IRanges(1:7*10, 1:7*10))
b = GRanges("chr1", IRanges(5:10*10, 5:10*10))
ssvConsensusIntervalSets(list(a, b))
```

`ssvFactorizeMembTable` *Convert any object accepted by `ssvMakeMembTable` to a factor To avoid ambiguity,*

Description

see [ssvMakeMembTable](#)

Usage

```
ssvFactorizeMembTable(object)
```

Arguments

`object` a valid object for conversion to a membership table and then factor

Value

a 2 column ("id" and "group") data.frame. "id" is factor of item names if any or simply order of items. "group" is a factor of set combinations

Examples

```
data(CTCF_in_10a_overlaps_gr)
ssvFactorizeMembTable(CTCF_in_10a_overlaps_gr)
ssvFactorizeMembTable(list(1:4, 2:3, 4:6))
```

| | |
|----------------|-------------------------------|
| ssvFeatureBars | <i>bar plots of set sizes</i> |
|----------------|-------------------------------|

Description

bar plots of set sizes

Usage

```
ssvFeatureBars(
  object,
  show_counts = TRUE,
  bar_colors = NULL,
  counts_text_colors = NULL,
  return_data = FALSE,
  count_label_size = 8
)
```

Arguments

| | |
|--------------------|--|
| object | passed to ssvMakeMembTable for conversion to membership table |
| show_counts | logical. should counts be displayed at the center of each bar. default is TRUE |
| bar_colors | character. rcolor or hex colors. default of NULL uses RColorBrewer Dark2. Will repeat to match number of samples. |
| counts_text_colors | character. rcolor or hex colors. default of NULL uses RColorBrewer Dark2. Will repeat to match number of samples. |
| return_data | logical. If TRUE, return value is no longer ggplot and is instead the data used to generate that plot. Default is FALSE. |
| count_label_size | Font size bar count labels. Default is 8. |

Value

ggplot of bar plot of set sizes

Examples

```
data(CTCF_in_10a_overlaps_gr)
ssvFeatureBars(list(1:3, 2:6))
ssvFeatureBars(CTCF_in_10a_overlaps_gr, count_label_size = 10)
ssvFeatureBars(S4Vectors::mcols(CTCF_in_10a_overlaps_gr)[,2:3])
```

```
ssvFeatureBinaryHeatmap
      ssvFeatureBinaryHeatmap
```

Description

Outputs a ggplot binary heatmap, where color indicates TRUE and the other indicates FALSE in a membership table. The heatmap is sorted, TRUE at the top, by column left to right. Changes to column order can reveal different patterns.

Usage

```
ssvFeatureBinaryHeatmap(
  object,
  raster_approximation = TRUE,
  true_color = "black",
  false_color = "#EFEFEF",
  raster_width_min = 1000,
  raster_height_min = 1000,
  return_data = FALSE
)
```

Arguments

| | |
|-----------------------------------|---|
| <code>object</code> | passed to <code>ssvMakeMembTable</code> |
| <code>raster_approximation</code> | If TRUE, instead of standard ggplot, write temporary raster png image and re-draw that as plot background. default is FALSE |
| <code>true_color</code> | character. rcolor or hex color used for TRUE values. default is "black". |
| <code>false_color</code> | character. rcolor or hex color used for TRUE values. default is "#EFEFEF", a gray. |
| <code>raster_width_min</code> | raster width will be minimum multiple of number of columns over this number. ignored if <code>raster_approximation</code> is FALSE. |
| <code>raster_height_min</code> | raster height will be minimum multiple of number of rows over this number ignored if <code>raster_approximation</code> is FALSE |
| <code>return_data</code> | logical. If TRUE, return value is no longer ggplot and is instead the data used to generate that plot. Default is TRUE |

Details

As a svg output, the final plot can be unwieldy. The default of `raster_approximation = TRUE` is easier to work with, especially for larger membership tables.

Value

ggplot using geom_tile of membership table sorted from left to right.

Examples

```
data(CTCF_in_10a_overlaps_gr)
ssvFeatureBinaryHeatmap(list(1:3, 2:6))
# horizontal version
ssvFeatureBinaryHeatmap(list(1:3, 2:6)) + coord_flip() +
  theme(axis.text.x = element_blank(), axis.text.y = element_text())
ssvFeatureBinaryHeatmap(CTCF_in_10a_overlaps_gr)
ssvFeatureBinaryHeatmap(S4Vectors::mcols(CTCF_in_10a_overlaps_gr)[,2:3])
ssvFeatureBinaryHeatmap(S4Vectors::mcols(CTCF_in_10a_overlaps_gr)[,3:2])
```

ssvFeatureEuler

Try to load a bed-like file and convert it to a GRanges object

Description

Try to load a bed-like file and convert it to a GRanges object

Usage

```
ssvFeatureEuler(
  object,
  line_width = 2,
  shape = c("circle", "ellipse")[1],
  n_points = 200,
  fill_alpha = 0.3,
  line_alpha = 1,
  circle_colors = NULL,
  return_data = FALSE
)
```

Arguments

| | |
|---------------|--|
| object | A membership table |
| line_width | numeric, passed to size aesthetic to control line width |
| shape | shape argument passed to eulerr::euler |
| n_points | number of points to use for drawing ellipses, passed to eulerr::ellipse |
| fill_alpha | numeric value from 0 to 1. Alpha value for circle fill |
| line_alpha | numeric value from 0 to 1. Alpha value for circle line |
| circle_colors | colors to choose from for circles. passed to ggplot2 color scales. |
| return_data | logical. If TRUE, return value is no longer ggplot and is instead the data used to generate that plot. Default is FALSE. |

Value

ggplot of venneuler results

Examples

```
data(CTCF_in_10a_overlaps_gr)
ssvFeatureEuler(list(1:3, 2:6))
ssvFeatureEuler(CTCF_in_10a_overlaps_gr)
ssvFeatureEuler(S4Vectors::mcols(CTCF_in_10a_overlaps_gr)[,2:3])
```

| | |
|---------------|----------------------|
| ssvFeaturePie | <i>ssvFeaturePie</i> |
|---------------|----------------------|

Description

Generate a ggplot pie plot of set sizes.

Usage

```
ssvFeaturePie(object, slice_colors = NULL, return_data = FALSE)
```

Arguments

| | |
|--------------|--|
| object | object that ssvMakeMembTable can convert to logical matrix membership |
| slice_colors | colors to use for pie slices |
| return_data | logical. If TRUE, return value is no longer ggplot and is instead the data used to generate that plot. Default is FALSE. |

Value

ggplot pie graph of set sizes

Examples

```
data(CTCF_in_10a_overlaps_gr)
ssvFeaturePie(list(1:3, 2:6))
ssvFeaturePie(CTCF_in_10a_overlaps_gr)
ssvFeaturePie(S4Vectors::mcols(CTCF_in_10a_overlaps_gr)[,2:3])
```

| | |
|------------------------------|------------------------|
| <code>ssvFeatureUpset</code> | <i>ssvFeatureUpset</i> |
|------------------------------|------------------------|

Description

Uses the UpSetR package to create an `UpSetR::upset` plot of region overlaps.

Usage

```
ssvFeatureUpset(
  object,
  return_UpSetR = FALSE,
  nsets = NULL,
  nintersects = 15,
  order.by = "freq",
  ...
)
```

Arguments

| | |
|----------------------------|--|
| <code>object</code> | will be passed to <code>ssvMakeMembTable</code> for conversion to membership matrix |
| <code>return_UpSetR</code> | If TRUE, return the UpSetR object, The default is FALSE and results in a gg-plotted version compatible with cowplot etc. |
| <code>nsets</code> | Number of sets to look at |
| <code>nintersects</code> | Number of intersections to plot. If set to NA, all intersections will be plotted. |
| <code>order.by</code> | How the intersections in the matrix should be ordered by. Options include frequency (entered as "freq"), degree, or both in any order. |
| <code>...</code> | Additional parameters passed to <code>upset</code> in the UpSetR package. |

Value

ggplot version of UpSetR plot

Examples

```
data(CTCF_in_10a_overlaps_gr)
ssvFeatureUpset(list(1:3, 2:6))
ssvFeatureUpset(CTCF_in_10a_overlaps_gr)
ssvFeatureUpset(S4Vectors::mcols(CTCF_in_10a_overlaps_gr)[,2:3])
```

| | |
|-----------------------------|-----------------------|
| <code>ssvFeatureVenn</code> | <i>ssvFeatureVenn</i> |
|-----------------------------|-----------------------|

Description

ggplot implementation of `vennDiagram` from `limma` package. Currently limited at 3 sets. [ssvFeatureUpset](#) and [ssvFeatureBinaryHeatmap](#) are good options for more than 3 sets. [ssvFeatureEuler](#) can work too but can take a very long time to run for more than 5 or so.

Usage

```
ssvFeatureVenn(
  object,
  group_names = NULL,
  counts_txt_size = 5,
  counts_as_labels = FALSE,
  show_outside_count = FALSE,
  line_width = 3,
  circle_colors = NULL,
  fill_alpha = 0.3,
  line_alpha = 1,
  counts_color = NULL,
  counts_as_percent = FALSE,
  percentage_digits = 1,
  percentage_suffix = "%",
  n_points = 200,
  return_data = FALSE
)
```

Arguments

| | |
|---------------------------------|---|
| <code>object</code> | will be passed to ssvMakeMembTable for conversion to membership matrix |
| <code>group_names</code> | useful if names weren't provided or were lost in creating membership matrix |
| <code>counts_txt_size</code> | font size for count numbers |
| <code>counts_as_labels</code> | if TRUE, <code>geom_label</code> is used instead of <code>geom_text</code> . can be easier to read. |
| <code>show_outside_count</code> | if TRUE, items outside of all sets are counted outside. can be confusing. |
| <code>line_width</code> | uses size aesthetic to control line width of circles. |
| <code>circle_colors</code> | colors to use for circle line colors. Uses Dark2 set from RColorBrewer by default. |
| <code>fill_alpha</code> | alpha value to use for fill, defaults to .3. |
| <code>line_alpha</code> | numeric value from 0 to 1. Alpha value for circle line |
| <code>counts_color</code> | character. single color to use for displaying counts |

`counts_as_percent` if TRUE, convert counts to percentages in plots.
`percentage_digits` The number of digits to round percentages to, default is 1.
`percentage_suffix` The character to append to percentages, default is "%".
`n_points` integer. number of points to approximate circle with. default is 200.
`return_data` logical. If TRUE, return value is no longer ggplot and is instead the data used to generate that plot. Default is FALSE.

Value

ggplot venn diagram

Examples

```

data(CTCF_in_10a_overlaps_gr)
ssvFeatureVenn(list(1:3, 2:6))
ssvFeatureVenn(CTCF_in_10a_overlaps_gr)
ssvFeatureVenn(S4Vectors::mcols(CTCF_in_10a_overlaps_gr)[,2:3])

ssvFeatureVenn(list(1:3, 2:6),
  counts_as_percent = TRUE,
  percentage_digits = 2)

ssvFeatureVenn(list(1:3, 2:6),
  counts_as_percent = TRUE,
  percentage_digits = 0,
  percentage_suffix = " %",
  counts_txt_size = 12)
  
```

| | |
|--------------------------|--|
| <code>ssvFetchBam</code> | <i>Iterates a character vector (ideally named) and calls <code>ssvFetchBam.single</code> on each. Appends grouping variable to each resulting <code>data.table</code> and uses <code>rbindlist</code> to efficiently combine results</i> |
|--------------------------|--|

Description

`ssvFetchBam` iteratively calls `fetchWindowedBam.single`. See [ssvFetchBam.single](#) for more info.

Usage

```

ssvFetchBam(
  file_paths,
  qgr,
  unique_names = NULL,
  ...
)
  
```

```

names_variable = "sample",
file_attribs = NULL,
win_size = 50,
win_method = c("sample", "summary")[1],
summary_FUN = stats::weighted.mean,
fragLens = "auto",
target_strand = c("*", "+", "-", "both")[1],
flip_strand = FALSE,
anchor = c("left", "left_unstranded", "center", "center_unstranded")[3],
return_data.table = FALSE,
max_dupes = Inf,
splice_strategy = c("none", "ignore", "add", "only", "splice_count")[1],
n_cores = getOption("mc.cores", 1),
n_region_splits = 1,
return_unprocessed = FALSE,
force_skip_centerFix = FALSE,
...
)

```

Arguments

| | |
|-------------------|---|
| file_paths | character vector of file_paths to load from. Alternatively, file_paths can be a data.frame or data.table whose first column is a character vector of paths and additional columns will be used as metadata. |
| qgr | Set of GRanges to query. For valid results the width of each interval should be identical and evenly divisible by win_size. |
| unique_names | names to use in final data.table to designate source bigwig. Default is 'sample' |
| names_variable | The column name where unique_names are stored. |
| file_attribs | optional data.frame/data.table with one row per item in file_paths. Each column will be a variable added to final tidy output. |
| win_size | The window size that evenly divides widths in qgr. |
| win_method | character. one of c("sample", "summary"). Determines if viewGRangesWinSample_dt or viewGRangesWinSummary_dt is used to represent each region in qgr. |
| summary_FUN | function. only relevant if win_method is "summary". passed to viewGRangesWinSummary_dt . |
| fragLens | numeric. The fragment length to use to extend reads. The default value "auto" causes an automatic calculation from 100 regions in qgr. NA causes no extension of reads to fragment size. |
| target_strand | character. One of c("", "+", "-"). <i>Controls filtering of reads by strand. Default of "" combines both strands.</i> |
| flip_strand | boolean. if TRUE strands are flipped. |
| anchor | character, one of c("center", "center_unstranded", "left", "left_unstranded") |
| return_data.table | logical. If TRUE the internal data.table is returned instead of GRanges. Default is FALSE. |

| | |
|-----------------------------------|---|
| <code>max_dupes</code> | numeric ≥ 1 . duplicate reads by strand start position over this number are removed, Default is Inf. |
| <code>splice_strategy</code> | character, one of c("none", "ignore", "add", "only", "splice_count"). Default is "none" and spliced alignment are assumed not present. <code>fragLen</code> will be forced to be NA for any other value. "ignore" will not count spliced regions. "add" counts spliced regions along with others, "only" will only count spliced regions and ignore others. |
| <code>n_cores</code> | integer number of cores to use. Uses <code>mc.cores</code> option if not supplied. |
| <code>n_region_splits</code> | integer number of splits to apply to <code>qgr</code> . The query GRanges will be split into this many roughly equal parts for increased parallelization. Default is 1, no split. |
| <code>return_unprocessed</code> | boolean. if TRUE returns read alignment in <code>data.table</code> . Default is FALSE. |
| <code>force_skip_centerFix</code> | boolean, if TRUE all query ranges will be used "as is". This is already the case by default if <code>win_method == "summary"</code> but may have applications where <code>win_method == "sample"</code> . |
| <code>...</code> | passed to <code>Rsamtools::ScanBamParam()</code> |

Details

if `qgr` contains the range `chr1:1-100` and `win_size` is 10, values from positions `chr1 5,15,25...85,` and 95 will be retrieved from `bw_file`

Value

A tidy formatted GRanges (or `data.table` if specified) containing fetched values.

Examples

```
if(Sys.info()['sysname'] != "Windows"){
  data(CTCF_in_10a_overlaps_gr)
  library(GenomicRanges)
  bam_f = system.file("extdata/test.bam",
    package = "seqsetvis", mustWork = TRUE)
  bam_files = c("a" = bam_f, "b" = bam_f)
  qgr = CTCF_in_10a_overlaps_gr[1:5]
  bw_gr = ssvFetchBam(bam_files, qgr, win_size = 10)
  bw_gr2 = ssvFetchBam(as.list(bam_files), qgr, win_size = 10)

  bw_dt = ssvFetchBam(bam_files, qgr, win_size = 10,
    return_data.table = TRUE)
}
```

ssvFetchBam.single *fetch a windowed version of a bam file, returns GRanges*

Description

fetch a windowed version of a bam file, returns GRanges

Usage

```
ssvFetchBam.single(
  bam_f,
  qgr,
  win_size = 50,
  win_method = c("sample", "summary")[1],
  summary_FUN = stats::weighted.mean,
  fragLen = NULL,
  target_strand = c("*", "+", "-", "both")[1],
  anchor = c("left", "left_unstranded", "center", "center_unstranded")[3],
  return_data.table = FALSE,
  max_dupes = Inf,
  splice_strategy = c("none", "ignore", "add", "only", "splice_count")[1],
  flip_strand = FALSE,
  return_unprocessed = FALSE,
  force_skip_centerFix = FALSE,
  ...
)
```

Arguments

| | |
|-------------------|--|
| bam_f | character or BamFile to load |
| qgr | GRanges regions to fetchs |
| win_size | numeric >=1. pileup grabbed every win_size bp for win_method sample. If win_method is summary, this is the number of windows used (confusing, sorry). |
| win_method | character. one of c("sample", "summary"). Determines if viewGRangesWinSample_dt or viewGRangesWinSummary_dt is used to represent each region in qgr. |
| summary_FUN | function. only relevant if win_method is "summary". passed to viewGRangesWinSummary_dt . |
| fragLen | numeric, NULL, or NA. if numeric, supplied value is used. if NULL, value is calculated with fragLen_calcStranded if NA, raw bam pileup with no cross strand shift is returned. |
| target_strand | character. if one of "+" or "-", reads are filtered accordingly. ignored if any other value. |
| anchor | character, one of c("center", "center_unstranded", "left", "left_unstranded") |
| return_data.table | logical. If TRUE the internal data.table is returned instead of GRanges. Default is FALSE. |

| | |
|----------------------|---|
| max_dupes | numeric ≥ 1 . duplicate reads by strand start position over this number are removed, Default is Inf. |
| splice_strategy | character, one of c("none", "ignore", "add", "only", "splice_count"). Default is "none" and spliced alignment are assumed not present. fragLen must be NA for any other value to be valid. "ignore" will not count spliced regions. "add" counts spliced regions along with others, "only" will only count spliced regions and ignore others. |
| flip_strand | if TRUE, strand alignment is flipped prior to fragLen extension. Default is FALSE. |
| return_unprocessed | boolean. if TRUE returns read alignment in data.table. Default is FALSE. |
| force_skip_centerFix | boolean, if TRUE all query ranges will be used "as is". This is already the case by default if win_method == "summary" but may have applications where win_method == "sample". |
| ... | passed to Rsamtools::ScanBamParam() |

Value

tidy GRanges (or data.table if specified) with pileups from bam file. pileup is calculated only every win_size bp.

| | |
|---------------|--|
| ssvFetchBamPE | <i>ssvFetchBam for paired-end ChIP-seq files. Only concordant reads are considered, but this has been minimally tested, please verify.</i> |
|---------------|--|

Description

Iterates a character vector (ideally named) and calls ssvFetchBamPE.single on each. Appends grouping variable to each resulting data.table and uses rbindlist to efficiently combine results

Usage

```
ssvFetchBamPE(
  file_paths,
  qgr,
  unique_names = NULL,
  win_size = 50,
  win_method = c("sample", "summary")[1],
  summary_FUN = stats::weighted.mean,
  fragLens = "not_used",
  anchor = c("left", "left_unstranded", "center", "center_unstranded")[3],
  names_variable = "sample",
  return_data.table = FALSE,
  max_dupes = Inf,
```

```

    n_cores = getOption("mc.cores", 1),
    n_region_splits = 1,
    min_isize = 1,
    max_isize = Inf,
    return_unprocessed = FALSE,
    return_fragSizes = FALSE,
    force_skip_centerFix = FALSE,
    ...
)

```

Arguments

| | |
|-----------------------------------|---|
| <code>file_paths</code> | character vector of <code>file_paths</code> to load from. Alternatively, <code>file_paths</code> can be a <code>data.frame</code> or <code>data.table</code> whose first column is a character vector of paths and additional columns will be used as metadata. |
| <code>qgr</code> | Set of GRanges to query. For valid results the width of each interval should be identical and evenly divisible by <code>win_size</code> . |
| <code>unique_names</code> | names to use in final <code>data.table</code> to designate source bigwig. Default is 'sample' |
| <code>win_size</code> | The window size that evenly divides widths in <code>qgr</code> . |
| <code>win_method</code> | character. one of <code>c("sample", "summary")</code> . Determines if <code>viewGRangesWinSample_dt</code> or <code>viewGRangesWinSummary_dt</code> is used to represent each region in <code>qgr</code> . |
| <code>summary_FUN</code> | function. only relevant if <code>win_method</code> is "summary". passed to <code>viewGRangesWinSummary_dt</code> . |
| <code>fragLens</code> | never used by <code>ssvFetchBamPE</code> Ignore. |
| <code>anchor</code> | character, one of <code>c("center", "center_unstranded", "left", "left_unstranded")</code> |
| <code>names_variable</code> | The column name where <code>unique_names</code> are stored. |
| <code>return_data.table</code> | logical. If TRUE the internal <code>data.table</code> is returned instead of GRanges. Default is FALSE. |
| <code>max_dupes</code> | numeric ≥ 1 . duplicate reads by strand and start position over this number are removed, Default is Inf. |
| <code>n_cores</code> | integer number of cores to use. |
| <code>n_region_splits</code> | integer number of splits to apply to <code>qgr</code> . The query GRanges will be split into this many roughly equal parts for increased parallelization. Default is 1, no split. |
| <code>min_isize</code> | integer. Read pairs must have an <code>isize</code> greater than or equal to this value. Default is 1. |
| <code>max_isize</code> | integer. Read pairs must have an <code>isize</code> less than or equal to this value. Default is Inf. |
| <code>return_unprocessed</code> | boolean. if TRUE returns read alignment in <code>data.table</code> . Default is FALSE. |
| <code>return_fragSizes</code> | boolean. if TRUE returns fragment sizes for all reads per region. |
| <code>force_skip_centerFix</code> | boolean, if TRUE all query ranges will be used "as is". This is already the case by default if <code>win_method == "summary"</code> but may have applications where <code>win_method == "sample"</code> . |

... passed to Rsamtools::ScanBamParam() Uses mc.cores option if not supplied.

Details

#' In contrast to ssvFetchBam, extension of reads to estimated fragment size is not an issue as each read pair represents a fragment of exact size.

ssvFetchBamPE iteratively calls fetchWindowedBam.single. See [ssvFetchBamPE.single](#) for more info.

if qgr contains the range chr1:1-100 and win_size is 10, values from positions chr1 5,15,25...85, and 95 will be retrieved from bw_file

Value

A tidy formatted GRanges (or data.table if specified) containing fetched values.

Examples

```
if(Sys.info()['sysname'] != "Windows"){
  library(GenomicRanges)
  bam_f = system.file("extdata/Bcell_PE.mm10.bam",
    package = "seqsetvis", mustWork = TRUE)
  bam_files = c("a" = bam_f, "b" = bam_f)
  data("Bcell_peaks")
  qgr = Bcell_peaks
  bw_gr = ssvFetchBamPE(bam_files, qgr, win_size = 10)
  bw_gr2 = ssvFetchBamPE(as.list(bam_files), qgr, win_size = 10)

  bw_dt = ssvFetchBamPE(bam_files, qgr, win_size = 10,
    return_data.table = TRUE)
}
```

ssvFetchBamPE.RNA *ssvFetchBamPE.RNA*

Description

ssvFetchBamPE.RNA

Usage

```
ssvFetchBamPE.RNA(
  file_paths,
  qgr,
  unique_names = NULL,
  win_size = 50,
  target_strand = "both",
  absolute_strand = FALSE,
  splice_strategy = "ignore",
```



```

    return_data.table = FALSE,
    win_method = "sample",
    max_dupes = Inf,
    flip_strand = FALSE,
    sum_reads = TRUE,
    n_cores = getOption("mc.cores", 1),
    force_skip_centerFix = TRUE,
    n_region_splits = 1
)

```

Arguments

| | |
|-----------------------------------|--|
| <code>file_paths</code> | character vector of <code>file_paths</code> to load from. Alternatively, <code>file_paths</code> can be a <code>data.frame</code> or <code>data.table</code> whose first column is a character vector of paths and additional columns will be used as metadata. |
| <code>qgr</code> | Set of <code>GRanges</code> to query. For valid results the width of each interval should be identical and evenly divisible by <code>win_size</code> . |
| <code>unique_names</code> | names to use in final <code>data.table</code> to designate source bigwig. Default is 'sample' |
| <code>win_size</code> | The window size that evenly divides widths in <code>qgr</code> . |
| <code>target_strand</code> | character. if one of "+" or "-", reads are filtered to match. ignored if any other value. |
| <code>absolute_strand</code> | If TRUE, strandedness of <code>qgr</code> will be ignored. This is useful when creating tracks for similar. |
| <code>splice_strategy</code> | character, one of <code>c("none", "ignore", "add", "only", "splice_count")</code> . Default is "none" and spliced alignment are assumed not present. <code>fragLen</code> must be NA for any other value to be valid. "ignore" will not count spliced regions. "add" counts spliced regions along with others, "only" will only count spliced regions and ignore others. |
| <code>return_data.table</code> | logical. If TRUE the internal <code>data.table</code> is returned instead of <code>GRanges</code> . Default is FALSE. |
| <code>win_method</code> | character. one of <code>c("sample", "summary")</code> . "sample" selects values at intervals and "summary" applies a weight mean function to all values in window. |
| <code>max_dupes</code> | numeric ≥ 1 . duplicate reads by strand and start position over this number are removed, Default is Inf. |
| <code>flip_strand</code> | logical. if TRUE strands are flipped. |
| <code>sum_reads</code> | logical. If true R1 and R2 reads are added together. If FALSE they are returned separately, identified by the "read" attribute. |
| <code>n_cores</code> | integer number of cores to use. Uses <code>mc.cores</code> option if not supplied. |
| <code>force_skip_centerFix</code> | boolean, if TRUE all query ranges will be used "as is". This is already the case by default if <code>win_method == "summary"</code> but may have applications where <code>win_method == "sample"</code> . |

n_region_splits

integer number of splits to apply to qgr. The query GRanges will be split into this many roughly equal parts for increased parallelization. Default is 1, no split.

Value

A tidy formatted GRanges (or data.table if specified) containing fetched values.

Examples

```
library(GenomicRanges)
pkg_dir = system.file(package = "seqsetvis", "extdata", mustWork = TRUE)
bam_files_esr1 = dir(pkg_dir, pattern = "H1.+R1.ESR1_RNA.+bam$", full.names = TRUE)
names(bam_files_esr1) = sub("_R.+_", "", basename(bam_files_esr1))
query_gr = GenomicRanges::GRanges("chr6:151656691-152129619:+")
query_gr = GenomicRanges::GRanges("chr6:152116691-152129619:+")

strand(query_gr) = "+"

prof_dt = ssvFetchBamPE.RNA(bam_files_esr1, query_gr, return_data.table = TRUE, win_size = 1)
prof_dt
```

ssvFetchBamPE.single *fetch a windowed version of a paired-end bam file, returns GRanges*
In contrast to ssvFetchBam, extension of reads to estimated fragment
size is not an issue as each read pair represents a fragment of exact
size.

Description

fetch a windowed version of a paired-end bam file, returns GRanges In contrast to ssvFetchBam, extension of reads to estimated fragment size is not an issue as each read pair represents a fragment of exact size.

Usage

```
ssvFetchBamPE.single(
  bam_f,
  qgr,
  win_size = 50,
  win_method = c("sample", "summary")[1],
  summary_FUN = stats::weighted.mean,
  anchor = c("left", "left_unstranded", "center", "center_unstranded")[3],
  return_data.table = FALSE,
  max_dupes = Inf,
  min_ysize = 1,
  max_ysize = Inf,
  return_unprocessed = FALSE,
  return_fragSizes = FALSE,
```

```

    force_skip_centerFix = FALSE,
    ...
)

```

Arguments

| | |
|-----------------------------------|--|
| <code>bam_f</code> | character or BamFile to load |
| <code>qgr</code> | GRanges regions to fetchs |
| <code>win_size</code> | numeric ≥ 1 . pileup grabbed every <code>win_size</code> bp for <code>win_method</code> sample. If <code>win_method</code> is <code>summary</code> , this is the number of windows used (confusing, sorry). |
| <code>win_method</code> | character. one of <code>c("sample", "summary")</code> . Determines if <code>viewGRangesWinSample_dt</code> or <code>viewGRangesWinSummary_dt</code> is used to represent each region in <code>qgr</code> . |
| <code>summary_FUN</code> | function. only relevant if <code>win_method</code> is <code>"summary"</code> . passed to <code>viewGRangesWinSummary_dt</code> . |
| <code>anchor</code> | character, one of <code>c("center", "center_unstranded", "left", "left_unstranded")</code> |
| <code>return_data.table</code> | logical. If TRUE the internal <code>data.table</code> is returned instead of GRanges. Default is FALSE. |
| <code>max_dupes</code> | numeric ≥ 1 . duplicate reads by strandd start position over this number are removed, Default is Inf. |
| <code>min_isize</code> | integer. Read pairs must have an <code>isize</code> greater than or equal to this value. Default is 1. |
| <code>max_isize</code> | integer. Read pairs must have an <code>isize</code> less than or equal to this value. Default is Inf. |
| <code>return_unprocessed</code> | boolean. if TRUE returns read alignment in <code>data.table</code> . Default is FALSE. |
| <code>return_fragSizes</code> | boolean. if TRUE returns fragment sizes for all reads per region. |
| <code>force_skip_centerFix</code> | boolean, if TRUE all query ranges will be used "as is". This is already the case by default if <code>win_method == "summary"</code> but may have applications where <code>win_method == "sample"</code> . |
| <code>...</code> | passed to <code>Rsamtools::ScanBamParam()</code> |

Value

tidy GRanges (or `data.table` if specified) with pileups from bam file. pileup is calculated only every `win_size` bp.

| | |
|----------------|---|
| ssvFetchBigwig | <i>Iterates a character vector (ideally named) and calls ssvFetchBigwig.single on each. Appends grouping variable to each resulting data.table and uses rbindlist to efficiently combine results.</i> |
|----------------|---|

Description

ssvFetchBigwig iteratively calls `fetchWindowedBigwig.single`. See [ssvFetchBigwig.single](#) for more info.

Usage

```
ssvFetchBigwig(
  file_paths,
  qgr,
  unique_names = NULL,
  names_variable = "sample",
  win_size = 50,
  win_method = c("sample", "summary")[1],
  summary_FUN = stats::weighted.mean,
  fragLens = "not_used",
  anchor = c("left", "left_unstranded", "center", "center_unstranded")[3],
  return_data.table = FALSE,
  n_cores = getOption("mc.cores", 1),
  n_region_splits = 1,
  force_skip_centerFix = FALSE
)
```

Arguments

| | |
|-----------------------------|---|
| <code>file_paths</code> | character vector of <code>file_paths</code> to load from. Alternatively, <code>file_paths</code> can be a <code>data.frame</code> or <code>data.table</code> whose first column is a character vector of paths and additional columns will be used as metadata. |
| <code>qgr</code> | Set of GRanges to query. For valid results the width of each interval should be identical and evenly divisible by <code>win_size</code> . |
| <code>unique_names</code> | names to use in final <code>data.table</code> to designate source bigwig. |
| <code>names_variable</code> | The column name where <code>unique_names</code> are stored. Default is 'sample' |
| <code>win_size</code> | The window size that evenly divides widths in <code>qgr</code> . |
| <code>win_method</code> | character. one of <code>c("sample", "summary")</code> . Determines if viewGRangesWinSample_dt or viewGRangesWinSummary_dt is used to represent each region in <code>qgr</code> . |
| <code>summary_FUN</code> | function. only relevant if <code>win_method</code> is "summary". passed to viewGRangesWinSummary_dt . |
| <code>fragLens</code> | never used by <code>ssvFetchBigwig</code> . Ignore. |
| <code>anchor</code> | character, one of <code>c("center", "center_unstranded", "left", "left_unstranded")</code> |

return_data.table
 logical. If TRUE the internal data.table is returned instead of GRanges. Default is FALSE.

n_cores
 integer number of cores to use. Uses mc.cores option if not supplied.

n_region_splits
 integer number of splits to apply to qgr. The query GRanges will be split into this many roughly equal parts for increased parallelization. Default is 1, no split.

force_skip_centerFix
 boolean, if TRUE all query ranges will be used "as is". This is already the case by default if win_method == "summary" but may have applications where win_method == "sample".

Details

if qgr contains the range chr1:1-100 and win_size is 10, values from positions chr1 5,15,25...85, and 95 will be retrieved from bw_file

Value

A tidy formatted GRanges (or data.table if specified) containing fetched values.

Examples

```
if(Sys.info()['sysname'] != "Windows"){
  library(GenomicRanges)
  bw_f = system.file("extdata/test_loading.bw",
    package = "seqsetvis", mustWork = TRUE)
  bw_files = c("a" = bw_f, "b" = bw_f)
  qgr = GRanges("chrTest", IRanges(1, 30))
  bw_gr = ssvFetchBigwig(bw_files, qgr, win_size = 10)
  bw_gr2 = ssvFetchBigwig(as.list(bw_files), qgr, win_size = 10)

  bw_dt = ssvFetchBigwig(bw_files, qgr, win_size = 10,
    return_data.table = TRUE)
}
```

ssvFetchBigwig.single *Fetch values from a bigwig appropriate for heatmaps etc.*

Description

ssvFetchBigwig.single Gets values for each region of the query GRanges (qgr). Values correspond to the center of each window of size win_size. A tidy formatted data.table object is returned suitable for plotting using ggplots.

Usage

```

ssvFetchBigwig.single(
  bw_file,
  qgr,
  win_size = 50,
  win_method = c("sample", "summary")[1],
  summary_FUN = stats::weighted.mean,
  anchor = c("left", "left_unstranded", "center", "center_unstranded")[3],
  return_data.table = FALSE,
  force_skip_centerFix = FALSE
)

```

Arguments

| | |
|-----------------------------------|--|
| <code>bw_file</code> | The character vector path to bigwig files to read from. |
| <code>qgr</code> | Set of GRanges to query. For valid results the width of each interval should be identical and evenly divisible by <code>win_size</code> . |
| <code>win_size</code> | The window size that evenly divides widths in <code>qgr</code> . |
| <code>win_method</code> | character. one of <code>c("sample", "summary")</code> . Determines if <code>viewGRangesWinSample_dt</code> or <code>viewGRangesWinSummary_dt</code> is used to represent each region in <code>qgr</code> . |
| <code>summary_FUN</code> | function. only relevant if <code>win_method</code> is "summary". passed to <code>viewGRangesWinSummary_dt</code> . |
| <code>anchor</code> | character, one of <code>c("center", "center_unstranded", "left", "left_unstranded")</code> |
| <code>return_data.table</code> | logical. If TRUE the internal <code>data.table</code> is returned instead of GRanges. Default is FALSE. |
| <code>force_skip_centerFix</code> | boolean, if TRUE all query ranges will be used "as is". This is already the case by default if <code>win_method == "summary"</code> but may have applications where <code>win_method == "sample"</code> . |

Details

if `qgr` contains the range `chr1:1-100` and `win_size` is 10, values from positions `chr1 5,15,25...85,` and 95 will be retrieved from `bw_file`

Value

A GRanges (or `data.table` if specified) containing fetched values.

| | |
|-----------------|---|
| ssvFetchGRanges | <i>Fetch coverage values for a list of GRanges.</i> |
|-----------------|---|

Description

ssvFetchGRanges Gets coverage values for each region of the query GRanges (qgr). Values correspond to the center of each window of size win_size. A tidy formatted data.table object is returned suitable for plotting using ggplots.

Usage

```
ssvFetchGRanges(
  grs,
  qgr,
  file_attribs = data.frame(matrix(0, nrow = length(grs), ncol = 0)),
  unique_names = names(grs),
  names_variable = "sample",
  win_size = 50,
  win_method = c("sample", "summary")[1],
  summary_FUN = function(x, w) max(x),
  target_strand = c("*", "+", "-", "both")[1],
  use_coverage = NULL,
  attrib_var = "score",
  fill_value = 0,
  anchor = c("left", "left_unstranded", "center", "center_unstranded")[3],
  return_data.table = FALSE,
  n_cores = getOption("mc.cores", 1),
  force_skip_centerFix = FALSE
)
```

Arguments

| | |
|----------------|--|
| grs | a list of GRanges for which to calculate coverage. |
| qgr | Set of GRanges to query. For valid results the width of each interval should be identical and evenly divisible by win_size. |
| file_attribs | data.frame (1 row per item in grs) containing attributes to append to results. |
| unique_names | The column name where unique_names are stored. Default is 'sample' |
| names_variable | The column name where unique_names are stored. Default is 'sample' |
| win_size | The window size that evenly divides widths in qgr. |
| win_method | character. one of c("sample", "summary"). Determines if viewGRangesWinSample_dt or viewGRangesWinSummary_dt is used to represent each region in qgr. |
| summary_FUN | function. only relevant if win_method is "summary". passed to viewGRangesWinSummary_dt . |
| target_strand | character. if one of "+" or "-", reads are filtered to match. ignored if any other value. |

| | |
|-----------------------------------|---|
| <code>use_coverage</code> | boolean or NULL, if TRUE, query regions are scored by the number of intervals overlapping. Default of NULL checks if <code>attrib_var</code> is "score" and uses coverage if so. |
| <code>attrib_var</code> | character, column in mcols of GRanges to pull values from. Default of "score" is compatible with internal coverage calculation or bedgraph-like files. |
| <code>fill_value</code> | numeric or character value to use where queried regions are empty. Default is 0 and appropriate for both calculated coverage and bedgraph/bigwig like files. Will automatically switch to "MISSING" if data is guessed to be qualitative. |
| <code>anchor</code> | character, one of <code>c("center", "center_unstranded", "left", "left_unstranded")</code> |
| <code>return_data.table</code> | logical. If TRUE the internal <code>data.table</code> is returned instead of GRanges. Default is FALSE. |
| <code>n_cores</code> | integer number of cores to use. Uses <code>mc.cores</code> option if not supplied. |
| <code>force_skip_centerFix</code> | boolean, if TRUE all query ranges will be used "as is". This is already the case by default if <code>win_method == "summary"</code> but may have applications where <code>win_method == "sample"</code> . |

Value

A tidy formatted GRanges (or `data.table` if specified) containing fetched values.

Examples

```
data(CTCF_in_10a_narrowPeak_grs)
data(CTCF_in_10a_overlaps_gr)
ssvFetchGRanges(CTCF_in_10a_narrowPeak_grs, CTCF_in_10a_overlaps_gr, win_size = 200)
```

`ssvFetchSignal` *signal loading framework*

Description

Does nothing unless `load_signal` is overridden to carry out reading data from `file_paths` (likely via the appropriate `ssvFetch*` function, ie. [ssvFetchBigwig](#) or [ssvFetchBam](#))

Usage

```
ssvFetchSignal(
  file_paths,
  qgr,
  unique_names = NULL,
  names_variable = "sample",
  file_attribs = NULL,
  win_size = 50,
  win_method = c("sample", "summary")[1],
```



```

return_data.table = FALSE,
load_signal = function(f, nam, qgr) {
  warning("nothing happened, ",
    "supply a function to", "load_signal parameter.")
},
n_cores = getOption("mc.cores", 1),
n_region_splits = 1,
force_skip_centerFix = FALSE
)

```

Arguments

| | |
|-----------------------------------|---|
| <code>file_paths</code> | character vector of <code>file_paths</code> to load from. Alternatively, <code>file_paths</code> can be a <code>data.frame</code> or <code>data.table</code> whose first column is a character vector of paths and additional columns will be used as metadata. |
| <code>qgr</code> | <code>GRanges</code> of intervals to return from each file |
| <code>unique_names</code> | unique file ids for each file in <code>file_paths</code> . Default is names of <code>file_paths</code> vector |
| <code>names_variable</code> | character, variable name for column containing <code>unique_names</code> entries. Default is "sample" |
| <code>file_attribs</code> | optional <code>data.frame</code> / <code>data.table</code> with one row per item in <code>file_paths</code> . Each column will be a variable added to final tidy output. |
| <code>win_size</code> | numeric/integer window size resolution to load signal at. Default is 50. |
| <code>win_method</code> | character. one of <code>c("sample", "summary")</code> . Determines if <code>viewGRangesWinSample_dt</code> or <code>viewGRangesWinSummary_dt</code> is used to represent each region in <code>qgr</code> . |
| <code>return_data.table</code> | logical. If <code>TRUE</code> <code>data.table</code> is returned instead of <code>GRanges</code> , the default. |
| <code>load_signal</code> | function taking <code>f</code> , <code>nam</code> , and <code>qgr</code> arguments. <code>f</code> is from <code>file_paths</code> , <code>nam</code> is from <code>unique_names</code> , and <code>qgr</code> is <code>qgr</code> . See details. |
| <code>n_cores</code> | integer number of cores to use. Uses <code>mc.cores</code> option if not supplied. |
| <code>n_region_splits</code> | integer number of splits to apply to <code>qgr</code> . The query <code>GRanges</code> will be split into this many roughly equal parts for increased parallelization. Default is 1, no split. |
| <code>force_skip_centerFix</code> | boolean, if <code>TRUE</code> all query ranges will be used "as is". This is already the case by default if <code>win_method == "summary"</code> but may have applications where <code>win_method == "sample"</code> . |

Details

`load_signal` is passed `f`, `nam`, and `qgr` and is executed in the environment where `load_signal` is defined. See `ssvFetchBigwig` and `ssvFetchBam` for examples.

Value

A `GRanges` with values read from `file_paths` at intervals of `win_size`. Originating file is coded by `unique_names` and assigned to column of name `names_variable`. Output is `data.table` is `return_data.table` is `TRUE`.

Examples

```

library(GenomicRanges)
data(CTCF_in_10a_overlaps_gr)
bam_f = system.file("extdata/test.bam",
  package = "seqsetvis", mustWork = TRUE)
bam_files = c("a" = bam_f, "b" = bam_f)
qgr = CTCF_in_10a_overlaps_gr[1:2]
qgr = resize(qgr, 500, "center")
load_bam = function(f, nam, qgr) {
  message("loading ", f, " ...")
  dt = seqsetvis::ssvFetchBam.single(bam_f = f,
    qgr = qgr,
    win_size = 50,
    fragLen = NULL,
    target_strand = "*",
    return_data.table = TRUE)

  data.table::set(dt, j = "sample", value = nam)
  message("finished loading ", nam, ".")
  dt
}
ssvFetchSignal(bam_files, qgr, load_signal = load_bam)

```

ssvMakeMembTable

generic for methods to convert various objects to a logical matrix indicating membership of items (rows) in sets (columns)

Description

generic for methods to convert various objects to a logical matrix indicating membership of items (rows) in sets (columns)

list of character vectors input

GRangesList input

GRanges with mcols input

DataFrame input

matrix of logicals, membership table

data.frame input, final output The final method for all inputs, checks column names and returns logical matrix

Usage

```
ssvMakeMembTable(object)
```

```
## S4 method for signature 'list'
ssvMakeMembTable(object)
```

```

## S4 method for signature 'GRangesList'
ssvMakeMembTable(object)

## S4 method for signature 'GRanges'
ssvMakeMembTable(object)

## S4 method for signature 'DataFrame'
ssvMakeMembTable(object)

## S4 method for signature 'matrix'
ssvMakeMembTable(object)

## S4 method for signature 'data.frame'
ssvMakeMembTable(object)

```

Arguments

object the object to convert. Supported types: list (of character or GRanges), GRanges with membership table metadata, GRangesList, data.frame/matrix/DataFrame of membership table

Value

a logical matrix indicating membership of items (rows) in sets (columns)

Examples

```

char_list = list(letters[1:3], letters[2:4])
ssvMakeMembTable(char_list)
library(GenomicRanges)
gr_list = list(GRanges("chr1", IRanges(1:3*2, 1:3*2)),
              GRanges("chr1", IRanges(2:4*2, 2:4*2)))
ssvMakeMembTable(gr_list)
library(GenomicRanges)
gr_list = list(GRanges("chr1", IRanges(1:3*2, 1:3*2)),
              GRanges("chr1", IRanges(2:4*2, 2:4*2)))
ssvMakeMembTable(GRangesList(gr_list))
gr = GRanges("chr1", IRanges(1:3*2, 1:3*2))
gr$set_a = c(TRUE, TRUE, FALSE)
gr$set_b = c(FALSE, TRUE, TRUE)
ssvMakeMembTable(gr)
gr = GRanges("chr1", IRanges(1:3*2, 1:3*2))
gr$set_a = c(TRUE, TRUE, FALSE)
gr$set_b = c(FALSE, TRUE, TRUE)
ssvMakeMembTable(mcols(gr))
memb_mat = matrix(c(TRUE, TRUE, FALSE, FALSE, TRUE, FALSE, TRUE, FALSE),
                 ncol = 2, byrow = FALSE)
ssvMakeMembTable(memb_mat)
memb_df = data.frame(a = c(TRUE, TRUE, FALSE, FALSE),
                    b = c(TRUE, FALSE, TRUE, FALSE))
ssvMakeMembTable(memb_df)

```

ssvOverlapIntervalSets

Intersect a list of GRanges to create a single GRanges object of merged ranges including metadata describing overlaps per input GRanges

Description

Intersect a list of GRanges to create a single GRanges object of merged ranges including metadata describing overlaps per input GRanges

Usage

```
ssvOverlapIntervalSets(
  grs,
  ext = 0,
  use_first = FALSE,
  preserve_mcols = FALSE,
  ...
)
```

Arguments

| | |
|----------------|--|
| grs | A list of GRanges |
| ext | An integer specifying how far to extend ranges before merging. in effect, ranges withing 2*ext of one another will be joined during the merge |
| use_first | A logical. If True, instead of merging all grs, only use first and add metadata logicals for others. |
| preserve_mcols | Controls carrying forward mcols metadata from input list of GRanges. If TRUE, all mcols will be carried forward with the item name appended. If a character vector, only those attributes will be carried and all must be present in all GRanges. The default of FALSE will carry nothing forward and only membership table will be generated. ssvAnnotateSubjectGRanges is used internally. |
| ... | arguments passed to IRanges::findOverlaps, i.e. maxgap, minoverlap, type, select, invert. |

Value

GRanges with metadata columns describing overlap of input grs.

Examples

```
library(GenomicRanges)
a = GRanges("chr1", IRanges(1:7*10, 1:7*10))
b = GRanges("chr1", IRanges(5:10*10, 5:10*10))
ssvOverlapIntervalSets(list(a, b))
```

```
ssvSignalBandedQuantiles
    plot profiles from bigwigs
```

Description

plot profiles from bigwigs

Usage

```
ssvSignalBandedQuantiles(
  bw_data,
  y_ = "y",
  x_ = "x",
  by_ = "fake",
  hsv_reverse = FALSE,
  hsv_saturation = 1,
  hsv_value = 1,
  hsv_grayscale = FALSE,
  hsv_hue_min = 0,
  hsv_hue_max = 0.7,
  hsv_symmetric = FALSE,
  n_quantile = 18,
  quantile_min = 0.05,
  quantile_max = 0.95,
  return_data = FALSE
)
```

Arguments

| | |
|-----------------------------|---|
| <code>bw_data</code> | a GRanges or data.table of bigwig signal. As returned from ssvFetchBam and ssvFetchBigwig |
| <code>y_</code> | the variable name in <code>bw_data</code> for y axis in plot |
| <code>x_</code> | the variable name in <code>bw_data</code> for x axis in plot |
| <code>by_</code> | the variable name in <code>bw_data</code> to facet on |
| <code>hsv_reverse</code> | logical, should color scale be reversed? default FALSE |
| <code>hsv_saturation</code> | numeric value from 0 to 1. Saturation for color scale. default 1 |
| <code>hsv_value</code> | numeric value from 0 to 1. Value for color scale. default 1 |
| <code>hsv_grayscale</code> | logical, if TRUE <code>gray()</code> is used instead of <code>rainbow()</code> . default FALSE |
| <code>hsv_hue_min</code> | numeric [0, <code>hsv_hue_max</code>) hue min of color scale |
| <code>hsv_hue_max</code> | numeric (<code>hsv_hue_min</code> , 1] hue max of color scale |
| <code>hsv_symmetric</code> | if TRUE, colorscale is symmetrical, default FALSE. |
| <code>n_quantile</code> | number of evenly size quantile bins |

quantile_min the lowest quantile start
 quantile_max the highest quantile end
 return_data logical. If TRUE, return value is no longer ggplot and is instead the data used to generate that plot. Default is FALSE.

Value

ggplot object using ribbon plots to show quantile distributions

Examples

```

data(CTCF_in_10a_profiles_gr)
#rainbow colors
qgr = CTCF_in_10a_profiles_gr
ssvSignalBandedQuantiles(qgr)
#grayscale
ssvSignalBandedQuantiles(qgr, hsv_grayscale = TRUE,
  hsv_symmetric = TRUE, hsv_reverse = TRUE)
#using "by_" per sample
ssvSignalBandedQuantiles(qgr, hsv_grayscale = TRUE,
  hsv_symmetric = TRUE, hsv_reverse = TRUE, by_ = "sample")
#adding spline smoothing
splined = applySpline(qgr, n = 10,
  by_ = c("id", "sample"))
ssvSignalBandedQuantiles(splined, n_quantile = 50,
  quantile_min = .25, quantile_max = .75,
  hsv_symmetric = TRUE, hsv_reverse = TRUE, by_ = "sample")

```

ssvSignalClustering *Clustering as for a heatmap. This is used internally by [ssvSignalHeatmap](#) but can also be run before calling [ssvSignalHeatmap](#) for greater control and access to clustering results directly.*

Description

Clustering is via k-means by default. The number of clusters is determined by `nclust`. Optionally, k-means can be initialized with a data.frame provided to `k_centroids`. As an alternative to k-means, a membership table from [ssvMakeMembTable](#) can be provided to determine logical clusters.

Usage

```

ssvSignalClustering(
  bw_data,
  nclust = NULL,
  k_centroids = NULL,
  memb_table = NULL,
  row_ = "id",
  column_ = "x",

```

```

    fill_ = "y",
    facet_ = "sample",
    cluster_ = "cluster_id",
    max_rows = 500,
    max_cols = 100,
    clustering_col_min = -Inf,
    clustering_col_max = Inf,
    within_order_strategy = valid_sort_strategies[2],
    dcast_fill = NA,
    iter.max = 30,
    fun.aggregate = "mean"
  )

```

Arguments

| | |
|------------------------------------|---|
| <code>bw_data</code> | a GRanges or data.table of bigwig signal. As returned from ssvFetchBam and ssvFetchBigwig |
| <code>nclust</code> | Number of clusters. Defaults to 6 if <code>nclust</code> , <code>k_centroids</code> , and <code>memb_table</code> are not set. |
| <code>k_centroids</code> | data.frame of centroids for k-means clusters. Incompatible with <code>nclust</code> or <code>memb_table</code> . |
| <code>memb_table</code> | Membership table as from ssvMakeMembTable . Logical groups from membership table will be clusters. Incompatible with <code>nclust</code> or <code>k_centroids</code> . |
| <code>row_</code> | variable name mapped to row, likely id or gene name for ngs data. Default is "id" and works with <code>ssvFetch*</code> output. |
| <code>column_</code> | variable mapped to column, likely bp position for ngs data. Default is "x" and works with <code>ssvFetch*</code> output. |
| <code>fill_</code> | numeric variable to map to fill. Default is "y" and works with <code>ssvFetch*</code> output. |
| <code>facet_</code> | variable name to facet horizontally by. Default is "sample" and works with <code>ssvFetch*</code> output. Set to "" if data is not faceted. |
| <code>cluster_</code> | variable name to use for cluster info. Default is "cluster_id". |
| <code>max_rows</code> | for speed rows are sampled to 500 by default, use Inf to plot full data |
| <code>max_cols</code> | for speed columns are sampled to 100 by default, use Inf to plot full data |
| <code>clustering_col_min</code> | numeric minimum for col range considered when clustering, default in -Inf |
| <code>clustering_col_max</code> | numeric maximum for col range considered when clustering, default in Inf |
| <code>within_order_strategy</code> | one of "hclust", "sort", "right", "left", "none", "reverse". If "hclust", hierarchical clustering will be used. If "sort", a simple decreasing sort of <code>rosSums</code> . If "left", will attempt to put high signal on left ("right" is opposite). If "none", existing order is preserved. If "reverse" reverses existing order. |
| <code>dcast_fill</code> | value to supply to <code>dcast</code> fill argument. default is NA. |
| <code>iter.max</code> | Number of max iterations to allow for k-means. Default is 30. |
| <code>fun.aggregate</code> | Function to aggregate when multiple values present for <code>facet_</code> , <code>row_</code> , and <code>column_</code> . The function should accept a single vector argument or be a character string naming such a function. |

Details

Within each cluster, items will either be sorted by decreasing average signal or hierachically clustered; this is controlled via `within_order_strategy`.

Value

data.table of signal profiles, ready for `ssvSignalHeatmap`

Examples

```
data(CTCF_in_10a_profiles_gr)
clust_dt = ssvSignalClustering(CTCF_in_10a_profiles_gr)
ssvSignalHeatmap(clust_dt)

clust_dt2 = ssvSignalClustering(CTCF_in_10a_profiles_gr, nclust = 2)
ssvSignalHeatmap(clust_dt2)

#clustering can be targetted to a specific part of the region
clust_dt3 = ssvSignalClustering(CTCF_in_10a_profiles_gr, nclust = 2,
  clustering_col_min = -250, clustering_col_max = -150)
ssvSignalHeatmap(clust_dt3)

# there are also multiple sorting strategies to apply within each cluster
clust_dt4 = ssvSignalClustering(
  CTCF_in_10a_profiles_gr,
  nclust = 2,
  within_order_strategy = "left"
)
ssvSignalHeatmap(clust_dt4)

clust_dt5 = ssvSignalClustering(
  CTCF_in_10a_profiles_gr,
  nclust = 2,
  within_order_strategy = "sort"
)
ssvSignalHeatmap(clust_dt5)
```

| | |
|-------------------------------|---|
| <code>ssvSignalHeatmap</code> | <i>heatmap style representation of membership table. instead of clustering, each column is sorted starting from the left.</i> |
|-------------------------------|---|

Description

See [ssvSignalHeatmap.ClusterBars](#) for an alternative with more control over where the cluster bars appear.

Usage

```

ssvSignalHeatmap(
  bw_data,
  nclust = 6,
  perform_clustering = c("auto", "yes", "no")[1],
  row_ = "id",
  column_ = "x",
  fill_ = "y",
  facet_ = "sample",
  cluster_ = "cluster_id",
  max_rows = 500,
  max_cols = 100,
  fill_limits = NULL,
  clustering_col_min = -Inf,
  clustering_col_max = Inf,
  within_order_strategy = c("hclust", "sort")[2],
  dcast_fill = NA,
  return_data = FALSE,
  show_cluster_bars = TRUE,
  rect_colors = c("black", "gray"),
  text_colors = rev(rect_colors),
  show_labels = TRUE,
  label_angle = 0,
  fun.aggregate = "mean"
)

```

Arguments

| | |
|---------------------------------|---|
| <code>bw_data</code> | a GRanges or data.table of bigwig signal. As returned from ssvFetchBam and ssvFetchBigwig |
| <code>nclust</code> | number of clusters |
| <code>perform_clustering</code> | should clustering be done? default is auto. auto considers if <code>row_</code> has been ordered by being a factor and if <code>cluster_</code> is a numeric. |
| <code>row_</code> | variable name mapped to row, likely id or gene name for ngs data. Default is "id" and works with <code>ssvFetch*</code> output. |
| <code>column_</code> | variable mapped to column, likely bp position for ngs data. Default is "x" and works with <code>ssvFetch*</code> output. |
| <code>fill_</code> | numeric variable to map to fill. Default is "y" and works with <code>ssvFetch*</code> output. |
| <code>facet_</code> | variable name to facet horizontally by. Default is "sample" and works with <code>ssvFetch*</code> output. Set to "" if data is not faceted. |
| <code>cluster_</code> | variable name to use for cluster info. Default is "cluster_id". |
| <code>max_rows</code> | for speed rows are sampled to 500 by default, use Inf to plot full data |
| <code>max_cols</code> | for speed columns are sampled to 100 by default, use Inf to plot full data |
| <code>fill_limits</code> | limits for fill legend. values will be cropped to this range if set. Default of NULL uses natural range of <code>fill_</code> . |

| | |
|-----------------------|--|
| clustering_col_min | numeric minimum for col range considered when clustering, default in -Inf |
| clustering_col_max | numeric maximum for col range considered when clustering, default in Inf |
| within_order_strategy | one of "hclust" or "sort". if hclust, hierarchical clustering will be used. if sort, a simple decreasing sort of rosSums. |
| dcast_fill | value to supply to dcast fill argument. default is NA. |
| return_data | logical. If TRUE, return value is no longer ggplot and is instead the data used to generate that plot. Default is FALSE. |
| show_cluster_bars | if TRUE, show bars indicating cluster membership. |
| rect_colors | colors of rectangle fill, repeat to match number of clusters. Default is c("black", "gray"). |
| text_colors | colors of text, repeat to match number of clusters. Default is reverse of rect_colors. |
| show_labels | logical, should rectangles be labelled with cluster identity. Default is TRUE. |
| label_angle | angle to add clusters labels at. Default is 0, which is horizontal. |
| fun.aggregate | Function to aggregate when multiple values present for facet_, row_, and column_. Affects both clustering and plotting. The function should accept a single vector argument or be a character string naming such a function. |

Value

ggplot heatmap of signal profiles, faceted by sample

Examples

```
data(CTCF_in_10a_profiles_gr)

#the simplest use
ssvSignalHeatmap(CTCF_in_10a_profiles_gr)
ssvSignalHeatmap(CTCF_in_10a_profiles_gr, show_cluster_bars = FALSE)

#clustering can be done manually beforehand
clust_dt = ssvSignalClustering(CTCF_in_10a_profiles_gr, nclust = 3)
ssvSignalHeatmap(clust_dt)

ssvSignalHeatmap(clust_dt, max_rows = 20, max_cols = 7)

# aggregation, when facet_ is shared by multiple samples
prof_gr = CTCF_in_10a_profiles_gr
prof_gr$mark = "CTCF"
clust_gr = ssvSignalClustering(
  prof_gr,
  facet_ = "mark",
  fun.aggregate = function(x)as.numeric(x > 10)
)
table(clust_gr$y)
```

```

ssvSignalHeatmap(prof_gr, facet_ = "mark",
  fun.aggregate = function(x)as.numeric(x > 10))
ssvSignalHeatmap(prof_gr, facet_ = "mark",
  fun.aggregate = max)
ssvSignalHeatmap(prof_gr, facet_ = "mark",
  fun.aggregate = min)

```

ssvSignalHeatmap.ClusterBars

heatmap style representation of membership table. instead of clustering, each column is sorted starting from the left.

Description

Compared to ssvSignalHeatmap, cluster_bars are displayed on the left once instead of for each facet

Usage

```

ssvSignalHeatmap.ClusterBars(
  bw_data,
  nclust = 6,
  perform_clustering = c("auto", "yes", "no")[1],
  row_ = "id",
  column_ = "x",
  fill_ = "y",
  facet_ = "sample",
  cluster_ = "cluster_id",
  FUN_format_heatmap = NULL,
  max_rows = 500,
  max_cols = 100,
  fill_limits = NULL,
  clustering_col_min = -Inf,
  clustering_col_max = Inf,
  within_order_strategy = c("hclust", "sort")[2],
  dcast_fill = NA,
  return_data = FALSE,
  return_unassembled_plots = FALSE,
  rel_widths = c(1, 9),
  rect_colors = c("black", "gray"),
  text_colors = rev(rect_colors),
  show_labels = TRUE,
  label_angle = 0,
  fun.aggregate = "mean",
  ...
)

```

Arguments

| | |
|---------------------------------------|--|
| <code>bw_data</code> | a GRanges or data.table of bigwig signal. As returned from ssvFetchBam and ssvFetchBigwig |
| <code>nclust</code> | number of clusters |
| <code>perform_clustering</code> | should clustering be done? default is auto. auto considers if <code>row_</code> has been ordered by being a factor and if <code>cluster_</code> is a numeric. |
| <code>row_</code> | variable name mapped to row, likely id or gene name for ngs data. Default is "id" and works with <code>ssvFetch*</code> output. |
| <code>column_</code> | variable mapped to column, likely bp position for ngs data. Default is "x" and works with <code>ssvFetch*</code> output. |
| <code>fill_</code> | numeric variable to map to fill. Default is "y" and works with <code>ssvFetch*</code> output. |
| <code>facet_</code> | variable name to facet horizontally by. Default is "sample" and works with <code>ssvFetch*</code> output. Set to "" if data is not faceted. |
| <code>cluster_</code> | variable name to use for cluster info. Default is "cluster_id". |
| <code>FUN_format_heatmap</code> | optional function to modify main ggplot (labels, themes, scales, etc.). Take a ggplot and returns a ggplot. Default is NULL. |
| <code>max_rows</code> | for speed rows are sampled to 500 by default, use Inf to plot full data |
| <code>max_cols</code> | for speed columns are sampled to 100 by default, use Inf to plot full data |
| <code>fill_limits</code> | limits for fill legend. values will be cropped to this range if set. Default of NULL uses natural range of <code>fill_</code> . |
| <code>clustering_col_min</code> | numeric minimum for col range considered when clustering, default in -Inf |
| <code>clustering_col_max</code> | numeric maximum for col range considered when clustering, default in Inf |
| <code>within_order_strategy</code> | one of "hclust" or "sort". if hclust, hierarchical clustering will be used. if sort, a simple decreasing sort of <code>rosSums</code> . |
| <code>dcast_fill</code> | value to supply to <code>dcast</code> fill argument. default is NA. |
| <code>return_data</code> | logical. If TRUE, return value is no longer ggplot and is instead the data used to generate that plot. Default is FALSE. |
| <code>return_unassembled_plots</code> | logical. If TRUE, return list of heatmap and cluster-bar ggplots. Can be customized and passed to assemble_heatmap_cluster_bars |
| <code>rel_widths</code> | numeric of length 2. Passed to <code>cowplot::plot_grid</code> . Default is <code>c(1, 9)</code> . |
| <code>rect_colors</code> | colors of rectangle fill, repeat to match number of clusters. Default is <code>c("black", "gray")</code> . |
| <code>text_colors</code> | colors of text, repeat to match number of clusters. Default is reverse of <code>rect_colors</code> . |
| <code>show_labels</code> | logical, should rectangles be labelled with cluster identity. Default is TRUE. |
| <code>label_angle</code> | angle to add clusters labels at. Default is 0, which is horizontal. |
| <code>fun.aggregate</code> | Function to aggregate when multiple values present for <code>facet_</code> , <code>row_</code> , and <code>column_</code> . Affects both clustering and plotting. The function should accept a single vector argument or be a character string naming such a function. |
| <code>...</code> | additional arguments passed to <code>cowplot::plot_grid</code> |

Value

ggplot heatmap of signal profiles, faceted by sample

Examples

```
data(CTCF_in_10a_profiles_gr)

#the simplest use
ssvSignalHeatmap.ClusterBars(CTCF_in_10a_profiles_gr)
ssvSignalHeatmap.ClusterBars(CTCF_in_10a_profiles_gr, rel_widths = c(1, 5))

#clustering can be done manually beforehand
clust_dt = ssvSignalClustering(data.table::as.data.table(CTCF_in_10a_profiles_gr), nclust = 3)
ssvSignalHeatmap.ClusterBars(clust_dt)

# aggregation, when facet_ is shared by multiple samples
prof_gr = CTCF_in_10a_profiles_gr
prof_gr$mark = "CTCF"
ssvSignalHeatmap.ClusterBars(prof_gr, facet_ = "mark", fun.aggregate = mean)
ssvSignalHeatmap.ClusterBars(prof_gr, facet_ = "mark", fun.aggregate = "sum")
```

| | |
|-------------------|--|
| ssvSignalLineplot | <i>construct line type plots where each region in each sample is represented</i> |
|-------------------|--|

Description

construct line type plots where each region in each sample is represented

Usage

```
ssvSignalLineplot(
  bw_data,
  x_ = "x",
  y_ = "y",
  color_ = "sample",
  sample_ = "sample",
  region_ = "id",
  group_ = "auto_grp",
  line_alpha = 1,
  facet_ = "auto_facet",
  facet_method = facet_wrap,
  spline_n = NULL,
  return_data = FALSE
)
```

Arguments

| | |
|---------------------------|--|
| <code>bw_data</code> | a GRanges or data.table of bigwig signal. As returned from <code>ssvFetchBam</code> and <code>ssvFetchBigwig</code> |
| <code>x_</code> | variable name mapped to x aesthetic, x by default. |
| <code>y_</code> | variable name mapped to y aesthetic, y by default. |
| <code>color_</code> | variable name mapped to color aesthetic, sample by default. |
| <code>sample_</code> | variable name, along with <code>region_</code> used to group and facet by default, change <code>group_</code> or <code>facet_</code> to override. |
| <code>region_</code> | variable name, along with <code>sample_</code> used to group and facet by default, change <code>group_</code> or <code>facet_</code> to override. |
| <code>group_</code> | group aesthetic keeps lines of <code>geom_path</code> from mis-connecting. <code>auto_grp</code> by default which combines <code>sample_</code> and <code>region_</code> . probably shouldn't change. |
| <code>line_alpha</code> | alpha value for lines. default is 1. |
| <code>facet_</code> | facetting divides up plots. <code>auto_facet</code> by default which combines <code>sample_</code> and <code>region_</code> . if overriding <code>facet_method</code> with <code>facet_grid</code> , make sure to include ~ between two variables, ie. "a~b", ".~b", "a~." |
| <code>facet_method</code> | ggplot2 facetting method or wrapper for same, <code>facet_wrap</code> by default. |
| <code>spline_n</code> | if not NULL, <code>applySpline</code> will be called with <code>n = spline_n</code> . default is NULL. |
| <code>return_data</code> | logical. If TRUE, return value is no longer ggplot and is instead the data used to generate that plot. Default is FALSE. |

Value

ggplot of signal potentially faceted by region and sample

Examples

```
data(CTCF_in_10a_profiles_gr)

bw_gr = CTCF_in_10a_profiles_gr
ssvSignalLineplot(subset(bw_gr, bw_gr$id %in% seq_len(3)), facet_ = "sample")
ssvSignalLineplot(subset(bw_gr, bw_gr$id %in% seq_len(3)),
  facet_ = "sample~.",
  facet_method = facet_grid)
ssvSignalLineplot(subset(bw_gr, bw_gr$id %in% seq_len(3)),
  facet_ = paste("sample", "~", "id"), facet_method = facet_grid)
ssvSignalLineplot(subset(bw_gr, bw_gr$id %in% seq_len(3)))
ssvSignalLineplot(subset(bw_gr, bw_gr$id %in% seq_len(3)), facet_ = "id")
ssvSignalLineplot(subset(bw_gr, bw_gr$id %in% seq_len(3)),
  facet_ = "id", spline_n = 10)
```

ssvSignalLineplotAgg *aggregate line signals in a single line plot*

Description

aggregate line signals in a single line plot

Usage

```
ssvSignalLineplotAgg(  
  bw_data,  
  x_ = "x",  
  y_ = "y",  
  sample_ = "sample",  
  color_ = sample_,  
  group_ = sample_,  
  agg_fun = mean,  
  spline_n = NULL,  
  return_data = FALSE  
)
```

Arguments

| | |
|-------------|---|
| bw_data | a GRanges or data.table of bigwig signal. As returned from ssvFetchBam and ssvFetchBigwig |
| x_ | variable name mapped to x aesthetic, x by default. |
| y_ | variable name mapped to y aesthetic, y by default. |
| sample_ | variable name, along with region_ used to group by default, |
| color_ | variable name mapped to color aesthetic, sample_ by default. change group_ to override. |
| group_ | group aesthetic keeps lines of geom_path from mis-connecting. Most useful if you need to supply a variable to later facet upon. Defaults to value of sample_. |
| agg_fun | the aggregation function to apply by sample_ and x_, default is mean |
| spline_n | if not NULL, applySpline will be called with n = spline_n. default is NULL. |
| return_data | logical. If TRUE, return value is no longer ggplot and is instead the data used to generate that plot. Default is FALSE. |

Value

ggplot of signal aggregated with agg_fun() by sample.

Examples

```

data(CTCF_in_10a_profiles_gr)
bw_gr = CTCF_in_10a_profiles_gr
ssvSignalLineplotAgg(bw_gr) +
  labs(title = "agg regions by sample.")
ssvSignalLineplotAgg(CTCF_in_10a_profiles_gr, spline_n = 10) +
  labs(title = "agg regions by sample, with spline smoothing.")
ssvSignalLineplotAgg(subset(bw_gr, bw_gr$id %in% seq_len(10)),
  sample_ = "id", color_ = "id") +
  labs(title = "agg samples by region id (weird)")
ssvSignalLineplotAgg(subset(bw_gr, bw_gr$id %in% seq_len(10)), sample_ = "id",
  color_ = "id", spline_n = 10) +
  labs(title = "agg samples by region id (weird), with spline smoothing")

```

`ssvSignalScatterplot` *maps signal from 2 sample profiles to the x and y axis. axes are standard or "volcano" min XY vs fold-change Y/X*

Description

maps signal from 2 sample profiles to the x and y axis. axes are standard or "volcano" min XY vs fold-change Y/X

Usage

```

ssvSignalScatterplot(
  bw_data,
  x_name,
  y_name,
  color_table = NULL,
  value_variable = "y",
  xy_variable = "sample",
  value_function = max,
  by_ = "id",
  plot_type = c("standard", "volcano")[1],
  show_help = FALSE,
  fixed_coords = TRUE,
  return_data = FALSE
)

```

Arguments

| | |
|----------------------|---|
| <code>bw_data</code> | a GRanges or data.table of bigwig signal. As returned from ssvFetchBam and ssvFetchBigwig |
| <code>x_name</code> | sample name to map to x-axis, must be stored in variable specified in <code>xy_variable</code> |
| <code>y_name</code> | sample name to map to y-axis, must be stored in variable specified in <code>xy_variable</code> |

| | |
|----------------|---|
| color_table | data.frame with 2 columns, one of which must be named "group" and gets mapped to color. The other column must be the same as by_ parameter and is used for merging. |
| value_variable | variable name that stores numeric values for plotting, default is "y" |
| xy_variable | variable name that stores sample, must contain entires for x_name and y_name |
| value_function | a function to apply to value_variable in all combintations of by_ per x_name and y_name |
| by_ | variables that store individual measurement ids |
| plot_type | standard or volcano, default is "standard" |
| show_help | if TRUE overlay labels to aid plot interpretation, default is FALSE |
| fixed_coords | if TRUE coordinate system is 1:1 ratio, default is TRUE |
| return_data | logical. If TRUE, return value is no longer ggplot and is instead the data used to generate that plot. Default is FALSE. |

Value

ggplot of points comparing signal from 2 samples

Examples

```

data(CTCF_in_10a_profiles_gr)
ssvSignalScatterplot(CTCF_in_10a_profiles_gr,
  x_name = "MCF10A_CTCF", y_name = "MCF10AT1_CTCF")
ssvSignalScatterplot(CTCF_in_10a_profiles_gr,
  x_name = "MCF10A_CTCF", y_name = "MCF10CA1_CTCF")

ssvSignalScatterplot(CTCF_in_10a_profiles_gr,
  x_name = "MCF10A_CTCF", y_name = "MCF10AT1_CTCF",
  value_function = median) + labs(title = "median FE in regions")

ssvSignalScatterplot(CTCF_in_10a_profiles_gr,
  x_name = "MCF10A_CTCF", y_name = "MCF10AT1_CTCF",
  plot_type = "volcano")

ssvSignalScatterplot(CTCF_in_10a_profiles_gr,
  x_name = "MCF10A_CTCF", y_name = "MCF10AT1_CTCF",
  plot_type = "volcano", show_help = TRUE)

```

ssv_mclapply

ssv_mclapply

Description

ssv_mclapply

Usage

```
ssv_mclapply(X, FUN, mc.cores = getOption("mc.cores", 1), ...)
```

Arguments

| | |
|----------|--|
| X | For pbsapply and pblapply, a vector (atomic or list) or an expressions vector (other objects including classed objects will be coerced by as.list.) For pbapply an array, including a matrix. For pbtapply an R object for which a split method exists. Typically vector-like, allowing subsetting with "[". |
| FUN | The function to be applied to each element of X: see apply, sapply, and lapply. In the case of functions like +, '%*%', etc., the function name must be backquoted or quoted. If FUN is NULL, pbtapply returns a vector which can be used to subscript the multi-way array pbtapply normally produces. |
| mc.cores | Number of cores to use for pbmclapply. Defaults to option mc.cores. |
| ... | passed to pbapply::pblapply or pbmclapply::pbmclapply |

Value

result of either pblapply or pbmclapply

| | |
|------------|---|
| test_peaks | <i>4 random peaks for single-end data and 4 control regions 30kb downstream from each peak.</i> |
|------------|---|

Description

matches `system.file("extdata/test_peaks.bam", package = "seqsetvis")`

Format

GRanges length 8

Details

this is included only for testing `ssvFetchBam` functions.

Value

GRanges length 8

```
viewGRangesWinSample_dt
      get a windowed sampling of score_gr
```

Description

This method is appropriate when all GRanges in qgr are identical width and when it is practical to use a window_size smaller than features in genomic signal. For instance, when retrieving signal around peaks or promoters this method maintains a fixed genomic scale across regions. This allows meaningful comparison of peak widths can be made.

Usage

```
viewGRangesWinSample_dt(
  score_gr,
  qgr,
  window_size,
  attrib_var = "score",
  fill_value = 0,
  anchor = c("center", "center_unstranded", "left", "left_unstranded")[1]
)
```

Arguments

| | |
|-------------|--|
| score_gr | GRanges with a "score" metadata column. |
| qgr | regions to view by window. |
| window_size | qgr will be represented by value from score_gr every window_size bp. |
| attrib_var | character name of attribute to pull data from. Default is "score", compatible with bigWigs or bam coverage. |
| fill_value | numeric or character value to use where queried regions are empty. Default is 0 and appropriate for both calculated coverage and bedgraph/bigwig like files. Will automatically switch to "MISSING" if data is guessed to be qualitative. |
| anchor | character. controls how x value is derived from position for each region in qgr. 0 may be the left side or center. If not unstranded, x coordinates are flipped for (-) strand. One of c("center", "center_unstranded", "left", "left_unstranded"). Default is "center". |

Details

Summarizes score_gr by grabbing value of "score" every window_size bp. Columns in output data.table are: standard GRanges columns: seqnames, start, end, width, strand id - matched to names(score_gr). if names(score_gr) is missing, added as 1:length(score_gr). y - value of score from score_gr. x - relative bp position.

Value

data.table that is GRanges compatible

Examples

```

data(CTCF_in_10a_overlaps_gr)
bam_file = system.file("extdata/test.bam",
  package = "seqsetvis")
qgr = CTCF_in_10a_overlaps_gr[seq_len(5)]
qgr = GenomicRanges::resize(qgr, width = 500, fix = "center")
bam_gr = seqsetvis::fetchBam(bam_file, qgr)
bam_dt = viewGRangesWinSample_dt(bam_gr, qgr, 50)

if(Sys.info()['sysname'] != "Windows"){
  bw_file = system.file("extdata/MCF10A_CTCF_FE_random100.bw",
    package = "seqsetvis")
  bw_gr = rtracklayer::import.bw(bw_file, which = qgr)
  bw_dt = viewGRangesWinSample_dt(bw_gr, qgr, 50)
}

```

```
viewGRangesWinSummary_dt
```

Summarizes signal in bins. The same number of bins per region in qgr is used and widths can vary in qgr, in contrast to [viewGRangesWinSample_dt](#) where width must be constant across regions.

Description

This function is most appropriate where features are expected to vary greatly in size and feature boundaries are important, ie. gene bodies, enhancers or TADs.

Usage

```

viewGRangesWinSummary_dt(
  score_gr,
  qgr,
  n_tiles = 100,
  attrib_var = "score",
  attrib_type = NULL,
  fill_value = 0,
  anchor = c("center", "center_unstranded", "left", "left_unstranded")[1],
  summary_FUN = stats::weighted.mean
)

```

Arguments

| | |
|----------|---|
| score_gr | GRanges with a "score" metadata column. |
| qgr | regions to view by window. |
| n_tiles | numeric >= 1, the number of tiles to use for every region in qgr. |

| | |
|-------------|--|
| attrib_var | character name of attribute to pull data from. Default is "score", compatible with with bigWigs or bam coverage. |
| attrib_type | one of NULL, qualitative or quantitative. If NULL will attempt to guess by casting attrib_var attribute to character or factor. Default is NULL. |
| fill_value | numeric or character value to use where queried regions are empty. Default is 0 and appropriate for both calculated coverage and bedgraph/bigwig like files. Will automatically switch to "MISSING" if data is guessed to be qualitative. |
| anchor | character. controls how x value is derived from position for each region in qgr. 0 may be the left side or center. If not unstranded, x coordinates are flipped for (-) strand. One of c("center", "center_unstranded", "left", "left_unstranded"). Default is "center". |
| summary_FUN | function. used to aggregate score by tile. must accept x=score and w=width numeric vectors as only arguments. default is weighted.mean. limma::weighted.median is a good alternative. |

Details

Columns in output data.table are: standard GRanges columns: seqnames, start, end, width, strand id - matched to names(score_gr). if names(score_gr) is missing, added as seq_along(score_gr). y - value of score from score_gr x - relative bp position

Value

data.table that is GRanges compatible

Examples

```
data(CTCF_in_10a_overlaps_gr)
bam_file = system.file("extdata/test.bam",
  package = "seqsetvis")
qgr = CTCF_in_10a_overlaps_gr[1:5]
# unlike viewGRangesWinSample_dt, width is not fixed
# qgr = GenomicRanges::resize(qgr, width = 500, fix = "center")
bam_gr = seqsetvis::fetchBam(bam_file, qgr)
bam_dt = viewGRangesWinSummary_dt(bam_gr, qgr, 50)

if(Sys.info()['sysname'] != "Windows"){
  bw_file = system.file("extdata/MCF10A-CTCF_FE_random100.bw",
    package = "seqsetvis")
  bw_gr = rtracklayer::import.bw(bw_file, which = qgr)
  bw_dt = viewGRangesWinSummary_dt(bw_gr, qgr, 50)
}
```

| | |
|-------------------|--------------------------|
| within_clust_sort | <i>within_clust_sort</i> |
|-------------------|--------------------------|

Description

Without modifying cluster assignments, modify the order of rows within each cluster based on within_order_strategy.

Usage

```
within_clust_sort(
  clust_dt,
  row_ = "id",
  column_ = "x",
  fill_ = "y",
  facet_ = "sample",
  cluster_ = "cluster_id",
  within_order_strategy = c("hclust", "sort", "left", "right", "none", "reverse")[2],
  clustering_col_min = -Inf,
  clustering_col_max = Inf,
  dcast_fill = NA
)
```

Arguments

| | |
|-----------------------|--|
| clust_dt | data.table output from ssvSignalClustering |
| row_ | variable name mapped to row, likely id or gene name for ngs data. Default is "id" and works with ssvFetch* output. |
| column_ | variable mapped to column, likely bp position for ngs data. Default is "x" and works with ssvFetch* output. |
| fill_ | numeric variable to map to fill. Default is "y" and works with ssvFetch* output. |
| facet_ | variable name to facet horizontally by. Default is "sample" and works with ssvFetch* output. Set to "" if data is not faceted. |
| cluster_ | variable name to use for cluster info. Default is "cluster_id". |
| within_order_strategy | one of "hclust", "sort", "right", "left", "reverse". If "hclust", hierarchical clustering will be used. If "sort", a simple decreasing sort of rosSums. If "left", will attempt to put high signal on left ("right" is opposite). If "reverse" reverses existing order (should only be used after meaningful order imposed). |
| clustering_col_min | numeric minimum for col range considered when clustering, default in -Inf |
| clustering_col_max | numeric maximum for col range considered when clustering, default in Inf |
| dcast_fill | value to supply to dcast fill argument. default is NA. |

Details

This is particularly useful when you want to sort within each cluster by a different variable from cluster assignment. Also if you've imported cluster assignments but want to sort within each for the new data for a prettier heatmap.

TODO refactor shared code with clusteringKmeansNestedHclust

Value

data.table matching input clust_dt save for the reassignment of levels of row_ variable.

Examples

```
data(CTCF_in_10a_profiles_dt)
#clustering by relative value per region does a good job highlighting changes
#when then plotting raw values the order within clusters is not smooth
#this is a good situation to apply a separate sort within clusters.
prof_dt = CTCF_in_10a_profiles_dt
prof_dt = append_ynorm(prof_dt)
prof_dt[, y_relative := y_norm / max(y_norm), list(id)]

clust_dt = ssvSignalClustering(prof_dt, fill_ = "y_relative")
clust_dt.sort = within_clust_sort(clust_dt)

cowplot::plot_grid(
  ssvSignalHeatmap(clust_dt) +
    labs(title = "clustered by relative, sorted by relative"),
  ssvSignalHeatmap(clust_dt.sort) +
    labs(title = "clustered by relative, sorted by raw value")
)
```

Index

* datasets

- Bcell_peaks, 12
- chromHMM_demo_bw_states_gr, 17
- chromHMM_demo_chain_url, 17
- chromHMM_demo_data, 18
- chromHMM_demo_overlaps_gr, 18
- chromHMM_demo_segmentation_url, 19
- chromHMM_demo_state_colors, 19
- chromHMM_demo_state_total_widths, 20
- CTCF_in_10a_bigWig_urls, 27
- CTCF_in_10a_data, 27
- CTCF_in_10a_narrowPeak_grs, 28
- CTCF_in_10a_narrowPeak_urls, 28
- CTCF_in_10a_overlaps_gr, 29
- CTCF_in_10a_profiles_dt, 29
- CTCF_in_10a_profiles_gr, 30
- test_peaks, 98
- .expand_cigar_dt, 4
- .expand_cigar_dt_recursive, 5
- .rm_dupes, 5
- .rm_dupesPE, 6
- add_cluster_annotation, 6
- append_ynorm, 8
- applyMovingAverage, 9
- applySpline, 10
- assemble_heatmap_clusterBars, 11, 92
- Bcell_peaks, 12
- calc_norm_factors, 8, 12
- centerAtMax, 13
- centerFixedSizeGRanges, 15
- centerGRangesAtMax, 16
- chromHMM_demo_bw_states_gr, 17, 18
- chromHMM_demo_chain_url, 17, 18
- chromHMM_demo_data, 17, 18, 19, 20
- chromHMM_demo_overlaps_gr, 18, 18
- chromHMM_demo_segmentation_url, 18, 19
- chromHMM_demo_state_colors, 18, 19
- chromHMM_demo_state_total_widths, 18, 20
- clusteringKmeans, 20
- clusteringKmeansNestedHclust, 21
- col2hex, 22
- collapse_gr, 23, 24
- convert_collapsed_coord, 24
- copy_clust_info, 25
- crossCorrByRle, 26
- CTCF_in_10a_bigWig_urls, 27, 27
- CTCF_in_10a_data, 27, 27, 28–30
- CTCF_in_10a_narrowPeak_grs, 28
- CTCF_in_10a_narrowPeak_urls, 27, 28
- CTCF_in_10a_overlaps_gr, 27, 29
- CTCF_in_10a_profiles_dt, 27, 29
- CTCF_in_10a_profiles_gr, 30
- easyLoad_bed, 30
- easyLoad_broadPeak, 31
- easyLoad_FUN, 32
- easyLoad_IDRmerged, 33
- easyLoad_narrowPeak, 33
- easyLoad_seacr, 34
- expandCigar, 35
- fetchBam, 36
- findMaxPos, 37
- fragLen_calcStranded, 38
- fragLen_fromMacs2Xls, 39
- get_mapped_reads, 40
- getReadLength, 39
- ggellipse, 40
- harmonize_seqlengths, 42
- make_clustering_matrix, 43
- merge_clusters, 44
- prepare_fetch_GRanges, 45

- prepare_fetch_GRanges_names, 46
- prepare_fetch_GRanges_width, 47
- quantileGRangesWidth, 48
- reorder_clusters_hclust, 49
- reorder_clusters_manual, 50
- reorder_clusters_stepdown, 51
- reverse_clusters, 52
- safeBrew, 53
- seqsetvis (seqsetvis-package), 4
- seqsetvis-package, 4
- set_list2memb, 54
- shift_anchor, 55
- split_cluster, 55
- ssv_mclapply, 97
- ssvAnnotateSubjectGRanges, 56, 59, 84
- ssvAnnotateSubjectGRanges, GRanges-method (ssvAnnotateSubjectGRanges), 56
- ssvAnnotateSubjectGRanges, GRangesList-method (ssvAnnotateSubjectGRanges), 56
- ssvAnnotateSubjectGRanges, list-method (ssvAnnotateSubjectGRanges), 56
- ssvConsensusIntervalSets, 58
- ssvFactorizeMembTable, 59
- ssvFeatureBars, 60
- ssvFeatureBinaryHeatmap, 61, 65
- ssvFeatureEuler, 62, 65
- ssvFeaturePie, 63
- ssvFeatureUpset, 64, 65
- ssvFeatureVenn, 65
- ssvFetchBam, 66, 80, 81, 85, 87, 89, 92, 94–96
- ssvFetchBam.single, 66, 69
- ssvFetchBamPE, 70
- ssvFetchBamPE.RNA, 72
- ssvFetchBamPE.single, 72, 74
- ssvFetchBigwig, 4, 11, 76, 80, 81, 85, 87, 89, 92, 94–96
- ssvFetchBigwig.single, 76, 77
- ssvFetchGRanges, 79
- ssvFetchSignal, 80
- ssvMakeMembTable, 59, 64, 65, 82, 86, 87
- ssvMakeMembTable, data.frame-method (ssvMakeMembTable), 82
- ssvMakeMembTable, DataFrame-method (ssvMakeMembTable), 82
- ssvMakeMembTable, GRanges-method (ssvMakeMembTable), 82
- ssvMakeMembTable, GRangesList-method (ssvMakeMembTable), 82
- ssvMakeMembTable, list-method (ssvMakeMembTable), 82
- ssvMakeMembTable, matrix-method (ssvMakeMembTable), 82
- ssvOverlapIntervalSets, 4, 84
- ssvSignalBandedQuantiles, 85
- ssvSignalClustering, 44, 49–53, 56, 86, 102
- ssvSignalHeatmap, 86, 88
- ssvSignalHeatmap.ClusterBars, 88, 91
- ssvSignalLineplot, 93
- ssvSignalLineplotAgg, 95
- ssvSignalScatterplot, 96
- test_peaks, 98
- upset, 64
- UpSetR::upset, 64
- viewGRangesWinSample_dt, 67, 69, 71, 75, 76, 78, 79, 81, 99, 100
- viewGRangesWinSummary_dt, 67, 69, 71, 75, 76, 78, 79, 81, 100
- within_clust_sort, 102