

# Package ‘GAprediction’

January 19, 2026

**Date** 2016-07-04  
**Type** Package  
**Title** Prediction of gestational age with Illumina HumanMethylation450 data  
**Version** 1.36.0  
**Author** Jon Bohlin  
**Maintainer** Jon Bohlin <jon.bohlin@gmail.com>  
**Description** [GAprediction] predicts gestational age using Illumina HumanMethylation450 CpG data.  
**License** GPL (>=2)  
**LazyData** TRUE  
**Depends** R (>= 3.3)  
**Imports** glmnet, stats, utils, Matrix  
**biocViews** ImmunoOncology, DNAMethylation, Epigenetics, Regression, BiomedicalInformatics  
**Suggests** knitr, rmarkdown  
**VignetteBuilder** knitr  
**git\_url** <https://git.bioconductor.org/packages/GAprediction>  
**git\_branch** RELEASE\_3\_22  
**git\_last\_commit** 57760f1  
**git\_last\_commit\_date** 2025-10-29  
**Repository** Bioconductor 3.22  
**Date/Publication** 2026-01-19

## Contents

|                        |          |
|------------------------|----------|
| extractSites . . . . . | 2        |
| predictGA . . . . .    | 3        |
| UL.mod.cv . . . . .    | 4        |
| <b>Index</b>           | <b>5</b> |

---

**extractSites***Extract CpG sites for gestational age prediction*

---

### Description

The function allows the user to extract CpG sites used for gestational age prediction with the function [predictGA](#).

### Usage

```
extractSites(type="se")
```

### Arguments

The argument `type=c("se", "min", "all")` can be used to specify which CpGs are to be extracted. "se" designates the CpGs needed by the `predictGA` function if the penalty term `lambda` is to be set to one standard error within the minimum, "min" specifies the minimum `lambda`, while "all" returns the complete sets of CpGs in the [UL.mod.cv](#) object.

`type` - a string that can be "se" (default), "min" or "all", depending on which CpGs is wanted by the user.

### Details

Use this function if `predictGA` fails due to missing predictor CpGs, or to see which CpGs are used by [predictGA](#) for gestational age prediction.

### Value

Returns a vector with the requested CpG sites.

### Author(s)

Jon Bohlin

### See Also

[predictGA](#), [UL.mod.cv](#)

### Examples

```
CpGs <- extractSites( type="se" )
```

---

`predictGA`*Predict gestational age in days from conception*

---

**Description**

The function `predictGA` takes a matrix with Illumina HumanMethylation450 type DNA methylation data. Column names must designate CpG sites (i.e. 'cgXXXXXX', X=number) and row names samples IDs.

**Usage**

```
predictGA(mldat, transp=TRUE, se=TRUE)
```

**Arguments**

|                     |                                                                                                                                                                                                                                                  |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>mldat</code>  | A matrix containing DNA methylation beta values ( $0 \leq \text{beta} \leq 1$ )                                                                                                                                                                  |
| <code>transp</code> | If TRUE (default), the transpose is automatically taken if the number of rows is greater than the number of columns.                                                                                                                             |
| <code>se</code>     | If <code>se=TRUE</code> , the estimated coefficients are based on the prediction model with the lambda penalty term being allowed to vary up to one standard error within the minimum. If <code>se=FALSE</code> , the minimum lambda is assumed. |

**Details**

The minimum lambda (`se=FALSE`) may result in slightly better predictions, however substantially more CpG sites are needed for estimation. Since the prediction difference is hardly noticeable `se=TRUE` is the default option.

**Value**

The function returns estimated gestational age predictions, together with samples IDs as row names, in a data.frame object.

**Note**

Requires quite a bit of memory due to the large DNA methylation matrix required for the prediction model.

**Author(s)**

Jon Bohlin

**References**

Jon Bohlin, Siri E. Haaberg, Per Magnus, et al. (2016). Prediction of gestational age based on genome-wide differentially methylated regions. *Genome Biology* (in review)

Jerome Friedman, Trevor Hastie, Robert Tibshirani (2010). Regularization Paths for Generalized Linear Models via Coordinate Descent. *Journal of Statistical Software*, 33(1), 1-22. URL <http://www.jstatsoft.org/v33/i01/>.

## Examples

```
## Make a mock Illumina HumanMethylation450 type DNA methylation matrix
cpgs <- extractSites( type="se" )
allcpgs <- extractSites( type="all" )
numsamples <- 100
mlmatr <- matrix( NA, ncol=length( allcpgs ), nrow=numsamples )
mlmatr <- data.frame( mlmatr )
for( i in cpgs )
  mlmatr[,i] <- runif( numsamples, min=0, max=1 )
## Perform gestational age prediction
mypred <- predictGA( mlmatr )
```

---

UL.mod.cv

*A glmnet-object trained to perform gestational age prediction.*


---

## Description

The glmnet-object consists of a Lasso-regression model 'trained' to perform gestational age predictions. It is called by the wrapper function [predictGA](#), which is more user-friendly.

## Details

The trained Lasso-model contains cross-validated estimates of the penalty term lambda that regulates the number of CpG sites needed for gestational age prediction. It is called by the glmnet-inherited predict function with a matrix of CpG betas (with values between 0 and 1) that conforms to the Illumina HumanMethylation450 platform. The gestational age estimates used to train the regression model were taken from the MoBa cohort and are based on ultrasound.

## Source

Magnus P, Irgens LM, Haug K, Nystad W, Skjaerven R, Stoltenberg C, MoBa Study Group. Cohort profile: the Norwegian mother and child cohort study (MoBa). International journal of epidemiology. 2006 Oct 1;35(5):1146-50.

## References

Jerome Friedman, Trevor Hastie, Robert Tibshirani (2010). Regularization Paths for Generalized Linear Models via Coordinate Descent. Journal of Statistical Software, 33(1), 1-22. URL <http://www.jstatsoft.org/v33/i01/>.

## Examples

```
## Extract all non-zero regression coefficients
temp <- as.matrix( coef( UL.mod.cv ) )
allNonZeroCoefs <- rownames( temp )[ temp[,1]!=0 ]
allNonZeroCoefs[ -1 ]
```

# Index

## \* **datasets**

UL.mod.cv, [4](#)

extractSites, [2](#)

predictGA, [2](#), [3](#), [4](#)

UL.mod.cv, [2](#), [4](#)