

# Package ‘LedPred’

January 20, 2026

**Title** Learning from DNA to Predict Enhancers

**Description** This package aims at creating a predictive model of regulatory sequences used to score unknown sequences based on the content of DNA motifs, next-generation sequencing (NGS) peaks and signals and other numerical scores of the sequences using supervised classification. The package contains a workflow based on the support vector machine (SVM) algorithm that maps features to sequences, optimize SVM parameters and feature number and creates a model that can be stored and used to score the regulatory potential of unknown sequences.

**Version** 1.44.0

**Date** 2016-08-13

**Author** Elodie Darbo, Denis Seyres, Aitor Gonzalez

**Maintainer** Aitor Gonzalez <aitor.gonzalez@univ-amu.fr>

**Depends** R (>= 3.2.0), e1071 (>= 1.6)

**Imports** akima, ggplot2, irr, jsonlite, parallel, plot3D, plyr, RCurl, ROCR, testthat

**License** MIT | file LICENSE

**LazyData** true

**biocViews** SupportVectorMachine, Software, MotifAnnotation, ChIPSeq, Sequencing, Classification

**NeedsCompilation** no

**BugReports** <https://github.com/aitgon/LedPred/issues>

**RoxygenNote** 5.0.1

**git\_url** <https://git.bioconductor.org/packages/LedPred>

**git\_branch** RELEASE\_3\_22

**git\_last\_commit** 087da83

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.22

**Date/Publication** 2026-01-19

## Contents

createModel . . . . .	2
crm.features . . . . .	3

evaluateModelPerformance . . . . .	3
feature.ranking . . . . .	4
LedPred . . . . .	4
mapFeaturesToCRMs . . . . .	6
mcTune . . . . .	7
rankFeatures . . . . .	9
scoreData . . . . .	10
tuneFeatureNb . . . . .	10

**Index****12**


---

createModel	<i>Create the model with the optimal features</i>
-------------	---

---

**Description**

createModel function creates a SVM model from the training data set with the selected features.

**Usage**

```
createModel(data, cl = 1, kernel = "radial", cost = 1, gamma = 1,
           valid.times = 10, feature.ranking = NULL, feature.nb = NULL,
           file.prefix = NULL)
```

**Arguments**

data	data.frame containing the training set
cl	integer indicating the column number corresponding to the response vector that classify positive and negative regions (default = 1)
kernel	SVM kernel, a character string: "linear" or "radial". (default = "radial")
cost	The SVM cost parameter for both linear and radial kernels. If NULL (default), the function mcTune is run.
gamma	The SVM gamma parameter for radial kernel. If radial kernel and NULL (default), the function mcTune is run.
valid.times	Integer indicating how many times the training set will be split for the cross validation step (default = 10). This number must be smaller than positive and negative sets sizes.
feature.ranking	List of ordered features.
feature.nb	the optimal number of feature to use from the list of ordered features.
file.prefix	A character string that will be used as a prefix followed by "_model.RData" for the resulting model file, if it is NULL (default), no model is saved

**Value**

the best SVM model

## Examples

```
data(crm.features)
cost <- 1
gamma <- 1
data(feature.ranking)
feature.nb <- 70
#svm.model <- createModel(data.granges=crm.features, cost=cost, gamma=gamma,
#  feature.ranking=feature.ranking, feature.nb=feature.nb)
#feature.weights <- as.data.frame(t(t(svm.model$coefs) %*% svm.model$SV))
```

crm.features

*This is data to be included in my package*

## Description

This is data to be included in my package

evaluateModelPerformance

*Evaluate model performances*

## Description

evaluateModelPerformance function computes the precision and recall measures to evaluate the model through cross validation steps using ROCR package.

## Usage

```
evaluateModelPerformance(data, cl = 1, valid.times = 10,
  feature.ranking = NULL, feature.nb = NULL,
  numcores = ifelse(.Platform$OS.type == "windows", 1, parallel::detectCores() - 1),
  file.prefix = NULL, kernel = "linear", cost = NULL,
  gamma = NULL)
```

## Arguments

data	data.frame containing the training set
cl	integer indicating the column number corresponding to the response vector that classify positive and negative regions (default = 1)
valid.times	Integer indicating how many times the training set will be split for the cross validation step (default = 10). This number must be smaller than positive and negative sets sizes.
feature.ranking	List of ordered features.
feature.nb	the optimal number of feature to use from the list of ordered features.
numcores	Number of cores to use for parallel computing (default: the number of available cores in the machine - 1)

file.prefix	A character string that will be used as a prefix followed by "_ROCR_perf.png" for the result plot file, if it is NULL (default), no plot is returned
kernel	SVM kernel, a character string: "linear" or "radial". (default = "radial")
cost	The SVM cost parameter for both linear and radial kernels. If NULL (default), the function mcTune is run.
gamma	The SVM gamma parameter for radial kernel. If radial kernel and NULL (default), the function mcTune is run.

### Value

A list with two objects.

probs	The predictions computed by the model for each subset during the cross-validation
labels	The actual class for each subset

### Examples

```
data(crm.features)
data(feature.ranking)
#probs.labels.list <- evaluateModelPerformance(data.granges=crm.features,
#      feature.ranking=feature.ranking, feature.nb=50,
#      file.prefix = "test")
#names(probs.labels.list[[1]])
```

---

feature.ranking	<i>This is data to be included in my package</i>
-----------------	--

---

### Description

This is data to be included in my package

---

LedPred	<i>Creates an SVM model given a feature matrix</i>
---------	--

---

### Description

The LedPred function computes the best SVM parameters, defines the optimal features for creating the SVM model by running sequentially mcTune, rankFeatures, tuneFeatureNb and createModel. The performances of this model are then computed usong evaluateModelPerformance.

### Usage

```
LedPred(data = NULL, cl = 1, ranges = list(gamma = c(1, 10), cost = c(1,
10)), cost = NULL, gamma = NULL, kernel = "linear", valid.times = 10,
file.prefix = NULL, numcores = ifelse(.Platform$OS.type == "windows", 1,
parallel::detectCores() - 1), step.nb = 10, halve.above = 100)
```

## Arguments

data	data.frame containing the training set
cl	integer indicating the column number corresponding to the response vector that classify positive and negative regions (default = 1)
ranges	list object containing one (linear kernel) or two (radial kernel) vectors of integers corresponding to SVM cost and SVM gamma parameters to test.
cost	The SVM cost parameter for both linear and radial kernels. If NULL (default), the function mcTune is run.
gamma	The SVM gamma parameter for radial kernel. If radial kernel and NULL (default), the function mcTune is run.
kernel	SVM kernel, a character string: "linear" or "radial". (default = "radial")
valid.times	Integer indicating how many times the training set will be split for the cross validation step (default = 10). This number must be smaller than positive and negative sets sizes.
file.prefix	A character string that will be used as a prefix for the result files. If it is NULL (default), no plot is returned
numcores	Number of cores to use for parallel computing (default: the number of available cores in the machine - 1)
step.nb	Number of features to add at each step (default = 10)
halve.above	During RFE, all the features are ranked at the first round and the half lowest ranked features (that contribute the least in the model) are removed for the next round. When the number of feauture is lower or equal to halve.above, the feautures are removed one by one. (default=100)

## Value

A list of the object produced at each step

best.params	A list of the parameters giving the lowest misclassification error
feature.ranking	List of ordered features from rankFeatures
feature.nb	the optimal number of feature to use from the list of ordered features from tuneFeatureNb
model.svm	The best SVM model createModel
probs.label.list	The cross-validation results from evaluateModelPerformance

## Examples

```
data(crm.features)
#cost_vector <- c(1,3,10)
#gamma_vector <- c(1,3,10)
#ledpred.list=LedPred(data.granges=crm.features, cl=1, ranges = list(cost=cost_vector,
#                                     gamma=gamma_vector), kernel="linear", halve.above=50)
#names(ledpred.list)
```

---

mapFeaturesToCRMs	<i>R interface to bed_to_matrix REST in server</i>
-------------------	--

---

## Description

The `mapFeaturesToCRMs` function allows the user to create a training set matrix to build a predictive model. The training set is composed of positive regions (known to be involved in the pathway of interest) and negative regions (randomly picked or known to not be involved in the pathway of interest) that will be described (scored) by features. Three types of features file format are accepted: Position specific scoring matrices modeling motifs recognised by transcription factors, bed files containing region coordinates for any discrete feature (NGS peaks, conservation blocks) and wig/bigWig files containing signal data. This script has been tested with version 0.99 of the online server. Go here to see current version of the server [http://ifbprod.aitorgonzalezlab.org/map\\_features\\_to\\_crms.php](http://ifbprod.aitorgonzalezlab.org/map_features_to_crms.php)

## Usage

```
mapFeaturesToCRMs(URL = "http://ifbprod.aitorgonzalezlab.org/map_features_to_crms.php",
  positive.bed = NULL, genome = NULL, negative.bed = NULL,
  shuffling = NULL, background.seqs = NULL, genome.info = NULL,
  pssm = NULL, background.freqs = NULL, ngs = NULL, bed.overlap = NULL,
  my.values = NULL, feature.ranking = NULL, feature.nb = NULL,
 .crm.feature.file = NULL, stderr.log.file = NULL, stdout.log.file = NULL)
```

## Arguments

URL	URL of the server REST target
positive.bed	Positive bed file path. Compulsory
genome	Genome code, eg. dm3 for Drosophila Melanogaster. Compulsory
negative.bed	Negative bed file path.
shuffling	Integer with number of time shuffle background sequences (background.seqs). If negative.bed is NULL and shuffling is set at 0, the feature matrix does not contain negative sequences. It is useful to produce a test set matrix.
background.seqs	Background sequences used for shuffling. If shuffling = 0, set this parameter at 0.
genome.info	File require for shuffling bed. If shuffling = 0, set this parameter at 0.
pssm	Position specific scoring matrices
background.freqs	Background frequencies of nucleotides in genome
ngs	NGS (bed and wig) files
bed.overlap	Minimal overlap as a fraction of query sequence with NGS bed peak. Equivalent with <code>intersectBed -f</code> argument. Default 1bp.
my.values	Bed file where fourth column are values to append to the SVM matrix
feature.ranking	File with ranked features (Output of <code>rankFeatures</code> ). It is used for scoring a query bed file
feature.nb	Integer with feature.nb

```

 .crm.feature.file
    Path to feature matrix file
 .stderr.log.file
    Path to error log
 .stdout.log.file
    Path to standard output log

```

### Value

A list

```

feature.matrix a data frame where each row is a region and each column a feature, each cell
               carry a score, the first column is the response vector
stdout.log     Standard output log of mapFeaturesToCRMs script in server
stderr.log     Standard error log of mapFeaturesToCRMs script in server

```

### Examples

```

## Not run:
dirPath <- system.file("extdata", package="LedPred")
file.list <- list.files(dirPath, full.names=TRUE)
background.freqs <- file.list[grep("freq", file.list)]
positive.regions <- file.list[grep("positive", file.list)]
negative.regions <- file.list[grep("negative", file.list)]
TF.matrices <- file.list[grep("tf", file.list)]
ngs.path <- system.file("extdata/ngs", package="LedPred")
ngs.files=list.files(ngs.path, full.names=TRUE)
crm.features.list <- mapFeaturesToCRMs(positive.bed=positive.regions,
                                         negative.bed=negative.regions, background.freqs=background.freqs,
                                         pssm=TF.matrices, genome="dm3", ngs=ngs.files,
                                        .crm.feature.file = "crm.features.tab",
                                         stderr.log.file = "stderr.log", stdout.log.file = "stdout.log")
names(crm.features.list)
class(crm.features.list$crm.features)
crm.features.list$stdout.log
crm.features.list$stderr.log

## End(Not run)

```

---

### Description

The mcTune function is a modified version of the function tune from package e1071 [6]. It tests the different combinations of C and gamma parameters given as vectors in a list and will return the prediction error computed during the cross-validation step.

### Usage

```

mcTune(data, cl = 1, ranges = list(gamma = c(1, 10), cost = c(1, 10)),
       kernel = "linear", valid.times = 10, file.prefix = NULL,
       numcores = ifelse(.Platform$OS.type == "windows", 1, parallel::detectCores() - 1))

```

## Arguments

<code>data</code>	data.frame containing the training set
<code>c1</code>	integer indicating the column number corresponding to the response vector that classify positive and negative regions (default = 1)
<code>ranges</code>	list object containing one (linear kernel) or two (radial kernel) vectors of integers corresponding to SVM cost and SVM gamma parameters to test.
<code>kernel</code>	SVM kernel, a character string: "linear" or "radial". (default = "radial")
<code>valid.times</code>	Integer indicating how many times the training set will be split for the cross validation step (default = 10). This number must be smaller than positive and negative sets sizes.
<code>file.prefix</code>	A character string that will be used as a prefix followed by "_c_g_eval.png" for result plot files, if it is NULL (default), no plot is returned
<code>numcores</code>	Number of cores to use for parallel computing (default: the number of available cores in the machine - 1)

## Value

A list of class tune	
<code>best.parameters</code>	A list of the parameters giving the lowest misclassification error
<code>best.performance</code>	The lowest misclassification error
<code>method</code>	The method used
<code>nparcomb</code>	the number of tested parameter combinations
<code>train.ind</code>	The indexes used to produce subsets during the cross validation step
<code>sampling</code>	The cross-validation fold number
<code>performances</code>	A matrix summarizing the cross-validation step with the error for each tested parameter at each round and the dispersion of these errors (regarding to the average error)
<code>best.model</code>	The model produced by the best parameters

## Examples

```
data(crm.features)
cost.vector <- c(1,3,10,30)
gamma.vector <- c(1,3,10,30)
#c.g.obj <- mcTune(data.granges= crm.features, ranges = list(cost=cost.vector,
#  gamma=gamma.vector), kernel='linear', file.prefix = "test")
#names(c.g.obj)
# cost <- c.g.obj$best.parameters$cost
# gamma <- c.g.obj$best.parameters$gamma
```

---

rankFeatures	<i>Ranking the features according to their importance</i>
--------------	---

---

## Description

The `rankFeatures` function performs a Recursive Feature Elimination (RFE) on subsets of the feature matrix. For each subset the features are ranked according to the weight attributed by SVM at each round of elimination and the average rank of each feature over the subsets is returned. We recommand to save the object containing the ranked features for the following steps.

## Usage

```
rankFeatures(data, cl = 1, halve.above = 100, valid.times = 10,
            kernel = "linear", cost = 1, gamma = 1,
            numcores = ifelse(.Platform$OS.type == "windows", 1, parallel::detectCores() - 1),
            file.prefix = NULL)
```

## Arguments

<code>data</code>	data.frame containing the training set
<code>cl</code>	integer indicating the column number corresponding to the response vector that classify positive and negative regions (default = 1)
<code>halve.above</code>	During RFE, all the features are ranked at the first round and the half lowest ranked features (that contribute the least in the model) are removed for the next round. When the number of feauture is lower or equal to <code>halve.above</code> , the features are removed one by one. (default=100)
<code>valid.times</code>	Integer indicating how many times the training set will be split (default = 10). This number must be smaller than positive and negative sets sizes.
<code>kernel</code>	SVM kernel, a character string: "linear" or "radial". (default = "radial")
<code>cost</code>	The SVM cost parameter for both linear and radial kernels. If <code>NULL</code> (default), the function <code>mcTune</code> is run.
<code>gamma</code>	The SVM gamma parameter for radial kernel. If radial kernel and <code>NULL</code> (default), the function <code>mcTune</code> is run.
<code>numcores</code>	Number of cores to use for parallel computing (default: the number of available cores in the machine - 1)
<code>file.prefix</code>	A character string that will be used as a prefix for output file, if it is <code>NULL</code> (default), no file is writen.

## Value

A 3-columns data frame with ranked features. First column contains the feature names, the second the original position of the feature in the feature.matrix and the third the average rank over the subsets.

## Examples

```
data(crm.features)
cost <- 1
gamma <- 1
#feature.ranking <- rankFeatures(data.granges=crm.features, cost=cost, gamma=gamma,
#      kernel='linear', file.prefix = "test", halve.above=10)
```

scoreData

*Predicting new regulatory regions***Description**

scoreData function predict new regulatory regions using SVM model from a test data set

**Usage**

```
scoreData(data, ledpred = NULL, model = NULL, score.file = NULL)
```

**Arguments**

data	data.frame containing the test set. This test set must have the same descriptive features as the one that were used to build the model.
ledpred	Returned object from the LedPred function
model	Returned object of the createModel function
score.file	A character string that will be used as the file name for the output file, if it is NULL (default), no file is written. The output file takes the form of two columns with object names and scores.

**Value**

A 2-columns dataframe. First column containing the SVM model prediction probabilities and the second containing the corresponding regions

**Examples**

```
data(crm.features)
data(svm.model)
#pred.test <- scoreData(data.granges=crm.features, model=svm.model,
# score.file="test_prediction.tab")
```

tuneFeatureNb

*Selecting the optimal number of features***Description**

tuneFeatureNb iterates through increasing feature numbers to calculate kappa values which represents the performance of the model computed with the given features. We recommend to save the object containing the optimal number of features for the following steps.

**Usage**

```
tuneFeatureNb(data, cl = 1, feature.ranking, step.nb = 10,
  valid.times = 10, cost = NULL, gamma = NULL, kernel = "linear",
  numcores = ifelse(.Platform$OS.type == "windows", 1, parallel::detectCores() - 1), file.prefix = NULL)
```

**Arguments**

data	data.frame containing the training set
c1	integer indicating the column number corresponding to the response vector that classify positive and negative regions (default = 1)
feature.ranking	List of ordered features.
step.nb	Number of features to add at each step (default = 10)
valid.times	Integer indicating how many times the training set will be split for the cross validation step (default = 10). This number must be smaller than positive and negative sets sizes.
cost	The SVM cost parameter for both linear and radial kernels. If NULL (default), the function mcTune is run.
gamma	The SVM gamma parameter for radial kernel. If radial kernel and NULL (default), the function mcTune is run.
kernel	SVM kernel, a character string: "linear" or "radial". (default = "radial")
numcores	Number of cores to use for parallel computing (default: the number of available cores in the machine - 1)
file.prefix	A character string that will be used as a prefix followed by "_kappa_measures.png" for the result plot file. If it is NULL (default), no plot is returned

**Value**

A list with two objects.

performance	2-columns data frame. first column correspond to the number of tested features, second column contains the corresponding kappa value
best.feature.nb	Integer corresponding to the number of features producing the model with the highest kappa value

**Examples**

```
data(crm.features)
data(feature.ranking)
cost <- 1
gamma <- 1
#feature.nb.obj <- tuneFeatureNb(data.granges=crm.features,
#      feature.ranking=feature.ranking, kernel='linear', cost=cost, gamma=gamma,
#      file.prefix = "test")
#names(feature.nb.obj)
```

# Index

createModel, 2  
crm.features, 3  
evaluateModelPerformance, 3  
feature.ranking, 4  
LedPred, 4  
mapFeaturesToCRMs, 6  
mcTune, 7  
rankFeatures, 9  
scoreData, 10  
tuneFeatureNb, 10