

Package ‘Rbec’

January 20, 2026

Type Package

Title Rbec: a tool for analysis of amplicon sequencing data from synthetic microbial communities

Version 1.18.0

Description Rbec is a adapted version of DADA2 for analyzing amplicon sequencing data from synthetic communities (SynComs), where the reference sequences for each strain exists. Rbec can not only accurately profile the microbial compositions in SynComs, but also predict the contaminants in SynCom samples.

License LGPL-3

Imports Rcpp (>= 1.0.6), dada2, ggplot2, readr, doParallel, foreach, grDevices, stats, utils

LinkingTo Rcpp

RoxygenNote 7.1.1

biocViews Sequencing, MicrobialStrain, Microbiome

Suggests knitr, rmarkdown

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/Rbec>

git_branch RELEASE_3_22

git_last_commit 1ce88ce

git_last_commit_date 2025-10-29

Repository Bioconductor 3.22

Date/Publication 2026-01-19

Author Pengfan Zhang [aut, cre]

Maintainer Pengfan Zhang <pzhang@mpipz.mpg.de>

Contents

Contam_detect	2
Rbec	3

Index

5

Contam_detect	<i>Reference-based error correction of amplicon sequencing data</i>
---------------	---

Description

This function is designed for predicting the contaminated samples

Usage

```
Contam_detect(log_file, outdir, outlier_constant=1.5)
```

Arguments

log_file	the file contains a list of log files of each sample outputted with Rbec function
outdir	output directory
outlier_constant	the multiplier of variance to define the outlier

Details

Ruben Garrido-Oter's group, Plant-Microbe interaction, Max Planck Institute for Plant Breeding Research

Value

Returns a plot showing the distribution of percentage of corrected reads across the whole sample set and a summary file recording which samples might be contaminated

Author(s)

Pengfan Zhang

Examples

```
#log_file <- system.file("extdata", "rbec_test.list", package = "Rbec")
log_path <- list.files(paste(path.package("Rbec"),
  "extdata/contamination_test", sep="/"),
  recursive=TRUE, full.names=TRUE)
log_file <- tempfile()
writeLines(log_path, log_file)
Contam_detect(log_file, tempdir())
```

Description

This function corrects the amplicon sequencing data from synthetic communities where the reference sequences are known a priori

Usage

```
Rbec(fastq, reference, outdir, threads=1, sampling_size=5000, ascii=33, min_cont_obs_abd=200, min_
```

Arguments

fastq	the path of the fastq file containg merged amplicon sequencing reads (Ns are not allowed in the reads)
reference	the path of the unique reference sequences, each sequence must be in one line (Ns are not allowed in the sequences)
outdir	the output directory, which should be created by the user
threads	the number of threads used, default 1
sampling_size	the sampling size for calculating the error matrix, default 5000
ascii	ascii characters used to encode phred scores (33 or 64), default 33
min_cont_obs_abd	the minimum oberseved abundace of unique tags for detecting contamination sequences, default 200
min_cont_abd	the relative abundance of unique tgas for detecting contamination sequences that can't be corrected by any of the references, default 0.03
min_E	the minimum expectation of the Possion distribution for the identification of paralogues, default 0.05
min_P	the minimum P value threshold of the Possion distribution to correct a read, default 1e-40
ref_seeker	the method for finding the candidate error-producing reference sequence for a tag showing identical lowest K-mer distance to multiple references. 1 for the abundance-based method; 2 for the transition probability-based method, default 1.
cn	the copy number table documenting the copy number of the marker gene in each strain. Rbec will normalize the strain abundance if the copy number is available

Details

Ruben Garrido-Oter's group, Plant-Microbe interaction, Max Planck Institute for Plant Breeding Research

Value

lambda_final.out the lambda value and pvalue of the Poisson distribution for each read
error_matrix_final.out the error matrix in the final iteration
strain_table.txt the strain composition of the sample
strain_table_normalized.txt the copy-number-normalized strain composition of the sample if the copy number table is provided
contamination_seq.fna the potential sequences generated by contaminants
rbec.log percentage of corrected reads, which can be used to predict contaminated samples
parologue_seq.fna parologue sequences found in each strain except for the reference provided

Author(s)

Pengfan Zhang

Examples

```
fastq <- system.file("extdata", "test_raw_merged_reads.fastq.gz", package = "Rbec")  
  
ref <- system.file("extdata", "test_ref.fasta", package = "Rbec")  
  
Rbec(fastq=fastq, reference=ref, outdir=tempdir(), threads=1, sampling_size=500, ascii=33)
```

Index

Contam_detect, 2

Rbec, 3