

Package ‘TPP’

January 20, 2026

Type Package

Title Analyze thermal proteome profiling (TPP) experiments

Version 3.38.0

Author Dorothee Childs, Nils Kurzawa, Holger Franken, Carola Doce, Mikhail Savitski and Wolfgang Huber

Maintainer Dorothee Childs <d.childs@posteo.de>

Depends R (>= 3.4), Biobase, dplyr, magrittr, tidyverse

Imports biobroom, broom, data.table, doParallel, foreach, futile.logger, ggplot2, grDevices, gridExtra, grid, knitr, limma, MASS, mefa, nls2, openxlsx (>= 2.4.0), parallel, plyr, purrr, RColorBrewer, RCurl, reshape2, rmarkdown, splines, stats, stringr, tibble, utils, VennDiagram, VGAM

Suggests BiocStyle, testthat

Description Analyze thermal proteome profiling (TPP) experiments with varying temperatures (TR) or compound concentrations (CCR).

License Artistic-2.0

VignetteBuilder knitr

biocViews ImmunoOncology, Proteomics, MassSpectrometry

git_url <https://git.bioconductor.org/packages/TPP>

git_branch RELEASE_3_22

git_last_commit 958aced

git_last_commit_date 2025-10-29

Repository Bioconductor 3.22

Date/Publication 2026-01-19

Contents

analyze2DTTP	3
analyzeTPPCCR	6
analyzeTPPTR	8
hdacCCR_config	11
hdacCCR_data	12
hdacCCR_smallExample	13
hdacTR_config	13

hdacTR_data	14
hdacTR_resultsTable_smallExample	14
hdacTR_smallExample	15
panobinostat_2DTPP_config	15
panobinostat_2DTPP_data	16
panobinostat_2DTPP_smallExample	16
resultTable	16
TPP	17
TPP-defunct	17
TPP-deprecated	18
tpp2dAddAdditionalInfo	18
tpp2dCalcFractAbundance	19
tpp2dComputeFoldChanges	20
tpp2dCreateDRplots	21
tpp2dCreateReport	22
tpp2dCreateTPPTRreference	24
tpp2dCurveFit	25
tpp2dExport	26
tpp2dExportPlots	28
tpp2dImport	28
tpp2dMerge2dRef	29
tpp2dNormalize	31
tpp2dPlotQChist	32
tpp2dPlotQCpEC50	32
tpp2dSplineFitAndTest	33
tpp2dSplinePlot	35
tpp2dTRReferenceObject	36
tppccrCurveFit	36
tppccrImport	38
tppccrNormalize	39
tppccrNormalizeToReference	40
tppccrPlotCurves	41
tppccrResultTable	42
tppccrTransform	43
tppDefaultTheme	44
tppExport	45
tppQCPLOTSCorrelateExperiments	46
tppRefData	47
tpptrAnalyzeMeltingCurves	47
tpptrCurveFit	48
tpptrDefaultNormReqs	50
tpptrFitSplines	50
tpptrFTest	51
tpptrImport	52
tpptrNormalize	54
tpptrPlotSplines	55
tpptrSplineFitAndTest	57
tpptrTidyUpESets	59
TPPTR_reference_results_HepG2	59
Index	60

analyze2DTPP	<i>Analyze a 2D-TPP experiment</i>
--------------	------------------------------------

Description

Performs the whole analysis workflow for 2D-TPP experiment by invoking routines for data import, data processing, fold change computation, median normalization, TPP-CCR curve fitting, plotting and production of the result table.

Usage

```
analyze2DTPP(  
  configTable,  
  data = NULL,  
  resultPath = NULL,  
  idVar = "gene_name",  
  fcStr = NULL,  
  intensityStr = "signal_sum_",  
  naStrs = c("NA", "n/d", "NaN", "<NA>"),  
  methods = "doseResponse",  
  qualColName = "qupm",  
  compFc = TRUE,  
  normalize = TRUE,  
  addCol = NULL,  
  nCores = 1,  
  nonZeroCols = "qssm",  
  fcTolerance = 0.1,  
  r2Cutoff = 0.8,  
  fcCutoff = 1.5,  
  slopeBounds = c(1, 50),  
  fractAbund = FALSE,  
  xlsxExport = TRUE,  
  plotAll = FALSE,  
  plotAllR2 = FALSE,  
  plotSingle = FALSE,  
  trRef = NULL,  
  refFcStr = "norm_rel_fc_",  
  addInfo = FALSE,  
  createReport = "none",  
  paletteName = "Spectral",  
  configFile  
)
```

Arguments

configTable	dataframe, or character object with the path to a file, that specifies important details of the 2D-TPP experiment. See Section details for instructions how to create this object.
data	single dataframe, containing fold change measurements and additional annotation columns to be imported. Can be used instead of specifying the file path in the configTable argument.

resultPath	location where to store dose-response curve plots and results table.
idVar	character string indicating which data column provides the unique identifiers for each protein.
fcStr	character string indicating which columns contain the actual fold change values. Those column names containing the prefix <code>fcStr</code> will be regarded as containing fold change values. Only relevant if <code>compFC = FALSE</code> .
intensityStr	character string indicating which columns contain the actual sumionarea values. Those column names containing the prefix <code>intensityStr</code> will be regarded as containing sumionarea values.
naStrs	character vector indicating missing values in the data table. When reading data from file, this value will be passed on to the argument <code>na.strings</code> in function <code>read.delim</code> .
methods	vector of character strings that indicate which methods should be used for the analysis (default: <code>c("doseResponse")</code> , alternative: <code>c("splineFit")</code> or <code>c("doseResponse", "splineFit")</code>)
qualColName	character string indicating which column can be used for additional quality criteria when deciding between different non-unique protein identifiers.
compFc	boolean flag which indicates whether to perform fold change computation regarding reference column from sumionareas (default: <code>TRUE</code>)
normalize	perform median normalization (default: <code>TRUE</code>).
addCol	character vector indicating which additional columns to include from the input data
nCores	either a numerical value given the desired number of CPUs, or 'max' to automatically assign the maximum possible number (default).
nonZeroCols	character string indicating a column that will be used for filtering out zero values.
fcTolerance	tolerance for the <code>fcCutoff</code> parameter. See details.
r2Cutoff	Quality criterion on dose response curve fit.
fcCutoff	Cutoff for highest compound concentration fold change.
slopeBounds	Bounds on the slope parameter for dose response curve fitting.
fractAbund	boolean variable, if set to <code>TRUE</code> additional information concerning sumionarea fractional abundance and dmsol vs. dmsol2 of adjacent temperatures is added to the output table
xlsxExport	produce results table in xlsx format and store at the location specified by the <code>resultPath</code> argument.
plotAll	boolean value indicating whether all dose response curves should be generated. Deactivating plotting decreases runtime.
plotAllR2	boolean value indicating whether all dose response curves which fulfill the demanded criteria (Rsquared, maximum plateau) should be generated. Deactivating plotting decreases runtime.
plotSingle	boolean value indicating whether all dose response curves which fulfill the demanded criteria (Rsquared, maximum plateau) should be generated. Deactivating plotting decreases runtime.
trRef	character string containing a valid system path to a previously generated TPP-TR reference object

refFcStr	character string indicating which columns in the reference data set contain the fold change values
addInfo	boolean variable, if set to TRUE additional information on counts of stabilization and destabilization of each protein is added to the output table
createReport	character string indicating whether a markdown report should be created and which format it have (default: "html_document", alternative: "pdf_document" or "none")
paletteName	color palette (see details).
configFile	DEPRECATED

Details

Invokes the following steps:

1. Import data using the [tpp2dImport](#) function.
2. Remove zero sumionarea values.
3. Compute fold changes from raw data (sumionarea)
4. Perform normalization by fold change medians (optional) using the [tpp2dNormalize](#) function. To perform normalization, set argument `normalize=TRUE`.

`paletteName` specifies the color palette to be used by the [brewer.pal](#) function from the RColorBrewer package to assign a separate color to each concentration.

Value

A data frame in which the model results (slopes and pEC50 values) are stored row-wise for each protein and administered temperatures.

References

Becher, I., Werner, T., Doce, C., Zaal, E. A., Berkers, C. R., T"ogel, I., Salzer, E., Bantscheff, M., Savitski, M. M. (2016) Thermal profiling reveals phenylalanine hydroxylase as an off-target of panobinostat. *Nature Chemical Biology*, 12(11), 908-910.

Examples

```
data(panobinostat_2DTPP_smallExample)
config_tpp2d <- panobinostat_2DTPP_config
data_tpp2d <- panobinostat_2DTPP_data
tpp2dResults <- analyze2DTPP(configTable = config_tpp2d,
                                data = data_tpp2d,
                                methods=c("doseResponse"),
                                createReport="none",
                                nCores=1,
                                idVar = "representative",
                                addCol = "clustername",
                                intensityStr = "sumionarea_protein_",
                                nonZeroCols = "qusm")
```

analyzeTPPCCR	<i>Analyze TPP-CCR experiment</i>
---------------	-----------------------------------

Description

Performs analysis of a TPP-CCR experiment by invoking routines for data import, data processing, normalization, curve fitting, and production of the result table.

Usage

```
analyzeTPPCCR(
  configTable,
  data = NULL,
  resultPath = NULL,
  idVar = "gene_name",
  fcStr = "rel_fc_",
  naStrs = c("NA", "n/d", "NaN", "<NA>"),
  qualColName = "qupm",
  normalize = TRUE,
  ggplotTheme = tppDefaultTheme(),
  nCores = "max",
  nonZeroCols = "qssm",
  r2Cutoff = 0.8,
  fcCutoff = 1.5,
  slopeBounds = c(1, 50),
  plotCurves = TRUE,
  verbose = FALSE,
  xlsxExport = TRUE,
  fcTolerance = 0.1
)
```

Arguments

<code>configTable</code>	dataframe, or character object with the path to a file, that specifies important details of the TPP-CCR experiment. See Section details for instructions how to create this object.
<code>data</code>	single dataframe, containing fold change measurements and additional annotation columns to be imported. Can be used instead of specifying the file path in the <code>configTable</code> argument.
<code>resultPath</code>	location where to store dose-response curve plots and results table.
<code>idVar</code>	character string indicating which data column provides the unique identifiers for each protein.
<code>fcStr</code>	character string indicating which columns contain the actual fold change values. Those column names containing the suffix <code>fcStr</code> will be regarded as containing fold change values.
<code>naStrs</code>	character vector indicating missing values in the data table. When reading data from file, this value will be passed on to the argument <code>na.strings</code> in function <code>read.delim</code> .
<code>qualColName</code>	character string indicating which column can be used for additional quality criteria when deciding between different non-unique protein identifiers.

normalize	perform median normalization (default: TRUE).
ggplotTheme	ggplot theme for dose response curve plots.
nCores	either a numerical value given the desired number of CPUs, or 'max' to automatically assign the maximum possible number (default).
nonZeroCols	character string indicating a column that will be used for filtering out zero values.
r2Cutoff	Quality criterion on dose response curve fit.
fcCutoff	Cutoff for highest compound concentration fold change.
slopeBounds	Bounds on the slope parameter for dose response curve fitting.
plotCurves	boolean value indicating whether dose response curves should be plotted. Deactivating plotting decreases runtime.
verbose	print name of each fitted or plotted protein to the command line as a means of progress report.
xlsxExport	produce results table in xlsx format and store at the location specified by the resultPath argument.
fcTolerance	tolerance for the fcCutoff parameter. See details.

Details

Invokes the following steps:

1. Import data using the [tppccrImport](#) function.
2. Perform normalization by fold change medians (optional) using the [tppccrNormalize](#) function. To perform normalization, set argument normalize=TRUE.
3. Fit and analyze dose response curves using the [tppccrCurveFit](#) function.
4. Export results to Excel using the [tppExport](#) function.

The default settings are tailored towards the output of the python package isobarQuant, but can be customized to your own dataset by the arguments idVar, fcStr, naStrs, qualColName.

If resultPath is not specified, result files are stored at the path defined in the first entry of configTable\$Path. If the input data are not specified in configTable, no result path will be set. This means that no output files or dose response curve plots are produced and analyzeTPPCCR just returns the results as a data frame.

The function analyzeTPPCCR reports intermediate results to the command line. To suppress this, use [suppressMessages](#).

The dose response curve plots will be stored in a subfolder with name DoseResponse_Curves at the location specified by resultPath.

Only proteins with fold changes bigger than $[fcCutoff * (1 - fcTolerance)]$ or smaller than $1 / [fcCutoff * (1 - fcTolerance)]$ will be used for curve fitting. Additionally, the proteins fulfilling the fcCutoff criterion without tolerance will be marked in the output column `meets_FC_requirement`.

Value

A data frame in which the fit results are stored row-wise for each protein.

References

Savitski, M. M., Reinhard, F. B., Franken, H., Werner, T., Savitski, M. F., Eberhard, D., ... & Drewes, G. (2014). Tracking cancer drugs in living cells by thermal profiling of the proteome. *Science*, 346(6205), 1255784.

Franken, H, Mathieson, T, Childs, D, Sweetman, G, Werner, T, Huber, W. & Savitski, M. M. (2015), Thermal proteome profiling for unbiased identification of drug targets and detection of downstream effectors. *Nature protocols* 10(10), 1567-1593.

See Also

`tppDefaultTheme`

Examples

```
data(hdacCCR_smallExample)
tppcrResults <- analyzeTPPCCR(configTable=hdacCCR_config,
                                 data=hdacCCR_data, nCores=1)
```

analyzeTPPTR

Analyze TPP-TR experiment

Description

Performs analysis of a TPP-TR experiment by invoking routines for data import, data processing, normalization, curve fitting, and production of the result table.

Usage

```
analyzeTPPTR(
  configTable,
  data = NULL,
  resultPath = NULL,
  methods = c("meltcurvefit", "splinefit"),
  idVar = "gene_name",
  fcStr = "rel_fc_",
  ciStr = NULL,
  naStrs = c("NA", "n/d", "NaN", "<NA>"),
  qualColName = "qupm",
  normalize = TRUE,
  normReqs = tpptrDefaultNormReqs(),
  ggplotTheme = tppDefaultTheme(),
  nCores = "max",
  startPars = c(P1 = 0, a = 550, b = 10),
  splineDF = c(3:7),
  maxAttempts = 500,
  plotCurves = TRUE,
  fixedReference = NULL,
  pValMethod = "robustZ",
  pValFilter = list(minR2 = 0.8, maxPlateau = 0.3),
  pValParams = list(binWidth = 300),
```

```

  verbose = FALSE,
  xlsxExport = TRUE
)

```

Arguments

configTable	dataframe, or character object with the path to a file, that specifies important details of the TPP-TR experiment. See Section details for instructions how to create this object.
data	single dataframe, or list of dataframes, containing fold change measurements and additional annotation columns to be imported. Can be used instead of specifying the file path in the configTable argument.
resultPath	location where to store melting curve plots, intermediate results, and the final results table.
methods	statistical methods for modeling melting behavior and detecting significant differences between experimental conditions. If more than one method are specified, results will be computed for each and concatenated in the result table (default: meltcurvefit).
idVar	character string indicating which data column provides the unique identifiers for each protein.
fcStr	character string indicating which columns contain the actual fold change values. Those column names containing the suffix fcStr will be regarded as containing fold change values.
ciStr	character string indicating which columns contain confidence intervals for the fold change measurements. If specified, confidence intervals will be plotted around the melting curves.
naStrs	character vector indicating missing values in the data table. When reading data from file, this value will be passed on to the argument na.strings in function read.delim.
qualColName	character string indicating which column can be used for additional quality criteria when deciding between different non-unique protein identifiers.
normalize	perform normalization (default: TRUE).
normReqs	list of filtering criteria for construction of the normalization set.
ggplotTheme	ggplot theme for melting curve plots.
nCores	either a numerical value given the desired number of CPUs, or 'max' to automatically assign the maximum possible number (default).
startPars	start values for the melting curve parameters. Will be passed to function <code>nls</code> for curve fitting.
splineDF	degrees of freedom for natural spline fitting.
maxAttempts	maximal number of curve fitting attempts if model does not converge.
plotCurves	boolean value indicating whether melting curves should be plotted. Deactivating plotting decreases runtime.
fixedReference	name of a fixed reference experiment for normalization. If NULL (default), the experiment with the best R2 when fitting a melting curve through the median fold changes is chosen as the reference.
pValMethod	Method for p-value computation. Currently restricted to 'robustZ' (see Cox & Mann (2008)).

pValFilter	optional list of filtering criteria to be applied before p-value computation.
pValParams	optional list of parameters for p-value computation.
verbose	print name of each fitted protein to the command line as a means of progress report.
xlsxExport	boolean value indicating whether to produce result table in .xlsx format (requires package openxlsx and a zip application to be installed).

Details

Invokes the following steps:

1. Import data using the [tpptrImport](#) function.
2. Perform normalization (optional) using the [tpptrNormalize](#) function. To perform normalization, set argument `normalize=TRUE`. The normalization will be filtered according to the criteria specified in the `normReqs` argument (also see the documentation of [tpptrNormalize](#) and [tpptrDefaultNormReqs](#) for further information).
3. Fit melting curves using the function [tpptrCurveFit](#).
4. Produce result table using the function [tpptrAnalyzeMeltingCurves](#).
5. Export results to Excel using the function [tppExport](#).

The default settings are tailored towards the output of the python package isobarQuant, but can be customized to your own dataset by the arguments `idVar`, `fcStr`, `naStrs`, `qualColName`.

If `resultPath` is not specified, the location of the first input file specified in `configTable` will be used. If the input data are not specified in `configTable`, no result path will be set. This means that no output files or melting curve plots are produced and `analyzeTPPTR` just returns the results as a data frame.

The function `analyzeTPPTR` reports intermediate results to the command line. To suppress this, use [suppressMessages](#).

The `configTable` argument is a dataframe, or the path to a spreadsheet (tab-delimited text-file or .xlsx format). Information about each experiment is stored row-wise. It contains the following columns:

- `Path`: location of each datafile. Alternatively, data can be directly handed over by the `data` argument.
- `Experiment`: unique experiment names.
- `Condition`: experimental conditions of each dataset.
- `Label` columns: each isobaric label names a column that contains the temperatures administered for the label in the individual experiments.

The argument `methods` can be one of the following: More than one method can be specified. For example, parametric testing of melting points and nonparametric spline-based goodness-of-fit tests can be performed sequentially in the same analysis. The results are then written to separate columns of the output table.

If `methods` contains "meltcurvefit", melting curve plots will be stored in a subfolder with name `Melting_Curves` at the location specified by `resultPath`. If `methods` contains "splinefit", plots of the natural spline fits will be stored in a subfolder with name `Spline_Fits` at the location specified by `resultPath`.

The argument `nCores` could be either 'max' (use all available cores) or an upper limit of CPUs to be used.

If `doPlot` = TRUE, melting curve plots are generated separately for each protein and stored in separate pdfs. Each file is named by the unique protein identifier. Filenames are truncated to 255 characters (requirement by most operation systems). Truncated filenames are indicated by the suffix "`_truncated[d]`", where [d] is a unique number to avoid redundancies. All melting curve plots are stored in a subfolder with name `Melting_Curves` at the location specified by `resultPath`.

If the melting curve fitting procedure does not converge, it will be repeatedly started from perturbed starting parameters (maximum iterations defined by argument `maxAttempts`).

Argument `splineDF` specifies the degrees of freedom for natural spline fitting. As a single numeric value, it is directly passed on to the `splineDF` argument of `splines::ns`. Experience shows that `splineDF` = 4 yields good results for TPP data sets with 10 temperature points. It is also possible to provide a numeric vector. In this case, splines are fitted for each entry and the optimal value is chosen per protein using Akaike's Information criterion.

Value

A data frame in which the fit results are stored row-wise for each protein.

References

Savitski, M. M., Reinhard, F. B., Franken, H., Werner, T., Savitski, M. F., Eberhard, D., ... & Drewes, G. (2014). Tracking cancer drugs in living cells by thermal profiling of the proteome. *Science*, 346(6205), 1255784.

Franken, H., Mathieson, T., Childs, D., Sweetman, G., Werner, T., Huber, W. & Savitski, M. M. (2015), Thermal proteome profiling for unbiased identification of drug targets and detection of downstream effectors. *Nature protocols* 10(10), 1567-1593.

See Also

`tppDefaultTheme`, `tpptrImport`, `tpptrNormalize`, `tpptrCurveFit`, `tpptrAnalyzeMeltingCurves`

Examples

```
data(hdacTR_smallExample)
tpptrResults <- analyzeTPPTR(configTable = hdacTR_config, data = hdacTR_data,
                               methods = "meltcurvefit", nCores = 1)
```

hdacCCR_config

The configuration table to analyze [hdacCCR_data](#).

Description

The configuration table to analyze [hdacCCR_data](#).

Details

`hdacCCR_config` is a data frame that specifies the experiment names, isobaric labels, and the administered drug concentrations at each label.

References

Franken, H, Mathieson, T, Childs, D. Sweetman, G. Werner, T. Huber, W. & Savitski, M. M. (2015), Thermal proteome profiling for unbiased identification of drug targets and detection of downstream effectors. *Nature protocols* 10(10), 1567-1593.

See Also

[hdacCCR_smallExample](#), [hdacCCR_data](#)

hdacCCR_data

TPP-CCR example dataset (replicates 1 and 2)

Description

Example subset of a Panobinostat TPP-CCR dataset (replicates 1 and 2)

Details

A list with two subsets of a dataset obtained by TPP-CCR experiments to investigate drug effects for HDAC inhibitor Panobinostat. It contains 7 HDACs as well as a random selection of 493 further proteins.

You can use this dataset to explore the [TPP](#) package functionalities without invoking the whole time consuming analysis on the big dataset.

The original dataset is located in the folder 'example_data/CCR_example_data' in the package's installation directory. You can find it on your system by the R command `system.file('example_data', package = 'TPP')`. The measurements were generated by four separate multiplexed TMT experiments with 10 TMT labels each. Quantitative values per protein were obtained by the python software isobarQuant and converted to fold changes relative to the lowest temperature. The raw data before quantification can be found in the `proteomicsDB` database (<http://www.proteomicsdb.org/#projects/4221/3102>) with the following sample mapping:

- Panobinostat_1: MS-experiment numbers P97404B02-B10
- Panobinostat_2: MS-experiment numbers P97414B02-B10

References

Franken, H, Mathieson, T, Childs, D. Sweetman, G. Werner, T. Huber, W. & Savitski, M. M. (2015), Thermal proteome profiling for unbiased identification of drug targets and detection of downstream effectors. *Nature protocols* 10(10), 1567-1593.

See Also

[hdacCCR_smallExample](#), [hdacTR_config](#)

`hdacCCR_smallExample` *Example subsets of a Panobinostat TPP-CCR dataset (replicates 1 and 2) and the corresponding configuration table to start the analysis.*

Description

Example dataset obtained by TPP-CCR experiments for analysis by the TPP-package. It contains all necessary arguments to start the analysis (config table and list of data frames).

References

Franken, H, Mathieson, T, Childs, D, Sweetman, G, Werner, T, Huber, W. & Savitski, M. M. (2015), Thermal proteome profiling for unbiased identification of drug targets and detection of downstream effectors. *Nature protocols* 10(10), 1567-1593.

See Also

[hdacCCR_data](#), [hdacCCR_config](#)

`hdacTR_config` *The configuration table to analyze [hdacTR_data](#).*

Description

The configuration table to analyze [hdacTR_data](#).

Details

`hdacTR_config` is a data frame that specifies the experiment name, isobaric labels, and the administered temperatures at each label.

References

Franken, H, Mathieson, T, Childs, D, Sweetman, G, Werner, T, Huber, W. & Savitski, M. M. (2015), Thermal proteome profiling for unbiased identification of drug targets and detection of downstream effectors. *Nature protocols* 10(10), 1567-1593.

See Also

[hdacTR_smallExample](#), [hdacTR_data](#)

hdacTR_data	<i>TPP-TR example dataset.</i>
-------------	--------------------------------

Description

Example subset of a dataset obtained by TPP-TR experiments to investigate possible targets for HDAC inhibitor Panobinostat.

Details

hdacTR_data is a list of data frames that contain measurements for HDACs as well as a random selection of 500 further proteins.

You can use this dataset to explore the [TPP](#) package functionalities without invoking the whole time consuming analysis on the whole dataset.

The original dataset is located in the folder 'example_data/TR_example_data' in the package's installation directory. You can find it on your system by the R command `system.file('example_data', package = 'TPP')`.

The measurements were generated by four separate multiplexed TMT experiments with 10 TMT labels each. Quantitative values per protein were obtained by the python software isobarQuant and converted to fold changes relative to the lowest temperature. The raw data before quantification can be found in the proteomicsDB database (<http://www.proteomicsdb.org/#projects/4221/3101>) with the following sample mapping:

- Panobinostat_1: MS-experiment numbers P85192B02-B10
- Panobinostat_2: MS-experiment numbers P85881B02-B10
- Vehicle_1: MS-experiment numbers P85202B02-B10
- Vehicle_2: MS-experiment numbers P85891B02-B10

References

Franken, H, Mathieson, T, Childs, D, Sweetman, G, Werner, T, Huber, W, & Savitski, M. M. (2015), Thermal proteome profiling for unbiased identification of drug targets and detection of downstream effectors. *Nature protocols* 10(10), 1567-1593.

See Also

[hdacTR_smallExample](#), [hdacTR_config](#)

hdacTR_resultsTable_smallExample	<i>Example of a TPP-TR result table.</i>
----------------------------------	--

Description

Example of a TPP-TR result table.

Details

Contains the data object [resultTable](#).

hdacTR_smallExample	<i>Example subset of a Panobinostat TPP-TR dataset and the corresponding configuration table to start the analysis.</i>
---------------------	---

Description

Example dataset obtained by TPP-TR experiments for analysis by the TPP-package. It contains all necessary arguments to start the analysis (config table and list of data frames).

References

Franken, H, Mathieson, T, Childs, D, Sweetman, G, Werner, T, Huber, W, & Savitski, M. M. (2015), Thermal proteome profiling for unbiased identification of drug targets and detection of downstream effectors. *Nature protocols* 10(10), 1567-1593.

See Also

[hdacTR_data](#), [hdacTR_config](#)

panobinostat_2DTPP_config

The configuration table to analyze [panobinostat_2DTPP_data](#).

Description

The configuration table to analyze [panobinostat_2DTPP_data](#).

Details

`panobinostat_2DTPP_config` is a data frame that specifies the experiment names, isobaric labels, and the administered drug concentrations at each label.

See Also

[panobinostat_2DTPP_data](#), [panobinostat_2DTPP_smallExample](#)

panobinostat_2DTPP_data*2D-TPP-CCR example dataset*

Description

Example subset of a Panobinostat 2D-TPP dataset

Details

A list with two subsets of a dataset obtained by 2D-TPP experiments to investigate drug effects for HDAC inhibitor Panobinostat. The experiment was performed on living HepG2 cells (see Becher et al. (2016). Thermal profiling reveals phenylalanine hydroxylase as an off-target of panobinostat. *Nature Chemical Biology*, (September)) It contains 7 HDACs as well as a random selection of 493 further proteins.

You can use this dataset to explore the [TPP](#) package functionalities without invoking the whole time consuming analysis on the big dataset.

See Also

[panobinostat_2DTPP_config](#), [panobinostat_2DTPP_smallExample](#)

panobinostat_2DTPP_smallExample*Example subsets of a Panobinostat 2D-TPP dataset and the corresponding configuration table to start the analysis.*

Description

Example dataset obtained by 2D-TPP experiments for analysis by the TPP-package. It contains all necessary arguments to start the analysis (config table and list of data frames).

See Also

[panobinostat_2DTPP_data](#), [panobinostat_2DTPP_config](#)

resultTable*Example of a TPP-TR result table.*

Description

Example of a TPP-TR result table.

Details

`resultTable` is a data frame that contains the measurements of several TPP-TR experiments, the fitted melting curve parameters, as well as p-values and the results of additional quality checks for each protein. It can be used as input for the function [tppQCPlotsCorrelateExperiments](#).

TPP	<i>Thermal proteome profiling (TPP)</i>
-----	---

Description

TPP is a toolbox for analyzing thermal proteome profiling (TPP) experiments.

Usage

```
.onLoad(libname, pkgname)
```

Arguments

libname	a character string giving the library directory where the package defining the namespace was found. Passed to .onLoad function.
pkgname	a character string giving the name of the package. Passed to .onLoad function.

Details

In order to start a TPP-TR analysis, use function [analyzeTPPTR](#). For a TPP-CCR analysis, use function [analyzeTPPCCR](#). See the vignette for detailed instructions.

Value

No return value defined for this document.

References

Savitski, M. M., Reinhard, F. B., Franken, H., Werner, T., Savitski, M. F., Eberhard, D., ... & Drewes, G. (2014). Tracking cancer drugs in living cells by thermal profiling of the proteome. *Science*, 346(6205), 1255784.

Franken, H., Mathieson, T., Childs, D., Sweetman, G., Werner, T., Huber, W. & Savitski, M. M. (2015), Thermal proteome profiling for unbiased identification of drug targets and detection of downstream effectors. *Nature protocols* 10(10), 1567-1593.

TPP-defunct	<i>Defunct functions in package 'TPP'</i>
-------------	---

Description

These functions are defunct and no longer available.

Usage

```
tpp2dPlotCCRGoodCurves()
tpp2dPlotCCRAllCurves()
tpp2dPlotCCRSingleCurves()
tpp2dEvalConfigTable()
tpp2dRemoveZeroSias()
tpp2dReplaceColNames()
tpp2dCreateCCRConfigFile()
```

Details

Defunct functions are: tpp2dPlotCCRGoodCurves, tpp2dPlotCCRAllCurves, tpp2dPlotCCRSingleCurves, tpp2dEvalConfigTable, tpp2dRemoveZeroSias, tpp2dReplaceColNames, tpp2dCreateCCRConfigFile

Value

No value returned

TPP-deprecated

Deprecated functions in package 'TPP'

Description

These functions are deprecated and no longer available.

Value

No value returned

tpp2dAddAdditionalInfo

Add additional info to 2D-TPP CCR output data

Description

Adds additional info to 2D-TPP CCR output data, like counts on how often a certain protein was stabilized or destabilized

Usage

```
tpp2dAddAdditionalInfo(data, idVar = "gene_name")
```

Arguments

data	output table returned by the tpp2dCurveFit function
idVar	character string indicating which column of the data table contains unique protein ids

Value

A data frame to which additional data like how often a protein has been (de-)stabilized has been attached

Examples

```
load(system.file("example_data/2D_example_data/shortCCRresults.RData", package="TPP"))
shortCCRresults <- tpp2dAddAdditionalInfo(data = shortCCRresults, idVar="representative")
```

tpp2dCalcFractAbundance

Calculate fractional abundance and DMSO ratio of successive sumionareas (usage of function is only reasonable when at least two temperatures are multiplexed!)

Description

Calculates fractional abundance and DMSO ratio of successive sumionareas and creates respective columns which are added to the data frame which is handed over

Usage

```
tpp2dCalcFractAbundance(
  configTable = NULL,
  data,
  intensityStr = NULL,
  idVar = NULL
)
```

Arguments

configTable	DEPRECATEDE
data	data frame of TPP-CCR results (e.g. obtained by run2DTPPCCR).
intensityStr	DEPRECATEDE
idVar	DEPRECATEDE

Value

Data frame that was handed over with additional columns of fractional abundance and DMSO1 vs DMSO2 ratio

Examples

```
data(panobinostat_2DTPP_smallExample)

# Import data:
datIn <- tpp2dImport(configTable = panobinostat_2DTPP_config,
                      data = panobinostat_2DTPP_data,
                      idVar = "representative",
                      addCol = "clustername",
                      intensityStr = "sumionarea_protein_",
                      nonZeroCols = "qusm")

# View attributes of imported data (experiment infos and import arguments):
attr(datIn, "importSettings") %>% unlist
attr(datIn, "configTable")

# Compute fractional abundance:
datDMSORatio <- tpp2dCalcFractAbundance(data = datIn)
colnames(datDMSORatio)
```

tpp2dComputeFoldChanges
Compute 2D-TPP fold changes

Description

Computes fold changes by calculating fold changes of the sumionarea relative to the reference column.

Usage

```
tpp2dComputeFoldChanges(
  configTable = NULL,
  data,
  intensityStr = NULL,
  fcStr = NULL,
  newFcStr = "rel_fc_"
)
```

Arguments

configTable	DEPRECATED
data	dataframe that contain the data for the 2D-TPP experiment
intensityStr	DEPRECATED
fcStr	DEPRECATED
newFcStr	character string indicating how columns that will contain the actual fold change values will be called. The suffix newFcStr will be pasted in front of the names of the experiments.

Value

A data.frame with additional columns with constitute fold changes calculated with respect to the intensity values of the zero treatment column

Examples

```
# Preparation:
data(panobinostat_2DTPP_smallExample)

# Import data:
datIn <- tpp2dImport(configTable = panobinostat_2DTPP_config,
                      data = panobinostat_2DTPP_data,
                      idVar = "representative",
                      addCol = "clustername",
                      intensityStr = "sumionarea_protein_",
                      nonZeroCols = "qusm")

# View attributes of imported data (experiment infos and import arguments):
attr(datIn, "importSettings") %>% unlist
attr(datIn, "configTable")

# Compute fold changes:
datFC <- tpp2dComputeFoldChanges(data = datIn)

# View updated attributes. Now contain field 'fcStrNorm' indicating prefix
# of the fold change columns after normalization.
attr(datFC, "importSettings")["fcStr"]
```

tpp2dCreateDRplots *Create dose response curve plots for 2D-TPP data*

Description

Generates a list of dose response curve plots per protein and temperature point.

Usage

```
tpp2dCreateDRplots(
  data = NULL,
  type = "all",
  verbose = FALSE,
  paletteName = "Spectral"
)
```

Arguments

<code>data</code>	the data that should be plotted.
<code>type</code>	string defining which curves to display (see details).
<code>verbose</code>	boolean variable stating whether a print description of problems/success for plotting of each protein should be printed.
<code>paletteName</code>	color palette (see details).

Details

`data` is a data frame in wide table format returned by function [tpp2dCurveFit](#). Its attributes contain information about the experiment names, temperatures, isobaric labels, as well as instructions on how to find the relevant columns in the wide table.

`type` defines which curves to display per plot. Possible values are:

- "all": Create one plot per protein. This plot simultaneously displays the curves for all available temperatures for this protein (the default).
- "good": Create one plot per protein. This plot displays all dose response curves with a high goodness-of-fit. Choose this option to save runtime by focusing only on the reliable fits.
- "single": Create one separate plot per protein and temperature. This plot displays all dose response curves with a high goodness-of-fit.

`paletteName` specifies the color palette to be used by the [brewer.pal](#) function from the RColorBrewer package to assign a separate color to each concentration.

Value

A list of successfully generated plot objects of class 'ggplot'

See Also

[tpp2dCurveFit](#) [brewer.pal](#)

Examples

```
data(panobinostat_2DTPP_smallExample)

# Import data:
datIn <- tpp2dImport(configTable = panobinostat_2DTPP_config,
                      data = panobinostat_2DTPP_data,
                      idVar = "representative",
                      addCol = "clustername",
                      intensityStr = "sumionarea_protein_",
                      nonZeroCols = "qusm")

# Compute fold changes:
fcData2d <- tpp2dComputeFoldChanges(data = datIn)
normData2d <- tpp2dNormalize(data = fcData2d)
ccr2dResults <- tpp2dCurveFit(data = normData2d)
allCurves <- tpp2dCreateDRplots(data = ccr2dResults, type = "all")
allCurves[["HDAC1"]]
```

Description

Creates a markdown pdf file that summarizes the 2D-TPP analysis by reporting e.g. R version and package versions used

Usage

```
tpp2dCreateReport(
  data = NULL,
  configFile = NULL,
  resultPath = NULL,
  documentType = "html_document",
  configTable = NULL,
  normalize = TRUE,
  methods = c(),
  idVar = "gene_name",
  fcStr = "rel_fc_",
  fcStrUpdated = "norm_rel_fc_",
  intensityStr = "signal_sum_",
  addCol = NULL,
  fcTolerance = NA,
  r2Cutoff = NA,
  fcCutoff = NA,
  slopeBounds = c(NA, NA),
  fTest = FALSE,
  trRef = "none"
)
```

Arguments

data	output data frame from an 2D-TPP analysis
configFile	character string containing a valid system path to a file which summarizes the experimental details of the 2D-TPP experiment or respective data frame
resultPath	character string containing a system path to where the report should be written
documentType	character string indicating which document type the report should have default: "html_document", alternatives: "pdf_document"
configTable	data frame summarizing the experimental details of the 2D-TPP experiment
normalize	boolean flag indicating whether median normalization has been performed
methods	vector of characters which indicate which methods have been used
idVar	unique protein identifier prefix
fcStr	fold change identifier prefix
fcStrUpdated	character string matching the fold change columns after normalization has been performed
intensityStr	intensity values prefix
addCol	vector of strings indicating which additional data columns were imported
fcTolerance	tolerance for the fcCutoff parameter
r2Cutoff	Quality criterion on dose response curve fit.
fcCutoff	Cutoff for highest compound concentration fold change
slopeBounds	Bounds on the slope parameter for dose response curve fitting
fTest	boolean variable stating whether an fTest was performed
trRef	character string containing a valid system path to a previously generated TPP-TR reference object

Value

A pdf or html report which summarizes all parameters that were set

tpp2dCreateTPPTRreference

Create TPP-TR reference for 2D-TPP experiment

Description

Performs a reference analysis of a TPP-TR experiment and generates boxplots for the distribution of fold changes at the different temperatures if desired.

Usage

```
tpp2dCreateTPPTRreference(
  trConfigTable = NULL,
  trDat = NULL,
  resultPath = NULL,
  outputName = NULL,
  createFCboxplots = FALSE,
  idVar = "gene_name",
  fcStr = "rel_fc_",
  qualColName = "qupm",
  normalize = TRUE
)
```

Arguments

trConfigTable	config file for a reference TR dataset
trDat	list of dataframes, containing fold change measurements and additional annotation columns to be imported. Can be used instead of specifying the file path in the configTable argument.
resultPath	character string containing a valid system path to which folder output files will be written
outputName	character string which will be used as name of the output folder
createFCboxplots	boolean flag indicating whether quality control boxplots are to be plotted
idVar	character string indicating which column of the data table contains the unique protein ids
fcStr	character string indicating which columns contain fold changes
qualColName	character string indicating which column contain protein identification quality measures
normalize	boolean argument stating whether the data should be normalized or not

Value

A TPP-TR reference object for a certain cell line with different supporting files in a desired output directory. The main object which is of interest for further analysis is the `trRefData.RData` file. This is the file to which a referencing system path has to be indicated when a function as `tpp2dSplineFitAndTest` require to input a TPP-TR reference object. The `RData` file consists of list carrying four different items:

1. `tppCfgTable`: the TPP-TR configtable which was used for generating this object
2. `sumResTable` a list of two elements 1. `detail`: the exact result data from the TR analysis and 2. `summary`: a summary of the analyzed TR data comprising the median and standard deviation values of the measurements at the different temperatures (encoded by the isobaric labels)
3. `temperatures` a table listing the temperatures which were used in the TR experiment in the different replicates
4. `lblsByTemp` a table matching each temperature to an isobaric label

tpp2dCurveFit

*Run TPP-CCR analysis for 2D-TPP experiment***Description**

Performs analysis of a TPP-CCR experiment by invoking the routine for TPP-CCR curve fitting for each temperature of the sample.

Usage

```
tpp2dCurveFit(
  configFile = NULL,
  data,
  nCores = 1,
  naStrs = NULL,
  fcStr = NULL,
  idVar = NULL,
  nonZeroCols = NULL,
  r2Cutoff = 0.8,
  fcCutoff = 1.5,
  slopeBounds = c(1, 50),
  fcTolerance = 0.1
)
```

Arguments

<code>configFile</code>	DEPRECATED
<code>data</code>	data frame that contains the data of the 2D-TPP experiment for each temperature.
<code>nCores</code>	numeric value stating how many cores are to be used for computation
<code>naStrs</code>	DEPRECATED
<code>fcStr</code>	DEPRECATED
<code>idVar</code>	DEPRECATED

nonZeroCols	DEPRECATED
r2Cutoff	Quality criterion on dose response curve fit.
fcCutoff	Cutoff for highest compound concentration fold change.
slopeBounds	Bounds on the slope parameter for dose response curve fitting.
fcTolerance	tolerance for the fcCutoff parameter. See details.

Value

A data frames in which the fit results are stored row-wise for each protein.

Examples

```
# Preparation:
data(panobinostat_2DTPP_smallExample)

# Import data:
datIn <- tpp2dImport(configTable = panobinostat_2DTPP_config,
                      data = panobinostat_2DTPP_data,
                      idVar = "representative",
                      addCol = "clustername",
                      intensityStr = "sumionarea_protein_",
                      nonZeroCols = "qusm")

# Compute fold changes:
datFC <- tpp2dComputeFoldChanges(data = datIn)

# Perform median normalization:
datNorm <- tpp2dNormalize(data = datFC)

# View updated attributes. Now contain field 'fcStrNorm' indicating prefix
# of the fold change columns after normalization.
attr(datNorm, "importSettings")["fcStrNorm"]

# Perform dose response curve fitting and pEC50 calculation:
datFit <- tpp2dCurveFit(data = datNorm)
```

tpp2dExport

Produce Excel table of 2D-TPP experiment.

Description

Produce Excel table of 2D-TPP experiment analysis results.

Usage

```
tpp2dExport(
  configTable = NULL,
  tab,
  resultPath = NULL,
  idVar = NULL,
  fcStr = NULL,
```

```

intensityStr = NULL,
outPath,
addCol = NULL,
normalizedData = NULL,
trRef = NULL,
addPlotColumns = TRUE
)

```

Arguments

configTable	DEPRECATED
tab	Table with results of the 2D-TPP analysis.
resultPath	DEPRECATED
idVar	DEPRECATED
fcStr	DEPRECATED
intensityStr	DEPRECATED
outPath	path for storing results table
addCol	additional names of columns which are to be attached to the result table
normalizedData	DEPRECATED
trRef	character string containing a valid system path to a TPP-TR reference RData file
addPlotColumns	boolean variable indicating whether paths to plot files should be generated and checked for validity. De-activate if no dose-response curve plots were produced during the analysis.

Value

Creates excel file of the TPP-CCR analysis of the 2D-TPP data.

Examples

```

data(panobinostat_2DTPP_smallExample)
load(system.file("example_data/2D_example_data/shortData2d.RData", package="TPP"))
# tpp2dExport(configTable = panobinostat_2DTPP_config, tab=shortData2d,
#             outPath=getwd(),
#             idVar="representative", fcStr="norm_rel_fc_protein_",
#             intensityStr="sumionarea_protein_", addCol=NULL)

data(panobinostat_2DTPP_smallExample)
# cfgRaw <- panobinostat_2DTPP_config
# datRaw <- panobinostat_2DTPP_data
# datIn <- tpp2dImport(cfgIn, datRaw, fcStr = NULL)
# datFC <- tpp2dComputeFoldChanges(data = datIn)
# datNorm <- tpp2dNormalize(data = datFC)
# cfgCCR <- convert_2D_cfgTable_to_CCR_cfgTable(cfgIn)
# datFitted <- tpp2dCurveFit(datNorm, nCores = 2)
# tpp2dCreateReport(getwd(), cfgIn, resultTable = datFitted, idVar = "representative",
#                   intensityStr = "sumionarea_protein_")
# tpp2dExport(tab = datFitted, outPath = getwd(), addPlotColumns = FALSE)

```

tpp2dExportPlots	<i>Export plots for 2D-TPP experiment.</i>
------------------	--

Description

Exports plots into plots/ directory in the resultPath

Usage

```
tpp2dExportPlots(plotList, resultPath, type = "none")
```

Arguments

plotList	list of ggplots returned from one of the plotting functions
resultPath	path for storing results
type	character string specifying which type of plot is to be exported

Details

Creates pdf files of the afore created plots by plot_2D_data_on_temperature_range or tpp2dCreateDRplots

Value

None

tpp2dImport	<i>Import 2D-TPP data</i>
-------------	---------------------------

Description

Imports data from 2D-TPP experiments by parsing a configTable and reading in corresponding data file or data frames containing raw data (sumionarea values) and creating a big data frame comprising all samples with respective fold changes

Usage

```
tpp2dImport(
  configTable = NULL,
  data = NULL,
  idVar = "gene_name",
  addCol = NULL,
  intensityStr = "signal_sum_",
  qualColName = "qupm",
  nonZeroCols = "qssm",
  fcStr = NULL
)
```

Arguments

configTable	dataframe, or character object with the path to a file, that specifies important details of the 2D-TPP experiment. See Section details for instructions how to create this object.
data	single dataframe, containing raw measurements and if already available fold changes and additional annotation columns to be imported. Can be used instead of specifying the file path in the configTable argument.
idVar	character string indicating which data column provides the unique identifiers for each protein.
addCol	additional column names that specify columns in the input data that are to be attached to the data frame throughout the analysis
intensityStr	character string indicating which columns contain the actual sumionarea values. Those column names containing the suffix intensityStr will be regarded as containing sumionarea values.
qualColName	character string indicating which column can be used for additional quality criteria when deciding between different non-unique protein identifiers.
nonZeroCols	character string indicating a column that will be used for filtering out zero values.
fcStr	character string indicating which columns contain the actual fold change values. Those column names containing the suffix fcStr will be regarded as containing fold change values.

Value

A dataframe comprising all experimental data

Examples

```
# Preparation:
data(panobinostat_2DTPP_smallExample)

# Import data:
datIn <- tpp2dImport(configTable = panobinostat_2DTPP_config,
                      data = panobinostat_2DTPP_data,
                      idVar = "representative",
                      addCol = "clustername",
                      intensityStr = "sumionarea_protein_",
                      nonZeroCols = "qusm")

# View attributes of imported data (experiment infos and import arguments):
attr(datIn, "importSettings") %>% unlist
attr(datIn, "configTable")
```

Description

Merges 2D-TPP result data with TPP-TR reference data to generate a big table including both results

Usage

```
tpp2dMerge2dRef(
  resultTable_2D,
  referenceDataSummary,
  refIDVar = "Protein_ID",
  idVar = NULL,
  data = NULL,
  trRef = NULL
)
```

Arguments

resultTable_2D	dataframe containing the 2D-TPP results
referenceDataSummary	summarized reference data results. See details.
refIDVar	character string indicating name of the columns containing the unique protein identifiers in the reference data set
idVar	DEPRECATED
data	DEPRECATED
trRef	DEPRECATED

Details

referenceSummary contains summary statistics like median fold changes and is produced by the function [tpp2dCreateTPPTRreference](#). It summarizes the results of a TPP-TR analysis of a reference data set. A reference data set is the a output of a TR experiment without drug treatment on the same cell line as resultTable_2D.

Value

A data frame with results merged from 2D-TPP and TPP-TR reference

See Also

[tpp2dCreateTPPTRreference](#)

Examples

```
data(panobinostat_2DTPP_smallExample)
config_tpp2d <- panobinostat_2DTPP_config
data_tpp2d <- panobinostat_2DTPP_data
tpp2dResults <- analyze2DTPP(configTable = config_tpp2d,
  data = data_tpp2d,
  methods=c("doseResponse"),
  createReport="none",
  nCores=1,
  idVar = "representative",
  addCol = "clustername",
  intensityStr = "sumionarea_protein_",
  nonZeroCols = "qusm")

trRef <- file.path(system.file("data", package="TPP"),
"TPPTR_reference_results_HepG2.RData")
```

```
annotatedTable <- tpp2dMerge2dRef(resultTable_2D = tpp2dResults,  
                                    referenceDataSummary = trRef)
```

tpp2dNormalize

Median normalization of protein fold changes of 2D-TPP data

Description

Normalizes fold changes retrieved from 2D-TPP experiment by dividing by the median fold change

Usage

```
tpp2dNormalize(configTable = NULL, data, fcStr = NULL)
```

Arguments

configTable	DEPRECATED
data	data frame that contains the data for the 2D-TPP experiment
fcStr	DEPRECATED

Value

A data frame identical to the input data frame except that the columns containing the fold change values have been normalized by their median.

Examples

```
# Preparation:  
data(panobinostat_2DTPP_smallExample)  
  
# Import data:  
datIn <- tpp2dImport(configTable = panobinostat_2DTPP_config,  
                      data = panobinostat_2DTPP_data,  
                      idVar = "representative",  
                      addCol = "clustername",  
                      intensityStr = "sumionarea_protein_",  
                      nonZeroCols = "qusm")  
  
# Compute fold changes:  
datFC <- tpp2dComputeFoldChanges(data = datIn)  
  
# Perform median normalization:  
datNorm <- tpp2dNormalize(data = datFC)  
  
# View updated attributes. Now contain field 'fcStrNorm' indicating prefix  
# of the fold change columns after normalization.  
attr(datNorm, "importSettings")["fcStrNorm"]
```

tpp2dPlotQChist	<i>Plot quality control histograms</i>
-----------------	--

Description

Plots quality control histograms of pEC50 values of reference dataset and indicates the pEC50 values of the 2D-TPP experiment

Usage

```
tpp2dPlotQChist(
  configFile = NULL,
  resultTable = NULL,
  resultPath = NULL,
  trRef = NULL,
  fcStr = "rel_fc_",
  idVar = "gene_name",
  qualColName = "qupm"
)
```

Arguments

configFile	data frame or system path to table that specifies important details of the 2D-TPP experiment
resultTable	data.frame containing the results of a CCR analysis of 2D-TPP data
resultPath	character string containing a valid system path to which the qc plots will be written
trRef	character string with a link to a TPP-TR reference object RData file
fcStr	character string indicating how columns that will contain the actual fold change values are called.
idVar	character string indicating name of the columns containing the unique protein identifiers
qualColName	character string indicating which column contain protein identification quality measures

Value

A pdf with various quality control plots for a specified 2D-TPP data set

tpp2dPlotQCpEC50	<i>Plot quality control pEC50 plots</i>
------------------	---

Description

Plots quality control plots which indicate at which temperatures the pEC50 values of the treatment curves lie in comparison to those of the reference data

Usage

```
tpp2dPlotQCpEC50(
  resultTable = NULL,
  resultPath = NULL,
  trRef = NULL,
  idVar = "gene_name"
)
```

Arguments

resultTable	data.frame containing the results of a CCR analysis of 2D-TPP data
resultPath	character string containing a valid system path to which the qc plots will be written
trRef	character string with a link to a TPP-TR reference object RData file
idVar	character string indicating how the column that contains the unique protein identifiers is called

Value

A folder with plots for each identified protein that compare melting points in the reference data set with the 2D-TPP data set

tpp2dSplineFitAndTest *Fit splines and perform f-Test*

Description

Fit splines through TR reference dataset and extrapolates relative 2D-TPP datapoints, then compares spline fits of different treatments with non-treatment with an f-test

Usage

```
tpp2dSplineFitAndTest(
  data_2D = NULL,
  data,
  trRefDataPath = NULL,
  dataRef,
  refIDVar = "Protein_ID",
  refFcStr = "norm_rel_fc_",
  resultPath = NULL,
  doPlot = TRUE,
  verbose = FALSE,
  nCores = "max",
  ggplotTheme = NULL
)
```

Arguments

data_2D	DEPRECATED
data	result data.frame from a 2D-TPP CCR analysis
trRefDataPath	DEPRECATED
dataRef	reference data from a TPP TR analysis on the same cell line as
refIDVar	character string indicating name of the columns containing the unique protein identifiers in the reference data set
refFcStr	character string indicating which columns contain the actual fold change values in the reference data. The suffix fcStr will be pasted in front of the names of the experiments.
resultPath	location where to store dose-response curve plots and results table.
doPlot	boolean value indicating whether protein-wise plots should be produced Deactivating plotting decreases runtime.
verbose	print description of problems for each protein for which splines fits could not be performed
nCores	either a numerical value given the desired number of CPUs, or 'max' to automatically assign the maximum possible number (default).
ggplotTheme	DEPRECATED

Details

dataRef can either be a tidy data frame of TPP-TR reference data, a list with TPP-TR reference data and additional information produced by [tpp2dCreateTPPTRreference](#), or a character string with a link to the data in one of the described formats.

Value

None

Examples

```
data(panobinostat_2DTPP_smallExample)
config_tpp2d <- panobinostat_2DTPP_config
data_tpp2d <- panobinostat_2DTPP_data
trRef <- file.path(system.file("data", package="TPP"),
  "TPPTR_reference_results_HepG2.RData")
datIn <- tpp2dImport(configTable = config_tpp2d,
  data = data_tpp2d,
  idVar = "representative",
  addCol = "clustername",
  intensityStr = "sumionarea_protein_",
  nonZeroCols = "qusm")
fcData2d <- tpp2dComputeFoldChanges(data = datIn)
normData2d <- tpp2dNormalize(data = fcData2d)
analysisResults <- tpp2dSplineFitAndTest(data = normData2d,
  dataRef = trRef,
  refIDVar = "Protein_ID",
  refFcStr = "norm_rel_fc_protein_",
  doPlot = FALSE,
  nCores = 1)
```

tpp2dSplinePlot	<i>Fit splines and generate ggplot visualizations</i>
-----------------	---

Description

Fit splines through TR reference dataset and extrapolates relative 2D-TPP datapoints, then compares spline fits of different treatments with non-treatment with an f-test

Usage

```
tpp2dSplinePlot(
  data_2D = NULL,
  trRef = NULL,
  fcStr = NULL,
  idVar = NULL,
  refIdVar = "Protein_ID",
  methods = c("doseResponse", "splineFit"),
  refFcStr = "norm_rel_fc_protein_",
  verbose = FALSE
)
```

Arguments

data_2D	result data.frame from a 2D-TPP CCR analysis
trRef	character string of a valid system path to a TPP-TR reference RData object
fcStr	character string indicating how columns that will contain the actual fold change values will be called. The suffix fcStr will be pasted in front of the names of the experiments.
idVar	character string indicating name of the columns containing the unique protein identifiers in the 2D data set
refIdVar	character string indicating name of the columns containing the unique protein identifiers in the reference data set
methods	vector of character strings that indicate which methods has been used for the previous analysis (default: c("doseResponse"), alternative: c("splineFit") or c("doseResponse", "splineFit"))
refFcStr	character string indicating how columns that will contain the fold change values in the reference data set
verbose	print description of problems for each protein for which splines fits could not be performed

Value

A list of ggplots which can be accessed via the unique protein ids in the idVar column

Examples

```
load(system.file("example_data/2D_example_data/shortData2d.RData", package="TPP"))
trRef <- system.file("example_data/2D_example_data/referenceNormData.RData", package="TPP")
```

tpp2dTRReferenceObject
TPP-TR reference object

Description

Definition of a TPP-TR reference object

Usage

```
tpp2dTRReferenceObject(  

  tppRefData = NULL,  

  tppRefPath = NULL,  

  fcStr = "norm_rel_fc_",  

  qualColName = "qupm"  

)
```

Arguments

tppRefData	TPP-TR reference object that can be directly passed to the function
tppRefPath	character string containing a system path to a RData file containing an TPP-TR reference object
fcStr	character string indicating which columns contain the fold changes
qualColName	character string indicating which column contain protein identification quality measures

Value

A TPP-TR reference object

Examples

```
trRef <- system.file("example_data/2D_example_data/referenceNormData.RData", package="TPP")  

tpp2dTRReferenceObject(tppRefPath=trRef)
```

tppccrCurveFit *Fit dose response curves*

Description

tppccrCurveFit fits logistic dose response curves to fold change measurements of a TPP-CCR experiment.

Usage

```
tppccrCurveFit(
  data = NULL,
  fcTable = NULL,
  cpdEffects = NULL,
  slopeBounds = c(1, 50),
  nCores = "max",
  verbose = FALSE
)
```

Arguments

data	list of expressionSet objects containing protein fold changes for dose response curve fitting.
fcTable	optional long table with fold changes for each experiment. Can be provided instead of the input argument data.
cpdEffects	optional long table of compound effects per protein and experiment. Can be provided instead of the input argument data.
slopeBounds	bounds on the slope parameter for dose response curve fitting.
nCores	either a numerical value given the desired number of CPUs, or 'max' to automatically assign the maximum possible number (default).
verbose	print name of each fitted protein to the command line as a means of progress report.

Details

data is a list of expressionSet objects created by [tppccrImport](#). If desired, it can be already preprocessed by [tppccrNormalize](#) or [tppccrTransform](#). It contains the isobaric labels and administered drug concentrations in the phenoData and user-defined protein properties in the featureData. Protein IDs are stored in the featureNames.

Measurements and compound effects for curve fitting can be provided by the arguments fcTable and cpdEffects, instead of being stored in expressionSets in data.

If specified, fcTable needs to be a long table with column names "id" (the protein names), "concentration" (the fold changes), "labelName" (the isobaric label to each measurement), and "experiment" (e.g. "Vehicle_1" or "Panobinostat_1").

If specified, cpdEffects needs to be a long table with column names "id" (the protein names), "cpdEff" (character vector of compound effects, may contain NAs), and "experiment" (e.g. "Vehicle_1" or "Panobinostat_1").

Value

A list of expressionSet objects storing fold changes, the fitted curve parameters, as well as row and column metadata. In each expressionSet S, the fold changes can be accessed by `Biobase::exprs(S)`. Protein expNames can be accessed by `featureNames(S)`. Isobaric labels and the corresponding concentrations are returned by `S$label` and `S$concentration`. The fitted curve parameters are stored in `codefeatureData(S)`.

See Also

[tppccrImport](#), [tppccrNormalize](#), [tppccrTransform](#)

Examples

```
data(hdacCCR_smallExample)
tppccrData <- tppccrImport(configTable=hdacCCR_config,
                             data=hdacCCR_data)
tppccrNorm <- tppccrNormalize(data=tppccrData)
tppccrTransformed <- tppccrTransform(data=tppccrNorm)
tppccrFitted <- tppccrCurveFit(data=tppccrTransformed, nCores=1)
```

tppccrImport

Import TPP-CCR dataset for analysis by the [TPP](#) package.

Description

`tppccrImport` imports a table of protein fold changes and stores them in an ExpressionSet for use in the [TPP](#) package.

Usage

```
tppccrImport(
  configTable,
  data = NULL,
  idVar = "gene_name",
  fcStr = "rel_fc_",
  naStrs = c("NA", "n/d", "NaN", "<NA>"),
  qualColName = "qupm",
  nonZeroCols = "qssm"
)
```

Arguments

<code>configTable</code>	either a datafram or the path to a spreadsheet. In both cases it specifies necessary information of the TPP-CCR experiment.
<code>data</code>	dataframe containing fold change measurements and additional annotation columns to be imported. Can be used instead of specifying the file path in <code>configTable</code> .
<code>idVar</code>	character string indicating which data column provides the unique identifiers for each protein.
<code>fcStr</code>	character string indicating which columns contain the actual fold change values. Those column names containing the suffix <code>fcStr</code> will be regarded as containing fold change values.
<code>naStrs</code>	character vector indicating missing values in the data table. When reading data from file, this value will be passed on to the argument <code>na.strings</code> in function <code>read.delim</code> .
<code>qualColName</code>	character string indicating which column can be used for additional quality criteria when deciding between different non-unique protein identifiers.
<code>nonZeroCols</code>	character string indicating a column that will be used for filtering out zero values.

Details

The imported dataset has to contain measurements obtained by a TPP-CCR experiment. Fold changes need to be pre-computed using the lowest concentration as reference.

The dataset can be specified by filename in the configTable argument, or given directly in the data argument

The default settings are adjusted to analyze data of the python package `isobarQuant`. You can also customize them for your own dataset.

The configTable argument is a dataframe, or the path to a spreadsheet (tab-delimited text-file without quoted strings, or xlsx format). Information about each experiment is stored row-wise. It contains the following columns:

- Path: location of the datafile. Alternatively, data can be directly handed over by the data argument.
- Experiment: unique experiment name.
- Label columns: each isobaric label names a column that contains the concentration administered for the label in the individual experiments.

During data import, proteins with NAs in the data column specified by `idVar` receive unique generic IDs so that they can be processed by the package.

Value

ExpressionSet object storing the measured fold changes, as well as row and column metadata. In each ExpressionSet `S`, the fold changes can be accessed by `Biobase::exprs(S)`. Protein `expNames` can be accessed by `featureNames(S)`. Isobaric labels and the corresponding concentrations are returned by `S$label` and `S$concentration`.

See Also

[tpptrImport](#), [tppccrCurveFit](#)

Examples

```
data(hdacCCR_smallExample)
tppccrData <- tppccrImport(configTable=hdacCCR_config,
data = hdacCCR_data)
```

tppccrNormalize *Normalize data from TPP-CCR experiments*

Description

Normalize each fold change column by its median.

Usage

```
tppccrNormalize(data)
```

Arguments

data	list of expressionSets with measurements to be normalized
------	---

Value

List of expressionSet objects storing the normalized fold changes, as well as row and column metadata. In each expressionSet S, the fold changes can be accessed by `Biobase::exprs(S)`. Protein names can be accessed by `featureNames(S)`. Isobaric labels and the corresponding concentrations are returned by `S$label` and `S$concentration`.

Examples

```
data(hdacCCR_smallExample)
tppccrData <- tppccrImport(configTable=hdacCCR_config, data = hdacCCR_data)
tppccrNorm <- tppccrNormalize(data=tppccrData)
head(Biobase::exprs(tppccrNorm[[1]]))
```

tppccrNormalizeToReference

Normalize fold changes of TPP-CCR experiment to a reference column

Description

Normalize fold changes of TPP-CCR experiment to a reference column (usually that with the lowest concentration) to ensure that the transformation by [tppccrTransform](#) yields values between 0 and 1.

Usage

```
tppccrNormalizeToReference(data, refCol = NULL)
```

Arguments

data	expressionSet object containing the data to be normalized
refCol	column number to use as a reference. Will contain only 1s after the normalization.

Value

List of expressionSet objects storing the normalized fold changes, as well as row and column metadata. In each expressionSet S, the fold changes can be accessed by `Biobase::exprs(S)`. Protein expNames can be accessed by `featureNames(S)`. Isobaric labels and the corresponding concentrations are returned by `S$label` and `S$concentration`.

Examples

```
data(hdacCCR_smallExample)
tppccrData <- tppccrImport(configTable=hdacCCR_config, data = hdacCCR_data)
tppccrNorm <- tppccrNormalize(data=tppccrData)
# Normalize to lowest concentration (in the first column):
tppccrNormToRef <- tppccrNormalizeToReference(data=tppccrNorm, refCol=1)
# Obtain results per replicate:
```

```

refTransf_replicate1 <- tppccrNormToRef$Panobinostat_1
head(Biobase::exprs(refTransf_replicate1))
# Perform transformation:
tppccrTransformed <- tppccrTransform(data=tppccrNormToRef)
# Obtain transformed measurements per replicate:
transf_replicate1 <- tppccrTransformed$Panobinostat_1
transf_replicate2 <- tppccrTransformed$Panobinostat_2
# Inspect transformed data in replicate 1:
effects_replicate1 <- Biobase::featureData(transf_replicate1)$compound_effect
newData_repl1 <- data.frame(Biobase::exprs(transf_replicate1),
                             Type=effects_replicate1)[!is.na(effects_replicate1),]

```

tppccrPlotCurves	<i>Plot dose response curves</i>
------------------	----------------------------------

Description

tppccrPlotCurves plots the logistic dose response curves, as well as the underlying fold change measurements for each TPP-CCR experiment in a study.

Usage

```

tppccrPlotCurves(
  data = NULL,
  fcTable = NULL,
  curvePars = NULL,
  resultPath = NULL,
  ggplotTheme = tppDefaultTheme(),
  nCores = "max",
  verbose = FALSE
)

```

Arguments

<code>data</code>	list of expressionSet objects containing protein fold changes, as well as fitted curve parameters.
<code>fcTable</code>	optional long table with fold changes for each experiment. Can be provided instead of the input argument <code>data</code> .
<code>curvePars</code>	optional long table of curve parameters per protein and experiment. Can be provided instead of the input argument <code>data</code> .
<code>resultPath</code>	location where to store dose-response curve plots.
<code>ggplotTheme</code>	ggplot theme for dose response curve plots.
<code>nCores</code>	either a numerical value given the desired number of CPUs, or 'max' to automatically assign the maximum possible number (default).
<code>verbose</code>	print name of each plotted protein to the command line as a means of progress report.

Details

`data` is a list of expressionSet objects created by [tppccrCurveFit](#). It contains the isobaric labels and administered drug concentrations in the `phenoData` and user-defined protein properties (including dose response curve parameters) in the `featureData`. Protein IDs are stored in the `featureNames`.

Measurements and compound effects for curve fitting can be provided by the arguments `fcTable` and `cpdEffects`, instead of being stored in expressionSets in `data`.

If specified, `fcTable` needs to be a long table with column names "id" (the protein names), "concentration" (the fold changes), "labelName" (the isobaric label to each measurement), and "experiment" (e.g. "Vehicle_1" or "Panobinostat_1").

If specified, `curvePars` needs to be a long table with column names "id" (the protein names), "param" (curve parameter per protein and experiment, see `TPP:::drCurveParamNames(names=TRUE, info=FALSE)` for possibilities), and "experiment" (e.g. "Vehicle_1" or "Panobinostat_1").

The dose response curve plots will be stored in a subfolder with name `DoseResponse_Curves` at the location specified by `resultPath`.

Value

A list of expressionSet objects storing fold changes, as well as row and column metadata. In each expressionSet `S`, the fold changes can be accessed by `Biobase:::exprs(S)`. Protein `expNames` can be accessed by `featureNames(S)`. Isobaric labels and the corresponding concentrations are returned by `S$label` and `S$concentration`. Paths to the produced plots are stored in `codefeatureData(S)$plot`.

See Also

[tppccrCurveFit](#), [tppDefaultTheme](#)

Examples

```
data(hdacCCR_smallExample)
tppccrData <- tppccrImport(configTable=hdacCCR_config,
                           data=hdacCCR_data)
tppccrNorm <- tppccrNormalize(data=tppccrData)
tppccrTransformed <- tppccrTransform(data=tppccrNorm)
tppccrFitted <- tppccrCurveFit(data=tppccrTransformed, nCores=1)
hdacSubset <- sapply(tppccrFitted, function(d)d[grepl("HDAC", rownames(d)),])
tppccrPlotted <- tppccrPlotCurves(hdacSubset, resultPath=getwd(), nCores = 1)
```

tppccrResultTable *Summarize results of a TPP-CCR study*

Description

`tppccrResultTable` summarizes the outcomes of a TPP-CCR study in a results table and includes quality information about the estimated dose response curves.

Usage

```
tppccrResultTable(data, r2Cutoff = 0.8)
```

Arguments

data	list of expressionSet objects containing protein fold changes, as well as fitted curve parameters.
r2Cutoff	quality criterion on dose response curve fit. @details data is a list of expressionSet objects created by tppccrCurveFit or tppccrPlotCurves . It contains the isobaric labels and administered drug concentrations in the phenoData and user-defined protein properties (including dose response curve parameters) in the featureData. Protein IDs are stored in the featureNames. If data is the output of tppccrPlotCurves , plot locations are given in the plot column of the featureData.

Value

A data frame in which the results are stored row-wise for each protein, together with the original annotation from the input files.

See Also

[tppccrCurveFit](#), [tppccrPlotCurves](#)

Examples

```
data(hdacCCR_smallExample)
tppccrData <- tppccrImport(configTable=hdacCCR_config,
                             data=hdacCCR_data)
tppccrNorm <- tppccrNormalize(data=tppccrData)
tppccrTransformed <- tppccrTransform(data=tppccrNorm)
tppccrFitted <- tppccrCurveFit(data=tppccrTransformed, nCores=1)
tppccrResults <- tppccrResultTable(data=tppccrFitted)
subset(tppccrResults, passed_filter_Panobinostat_1 & passed_filter_Panobinostat_2)
```

tppccrTransform

Transform fold changes of TPP-CCR experiment

Description

Transform fold changes of TPP-CCR experiment to prepare them for dose response curve fitting.

Usage

```
tppccrTransform(data, fcCutoff = 1.5, fcTolerance = 0.1)
```

Arguments

data	expressionSet object containing the data to be transformed.
fcCutoff	cutoff for highest compound concentration fold change.
fcTolerance	tolerance for the fcCutoff parameter. See details.

Details

Only proteins with fold changes bigger than $[fcCutoff * (1 - fcTolerance)$ or smaller than $1/(fcCutoff * (1 - fcTolerance))$] will be used for curve fitting. Additionally, the proteins fulfilling the fc-Cutoff criterion without tolerance will be marked in the output column `meets_FC_requirement`.

Value

List of expressionSet objects storing the transformed fold changes, as well as row and column metadata. In each expressionSet `S`, the fold changes can be accessed by `Biobase::exprs(S)`. Protein expNames can be accessed by `featureNames(S)`. Isobaric labels and the corresponding concentrations are returned by `S$label` and `S$concentration`.

Examples

```
data(hdacCCR_smallExample)
tppccrData <- tppccrImport(configTable=hdacCCR_config, data = hdacCCR_data)
tppccrNorm <- tppccrNormalize(data=tppccrData)
# Perform transformation:
tppccrTransformed <- tppccrTransform(data=tppccrNorm)
# Obtain transformed measurements per replicate:
transf_replicate1 <- tppccrTransformed$Panobinostat_1
transf_replicate2 <- tppccrTransformed$Panobinostat_2
# Inspect transformed data in replicate 1:
effects_replicate1 <- Biobase::featureData(transf_replicate1)$compound_effect
newData_repl1 <- data.frame(Biobase::exprs(transf_replicate1),
                             Type=effects_replicate1)[!is.na(effects_replicate1),]
```

tppDefaultTheme

Default ggplot theme for melting curve plots.

Description

Default theme to be passed to the gplots produced by the TPP package.

Usage

```
tppDefaultTheme()
```

Details

Internally, the theme is used as an argument for the function `ggplot2::theme_set` in order specify the appearance of the melting curve plots.

The specified plot properties include bold font and increased font size for axis labels and title, as well as a 90 degree angle for y axis labels.

Value

ggplot theme with default settings for melting plot appearance.

Examples

```
# Import data:  
data(hdacTR_smallExample)  
tpptrData <- tpptrImport(configTable=hdacTR_config, data=hdacTR_data)  
# Obtain template with default settings:  
normRequirements <- tpptrDefaultNormReqs()  
print(normRequirements)  
# Relax filter on the 10th fold change column for  
# normalization set production:  
normRequirements$fcRequirements[3,3] <- 0.25  
# Perform normalization:  
tpptrNorm <- tpptrNormalize(data=tpptrData, normReqs=)
```

tppExport

Produce Excel table of TPP-TR or TPP-CCR experiment.

Description

Produce Excel table of TPP-TR or TPP-CCR experiment out of the data frame returned by [tpptrAnalyzeMeltingCurves](#)

Usage

```
tppExport(tab, file, expNames = NULL, expColors = NULL)
```

Arguments

tab	Table with results of the TPP analysis.
file	path for storing results table
expNames	character vector of experiment names of the same length as expColors.
expColors	character vector of background colors to group the result columns belonging to different experiments.

Value

No value returned.

Examples

```
data(hdacTR_resultsTable_smallExample)  
tppExport(resultTable, "tpptr_example_results.xlsx")
```

tppQCPlotsCorrelateExperiments

Visually compare fold changes of different TPP experiments.

Description

Plot pairwise relationships between the proteins in different TPP experiments.

Usage

```
tppQCPlotsCorrelateExperiments(
  tppData,
  annotStr = "",
  path = NULL,
  ggplotTheme = tppDefaultTheme()
)
```

Arguments

tppData	List of expressionSets with data to be plotted.
annotStr	String with additional information to be added to the plot.
path	Location where to store resulting plot.
ggplotTheme	ggplot theme for the created plots.

Value

List of plots for each experiment.

See Also

[tppDefaultTheme](#)

Examples

```
data(hdacTR_smallExample)
tpptrData <- tpptrImport(configTable=hdacTR_config, data=hdacTR_data)
# Quality control (QC) plots BEFORE normalization:
tppQCPlotsCorrelateExperiments(tppData=tpptrData,
  annotStr="Non-normalized Fold Changes")
# Quality control (QC) plots AFTER normalization:
tpptrNorm <- tpptrNormalize(data=tpptrData, normReqs=tpptrDefaultNormReqs())
tpptrDataNormalized <- tpptrNorm$normData
tppQCPlotsCorrelateExperiments(tppData=tpptrDataNormalized,
  annotStr="Normalized Fold Changes")
```

tppRefData

Example of a reference dataset for 2D-TPP experiments.

Description

Reference dataset obtained by TPP-TR experiments without drug treatment on HepG2 cell lines.

Details

tppRefData is a list of data frames that contains TPP-TR measurements for a large number of proteins in wide format. The experiments were performed in two replicates. It can be used as a reference for normalization of 2D-TPP data. See the vignette for the 2D workflow for details.

tpptrAnalyzeMeltingCurves

Analyze fitted curve parameters to detect significant shifts in melting points.

Description

Compute p-values for the pairwise comparisons of melting curve shifts between different conditions.

Usage

```
tpptrAnalyzeMeltingCurves(  
  data,  
  pValMethod = "robustZ",  
  pValFilter = list(minR2 = 0.8, maxPlateau = 0.3),  
  pValParams = list(binWidth = 300)  
)
```

Arguments

data	list of ExpressionSets containing fold changes and metadata. Their featureData fields contain the fitted melting curve parameters.
pValMethod	Method for p-value computation. Currently restricted to 'robustZ' (see Cox & Mann (2008)).
pValFilter	optional list of filtering criteria to be applied before p-value computation.
pValParams	optional list of parameters for p-value computation.

Details

The pValParams argument is a list that can contain optional parameters for the chosen p-value computation pValMethod. The following options are available:

1. pValMethod = "robustZ":
pValParams=list(binWidth=[your_binWidth]).

Value

A data frame in which the fit results are stored row-wise for each protein.

References

Cox, J., & Mann, M. (2008). MaxQuant enables high peptide identification rates, individualized ppb-range mass accuracies and proteome-wide protein quantification. *Nature biotechnology*, 26(12), 1367-1372.

Examples

```
data(hdacTR_smallExample)
tpptrData <- tpptrImport(hdacTR_config, hdacTR_data)
tpptrNorm <- tpptrNormalize(data=tpptrData,
                             normReqs=tpptrDefaultNormReqs())
normalizedData <- tpptrNorm$normData
## Not run:
# Fit melting curves to each protein
# (can take some time depending on device used):
fittedData <- tpptrCurveFit(normalizedData, nCores=1)
resultTable <- tpptrAnalyzeMeltingCurves(fittedData)
subset(resultTable, fulfills_all_4_requirements)$Protein_ID

## End(Not run)
```

tpptrCurveFit

Fit melting curves to all proteins in a dataset.

Description

Fit melting curves to all proteins in a dataset.

Usage

```
tpptrCurveFit(
  data,
  dataCI = NULL,
  resultPath = NULL,
  ggplotTheme = tppDefaultTheme(),
  doPlot = TRUE,
  startPars = c(Pl = 0, a = 550, b = 10),
  maxAttempts = 500,
  nCores = "max",
  verbose = FALSE
)
```

Arguments

data	list of ExpressionSets with protein fold changes for curve fitting.
dataCI	list of ExpressionSets with protein fold change confidence intervals for curve fitting. Default to NULL.

resultPath	location where to store the melting curve plots.
ggplotTheme	ggplot theme for melting curve plots.
doPlot	boolean value indicating whether melting curves should be plotted, or whether just the curve parameters should be returned.
startPars	start values for the melting curve parameters. Will be passed to function nls for curve fitting.
maxAttempts	maximal number of curve fitting attempts if model does not converge.
nCores	either a numerical value given the desired number of CPUs, or 'max' to automatically assign the maximum possible number (default).
verbose	plot name of each fitted protein to the command line as a means of progress report.

Details

If the melting curve fitting procedure does not converge, it will be repeatedly started from perturbed starting parameters (maximum iterations defined by argument `maxAttempts`)

If `doPlot = TRUE`, melting curves are plotted in individual files per protein. Each file is named by its unique identifier. Filenames are truncated to 255 characters (requirement by most operation systems). Truncated filenames are indicated by the suffix `"_truncated[d]"`, where [d] is a unique number to avoid redundancies.

The melting curve plots will be stored in a subfolder with name `Melting_Curves` at the location specified by `resultPath`.

Value

A list of ExpressionSets storing the data together with the melting curve parameters for each experiment. Each ExpressionSet contains the measured fold changes, as well as row and column metadata. In each ExpressionSet `S`, the fold changes can be accessed by `Biobase::exprs(S)`. Protein exp-Names can be accessed by `featureNames(S)`. Isobaric labels and the corresponding temperatures are returned by `S$label` and `S$temperature`.

See Also

[tppDefaultTheme](#)

Examples

```
data(hdacTR_smallExample)
tpptrData <- tpptrImport(configTable=hdacTR_config, data=hdacTR_data)
tpptrNorm <- tpptrNormalize(data=tpptrData, normReqs=tpptrDefaultNormReqs())
normalizedData <- tpptrNorm$normData
hdacSubsets <- lapply(normalizedData,
  function(d) d[grep1("HDAC", Biobase::featureNames(d))])
tpptrFittedHDACs <- tpptrCurveFit(hdacSubsets, nCores=1)
# Show estimated parameters for vehicle and treatment experiments:
Biobase::pData(Biobase::featureData(tpptrFittedHDACs[["Vehicle_1"]]))
Biobase::pData(Biobase::featureData(tpptrFittedHDACs[["Panobinostat_1"]]))
```

`tpptrDefaultNormReqs` *Default filter criteria for fold change normalization*

Description

Filter criteria as described in the publication.

Usage

```
tpptrDefaultNormReqs()
```

Value

List with two entries: 'fcRequirements' describes filtering requirements on fold change columns, 'otherRequirements' contains criteria on additional metadata columns.

Examples

```
data(hdacTR_smallExample)
tpptrData <- tpptrImport(configTable=hdacTR_config, data=hdacTR_data)
tpptrNorm <- tpptrNormalize(data=tpptrData, normReqs=tpptrDefaultNormReqs())
```

`tpptrFitSplines` *Perform spline fitting*

Description

Fit natural splines to all proteins in a dataset.

Usage

```
tpptrFitSplines(
  data,
  factorsH1,
  factorsH0 = character(),
  splineDF = 3:7,
  computeAUC = NULL,
  returnModels = TRUE,
  nCores = "max"
)
```

Arguments

<code>data</code>	the data to be fitted
<code>factorsH1</code>	which factors should be included in the alternative model?
<code>factorsH0</code>	which factors should be included in the null model?
<code>splineDF</code>	degrees of freedom for natural spline fitting.
<code>computeAUC</code>	DEPRECATED

returnModels	should the linear models be returned in a column of the result table? Activation increases memory requirements.
nCores	either a numerical value given the desired number of CPUs, or 'max' to automatically assign the maximum possible number (default).
	Argument splineDF specifies the degrees of freedom for natural spline fitting. As a single numeric value, it is directly passed on to the splineDF argument of <code>splines::ns</code> . Experience shows that <code>splineDF = 4</code> yields good results for TPP data sets with 10 temperature points. It is also possible to provide a numeric vector. In this case, splines are fitted for each entry and the optimal value is chosen per protein using Akaike's Information criterion.

Value

A table containing the fitted models per protein

See Also

[ns](#), [AICc](#)

Examples

```
data(hdacTR_smallExample)
tpptrData <- tpptrImport(configTable = hdacTR_config, data = hdacTR_data)
normResults <- tpptrNormalize(data = tpptrData,
                               normReqs = tpptrDefaultNormReqs())
normData_eSets <- normResults$normData
normData_longTable <- tpptrTidyUpESets(normData_eSets)
hdacSubset <- subset(normData_longTable, grepl("HDAC", uniqueID))
hdacSplineFits <- tpptrFitSplines(data = hdacSubset,
                                    factorsH1 = c("condition"),
                                    nCores = 1)
```

tpptrFTest

Analyze spline fits to detect differential behavior over time

Description

Analyze fitted natural spline models and look for differential behaviour between conditions by a moderated F-test.

Usage

```
tpptrFTest(fittedModels, doPlot = FALSE, resultPath = NULL)
```

Arguments

fittedModels	a table of fitted spline models (produced by <code>tpptrFitSplines</code>).
doPlot	boolean value indicating whether QC plots should be produced. Currently, QC plots comprise distributions of the F statistics, and the p-values before/ after Benjamini Hochberg adjustment.
resultPath	location where to store QC plots, if <code>doPlot = TRUE</code> .

Details

If `doPlot` is `TRUE`, but no `resultPath` is specified, the plots will be prompted to the active device.
 The moderated F-statistic is calculated by the following equation: ...

Value

A long table containing the hypothesis test results per protein.

See Also

[ns](#), [squeezeVar](#)

Examples

```
data(hdacTR_smallExample)
tpptrData <- tpptrImport(configTable = hdacTR_config, data = hdacTR_data)
normResults <- tpptrNormalize(data = tpptrData, normReqs = tpptrDefaultNormReqs())
normData_eSets <- normResults$normData
fitData <- tpptrTidyUpEsets(normData_eSets)
fits <- tpptrFitSplines(data = fitData, factorsH1 = "condition", nCores = 1, splineDF = 4:5)
testResults <- tpptrFTest(fittedModels = fits)
```

tpptrImport

Import TPP-TR datasets for analysis by the [TPP](#) package.

Description

`tpptrImport` imports several tables of protein fold changes and stores them in a list of Expression-Sets for use in the [TPP](#) package.

Usage

```
tpptrImport(
  configTable,
  data = NULL,
  idVar = "gene_name",
  fcStr = "rel_fc_",
  naStrs = c("NA", "n/d", "NaN"),
  qualColName = "qupm",
  outputFormat = "eSetList"
)
```

Arguments

<code>configTable</code>	either a datafram or the path to a spreadsheet. In both cases it specifies necessary information of the TPP-CCR experiment.
<code>data</code>	single datafram, or list of dataframes, containing fold change measurements and additional annotation columns to be imported. Can be used instead of specifying the file path in <code>configTable</code> .

<code>idVar</code>	character string indicating which data column provides the unique identifiers for each protein.
<code>fcStr</code>	character string indicating which columns contain the actual fold change values. Those column names containing the suffix <code>fcStr</code> will be regarded as containing fold change values.
<code>naStrs</code>	character vector indicating missing values in the data table. When reading data from file, this value will be passed on to the argument <code>na.strings</code> in function <code>read.delim</code> .
<code>qualColName</code>	character string indicating which column can be used for additional quality criteria when deciding between different non-unique protein identifiers.
<code>outputFormat</code>	output format. Either "eSetList" to obtain output in the same way as previously (will be deprecated soon), or "tidy" to obtain a

Details

The imported datasets have to contain measurements obtained by TPP-TR experiments. Fold changes need to be pre-computed using the lowest temperature as reference.

An arbitrary number of datasets can be specified by filename in the Path-column of the `configTable` argument, or given directly as a list of dataframes in the `data` argument. They can differ, for example, by biological replicate or by experimental condition (for example, treatment versus vehicle). Their names are defined uniquely by the `Experiment` column in `configTable`. Experimental conditions can be specified by an optional column in `configTable`.

The default settings are adjusted to analyze data of the python package `isobarQuant`. You can also customize them for your own dataset.

The `configTable` argument is a dataframe, or the path to a spreadsheet (tab-delimited text-file without quoted strings, or `xlsx` format). Information about each experiment is stored row-wise. It contains the following columns:

- `Path`: location of each datafile. Alternatively, data can be directly handed over by the `data` argument.
- `Experiment`: unique experiment names.
- `Condition`: experimental conditions of each dataset.
- `Label` columns: each isobaric label names a column that contains the temperatures administered for the label in the individual experiments.

Proteins with NAs in the data column specified by `idVar` receive unique generic IDs so that they can be processed by the package.

Value

A list of ExpressionSets storing the imported data for experiment. Each ExpressionSet contains the measured fold changes, as well as row and column metadata. In each ExpressionSet `S`, the fold changes can be accessed by `Biobase::exprs(S)`. Protein `expNames` can be accessed by `featureNames(S)`. Isobaric labels and the corresponding temperatures are returned by `S$label` and `S$temperature`

See Also

[tppccrImport](#)

Examples

```
data(hdacTR_smallExample)
tpptrData <- tpptrImport(hdacTR_config, hdacTR_data)
```

tpptrNormalize	<i>Normalize protein fold changes</i>
----------------	---------------------------------------

Description

Normalizes fold changes determined by TPP-TR experiments over different experimental groups.

Usage

```
tpptrNormalize(
  data,
  normReqs = tpptrDefaultNormReqs(),
  qcPlotTheme = tppDefaultTheme(),
  qcPlotPath = NULL,
  startPars = c(Pl = 0, a = 550, b = 10),
  maxAttempts = 1,
  fixedReference = NULL
)
```

Arguments

<code>data</code>	List of ExpressionSets with protein fold changes to be normalized.
<code>normReqs</code>	List of filtering criteria for construction of the normalization set.
<code>qcPlotTheme</code>	ggplot theme for the created plots
<code>qcPlotPath</code>	location where plots of the curves fitted to the normalization set medians should be stored.
<code>startPars</code>	start values for the melting curve parameters. Will be passed to function <code>nls</code> for curve fitting.
<code>maxAttempts</code>	maximal number of curve attempts to fit melting curve to fold change medians when computing normalization factors.
<code>fixedReference</code>	name of a fixed reference experiment for normalization. If <code>NULL</code> (default), the experiment with the best <code>R2</code> when fitting a melting curve through the median fold changes is chosen as the reference.

Details

Performs normalization of all fold changes in a given list of ExpressionSets. The normalization procedure is described in detail in Savitski et al. (2014). Whether normalization needs to be performed and what method is best suited depends on the experiment. Here we provide a reasonable solution for the data at hand.

We distinguish between filtering conditions on fold changes and on additional annotation columns. Correspondingly, `normReqs` contains two fields, `fcFilters` and `otherFilters`. Each entry contains a data frame with three columns specifying the column to be filtered, as well as upper and lower bounds. An example is given by [tpptrDefaultNormReqs](#).

Value

A list of ExpressionSets storing the normalized data for each experiment. Each ExpressionSet contains the measured fold changes, as well as row and column metadata. In each ExpressionSet S, the fold changes can be accessed by `Biobase::exprs(S)`. Protein expNames can be accessed by `featureNames(S)`. Isobaric labels and the corresponding temperatures are returned by `S$label` and `S$temperature`

References

Savitski, M. M., Reinhard, F. B., Franken, H., Werner, T., Savitski, M. F., Eberhard, D., ... & Drewes, G. (2014). Tracking cancer drugs in living cells by thermal profiling of the proteome. *Science*, 346(6205), 1255784.

Franken, H., Mathieson, T., Childs, D., Sweetman, G., Werner, T., Huber, W. & Savitski, M. M. (2015), Thermal proteome profiling for unbiased identification of drug targets and detection of downstream effectors. *Nature protocols* 10(10), 1567-1593.

See Also

[tpptrImport](#)

Examples

```
data(hdacTR_smallExample)
tpptrData <- tpptrImport(hdacTR_config, hdacTR_data)
tpptrNorm <- tpptrNormalize(data=tpptrData, normReqs=tpptrDefaultNormReqs())
names(tpptrNorm)
```

tpptrPlotSplines *Plot spline fits per protein*

Description

Plot spline fits per protein

Usage

```
tpptrPlotSplines(
  data,
  factorsH1 = NULL,
  factorsH0 = NULL,
  fittedModels,
  testResults,
  resultPath = NULL,
  individual = TRUE,
  overview = FALSE,
  returnPlots = FALSE,
  control = list(nCores = "max", maxRank = 500, highlightBelow = 0.05),
  maxRank = NULL,
  highlightBelow = NULL,
  plotIndividual = NULL,
  plotAlphabetical = NULL
)
```

Arguments

<code>data</code>	long table of proteins measurements that were used for spline fitting.
<code>factorsH1</code>	DEPRECATED
<code>factorsH0</code>	DEPRECATED
<code>fittedModels</code>	long table of fitted models. Output of tpptrFitSplines .
<code>testResults</code>	long table of p-values per protein. Output of tpptrFTest .
<code>resultPath</code>	an optional character vector with the name of the path where the plots should be saved.
<code>individual</code>	logical. Export each plot to individual files?
<code>overview</code>	logical. Generate summary pdfs?
<code>returnPlots</code>	logical. Should the ggplot objects be returned as well?
<code>control</code>	a list of general settings.
<code>maxRank</code>	DEPRECATED
<code>highlightBelow</code>	DEPRECATED
<code>plotIndividual</code>	DEPRECATED
<code>plotAlphabetical</code>	DEPRECATED Contains the following fields: <ul style="list-style-type: none"> • <code>nCores</code>: number of CPUs for parallel production of plots per protein if <code>individual = TRUE</code> (default: "max") • <code>maxRank</code>: how many of the top hits should be plotted if <code>overview = TRUE</code> (default: 500) • <code>highlightBelow</code>: maximum adjusted p-value for which a protein is highlighted by a different background color if <code>overview = TRUE</code> (default: 0.05)

Details

Plots of the natural spline fits will be stored in a subfolder with name `Spline_Fits` at the location specified by `resultPath`.

Exporting each plot to individual files (`individual = TRUE`) can cost runtime and the resulting files can be tedious to browse. If you just want to browse the results, use `overview = TRUE` instead.

If `overview = TRUE`, two summary PDFs are created that enable quick browsing through all results. They contain the plots in alphabetical order (`splineFit_alphabetical.pdf`), or ranked by p-values (`splineFit_top_xx.pdf`, where `xx` is the maximum rank defined by `overviewSettings$maxRank`).

Value

None

See Also

[ns](#), [AICc](#), [tpptrFitSplines](#), [tpptrFTest](#)

Examples

```
data(hdacTR_smallExample)
tpptrData <- tpptrImport(configTable = hdacTR_config, data = hdacTR_data)
tidyData <- tpptrTidyUpESets(tpptrData)
splineFits <- tpptrFitSplines(data = tidyData, nCores = 1, splineDF = 4:5,
                                 factorsH1 = "condition", returnModels = TRUE)
testResults <- tpptrFTest(fittedModels = splineFits, doPlot = FALSE)
tpptrPlotSplines(data = tidyData, fittedModels = splineFits,
                  individual = FALSE,
                  testResults = testResults, resultPath = getwd())
```

tpptrSplineFitAndTest *Perform spline fitting and analyze by moderated F-test*

Description

A wrapper function around the functions `tpptrFitSplines`, `tpptrFTest`, `tpptrPlotSplines`, which fits natural splines to all proteins in a dataset and detect differential behavior between conditions by a moderated F-test. The results are formatted as a wide table with one row per protein. This table contains all the original data, the test results, and (optionally) additional annotation columns for each protein.

Usage

```
tpptrSplineFitAndTest(
  data,
  factorsH1,
  factorsH0 = character(),
  resultPath = NULL,
  doPlot = TRUE,
  nCores = "max",
  splineDF = 3:7,
  additionalCols = NULL,
  verbose = NULL,
  ggplotTheme = NULL
)
```

Arguments

<code>data</code>	the data to be fitted.
<code>factorsH1</code>	which factors should be included in the alternative model?
<code>factorsH0</code>	which factors should be included in the null model?
<code>resultPath</code>	location where to store the spline plots per protein.
<code>doPlot</code>	boolean value indicating whether melting curves should be plotted, or whether just the curve parameters should be returned.
<code>nCores</code>	either a numerical value given the desired number of CPUs, or 'max' to automatically assign the maximum possible number (default).
<code>splineDF</code>	degrees of freedom for natural spline fitting.

```
additionalCols additional annotation per protein to append to the result table.
verbose DEPRECATED
ggplotTheme DEPRECATED.
```

Details

Plots of the natural spline fits will be stored in a subfolder with name Spline_Fits at the location specified by resultPath.

Argument data can either be long table, or a list of expressionSets as returned by [tpptrImport](#). If a long table, it needs to contain the following columns: 'uniqueID' (identifier), 'x' (independent variable for fitting, usually the temperature) and 'y' (dependent variable for fitting, usually the relative concentration).

Argument splineDF specifies the degrees of freedom for natural spline fitting. As a single numeric value, it is directly passed on to the splineDF argument of `splines::ns`. Experience shows that `splineDF = 4` yields good results for TPP data sets with 10 temperature points. It is also possible to provide a numeric vector. In this case, splines are fitted for each entry and the optimal value is chosen per protein using Akaike's Information criterion.

Value

A data frame in wide format with one row per protein. It contains the smoothing spline parameters and F-test results obtained by comparing the null and alternative models.

See Also

[ns](#), [AICc](#)

Examples

```
data(hdacTR_smallExample)
tpptrData <- tpptrImport(configTable = hdacTR_config, data = hdacTR_data)
fitData <- tpptrTidyUpESets(tpptrData)
hdacSplineFits <- tpptrSplineFitAndTest(data = fitData,
                                         factorsH1 = "condition",
                                         nCores = 1,
                                         splineDF = 4:5,
                                         doPlot = FALSE)
# Show estimated splines for HDAC1:
filter(hdacSplineFits, Protein_ID == "HDAC1")
# -> Which proteins showed significant condition effects?
hdacSplineFits %>% filter(p_adj_NPARC <= 0.01) %>% select(Protein_ID, p_adj_NPARC)
# Quality control: test for replicate-specific effects:
testResults <- tpptrSplineFitAndTest(data = fitData,
                                         factorsH1 = "replicate",
                                         nCores = 1,
                                         splineDF = 4,
                                         doPlot = FALSE)
# -> Which proteins showed significant replicate effects?
testResults %>% filter(p_adj_NPARC <= 0.01) %>% select(Protein_ID, p_adj_NPARC)
```

`tpptrTidyUpESets` *Tidy up expressionSets*

Description

Convert list of expressionSets (intermediate output of several TPP-TR functions) to tidy tables.

Usage

```
tpptrTidyUpESets(tppESetList, returnType = "exprs")
```

Arguments

`tppESetList` A list of expressionSets, returned by most TPP-TR functions.
`returnType` A string with two possible values: "exprs", "featureData".

Details

expressionSet lists are for example produced by [tpptrImport](#), [tpptrNormalize](#), [tpptrCurveFit](#).

Value

Either the fold changes per protein across all experiments (if `returnType = "exprs"`), or the additional annotation per protein and experiment (if `returnType = "featureData"`). For example, the peptide counts per identified protein can be found here.

Examples

```
data(hdacTR_smallExample)
tpptrData <- tpptrImport(configTable = hdacTR_config, data = hdacTR_data)
concentrations <- tpptrTidyUpESets(tpptrData)
additionalInfos <- tpptrTidyUpESets(tpptrData, returnType = "featureData")
summary(concentrations)
```

`TPPTR_reference_results_HepG2`

Example of a reference dataset for 2D-TPP experiments.

Description

Reference dataset obtained by TPP-TR experiments without drug treatment on HepG2 cell lines.

Details

Contains the data object [tppRefData](#).

Index

.onLoad (TPP), 17
AICc, 51, 56, 58
analyze2DTPP, 3
analyzeTPPCCR, 6, 17
analyzeTPPTR, 8, 17
brewer.pal, 5, 22
hdacCCR_config, 11, 13
hdacCCR_data, 11, 12, 12, 13
hdacCCR_smallExample, 12, 13
hdacTR_config, 12, 13, 14, 15
hdacTR_data, 13, 14, 15
hdacTR_resultsTable_smallExample, 14
hdacTR_smallExample, 13, 14, 15
nls, 9, 49, 54
ns, 51, 52, 56, 58
panobinostat_2DTPP_config, 15, 16
panobinostat_2DTPP_data, 15, 16, 16
panobinostat_2DTPP_smallExample, 15, 16, 16
resultTable, 14, 16
squeezeVar, 52
suppressMessages, 7, 10
TPP, 12, 14, 16, 17, 38, 52
TPP-defunct, 17
TPP-deprecated, 18
tpp2dAddAdditionalInfo, 18
tpp2dCalcFractAbundance, 19
tpp2dComputeFoldChanges, 20
tpp2dCreateCCRConfigFile (TPP-defunct), 17
tpp2dCreateDRplots, 21
tpp2dCreateReport, 22
tpp2dCreateTPPTRreference, 24, 30, 34
tpp2dCurveFit, 22, 25
tpp2dEvalConfigTable (TPP-defunct), 17
tpp2dExport, 26
tpp2dExportPlots, 28
tpp2dImport, 5, 28
tpp2dMerge2dRef, 29
tpp2dNormalize, 5, 31
tpp2dPlotCCRAllCurves (TPP-defunct), 17
tpp2dPlotCCRGoodCurves (TPP-defunct), 17
tpp2dPlotCCRSingleCurves (TPP-defunct), 17
tpp2dPlotQChist, 32
tpp2dPlotQCpEC50, 32
tpp2dRemoveZeroSias (TPP-defunct), 17
tpp2dReplaceColNames (TPP-defunct), 17
tpp2dSplineFitAndTest, 25, 33
tpp2dSplinePlot, 35
tpp2dTRReferenceObject, 36
tppccrCurveFit, 7, 36, 39, 42, 43
tppccrImport, 7, 37, 38, 53
tppccrNormalize, 7, 37, 39
tppccrNormalizeToReference, 40
tppccrPlotCurves, 41, 43
tppccrResultTable, 42
tppccrTransform, 37, 40, 43
tppDefaultTheme, 42, 44, 46, 49
tppExport, 7, 10, 45
tppQCPLOTSCorrelateExperiments, 16, 46
tppRefData, 47, 59
TPPTR_reference_results_HepG2, 59
tpptrAnalyzeMeltingCurves, 10, 45, 47
tpptrCurveFit, 10, 48, 59
tpptrDefaultNormReqs, 10, 50, 54
tpptrFitSplines, 50, 56
tpptrFTTest, 51, 56
tpptrImport, 10, 39, 52, 55, 58, 59
tpptrNormalize, 10, 54, 59
tpptrPlotSplines, 55
tpptrSplineFitAndTest, 57
tpptrTidyUpESets, 59