

Package ‘oligoClasses’

January 20, 2026

Version 1.72.0

Title Classes for high-throughput arrays supported by oligo and crlmm

Author Benilton Carvalho and Robert Scharpf

Maintainer Benilton Carvalho <beniltoncarvalho@gmail.com> and Robert Scharpf <rscharpf@jhsph.edu>

Depends R (>= 2.14)

Imports BiocGenerics (>= 0.27.1), Biobase (>= 2.17.8), methods, graphics, IRanges (>= 2.5.17), GenomicRanges (>= 1.23.7), SummarizedExperiment, Biostrings (>= 2.23.6), affyio (>= 1.23.2), foreach, BiocManager, utils, S4Vectors (>= 0.9.25), RSQLite, DBI, ff

Enhances doMC, doMPI, doSNOW, doParallel, doRedis

Suggests hapmapsnp5, hapmapsnp6, pd.genomewidesnp.6, pd.genomewidesnp.5, pd.mapping50k.hind240, pd.mapping50k.xba240, pd.mapping250k.sty, pd.mapping250k.nsp, genomewidesnp6Crlmm (>= 1.0.7), genomewidesnp5Crlmm (>= 1.0.6), RUnit, human370v1cCrlmm, VanillaICE, crlmm

Description This package contains class definitions, validity checks, and initialization methods for classes used by the oligo and crlmm packages.

License GPL (>= 2)

LazyLoad yes

Collate AllClasses.R AllGenerics.R utils-general.R utils-lds.R
utils-parallel.R methods-gSet.R initialize-methods.R
methods-AlleleSet.R methods-AnnotatedDataFrame.R
methods-FeatureSet.R methods-AssayData.R
methods-SnpFeatureSet.R methods-oligoSnpSet.R
methods-CopyNumberSet.R methods-CNSet.R methods-PDInfo.R
methods-RangedDataCNV.R methods-SnpSet.R
methods-GenomeAnnotatedDataFrame.R methods-BeadStudioSet.R
methods-BeadStudioSetList.R methods-gSetList.R
methods-GRanges.R methods-SummarizedExperiment.R show-methods.R
functions.R zzz.R

biocViews Infrastructure

time-stamp-pattern ``8/Date: %3a %3b %2d %02H:%02M:%02S %Z %:y\n"

RxygenNote 6.1.1

git_url <https://git.bioconductor.org/packages/oligoClasses>

git_branch RELEASE_3_22
git_last_commit d8ec574
git_last_commit_date 2025-10-29
Repository Bioconductor 3.22
Date/Publication 2026-01-19

Contents

affyPlatforms	3
AlleleSet-class	4
annotationPackages	5
AssayData-methods	5
AssayDataList	6
assayDataList-methods	7
batch	7
batchStatistics	8
BeadStudioSet-class	9
BeadStudioSetList-class	10
celfileDate	11
celfileName	11
checkExists	12
checkOrder	13
chromosome-methods	14
chromosome2integer	15
CNSet-class	15
CopyNumberSet-class	17
CopyNumberSet-methods	18
createFF	20
db	20
DBPDIInfo-class	21
Deprecated	21
efsExample	22
exprs-methods	22
featureDataList-methods	22
FeatureSet-class	23
ffdf-class	24
ff_matrix-class	24
ff_or_matrix-class	25
fileConnections	25
flags	26
generics	27
GenomeAnnotatedDataFrame-class	27
GenomeAnnotatedDataFrameFrom-methods	28
genomeBuild	29
geometry	30
getA	30
getBar	31
getSequenceLengths	32
GRanges-methods	33
gSet-class	34

gSetList-class	35
i2p	36
initializeBigMatrix	37
integerMatrix	38
is.ffmatrix	39
isPackageLoaded	39
isSnp-methods	40
kind	40
ldSetOptions	41
length-methods	42
library2	42
list.celfiles	43
ListClasses	43
locusLevelData	44
makeFeatureGRanges	44
manufacturer-methods	45
ocLapply	46
ocSamples	46
oligoSet	47
oligoSnpSet-methods	48
parStatus	49
pdPkgFromBioC	49
platform-methods	50
pmFragmentLength-methods	50
position-methods	51
requireAnnotation	51
requireClusterPkgSet	52
sampleNames-methods	53
scqsExample	53
setCluster	53
sfsExample	54
SnpSet-methods	55
SnpSet2-class	56
SnpSuperSet-class	57
splitIndicesByLength	58
sqsExample	59
SummarizedExperiment-methods	59

Index**61**

affyPlatformsAvailable Affymetrix platforms for SNP arrays

Description

Provides a listing of available Affymetrix platforms currently supported by the R package oligo

Usage

```
affyPlatforms()
```

Value

A vector of class character.

Author(s)

R. Scharpf

Examples

```
affyPlatforms()
```

AlleleSet-class

Class "AlleleSet"

Description

A class for storing the locus-level summaries of the normalized intensities

Objects from the Class

Objects can be created by calls of the form `new("AlleleSet", assayData, phenoData, featureData, experimentData, annotation, protocolData, ...)`.

Slots

```
assayData: Object of class "AssayData" ~~
phenoData: Object of class "AnnotatedDataFrame" ~~
featureData: Object of class "AnnotatedDataFrame" ~~
experimentData: Object of class "MIAME" ~~
annotation: Object of class "character" ~~
protocolData: Object of class "AnnotatedDataFrame" ~~
__.classVersion__: Object of class "Versions" ~~
```

Extends

Class "[eSet](#)", directly. Class "[VersionedBiobase](#)", by class "eSet", distance 2. Class "[Versioned](#)", by class "eSet", distance 3.

Methods

```
allele signature(object = "AlleleSet"): extract allele specific summaries. For 50K (XBA and Hind) and 250K (Sty and Nsp) arrays, an additional argument (strand) must be used (allowed values: 'sense', 'antisense').
bothStrands signature(object = "AlleleSet"): tests if data contains allele summaries on both strands for a given SNP.
bothStrands signature(object = "SnpFeatureSet"): tests if data contains allele summaries on both strands for a given SnpFeatureSet.
db signature(object = "AlleleSet"): link to database connection.
getA signature(object = "AlleleSet"): average intensities (across alleles)
getM signature(object = "AlleleSet"): log-ratio (Allele A vs. Allele B)
```

Author(s)

R. Scharpf

See Also

[SnpSuperSet](#), [CNSet](#)

Examples

```
showClass("AlleleSet")
## an empty AlleleSet
x <- new("matrix")
new("AlleleSet", senseAlleleA=x, senseAlleleB=x,
    antisenseAlleleA=x, antisenseAlleleB=x)
##or
new("AlleleSet", alleleA=x, alleleB=x)
```

annotationPackages *Annotation Packages*

Description

annotationPackages will return a character vector of the names of annotation packages.

Usage

```
annotationPackages()
```

Value

a character vector of the names of annotation packages

AssayData-methods *Methods for class AssayData in the oligoClasses package*

Description

Batch statistics used for estimating copy number are stored as AssayData in the 'batchStatistics' slot of the CNSet class. Each element in the AssayData must have the same number of rows and columns. Rows correspond to features and columns correspond to batch.

Objects from the Class

A virtual Class: No objects may be created from it.

Methods

```
batchNames signature(object = "AssayData"): ...
batchNames<- signature(object = "AssayData"): ...
corr signature(object = "AssayData", allele = "character"): ...
nu signature(object = "AssayData", allele = "character"): ...
phi signature(object = "AssayData", allele = "character"): ...
```

Details

- lM: Extracts entire list of linear model parameters.
- corr: The within-genotype correlation of log2(A) and log2(B) intensities.
- nu: The intercept for the linear model. The linear model is fit to the A and B alleles independently.
- phi: The slope for the linear model. The linear model is fit independently to the A and B alleles.

See Also

[CNSet-class](#)

Examples

```
library(crlmm)
library(BioBase)
data(cnSetExample, package="crlmm")
cnSet <- cnSetExample
isCurrent(cnSet)
assayDataElementNames(batchStatistics(cnSet))
## Accessors for linear model parameters
## -- Included here primarily as a check that accessors are working
## -- Values are all NA until CN estimation is performed using the crlmm package
##
## subsetting
cnSet[1:10, ]
## names of elements in the object
## accessors for parameters
nu(cnSet, "A")[1:10, ]
nu(cnSet, "B")[1:10, ]
phi(cnSet, "A")[1:10, ]
phi(cnSet, "B")[1:10, ]
```

AssayDataList

Create a list of assay data elements

Description

The eSetList-derived classes have an assayDataList slot instead of an assayData slot.

Usage

```
AssayDataList(storage.mode = c("lockedEnvironment", "environment", "list"), ...)
```

Arguments

- storage.mode See `assayDataNew`.
- ... Named lists of matrices

Value

`environment`

Author(s)

R.Scharpf

See Also[assayDataNew](#)**Examples**

```
r <- replicate(5, matrix(rnorm(25),5,5), simplify=FALSE)
r <- lapply(r, function(x,dns) {dimnames(x) <- dns; return(x)}, dns=list(letters[1:5], LETTERS[1:5]))
ad <- AssayDataList(r=r)
ls(ad)
```

assayDataList-methods *Accessor for slot assayDataList in Package **oligoClasses***

Description

Accessor for slot assayDataList in Package **oligoClasses**

Methods

```
signature(object = "gSetList") An object inheriting from class gSetList.
signature(object = "oligoSetList") An object inheriting from class gSetList.
```

batch *The batch variable for the samples.*

Description

Copy number estimates are susceptible to systematic differences between groups of samples that were processed at different times or by different labs. While 'batch' is often unknown, a useful surrogate is often the scan date of the arrays (e.g., the month of the calendar year) or the 96 well chemistry plate on which the samples were arrayed during lab processing.

Usage

```
batch(object)
batchNames(object)
batchNames(object) <- value
```

Arguments

object	An object of class CNSet.
value	For 'batchNames', the value must be a character string corresponding of the unique batch names.

Value

The method 'batch' returns a character vector that has the same length as the number of samples in the CNSet object.

Author(s)

R. Scharpf

See Also

[CNSet-class](#)

Examples

```
a <- matrix(1:25, 5, 5)
colnames(a) <- letters[1:5]
object <- new("CNSet", alleleA=a, batch=rep("batch1", 5))
batch(object)
batchNames(object)
```

batchStatistics

Accessor for batch statistics uses for copy number estimation and storage of model parameters

Description

The batchStatistics slot contains statistics estimated from each batch that are used to derive copy number estimates.

Usage

```
batchStatistics(object)
batchStatistics(object) <- value
```

Arguments

object	An object of class CNSet
value	An object of class AssayData

Details

An object of class AssayData for slot batchStatistics is initialized automatically when creating a new CNSet instance. Required in the call to new is a factor called batch whose unique values determine the number of columns for each assay data element.

Value

batchStatics is an accessor for the slot batchStatistics that returns an object of class AssayData.

See Also

[CNSet-class](#), [batchNames](#), [batch](#)

BeadStudioSet-class *Class "BeadStudioSet"*

Description

A container for log R ratios and B allele frequencies from SNP arrays.

Objects from the Class

Objects can be created by calls of the form `new("BeadStudioSet", assayData, phenoData, featureData, experimentData, annotation, protocolData, baf, lrr, ...)`.

Slots

`featureData`: Object of class "GenomeAnnotatedDataFrame" ~~
`assayData`: Object of class "AssayData" ~~
`phenoData`: Object of class "AnnotatedDataFrame" ~~
`experimentData`: Object of class "MIAxE" ~~
`annotation`: Object of class "character" ~~
`protocolData`: Object of class "AnnotatedDataFrame" ~~
`genome`: Object of class "character" ~~
`.__classVersion__`: Object of class "Versions" ~~

Extends

Class "[gSet](#)", directly. Class "[eSet](#)", by class "gSet", distance 2. Class "[VersionedBiobase](#)", by class "gSet", distance 3. Class "[Versioned](#)", by class "gSet", distance 4.

Methods

In the methods below, `object` has class `BeadStudioSet`.

`baf(object)`: accessor for the matrix of B allele frequencies.
`baf(object) <- value`: replacement method for B allele frequencies: value must be a matrix of integers.
`as(object, "data.frame")`: coerce to data.frame with column headers 'lrr', 'baf', 'x' (physical position with unit Mb), 'id', and 'is.snp'. Used for plotting with lattice.
`copyNumber(object)`: accessor for log R ratios.
`copyNumber(object) <- value`: replacement method for the log R ratios
`initialize` `signature(.Object = "BeadStudioSet")`: constructs an instance of the class
`lrr(object)`: accessor for matrix of log R ratios
`lrr(object) <- value`: replacement method for log R ratios: value should be a matrix or a `ff_matrix`.
`show(object)`: print a short summary of the `BeadStudioSet` object.
`updateObject(object)`: update a `BeadStudioSet` object.

Author(s)

R. Scharpf

Examples

```
new("BeadStudioSet")
```

BeadStudioSetList-class

List classes with assay data listed by chromosome

Description

Container for log R ratios and B allele frequencies stored by chromosome.

Slots

assayDataList: Object of class "AssayData" ~~
phenoData: Object of class "AnnotatedDataFrame" ~~
featureDataList: Object of class "list" ~~
chromosome: Object of class "integer" ~~
annotation: Object of class "character" ~~
genome: Object of class "character" indicating the genome build. Valid entries are "hg18" and "hg19".

Methods defined for the class

clone2(object, id, prefix="", ...)

Performs a deep copy of the ff objects in the assay data elements of object. A new object of the same class will be instantiated. The ff objects in the instantiated object will point to ff files on disk with prefix given by the argument **prefix**.

A use-case for such a function is that one may want to perform wave correction on the log R ratios in object, but keep a copy of the original unadjusted log R ratios. If object is not copied using **clone2** prior to wave correction, the log R ratios will be updated on disk and the original, unadjusted log R ratios will no longer be available.

Accessors

baf(object) An accessor for the B allele frequencies (BAFs). The accessor returns a list where each element of the list is a matrix of the BAFs for the corresponding element in the SetList object. While the BAFs have a range [0, 1], they are often saved internally as integers by multiplying the original BAFs by 1000. Users can restore the original scale by dividing by 1000.

lrr(object) An accessor for the log R ratios, an estimate of the copy number (presumably relative to diploid copy number) at each marker on a SNP array. The accessor returns a list where each element of the list is a matrix of the log R ratios for the corresponding element in the SetList object. The log R ratios are often saved internally as integers by multiplying the original LRRs by 100 in order to reduce the memory footprint of large studies. Users can restore the original scale by dividing by 100.

Author(s)

R. Scharpf

See Also

See supporting packages for methods defined for the class.

celfileDate

Cel file dates

Description

Parses cel file dates from the header of .CEL files for the Affymetrix platform

Usage

```
celfileDate(filename)
```

Arguments

filename Name of cel file

Value

character string

Author(s)

H. Jaffee

Examples

```
require(hapmapsnp6)
path <- system.file("celFiles", package="hapmapsnp6")
celfiles <- list.celfiles(path, full.names=TRUE)
dts <- sapply(celfiles, celfileDate)
```

celfileName

Extracts complete cel file name from a CNSet object

Description

Returns the complete cel file (including path) for a CNSet object

Usage

```
celfileName(object)
```

Arguments

object An object of class CNSet

Value

Character string vector.

Note

If the CEL files for an experiment are relocated, the datadir should be updated accordingly. See examples.

Author(s)

R. Scharpf

Examples

```
## Not run:
if(require(crlmm)){
  data(cnSetExample, package="crlmm")
  celfileName(cnSetExample)
}

## End(Not run)
```

checkExists

Checks to see whether an object exists and, if not, executes the appropriate function.

Description

Only loads an object if the object name is not in the global environment. If not in the global environment and the file exists, the object is loaded (by default). If the file does not exist, the function FUN is run.

Usage

```
checkExists(.name, .path = ".", .FUN, .FUN2, .save.it=TRUE, .load.it, ...)
```

Arguments

.name	Character string giving name of object in global environment
.path	Path to where the object is saved.
.FUN	Function to be executed if <name> is not in the global environment and the file does not exist.
.FUN2	Not currently used.
.save.it	Logical. Whether to save the object to the directory indicated by path. This argument is ignored if the object was loaded from file or already exists in the .GlobalEnv.
.load.it	Logical. If load.it is TRUE, we try to load the object from the indicated path. The returned object will replace the object in the .GlobalEnv unless the object is bound to a different name (symbol) when the function is executed.
...	Additional arguments passed to FUN.

Value

Could be anything – depends on what FUN, FUN2 perform.

Future versions could return a 0 or 1 indicating whether the function performed as expected.

Author(s)

R. Scharpf

Examples

```
path <- tempdir()
dir.create(path)
x <- 3+6
x <- checkExists("x", .path=path, .FUN=function(y, z) y+z, y=3, z=6)
rm(x)
x <- checkExists("x", .path=path, .FUN=function(y, z) y+z, y=3, z=6)
rm(x)
x <- checkExists("x", .path=path, .FUN=function(y, z) y+z, y=3, z=6)
rm(x)
##now there is a file called x.rda in tempdir(). The file will be loaded
x <- checkExists("x", .path=path, .FUN=function(y, z) y+z, y=3, z=6)
rm(x)
unlink(path, recursive=TRUE)
```

checkOrder

Checks whether a eSet-derived class is ordered by chromosome and physical position

Description

Checks whether a eSet-derived class (e.g., a SnpSet or CNSet object) is ordered by chromosome and physical position

Usage

```
checkOrder(object, verbose = FALSE)
chromosomePositionOrder(object, ...)
```

Arguments

object	A SnpSet or CopyNumberSet.
verbose	Logical.
...	additional arguments to order

Details

Checks whether the object is ordered by chromosome and physical position.

Value

Logical

Author(s)

R. Scharpf

See Also

[order](#)

Examples

```
data(oligoSetExample)
if(!checkOrder(oligoSet)){
  oligoSet <- chromosomePositionOrder(oligoSet)
}
checkOrder(oligoSet)
```

chromosome-methods

Methods for function chromosome in package oligoClasses

Description

Methods for function **chromosome** in package **oligoClasses** ~~

Methods

The methods for **chromosome** extracts the chromosome (represented as an integer) for each marker in a **eSet**-derived class or a **AnnotatedDataFrame**-derived class.

```
signature(object = "AnnotatedDataFrame") Accessor for chromosome.
signature(object = "eSet") If 'chromosome' is included in fvarLabels(object), the integer
                           representation of the chromosome will be returned. Otherwise, an error is thrown.
signature(object = "GenomeAnnotatedDataFrame") Accessor for chromosome. If annotation
                           was not available due to a missing or non-existent annotation package, the value returned by
                           the accessor will be a vector of zero's.
(chromosome(object) <- value): Assign chromosome to the AnnotatedDataFrame slot of an
                           eSet-derived object.
signature(object = "RangedDataCNV") Accessor for chromosome.
```

Note

Integer representation: chr X = 23, chr Y = 24, chr XY = 25. Symbols M, Mt, and MT are coded as 26.

See Also

[chromosome2integer](#)

Examples

```
chromosome2integer(c(1:22, "X", "Y", "XY", "M"))
```

chromosome2integer	<i>Converts chromosome to integer</i>
--------------------	---------------------------------------

Description

Coerces character string for chromosome in the pd. annotation packages to integers

Usage

```
chromosome2integer(chrom)
integer2chromosome(intChrom)
```

Arguments

chrom	A one or 2 letter character string (e.g, "1", "X", "Y", "MT", "XY")
intChrom	An integer vector with values 1-25 possible

Details

This is useful when sorting SNPs in an object by chromosome and physical position – ensures that the sorting is done in the same way for different objects.

Value

integer2chromosome returns a vector of character string indicating the chromosome the same length as intChrom. chromosome2integer returns a vector of integers the same length as the number of elements in the chrom vector.

Author(s)

R. Scharpf

Examples

```
chromosome2integer(c(1:22, "X", "Y", "XY", "M"))
integer2chromosome(chromosome2integer(c(1:22, "X", "Y", "XY", "M")))
```

CNSet-class	<i>Class "CNSet"</i>
-------------	----------------------

Description

CNSet is a container for intermediate data and parameters pertaining to allele-specific copy number estimation. Methods for CNSet objects, including accessors for linear model parameters and allele-specific copy number are included here.

Objects from the Class

An object from the class is not generally intended to be initialized by the user, but returned by the `genotype` function in the `crlmm` package.

The following creates a very basic CNSet with `assayData` containing the required elements.

```
new(CNSet, alleleA=new("matrix"), alleleB=new("matrix"), call=new("matrix"), callProbability=new("matrix"),
batch=new("factor"))
```

Slots

```
batch: Object of class "factor" ~~
batchStatistics: Object of class "AssayData" ~~
assayData: Object of class "AssayData" ~~
phenoData: Object of class "AnnotatedDataFrame" ~~
featureData: Object of class "AnnotatedDataFrame" ~~
experimentData: Object of class "MIAME" ~~
annotation: Object of class "character" ~~
protocolData: Object of class "AnnotatedDataFrame" ~~
datadir: Object of class "list" ~~
mixtureParams: Object of class "matrix" ~~
._classVersion_.: Object of class "Versions" ~~
```

Methods

The argument `object` for the following methods is a CNSet.

```
object[i, j]: subset the CNSet object by markers (i) and/or samples (j).
A(objet): accessor for the normalized intensities of allele A
A(object) <- value: replace intensities for the A allele intensities by value. The object value
must be a matrix, ff_matrix, or ffdf.
allele(object, allele): accessor for the normalized intensities for the A or B allele. The
argument for allele must be either 'A' or 'B'
B(objet): accessor for the normalized intensities of allele B
B(object) <- value: replace intensities for the B allele intensities by value. The object value
must be a matrix, ff_matrix, or ffdf.
batch(object): vector of batch labels for each sample.
batchNames(object): the unique batch names
batchNames(object) <- value: relabel the batches
calls(object): accessor for genotype calls coded as 1 (AA), 2 (AB), or 3 (BB). Nonpolymorphic
markers are NA.
confs(object): accessor for the genotype confidence scores.
close(object): close any open file connections to ff objects stored in the CNSet object.
as(object, "oligoSnpSet"): coerce a CNSet object to an object of class oligoSnpSet – a con-
tainer for the total copy number and genotype calls.
corr(object): the correlation of the A and B intensities within each genotype.
```

```

flags(object): flags to indicate possible problems with the copy number estimation. Not fully
implemented at this point.

new("CNSet"): instantiating a CNSet object.

nu(object, allele): accessor for the intercept (background) for the A and B alleles. The value
of allele must be 'A' or 'B'.

open(object) open file connections for all ff objects stored in the CNSet object.

nu(object, allele): accessor for the slope for the A and B alleles. The value of allele must
be 'A' or 'B'.

sigma2(object, allele): accessor for the within genotype variance

tau2(object, allele): accessor for background variance

```

Author(s)

R. Scharpf

Examples

```
new("CNSet")
```

CopyNumberSet-class *Class "CopyNumberSet"*

Description

Container for storing total copy number estimates and confidence scores of the copy number estimates.

Objects from the Class

Objects can be created by calls of the form `new("CopyNumberSet", assayData, phenoData, featureData, experimentData, annotation, protocolData, copyNumber, cnConfidence, ...)`.

Slots

```

assayData: Object of class "AssayData" ~~
phenoData: Object of class "AnnotatedDataFrame" ~~
featureData: Object of class "AnnotatedDataFrame" ~~
experimentData: Object of class "MIAxE" ~~
annotation: Object of class "character" ~~
protocolData: Object of class "AnnotatedDataFrame" ~~
._classVersion_.: Object of class "Versions" ~~

```

Extends

Class "[eSet](#)", directly. Class "[VersionedBiobase](#)", by class "eSet", distance 2. Class "[Versioned](#)", by class "eSet", distance 3.

Methods

```

cnConfidence signature(object = "CopyNumberSet"): ...
cnConfidence<- signature(object = "CopyNumberSet", value = "matrix"): ...
coerce signature(from = "CNSet", to = "CopyNumberSet"): ...
copyNumber signature(object = "CopyNumberSet"): ...
copyNumber<- signature(object = "CopyNumberSet", value = "matrix"): ...
initialize signature(.Object = "CopyNumberSet"): ...

```

Note

This container is primarily for platforms for which genotypes are unavailable. As `oligoSnpSet` extends this class, methods related to total copy number that do not depend on genotypes can be defined at this level.

Author(s)

R. Scharpf

See Also

For genotyping platforms, total copy number estimates and genotype calls can be stored in the `oligoSnpSet` class.

Examples

```

showClass("CopyNumberSet")
cnset <- new("CopyNumberSet")
ls(Biobase::assayData(cnset))

```

CopyNumberSet-methods *Methods for class CopyNumberSet.*

Description

Accessors and CopyNumberSet

Usage

```

copyNumber(object, ...)
cnConfidence(object)
copyNumber(object) <- value
cnConfidence(object) <- value

```

Arguments

object	CopyNumberSet object or derived class
...	Ignored for CopyNumberSet and oligoSnpSet.
value	matrix

Value

copyNumber returns a matrix of copy number estimates or relative copy number estimates. Since the copy number estimates are stored as integers (copy number * 100), the matrix returned by the copyNumber accessor will need to be divided by a factor of 100 to transform the measurements back to the original copy number scale.

cnConfidence returns a matrix of confidence scores for the copy number estimates. These are also represented as integers and will require a back-transformation to the original scale.

Examples

```
library(Biobase)
data(locusLevelData)
path <- system.file("extdata", package="oligoClasses")
fd <- readRDS(file.path(path, "genomeAnnotatedDataFrameExample.rds"))
## the following command creates an 'oligoSnpSet' object, storing
## an integer representation of the log2 copy number in the 'copyNumber' element
## of the assayData. Genotype calls and genotype confidence scores are also stored
## in the assayData.
oligoSet <- new("oligoSnpSet",
  copyNumber=integerMatrix(log2(locusLevelData[["copynumber"]]/100), 100),
  call=locusLevelData[["genotypes"]],
  callProbability=integerMatrix(locusLevelData[["crlmmConfidence"]], 1),
  annotation=locusLevelData[["platform"]],
  featureData=fd,
  genome="hg19")

## There are several accessors for the oligoSnpSet class.
icn <- copyNumber(oligoSet)
range(icn) ## integer scale
lcn <- icn/100
range(lcn) ## log2 copy number

## confidence scores for the genotypes are also represented on an integer scale
ipr <- snpCallProbability(oligoSet)
range(ipr) ## integer scale

## for genotype confidence scores, the helper function i2p
## converts back to a probability scale
pr <- i2p(ipr)
range(pr)

## The helper function confs is a shortcut, extracting the
## integer-based confidence scores and transforming to the
## probability scale
pr2 <- confs(oligoSet)
all.equal(pr, pr2)

## To extract information on the annotation of the SNPs, one can use
position(oligoSet)
chromosome(oligoSet)
## the position and chromosome coordinates were extracted from build hg19
genomeBuild(oligoSet)
```

createFF	<i>Create ff objects.</i>
----------	---------------------------

Description

Creates ff objects (array-like) using settings (path) defined by oligoClasses.

Usage

```
createFF(name, dim, vmode = "double", initdata = NULL)
```

Arguments

name	Prefix for filename.
dim	Dimensions.
vmode	Mode.
initdata	NULL.

Value

ff object.

Note

This function is meant to be used by developers.

See Also

ff

db	<i>Get the connection to the SQLite Database</i>
----	--

Description

This function will return the SQLite connection to the database associated to objects used in oligo.

Usage

```
db(object)
```

Arguments

object	Object of valid class. See methods.
--------	-------------------------------------

Value

SQLite connection.

Methods

```
object = "FeatureSet" object of class FeatureSet
object = "SnpCallSet" object of class SnpCallSet
object = "DBPDInfo" object of class DBPDInfo
object = "SnpLevelSet" object of class SnpLevelSet
```

Author(s)

Benilton Carvalho

Examples

```
## db(object)
```

DBPDInfo-class	<i>Class "DBPDInfo"</i>
----------------	-------------------------

Description

A class for Platform Design Information objects, stored using a database approach

Objects from the Class

Objects can be created by calls of the form `new("DBPDInfo", ...)`.

Slots

```
getdb: Object of class "function"
tableInfo: Object of class "data.frame"
manufacturer: Object of class "character"
genomebuild: Object of class "character"
geometry: Object of class "integer" with length 2 (rows x columns)
```

Methods

annotation string describing annotation package associated to object

Deprecated	<i>oligoClasses Deprecated</i>
------------	--------------------------------

Description

The function, class, or data object you asked for has been deprecated.

efsExample	<i>ExpressionFeatureSet Object</i>
------------	------------------------------------

Description

Example of ExpressionFeatureSet Object.

Usage

```
data(efsExample)
```

Format

Object belongs to ExpressionFeatureSet class.

Examples

```
data(efsExample)
class(efsExample)
```

exprs-methods	<i>Accessor for the 'exprs' slot</i>
---------------	--------------------------------------

Description

Accessor for the 'exprs'/'se.exprs' slot of FeatureSet-like objects

Methods

object = "ExpressionSet" Expression matrix for objects of this class. Usually results of pre-processing algorithms, like RMA.
object = "FeatureSet" General container 'exprs' inherited from eSet
object = "SnpSet" General container 'exprs' inherited from eSet, not yet used.

featureDataList-methods	<i>Accessor for slot featureDataList in Package oligoClasses ~~</i>
-------------------------	--

Description

Accessor for slot featureDataList in Package **oligoClasses** ~~

Methods

signature(object = "gSetList") An object inheriting from class gSetList.

FeatureSet-class *"FeatureSet" and "FeatureSet" Extensions*

Description

Classes to store data from Expression/Exon/SNP/Tiling arrays at the feature level.

Objects from the Class

The FeatureSet class is VIRTUAL. Therefore users are not able to create instances of such class.

Objects for FeatureSet-like classes can be created by calls of the form: `new(CLASSNAME, assayData, manufacturer, platform, exprs, phenoData, featureData, experimentData, annotation, ...)`. But the preferred way is using parsers like [read.celfiles](#) and [read.xysfiles](#).

Slots

`manufacturer`: Object of class "character"
`assayData`: Object of class "AssayData"
`phenoData`: Object of class "AnnotatedDataFrame"
`featureData`: Object of class "AnnotatedDataFrame"
`experimentData`: Object of class "MIAME"
`annotation`: Object of class "character"
`.__classVersion__`: Object of class "Versions"

Methods

show `signature(.Object = "FeatureSet")`: show object contents
bothStrands `signature(.Object = "SnpFeatureSet")`: checks if object contains data for both strands simultaneously (50K/250K Affymetrix SNP chips - in this case it returns TRUE); if object contains data for one strand at a time (SNP 5.0 and SNP 6.0 - in this case it returns FALSE)

Author(s)

Benilton Carvalho

See Also

[eSet](#), [VersionedBiobase](#), [Versioned](#)

Examples

```
set.seed(1)
tmp <- 2^matrix(rnorm(100), ncol=4)
rownames(tmp) <- 1:25
colnames(tmp) <- paste("sample", 1:4, sep="")
efs <- new("ExpressionFeatureSet", exprs=tmp)
```

ffdf-class	<i>Class "ffdf"</i>
------------	---------------------

Description

Extended package ff's class definitions for ff to S4.

Objects from the Class

A virtual Class: No objects may be created from it.

Slots

.S3Class: Object of class ffdf ~~

Extends

Class "[oldClass](#)", directly. Class "[list_or_ffdf](#)", directly.

Methods

No methods defined with class "ffdf" in the signature.

ff_matrix-class	<i>Class "ff_matrix"</i>
-----------------	--------------------------

Description

~~ A concise (1-5 lines) description of what the class is. ~~

Objects from the Class

A virtual Class: No objects may be created from it.

Slots

.S3Class: Object of class "character" ~~

Extends

Class "[oldClass](#)", directly.

Methods

annotatedDataFrameFrom signature(object = "ff_matrix"): ...

Examples

```
showClass("ff_matrix")
```

ff_or_matrix-class *Class "ff_or_matrix"*

Description

A class union of 'ffdf', 'ff_matrix', and 'matrix'

Objects from the Class

A virtual Class: No objects may be created from it.

Methods

GenomeAnnotatedDataFrameFrom `signature(object = "ff_or_matrix"):` ...

Author(s)

R. Scharpf

See Also

[ff](#), [ffdf](#)

Examples

```
showClass("ff_or_matrix")
```

fileConnections *Open and close methods for matrices and numeric vectors*

Description

CNSet objects can contain ff-derived objects that contain pointers to files on disk, or ordinary matrices. Here we define open and close methods for ordinary matrices and vectors that that simply pass back the original matrix/vector.

Usage

```
open(con, ...)
openff(object)
closeff(object)
```

Arguments

con	matrix or vector
object	A CNSet object.
...	Ignored

Value

not applicable

Author(s)

R. Scharpf

Examples

```
open(rnorm(15))
open(matrix(rnorm(15), 5, 3))
```

flags

Batch-level summary of SNP flags.

Description

Used to flag SNPs with low minor allele frequencies, or for possible problems during the CN estimation step. Currently, this is primarily more for internal use.

Usage

```
flags(object)
```

Arguments

object An object of class CNSet

Value

A `matrix` or `ff_matrix` object with rows corresponding to markers and columns corresponding to batch.

See Also

[batchStatistics](#)

Examples

```
x <- matrix(runif(250*96*2, 0, 2), 250, 96*2)
test1 <- new("CNSet", alleleA=x, alleleB=x, call=x, callProbability=x,
            batch=as.character(rep(letters[1:2], each=96)))
dim(flags(test1))
```

generics	<i>Miscellaneous generics. Methods defined in packages that depend on oligoClasses</i>
----------	--

Description

Miscellaneous generics. Methods defined in packages that depend on oligoClasses

Usage

```
baf(object)  
lrr(object)
```

Arguments

object A eSet-derived class.

Author(s)

R. Scharpf

GenomeAnnotatedDataFrame-class	<i>Class "GenomeAnnotatedDataFrame"</i>
--------------------------------	---

Description

AnnotatedDataFrame with genomic coordinates (chromosome, position)

Slots

```
varMetadata: Object of class "data.frame" ~~  
data: Object of class "data.frame" ~~  
dimLabels: Object of class "character" ~~  
.__classVersion__: Object of class "Versions" ~~
```

Extends

Class "[AnnotatedDataFrame](#)", directly. Class "[Versioned](#)", by class "AnnotatedDataFrame", distance 2.

Coercion to or from other classes

```
as(from, "GenomeAnnotatedDataFrame"):  
  Coerce an object of class AnnotatedDataFrame to a GenomeAnnotatedDataFrame.  
makeFeatureGRanges(object, genome, ...):  
  Construct a GRanges instance from a GenomeAnnotatedDataFrame object. genome is a character string indicating the UCSC build. Supported builds are "hg18" and "hg19", but are platform specific. In particular, some platforms only support build hg19 at this time.  
updateObject(object):  
  For updating a GenomeAnnotatedDataFrame
```

Accessors

`chromosome(object)`, `chromosome(object) <- value`
 Get or set chromosome.

`isSnp(object)`:
 Many platforms include polymorphic and nonpolymorphic markers. `isSnp` evaluates to TRUE if the marker is polymorphic.

`position(object)`:
 Physical position in the genome

`getArm(object, genome)`:
 Retrieve character vector indicating the chromosome arm of each marker in `object`. `genome` should indicate which genome build was used to define the chromosomal locations (currently, only UCSC genome builds 'hg18' and 'hg19' supported for this function).

Author(s)

R. Scharpf

GenomeAnnotatedDataFrameFrom-methods

Methods for Function `GenomeAnnotatedDataFrameFrom` in Package `oligoClasses`

Description

`GenomeAnnotatedDataFrameFrom` is a convenience for creating `GenomeAnnotatedDataFrame` objects.

Methods

Use the method with `GenomeAnnotatedDataFrameFrom(object, annotationPkg, genome, ...)`; the argument `annotationPkg` *must* be specified for `matrix` and `AssayData` classes.

`signature(object="assayData")` This method creates an `GenomeAnnotatedDataFrame` using feature names and dimensions of an `AssayData` object as a template.

`signature(object="matrix")` This method creates an `GenomeAnnotatedDataFrame` using row names and dimensions of a `matrix` object as a template.

`signature(object="NULL")` This method (called with 'NULL' as the object) creates an empty `GenomeAnnotatedDataFrame`.

`signature(object="array")` This method (called with 'array' as the object) creates a `GenomeAnnotatedDataFrame` using the first dimension of the array (rows are the number of features).

Author(s)

R Scharpf

Examples

```
require(Biobase)
minReqVersion <- "1.0.2"
require(human370v1cCrlmm)
if (packageDescription("human370v1cCrlmm", fields='Version') >= minReqVersion){
  x <- matrix(1:25, 5, 5,
              dimnames=list(c("rs10000092", "rs1000055", "rs100016", "rs10003241", "rs10004197"), NULL))
  gd <- GenomeAnnotatedDataFrameFrom(x, annotationPkg="human370v1cCrlmm",
                                       genome="hg18")
  pData(gd)
  chromosome(gd)
  position(gd)
}
```

genomeBuild

Genome Build Information

Description

Returns the genome build. This information comes from the annotation package and is given as an argument during the package creation process.

Usage

```
genomeBuild(object)
```

Arguments

object	Supported objects include PDInfo, FeatureSet, and any gSet-derived or eSetList-derived object.
--------	--

Value

character string

Note

Supported builds are UCSC genome builds are 'hg18' and 'hg19'.

Examples

```
showMethods("genomeBuild", where="package:oligoClasses")
```

geometry	<i>Array Geometry Information</i>
----------	-----------------------------------

Description

For a given array, `geometry` returns the physical geometry of it.

Usage

```
geometry(object)
```

Arguments

object	PDInfo or FeatureSet object
--------	-----------------------------

Examples

```
if (require(pd.mapping50k.xba240))
  geometry(pd.mapping50k.xba240)
```

getA	<i>Compute average log-intensities / log-ratios</i>
------	---

Description

Methods to compute average log-intensities and log-ratios across alleles, within strand.

Usage

```
getA(object)
getM(object)
A(object, ...)
B(object, ...)
```

Arguments

object	SnpQSet, SnpCnvQSet or TilingFeatureSet2 object.
...	arguments to be passed to <code>allele</code> - 'sense' and 'antisense' are valid values if the array is pre- <code>SNP_5.0</code>

Details

For SNP data, SNPRMA summarizes the SNP information into 4 quantities (log2-scale):

- `antisenseThetaA` antisense allele A. (Not applicable for Affymetrix 5.0 and 6.0 platforms.)
- `antisenseThetaB` antisense allele B. (Not applicable for Affymetrix 5.0 and 6.0 platforms.)
- `senseThetaA` sense allele A. (Not applicable for Affymetrix 5.0 and 6.0 platforms.)
- `senseThetaB` sense allele B. (Not applicable for Affymetrix 5.0 and 6.0 platforms.)
- `alleleAAffymetrix` 5.0 and 6.0 platforms

- alleleBAffymetrix 5.0 and 6.0 platforms

The average log-intensities are given by: $(\text{antisenseThetaA} + \text{antisenseThetaB})/2$ and $(\text{senseThetaA} + \text{senseThetaB})/2$

The average log-ratios are given by: $\text{antisenseThetaA} - \text{antisenseThetaB}$ and $\text{senseThetaA} - \text{senseThetaB}$.

For Tiling data, getM and getA return the log-ratio and average log-intensities computed across channels: $M = \log_2(\text{channel1}) - \log_2(\text{channel2})$ $A = (\log_2(\text{channel1}) + \log_2(\text{channel2}))/2$

When large data support is enabled with the ff package, the AssayData elements of an AlleleSet object can be ff_matrix or ffdf, in which case pointers to the ff object are stored in the assay data. The functions open and close can be used to open or close the connection, respectively.

Value

A 3-dimensional array (SNP's x Samples x Strand) with the requested measure, when the input SNP data (50K, 250K).

A 2-dimensional array (SNP's x Samples), when the input is from SNP 5.0 and SNP 6.0 arrays.

A 2-dimensional array if the input is from Tiling arrays.

See Also

[snprma](#)

getBar

Gets a bar of a given length.

Description

Gets a bar of a given length.

Usage

```
getBar(width =getOption("width"))
```

Arguments

width desired length of the bar.

Value

character string.

Author(s)

Benilton S Carvalho

Examples

```
message(getBar())
```

getSequenceLengths	<i>Load chromosome sequence lengths for UCSC genome build hg18 or hg19</i>
--------------------	--

Description

Load chromosome sequence lengths for UCSC genome build hg18 or hg19

Usage

```
getSequenceLengths(build)
```

Arguments

build	character string: "hg18" or "hg19"
-------	------------------------------------

Details

The chromosome sequence lengths for UCSC builds hg18 and hg19 were extracted from the packages `BSgenome.Hsapiens.UCSC.hg18` and `BSgenome.Hsapiens.UCSC.hg19`, respectively.

Value

Names integer vector of chromosome lengths.

Author(s)

R. Scharpf

Examples

```
getSequenceLengths("hg18")
getSequenceLengths("hg19")

if(require("GenomicRanges")){
  ## from GenomicRanges
  sl <- getSequenceLengths("hg18")[c("chr1", "chr2", "chr3")]
  gr <-
  GRanges(seqnames =
  Rle(c("chr1", "chr2", "chr1", "chr3"), c(1, 3, 2, 4)),
  ranges =
  IRanges(1:10, width = 10:1, names = head(letters,10)),
  strand =
  Rle(strand(c("-", "+", "*", "+", "-")),
  c(1, 2, 2, 3, 2)),
  score = 1:10,
  GC = seq(1, 0, length=10),
  seqlengths=sl)
  metadata(gr) <- list(genome="hg18")
  gr
  metadata(gr)
}
```

Description

Methods for GRanges objects

findOverlaps methods

`findOverlaps(query, subject, ...):`

Find the feature indices in `subject` that overlap the genomic intervals in `query`, where `query` is a GRanges object and `subject` is a gSet-derived object. Additional arguments to the `findOverlaps` method in the package **IRanges** can be passed through the `...` operator.

Accessors

`object` is an instance of the GRanges class.

`coverage2(object):`

For the GRanges and GRangesList objects returned by the hidden Markov model implemented in the "VanillaICE" package and the segmentation algorithm in the "MinimumDistance" package, the intervals are annotated by the number of probes (markers) for SNPs and nonpolymorphic regions. `coverage2` and `numberProbes` are convenient accessors for these annotations.

`genomeBuild(object):`

Accessor for the UCSC genome build.

`numberProbes(object):`

Integer vector indicating the number of probes (markers) for each range in `object`. Equivalent to `coverage2`.

`state(object):`

Accessor for the `elementMetadata` column 'state', when applicable. State is used to contain the index of the inferred copy number state for various `hmm` methods defined in the **VanillaICE**.

See Also

[GRanges](#)

Examples

```
library(IRanges)
library(GenomicRanges)
gr1 <- GRanges(seqnames = "chr2", ranges = IRanges(3, 6),
  state=3L, numberProbes=100L)
## convenience functions
state(gr1)
numberProbes(gr1)

gr2 <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(7,13), width = 3),
  state=c(2L, 2L), numberProbes=c(200L, 250L))
gr3 <- GRanges(seqnames = c("chr1", "chr2"),
  ranges = IRanges(c(1, 4), c(3, 9)),
```

```

state=c(1L, 4L), numberProbes=c(300L, 350L))
## Ranges organized by sample
gr1 <- GRangesList("sample1" = gr1, "sample2" = gr2, "sample3" = gr3)
sampleNames(gr1) ## same as names(gr1)
numberProbes(gr1)
chromosome(gr1)
state(gr1)
gr <- stack(gr1)
sampleNames(gr)
chromosome(gr)
state(gr)

```

gSet-class*Container for objects with genomic annotation on SNPs*

Description

Container for objects with genomic annotation on SNPs

Objects from the Class

A virtual Class: No objects may be created from it.

Slots

```

featureData: Object of class "GenomeAnnotatedDataFrame" ~~
assayData: Object of class "AssayData" ~~
phenoData: Object of class "AnnotatedDataFrame" ~~
experimentData: Object of class "MIAxE" ~~
annotation: Object of class "character" ~~
protocolData: Object of class "AnnotatedDataFrame" ~~
genome: Object of class "character" ~~
._classVersion_.: Object of class "Versions" ~~

```

Extends

Class "[eSet](#)", directly. Class "[VersionedBiobase](#)", by class "eSet", distance 2. Class "[Versioned](#)", by class "eSet", distance 3.

Methods

The object for the below methods is a class that extends the virtual class gSet.

`checkOrder(object)`: checks that the object is ordered by chromosome and physical position.
Returns logical.

`chromosome(object)`: accessor for chromosome in the GenomeAnnotatedDataFrame slot.

`chromosome(object) <- value`: replacement method for chromosome in the GenomeAnnotatedDataFrame slot. value must be an `integer` vector.

`db(object)`: database connection

```
genomeBuild(object), genomeBuild(object) <- value:  
  Get or set the UCSC genome build. Supported builds are hg18 and hg19.  
getArm(object): Character vector indicating the chromosomal arm for each marker in object.  
isSnp(object): whether the marker is polymorphic. Returns a logical vector.  
makeFeatureGRanges(object): Construct an instance of the GRanges class from a GenomeAnnotatedDataFrame.  
position(object): integer vector of the genomic position  
show(object):  
  Print a concise summary of object.
```

Author(s)

R. Scharpf

See Also

[chromosome](#), [position](#), [isSnp](#)

Examples

```
showClass("gSet")
```

gSetList-class *Virtual Class for Lists of eSets*

Description

Virtual Class for Lists of eSets.

Objects from the Class

A virtual Class: No objects may be created from it.

Slots

```
assayDataList: Object of class "AssayData" ~~  
phenoData: Object of class "AnnotatedDataFrame" ~~  
protocolData: Object of class "AnnotatedDataFrame" ~~  
experimentData: Object of class "MIAME" ~~  
featureDataList: Object of class "list" ~~  
chromosome: Object of class "vector" ~~  
annotation: Object of class "character" ~~  
genome: Object of class "character" ~~
```

Accessors

object is an instance of a gSetList-derived class.

annotation(object):

character string indicating the package used to provide annotation for the features on the array.

chromosome(object):

Returns the chromosome corresponding to each element in the gSetList object

elementNROWS(object): Returns the number of rows for each list of assays. In most gSetList-derived classes, the assays are organized by chromosome and elementNROWS returns the number of markers for each chromosome.

genomeBuild(object), genomeBuild(object) <- value:

Get or set the UCSC genome build. Supported builds are hg18 and hg19.

Coercion

object is an instance of a gSetList-derived class.

makeFeatureGRanges(object, ...):

Create a GRanges object for the featureData. The featureData is stored as a list. This method stacks the featureData from each list element. Metadata columns in the GRanges object include physical position ('position'), a SNP indicator ('isSnp'), and the chromosome. The genome build is extracted from object using the method genomeBuild.

Author(s)

R. Scharpf

See Also

[oligoSetList](#), [BeadStudioSetList](#)

Examples

`showClass("gSetList")`

i2p

Functions to convert probabilities to integers, or integers to probabilities.

Description

Probabilities estimated in the crlmm package are often stored as integers to save memory. We provide a few utility functions to go back and forth between the probability and integer representations.

Usage

`i2p(i)`
`p2i(p)`

Arguments

- i A matrix or vector of integers.
- p A matrix or vector of probabilities.

Value

The value returned by i2p is

$1 - \exp(-i/1000)$

The value returned by 2pi is

`as.integer(-1000*log(1-p))`

See Also

[conf](#)

Examples

```
i2p(693)
p2i(0.5)
i2p(p2i(0.5))
```

`initializeBigMatrix` *Initialize big matrices/vectors.*

Description

Initialize big matrices or vectors appropriately (conditioned on the status of support for large datasets - see Details).

Usage

```
initializeBigMatrix(name=basename(tempfile()), nr=0L, nc=0L, vmode = "integer", initdata = NA)
initializeBigVector(name=basename(tempfile()), n=0L, vmode = "integer",
  initdata = NA)
initializeBigArray(name=basename(tempfile()), dim=c(0L,0L,0L),
  vmode="integer", initdata=NA)
```

Arguments

- name prefix to be used for file stored on disk
- nr number of rows
- nc number of columns
- n length of the vector
- vmode mode - "integer", "double"
- initdata Default is NA
- dim Integer vector indicating the dimensions of the array to initialize

Details

These functions are meant to be used by developers. They provide means to appropriately create big vectors or matrices for packages like oligo and crlmm (and friends). These objects are created conditioned on the status of support for large datasets.

Value

If the 'ff' package is loaded (in the search path), then an 'ff' object is returned. A regular R vector or array is returned otherwise.

Examples

```
x <- initializeBigVector("test", 10)
class(x)
x
if (isPackageLoaded("ff"))
  finalizer(x) <- "delete"
rm(x)
initializeBigMatrix(nr=5L, nc=5L)
initializeBigArray(dim=c(10, 5, 3))
```

integerMatrix

Coerce numeric matrix (or array) to a matrix (array) of integers, retaining dimnames.

Description

Coerce numeric matrix to matrix of integers, retaining dimnames.

Usage

```
integerMatrix(x, scale = 100)
integerArray(x, scale=100)
```

Arguments

x	a matrix or array
scale	scalar (numeric). If not 1, x is multiplied by scale prior to coercing to a matrix of integers.

Value

A matrix or array of integers.

Author(s)

R. Scharpf

Examples

```
x <- matrix(rnorm(10), 5, 2)
rownames(x) = letters[1:5]
i <- integerMatrix(x, scale=100)
```

is.ffmatrix	<i>Check if object is an ff-matrix object.</i>
-------------	--

Description

Check if object is an ff-matrix object.

Usage

```
is.ffmatrix(object)
```

Arguments

object	object to be checked
--------	----------------------

Value

Logical.

Note

This function is meant to be used by developers.

Examples

```
if (isPackageLoaded("ff")){
  x1 <- ff(vmode="double", dim=c(10, 2))
  is.ffmatrix(x1)
}
x1 <- matrix(0, nr=10, nc=2)
is.ffmatrix(x1)
```

isPackageLoaded	<i>Check if package is loaded.</i>
-----------------	------------------------------------

Description

Checks if package is loaded.

Usage

```
isPackageLoaded(pkg)
```

Arguments

pkg	Package to be checked.
-----	------------------------

Details

Checks if package name is in the search path.

Value

Logical.

See Also

search

Examples

```
isPackageLoaded("oligoClasses")
isPackageLoaded("ff")
isPackageLoaded("snow")
```

isSnp-methods

Methods for Function isSnp in package oligoClasses~~

Description

~~ Methods for function **isSnp** in package **oligoClasses** ~~

Methods

Return an indicator for whether the marker is polymorphic (value 1) or nonpolymorphic (value 0).

Return an indicator for whether the vector of marker identifiers in **object** is polymorphic. **pkgname** must be one of the supported annotation packages specific to the platform.

```
signature(object = "character", pkgname = "character")signature(object = "eSet", pkgname = "ANY")
If 'isSnp' is included in fvarLabels(object), an indicator for polymorphic markers is returned. Otherwise, an error is thrown.
```

```
signature(object = "GenomeAnnotatedDataFrame", pkgname = "ANY") Accessor for indicator
of whether the marker is polymorphic. If annotation was not available due to a missing or non-
existent annotation package, the value returned by the accessor will be a vector of zero's.
```

kind

Array type

Description

Retrieves the array type.

Usage

```
kind(object)
```

Arguments

object	FeatureSet or DBPDInfo object
---------------	-------------------------------

Value

String: "Expression", "Exon", "SNP" or "Tiling"

Examples

```
if (require(pd.mapping50k.xba240)){
  data(sfsExample)
  Biobase::annotation(sfsExample) <- "pd.mapping50k.xba240"
  kind(sfsExample)
}
```

ldSetOptions

Set/check large dataset options.

Description

Set/check large dataset options.

Usage

```
ldSetOptions(nsamples=100, nprobesets=20000, path=getwd(), verbose=FALSE)
ldStatus(verbose=FALSE)
ldPath(path)
```

Arguments

nsamples	number of samples to be processed at once.
nprobesets	number of probesets to be processed at once.
path	path where to store large dataset objects.
verbose	verbosity (logical).

Details

Some functions in oligo/crlmm can process data in batches to minimize memory footprint. When using this feature, the 'ff' package resources are used (and possibly combined with cluster resources set in options() via 'snow' package).

Methods that are executed on a sample-by-sample manner can use ocSamples() to automatically define how many samples are processed at once (on a compute node). Similarly, methods applied to probesets can use ocProbesets(). Users should set these options appropriately.

ldStatus checks the support for large datasets.

ldPath checks where ff files are stored.

Author(s)

Benilton S Carvalho

See Also

ocSamples, ocProbesets

Examples

```
ldStatus(TRUE)
```

length-methods	<i>Number of samples for FeatureSet-like objects.</i>
----------------	---

Description

Number of samples for FeatureSet-like objects.

Methods

x = "FeatureSet" Number of samples

library2	<i>Supress package startup messages when loading a library</i>
----------	--

Description

Supress package startup messages when loading a library

Usage

```
library2(...)
```

Arguments

... arguments to library

Author(s)

R. Scharpf

See Also

[library](#)

Examples

```
library2("Biobase")
```

list.celfiles	<i>List CEL files.</i>
---------------	------------------------

Description

Function used to get a list of CEL files.

Usage

```
list.celfiles(..., listGzipped=FALSE)
```

Arguments

...	Passed to list.files
listGzipped	Logical. List .CEL.gz files?

Value

Character vector with filenames.

Note

Quite often users want to use this function to pass filenames to other methods. In this situations, it is safer to use the argument 'full.names=TRUE'.

See Also

[list.files](#)

Examples

```
if (require(hapmapsnp5)){
  path <- system.file("celFiles", package="hapmapsnp5")

  ## only the filenames
  list.celfiles(path)

  ## the filenames with full path...
  ## very useful when genotyping samples not in the working directory
  list.celfiles(path, full.names=TRUE)
} else{
  ## this won't return anything
  ## if in the working directory there isn't any CEL
  list.celfiles(getwd())
}
```

ListClasses	<i>eSetList class</i>
-------------	-----------------------

Description

Initialization method for eSetList virtual class.

locusLevelData	<i>Basic data elements required for the HMM</i>
----------------	---

Description

This object is a list containing the basic data elements required for the HMM

Usage

```
data(locusLevelData)
```

Format

A list

Details

The basic assay data elements that can be used for fitting the HMM are:

1. a mapping of platform identifiers to chromosome and physical position
2. (optional) a matrix of copy number estimates
3. (optional) a matrix of confidence scores for the copy number estimates (e.g., inverse standard deviations)
4. (optional) a matrix of genotype calls
5. (optional) CRLMM confidence scores for the genotype calls

At least (2) or (4) is required. The locusLevelData is a list that contains (1), (2), (4), and (5).

Source

A HapMap sample on the Affymetrix 50k platform. Chromosomal alterations were simulated. The last 100 SNPs on chromosome 2 are, in fact, a repeat of the first 100 SNPs on chromosome 1 – this was added for internal use.

Examples

```
data(locusLevelData)
str(locusLevelData)
```

makeFeatureGRanges	<i>Construct a GRanges object from several possible feature-level classes</i>
--------------------	---

Description

Construct a GRanges object from several possible feature-level classes. The conversion is useful for subsequent ranged-data queries, such as `findOverlaps`, `countOverlaps`, etc.

Usage

```
makeFeatureGRanges(object, ...)
```

Arguments

object A gSet-derived object containing chromosome and physical position for the markers on the array.

... See the `makeFeatureGRanges` method for `GenomeAnnotatedDataFrame`.

Value

A GRanges object.

Author(s)

R. Scharpf

See Also

[findOverlaps](#), [GRanges](#), [GenomeAnnotatedDataFrame](#)

Examples

```
library(oligoClasses)
library(GenomicRanges)
library(BioBase)
library(foreach)
registerDoseQ()
data(oligoSetExample, package="oligoClasses")
oligoSet <- oligoSet[chromosome(oligoSet) == 1, ]
makeFeatureGRanges(oligoSet)
```

manufacturer-methods *Manufacturer ID for FeatureSet-like objects.*

Description

Manufacturer ID for FeatureSet-like and DBPDInfo-like objects.

Methods

object = "FeatureSet" Manufacturer ID

object = "PDInfo" Manufacturer ID

ocLapply	<i>lapply-like function that parallelizes code when possible.</i>
----------	---

Description

ocLapply is an lapply-like function that checks if ff/snow are loaded and if the cluster variable is set to execute FUN on a cluster. If these requirements are not available, then lapply is used.

Usage

```
ocLapply(X, FUN, ..., neededPkgs)
```

Arguments

X	first argument to FUN.
FUN	function to be executed.
...	additional arguments to FUN.
neededPkgs	packages needed to execute FUN on the compute nodes.

Details

neededPkgs is needed when parallel computing is expected to be used. These packages are loaded on the compute nodes before the execution of FUN.

Value

A list of length length(X).

Author(s)

Benilton S Carvalho

See Also

`lapply`, `parStatus`

ocSamples	<i>Cluster and large dataset management utilities.</i>
-----------	--

Description

Tools to simplify management of clusters via 'snow' package and large dataset handling through the 'bigmemory' package.

Usage

```
ocSamples(n)
ocProbesets(n)
```

Arguments

n integer representing the maximum number of samples/probesets to be processed simultaneously on a compute node.

Details

Some methods in the oligo/crlmm packages, like `backgroundCorrect`, `normalize`, `summarize` and `rma` can use a cluster (set through the `'foreach'` package). The use of cluster features is conditioned on the availability of the `'ff'` (used to provide shared objects across compute nodes) and `'foreach'` packages.

To use a cluster, `'oligo/crlmm'` checks for three requirements: 1) `'ff'` is loaded; 2) an adaptor for the parallel backend (like `'doMPI'`, `'doSNOW'`, `'doMC'`) is loaded and registered.

If only the `'ff'` package is available and loaded (in addition to the caller package - `'oligo'` or `'crlmm'`), these methods will allow the user to analyze datasets that would not fit in RAM at the expense of performance.

In the situations above (large datasets and cluster), `oligo/crlmm` uses the options `ocSamples` and `ocProbesets` to limit the amount of RAM used by the machine(s). For example, if `ocSamples` is set to 100, steps like background correction and normalization process (in RAM) 100 samples simultaneously on each compute node. If `ocProbesets` is set to 10K, then summarization processes 10K probesets at a time on each machine.

Warning

In both scenarios (large dataset and/or cluster use), there is a penalty in performance because data are written to disk (to either minimize memory footprint or share data across compute nodes).

Author(s)

Benilton Carvalho

Examples

```
if(require(doMC)) {  
  registerDoMC()  
  ## tasks like summarize()  
}
```

oligoSet

An example instance of oligoSnpSet class

Description

An example instance of the `oligoSnpSet` class

Usage

```
data(oligoSetExample)
```

Source

Created from the simulated `locusLevelData` provided in this package.

See Also[locusLevelData](#)**Examples**

```
## Not run:
## 'oligoSetExample' created by the following
data(locusLevelData)
oligoSet <- new("oligoSnpSet",
  copyNumber=integerMatrix(log2(locusLevelData[["copynumber"]]/100), 100),
  call=locusLevelData[["genotypes"]],
  callProbability=locusLevelData[["crlmmConfidence"]],
  annotation=locusLevelData[["platform"]],
  genome="hg19")
oligoSet <- oligoSet[!is.na(chromosome(oligoSet)), ]
oligoSet <- oligoSet[chromosome(oligoSet) < 3, ]

## End(Not run)
data(oligoSetExample)
oligoSet
```

oligoSnpSet-methods *Methods for oligoSnpSet class*

Description

Methods for oligoSnpSet class

Methods

In the following code, `object` is an instance of the `oligoSnpSet` class.

`new("oligoSnpSet", ...)`: Instantiates an object of class `oligoSnpSet`. The `assayData` elements of the `oligoSnpSet` class can include matrices of genotype calls, confidence scores for the genotype calls, B allele frequencies, absolute or relative copy number, and confidence scores for the copy number estimates. Each matrix should be coerced to an integer scale prior to assignment to the `oligoSnpSet` object. Validity methods defined for the class will fail if the matrices are not integers. See examples for additional details.

`baf(object)`: Accessor for integer representation of the B allele frequencies. The value returned by this method can be divided by 1000 to obtain B allele frequencies on the original [0,1] scale.

`baf(object) <- value`: Assign an integer representation of the B allele frequencies to the 'baf' element of the `assayData` slot. `value` must be a matrix of integers. See the examples for help converting BAFs to a matrix of integers.

parStatus*Checks if oligo/crlmm can use parallel resources.*

Description

Checks if oligo/crlmm can use parallel resources (needs ff and snow package, in addition to options(cluster=makeCluster(...))).

Usage

```
parStatus()
```

Value

logical

Author(s)

Benilton S Carvalho

pdPkgFromBioC*Get packages from BioConductor.*

Description

This function checks if a given package is available on BioConductor and installs it, in case it is.

Usage

```
pdPkgFromBioC(pkgname, lib = .libPaths()[1], verbose = TRUE)
```

Arguments

pkgname	character. Name of the package to be installed.
lib	character. Path where to install the package at.
verbose	logical. Verbosity flag.

Details

Internet connection required.

Value

Logical: TRUE if package was found, downloaded and installed; FALSE otherwise.

Author(s)

Benilton Carvalho

See Also

download.packages

Examples

```
## Not run:  
pdPkgFromBioC("pd.mapping50k.xba240")  
## End(Not run)
```

platform-methods *Platform Information*

Description

Platform Information

Methods

object = "FeatureSet" platform information

pmFragmentLength-methods
Information on Fragment Length

Description

This method will return the fragment length for PM probes.

Methods

object = "AffySNPPDInfo" On AffySNPPDInfo objects, it will return the fragment length that contains the SNP in question.

Description

Methods for function **position** in package **oligoClasses**

Methods

The methods for **position** extracts the physical position stored as an integer for each marker in a **eSet**-derived class or a **AnnotatedDataFrame**-derived class.

signature(object = "AnnotatedDataFrame") Accessor for physical position.

signature(object = "eSet") If 'position' is included in **fvarLabels(object)**, the physical position will be returned. Otherwise, an error is thrown.

signature(object = "GenomeAnnotatedDataFrame") Accessor for physical position. If annotation was not available due to a missing or non-existent annotation package, the value returned by the accessor will be a vector of zero's.

Description

This function checkes the existence of a given package and loads it if available. If the package is not available, the function checks its availability on BioConductor, downloads it and installs it.

Usage

```
requireAnnotation(pkgname, lib=.libPaths()[1], verbose = TRUE)
```

Arguments

pkgname	character. Package name (usually an annotation package).
lib	character. Path where to install packages at.
verbose	logical. Verbosity flag.

Value

Logical: TRUE if package is available or FALSE if package unavailable for download.

Author(s)

Benilton Carvalho

See Also

`install.packages`

Examples

```
## Not run:
requirePackage("pd.mapping50k.xba240")

## End(Not run)
```

requireClusterPkgSet *DEPRECATED FUNCTIONS. Package loaders for clusters.*

Description

Package loaders for clusters.

Usage

```
requireClusterPkgSet(packages)
requireClusterPkg(pkg, character.only)
```

Arguments

packages	character vector with the names of the packages to be loaded on the compute nodes.
pkg	name of a package given as a name or literal character string
character.only	a logical indicating whether ‘pkg’ can be assumed to be a character string

Details

requireClusterPkgSet applies require for a set of packages on the cluster nodes.

requireClusterPkg applies require for **ONE** package on the cluster nodes and accepts every argument taken by require.

Value

Logical.

Author(s)

Benilton S Carvalho

See Also

require

sampleNames-methods *Sample names for FeatureSet-like objects*

Description

Returns sample names for FeatureSet-like objects.

Methods

object = "FeatureSet" Sample names

scqsExample *SnpCnvQSet Example*

Description

Example of SnpCnvQSet object.

Usage

```
data(scqsExample)
```

Format

Object belongs to SnpCnvQSet class.

Examples

```
data(scqsExample)
class(scqsExample)
```

setCluster *DEPRECATED FUNCTIONS. Cluster and large dataset management utilities.*

Description

Tools to simplify management of clusters via 'snow' package and large dataset handling through the 'bigmemory' package.

Usage

```
setCluster(...)
getCluster()
delCluster()
```

Arguments

... arguments to be passed to `makeCluster` in the 'snow' package.

Details

Some methods in the oligo/crlmm packages, like `backgroundCorrect`, `normalize`, `summarize` and `rma` can use a cluster (set through 'snow' package). The use of cluster features is conditioned on the availability of the 'bigmemory' (used to provide shared objects across compute nodes) and 'snow' packages.

To use a cluster, 'oligo/crlmm' checks for three requirements: 1) 'ff' is loaded; 2) 'snow' is loaded; and 3) the 'cluster' option is set (e.g., via `options(cluster=makeCluster(...))` or `setCluster(...)`).

If only the 'ff' package is available and loaded (in addition to the caller package - 'oligo' or 'crlmm'), these methods will allow the user to analyze datasets that would not fit in RAM at the expense of performance.

In the situations above (large datasets and cluster), oligo/crlmm uses the options `ocSamples` and `ocProbesets` to limit the amount of RAM used by the machine(s). For example, if `ocSamples` is set to 100, steps like background correction and normalization process (in RAM) 100 samples simultaneously on each compute node. If `ocProbesets` is set to 10K, then summarization processes 10K probesets at a time on each machine.

Warning

In both scenarios (large dataset and/or cluster use), there is a penalty in performance because data are written to disk (to either minimize memory footprint or share data across compute nodes).

Author(s)

Benilton Carvalho

sfsExample

SnpFeatureSet Example

Description

Example of `SnpFeatureSet` object.

Usage

`data(sfsExample)`

Format

Object belongs to `SnpFeatureSet` class

Examples

`data(sfsExample)`
`class(sfsExample)`

Description

Utility functions for accessing data in SnpSet objects.

Usage

```
calls(object)
calls(object) <- value
confS(object, transform=TRUE)
confS(object) <- value
```

Arguments

object	A SnpSet object.
transform	Logical. Whether to transform the integer representation of the confidence score (for memory efficiency) to a probability. See details.
value	A matrix.

Details

`calls` returns the genotype calls. CRLMM stores genotype calls as integers (1 - AA; 2 - AB; 3 - BB).

`confS` returns the confidences associated with the genotype calls. The current implementation of CRLMM stores the confidences as integers to save memory on disk by using the transformation:
`round(-1000*log2(1-p))`,

where '`p`' is the posterior probability of the call. `confS` is a convenience function that transforms the integer representation back to a probability. Note that if the `assayData` elements of the `SnpSet` objects are `ff_matrix` or `ffdf`, the `confS` function will return a warning. For such objects, one should first subset the `ff` object and coerce to a matrix, then apply the above conversion. The function `snpCallProbability` for the `callProbability` slot of `SnpSet` objects. See the examples below.

`checkOrder` checks whether the object is ordered by chromosome and physical position, evaluating to `TRUE` or `FALSE`.

Note

Note that the replacement method for `confS<-` expects a matrix of probabilities and will automatically convert the probabilities to an integer representation. See details for the conversion.

The accessor `snpCallProbability` is an accessor for the '`callProbability`' element of the `assayData`. The name can be misleading, however, as the accessor will not return a probability if the call probabilities are represented as integers.

See Also

The helper functions `p2i` converts probabilities to integers and `i2p` converts integers to probabilities.

See `order` and `checkOrder`.

Examples

```
theCalls <- matrix(sample(1:3, 20, rep=TRUE), nc=2)
p <- matrix(runif(20), nc=2)
integerRepresentation <- matrix(as.integer(round(-1000*log(1-p)))), 10, 2)
obj <- new("SnpSet2", call=theCalls, callProbability=integerRepresentation)
calls(obj)
  confs(obj)  ## coerces to probability scale
  int <- Biobase::snpCallProbability(obj) ## not necessarily a probability
  p3 <- i2p(int) ## to convert back to a probability
```

SnpSet2-class

Class "SnpSet2"

Description

A container for genotype calls and confidence scores. Similar to the SnpSet class in **Biobase**, but SnpSet2 extends gSet directly whereas SnpSet extends eSet. Useful properties of gSet include the genome slot and the GenomeAnnotatedDataFrame.

Objects from the Class

Objects can be created by calls of the form `new("SnpSet2", assayData, phenoData, featureData, experimentData, annotation, protocolData, call, callProbability, genome, ...)`.

Slots

genome: Object of class "character" indicating the UCSC genome build. Supported builds are 'hg18' and 'hg19'.
assayData: Object of class "AssayData".
phenoData: Object of class "AnnotatedDataFrame".
featureData: Object of class "AnnotatedDataFrame".
experimentData: Object of class "MIAxE".
annotation: Object of class "character" ~~
protocolData: Object of class "AnnotatedDataFrame" ~~
__classVersion__: Object of class "Versions" ~~

Extends

Class "[gSet](#)", directly. Class "[eSet](#)", by class "gSet", distance 2. Class "[VersionedBiobase](#)", by class "gSet", distance 3. Class "[Versioned](#)", by class "gSet", distance 4.

Accessors

The argument `object` for the following methods is an instance of the SnpSet2 class.

calls(object): `calls(object) <- value`:
 Gets or sets the genotype calls. `value` can be a `matrix` or a `ff_matrix`.
confs(object): `confs(object) <- value`:
 Gets or sets the genotype confidence scores. `value` can be a `matrix` or a `ff_matrix`.
snpCall(object): `snpCallProbability(object) <- value`:
 Gets or sets the genotype confidence scores.

Author(s)

R. Scharpf

See Also

[SnpSet](#)

Examples

```
showClass("SnpSet2")
new("SnpSet2")
```

SnpSuperSet-class *Class "SnpSuperSet"*

Description

A class to store locus-level summaries of the quantile normalized intensities, genotype calls, and genotype confidence scores

Objects from the Class

```
new("SnpSuperSet", allelea=alleleA, alleleB=alleleB, call=call, callProbability, ...).
```

Slots

```
assayData: Object of class "AssayData" ~~
phenoData: Object of class "AnnotatedDataFrame" ~~
featureData: Object of class "AnnotatedDataFrame" ~~
experimentData: Object of class "MIAME" ~~
annotation: Object of class "character" ~~
protocolData: Object of class "AnnotatedDataFrame" ~~
._classVersion_.: Object of class "Versions" ~~
```

Extends

Class "[AlleleSet](#)", directly. Class "[SnpSet](#)", directly. Class "[eSet](#)", by class "AlleleSet", distance 2. Class "[VersionedBiobase](#)", by class "AlleleSet", distance 3. Class "[Versioned](#)", by class "AlleleSet", distance 4.

Methods

No methods defined with class "SnpSuperSet" in the signature.

Author(s)

R. Scharpf

See Also

[AlleleSet](#)

Examples

```
showClass("SnpSuperSet")
## empty object from the class
x <- new("matrix")
new("SnpSuperSet", alleleA=x, alleleB=x, call=x, callProbability=x)
```

splitIndicesByLength *Tools to distribute objects across nodes or by length.*

Description

Tools to distribute objects across nodes or by length.

Usage

```
splitIndicesByLength(x, lg, balance=FALSE)
splitIndicesByNode(x)
```

Arguments

x	object to be split
lg	length
balance	logical. Currently ignored

Details

`splitIndicesByLength` splits `x` in groups of length `lg`.

`splitIndicesByNode` splits `x` in `N` groups (where `N` is the number of compute nodes available).

Value

List.

Author(s)

Benilton S Carvalho

See Also

`split`

Examples

```
x <- 1:100
splitIndicesByLength(x, 8)
splitIndicesByLength(x, 8, balance=TRUE)
splitIndicesByNode(x)
```

sqExample

SnpQSet Example

Description

Example of SnpQSet instance.

Usage

```
data(sqExample)
```

Format

Belongs to SnpQSet class.

Examples

```
data(sqExample)
class(sqExample)
```

SummarizedExperiment-methods

Methods for RangedSummarizedExperiment objects

Description

Methods for RangedSummarizedExperiment.

Usage

```
## S4 method for signature 'RangedSummarizedExperiment'
baf(object)
## S4 method for signature 'RangedSummarizedExperiment'
chromosome(object,...)
## S4 method for signature 'RangedSummarizedExperiment'
isSnp(object, ...)
## S4 method for signature 'RangedSummarizedExperiment'
lrr(object)
```

Arguments

object	A RangedSummarizedExperiment object.
...	ignored

Details

`baf` and `lrr` are accessors for the B allele frequencies and log R ratio assays (matrices or arrays), respectively,

`chromosome` returns the seqnames of the `rowRanges`.

`isSnp` returns a logical vector for each marker in `rowRanges` indicating whether the marker targets a SNP (nonpolymorphic regions are FALSE).

See Also

[RangedSummarizedExperiment](#)

Index

- * **IO**
 - list.celfiles, 43
- * **attribute**
 - getSequenceLengths, 32
- * **classes**
 - AlleleSet-class, 4
 - AssayData-methods, 5
 - BeadStudioSet-class, 9
 - BeadStudioSetList-class, 10
 - CNSet-class, 15
 - CopyNumberSet-class, 17
 - DBPDIInfo-class, 21
 - FeatureSet-class, 23
 - ff_matrix-class, 24
 - ff_or_matrix-class, 25
 - ffdf-class, 24
 - gSet-class, 34
 - gSetList-class, 35
 - ListClasses, 43
 - SnpSet2-class, 56
 - SnpSuperSet-class, 57
- * **datasets**
 - efsExample, 22
 - locusLevelData, 44
 - oligoSet, 47
 - scqsExample, 53
 - sfsExample, 54
 - sqsExample, 59
- * **data**
 - pdPkgFromBioC, 49
 - requireAnnotation, 51
- * **internal**
 - Deprecated, 21
- * **list**
 - affyPlatforms, 3
- * **manip**
 - AssayDataList, 6
 - assayDataList-methods, 7
 - batchStatistics, 8
 - celfileDate, 11
 - celfileName, 11
 - checkExists, 12
 - checkOrder, 13
- chromosome2integer, 15
- CopyNumberSet-methods, 18
- createFF, 20
- featureDataList-methods, 22
- fileConnections, 25
- flags, 26
- genomeBuild, 29
- geometry, 30
- getA, 30
- getBar, 31
- i2p, 36
- initializeBigMatrix, 37
- integerMatrix, 38
- is.ffdmatrix, 39
- isPackageLoaded, 39
- kind, 40
- ldSetOptions, 41
- library2, 42
- makeFeatureGRanges, 44
- ocApply, 46
- ocSamples, 46
- parStatus, 49
- requireClusterPkgSet, 52
- setCluster, 53
- SnpSet-methods, 55
- splitIndicesByLength, 58
- * **methods**
 - assayDataList-methods, 7
 - batch, 7
 - batchStatistics, 8
 - chromosome-methods, 14
 - CopyNumberSet-methods, 18
 - db, 20
 - exprs-methods, 22
 - featureDataList-methods, 22
 - flags, 26
 - GenomeAnnotatedDataFrameFrom-methods, 28
 - GRanges-methods, 33
 - isSnp-methods, 40
 - length-methods, 42
 - manufacturer-methods, 45
 - oligoSnpSet-methods, 48

platform-methods, 50
 pmFragmentLength-methods, 50
 position-methods, 51
 sampleNames-methods, 53
 SummarizedExperiment-methods, 59
*** misc**
 affyPlatforms, 3
 generics, 27
*** utilities**
 list.celfiles, 43
 [,CNSet,ANY-method (CNSet-class), 15
 [,CNSet-method (CNSet-class), 15
 [,gSetList,ANY-method (gSetList-class), 35
 [,gSetList-method (gSetList-class), 35
 [[,BafLrrSetList,ANY,ANY-method
 (BeadStudioSetList-class), 10
 [[,BeadStudioSetList,ANY,ANY-method
 (BeadStudioSetList-class), 10
 [[<-,BafLrrSetList,ANY,ANY,BafLrrSet-method
 (BeadStudioSetList-class), 10
 [[<-,gSetList,ANY,ANY,BafLrrSet-method
 (gSetList-class), 35
 \$,gSetList-method (gSetList-class), 35
 \$<-,gSetList-method (gSetList-class), 35

 A (getA), 30
 A,AlleleSet-method (getA), 30
 A,CNSet-method (CNSet-class), 15
 A<- (getA), 30
 A<-,AlleleSet,matrix-method (getA), 30
 A<-,AlleleSet-method (getA), 30
 A<-,CNSet-method (CNSet-class), 15
 AffyExonPDInfo (DBPDInfo-class), 21
 AffyExonPDInfo-class (DBPDInfo-class), 21
 AffyExpressionPDInfo (DBPDInfo-class), 21
 AffyExpressionPDInfo-class
 (DBPDInfo-class), 21
 AffyGenePDInfo (DBPDInfo-class), 21
 AffyGenePDInfo-class (DBPDInfo-class), 21
 affyPlatforms, 3
 AffySNPCNVPDInfo (DBPDInfo-class), 21
 AffySNPCNVPDInfo-class
 (DBPDInfo-class), 21
 AffySNPPDInfo (DBPDInfo-class), 21
 AffySNPPDInfo-class (DBPDInfo-class), 21
 AffySTPDInfo (DBPDInfo-class), 21
 AffySTPDInfo-class (DBPDInfo-class), 21
 AffyTilingPDInfo (DBPDInfo-class), 21

 AffyTilingPDInfo-class
 (DBPDInfo-class), 21
 allele (AlleleSet-class), 4
 allele,AlleleSet-method
 (AlleleSet-class), 4
 allele,CNSet-method (CNSet-class), 15
 allele,SnpFeatureSet-method
 (AlleleSet-class), 4
 AlleleSet, 57
 AlleleSet (AlleleSet-class), 4
 AlleleSet-class, 4
 AnnotatedDataFrame, 27
 annotatedDataFrameFrom,ff_matrix-method
 (ff_matrix-class), 24
 annotation,DBPDInfo-method
 (DBPDInfo-class), 21
 annotation,gSetList-method
 (gSetList-class), 35
 annotationPackages, 5
 AssayData, 28
 AssayData-methods, 5
 AssayDataList, 6
 assayDataList (assayDataList-methods), 7
 assayDataList,gSetList-method
 (gSetList-class), 35
 assayDataList,oligoSetList-method
 (assayDataList-methods), 7
 assayDataList-methods, 7
 assayDataNew, 7

 B (getA), 30
 B,AlleleSet-method (getA), 30
 B,CNSet-method (CNSet-class), 15
 B<- (getA), 30
 B<-,AlleleSet,matrix-method (getA), 30
 B<-,AlleleSet-method (getA), 30
 B<-,CNSet-method (CNSet-class), 15
 baf (generics), 27
 baf,BafLrrSetList-method
 (BeadStudioSetList-class), 10
 baf,BeadStudioSet-method
 (BeadStudioSet-class), 9
 baf,BeadStudioSetList-method
 (BeadStudioSetList-class), 10
 baf,oligoSetList-method
 (BeadStudioSetList-class), 10
 baf,oligoSnpSet-method
 (oligoSnpSet-methods), 48
 baf,RangedSummarizedExperiment-method
 (SummarizedExperiment-methods), 59
 baf,SummarizedExperiment-method
 (SummarizedExperiment-methods),

59
baf<- (BeadStudioSet-class), 9
baf<-, BeadStudioSet-method
 (BeadStudioSet-class), 9
baf<-, oligoSnpSet-method
 (oligoSnpSet-methods), 48
BafLrrSet-class (BeadStudioSet-class), 9
BafLrrSetList-class
 (BeadStudioSetList-class), 10
batch, 7, 8
batch, CNSet-method (CNSet-class), 15
batchNames, 8
batchNames (batch), 7
batchNames, AssayData-method
 (AssayData-methods), 5
batchNames, CNSet-method (CNSet-class),
 15
batchNames<- (batch), 7
batchNames<-, AssayData-method
 (AssayData-methods), 5
batchNames<-, CNSet-method
 (CNSet-class), 15
batchStatistics, 8, 26
batchStatistics, CNSet-method
 (CNSet-class), 15
batchStatistics<- (batchStatistics), 8
batchStatistics<-, CNSet, AssayData-method
 (CNSet-class), 15
BeadStudioSet (BeadStudioSet-class), 9
BeadStudioSet-class, 9
BeadStudioSetList, 36
BeadStudioSetList-class, 10
bothStrands (AlleleSet-class), 4
bothStrands, AlleleSet-method
 (AlleleSet-class), 4
bothStrands, SnpFeatureSet-method
 (AlleleSet-class), 4

calls (SnpSet-methods), 55
calls, CNSet-method (CNSet-class), 15
calls, oligoSetList-method
 (BeadStudioSetList-class), 10
calls, oligoSnpSet-method
 (oligoSnpSet-methods), 48
calls, SnpSet-method (SnpSet-methods), 55
calls, SnpSet2-method (SnpSet2-class), 56
calls<- (SnpSet-methods), 55
calls<-, CNSet, matrix-method
 (CNSet-class), 15
calls<-, oligoSnpSet, matrix-method
 (oligoSnpSet-methods), 48
calls<-, SnpSet, matrix-method
 (SnpSet-methods), 55

calls<-, SnpSet2, matrix-method
 (SnpSet2-class), 56
callsConfidence, oligoSnpSet-method
 (oligoSnpSet-methods), 48
callsConfidence<-, oligoSnpSet, matrix-method
 (oligoSnpSet-methods), 48
celfileDate, 11
celfileName, 11
checkExists, 12
checkOrder, 13, 55
checkOrder, CopyNumberSet-method
 (CopyNumberSet-class), 17
checkOrder, gSet-method (gSet-class), 34
checkOrder, SnpSet-method
 (SnpSet-methods), 55
chromosome, 35
chromosome (chromosome-methods), 14
chromosome, AnnotatedDataFrame-method
 (chromosome-methods), 14
chromosome, GenomeAnnotatedDataFrame-method
 (chromosome-methods), 14
chromosome, GRanges-method
 (chromosome-methods), 14
chromosome, GRangesList-method
 (chromosome-methods), 14
chromosome, gSet-method
 (chromosome-methods), 14
chromosome, gSetList-method
 (gSetList-class), 35
chromosome, RangedDataCNV-method
 (Deprecated), 21
chromosome, RangedSummarizedExperiment-method
 (SummarizedExperiment-methods),
 59
chromosome, SnpSet-method
 (chromosome-methods), 14
chromosome, SummarizedExperiment-method
 (SummarizedExperiment-methods),
 59
chromosome-methods, 14
chromosome2integer, 14, 15
chromosome<- (chromosome-methods), 14
chromosome<-, GenomeAnnotatedDataFrame, integer-method
 (chromosome-methods), 14
chromosome<-, gSet, integer-method
 (chromosome-methods), 14
chromosome<-, SnpSet, integer-method
 (chromosome-methods), 14
chromosomePositionOrder (checkOrder), 13
clone2 (BeadStudioSetList-class), 10
clone2, BaflrrSetList-method
 (BeadStudioSetList-class), 10

close (fileConnections), 25
 close, AlleleSet-method (getA), 30
 close, array-method (fileConnections), 25
 close, CNSet-method (CNSet-class), 15
 close, matrix-method (fileConnections), 25
 close, numeric-method (fileConnections), 25
 closeff (fileConnections), 25
 closeff, CNSet-method (fileConnections), 25
 cnConfidence (CopyNumberSet-methods), 18
 cnConfidence, CopyNumberSet-method (CopyNumberSet-class), 17
 cnConfidence, oligoSnpSet-method (oligoSnpSet-methods), 48
 cnConfidence<- (CopyNumberSet-methods), 18
 cnConfidence<-, CopyNumberSet, matrix-method (CopyNumberSet-class), 17
 cnConfidence<-, oligoSnpSet, matrix-method (oligoSnpSet-methods), 48
 CNSet, 5
 CNSet (CNSet-class), 15
 CNSet-class, 15
 coerce, AnnotatedDataFrame, GenomeAnnotatedDataFrame (GenomeAnnotatedDataFrame-class), 27
 coerce, BeadStudioSet, data.frame-method (BeadStudioSet-class), 9
 coerce, CNSet, CopyNumberSet-method (CNSet-class), 15
 coerce, CNSet, oligoSnpSet (CNSet-class), 15
 coerce, CNSet, oligoSnpSet-method (CNSet-class), 15
 coerce, CNSetLM, CNSet-method (CNSet-class), 15
 coerce, gSetList, list-method (gSetList-class), 35
 coerce, oligoSnpSet, data.frame-method (oligoSnpSet-methods), 48
 confs, 37
 confs (SnpSet-methods), 55
 confs, CNSet-method (CNSet-class), 15
 confs, SnpSet-method (SnpSet-methods), 55
 confs, SnpSet2-method (SnpSet2-class), 56
 confs<- (SnpSet-methods), 55
 confs<-, CNSet, matrix-method (CNSet-class), 15
 confs<-, SnpSet, matrix-method (SnpSet-methods), 55
 confs<-, SnpSet2, matrix-method (SnpSet2-class), 56
 copyNumber (CopyNumberSet-methods), 18
 copyNumber, BeadStudioSet-method (BeadStudioSet-class), 9
 copyNumber, CopyNumberSet-method (CopyNumberSet-class), 17
 copyNumber, oligoSetList-method (BeadStudioSetList-class), 10
 copyNumber, oligoSnpSet-method (oligoSnpSet-methods), 48
 copyNumber<- (CopyNumberSet-methods), 18
 copyNumber<-, BeadStudioSet, ANY-method (BeadStudioSet-class), 9
 copyNumber<-, CopyNumberSet, matrix-method (CopyNumberSet-class), 17
 copyNumber<-, oligoSnpSet, matrix-method (oligoSnpSet-methods), 48
 CopyNumberSet (CopyNumberSet-class), 17
 CopyNumberSet-class, 17
 CopyNumberSet-methods, 18
 corr (AssayData-methods), 5
 corr, CNSet, character-method (CNSet-class), 15
 coverage2 (GRanges-methods), 33
 coverage2, GRanges-method (GRanges-methods), 33
 coverage2, GRangesList-method (GRanges-methods), 33
 coverage2, RangedDataCNV-method (Deprecated), 21
 createFF, 20
 db, 20
 db, AlleleSet-method (AlleleSet-class), 4
 db, DBPDIInfo-method (db), 20
 db, FeatureSet-method (db), 20
 db, gSet-method (gSet-class), 34
 db, SnpCnvQSet-method (db), 20
 db, SnpQSet-method (db), 20
 db, SnpSet-method (db), 20
 db-methods (db), 20
 DBPDIInfo (DBPDIInfo-class), 21
 DBPDIInfo-class, 21
 delCluster (setCluster), 53
 delCluster-deprecated (setCluster), 53
 Deprecated, 21
 dims, gSetList-method (gSetList-class), 35
 efsExample, 22
 elementNROWS, gSetList-method (gSetList-class), 35

eSet, 4, 9, 17, 23, 34, 56, 57
ExonFeatureSet (FeatureSet-class), 23
ExonFeatureSet-class
 (FeatureSet-class), 23
ExpressionFeatureSet
 (FeatureSet-class), 23
ExpressionFeatureSet-class
 (FeatureSet-class), 23
ExpressionPDInfo (DBPDInfo-class), 21
ExpressionPDInfo-class
 (DBPDInfo-class), 21
exprs, FeatureSet-method
 (exprs-methods), 22
exprs, SnpSet2-method (SnpSet2-class), 56
exprs-methods, 22

featureDataList
 (featureDataList-methods), 22
featureDataList, gSetList-method
 (gSetList-class), 35
featureDataList-methods, 22
FeatureSet (FeatureSet-class), 23
FeatureSet-class, 23
featuresInRange (Deprecated), 21
featuresInRange, SnpSet2, RangedDataCNV-method
 (Deprecated), 21
ff, 25
ff_matrix-class, 24
ff_or_matrix-class, 25
ffdf, 25
ffdf-class, 24
fileConnections, 25
findOverlaps, 45
findOverlaps, AnnotatedDataFrame, RangedDataCNV-method
 (Deprecated), 21
findOverlaps, GRanges, gSet-method
 (GRanges-methods), 33
findOverlaps, GRangesList, gSet-method
 (GRanges-methods), 33
findOverlaps, RangedDataCNV, AnnotatedDataFrame-method
 (Deprecated), 21
findOverlaps, RangedDataCNV, CNSet-method
 (Deprecated), 21
findOverlaps, RangedDataCNV, RangedDataCNV-method
 (Deprecated), 21
findOverlaps, RangedDataCNV, SnpSet-method
 (Deprecated), 21
findOverlaps, RangedDataHMM, RangedDataHMM-method
 (Deprecated), 21
flags, 26
flags, AssayData-method
 (AssayData-methods), 5
flags, CNSet-method (CNSet-class), 15
GeneFeatureSet (FeatureSet-class), 23
GeneFeatureSet-class
 (FeatureSet-class), 23
GenericFeatureSet (FeatureSet-class), 23
GenericFeatureSet-class
 (FeatureSet-class), 23
GenericPDInfo (DBPDInfo-class), 21
GenericPDInfo-class (DBPDInfo-class), 21
generics, 27
GenomeAnnotatedDataFrame, 28, 45
GenomeAnnotatedDataFrame
 (GenomeAnnotatedDataFrame-class), 27
GenomeAnnotatedDataFrame-class, 27
GenomeAnnotatedDataFrameFrom
 (GenomeAnnotatedDataFrameFrom-methods), 28
GenomeAnnotatedDataFrameFrom, array-method
 (GenomeAnnotatedDataFrameFrom-methods), 28
GenomeAnnotatedDataFrameFrom, AssayData-method
 (GenomeAnnotatedDataFrameFrom-methods), 28
GenomeAnnotatedDataFrameFrom, ff_or_matrix-method
 (GenomeAnnotatedDataFrameFrom-methods), 28
GenomeAnnotatedDataFrameFrom, list-method
 (GenomeAnnotatedDataFrameFrom-methods), 28
GenomeAnnotatedDataFrameFrom, NULL-method
 (GenomeAnnotatedDataFrameFrom-methods), 28
GenomeAnnotatedDataFrameFrom-methods, 28
genomeBuild, 29
genomeBuild, DBPDInfo-method
 (genomeBuild), 29
genomeBuild, FeatureSet-method
 (genomeBuild), 29
genomeBuild, GRanges-method
 (GRanges-methods), 33
genomeBuild, gSet-method (gSet-class), 34
genomeBuild, gSetList-method
 (gSetList-class), 35
genomeBuild<-, 29
genomeBuild<-, gSet, character-method
 (gSet-class), 34
genomeBuild<-, gSetList, character-method
 (gSetList-class), 35
geometry, 30
geometry, DBPDInfo-method (geometry), 30
geometry, FeatureSet-method (geometry),

30
 getA, 30
 getA, AlleleSet-method
 (AlleleSet-class), 4
 getA, SnpCnvQSet-method (getA), 30
 getA, SnpQSet-method (getA), 30
 getA, TilingFeatureSet2-method (getA), 30
 getArm (gSet-class), 34
 getArm, GenomeAnnotatedDataFrame-method
 (GenomeAnnotatedDataFrame-class),
 27
 getArm, gSet-method (gSet-class), 34
 getBar, 31
 getCluster (setCluster), 53
 getCluster-deprecated (setCluster), 53
 getM (getA), 30
 getM, AlleleSet-method
 (AlleleSet-class), 4
 getM, SnpCnvQSet-method (getA), 30
 getM, SnpQSet-method (getA), 30
 getM, TilingFeatureSet2-method (getA), 30
 getSequenceLengths, 32
 GRanges, 33, 45
 GRanges-methods, 33
 gSet, 9, 56
 gSet (gSet-class), 34
 gSet-class, 34
 gSetList-class, 35

 i2p, 36, 55
 initialize, BeadStudioSet-method
 (BeadStudioSet-class), 9
 initialize, BeadStudioSetList-method
 (BeadStudioSetList-class), 10
 initialize, CNSet-method (CNSet-class),
 15
 initialize, CNSetLM-method
 (CNSet-class), 15
 initialize, CopyNumberSet-method
 (CopyNumberSet-class), 17
 initialize, DBPDIInfo-method
 (DBPDIInfo-class), 21
 initialize, eSetList-method
 (ListClasses), 43
 initialize, FeatureSet-method
 (FeatureSet-class), 23
 initialize, GenomeAnnotatedDataFrame-method
 (GenomeAnnotatedDataFrame-class),
 27
 initialize, gSet-method (gSet-class), 34
 initialize, gSetList-method
 (gSetList-class), 35

 initialize, oligoSnpSet-method
 (oligoSnpSet-methods), 48
 initialize, SnpSet2-method
 (SnpSet2-class), 56
 initialize, SnpSuperSet-method
 (SnpSuperSet-class), 57
 initializeBigArray
 (initializeBigMatrix), 37
 initializeBigMatrix, 37
 initializeBigVector
 (initializeBigMatrix), 37
 integer2chromosome
 (chromosome2integer), 15
 integerArray (integerMatrix), 38
 integerMatrix, 38
 is_ffmatrix, 39
 isPackageLoaded, 39
 isSnp, 35
 isSnp (isSnp-methods), 40
 isSnp, character-method (isSnp-methods),
 40
 isSnp, GenomeAnnotatedDataFrame-method
 (isSnp-methods), 40
 isSnp, gSet-method (isSnp-methods), 40
 isSnp, RangedSummarizedExperiment-method
 (SummarizedExperiment-methods),
 59
 isSnp, SnpSet-method (isSnp-methods), 40
 isSnp, SummarizedExperiment-method
 (SummarizedExperiment-methods),
 59
 isSnp-methods, 40

 kind, 40
 kind, AffyExonPDIInfo-method (kind), 40
 kind, AffyExpressionPDIInfo-method
 (kind), 40
 kind, AffyGenePDIInfo-method (kind), 40
 kind, AffyHTAPDIInfo-method (kind), 40
 kind, AffySNPCNVPDIInfo-method (kind), 40
 kind, AffySNPPDIInfo-method (kind), 40
 kind, ExpressionPDIInfo-method (kind), 40
 kind, FeatureSet-method (kind), 40
 kind, GenericPDIInfo-method (kind), 40
 kind, TilingPDIInfo-method (kind), 40

 ldPath (ldSetOptions), 41
 ldSetOptions, 41
 ldStatus (ldSetOptions), 41
 length, FeatureSet-method
 (length-methods), 42
 length, gSetList-method
 (gSetList-class), 35

length-methods, 42
library, 42
library2, 42
list.celfiles, 43
list.files, 43
list_or_ffdf, 24
list_or_ffdf-class (ffdf-class), 24
ListClasses, 43
locusLevelData, 44, 48
lrr (generics), 27
lrr, BafLrrSetList-method
 (BeadStudioSetList-class), 10
lrr, BeadStudioSet-method
 (BeadStudioSet-class), 9
lrr, BeadStudioSetList-method
 (BeadStudioSetList-class), 10
lrr, RangedSummarizedExperiment-method
 (SummarizedExperiment-methods), 59
lrr, SummarizedExperiment-method
 (SummarizedExperiment-methods), 59
lrr<- (BeadStudioSet-class), 9
lrr<-, BafLrrSet, ANY-method
 (BeadStudioSet-class), 9
lrr<-, BafLrrSet-method
 (BeadStudioSet-class), 9
lrr<-, BafLrrSetList, matrix-method
 (BeadStudioSetList-class), 10
lrr<-, BeadStudioSet, ANY-method
 (BeadStudioSet-class), 9
lrr<-, BeadStudioSet-method
 (BeadStudioSet-class), 9
makeFeatureGRanges, 44
makeFeatureGRanges, GenomeAnnotatedDataFrame-method
 (GenomeAnnotatedDataFrame-class), 27
makeFeatureGRanges, gSet-method
 (gSet-class), 34
makeFeatureGRanges, gSetList-method
 (gSetList-class), 35
manufacturer (manufacturer-methods), 45
manufacturer, DBPDIInfo-method
 (manufacturer-methods), 45
manufacturer, FeatureSet-method
 (manufacturer-methods), 45
manufacturer-methods, 45
matrix, 28
mean, RangedDataCBS-method (Deprecated), 21
NgsExpressionPDIInfo (DBPDIInfo-class), 21
NgsExpressionPDIInfo-class
 (DBPDIInfo-class), 21
NgsTilingPDIInfo (DBPDIInfo-class), 21
NgsTilingPDIInfo-class (DBPDIInfo-class), 21
nu (AssayData-methods), 5
nu, AssayData, character-method
 (AssayData-methods), 5
nu, CNSet, character-method
 (CNSet-class), 15
numberProbes (GRanges-methods), 33
numberProbes, GRanges-method
 (GRanges-methods), 33
numberProbes, GRangesList-method
 (GRanges-methods), 33
ocLapply, 46
ocProbesets (ocSamples), 46
ocSamples, 46
oldClass, 24
oligoSet, 47
oligoSetList, 36
oligoSetList-class
 (BeadStudioSetList-class), 10
oligoSnpSet, 18
oligoSnpSet-class
 (oligoSnpSet-methods), 48
oligoSnpSet-methods, 48
open (fileConnections), 25
open, AlleleSet-method (getA), 30
open, array-method (fileConnections), 25
open, CNSet-method (CNSet-class), 15
open, matrix-method (fileConnections), 25
open, numeric-method (fileConnections), 25
openff (fileConnections), 25
openff, CNSet-method (fileConnections), 25
order, 14, 55
p2i, 55
p2i (i2p), 36
parStatus, 49
pdPkgFromBioC, 49
phi (AssayData-methods), 5
phi, AssayData, character-method
 (AssayData-methods), 5
phi, CNSet, character-method
 (CNSet-class), 15
platform (platform-methods), 50
platform, FeatureSet-method
 (platform-methods), 50
platform-methods, 50

pmFragmentLength
 (pmFragmentLength-methods), 50
 pmFragmentLength,AffySNPPDInfo-method
 (pmFragmentLength-methods), 50
 pmFragmentLength-methods, 50
 position, 35
 position (position-methods), 51
 position, AnnotatedDataFrame-method
 (position-methods), 51
 position, GenomeAnnotatedDataFrame-method
 (position-methods), 51
 position,gSet-method
 (position-methods), 51
 position,gSetList-method
 (gSetList-class), 35
 position,SnpSet-method
 (position-methods), 51
 position-methods, 51
 position<-
 (GenomeAnnotatedDataFrame-class),
 27
 position<-, GenomeAnnotatedDataFrame, integer-method
 (GenomeAnnotatedDataFrame-class),
 27
 position<-, oligoSnpSet, integer-method
 (oligoSnpSet-methods), 48

 RangedDataCBS (Deprecated), 21
 RangedDataCBS-class (Deprecated), 21
 RangedDataCNV (Deprecated), 21
 RangedDataCNV-class (Deprecated), 21
 RangedDataCopyNumber-class
 (Deprecated), 21
 RangedDataHMM (Deprecated), 21
 RangedDataHMM-class (Deprecated), 21
 RangedSummarizedExperiment, 59, 60
 read.celfiles, 23
 read.xysfiles, 23
 requireAnnotation, 51
 requireClusterPkg
 (requireClusterPkgSet), 52
 requireClusterPkg-deprecated
 (requireClusterPkgSet), 52
 requireClusterPkgSet, 52
 requireClusterPkgSet-deprecated
 (requireClusterPkgSet), 52

 sampleNames, FeatureSet-method
 (sampleNames-methods), 53
 sampleNames, GRanges-method
 (GRanges-methods), 33
 sampleNames, GRangesList-method
 (GRanges-methods), 33

sampleNames,gSetList-method
 (gSetList-class), 35
 sampleNames,RangedDataCNV-method
 (Deprecated), 21
 sampleNames-methods, 53
 sampleNames<, gSetList, character-method
 (gSetList-class), 35
 sampleNames<, RangedDataCNV, character-method
 (Deprecated), 21
 scqsExample, 53
 se.exprs, FeatureSet-method
 (exprs-methods), 22
 setCluster, 53
 setCluster-deprecated (setCluster), 53
 sfsExample, 54
 show, BeadStudioSet-method
 (BeadStudioSet-class), 9
 show, CNSet-method (CNSet-class), 15
 show, DBPDInfo-method (DBPDInfo-class),
 21
 show, FeatureSet-method
 (FeatureSet-class), 23
 show, gSet-method (gSet-class), 34
 show, gSetList-method (gSetList-class),
 35
 sigma2, CNSet, character-method
 (CNSet-class), 15
 .snpCallProbability, 55
 .snpCallProbability, CNSet-method
 (CNSet-class), 15
 SnpCnvFeatureSet (FeatureSet-class), 23
 SnpCnvFeatureSet-class
 (FeatureSet-class), 23
 SNPCNVPDInfo (DBPDInfo-class), 21
 SNPCNVPDInfo-class (DBPDInfo-class), 21
 SnpFeatureSet (FeatureSet-class), 23
 SnpFeatureSet-class (FeatureSet-class),
 23
 SNPPDInfo (DBPDInfo-class), 21
 SNPPDInfo-class (DBPDInfo-class), 21
 snprma, 31
 SnpSet, 55, 57
 SnpSet-methods, 55
 SnpSet2-class, 56
 SnpSuperSet, 5
 SnpSuperSet (SnpSuperSet-class), 57
 SnpSuperSet-class, 57
 splitIndicesByLength, 58
 splitIndicesByNode
 (splitIndicesByLength), 58
 sqsExample, 59
 state (GRanges-methods), 33

state, GRanges-method (GRanges-methods),
 33
state, GRangesList-method
 (GRanges-methods), 33
state, RangedDataCNV-method
 (Deprecated), 21
SummarizedExperiment-methods, 59

tau2, CNSet, character-method
 (CNSet-class), 15
TilingFeatureSet (FeatureSet-class), 23
TilingFeatureSet-class
 (FeatureSet-class), 23
TilingFeatureSet2 (FeatureSet-class), 23
TilingFeatureSet2-class
 (FeatureSet-class), 23
TilingPDIInfo (DBPDIInfo-class), 21
TilingPDIInfo-class (DBPDIInfo-class), 21

updateObject, BeadStudioSet-method
 (BeadStudioSet-class), 9
updateObject, BeadStudioSetList-method
 (BeadStudioSetList-class), 10
updateObject, CNSet-method
 (CNSet-class), 15
updateObject, GenomeAnnotatedDataFrame-method
 (GenomeAnnotatedDataFrame-class),
 27
updateObject, oligoSnpSet-method
 (oligoSnpSet-methods), 48

Versioned, 4, 9, 17, 23, 27, 34, 56, 57
VersionedBiobase, 4, 9, 17, 23, 34, 56, 57