

# Package ‘packFinder’

January 20, 2026

**Type** Package

**Title** de novo Annotation of Pack-TYPE Transposable Elements

**Version** 1.22.0

**Description** Algorithm and tools for in silico pack-TYPE transposon discovery. Filters a given genome for properties unique to DNA transposons and provides tools for the investigation of returned matches. Sequences are input in DNAString format, and ranges are returned as a dataframe (in the format returned by as.dataframe(GRanges)).

**License** GPL-2

**Encoding** UTF-8

**Depends** R (>= 4.1.0)

**Imports** Biostrings, GenomicRanges, kmer, ape, methods, IRanges, S4Vectors

**Suggests** biomartr, knitr, rmarkdown, testthat, dendextend, biocViews, BiocCheck, BiocStyle

**RoxygenNote** 7.2.0

**VignetteBuilder** knitr

**URL** <https://github.com/jackgisby/packFinder>

**BugReports** <https://github.com/jackgisby/packFinder/issues>

**biocViews** Genetics, SequenceMatching, Annotation

**git\_url** <https://git.bioconductor.org/packages/packFinder>

**git\_branch** RELEASE\_3\_22

**git\_last\_commit** 360ddfb

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.22

**Date/Publication** 2026-01-19

**Author** Jack Gisby [aut, cre] (ORCID: <<https://orcid.org/0000-0003-0511-8123>>),  
Marco Catoni [aut] (ORCID: <<https://orcid.org/0000-0002-3258-2522>>)

**Maintainer** Jack Gisby <[jackgisby@gmail.com](mailto:jackgisby@gmail.com)>

## Contents

arabidopsisThalianaRefseq	2
blastAnalysis	3
blastAnnotate	5
collapseSeqs	6
filterWildcards	7
getPackSeqs	8
getPacksFromCsv	9
getPacksFromFasta	10
getPacksFromGRanges	11
getTsds	12
identifyPotentialPackElements	13
identifyTirMatches	14
makeBlastDb	16
packAlign	17
packBlast	18
packClust	21
packFinder	22
packMatches	23
packSearch	24
packsToCsv	26
packsToFasta	27
packsToGRanges	28
readBlast	29
readUc	31
tirClust	33

<b>Index</b>	<b>35</b>
--------------	-----------

---

arabidopsisThalianaRefseq

*Arabidopsis thaliana Refseq Genome Chromosome 3 Subset*

---

### Description

The chromosome 3 reference sequence for *Arabidopsis thaliana* as a `DNAStrongSet`. Can be used as a test data set, as in the associated introduction vignette. The DNA sequence between bases 10,500,000 and 14,300,000 was extracted for use in this dataset.

### Usage

```
data(arabidopsisThalianaRefseq)
```

### Format

A `DNAStrongSet` object containing a `DNAStrong` for *Arabidopsis thaliana*'s chromosome 3 sequence.

### Author(s)

Jack Gisby

## Source

The *Arabidopsis thaliana* genome was downloaded from the NCBI refseq database on 20/SEP/2019, using [getGenome](#), and chromosome 3 was extracted. The genome may also be accessed from the NCBI ftp server: <ftp://ftp.ncbi.nlm.nih.gov/genomes>.

## See Also

[getGenome](#), [DNAStringSet](#), [DNAString](#), [packSearch](#)

## Examples

```
data(arabidopsisThalianaRefseq)

packMatches <- packSearch(
  Biostrings::DNAString("CACTACAA"),
  arabidopsisThalianaRefseq,
  elementLength = c(300, 3500),
  tsdLength = 3
)
```

---

blastAnalysis

*BLAST Analysis of PackTYPE Elements*

---

## Description

Run BLAST against user-specified databases of non-transposon and transposon-related proteins. Can be used to classify transposons based on their internal sequences.

## Usage

```
blastAnalysis(
  packMatches,
  Genome,
  blastPath,
  protDb = NULL,
  autoDb = NULL,
  minE = 0.001,
  blastTask = "blastn-short",
  maxHits = 100,
  threads = 1,
  saveFolder = NULL,
  tirCutoff = 0
)
```

## Arguments

packMatches	A dataframe of potential Pack-TYPE transposable elements, in the format given by <a href="#">packSearch</a> . This dataframe is in the format produced by coercing a <code>link[GenomicRanges:GRanges]</code> object to a dataframe: <code>data.frame(GRanges)</code> . Will be saved as a FASTA file for VSEARCH.
-------------	--

Genome	A DNAStringSet object containing sequences referred to in packMatches (the object originally used to predict the transposons <a href="#">packSearch</a> ).
blastPath	Path to the BLAST+ executable, or name of the BLAST+ application for Linux/MacOS users.
protDb	For assigning Pack-TYPE elements. Path to the blast database containing nucleotide or protein sequences to be matched against internal transposon sequences. Can be generated using BLAST+, or with <code>link{makeBlastDb}</code> .
autoDb	For assigning autonomous elements. Path to the blast database containing nucleotide or protein sequences to be matched against internal transposon sequences. Can be generated using BLAST+, or with <code>link{makeBlastDb}</code> .
minE	Blast results with e values greater than the specified cutoff will be ignored.
blastTask	Type of BLAST+ task, defaults to "blastn-short".
maxHits	Maximum hits returned by BLAST+ per query.
threads	Allowable number of threads to be utilised by BLAST+.
saveFolder	Directory to save BLAST+ results in; defaults to the working directory.
tirCutoff	How many bases to ignore at the terminal ends of the transposons to prevent hits to TIR sequences.

### Value

No return value; executes BLAST+ to generate hits which are stored in a .blast file in the chosen directory.

### Author(s)

Jack Gisby

### References

For further information, see the NCBI BLAST+ application documentation and help pages (<https://www.ncbi.nlm.nih.gov/blast/doc/manual.html>).

### See Also

[blastAnnotate](#), [readBlast](#), [packBlast](#)

### Examples

```
## Not run:
packMatches <- data(packMatches)
Genome <- data(arabidopsisThalianaRefseq)

blastAnalysis(packMatches, Genome,
  protDb = "C:/data/TAIR10_CDS",
  autoDb = "C:/data/TAIR10_transposons",
  blastPath = "C:/blast/bin/blastn.exe")

## End(Not run)
```

## Description

Uses hits, previously generated using blast, to annotate transposon hits. Transposons with non-redundant transposase hits are classed as autonomous ("auto"), while others are classed as "other" or "pack" based on whether the element has non-redundant hits to other proteins.

## Usage

```
blastAnnotate(prothits, autohits, packmatches)
```

## Arguments

prothits	BLAST results for non-transposon related genes or proteins (as a <code>data.frame</code> ). Generated using <a href="#">blastAnalysis</a> .
autohits	BLAST results for transposon related genes or proteins (as a <code>data.frame</code> ). Generated using <a href="#">blastAnalysis</a> .
packmatches	A datafram of potential Pack-TYPE transposable elements, in the format given by <a href="#">packSearch</a> . This datafram is in the format produced by coercing a <code>link[GenomicRanges:GRanges]</code> object to a datafram: <code>data.frame(GRanges)</code> . Will be saved as a FASTA file for VSEARCH.

## Value

Returns the original packMatches datafram, with the addition of a "classification" column containing one of the following values:

- auto - elements that match known transposases or transposon-related proteins are classified as autonomous elements
- pack - elements that match other proteins or genic sequences may be classified as Pack-TYPE elements
- other - elements that generate no significant hits

## Note

Requires that the query ids in the protein and autonomous hits match the row names in packMatches.

## Author(s)

Jack Gisby

## References

For further information, see the NCBI BLAST+ application documentation and help pages (<https://www.ncbi.nlm.nih.gov/blast/doc/manual.html>)

## See Also

[blastAnalysis](#), [readBlast](#), [packBlast](#)

## Examples

```
data("packMatches")

# read in some protein hits
p <- data.frame(
  query_id = c(2, 3),
  subject_id = c("prot", "hyp")
)

# read in some autonomous hits
a <- data.frame(
  query_id = c(3, 4),
  subject_id = c("transposase", "mutator")
)

blastAnnotate(p, a, packMatches)
```

---

collapseSeqs

*Collapse Overlapping Sequences*

---

## Description

The sequences predicted by [packSearch](#) often overlap, which may be due to the presence of closely interspersed elements or false TIR identification. In such cases, these elements can be combined using `link[GenomicRanges:GRanges-class]{GRanges}` in order to collapse overlapping elements, preventing over-estimation of transposon numbers. Also removes duplicate elements that have been generated in the case of multiple searches.

## Usage

```
collapseSeqs(packMatches, Genome)
```

## Arguments

packMatches	A data frame containing genomic ranges and names referring to sequences to be extracted. This data frame is in the format produced by coercing a <code>link[GenomicRanges:GRanges-class]{GRanges}</code> object to a data frame: <code>data.frame(GRanges)</code> . Must contain the following features: <ul style="list-style-type: none"> <li>• start - the predicted element's start base sequence position.</li> <li>• end - the predicted element's end base sequence position.</li> <li>• seqnames - character string referring to the sequence name in Genome to which start and end refer to.</li> </ul>
Genome	A DNAStringSet object containing sequences referred to in packMatches (the object originally used to predict the transposons <a href="#">packSearch</a> ).

## Value

A set of non-overlapping transposon sequences in the format of the input data frame.

**Author(s)**

Jack Gisby

**See Also**[packSearch](#), [link\[GenomicRanges:GRanges-class\]{GRanges}](#)**Examples**

```
data(packMatches)
data(arabidopsisThalianaRefseq)

packMatches$start <- 1
packMatches$end <- 10

collapseSeqs(packMatches, arabidopsisThalianaRefseq)
```

---

filterWildcards*Remove Low Quality Sequences*

---

**Description**

Takes transposable elements detected by [packSearch](#) and removes those with large numbers of wildcard ("N") bases. Used by [packClust](#) and [packAlign](#) to remove poor quality sequences that may interfere with the quality of sequence alignments.

**Usage**

```
filterWildcards(packMatches, Genome, maxWildcards = 0.05)
```

**Arguments**

packMatches	A data frame containing genomic ranges and names referring to sequences to be extracted.
Genome	The original set of sequences used to generate the transposons detected by <a href="#">packSearch</a> .
maxWildcards	The maximal allowable proportion of wildcards in the sequence of each match (defaults to 0.05).

**Value**

The original data frame, packMatches, with sequences removed that are found to contain a proportion of wildcards ("N") greater than that specified in maxWildcards.

**Author(s)**

Jack Gisby

**See Also**[packClust](#), [packAlign](#), packMatches, data(arabidopsisThalianaRefseq)

## Examples

```

data(arabidopsisThalianaRefseq)
data(packMatches)

filteredMatches <- filterWildcards(
  packMatches,
  arabidopsisThalianaRefseq,
  maxWildcards = 0.05
)

```

---

getPackSeqs

*Extract Sequences of Pack-TYPE Elements*

---

## Description

Method to quickly extract the sequences of predicted Pack-TYPE elements (as created by [packSearch](#)).

## Usage

```
getPackSeqs(packMatches, Genome, output = "DNAStringSet")
```

## Arguments

packMatches	A data frame containing genomic ranges and names referring to sequences to be extracted. This data frame is in the format produced by coercing a <a href="#">link[GenomicRanges:GRanges-class]</a> object to a data frame: <code>data.frame(GRanges)</code> . Must contain the following features: <ul style="list-style-type: none"> <li>• start - the predicted element's start base sequence position.</li> <li>• end - the predicted element's end base sequence position.</li> <li>• seqnames - character string referring to the sequence name in Genome to which start and end refer to.</li> </ul>
Genome	A <code>DNAStringSet</code> object containing sequences referred to in <code>packMatches</code> (the object originally used to predict the transposons <a href="#">packSearch</a> ).
output	The type of object to be returned: <ul style="list-style-type: none"> <li>• <code>output = "DNAStringSet"</code>, returns a <code>DNAStringSet</code> object (default).</li> <li>• <code>output = "character"</code>, returns a character vector.</li> </ul>

## Value

transposon sequences extracted from `packMatches`. At default returns the sequences as a `DNAStringSet` or, if `output` is set to "character", returns a character vector.

## Author(s)

Jack Gisby

## See Also

[DNAStringSet](#), [packSearch](#), [DNAString](#)

## Examples

```
data(arabidopsisThalianaRefseq)

packMatches <- packSearch(
  Biostrings::DNAString("CACTACAA"),
  arabidopsisThalianaRefseq,
  elementLength = c(300, 3500),
  tsdLength = 3
)

packSeqs <- getPackSeqs(packMatches, arabidopsisThalianaRefseq)
```

---

getPacksFromCsv

*Retrieve Saved packFinder Results (.csv)*

---

## Description

Retrieves a datafram of potential Pack-TYPE elements, previously saved using [packSearch](#) followed by [packsToCsv](#).

## Usage

```
getPacksFromCsv(file)
```

## Arguments

**file** File path to predicted transposons in CSV format.

## Value

Datafram in the format used by [packSearch](#).

## Author(s)

Jack Gisby

## See Also

[packsToCsv](#), [read.table](#), [packSearch](#)

## Examples

```
data(packMatches)

packMatches <- getPacksFromCsv(
  system.file("extdata", "packMatches.csv", package = "packFinder")
)
```

---

getPacksFromFasta      *Retrieve Saved packFinder Results (.fasta)*

---

## Description

Retrieves a data frame of potential Pack-TYPE elements, previously saved using [packSearch](#) followed by [packsToFasta](#). Parses the .fasta file and title field containing:

- seqnames - name of origin sequence
- start - transposon base start position on origin sequence
- end - transposon base end position on origin sequence
- width - width of transposon
- strand - direction of transposon ("+", "-" or "\*")
- TSD - terminal site duplication (TSD) sequence

## Usage

```
getPacksFromFasta(file)
```

## Arguments

file      Path to predicted transposons in FASTA format.

## Value

Data frame in the format used by [packSearch](#).

## Author(s)

Jack Gisby

## See Also

[packsToFasta](#), [packSearch](#)

## Examples

```
data(arabidopsisThalianaRefseq)
data(packMatches)

packMatches <- getPacksFromFasta(
  system.file("extdata", "packMatches.fasta", package = "packFinder")
)
```

---

getPacksFromGRanges     *Retrieve packFinder Results from GRanges Object*

---

## Description

A `link[GenomicRanges:GRanges-class]{GRanges}` object, potentially generated using [packSearch](#) and [packsToGRanges](#), can be converted to a dataframe. If a `GRanges` object is supplied without TSD information, this can be calculated and appended to the final dataframe.

## Usage

```
getPacksFromGRanges(packGRanges, Genome = NULL, tsdLength = NULL)
```

## Arguments

`packGRanges`     `link[GenomicRanges:GRanges-class]{GRanges}` object to be coerced.  
`Genome`     (optional) Sequences referred to by `packGRanges`.  
`tsdLength`     (optional) Length of TSD sequences.

## Value

Dataframe in the format used by [packSearch](#). If `Genome` and `tsdLength` are supplied, then TSD sequences are retrieved and returned as part of the dataframe.

## Author(s)

Jack Gisby

## See Also

[packsToGRanges](#), `link[GenomicRanges:GRanges-class]{GRanges}`, [packSearch](#)

## Examples

```
data(packMatches)

GRangesObject <- packsToGRanges(packMatches)
packMatches <- getPacksFromGRanges(GRangesObject)
```

---

**getTsds***Get Flanking Terminal Site Duplication Sequences*

---

**Description**

Gets the flanking TSD sequences of TIRs or predicted Pack-TYPE transposable elements. A datafram of these elements can be in `tirMatches`.

**Usage**

```
getTsds(tirMatches, Genome, tsdLength, strand = "+", output = "character")
```

**Arguments**

<code>tirMatches</code>	A datafram containing genomic ranges and names referring to TIR sequences or predicted Pack-TYPE transposable elements. Should be in the format used by <code>packSearch</code> .
<code>Genome</code>	A <code>DNAStringSet</code> object containing sequences referred to in <code>tirMatches</code> .
<code>tsdLength</code>	The length of the TSD region to be retrieved (integer).
<code>strand</code>	The strand of the TIR; "+" for forward, "-" for reverse. If the TSD sequences of transposable elements are being predicted, then this parameter can be left as default ("+"); if the TSD sequences of TIRs are being found then the strand direction must be supplied.
<code>output</code>	The type of object to be returned: <ul style="list-style-type: none"><li>• <code>output = "DNAStringSet"</code>, returns a <code>DNAStringSet</code> object.</li><li>• <code>output = "character"</code>, returns a character vector (default).</li></ul>

**Details**

Called by `packSearch`. It is recommended to use the general pipeline function `packSearch` for identification of potential pack elements, which returns TSD sequences as a feature of results, however each stage may be called individually.

**Value**

Flanking TSD sequences as a vector of characters, or if output is specified as "DNAStringSet", TSD sequences will be returned as a `DNAStringSet` object.

**Author(s)**

Jack Gisby

**See Also**

`DNAStringSet`, `packSearch`, `tirMatches`

## Examples

```
data(arabidopsisThalianaRefseq)
data(packMatches)

tsdSeqs <- getTsdSeqs(packMatches, arabidopsisThalianaRefseq, 3)
```

---

identifyPotentialPackElements  
*Pack Element Filtering*

---

## Description

Primary filtering stage for the `packSearch` algorithm. Identifies potential Pack-TYPE transposable elements based on proximity of matching inverted repeats and equality of TSD sequences.

## Usage

```
identifyPotentialPackElements(
  forwardMatches,
  reverseMatches,
  Genome,
  elementLength,
  tsdMismatch = 0
)
```

## Arguments

<code>forwardMatches</code>	A data frame containing genomic ranges and names referring to forwards-facing TIR sequences and their respective TSD sequences.
<code>reverseMatches</code>	A data frame containing genomic ranges and names referring to reverse-facing TIR sequences and their respective TSD sequences.
<code>Genome</code>	A <code>DNAStringSet</code> object containing the matches referred to in <code>forwardMatches</code> and <code>reverseMatches</code>
<code>elementLength</code>	A vector of two integers containing the minimum and maximum transposable element length.
<code>tsdMismatch</code>	An integer referring to the allowable mismatch (substitutions or indels) between a transposon's TSD sequences. <code>matchPattern</code> from <code>Biostrings</code> is used for pattern matching.

## Details

Used by `packSearch` as a primary filtering stage. Identifies matches likely to be transposons based on their TIR region, from `identifyTirMatches`, and their TSD region, from `getTsdSeqs`. It is recommended to use the general pipeline function `packSearch` for identification of potential pack elements, however each stage may be called individually. Note that only exact TSD matches are considered, so supplying long sequences for TSD elements may lead to false-negative results.

**Value**

A dataframe, packMatches, containing the locations of potential Pack-TYPE transposable elements in Genome.

**Author(s)**

Jack Gisby

**See Also**

packSearch

**Examples**

```
data(arabidopsisThalianaRefseq)

forwardMatches <- identifyTirMatches(
  Biostrings::DNAString("CACTACAA"),
  arabidopsisThalianaRefseq,
  tsdLength = 3,
  strand = "+"
)

reverseMatches <- identifyTirMatches(
  Biostrings::reverseComplement(Biostrings::DNAString("CACTACAA")),
  arabidopsisThalianaRefseq,
  tsdLength = 3,
  strand = "-"
)

packMatches <- identifyPotentialPackElements(
  forwardMatches,
  reverseMatches,
  arabidopsisThalianaRefseq,
  c(300, 3500)
)
```

**identifyTirMatches** *Identify Terminal Inverted Repeat Matches*

**Description**

Searches a [DNAStringSet](#) for potential TIRs based on sequence similarity.

**Usage**

```
identifyTirMatches(
  tirSeq,
  Genome,
  mismatch = 0,
  strand = "*",
  tsdLength,
```

```
  fixed = TRUE
)
```

## Arguments

tirSeq	A <a href="#">DNAString</a> object to be searched for.
Genome	A <a href="#">DNAStringSet</a> object containing the <a href="#">DNAString</a> objects to be searched.
mismatch	The allowable mismatch between tirSeq and a given slice of Genome. Includes indels.
strand	The directionality of the search string ("+" or "-"). Note that this does affect the search for tirSeqs, if you wish to search the reverse strand you should use the reverse complement of your sequence.
tsdLength	Integer referring to the length of the flanking TSD region.
fixed	Logical that will be passed to the ‘fixed’ argument of <a href="#">matchPattern</a> . Determines the behaviour of IUPAC ambiguity codes when searching for TIR sequences.

## Details

Called by [packSearch](#). Used by [packSearch](#) as an initial filtering stage. [matchPattern](#) from Biostrings is used for pattern matching. It is recommended to use the general pipeline function [packSearch](#) for identification of potential pack elements, however each stage may be called individually.

## Value

A data frame, `tirMatches`, containing identified matches. The data frame is in the format generated by [packSearch](#).

## Author(s)

Jack Gisby

## See Also

[DNAStringSet](#), [packSearch](#), [matchPattern](#), [DNAString](#)

## Examples

```
data(arabidopsisThalianaRefseq)

forwardMatches <- identifyTirMatches(
  Biostrings::DNAString("CACTACAA"),
  arabidopsisThalianaRefseq,
  tsdLength = 3,
  strand = "+"
)
```

---

makeBlastDb

*Make Blast Database*

---

## Description

Generates a BLAST database to be queried. Required for identifying sequences using the BLAST+ software.

## Usage

```
makeBlastDb(fastaFile, dbPath, blastPath, dbType = "nucl")
```

## Arguments

fastaFile	FASTA file containing sequences to generate a BLAST database from.
dbPath	Path to save the BLAST database to.
blastPath	Path/name of BLAST program to use. Name of the application for Linux/MacOS, absolute path for the executable for windows users.
dbType	Type of BLAST database to create, e.g. "nucl" for a nucleotide database.

## Value

No return value; generates a blast database in the chosen directory.

## Author(s)

Jack Gisby

## References

For further information, see the NCBI BLAST+ application documentation and help pages (<https://www.ncbi.nlm.nih.gov/blast/doc/manual.html>)

## See Also

[packSearch](#)

## Examples

```
## Not run:  
makeBlastDb("genes.fasta", "blastdb.db", "C:/blast.exe")  
## End(Not run)
```

## Description

A global pairwise alignment of pack-TYPE elements by sequence similarity. mIt may be useful to run [packClust](#) to identify groups of similar transposable elements, before generating alignments of each group.

## Usage

```
packAlign(  
  packMatches,  
  Genome,  
  identity = 0,  
  threads = 1,  
  identityDefinition = 2,  
  maxWildcards = 0.05,  
  saveFolder,  
  vSearchPath = "vsearch"  
)
```

## Arguments

packMatches	A data frame of potential Pack-TYPE transposable elements, in the format given by <a href="#">packSearch</a> . This data frame is in the format produced by coercing a <code>link[GenomicRanges:GRanges]</code> object to a data frame: <code>data.frame(GRanges)</code> . Will be saved as a FASTA file for VSEARCH.
Genome	A DNAStringSet object containing sequences referred to in packMatches (the object originally used to predict the transposons <a href="#">packSearch</a> ).
identity	The sequence identity of two transposable elements in packMatches required to be grouped into a cluster.
threads	The number of threads to be used by VSEARCH.
identityDefinition	The pairwise identity definition used by VSEARCH. Defaults to 2, the standard VSEARCH definition.
maxWildcards	The maximal allowable proportion of wildcards in the sequence of each match (defaults to 0.05).
saveFolder	The folder to save saveFolder files (uc, blast6out, FASTA)
vSearchPath	When the package is run on windows systems, the location of the VSEARCH executable file must be given; this should be left as default on Linux/MacOS systems.

## Value

Saves alignment information, including a uc, blast6out and a pairwise alignment fasta file, to the specified location. Returns the uc summary file generated by the alignment.

**Note**

In order to align sequences using VSEARCH, the executable file must first be installed.

**Author(s)**

Jack Gisby

**References**

VSEARCH may be downloaded from <https://github.com/torognes/vsearch>, along with a manual documenting the program's parameters. See <https://www.ncbi.nlm.nih.gov/pubmed/27781170> for further information.

**See Also**

[tirClust](#), [packClust](#), [readBlast](#), [readUc](#), [filterWildcards](#), [packSearch](#)

**Examples**

```
data(arabidopsisThalianaRefseq)
data(packMatches)

# packAlign run on a Linux/MacOS system
## Not run:
packAlign(packMatches, Genome)

## End(Not run)

# packAlign run on a Windows system
## Not run:
packAlign(packMatches, Genome,
          vSearchPath = "path/to/vsearch/vsearch.exe")

## End(Not run)
```

**Description**

Run BLAST against user-specified databases of non-transposon and transposon-related proteins. Can be used to classify transposons based on their internal sequences.

**Usage**

```
packBlast(
  packMatches,
  Genome,
  blastPath,
  protDb,
  autoDb,
  minE = 0.001,
```

```

blastTask = "blastn-short",
maxHits = 100,
threads = 1,
saveFolder = NULL,
tirCutoff = 100,
autoCutoff = 1e-05,
autoLength = 150,
autoIdentity = 70,
autoScope = NULL,
protCutoff = 1e-05,
protLength = 250,
protIdentity = 70,
protScope = 0.3
)

```

## Arguments

packMatches	A dataframe of potential Pack-TYPE transposable elements, in the format given by <a href="#">packSearch</a> . This dataframe is in the format produced by coercing a <code>link[GenomicRanges:GRanges]</code> object to a dataframe: <code>data.frame(GRanges)</code> . Will be saved as a FASTA file for VSEARCH.
Genome	A DNAStringSet object containing sequences referred to in packMatches (the object originally used to predict the transposons <a href="#">packSearch</a> ).
blastPath	Path to the BLAST+ executable, or name of the BLAST+ application for Linux/MacOS users.
protDb	For assigning Pack-TYPE elements. Path to the blast database containing nucleotide or protein sequences to be matched against internal transposon sequences. Can be generated using BLAST+, or with <code>link{makeBlastDb}</code> .
autoDb	For assigning autonomous elements. Path to the blast database containing nucleotide or protein sequences to be matched against internal transposon sequences. Can be generated using BLAST+, or with <code>link{makeBlastDb}</code> .
minE	Blast results with e values greater than the specified cutoff will be ignored. This will be passed to BLASTN and applied to both transposon and non-transposon matches.
blastTask	Type of BLAST+ task, defaults to "blastn-short".
maxHits	Maximum hits returned by BLAST+ per query.
threads	Allowable number of threads to be utilised by BLAST+.
saveFolder	Directory to save BLAST+ results in; defaults to the working directory.
tirCutoff	How many bases to ignore at the terminal ends of the transposons to prevent hits to TIR sequences.
autoCutoff	Blast results for transposon-related elements will be filtered to ignore those with e values above the specified cutoff.
autoLength	Blast results for transposon-related elements containing hits with alignment lengths lower than this value will be ignored
autoIdentity	Blast results for transposon-related elements containing hits with sequence identities lower than this value will be ignored
autoScope	If specified, transposon-related blast results below the specified value will be ignored. Note that the dataframe of transposon matches must also be supplied to calculate scope. Scope is the proportion of the transposon's internal sequence occupied by the BLAST hit.

protCutoff	Blast results for genic/other matches will be filtered to ignore those with e values above the specified cutoff.
protLength	Blast results for genic/other matches containing hits with alignment lengths lower than this value will be ignored
protIdentity	Blast results for genic/other matches containing hits with sequence identities lower than this value will be ignored
protScope	If specified, genic/other blast matches below the specified value will be ignored. Note that the dataframe of transposon matches must also be supplied to calculate scope. Scope is the proportion of the transposon's internal sequence occupied by the BLAST hit.

**Value**

Returns the original `packMatches` dataframe, with the addition of a "classification" column containing one of the following values:

- auto - elements that match known transposases or transposon-related proteins are classified as autonomous elements
- pack - elements that match other proteins or genic sequences may be classified as Pack-TYPE elements
- other - elements that generate no significant hits

**Author(s)**

Jack Gisby

**References**

For further information, see the NCBI BLAST+ application documentation and help pages (<https://www.ncbi.nlm.nih.gov/blast/doc/manual.html>)

**See Also**

[blastAnalysis](#), [packSearch](#), [readBlast](#), [blastAnnotate](#)

**Examples**

```
## Not run:
packMatches <- data(packMatches)
Genome <- data(arabidopsisThalianaRefseq)

packBlast(packMatches, Genome,
          protDb = "C:/data/TAIR10_CDS",
          autoDb = "C:/data/TAIR10_transposons",
          blastPath = "C:/blast/bin/blastn.exe")

## End(Not run)
```

packClust

*Cluster Transposons with VSEARCH***Description**

Cluster potential pack-TYPE elements by sequence similarity. Resulting groups may be aligned with [packAlign](#), or the clusters may be analysed with [tirClust](#)

**Usage**

```
packClust(
  packMatches,
  Genome,
  identity = 0.6,
  threads = 1,
  identityDefinition = 2,
  maxWildcards = 0.05,
  strand = "both",
  saveFolder = NULL,
  vSearchPath = "vsearch"
)
```

**Arguments**

packMatches	A data frame of potential Pack-TYPE transposable elements, in the format given by <a href="#">packSearch</a> . This data frame is in the format produced by coercing a <code>link[GenomicRanges:GRanges]</code> object to a data frame: <code>data.frame(GRanges)</code> . Will be saved as a FASTA file for VSEARCH.
Genome	A DNAStringSet object containing sequences referred to in packMatches (the object originally used to predict the transposons <a href="#">packSearch</a> ).
identity	The sequence identity of two transposable elements in packMatches required to be grouped into a cluster.
threads	The number of threads to be used by VSEARCH.
identityDefinition	The pairwise identity definition used by VSEARCH. Defaults to 2, the standard VSEARCH definition.
maxWildcards	The maximal allowable proportion of wildcards in the sequence of each match (defaults to 0.05).
strand	The strand direction (+, - or *) to be clustered.
saveFolder	The folder to save output files (uc, blast6out, FASTA)
vSearchPath	When the package is run on windows systems, the location of the VSEARCH executable file must be given; this should be left as default on Linux/MacOS systems.

**Value**

Saves cluster information, including a uc and blast6out file, to the specified location. Returns the given packMatches data frame with an additional column, cluster, containing cluster IDs.

**Note**

In order to cluster sequences using VSEARCH, the executable file must first be installed.

**Author(s)**

Jack Gisby

**References**

VSEARCH may be downloaded from <https://github.com/torognes/vsearch>. See <https://www.ncbi.nlm.nih.gov/pubmed/27781170> for further information.

**See Also**

[tirClust](#), [packAlign](#), [readBlast](#), [readUc](#), [filterWildcards](#), [packSearch](#)

**Examples**

```
data(arabidopsisThalianaRefseq)
data(packMatches)

# packClust run on a Linux/MacOS system
## Not run:
  packClust(packMatches, Genome)

## End(Not run)

# packClust run on a Windows system
## Not run:
  packClust(packMatches, Genome,
  vSearchPath = "path/to/vsearch/vsearch.exe")

## End(Not run)
```

**Description**

Algorithm and tools for in silico pack-TYPE transposon discovery. Filters a given genome for properties unique to DNA transposons and provides tools for the investigation of returned matches.

**Main Algorithm**

The goal of packFinder was to implement a simple tool for the prediction of potential Pack-TYPE elements. packFinder uses the following prior knowledge, provided by the user, to detect transposons:

- Terminal Inverted Repeat (TIR) Base Sequence
- Length of Terminal Site Duplication (TSD)

- Length of the Transposon

These features provide enough information to detect autonomous and pack-TYPE elements. For a transposon to be predicted by packFinder its TSD sequences must be identical to each other, its forward TIR sequence must match the base sequence provided and its reverse TIR sequence must match its reverse complement.

Transposons are therefore predicted by searching a given genome for these characteristics, and further analysis steps can reveal the nature of these elements - while the packFinder tool is sensitive for the detection of transposons, it does not discriminate between autonomous and Pack-TYPE elements. Autonomous elements will contain a transposase gene within the terminal inverted repeats and tend to be larger than their Pack-TYPE counterparts; pack-TYPE elements instead capture sections of host genomes. Following cluster analysis, BLAST can be used to discern which predicted elements are autonomous (transposase-containing) and which are true Pack-TYPE elements.

## Workflow

An example of a standard workflow can be found using `browseVignettes(package = "packFinder")`. The primary functions include:

- `packSearch` - the `packSearch` algorithm uses simple pattern matching to detect DNA transposons.
- `packClust` - VSEARCH is used for clustering elements based on sequence similarity.

Having obtained the sequences of transposable elements in a given genome, it is recommended to carry out a BLAST search for each transposon cluster. This can identify which elements are likely autonomous, and which may be Pack-TYPE.

The `packFinder` functions report the position of elements in a given genome using a dataframe in the format of `packMatches`. This dataframe is in the format produced by coercing a `link[GenomicRanges:GRanges-class]` object to a dataframe: `data.frame(GRanges)`.

## Author(s)

Jack Gisby

## See Also

[packSearch](#)

---

packMatches

*Sample packFinder Output*

---

## Description

A sample output from `packSearch` with cluster information. This dataframe is in the format produced by coercing a `link[GenomicRanges:GRanges-class]` object to a dataframe: `data.frame(GRanges)`.

## Usage

`data(packMatches)`

**Format**

A dataframe of 9 obs. and 7 variables.

**Details**

Was obtained from running [packSearch](#) on the *Arabidopsis thaliana* chromosome 3 reference sequence, followed by clustering using [packClust](#). Contains the following features:

- start - the predicted element's start base sequence position.
- end - the predicted element's end base sequence position.
- seqnames - character string referring to the sequence name in Genome to which start and end refer to.

The dataset was generated as in the example below.

**See Also**

[packSearch](#), [data.frame](#), [arabidopsisThalianaRefseq](#)

**Examples**

```
data(arabidopsisThalianaRefseq)

packMatches <- packSearch(
  Biostrings:::DNAString("CACTACAA"),
  arabidopsisThalianaRefseq,
  elementLength = c(300, 3500),
  tsdLength = 3
)
```

---

packSearch

*packFinder Algorithm Pipeline*

---

**Description**

General use pipeline function for the Pack-TYPE transposon finding algorithm.

**Usage**

```
packSearch(
  tirSeq,
  Genome,
  mismatch = 0,
  elementLength,
  tsdLength,
  tsdMismatch = 0,
  fixed = TRUE
)
```

## Arguments

tirSeq	A <a href="#">DNAString</a> object containing the TIR sequence to be searched for.
Genome	A <a href="#">DNAStringSet</a> object to be searched.
mismatch	The maximum edit distance to be considered for TIR matches (indels + substitutions). See <a href="#">matchPattern</a> for details.
elementLength	The maximum element length to be considered, as a vector of two integers. E.g. <code>c(300, 3500)</code>
tsdLength	Integer referring to the length of the flanking TSD region.
tsdMismatch	An integer referring to the allowable mismatch (substitutions or indels) between a transposon's TSD sequences. <a href="#">matchPattern</a> from Biostings is used for pattern matching.
fixed	Logical that will be passed to the 'fixed' argument of <a href="#">matchPattern</a> . Determines the behaviour of IUPAC ambiguity codes when searching for TIR sequences.

## Details

Finds potential pack-TYPE elements based on:

- Similarity of TIR sequence to `tirSeq`
- Proximity of potential TIR sequences
- Directionality of TIR sequences
- Similarity of TSD sequences

The algorithm finds potential forward and reverse TIR sequences using [identifyTirMatches](#) and their associated TSD sequence via [getTsds](#). The main filtering stage, [identifyPotentialPackElements](#), filters matches to obtain a dataframe of potential PACK elements. Note that this pipeline does not consider the possibility of discovered elements being autonomous elements, so it is recommended to cluster and/or BLAST elements for further analysis. Furthermore, only exact TSD matches are considered, so supplying long sequences for TSD elements may lead to false-negative results.

## Value

A datafram, containing elements identified by the algorithm. These may be autonomous or pack-TYPE elements. Will contain the following features:

- `start` - the predicted element's start base sequence position.
- `end` - the predicted element's end base sequence position.
- `seqnames` - character string referring to the sequence name in `Genome` to which `start` and `end` refer to.
- `width` - the width of the predicted element.
- `strand` - the strand direction of the transposable element. This will be set to "\*" as the `packSearch` function does not consider transposons to have a direction - only TIR sequences. Passing the `packMatches` datafram to [packClust](#) will assign a direction to each predicted Pack-TYPE element.

This datafram is in the format produced by coercing a `link[GenomicRanges:GRanges-class]{GRanges}` object to a datafram: `data.frame(GRanges)`. Downstream functions, such as [packClust](#), use this datafram to manipulate predicted transposable elements.

**Note**

This algorithm does not consider:

- Autonomous elements - autonomous elements will be predicted by this algorithm as there is no BLAST step. It is recommended that, after clustering elements using `packClust`, the user analyses each group to determine which predicted elements are autonomous and which are likely Pack-TYPE elements. Alternatively, databases such as Repbase (<https://www.girinst.org/reppbase/>) supply annotations for autonomous transposable elements that can be used to filter autonomous matches.
- TSD Mismatches - if two TIRs do not have exact matches for their terminal site duplications they will be ignored. Supplying longer TSD sequences will likely lead to a lower false-positive rate, however may also cause a greater rate of false-negative results.

Pattern matching is done via `matchPattern`.

**Author(s)**

Jack Gisby

**See Also**

`identifyTirMatches`, `getTsd`, `identifyPotentialPackElements`, `packClust`, `packMatches`, `DNAStringSet`, `DNAString`, `matchPattern`

**Examples**

```
data(arabidopsisThalianaRefseq)

packMatches <- packSearch(
  Biostrings::DNAString("CACTACAA"),
  arabidopsisThalianaRefseq,
  elementLength = c(300, 3500),
  tsdLength = 3
)
```

---

packsToCsv

*Save packFinder Results in CSV Format (.csv)*

---

**Description**

Saves a data frame of potential Pack-TYPE elements, usually generated via `packSearch`. May be retrieved using `getPacksFromCsv`.

**Usage**

```
packsToCsv(packMatches, file)
```

**Arguments**

packMatches	A data frame containing genomic ranges and names referring to sequences to be extracted. Can be obtained from <a href="#">packSearch</a> or generated from a <a href="#">GRanges</a> object, after conversion to a data frame. Must contain the following features: <ul style="list-style-type: none"><li>• start - the predicted element's start base sequence position.</li><li>• end - the predicted element's end base sequence position.</li><li>• seqnames - character string referring to the sequence name in Genome to which start and end refer to.</li></ul>
file	CSV file save path.

**Value**

Save location of csv file.

**Author(s)**

Jack Gisby

**See Also**

[getPacksFromCsv](#), [write.table](#), [packSearch](#)

**Examples**

```
data(packMatches)

packsToCsv(
  packMatches,
  system.file("extdata", "packMatches.csv", package = "packFinder")
)
```

---

packsToFasta

*Save packFinder Results in FASTA Format (.fasta)*

---

**Description**

Saves a data frame of potential Pack-TYPE elements, usually generated via [packSearch](#). May be retrieved using [getPacksFromFasta](#).

**Usage**

```
packsToFasta(packMatches, file, Genome)
```

**Arguments**

packMatches	taframe containing genomic ranges and names referring to sequences to be extracted. Can be obtained from <a href="#">packSearch</a> or generated from a <a href="#">GRanges</a> object, after conversion to a dataframe. Must contain the following features:
	<ul style="list-style-type: none"> <li>• start - the predicted element's start base sequence position.</li> <li>• end - the predicted element's end base sequence position.</li> <li>• seqnames - character string referring to the sequence name in Genome to which start and end refer to.</li> </ul>
file	FASTA file save path.
Genome	A DNAStringSet object containing sequences referred to in packMatches (the object originally used to predict the transposons <a href="#">packSearch</a> ).

**Value**

Save location of Fasta file.

**Author(s)**

Jack Gisby

**See Also**

[getPacksFromFasta](#), [packSearch](#)

**Examples**

```
data(arabidopsisThalianaRefseq)
data(packMatches)

packsToFasta(
  packMatches,
  system.file("extdata", "packMatches.fasta", package = "packFinder"),
  arabidopsisThalianaRefseq
)
```

---

packsToGRanges

*Export packFinder Results to a GRanges Object*

---

**Description**

A dataframe containing genomic ranges and names referring to sequences to be extracted, likely obtained from [packSearch](#), can be converted to a [GRanges](#) object. Can be converted back to a dataframe using [getPacksFromGRanges](#). Additional features, such as clusters and TSD sequences, will be included in the object as metadata columns.

**Usage**

`packsToGRanges(packMatches)`

**Arguments**

packMatches A dataframe containing genomic ranges and names referring to sequences to be extracted. Can be obtained from [packSearch](#) or generated from a [GRanges](#) object, after conversion to a dataframe. Must contain the following features:

- start - the predicted element's start base sequence position.
- end - the predicted element's end base sequence position.
- seqnames - character string referring to the sequence name in Genome to which start and end refer to.

**Value**

A GRanges object containing the ranges contained in packMatches and additional metadata columns. May be easily converted between dataframe and GRanges format for use in the [packFinder](#) package and [link\[GenomicRanges:GRanges-class\]{GRanges}](#) package. Note that most functions in the [packFinder](#) package require sequence ranges to be provided in dataframe format.

**Author(s)**

Jack Gisby

**See Also**

[getPacksFromGRanges](#), [link\[GenomicRanges:GRanges-class\]{GRanges}](#)

**Examples**

```
data(packMatches)
packGRanges <- packsToGRanges(packMatches)
```

---

readBlast

*Convert NCBI BLAST+ Files to Dataframe*

---

**Description**

Reads .blast6out files (NCBI Blast Format) generated by the VSEARCH clustering and alignment algorithms.

**Usage**

```
readBlast(
  file,
  minE = 1,
  length = 0,
  identity = 0,
  removeExactMatches = FALSE,
  scope = NULL,
  packMatches = NULL
)
```

### Arguments

file	The file path of the blast file.
minE	Blast results with e values greater than the specified cutoff will be ignored.
length	Blast results alignment lengths lower below this value will be ignored
identity	Blast results with target sequence identities below this value will be ignored.
removeExactMatches	If true, matches with 100 be ignored to prevent self-hits.
scope	If specified, blast results below the specified value will be ignored. Note that the dataframe of transposon matches must also be supplied to calculate scope. Scope is the proportion of the transposon's internal sequence occupied by the BLAST hit.
packMatches	taframe containing genomic ranges and names referring to sequences to be extracted. Can be obtained from <a href="#">packSearch</a> or generated from a <a href="#">GRanges</a> object, after conversion to a dataframe. Must contain the following features: <ul style="list-style-type: none"> <li>• start - the predicted element's start base sequence position.</li> <li>• end - the predicted element's end base sequence position.</li> <li>• seqnames - character string referring to the sequence name in Genome to which start and end refer to.</li> </ul>

### Details

blast6out file is tab-separated text file compatible with NCBI BLAST m8 and NCBI BLAST+ outfmt 6 formats. One cluster/alignment can be found for each line.

### Value

A dataframe containing the converted .blast6out file. The file contains the following features:

- Query sequence ID
- Target sequence ID
- Percentty sequence identity
- Alignment length
- Number of mismatches
- Number of gaps
- Base position of alignment start in query sequence
- Base position of alignment end in query sequence
- Base position of alignment start in target sequence
- Base position of alignment end in target sequence
- E-value
- Bit score

### Author(s)

Jack Gisby

## References

For further information, see the NCBI BLAST+ application documentation and help pages (<https://www.ncbi.nlm.nih.gov>). VSEARCH may be downloaded from <https://github.com/torognes/vsearch>; see <https://www.ncbi.nlm.nih.gov/pubmed/27781170> for further information.

## See Also

[codeblastAnalysis](#), [codeblastAnnotate](#), [codepackAlign](#), [codereadUc](#), [codepackClust](#)

## Examples

```
readBlast(system.file(  
  "extdata",  
  "packMatches.blast6out",  
  package = "packFinder"  
)
```

---

readUc

*Convert .uc Files to Dataframe*

---

## Description

Reads .uc files (USEARCH Cluster Format) generated by the VSEARCH clustering and alignment algorithms.

## Usage

```
readUc(file, output = "cluster")
```

## Arguments

file	The file path of the .uc file.
output	The type of analysis that was carried out to produce the .uc file. <ul style="list-style-type: none"><li>• If output is specified as "cluster", VSEARCH clustering was carried out.</li><li>• If output is specified as "alignment", VSEARCH pairwise global alignment was carried out.</li></ul>

Note that clustering produces one "H" record for each sequence, and one "C" record for each cluster, while an alignment produces an "H" record for each alignment (see details).

## Details

USEARCH cluster format is a tab separated text file that contains clustering and/or alignment information for a set of sequences. For each sequence a record type, "H, C or N", is provided providing information about the type of "hit" in the dataframe. These refer to:

- H - Hit - for alignments, indicates an identified alignment of two supplied sequences. For clustering, indicates the cluster assignment for a query.
- C - Cluster record - a record for each cluster generated.

- N - No hit - indicates that no cluster was assigned or no alignment was found with a target sequence. For clustering, a query with no hits becomes the centroid of a new cluster.

Additionally, for each record a "compressed alignment" is generated. This is the alignment represented in a compact format including the letters "M", "D", and "I". Before each letter, the number of consecutive columns of the given letter type is also given. The letter types are as follows:

- "M" - Match - Identical bases between the query and target sequence
- "D" - Deletion - A gap in the target sequence
- "I" - Insertion - A gap in the query sequence

An example of this would be "13M", referring to 13 consecutive matches between the query and target sequence.

### Value

A dataframe containing the converted .uc file. The fields contained within are as follows:

- Record type - "H, C or N", see details for further information.
- Cluster designation (output = "cluster" only)
- Sequence length, or cluster size
- Percent identity to target
- The nucleotide strand (output = "cluster" only)
- A compressed alignment - see details for further information.
- ID of query sequence
- ID of target sequence ("H" records only)

### Author(s)

Jack Gisby

### References

VSEARCH may be downloaded from <https://github.com/torognes/vsearch>. See <https://www.ncbi.nlm.nih.gov/pubmed/27781170> for further information.

### See Also

[codetirClust](#), [codepackAlign](#), [codereadBlast](#), [codepackClust](#)

### Examples

```
readUc(system.file(
  "extdata",
  "packMatches.uc",
  package = "packFinder"
))
```

---

**tirClust***Analyse TIR Sequences of Pre-clustered Transposable Elements*

---

**Description**

Takes transposable elements clustered by VSEARCH, [packClust](#), and produces consensus sequences for the terminal inverted repeats of each. Allows for the visualisation of TIR similarities between clusters for both forward and reverse strands.

**Usage**

```
tirClust(  
  packMatches,  
  Genome,  
  tirLength = 25,  
  plot = TRUE,  
  plotSavePath = NULL,  
  k = 5,  
  output = "consensus"  
)
```

**Arguments**

packMatches	A datafame containing genomic ranges and names referring to sequences to be extracted. This datafame is in the format produced by coercing a <a href="#">link[GenomicRanges:GRanges-class]</a> object to a datafame: <code>data.frame(GRanges)</code> . Must contain the following features: <ul style="list-style-type: none"><li>• start - the predicted element's start base sequence position.</li><li>• end - the predicted element's end base sequence position.</li><li>• seqnames - character string referring to the sequence name in Genome to which start and end refer to.</li></ul>
Genome	A DNAStringSet object containing sequences referred to in packMatches (the object originally used to predict the transposons <a href="#">packSearch</a> ).
tirLength	The TIR size to be considered. Consensus sequences will be generated based on the first and last tirLength bases of a transposon.
plot	Argument specifying whether the TIR consensus sequences should be plotted as a dendrogram.
plotSavePath	File path for the dendrogram plot. If unspecified, the dendrogram plot is not saved.
k	The k-mer size to be used for calculating a distance matrix between TIR consensus sequences. See <a href="#">kdistance</a> . Larger word sizes will not be suitable for longer TIR sequences, due to processing time required. Additionally, k must be greater than the TIR sequence length.
output	Controls the output of tirClust. If output is specified as "consensus", the consensus sequences of each TIR cluster will be returned; else, if output is specified as "dendrogram", a dendrogram object will be returned for creation of customisable plots.

**Value**

If `output` is specified as "consensus" (default), returns a list of consensus sequences for each cluster specified in `packMatches` as a [DNAStringSet](#). Else if `output` is specified as "dendrogram", returns a dendrogram object used to create hierarchical clustering diagrams.

**Author(s)**

Jack Gisby

**See Also**

[codepackClust](#), [codepackAlign](#), [kdistance](#), [DNAStringSet](#), [as.alignment](#), [packSearch](#)

**Examples**

```
data(arabidopsisThalianaRefseq)
data(packMatches)

tirClust(packMatches, arabidopsisThalianaRefseq)
```

# Index

\* datasets  
arabidopsisThalianaRefseq, 2  
packMatches, 23

arabidopsisThalianaRefseq, 2, 24  
as.alignment, 34

blastAnalysis, 3, 5, 20, 31  
blastAnnotate, 4, 5, 20, 31

collapseSeqs, 6

data.frame, 24  
DNAString, 2, 3, 8, 15, 25, 26  
DNAStringSet, 2, 3, 8, 12, 14, 15, 25, 26, 34

filterWildcards, 7, 18, 22

getGenome, 3  
getPackSeqs, 8  
getPacksFromCsv, 9, 26, 27  
getPacksFromFasta, 10, 27, 28  
getPacksFromGRanges, 11, 28, 29  
getTsds, 12, 13, 25, 26  
GRanges, 27–30

identifyPotentialPackElements, 13, 25,  
26  
identifyTirMatches, 13, 14, 25, 26

kdistance, 33, 34

makeBlastDb, 16  
matchPattern, 13, 15, 25, 26

packAlign, 7, 17, 21, 22, 31, 32, 34  
packBlast, 4, 5, 18  
packClust, 7, 17, 18, 21, 24–26, 31–34  
packFinder, 22  
packMatches, 23, 23, 26  
packSearch, 3–13, 15–24, 24, 26–30, 33, 34  
packsToCsv, 9, 26  
packsToFasta, 10, 27  
packsToGRanges, 11, 28

read.table, 9

readBlast, 4, 5, 18, 20, 22, 29, 32  
readUc, 18, 22, 31, 31

tirClust, 18, 21, 22, 32, 33

write.table, 27