

Package ‘qcmetrics’

January 20, 2026

Type Package

Title A Framework for Quality Control

Version 1.48.0

Description The package provides a framework for generic quality control of data. It permits to create, manage and visualise individual or sets of quality control metrics and generate quality control reports in various formats.

Depends R (>= 3.3)

Imports Biobase, methods, knitr, tools, xtable, pander, S4Vectors

Suggests affy, MSnbase, ggplot2, lattice, mzR, BiocStyle, rmarkdown, markdown

License GPL-2

URL <http://lgatto.github.io/qcmetrics/articles/qcmetrics.html>

BugReports <https://github.com/lgatto/qcmetrics/issues>

biocViews ImmunoOncology, Software, QualityControl, Proteomics, Microarray, MassSpectrometry, Visualization, ReportWriting

VignetteBuilder knitr

RoxygenNote 6.1.0

git_url <https://git.bioconductor.org/packages/qcmetrics>

git_branch RELEASE_3_22

git_last_commit 7058a53

git_last_commit_date 2025-10-29

Repository Bioconductor 3.22

Date/Publication 2026-01-19

Author Laurent Gatto [aut, cre]

Maintainer Laurent Gatto <laurent.gatto@uclouvain.be>

Contents

n15qc	2
psm	3
Qc2Tex	3

QcMetadata-class	4
QcMetric-class	5
QcMetrics-class	7
qcReport-methods	8

Index

10

n15qc

N15 labelling QC report

Description

A simple wrapper for the QC of 15N labelling. The respective QC items are the distribution of PSM incorporation rates, distribution of log2 fold-changes and number of identified features. See the vignette for details.

Usage

```
n15qc(object,
      fcol = c("Protein_Accession", "Peptide_Sequence", "Number_Of_Unique_Peptides", "Variable_Modifications"),
      inctr = 97.5, lfctr = c(-0.5, 0.5), type, reportname)
```

Arguments

object	An MSnSet to be quality controlled.
fcol	The name of the feature variables for the protein identifiers (accession numbers for example), the peptide sequences, the number of unique peptides for each identified protein, the variable modifications identified on the peptides and the N15 incorporation rate. These must be provided in that order. Defaults are Protein_Accession, Peptide_Sequence, Number_Of_Unique_Peptides, Variable_Modifications, and inc.
inctr	The minimum level of median incorporation rate to set the QC item status to TRUE. Default is 97.5.
lfctr	The range of accepted median PSM log2 fold-change for the QC item status to be set to TRUE. Default is c(-0.5, 0.5).
type	The type of report to be saved. If missing (default), no report is generated. See qcReport for details.
reportname	The name of the report, in case a type is defined. If missing (default), the report will be names n15qcreport followed by the generation date and time.

Value

Invisibly returns the resulting QcMetrics instance.

Author(s)

Laurent Gatto

psm

15N example data

Description

An example data for 15N metabolic labelling, distributed as an MSnSet to illustrate 15N QC.

Usage

```
data(n15psm)
```

References

See MSnSet and the MSnbase-demo vignette in the MSnbase package.

Examples

```
library("MSnbase")
data(n15psm)
psm
```

Qc2Tex

'QcMetric' sectioning functions

Description

These functions convert the *i*th QcMetric instance of the QcMetrics object into a section of the adequate format, i.e. TeX or R markdown.

Usage

```
Qc2Tex(object, i)
Qc2Tex2(object, i)
Qc2Tex3(object, i)
Qc2Rmd(object, i)
```

Arguments

object	An instance of class QcMetrics with at least one QC item.
i	A numeric of length 1 indicating the index of the item to be converted into text section.

Value

A character representing the QC item section.

Author(s)

Laurent Gatto

See Also

[qcReport](#) and the vignette.

QcMetadata-class	<i>The "QcMetadata" class</i>
------------------	-------------------------------

Description

The QcMetadata class is a simple interface to metadata. The objects can be displayed with `show` for a summary and `print` for the content.

Objects from the Class

Objects can be created by calls of the form `QcMetadata(...)`.

Slots

metadata: Object of class "list" that stores the metadata variables. The list must be named. NA and empty characters are not allowed.

Methods

`[` `signature(x = "QcMetadata")`: subsets `x` as a new QcMetadata instance.
`[[` `signature(x = "QcMetadata")`: extracts a single element of `x`.
`metadata` `signature(x = "QcMetadata")`: return the object's metadata list. Also available as `mdata`.
`metadata<-` `signature(x = "QcMetadata", value = "list")`: sets the objects metadata. Also available as `mdata`.
`length` `signature(x = "QcMetadata")`: returns the number of metadata variables.
`names` `signature(x = "QcMetadata")`: returns the names of the metadata variables.

Author(s)

Laurent Gatto

Examples

```

QcMetadata(metadata =
  list(name = "John Doe",
       lab = "Big Lab in Big Uni"))
## less typing
qmd <- QcMetadata(list(name = "John Doe",
                        lab = "Big Lab in Big Uni"))
mdata(qmd)
show(qmd)
print(qmd)
  
```

QcMetric-class	<i>The "QcMetric" class for QC items</i>
----------------	--

Description

Data structure for individual QC metrics items.

Objects from the Class

Objects can be created using the constructor `QcMetric(...)`, where slots are assigned individually. See example below.

Slots

name: Object of class "character" of length 1 naming the object.
description: Object of class "character" of arbitrary length describing the qc metric in more details.
qcdata: Object of class "environment" that stores the actual data.
plot: Object of class "function" to graphically represent the data and infer quality status.
show: Object of class "function" to print a short textual representation of the object. A reasonable default value is provided.
status: Object of class "logical" that indicates whether the data passes (TRUE) or fails (FALSE) the metric or has not yet been evaluated.

Methods

name `signature(object = "QcMetric")`: retrieves the name of the object.
name<- `signature(object = "QcMetric", value = "character")`: set the name of the object.
description `signature(object = "QcMetric")`: retrieves the description of the object.
description<- `signature(object = "QcMetric", value = "character")`: set the description of the object.
status `signature(object = "QcMetric")`: retrieves the status of the object.
status<- `signature(object = "QcMetric", value = "logical")`: sets the status of the objects.
qcdata `signature(object = "QcMetric", x = "missing")`: lists all the data objects that are associated with the objects.
qcdata `signature(object = "QcMetric", x = "character")`: retrieves the variable x for the object.
qcdata<- `signature(object = "QcMetric", var)`: creates or overwrites (with a message) the data variable var by assigning the RHS value. If var is missing and the RHS expression is an environment, then qcdata is reset with all the variables in value.
qcenv `signature(object = "QcMetric")`: return the environment that stores the QC data.
qcenv<- `signature(object = "QcMetric")`: Set all variable in the RHS environment as qcdata variables. Equivalent to `qcdata(object) <- x` where x is an environment.
show `signature(object = "QcMetric")`: shows a textual summary of object. The default show implementation is available as the `qcshow{object, qcdata}` function. The second argument is a logical (default is TRUE) that specifies whether `qcdata(object)` should be displayed.

show<- `signature(object = "QcMetric", value = "function")`: sets a custom show method for object.

plot `signature(x = "QcMetric", y = "missing")`: plots the object using the provide show method.

plot<- `signature(object = "QcMetric", value = "function")`: sets a custom plot method for object.

qcReport `signature(x = "QcMetric", ...)`: to generate quality reports. See [qcReport](#) for details.

Author(s)

Laurent Gatto

See Also

The [QcMetrics](#) class to bundle a set of QcMetric instances.

Examples

```
(qc <- QcMetric())
qadata(qc)
try(qadata(qc, "x"))

x <- rnorm(10)
qadata(qc, "qc1") <- x
qadata(qc, "qc2") <- 1:10
qadata(qc)
all.equal(qadata(qc, "qc1"), x)
all.equal(qadata(qc, "qc2"), 1:10)
name(qc) <- "My test QcMetric"
description(qc) <- "This qc metric describes bla bla bla, indicating possible issues in the third step of protocol"
status(qc) <- FALSE
qc

## or
e <- new.env()
e$qc1 <- rnorm(100)
e$qc2 <- 1:100
qcenv(qc) <- e
length(qadata(qc, "qc1"))
head(qadata(qc, "qc2"))

show(qc)
show(qc) <- function(object) cat("Updated show method\n")
show(qc)
show(qc) <- qcshow
qc

plot(qc)
plot(qc) <-
  function(object, ...)
    plot(qadata(object, "qc2"),
         qadata(object, "qc1"),
         xlab = "qc1",
         ylab = "qc2",
```

```
    ...)  
plot(qc)  
plot(qc, col = "red", pch = 19)
```

QcMetrics-class	<i>The "QcMetrics" class for collections of QC items</i>
-----------------	--

Description

Data structure for storing lists of QcMetric items.

Objects from the Class

Objects can be created using the constructor `QcMetrics(...)`, where slots are assigned individually. See example below.

In a standardised quality control pipeline, the `QcMetrics` and `QcMetric` object are not generated manually. Their creation is delegated to a wrapper function that reads a specific type of files, parses the data, produces the individual `QcMetric` instances and, eventually, the `QcMetric` object. See the package vignette for details and examples.

Slots

metadata: Object of class `QcMetadata` storing the metadata of the object. This list would typically contain the input file the data was read from, the date the object was generated, ... or fully fledged *minimum information* descriptions (see [MIAxE](#)), when available.

qadata: Object of class "list" storing all the individual `QcMetric` instances.

Methods

```
[ signature(x = "QcMetrics"): subsets x as a new QcMetrics instance.  
[[ signature(x = "QcMetrics"): extracts a single QcMetric instance.  
length signature(x = "QcMetrics"): returns the number of QcMetric instances populate x.  
metadata signature(x = "QcMetrics"): return the object's metadata list. Also available as mdata.  
metadata<- signature(x = "QcMetrics", value = "list"): sets the objects metadata. Also available as mdata.  
metadata<- signature(x = "QcMetric", value = "QcMetadata"): sets the objects metadata. Also available as mdata.  
name signature(object = "QcMetrics"): returns a character vector of length length(object) with the names of the QcMetric instances.  
qadata signature(object = "QcMetrics", x = "missing"): returns a list of all QcMetric instances.  
qadata<- signature(object = "QcMetrics", value = "list"): sets the qadata of object.  
show signature(object = "QcMetrics"): prints a short textual description of object.  
status signature(object = "QcMetrics"): returns a vector of quality statuses (logicals).  
status<- signature(object = "QcMetrics", value = "logical"): sets the quality statuses. Length of value and object must be identical.
```

```
as.signature(object = "QcMetrics", "data.frame"): coerces object as a length(object)
by 2 data frame with the respective QcMetric instances names and statuses.
qcReport signature(object = "QcMetrics"): ...
```

Author(s)

Laurent Gatto

See Also

The [QcMetric](#) class for individual QC items.

Examples

```
example(QcMetric)
show(qc)

qc2 <- QcMetric(name = "My other metric", status = TRUE)
qcd(data(qc2, "x") <- rnorm(100)
qcd(data(qc2, "k") <- rep(LETTERS[1:2], 50)

plot(qc2) <- function(object, ...) {
  require("lattice")
  d <- data.frame(x = qcd(data(object, "x")),
                   k = qcd(data(object, "k")))
  bwplot(x ~ k, data = d)
}

qcm <- QcMetrics(qcd = list(qc, qc2))
qcm

qcm[1] ## a QcMetrics instance
qcm[[1]] ## a single QcMetric

metadata(qcm)
metadata(qcm) <- QcMetadata(list(name = "Prof. Who",
                                   lab = "Cabin University"))
## or, shorter but equivalent
metadata(qcm) <- list(name = "Prof. Who",
                       lab = "Cabin University")
metadata(qcm) ## or mdata(qcm)
## update metadata
metadata(qcm) <- list(lab = "Big lab", ## updated
                      uni = "Cabin University") ## added
mdata(qcm)
```

Description

The qcReport method generates report in various formats taking a [QcMetrics](#) instance as input. Each individual quality control item produces a section with description of the item and a assessment figure.

Details

The reporting functions take a `QcMetrics` instance as input, generate the source of the report and compile it into the final format that are currently available are `reporting_pdf`, `reporting_tex`, `reporting_rmd` and `reporting_html`. See `qcto` for details about the sectioning functions, that convert individual `QcMetric` objects into adequate report sections.

The package vignette documents the report generation in more details and describes possibilities for customisation.

Methods

```
signature( object = "QcMetrics", reportname = "character", type = "character", author = "character", t
  generates a report for the QcMetrics object. The report will be named according the reportname
  (default is qcreprt) and type, the latter defining the output format and the extension. Possi-
  ble types are pdf (default), "tex", "Rmd", "html" (all generated using the package knitr). A
  custom title can be provided; default is "Quality control report generated with qcmetrics". If no
  author is provided, the default value (Sys.getenv("USER")) is used. The addition of a table of
  contents (default is FALSE), a metadata section, a summary section and the session information
  arguments. The metadata section is added to the report when present and the other have TRUE
  as default.
```

Intermediate files are deleted, unless `clean` is set to `FALSE` and verbose output can be turned on by setting `quiet` to `FALSE`.

The `reporter` and `qcto` arguments are used to convert `QcMetric` and `QcMetrics` objects into report source. See Details and the package vignette for details.

Additional parameters can be passed to inner functions. For the `pdf` report, passed to `texi2pdf`; for `html`, passed to `markdown::markdownToHTML`.

The method invisibly returns the name of the report that was generated.

Examples

```
example(QcMetrics)
show(qcm)

destdir <- tempdir()
(report <- file.path(destdir, "testQCReport"))

## Not run:
## pdf report
qcReport(qcm, reportname = report)
## use pdflatex to generate the pdf file
qcReport(qcm, reportname = report, texi2dvi = "pdflatex")

## End(Not run)

## default html report
html <- qcReport(qcm, reportname = report, type = "html")
html
if (interactive())
  browseURL(html)
```

Index

```
* classes
  QcMetadata-class, 4
  QcMetric-class, 5
  QcMetrics-class, 7
* datasets
  psm, 3
* methods
  qcReport-methods, 8
* report
  qcReport-methods, 8
[[,QcMetadata-method (QcMetadata-class),
  4
[,QcMetrics-method (QcMetrics-class), 7
[[,QcMetadata-method
  (QcMetadata-class), 4
[[,QcMetrics-method (QcMetrics-class), 7
as.data.frame.QcMetrics
  (QcMetrics-class), 7
class:QcMetadata (QcMetadata-class), 4
class:QcMetric (QcMetric-class), 5
class:QcMetrics (QcMetrics-class), 7
description,QcMetric-method
  (QcMetric-class), 5
description<-,QcMetric,character-method
  (QcMetric-class), 5
example_reports (qcReport-methods), 8
length,QcMetadata-method
  (QcMetadata-class), 4
length,QcMetrics-method
  (QcMetrics-class), 7
mdata (QcMetrics-class), 7
mdata,QcMetadata-method
  (QcMetadata-class), 4
mdata,QcMetrics-method
  (QcMetrics-class), 7
mdata<- (QcMetrics-class), 7
mdata<-,QcMetadata,list-method
  (QcMetadata-class), 4
mdata<-,QcMetrics,list-method
  (QcMetrics-class), 7
metadata (QcMetrics-class), 7
metadata,QcMetadata-method
  (QcMetadata-class), 4
metadata,QcMetrics-method
  (QcMetrics-class), 7
metadata<- (QcMetrics-class), 7
metadata<-,QcMetadata,list-method
  (QcMetadata-class), 4
metadata<-,QcMetrics,list-method
  (QcMetrics-class), 7
metadata<-,QcMetrics,QcMetadata-method
  (QcMetrics-class), 7
MIAxE, 7
n15psm (psm), 3
n15qc, 2
name (QcMetrics-class), 7
name ,QcMetric-method (QcMetric-class), 5
name ,QcMetrics-method
  (QcMetrics-class), 7
name<- (QcMetrics-class), 7
name<-,QcMetric,character-method
  (QcMetric-class), 5
name<-,QcMetrics,character-method
  (QcMetrics-class), 7
names ,QcMetadata-method
  (QcMetadata-class), 4
names<- ,QcMetadata,character-method
  (QcMetadata-class), 4
plot,QcMetric,missing-method
  (QcMetric-class), 5
plot<- (QcMetric-class), 5
plot<-,QcMetric,function-method
  (QcMetric-class), 5
print,QcMetadata-method
  (QcMetadata-class), 4
psm, 3
Qc2Rmd (Qc2Tex), 3
```

Qc2Tex, 3
Qc2Tex2 (Qc2Tex), 3
Qc2Tex3 (Qc2Tex), 3
qcdata (QcMetric-class), 5
qcdata, QcMetric, character-method
 (QcMetric-class), 5
qcdata, QcMetric, missing-method
 (QcMetric-class), 5
qcdata, QcMetrics, ANY-method
 (QcMetrics-class), 7
qcdata<- (QcMetric-class), 5
qcdata<-, QcMetric, ANY-method
 (QcMetric-class), 5
qcdata<-, QcMetrics, list-method
 (QcMetrics-class), 7
qcenv (QcMetric-class), 5
qcenv, QcMetric-method (QcMetric-class),
 5
qcenv<- (QcMetric-class), 5
qcenv<-, QcMetric, environment-method
 (QcMetric-class), 5
QcMetadata, 7
QcMetadata (QcMetadata-class), 4
QcMetadata-class, 4
QcMetric, 7, 8
QcMetric (QcMetric-class), 5
QcMetric-class, 5
QcMetrics, 6, 8, 9
QcMetrics (QcMetrics-class), 7
QcMetrics-class, 7
qcReport, 2, 4, 6
qcReport (qcReport-methods), 8
qcReport, QcMetrics-method
 (qcReport-methods), 8
qcReport-methods, 8
qcshow (QcMetric-class), 5
qcto, 9
qcto (Qc2Tex), 3

reporting (qcReport-methods), 8
reporting_html (qcReport-methods), 8
reporting_pdf (qcReport-methods), 8
reporting_rmd (qcReport-methods), 8
reporting_tex (qcReport-methods), 8

show, QcMetadata-method
 (QcMetadata-class), 4
show, QcMetric-method (QcMetric-class), 5
show, QcMetrics-method
 (QcMetrics-class), 7
show<- (QcMetric-class), 5
show<-, QcMetric, function-method
 (QcMetric-class), 5
status (QcMetric-class), 5
status, QcMetric-method
 (QcMetric-class), 5
status, QcMetrics-method
 (QcMetrics-class), 7
status<- (QcMetric-class), 5
status<-, QcMetric, logical-method
 (QcMetric-class), 5
status<-, QcMetrics, logical-method
 (QcMetrics-class), 7