

# Package ‘rsbml’

January 20, 2026

**Version** 2.68.0

**Title** R support for SBML, using libsbml

**Author** Michael Lawrence <michafla@gene.com>

**Depends** R (>= 2.6.0), BiocGenerics (>= 0.3.2), methods, utils

**Imports** BiocGenerics, graph, utils

**SystemRequirements** libsbml (==5.10.2)

**Maintainer** Michael Lawrence <michafla@gene.com>

**Description** Links R to libsbml for SBML parsing, validating output, provides an S4 SBML DOM, converts SBML to R graph objects. Optionally links to the SBML ODE Solver Library (SOSLib) for simulating models.

**License** Artistic-2.0

**URL** <http://www.sbml.org>

**biocViews** GraphAndNetwork, Pathways, Network

**git\_url** <https://git.bioconductor.org/packages/rsbml>

**git\_branch** RELEASE\_3\_22

**git\_last\_commit** 8d17d9d

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.22

**Date/Publication** 2026-01-19

## Contents

AlgebraicRule-class . . . . .	3
AssignmentRule-class . . . . .	4
BoundingBox-class . . . . .	5
Compartment-class . . . . .	6
CompartmentGlyph-class . . . . .	7
CompartmentType-class . . . . .	8
CompartmentVolumeRule-class . . . . .	9
Constraint-class . . . . .	10
CubicBezier-class . . . . .	11
Curve-class . . . . .	12
CVTerm-class . . . . .	13

Delay-class . . . . .	14
describe . . . . .	15
Dimensions-class . . . . .	15
Event-class . . . . .	16
EventAssignment-class . . . . .	18
Experiment-class . . . . .	19
FunctionDefinition-class . . . . .	20
GraphicalObject-class . . . . .	21
InitialAssignment-class . . . . .	22
KineticLaw-class . . . . .	23
Layout-class . . . . .	24
LineSegment-class . . . . .	25
math . . . . .	26
Model-class . . . . .	27
ModelCreator-class . . . . .	29
ModelHistory-class . . . . .	30
ModifierSpeciesReference-class . . . . .	31
Parameter-class . . . . .	32
ParameterRule-class . . . . .	33
Point-class . . . . .	34
RateRule-class . . . . .	35
Reaction-class . . . . .	36
ReactionGlyph-class . . . . .	37
Rule-class . . . . .	39
SBase-class . . . . .	40
SBML import . . . . .	41
SBML-class . . . . .	42
SBMLDocument-class . . . . .	43
SBMLProblem-class . . . . .	45
SBMLProblems-class . . . . .	45
SimpleSpeciesReference-class . . . . .	46
SOSDesign-class . . . . .	47
SOSExperiment-class . . . . .	48
SOSProtocol-class . . . . .	50
SOSResult-class . . . . .	51
SOSSubject-class . . . . .	52
Species-class . . . . .	53
SpeciesConcentrationRule-class . . . . .	55
SpeciesGlyph-class . . . . .	56
SpeciesReference-class . . . . .	57
SpeciesReferenceGlyph-class . . . . .	58
SpeciesType-class . . . . .	59
StoichiometryMath-class . . . . .	60
TextGlyph-class . . . . .	61
Trigger-class . . . . .	62
Unit-class . . . . .	63
UnitDefinition-class . . . . .	64

---

AlgebraicRule-class     SBML type "AlgebraicRule"

---

## Description

Expresses equations that are not assignments nor rates of change.

## Instantiation

Objects can be created by calls of the form `new("AlgebraicRule", ...)`.

## Slots

**math:** Object of class "expression" specifying the equation.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[Rule](#)", directly. Class "[SBase](#)", by class "Rule", distance 2.

## Methods

No methods defined with class "AlgebraicRule" in the signature.

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

---

AssignmentRule-class    SBML type "AssignmentRule"

---

## Description

An equation that assigns a value to the quantity of a [Species](#), the size of a [Compartment](#) or the value of a [Parameter](#).

## Instantiation

Objects can be created by calls of the form `new("AssignmentRule", ...)`.

## Slots

**variable:** Object of class "character" naming the variable (the id of a [Species](#), [Compartment](#) or [Parameter](#)) to set.

**type:** Object of class "character", deprecated.

**math:** Object of class "expression" specifying the equation.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[Rule](#)", directly. Class "[SBase](#)", by class "Rule", distance 2.

## Methods

**variable** `signature(object = "AssignmentRule")`: gets the variable slot

**variable<-** `signature(object = "AssignmentRule")`: sets the variable slot

**type** `signature(object = "AssignmentRule")`: gets the type slot

**type<-** `signature(object = "AssignmentRule")`: sets the type slot

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

---

BoundingBox-class      *SBML type "BoundingBox"*

---

## Description

Specifies the size and position of an SBML layout object.

## Instantiation

Objects can be created by calls of the form `new("BoundingBox", ...)`.

## Slots

**id:** Object of class "character" uniquely identifying this component.

**position:** Object of class "Point" specifying the position.

**dimensions:** Object of class "Dimensions" specifying the size.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

**id** `signature(object = "BoundingBox")`: gets the id slot

**id<-** `signature(object = "BoundingBox")`: sets the id slot

**dimensions** `signature(object = "BoundingBox")`: gets the dimensions slot

**dimensions<-** `signature(object = "BoundingBox")`: sets the dimensions slot

**position** `signature(object = "BoundingBox")`: gets the position slot

**position<-** `signature(object = "BoundingBox")`: sets the position slot

## Author(s)

Michael Lawrence

## References

<http://projects.villa-bosch.de/bcb/sbml>

---

Compartment-class	SBML type "Compartment"
-------------------	-------------------------

---

## Description

A bounded space that contains [Species](#).

## Instantiation

Objects can be created by calls of the form `new("Compartment", ...)`.

## Slots

**id:** Object of class "character" uniquely identifying this component.

**name:** Object of class "character" naming this component.

**spatialDimensions:** Object of class "integer" indicating the number of dimensions (0, 1, 2, or 3)

**size:** Object of class "numeric" indicating the size in the given units.

**units:** Object of class "character" indicating the units (built-in or the id of a [UnitDefinition](#)).

**outside:** Object of class "character" identifying the compartment containing this compartment.

**constant:** Object of class "logical" indicating whether the size changes during simulation.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

```

id signature(object = "Compartment"): gets the id slot
id<- signature(object = "Compartment"): sets the id slot
name signature(object = "Compartment"): gets the name slot
name<- signature(object = "Compartment"): sets the name slot
constant signature(object = "Compartment"): gets the constant slot
constant<- signature(object = "Compartment"): sets the constant slot
outside signature(object = "Compartment"): gets the outside slot
outside<- signature(object = "Compartment"): sets the outside slot

```

```
size signature(object = "Compartment"): gets the size slot
size<- signature(object = "Compartment"): sets the size slot
units signature(object = "Compartment"): gets the constant slot
units<- signature(object = "Compartment"): sets the constant slot
spatialDimensions signature(object = "Compartment"): gets the spatialDimensions slot
spatialDimensions<- signature(object = "Compartment"): sets the spatialDimensions slot
```

### Author(s)

Michael Lawrence

### References

<http://sbml.org/documents/>

---

CompartmentGlyph-class

SBML type "CompartmentGlyph"

---

### Description

A glyph representing a [Compartment](#).

### Instantiation

Objects can be created by calls of the form new("CompartmentGlyph", ...).

### Slots

**compartment:** Object of class "character" identifying the compartment this glyph represents.  
**id:** Object of class "character" uniquely identifying this component.  
**boundingBox:** Object of class "BoundingBox" describing the position and size of the graphical object.  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

### Extends

Class "[GraphicalObject](#)", directly. Class "[SBase](#)", by class "GraphicalObject", distance 2.

## Methods

**compartment** signature(object = "CompartmentGlyph"): gets the compartment slot  
**compartment<-** signature(object = "CompartmentGlyph"): sets the compartment slot

## Author(s)

Michael Lawrence

## References

<http://projects.villa-bosch.de/bcb/sbml>

---

CompartmentType-class *SBML Type "CompartmentType"*

---

## Description

Declares a type of [Compartment](#). Compartments with the same type are logically similar.

## Objects from the Class

Objects can be created by calls of the form new("CompartmentType", ...).

## Slots

**id:** Object of class "character" uniquely identifying this component.  
**name:** Object of class "character" naming this component.  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

**id** signature(object = "CompartmentType"): gets the id slot  
**id<-** signature(object = "CompartmentType"): sets the id slot  
**name** signature(object = "CompartmentType"): gets the name slot  
**name<-** signature(object = "CompartmentType"): sets the name slot

**Note**

Requires libsbml >= 3.0

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

**See Also**

[Compartment](#)

---

CompartmentVolumeRule-class

*SBML type "CompartmentVolumeRule"*

---

**Description**

**Obsolete** way to assign a volume to a [Compartment](#).

**Instantiation**

Objects can be created by calls of the form new("CompartmentVolumeRule", ...).

**Slots**

**compartment:** Object of class "character" identifying the compartment  
**variable:** Object of class "character", ignored.  
**type:** Object of class "character", deprecated.  
**math:** Object of class "expression" specifying the equation.  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[AssignmentRule](#)", directly. Class "[Rule](#)", by class "AssignmentRule", distance 2. Class "[SBase](#)", by class "AssignmentRule", distance 3.

## Methods

**compartment** signature(object = "CompartmentVolumeRule"): gets the compartment slot  
**compartment<-** signature(object = "CompartmentVolumeRule"): sets the compartment slot

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

---

Constraint-class      *SBML Type "Constraint"*

---

## Description

A constraint that must be continuously satisfied throughout the simulation of a model. Once a constraint is no longer met, the simulation must halt.

## Objects from the Class

Objects can be created by calls of the form new("Constraint", ...).

## Slots

**math:** Object of class "expression" that evaluates to FALSE if the constraint is not satisfied, otherwise evaluates to TRUE.

**message:** Object of class "character", formatted in XHTML, that is displayed to the user by an application when the constraint is not satisfied.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

**math** signature(domain = "Constraint"): gets the math slot.  
**math<-** signature(object = "Constraint"): sets the math slot.  
**msg** signature(domain = "Constraint"): gets the msg slot.  
**msg<-** signature(object = "Constraint"): sets the msg slot.

**Note**

Requires libsbml >= 3.0

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

---

CubicBezier-class      SBML type "CubicBezier"

---

**Description**

A cubic bezier curve in an SBML layout.

**Instantiation**

Objects can be created by calls of the form new("CubicBezier", ...).

**Slots**

**basePoint1:** Object of class "Point" indicating the position of the base point closest to the starting point.

**basePoint2:** Object of class "Point" indicating the position of the base point farthest from the starting point.

**start:** Object of class "Point" ~~

**end:** Object of class "Point" ~~

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[LineSegment](#)", directly. Class "[SBase](#)", by class "LineSegment", distance 2.

**Methods**

**basePoint1** signature(object = "CubicBezier"): gets the basePoint1 slot

**basePoint1<-** signature(object = "CubicBezier"): sets the basePoint1 slot

**basePoint2** signature(object = "CubicBezier"): gets the basePoint2 slot

**basePoint2<-** signature(object = "CubicBezier"): sets the basePoint2 slot

**Author(s)**

Michael Lawrence

**References**

<http://projects.villa-bosch.de/bcb/sbml>

---

Curve-class	<i>SBML type "Curve"</i>
-------------	--------------------------

---

**Description**

A curve (list of line segments) in an SBML layout.

**Instantiation**

Objects can be created by calls of the form `new("Curve", ...)`.

**Slots**

**curveSegments:** Object of class "list" containing the [LineSegments](#) that compose the curve.  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[SBase](#)", directly.

**Methods**

**curveSegments** `signature(object = "Curve")`: gets the curveSegments slot  
**curveSegments<-** `signature(object = "Curve")`: sets the curveSegments slot

**Author(s)**

Michael Lawrence

**References**

<http://projects.villa-bosch.de/bcb/sbml>

---

CVTerm-class	<i>SBML Type "CVTerm"</i>
--------------	---------------------------

---

## Description

A MIRIAM annotation, consisting of a qualifier ("model", "biological" or something else) and a resource (URI).

## Objects from the Class

Objects can be created by calls of the form `new("CVTerm", ...)`.

## Slots

**qualifierType:** Object of class "character" specifying the type of qualifier for this term. Types "model" and "biological" have special meaning, but any string may be specified.

**modelQualifierType:** Object of class "character" specifying the type of model qualifier, if `qualifierType` is set to "model". Types "is" and "isDescribedBy" are formally defined in MIRIAM, but any string may be specified.

**biologicalQualifierType:** Object of class "character" specifying the type of biological qualifier, if `qualifierType` is set to "biological". Types "is", "hasPart", "isPartOf", "isVersionOf", "hasVersion", "isHomologTo", and "isDescribedBy" are formally defined in MIRIAM, though any string may be specified.

**resources:** Object of class "character" specifying a URI that identifies some resource related an SBML element by the qualifier.

## Methods

**biologicalQualifierType** `signature(object = "CVTerm")`: gets the `biologicalQualifierType` slot.

**biologicalQualifierType<-** `signature(object = "CVTerm")`: sets the `biologicalQualifierType` slot.

**modelQualifierType** `signature(object = "CVTerm")`: gets the `modelQualifierType` slot.

**modelQualifierType<-** `signature(object = "CVTerm")`: sets the `modelQualifierType` slot.

**qualifierType** `signature(object = "CVTerm")`: gets the `qualifierType` slot.

**qualifierType<-** `signature(object = "CVTerm")`: sets the `qualifierType` slot.

**resources** `signature(object = "CVTerm")`: gets the `resources` slot.

**resources<-** `signature(object = "CVTerm")`: sets the `resources` slot.

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

---

Delay-class	SBML Type "Delay"
-------------	-------------------

---

## Description

The length of time between the [Triggering](#) of an [Event](#) and the execution of its [EventAssignments](#).

## Objects from the Class

Objects can be created by calls of the form `new("Delay", ...)`.

## Slots

**math:** Object of class "expression" that evaluates to a quantity of time.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

**math** `signature(domain = "Delay")`: gets the `math` slot.

**math<-** `signature(object = "Delay")`: sets the `math` slot.

## Note

Requires libsbml  $\geq 3.0$

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

## See Also

[Event](#)

---

**describe***Describing objects*

---

## Description

Each class in the SBML DOM extends the Describable class and thus has a `describe` method, which describes an object with a short string. This is used by the `show` method to output terse textual representations of the DOM.

## Usage

```
describe(object, ...)
```

## Arguments

object	The object to be described.
...	Additional arguments for methods.

## Value

A short textual (string) representation of `object`.

## Describable objects

An object that extends Describable has a method for the `describe` generic, and by default Describable objects are shown by printing the output of `describe`. Note that Describable is a virtual tag class, no objects may be created from it.

## Describable methods

`show` signature(`object = "Describable"`): outputs the return value of `describe`.

## Author(s)

Michael Lawrence

---

**Dimensions-class***SBML type "Dimensions"*

---

## Description

Holds the size of an SBML layout object.

## Instantiation

Objects can be created by calls of the form `new("Dimensions", ...)`.

**Slots**

**width:** Object of class "numeric" indicating the width, in pixels  
**height:** Object of class "numeric" indicating the height, in pixels  
**depth:** Object of class "numeric" indicating the depth, in pixels  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[SBase](#)", directly.

**Methods**

**depth** `signature(object = "Dimensions")`: gets the depth slot  
**depth<-** `signature(object = "Dimensions")`: sets the depth slot  
**height** `signature(object = "Dimensions")`: gets the height slot  
**height<-** `signature(object = "Dimensions")`: sets the height slot  
**width** `signature(object = "Dimensions")`: gets the width slot  
**width<-** `signature(object = "Dimensions")`: sets the width slot

**Author(s)**

Michael Lawrence

**References**

<http://projects.villa-bosch.de/bcb/sbml>

---

Event-class

*SBML type "Event"*

---

**Description**

Description of a instantaneous, discontinuous change in the model state.

**Instantiation**

Objects can be created by calls of the form `new("Event", ...)`.

## Slots

**id:** Object of class "character" uniquely identifying this component.  
**name:** Object of class "character" naming this component.  
**trigger:** Object of class "expression" that evaluates to TRUE when the event is to be fired.  
**eventDelay:** Object of class "expression" that evaluates to the time until execution of this event after it has been fired.  
**timeUnits:** Object of class "character" identifying the units of the delay.  
**eventAssignments:** Object of class "list" containing [EventAssignments](#) that are performed at execution.  
**useValuesFromTriggerTime:** Object of class "logical". If FALSE, the event is evaluated after the delay, rather than when the event is executed.  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

```

id signature(object = "Event"): gets the id slot
id<- signature(object = "Event"): sets the id slot
name signature(object = "Event"): gets the name slot
name<- signature(object = "Event"): sets the name slot
timeUnits signature(object = "Event"): gets the timeUnits slot
timeUnits<- signature(object = "Event"): sets the timeUnits slot
eventDelay signature(x = "Event"): ...
eventDelay<- signature(object = "Event"): sets the delay slot
eventAssignments signature(object = "Event"): gets the eventAssignments slot
eventAssignments<- signature(object = "Event"): sets the eventAssignments slot
trigger signature(object = "Event"): gets the trigger slot
trigger<- signature(object = "Event"): sets the trigger slot
  
```

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

---

EventAssignment-class *SBML type "EventAssignment"*

---

## Description

As part of an event, assigns a value to the quantity of a [Species](#), the size of a [Compartment](#) or the value of a [Parameter](#).

## Instantiation

Objects can be created by calls of the form new("EventAssignment", ...).

## Slots

**variable:** Object of class "character" ~~  
**math:** Object of class "expression" that evaluates to the value to assign.  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

**math** signature(object = "EventAssignment"): gets the math slot  
**math<-** signature(object = "EventAssignment"): sets the math slot  
**variable** signature(object = "EventAssignment"): gets the variable slot  
**variable<-** signature(object = "EventAssignment"): sets the variable slot

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

---

Experiment-class      *Experiment*

---

## Description

This class is an abstraction for an experiment, e.g. in a simulation. An experiment consists of a `ExperimentProtocol`, `ExperimentDesign`, `ExperimentSubject` and `ExperimentResult`.

## Objects from the Class

A virtual Class: No objects may be created from it.

## Slots

**protocol**: Object of empty virtual class `ExperimentProtocol`, how the experiment was or is to be performed.

**design**: Object of empty virtual class `ExperimentDesign`, the design of the experiment.

**subject**: Object of empty virtual class `ExperimentSubject`, the object being observed by the experiment.

**result**: Object of empty virtual class `ExperimentResult`, the result of the experiment.

## Methods

**design** `signature(object = "Experiment")`: Gets the design slot.

**design<-** `signature(object = "Experiment")`: Sets the design slot.

**protocol** `signature(object = "Experiment")`: Gets the protocol slot.

**protocol<-** `signature(object = "Experiment")`: Sets the protocol slot.

**result** `signature(object = "Experiment")`: Gets the result slot.

**result<-** `signature(object = "Experiment")`: Sets the result slot.

**subject** `signature(object = "Experiment")`: Gets the subject slot.

**subject<-** `signature(object = "Experiment")`: Sets the subject slot.

## Author(s)

Michael Lawrence

## See Also

[SOSExperiment](#), an implementation that simulates SBML modules using the SBML ODE Solver library.

---

**FunctionDefinition-class***SBML type "FunctionDefinition"*

---

**Description**

Identifies a mathematical expression so that it may be referenced in other expressions.

**Instantiation**

Objects can be created by calls of the form `new("FunctionDefinition", ...)`.

**Slots**

**id:** Object of class "character" uniquely identifying this component.

**name:** Object of class "character" naming this component.

**math:** Object of class "expression" that defines the function.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[SBase](#)", directly.

**Methods**

**id** `signature(object = "FunctionDefinition")`: gets the **id** slot

**id<-** `signature(object = "FunctionDefinition")`: sets the **id** slot

**name** `signature(object = "FunctionDefinition")`: gets the **name** slot

**name<-** `signature(object = "FunctionDefinition")`: sets the **name** slot

**math** `signature(object = "FunctionDefinition")`: gets the **math** slot

**math<-** `signature(object = "FunctionDefinition")`: sets the **math** slot

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

---

GraphicalObject-class SBML type "GraphicalObject"

---

## Description

The base class for graphical objects (e.g. glyphs) in SBML layouts.

## Instantiation

Objects can be created by calls of the form `new("GraphicalObject", ...)`.

## Slots

**id:** Object of class "character" uniquely identifying this component.

**boundingBox:** Object of class "BoundingBox" describing the position and size of the graphical object.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

**id** `signature(object = "GraphicalObject")`: gets the id slot

**id<-** `signature(object = "GraphicalObject")`: sets the id slot

**boundingBox** `signature(object = "GraphicalObject")`: gets the boundingBox slot

**boundingBox<-** `signature(object = "GraphicalObject")`: sets the boundingBox slot

## Author(s)

Michael Lawrence

## References

<http://projects.villa-bosch.de/bcb/sbml>

---

**InitialAssignment-class***SBML Type "InitialAssignment"*

---

**Description**

Calculates the value of a symbol when the model is initialized.

**Objects from the Class**

Objects can be created by calls of the form `new("InitialAssignment", ...)`.

**Slots**

**symbol**: Object of class "character" to which the value is assigned.

**math**: Object of class "expression" that evaluates to the assigned value.

**metaId**: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes**: Object of class "character" containing user-readable XHTML notes about an element.

**annotation**: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms**: Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm**: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[SBase](#)", directly.

**Methods**

**math** `signature(object = "InitialAssignment")`: gets the **math** slot.

**math<-** `signature(object = "InitialAssignment")`: sets the **math** slot.

**symbol** `signature(object = "InitialAssignment")`: gets the **symbol** slot.

**symbol<-** `signature(object = "InitialAssignment")`: sets the **symbol** slot.

**Note**

Requires `libsbml >= 3.0`

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

## See Also

[AssignmentRule](#), which can set a value at any time but cannot set constants.

---

KineticLaw-class	<i>SBML type "KineticLaw"</i>
------------------	-------------------------------

---

## Description

Describes the rate of a [Reaction](#).

## Instantiation

Objects can be created by calls of the form `new("KineticLaw", ...)`.

## Slots

**math:** Object of class "expression" defining the rate of the reaction.

**parameters:** Object of class "list" containing [Parameters](#)s that may be used in **math**. The names of the list correspond to the IDs of the elements.

**timeUnits:** Object of class "character" indicating the units for time.

**substanceUnits:** Object of class "character" indicating the units for substance.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

**math** `signature(object = "KineticLaw")`: gets the **math** slot

**math<-** `signature(object = "KineticLaw")`: sets the **math** slot

**substanceUnits** `signature(object = "KineticLaw")`: gets the **substanceUnits** slot

**substanceUnits<-** `signature(object = "KineticLaw")`: sets the **substanceUnits** slot

**timeUnits** `signature(object = "KineticLaw")`: gets the **timeUnits** slot

**timeUnits<-** `signature(object = "KineticLaw")`: sets the **timeUnits** slot

**parameters** `signature(object = "KineticLaw")`: gets the **parameters** slot

**parameters<-** `signature(object = "KineticLaw")`: sets the **parameters** slot

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

---

Layout-class

*SBML type "Layout"*

---

**Description**

Contains the glyphs and other graphical objects that compose an SBML layout. Layouts are not part of the core SBML specification. See the reference for the SBML layout extension specification.

**Instantiation**

Objects can be created by calls of the form `new("Layout", ...)`.

**Slots**

**id:** Object of class "character" uniquely identifying this component.

**dimensions:** Object of class "Dimensions" specifying the size of the layout.

**compartmentGlyphs:** Object of class "list" containing the [CompartmentGlyphs](#). The names of the list correspond to the IDs of the elements.

**speciesGlyphs:** Object of class "list" containing the [SpeciesGlyphs](#). The names of the list correspond to the IDs of the elements.

**reactionGlyphs:** Object of class "list" containing the [ReactionGlyphs](#). The names of the list correspond to the IDs of the elements.

**textGlyphs:** Object of class "list" containing the [TextGlyphs](#). The names of the list correspond to the IDs of the elements.

**additionalGraphicalObjects:** Object of class "list" containing the additional [GraphicalObjects](#) that are not bound to any model component. The names of the list correspond to the IDs of the elements.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[SBase](#)", directly.

## Methods

```

id signature(object = "Layout"): gets the id slot
id<- signature(object = "Layout"): sets the id slot
additionalGraphicalObjects signature(object = "Layout"): gets the additionalGraphicalObjects slot
additionalGraphicalObjects<- signature(object = "Layout"): sets the additionalGraphicalObjects slot
compartmentGlyphs signature(object = "Layout"): gets the compartmentGlyphs slot
compartmentGlyphs<- signature(object = "Layout"): sets the compartmentGlyphs slot
dimensions signature(object = "Layout"): gets the dimensions slot
dimensions<- signature(object = "Layout"): sets the dimensions slot
reactionGlyphs signature(object = "Layout"): gets the reactionGlyphs slot
reactionGlyphs<- signature(object = "Layout"): sets the reactionGlyphs slot
speciesGlyphs signature(object = "Layout"): gets the speciesGlyphs slot
speciesGlyphs<- signature(object = "Layout"): sets the speciesGlyphs slot
textGlyphs signature(object = "Layout"): gets the textGlyphs slot
textGlyphs<- signature(object = "Layout"): sets the textGlyphs slot

```

## Author(s)

Michael Lawrence

## References

<http://projects.villa-bosch.de/bcb/sbml>

---

LineSegment-class      SBML type "LineSegment"

---

## Description

Describes a simple A-B line.

## Instantiation

Objects can be created by calls of the form new("LineSegment", ...).

## Slots

**start:** Object of class "Point" indicating the start position.  
**end:** Object of class "Point" indicating the end position.  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

**end** `signature(x = "LineSegment")`: ...

**end<-** `signature(object = "LineSegment")`: sets the end slot

**start** `signature(x = "LineSegment")`: ...

**start<-** `signature(object = "LineSegment")`: sets the start slot

## Author(s)

Michael Lawrence

## References

<http://projects.villa-bosch.de/bcb/sbml>

## Description

Each of these functions implements a trigonometry function found in the MathML specification but not found in base R. These are all simple wrappers around existing R trig functions.

## Usage

```
acot(x)
acoth(x)
acsc(x)
acsch(x)
asec(x)
asech(x)
cot(x)
coth(x)
csc(x)
csch(x)
sec(x)
sech(x)
```

## Arguments

<code>x</code>	The numeric value(s) for the trigonometry operation
----------------	---

**Value**

A numeric vector, the same length as `x`.

**Author(s)**

Michael Lawrence

---

Model-class	<i>SBML type "Model"</i>
-------------	--------------------------

---

**Description**

The central SBML element. Contains the [Species](#), [Reactions](#), [Compartments](#) and other components of the model. See the SBML specification, at the reference, for further details.

**Instantiation**

Objects can be created by calls of the form `new("Model", ...)`.

**Slots**

`id`: Object of class "character" uniquely identifying this component.

`name`: Object of class "character" naming this component.

`functionDefinitions`: Object of class "list" containing [FunctionDefinitions](#). The names of the list correspond to the IDs of the elements.

`unitDefinitions`: Object of class "list" containing [UnitDefinitions](#). The names of the list correspond to the IDs of the elements.

`compartments`: Object of class "list" containing [Compartments](#). The names of the list correspond to the IDs of the elements.

`species`: Object of class "list" containing [Species](#). The names of the list correspond to the IDs of the elements.

`parameters`: Object of class "list" containing [Parameters](#). The names of the list correspond to the IDs of the elements.

`rules`: Object of class "list" containing [Rules](#).

`reactions`: Object of class "list" containing [Reactions](#). The names of the list correspond to the IDs of the elements.

`events`: Object of class "list" containing [Events](#). The names of the list correspond to the IDs of the elements.

`layouts`: Object of class "list" containing [Layouts](#). The names of the list correspond to the IDs of the elements.

`speciesTypes`: Object of class "list" containing [SpeciesTypes](#). The names of the list correspond to the IDs of the elements.

`compartmentTypes`: Object of class "list" containing [CompartmentsTypes](#). The names of the list correspond to the IDs of the elements.

`constraints`: Object of class "list" containing [Constraints](#). The names of the list correspond to the IDs of the elements.

**initialAssignments:** Object of class "list" containing [InitialAssignments](#).  
**modelHistory:** Object of class [ModelHistory](#) recording the history of the model.  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

### Extends

Class "[SBase](#)", directly.

### Methods

```

id signature(object = "Model"): gets the id slot
id<- signature(object = "Model"): sets the id slot
name signature(object = "Model"): gets the name slot
name<- signature(object = "Model"): sets the name slot
compartments signature(object = "Model"): gets the compartments slot
compartments<- signature(object = "Model"): sets the compartments slot
events signature(object = "Model"): gets the events slot
events<- signature(object = "Model"): sets the events slot
functionDefinitions signature(object = "Model"): gets the functionDefinitions slot
functionDefinitions<- signature(object = "Model"): sets the functionDefinitions slot
layouts signature(object = "Model"): gets the layouts slot
layouts<- signature(object = "Model"): sets the layouts slot
parameters signature(object = "Model"): gets the parameters slot
parameters<- signature(object = "Model"): sets the parameters slot
species signature(object = "Model"): gets the species slot
species<- signature(object = "Model"): sets the species slot
reactions signature(object = "Model"): gets the reactions slot
reactions<- signature(object = "Model"): sets the reactions slot
rules signature(object = "Model"): gets the rules slot
rules<- signature(object = "Model"): sets the rules slot
unitDefinitions signature(object = "Model"): gets the unitDefinitions slot
unitDefinitions<- signature(object = "Model"): sets the unitDefinitions slot
compartmentTypes signature(object = "Model"): gets the compartmentTypes slot
compartmentTypes<- signature(object = "Model"): sets the compartmentTypes slot
constraints signature(object = "Model"): gets the constraints slot
  
```

```
constraints<- signature(object = "Model"): sets the constraints slot
initialAssignments signature(object = "Model"): gets the initialAssignments slot
initialAssignments<- signature(object = "Model"): sets the initialAssignments slot
speciesTypes signature(object = "Model"): gets the speciesTypes slot
speciesTypes<- signature(object = "Model"): sets the speciesTypes slot
modelHistory signature(object = "Model"): gets the modelHistory slot
modelHistory<- signature(object = "Model"): sets the modelHistory slot
stoichiometryMatrix signature(object = "Model"): calculates the stoichiometry matrix of the
model
```

### Author(s)

Michael Lawrence

### References

<http://sbml.org/documents/>

---

ModelCreator-class      *SBML Type "ModelCreator"*

---

### Description

Information, such as name, email and organization, about a creator of an SBML model.

### Objects from the Class

Objects can be created by calls of the form `new("ModelCreator", ...)`.

### Slots

**familyName**: Object of class "character" specifying the family name of the creator.  
**givenName**: Object of class "character" specifying the given name of the creator.  
**email**: Object of class "character" specifying the email address of the creator.  
**organization**: Object of class "character" specifying the name of the organization to which the creator belongs.

### Methods

```
email signature(object = "ModelCreator"): gets the email slot.
email<- signature(object = "ModelCreator"): sets the email<- slot.
familyName signature(object = "ModelCreator"): gets the familyName slot.
familyName<- signature(object = "ModelCreator"): sets the familyName<- slot.
givenName signature(object = "ModelCreator"): gets the givenName slot.
givenName<- signature(object = "ModelCreator"): sets the givenName<- slot.
organization signature(object = "ModelCreator"): gets the organization slot.
organization<- signature(object = "ModelCreator"): sets the organization<- slot.
```

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

---

ModelHistory-class      *SBML Type "ModelHistory"*

---

**Description**

Stores the history of an SBML model, including the created/modified dates and the creators.

**Objects from the Class**

Objects can be created by calls of the form `new("ModelHistory", ...)`.

**Slots**

**createdDate**: Object of class "character" representing the date/time of creation, in W3CDTF format: YYYY-MM-DDThh:mm:ssTZD, e.g. "1997-07-16T19:20:30+01:00".

**modifiedDate**: Object of class "character" representing the date/time of last modification, in W3CDTF format: YYYY-MM-DDThh:mm:ssTZD, e.g. "1997-07-16T19:20:30+01:00".

**creators**: Object of class "list" of instances of [ModelCreator](#), one for each creator of the model.

**Methods**

**createdDate** `signature(object = "ModelHistory")`: get the `createdDate` slot.

**createdDate<-** `signature(object = "ModelHistory", value = "character")`: Set the `createdDate` slot to a correctly formatted string.

**createdDate<-** `signature(object = "ModelHistory", value = "POSIXt")`: Set the `createdDate` slot with a [POSIXt](#) instance, obtained e.g. from [Sys.time](#).

**creators** `signature(object = "ModelHistory")`: gets the `creators` slot.

**creators<-** `signature(object = "ModelHistory")`: sets the `creators` slot.

**modifiedDate** `signature(object = "ModelHistory")`: get the `modifiedDate` slot.

**modifiedDate<-** `signature(object = "ModelHistory", value = "character")`: Set the `modifiedDate` slot to a correctly formatted string.

**modifiedDate<-** `signature(object = "ModelHistory", value = "POSIXt")`: Set the `modifiedDate` slot with a [POSIXt](#) instance, obtained e.g. from [Sys.time](#).

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

---

ModifierSpeciesReference-class  
SBML type "ModifierSpeciesReference"

---

## Description

Identifies a [Species](#) that modifies the parent [Reaction](#).

## Instantiation

Objects can be created by calls of the form `new("ModifierSpeciesReference", ...)`.

## Slots

**id:** Object of class "character" uniquely identifying this component.

**species:** Object of class "character" identifying the [Species](#) being referenced.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SimpleSpeciesReference](#)", directly. Class "[SBase](#)", by class "SimpleSpeciesReference", distance 2.

## Methods

No methods defined with class "ModifierSpeciesReference" in the signature.

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

---

Parameter-class	<i>SBML type "Parameter"</i>
-----------------	------------------------------

---

## Description

Declares a variable to be used in a mathematical expression.

## Instantiation

Objects can be created by calls of the form `new("Parameter", ...)`.

## Slots

**id**: Object of class "character" uniquely identifying this component.  
**name**: Object of class "character" naming this component.  
**value**: Object of class "numeric" specifying the initial value.  
**units**: Object of class "character" identifying the units.  
**constant**: Object of class "logical" indicating whether the value of this parameter is constant.  
**metaId**: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes**: Object of class "character" containing user-readable XHTML notes about an element.  
**annotation**: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms**: Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm**: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

```

id signature(object = "Parameter"): gets the id slot
id<- signature(object = "Parameter"): sets the id slot
name signature(object = "Parameter"): gets the name slot
name<- signature(object = "Parameter"): sets the name slot
units signature(object = "Parameter"): gets the units slot
units<- signature(object = "Parameter"): sets the units slot
constant signature(object = "Parameter"): gets the constant slot
constant<- signature(object = "Parameter"): sets the constant slot
value signature(object = "Parameter"): gets the value slot
value<- signature(object = "Parameter"): sets the value slot
  
```

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

---

ParameterRule-class     *SBML type "ParameterRule"*

---

**Description**

**Obsolete** rule that controls the value of a [Parameter](#).

**Instantiation**

Objects can be created by calls of the form new("ParameterRule", ...).

**Slots**

**name:** Object of class "character" naming this component.  
**units:** Object of class "character" identifying the units of the assigned value.  
**variable:** Object of class "character", ignored.  
**type:** Object of class "character", deprecated.  
**math:** Object of class "expression" specifying the equation.  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[AssignmentRule](#)", directly. Class "[Rule](#)", by class "AssignmentRule", distance 2. Class "[SBase](#)", by class "AssignmentRule", distance 3.

**Methods**

**name** `signature(object = "Parameter")`: gets the name slot  
**name<-** `signature(object = "Parameter")`: sets the name slot  
**units** `signature(object = "Parameter")`: gets the units slot  
**units<-** `signature(object = "Parameter")`: sets the units slot  
**variable** `signature(object = "Parameter")`: gets the variable slot

**variable<-** signature(object = "Parameter"): sets the variable slot  
**type** signature(object = "Parameter"): gets the type slot  
**type<-** signature(object = "Parameter"): sets the type slot  
**math** signature(object = "Parameter"): gets the math slot  
**math<-** signature(object = "Parameter"): sets the math slot

### Author(s)

Michael Lawrence

### References

<http://sbml.org/documents/>

---

Point-class

*SBML type "Point"*

---

### Description

Specifies a position in 3D space.

### Instantiation

Objects can be created by calls of the form new("Point", ...).

### Slots

**x:** Object of class "numeric" indicating the X coordinate  
**y:** Object of class "numeric" indicating the Y coordinate  
**z:** Object of class "numeric" indicating the Z coordinate  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

### Extends

Class "[SBase](#)", directly.

## Methods

```

x signature(object = "Point"): gets the x slot
x<- signature(object = "Point"): sets the x slot
y signature(object = "Point"): gets the y slot
y<- signature(object = "Point"): sets the y slot
z signature(object = "Point"): gets the z slot
z<- signature(object = "Point"): sets the z slot

```

## Author(s)

Michael Lawrence

## References

<http://projects.villa-bosch.de/bcb/sbml>

---

RateRule-class	<i>SBML type "RateRule"</i>
----------------	-----------------------------

---

## Description

An equation that describes the rate of change in the quantity of a [Species](#), the size of a [Compartment](#) or the value of a [Parameter](#).

## Instantiation

Objects can be created by calls of the form `new("RateRule", ...)`.

## Slots

**variable:** Object of class "character" naming the variable (the id of a [Species](#), [Compartment](#) or [Parameter](#)) being described.

**math:** Object of class "expression" specifying the equation.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[Rule](#)", directly. Class "[SBase](#)", by class "Rule", distance 2.

## Methods

**variable** signature(object = "RateRule"): gets the variable slot  
**variable<-** signature(object = "RateRule"): sets the variable slot

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

---

Reaction-class      *SBML type "Reaction"*

---

## Description

Any transformation, transportation or binding process that changes the quantity of one or more [Species](#).

## Instantiation

Objects can be created by calls of the form new("Reaction", ...).

## Slots

**id:** Object of class "character" uniquely identifying this component.  
**name:** Object of class "character" naming this component.  
**reactants:** Object of class "list" containing [SpeciesReferences](#) specifying the [Species](#) that are reactants for this reaction. The names of the list correspond to the IDs of the species.  
**products:** Object of class "list" containing [SpeciesReferences](#) specifying the [Species](#) that are products for this reaction. The names of the list correspond to the IDs of the species.  
**modifiers:** Object of class "list" containing [ModifierSpeciesReferences](#) specifying the [Species](#) that are modifiers for this reaction. The names of the list correspond to the IDs of the species.  
**kineticLaw:** Object of class "KineticLaw" that dynamically defines the rate of the reaction.  
**reversible:** Object of class "logical" indicating whether the direction of this reaction is reversible.  
**fast:** Object of class "logical" indicating whether this reaction should be considered instantaneous relative to non-fast reactions.  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[SBase](#)", directly.

**Methods**

**id** signature(object = "Reaction"): gets the id slot  
**id<-** signature(object = "Reaction"): sets the id slot  
**name** signature(object = "Reaction"): gets the name slot  
**name<-** signature(object = "Reaction"): sets the name slot  
**fast** signature(object = "Reaction"): gets the fast slot  
**fast<-** signature(object = "Reaction"): sets the fast slot  
**kineticLaw** signature(object = "Reaction"): gets the kineticLaw slot  
**kineticLaw<-** signature(object = "Reaction"): sets the kineticLaw slot  
**modifiers** signature(object = "Reaction"): gets the modifiers slot  
**modifiers<-** signature(object = "Reaction"): sets the modifiers slot  
**products** signature(object = "Reaction"): gets the products slot  
**products<-** signature(object = "Reaction"): sets the products slot  
**reactants** signature(object = "Reaction"): gets the reactants slot  
**reactants<-** signature(object = "Reaction"): sets the reactants slot  
**reversible** signature(object = "Reaction"): gets the reversible slot  
**reversible<-** signature(object = "Reaction"): sets the reversible slot

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

---

ReactionGlyph-class     *SBML type "ReactionGlyph"*

---

**Description**

A glyph representing a [Reaction](#) in the SBML layout.

**Instantiation**

Objects can be created by calls of the form `new("ReactionGlyph", ...)`.

## Slots

**reaction:** Object of class "character" identifying the reaction represented by this glyph.

**glyphCurve:** Object of class "Curve" describing this glyph as a curve (optional).

**speciesReferenceGlyphs:** Object of class "list" containing [SpeciesReferenceGlyphs](#) that represent the [SpeciesReferences](#) of the underlying [Reaction](#). The names of the list correspond to the IDs of the elements.

**id:** Object of class "character" uniquely identifying this component.

**boundingBox:** Object of class "BoundingBox" describing the position and size of the graphical object.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[GraphicalObject](#)", directly. Class "[SBase](#)", by class "GraphicalObject", distance 2.

## Methods

**glyphCurve** `signature(expr = "ReactionGlyph")`: gets the `glyphCurve` slot

**glyphCurve<-** `signature(object = "ReactionGlyph")`: sets the `glyphCurve` slot

**reaction** `signature(object = "ReactionGlyph")`: gets the `reaction` slot

**reaction<-** `signature(object = "ReactionGlyph")`: sets the `reaction` slot

**speciesReferenceGlyphs** `signature(object = "ReactionGlyph")`: gets the `speciesReferenceGlyphs` slot

**speciesReferenceGlyphs<-** `signature(object = "ReactionGlyph")`: sets the `speciesReferenceGlyphs` slot

## Author(s)

Michael Lawrence

## References

<http://projects.villa-bosch.de/bcb/sbml>

---

Rule-class	<i>SBML type "Rule"</i>
------------	-------------------------

---

## Description

A mathematical equation.

## Instantiation

A virtual Class: No objects may be created from it.

## Slots

**math:** Object of class "expression" specifying the equation.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

**math** `signature(object = "Rule")`: gets the **math** slot

**math<-** `signature(object = "Rule")`: sets the **math** slot

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

---

SBase-class	<i>SBML type "SBase"</i>
-------------	--------------------------

---

## Description

The abstract type from which all other SBML types are derived.

## Instantiation

A virtual Class: No objects may be created from it.

## Slots

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Methods

**annotation** `signature(object = "SBase")`: gets the annotation slot

**annotation<-** `signature(object = "SBase")`: sets the annotation slot

**metaId** `signature(object = "SBase")`: gets the metaId slot

**metaId<-** `signature(object = "SBase")`: sets the metaId slot

**notes** `signature(object = "SBase")`: gets the notes slot

**notes<-** `signature(object = "SBase")`: sets the notes slot

**cvTerms** `signature(object = "SBase")`: gets the cvTerms slot.

**cvTerms<-** `signature(object = "SBase")`: sets the cvTerms slot.

**sboTerm** `signature(object = "SBase")`: gets the sboTerm slot.

**sboTerm<-** `signature(object = "SBase")`: sets the sboTerm slot.

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

---

SBML import	<i>Read in an SBML file (start here)</i>
-------------	--

---

## Description

Read an SBML file into R.

## Usage

```
rsbml_read(filename, text, dom = TRUE, strict = FALSE, schema = FALSE,  
           consistency = TRUE)
```

## Arguments

filename	the name of the SBML file to parse
text	a string of SBML text to parse (instead of file)
dom	whether to convert directly to the S4 DOM (TRUE, the default) or leave as the internal <a href="#">SBMLDocument</a> .
strict	whether to report warnings in addition to errors or not (FALSE, the default).
schema	whether to perform XML schema validation
consistency	whether to perform consistency checks; recommended but might cause performance deficiencies.

## Value

a [SBML](#) object, or a [SBMLDocument](#) if dom is FALSE.

## Author(s)

Michael Lawrence

## Examples

```
# Read an SBML file  
file <- system.file("sbml", "GlycolysisLayout.xml", package = "rsbml")  
doc <- rsbml_read(file)  
  
# Read an SBML string  
string <- paste(readLines(file), collapse="\n")  
doc <- rsbml_read(text = string)
```

---

SBML-class	<i>SBML type "SBML"</i>
------------	-------------------------

---

## Description

The root element of an SBML document. An actual SBML [Model](#) may be retrieved from an instance of this class.

## Instantiation

Objects can be created by calls of the form `new("SBML", ...)`.

## Slots

**level:** Object of class "integer" indicating the level of the SBML standard (currently at 2).  
**ver:** Object of class "integer" indicating the version of the level (currently at 2 for level 2).  
**model:** Object of class "Model" the SBML model itself.  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

**coerce** `signature(from = "SBMLDocument", to = "SBML")`: constructs the S4 object model from a low-level libsbml document.  
**coerce** `signature(from = "SBML", to = "SBMLDocument")`: converts the S4 object model to a low-level libsbml document.  
**coerce** `signature(from = "SBML", to = "graph")`: converts the S4 object model to a graph.  
**level** `signature(object = "SBML")`: gets the level slot  
**level<-** `signature(object = "SBML")`: sets the level slot  
**model** `signature(object = "SBML")`: gets the model slot  
**model<-** `signature(object = "SBML")`: sets the model slot  
**rsbml\\_doc** `signature(model = "SBML")`: converts the S4 object model to a low-level libsbml document.  
**rsbml\\_write** `signature(object = "SBML")`: writes this document to a file as SBML.  
**rsbml\\_xml** `signature(object = "SBML")`: converts this document to a string as SBML.

```

rsbml\graph signature(object = "SBML"): converts this document to a graph object.

rsbml\check signature(object = "SBML"): perform consistency checks, see rsbml\_check.

simulate signature(object = "SBML"): converts this document to an internal SBMLDocument and
calls simulate on it.

ver signature(object = "SBML"): gets the ver slot

ver<- signature(object = "SBML"): sets the ver slot

```

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

## Examples

```

# Get a DOM
dom <- rsbml_read(system.file("sbml", "GlycolysisLayout.xml", package = "rsbml"))

# Get the species ID's
sapply(species(model(dom)), id)

# Convert DOM back to a low-level document for checking
doc <- rsbml_doc(dom)
rsbml_check(doc)

# Write a DOM to a file
## Not run: rsbml_write(dom, "my.xml")

```

---

SBMLDocument-class     "SBMLDocument" from *libsbml*

---

## Description

Low-level libsbml document structure.

## Instantiation

A virtual Class: No objects may be created from it.

## Extends

Class "[oldClass](#)", directly.

## Methods

**rsbml\check** signature(object = "SBMLDocument"): rsbml\_check(object, strict = FALSE, consistency = TRUE): Check for problems with the document and signal R conditions if any errors are detected. If strict is TRUE, libsbml warnings will be emitted as R warnings (these are often too pedantic). If consistency is also TRUE, reports problems regarding internal model inconsistencies. This can be time consuming.

**rsbml\dom** signature(doc = "SBMLDocument"): Constructs an S4 object model from a libsbml document.

**rsbml\graph** signature(doc = "SBMLDocument"): Converts a libsbml document to a [graph](#).

**rsbml\problems** signature(object = "SBMLDocument"): reports problems encountered during parsing and/or validation.

**rsbml\write** signature(object = "SBMLDocument"): writes this document to a file as SBML.

**rsbml\xml** signature(object = "SBMLDocument"): converts this document to a string as SBML.

**simulate** signature(object = "SBMLDocument"): simulate(object, nsim = 10, seed, ...): a shortcut for simulating the model in this document using the SBML ODE Solver library. Arguments in ... should match slots of [SOSProtocol](#). See [simulate](#) for more details.

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

## Examples

```
# Read a document into an R DOM
dom <- rsbml_read(system.file("sbml", "GlycolysisLayout.xml", package
= "rsbml"))

# Convert to a graph
graph <- rsbml_graph(dom)

# Write it out to a file
## Not run: rsbml_write(dom, "my.xml")

# Or convert it to a string of XML
rsbml_xml(dom)

# Read into external libsbml data structure
doc <- rsbml_read(system.file("sbml", "GlycolysisLayout.xml", package
= "rsbml"), dom = FALSE)

# Convert it explicitly to an S4 DOM
dom <- rsbml_dom(doc)
```

---

SBMLProblem-class      *SBMLProblem*

---

## Description

Represents an exception thrown during SBML parsing.

## Details

There are trivial subclasses for fatal errors (SBMLFatal), recoverable errors (SBMLError), warnings (SBMLWarning) and informational messages (SBMLInfo). Errors become R error `conditions`, warnings become R `warning` conditions and messages are output via `message`.

## Slots

`line`: The "numeric" line number in the SBML file where the problem was detected.  
`column`: Object of class "numeric" column number in the SBML file where the problem was detected.  
`msg`: Object of class "character", a human-readable description of the problem.

## Methods

`.condition` `signature(object = "SBMLProblem")`: constructs a `condition` object representing the exception.

## Author(s)

Michael Lawrence

## See Also

[SBMLProblems](#), a container for instances of this class.

---

SBMLProblems-class      *SBMLProblems*

---

## Description

A class representing errors encountered during parsing of SBML.

## Slots

`fatal`: A list of `SBMLFatal` instances.  
`error`: A list of `SBMLError` instances.  
`warning`: A list of `SBMLWarning` instances.  
`info`: A list of `SBMLInfo` instances.

## Methods

**.throw** signature(object = "SBMLProblems"): Throws each [SBMLProblem](#) in this object.  
**errors** signature(object = "SBMLProblems"): Gets the errors slot.  
**fatal**s signature(object = "SBMLProblems"): Gets the fatal slot.  
**infos** signature(object = "SBMLProblems"): Gets the infos slot.  
**warns** signature(object = "SBMLProblems"): Gets the warns slot.

## Author(s)

Michael Lawrence

## See Also

The [rsbml\\_problems](#) function for obtaining an instance of this class describing any problems encountered during parsing.

SimpleSpeciesReference-class  
*SBML type "SimpleSpeciesReference"*

## Description

Base class for bindings between a [Species](#) and a [Reaction](#).

## Instantiation

Objects can be created by calls of the form `new("SimpleSpeciesReference", ...)`.

## Slots

**id:** Object of class "character" uniquely identifying this component.  
**species:** Object of class "character" identifying the [Species](#) being referenced.  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

```
id  signature(object = "SpeciesGlyph"): gets the id slot
id<- signature(object = "SpeciesGlyph"): sets the id slot
species  signature(object = "SpeciesGlyph"): gets the species slot
species<- signature(object = "SpeciesGlyph"): sets the species slot
```

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

---

SOSDesign-class

*SOSDesign*

---

## Description

Specifies the reaction names and their parameter settings for each run in a batch experiment. It extends `matrix`; each column corresponds to a parameter in the model and each row should hold the parameter settings for one run of the experiment.

## Details

It is often desirable to explore the state space of a model by adjusting its initial parameter settings. One could do this by modifying the model itself for each experiment, but this class aims to provide a more convenient and systematic means of running experiments in batch, over a range of parameter settings. The results of the experiment will then contain the output from each run, which may then be compared.

The design is specified as a matrix, and each column in the matrix should correspond to a parameter defined in an SBML model. The column names should identify the parameters. These are not to be confused with the simulation parameters specified in `SOSProtocol`, which control how the simulation is executed. These should be and are designed to be kept constant across the runs.

There are two different types of parameters: global and local (reaction) parameters. Global parameters may correspond to a `Species` quantity, `Compartment` size, or model-level `Parameter` value. These should be identified in the column names by the `id` of the corresponding SBML element. The element in the `reactions` slot for one of these parameters should be the empty string.

The second type of parameter specifies the value of a `Parameter` element within the `KineticLaw` of a reaction. These should be named by the `id` of the `Parameter`. They also should be namespaced by the containing `Reaction` id, which is stored in the corresponding element of the `reactions` slot.

## Objects from the Class

Objects can be created by calls of the form `new("SOSDesign", data, nrow, ncol, byrow, dimnames, ...)`. This is the same as initializing a `matrix`.

**Slots**

**.Data:** Object of class "matrix", holding the parameter settings.

**reactions:** Object of class "character" of length the number of columns, holding the reaction IDs for parameters local to a reaction (i.e. [KineticLaw Parameters](#)). For global parameters, the corresponding value should be the empty string.

**Extends**

Class "matrix", from data part. Class "ExperimentDesign", directly. Class "array", by class "matrix", distance 2. Class "structure", by class "matrix", distance 3. Class "vector", by class "matrix", distance 4, with explicit coerce.

**Methods**

**reactions** `signature(object = "SOSDesign")`: gets the reactions slot.

**reactions<-** `signature(object = "SOSDesign")`: sets the reactions slot.

**Author(s)**

Michael Lawrence

**References**

See <http://www.tbi.univie.ac.at/~raim/odeSolver/> for more information on the SBML ODE Solver library.

**See Also**

[SOSExperiment](#), the container of this class, for configuring and running a simulation.

---

SOSExperiment-class    *SOS Experiment*

---

**Description**

Implementation of [Experiment](#) for simulating SBML models using the SOS: (S)BML (O)DE (S)olver library.

**Details**

The general workflow for running a simulation:

1. Create or import an [SBML DOM](#).
2. Customize the model, for example by adding perturbation [Events](#).
3. Wrap the SBML DOM in a [SOSSubject](#), e.g. `new("SOSSubject", dom)`.
4. Optionally construct a [SOSDesign](#) for running the experiment in batch over several sets of model parameter settings.
5. Optionally construct a [SOSProtocol](#) for specifying the time points and other parameters controlling the simulation.
6. Construct an instance of this class that groups the subject, design and protocol.

7. Run `simulate` on the `SOSExperiment`, optionally specifying the number of iterations and the random seed.
8. Analyze the returned `SOSResult`, perhaps starting by converting it to a time series with `as.ts` and making some plots.

## Objects from the Class

Objects can be created by calls of the form `new("SOSExperiment", ...)`.

### Slots

`protocol`: Object of class `SOSProtocol`, where the simulation parameters are specified.

`design`: Object of class `SOSDesign`, specifying model parameters for each run of a batch experiment.

`subject`: Object of class `SOSSubject`, containing the `Model` to be simulated.

`result`: Object of class `SOSResult` containing the result of the simulation.

### Extends

Class `Experiment`, directly.

### Methods

**simulate** `signature(object = "SOSExperiment")`: `simulate(object, nsim = 10, seed, ...)`:  
Simulates the SBML document in the `subject` slot according to the design points in `design` and parameters in `protocol` for `nsim` iterations, using `seed` as the random seed. Returns an instance of `SOSExperiment`, which now should include a `SOSResult` for analysis.

### Author(s)

Michael Lawrence

### References

See <http://www.tbi.univie.ac.at/~raim/odeSolver/> for more information on the SBML ODE Solver library.

### See Also

The `simulate` method on `SBMLDocument` is a shortcut, but most users will probably find the above approach most useful.

---

SOSProtocol-class	<i>SOSProtocol</i>
-------------------	--------------------

---

## Description

Holds the parameters controlling the execution of the simulation using the SBML ODE Solver library.

## Details

Most users will probably set only the `times` slot, either directly or through the `timeStep` slot and the `nsim` parameter to [simulate](#).

## Objects from the Class

Objects can be created by calls of the form `new("SOSProtocol", ...)`. Each argument in `...` should correspond to one of the slots described below.

## Slots

**times:** A "numeric" vector indicating the time points at which to evaluate the model. Defaults to `tail(seq(0, by = timeStep, length.out = nsim + 1), -1)`. The model is always evaluated at  $t = 0$ . This slot is ignored when `indefinite` (below) is TRUE.

**timeStep:** A scalar "numeric" value, giving the length in time between model evaluations. This is used when calculating the default value of `times`, above, but is otherwise only relevant when the `indefinite` slot, below, is TRUE. Defaults to 1.

**indefinite:** A scalar "logical", indicating whether the simulation should run indefinitely, i.e. until one of the stopping conditions is met. See `haltOnEvent` and `haltOnSteadyState` below. Defaults to FALSE.

**atol:** Scalar "numeric", the absolute tolerance in integration error. Defaults to `1e-18`.

**rtol:** Scalar "numeric", the relative tolerance in integration error. Defaults to `1e-10`.

**maxStep:** Scalar "numeric", the maximum number of steps for integration. Not to be confused with `timeStep`, etc, above, which control the simulation time points. Defaults to 10000.

**odeMethod:** Scalar "character" naming the method for solving ODEs. Either "bdf" (the default) or "adams-moulton".

**iterMethod:** Scalar "character", naming the iteration method used by the ODE solver, either "newton" (the default) or "functional".

**maxOrder:** Scalar "numeric" indicating maximum order for the ODE solver. Defaults to 5.

**sensMethod:** Scalar "character" naming the method for sensitivity analysis. One of "none" (the default and currently the only valid option), "simultaneous", "staggered" or "staggered1".

**haltOnEvent:** Scalar "logical" indicating whether the simulation should halt when the model emits an [Event](#). This allows the model to stop the simulation when some state is reached. Defaults to FALSE.

**haltOnSteadyState:** Scalar "logical", indicating whether to halt when a steady state is detected. Defaults to FALSE.

**useJacobian:** Scalar "logical" indicating whether to use Jacobian ASTs (TRUE, the default) or the internal approximation in the CVODES library.

**storeResults:** Scalar "logical" indicating whether to store the entire time course (TRUE, the default) or just the last time point. Just for performance.

**Extends**

Class "[ExperimentProtocol](#)", directly.

**Methods**

No methods defined with class "SOSProtocol" in the signature.

**Author(s)**

Michael Lawrence

**References**

See <http://www.tbi.univie.ac.at/~raim/odeSolver/> for more information on the SBML ODE Solver library.

**See Also**

The [SOSExperiment](#) class, which contains a SOSProtocol instance, for setting up and running a simulation.

---

SOSResult-class

*SOSResult*

---

**Description**

A result from simulating an [SOSExperiment](#). Contains the time course for each of the model variables: the [Species](#) quantities, [Compartment](#) sizes, [Parameter](#) values, and [Reaction](#) rates.

**Slots**

**data:** A "data.frame" containing the time course data. Each row contains the value at a single time point for a single time course. Has the following columns:

- sample** A factor, the run number, only exists if there were multiple runs, see [SOSDesign](#).
- type** A factor, the SBML element type for the time course, e.g. "species".
- id** A factor, the id of the SBML element for the time course.
- time** The numeric time value for the time point.
- value** The actual numeric value for the time course at that time.

**sens:** A "matrix" with results from sensitivity analysis, not yet supported.

**Extends**

Class "[ExperimentResult](#)", directly.

## Methods

**as.ts** `signature(x = "SOSResult")`: converts this object to a time course object of class `ts`. This allows analysis of the results with existing R infrastructure for time course analysis.

**compartments** `signature(object = "SOSResult")`: returns a subset containing only the `Compartment` size courses.

**parameters** `signature(object = "SOSResult")`: returns a subset containing only the global `Parameter` value courses.

**reactions** `signature(object = "SOSResult")`: returns a subset containing only the `Reaction` rate courses.

**species** `signature(object = "SOSResult")`: returns a subset containing only the `Species` quantity courses.

## Author(s)

Michael Lawrence

## References

See <http://www.tbi.univie.ac.at/~raim/odeSolver/> for more information on the SBML ODE Solver library.

## See Also

[SOSExperiment](#) for running a simulation and obtaining an instance of this class.

---

SOSSubject-class      *SOSSubject*

---

## Description

This just marks an `SBML` object as being a valid subject for simulation using the SBML ODE Solver library.

## Objects from the Class

Normally created from a SBML with: `new("SOSSubject", model)`.

## Extends

Class "[ExperimentSubject](#)", directly. Class "[SBML](#)", directly. Class "[SBase](#)", by class "SBML", distance 2. Class "[Describable](#)", by class "SBML", distance 3.

## Author(s)

Michael Lawrence

## References

See <http://www.tbi.univie.ac.at/~raim/odeSolver/> for more information on the SBML ODE Solver library.

## See Also

[SOSExperiment](#) for running a simulation on a SOSSubject.

---

Species-class	<i>SBML type "Species"</i>
---------------	----------------------------

---

## Description

A participant in an SBML model.

## Instantiation

Objects can be created by calls of the form `new("Species", ...)`.

## Slots

**id:** Object of class "character" uniquely identifying this component.

**name:** Object of class "character" naming this component.

**compartment:** Object of class "character" identifying the compartment in which this species is located.

**initialAmount:** Object of class "numeric" indicating the initial amount for this species (mutually exclusive with **initialConcentration**).

**initialConcentration:** Object of class "numeric" indicating the initial concentration for this species (mutually exclusive with **initialAmount**).

**substanceUnits:** Object of class "character" identifying the units for the amount of this species or the numerator of the concentration.

**spatialSizeUnits:** Object of class "character" identifying the units for the denominator of the species concentration.

**hasOnlySubstanceUnits:** Object of class "logical" indicating whether the quantity of this species is specified as an amount or a concentration.

**boundaryCondition:** Object of class "logical". If TRUE, indicates that the quantity of this species cannot be changed by a reaction.

**charge:** Object of class "integer" indicating the electrical charge of this species.

**constant:** Object of class "logical" indicating whether the quantity of this species can change.

**units:** Object of class "character", deprecated.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[SBase](#)", directly.

**Methods**

**id** signature(object = "Species"): gets the id slot  
**id<-** signature(object = "Species"): sets the id slot  
**name** signature(object = "Species"): gets the name slot  
**name<-** signature(object = "Species"): sets the name slot  
**boundaryCondition** signature(object = "Species"): gets the boundaryCondition slot  
**boundaryCondition<-** signature(object = "Species"): sets the boundaryCondition slot  
**charge** signature(object = "Species"): gets the charge slot  
**charge<-** signature(object = "Species"): sets the charge slot  
**compartment** signature(object = "Species"): gets the compartment slot  
**compartment<-** signature(object = "Species"): sets the compartment slot  
**constant** signature(object = "Species"): gets the constant slot  
**constant<-** signature(object = "Species"): sets the constant slot  
**units** signature(object = "Species"): gets the constant slot  
**units<-** signature(object = "Species"): sets the constant slot  
**hasOnlySubstanceUnits** signature(object = "Species"): gets the hasOnlySubstanceUnits slot  
**hasOnlySubstanceUnits<-** signature(object = "Species"): sets the hasOnlySubstanceUnits slot  
**initialAmount** signature(object = "Species"): gets the initialAmount slot  
**initialAmount<-** signature(object = "Species"): sets the initialAmount slot  
**initialConcentration** signature(object = "Species"): gets the initialConcentration slot  
**initialConcentration<-** signature(object = "Species"): sets the initialConcentration slot  
**spatialSizeUnits** signature(object = "Species"): gets the spatialSizeUnits slot  
**spatialSizeUnits<-** signature(object = "Species"): sets the spatialSizeUnits slot  
**substanceUnits** signature(object = "Species"): gets the substanceUnits slot  
**substanceUnits<-** signature(object = "Species"): sets the substanceUnits slot

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

---

SpeciesConcentrationRule-class  
SBML type "SpeciesConcentrationRule"

---

### Description

**Obsolete** type of rule that describes the concentration of [Species](#).

### Instantiation

Objects can be created by calls of the form new("SpeciesConcentrationRule", ...).

### Slots

**species**: Object of class "character" identifying the [Species](#).

**variable**: Object of class "character", ignored.

**type**: Object of class "character", deprecated.

**math**: Object of class "expression" specifying the equation.

**metaId**: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes**: Object of class "character" containing user-readable XHTML notes about an element.

**annotation**: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms**: Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm**: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

### Extends

Class "[AssignmentRule](#)", directly. Class "[Rule](#)", by class "AssignmentRule", distance 2. Class "[SBase](#)", by class "AssignmentRule", distance 3.

### Methods

**species** `signature(object = "SpeciesConcentrationRule")`: gets the species slot

**species<-** `signature(object = "SpeciesConcentrationRule")`: sets the species slot

### Author(s)

Michael Lawrence

### References

<http://sbml.org/documents/>

---

SpeciesGlyph-class	SBML type "SpeciesGlyph"
--------------------	--------------------------

---

## Description

A glyph representing a [Species](#) in an SBML layout.

## Instantiation

Objects can be created by calls of the form `new("SpeciesGlyph", ...)`.

## Slots

**species:** Object of class "character" identifying the species this glyph represents.

**id:** Object of class "character" uniquely identifying this component.

**boundingBox:** Object of class "BoundingBox" describing the position and size of the graphical object.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[GraphicalObject](#)", directly. Class "[SBase](#)", by class "GraphicalObject", distance 2.

## Methods

**species** `signature(object = "SpeciesGlyph")`: gets the species slot

**species<-** `signature(object = "SpeciesGlyph")`: sets the species slot

## Author(s)

Michael Lawrence

## References

<http://projects.villa-bosch.de/bcb/sbml>

---

SpeciesReference-class  
SBML type "SpeciesReference"

---

## Description

Binds a reactant or product [Species](#) to a [Reaction](#).

## Instantiation

Objects can be created by calls of the form `new("SpeciesReference", ...)`.

## Slots

**stoichiometry**: Object of class "numeric" indicating the (static) stoichiometric coefficient.  
**stoichiometryMath**: Object of class "StoichiometryMath" that dynamically calculates the stoichiometric coefficient.  
**id**: Object of class "character" uniquely identifying this component.  
**species**: Object of class "character" identifying the [Species](#) being referenced.  
**metaId**: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes**: Object of class "character" containing user-readable XHTML notes about an element.  
**annotation**: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms**: Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm**: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SimpleSpeciesReference](#)", directly. Class "[SBase](#)", by class "SimpleSpeciesReference", distance 2.

## Methods

**stoichiometry** `signature(object = "SpeciesReference")`: gets the stoichiometry slot  
**stoichiometry<-** `signature(object = "SpeciesReference")`: sets the stoichiometry slot  
**stoichiometryMath** `signature(object = "SpeciesReference")`: gets the stoichiometryMath slot  
**stoichiometryMath<-** `signature(object = "SpeciesReference")`: sets the stoichiometryMath slot

## Author(s)

Michael Lawrence

## References

<http://sbml.org/documents/>

## SpeciesReferenceGlyph-class

SBML type "SpeciesReferenceGlyph"

**Description**

A glyph representing a [SpeciesReference](#) in an SBML layout.

**Instantiation**

Objects can be created by calls of the form `new("SpeciesReferenceGlyph", ...)`.

**Slots**

**speciesGlyph:** Object of class "character" identifying the [SpeciesGlyph](#) representing the [Species](#) that is referenced by the underlying [SpeciesReference](#).

**speciesReference:** Object of class "character" identifying the `linkS4class{SpeciesReference}` represented by this glyph.

**role:** Object of class "character" indicating how this glyph should represent the "role" of the underlying [SpeciesReference](#).

**glyphCurve:** Object of class "Curve" describing this glyph as a curve (optional).

**id:** Object of class "character" uniquely identifying this component.

**boundingBox:** Object of class "BoundingBox" describing the position and size of the graphical object.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[GraphicalObject](#)", directly. Class "[SBase](#)", by class "GraphicalObject", distance 2.

**Methods**

**role** `signature(object = "SpeciesReferenceGlyph")`: gets the `role` slot

**role<-** `signature(object = "SpeciesReferenceGlyph")`: sets the `role` slot

**speciesGlyph** `signature(object = "SpeciesReferenceGlyph")`: gets the `speciesGlyph` slot

**speciesGlyph<-** `signature(object = "SpeciesReferenceGlyph")`: sets the `speciesGlyph` slot

**speciesReference** `signature(object = "SpeciesReferenceGlyph")`: gets the `speciesReference` slot

```
speciesReference<- signature(object = "SpeciesReferenceGlyph"): sets the speciesReference
slot
glyphCurve signature(expr = "SpeciesReferenceGlyph"): gets the glyphCurve slot
glyphCurve<- signature(object = "SpeciesReferenceGlyph"): sets the glyphCurve slot
```

### Author(s)

Michael Lawrence

### References

<http://projects.villa-bosch.de/bcb/sbml>

---

SpeciesType-class      SBML Type "SpeciesType"

---

### Description

A **Species** represents a pool of a chemical in a particular linkS4class{Compartment}. This element specifies a type of species, that is, the chemical independent of location.

### Objects from the Class

Objects can be created by calls of the form new("SpeciesType", ...).

### Slots

**id:** Object of class "character" uniquely identifying this component.

**name:** Object of class "character" naming this component.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of **CVTerm** associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

### Extends

Class "**SBase**", directly.

### Methods

```
id signature(object = "SpeciesType"): gets the id slot
id<- signature(object = "SpeciesType"): sets the id slot
name signature(object = "SpeciesType"): gets the name slot
name<- signature(object = "SpeciesType"): sets the name slot
```

**Note**

Requires libsbml >= 3.0

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

**See Also**

[Species](#)

---

StoichiometryMath-class

*SBML type "StoichiometryMath"*

---

**Description**

Dynamically defines the stoichiometry of a [SpeciesReference](#).

**Instantiation**

Objects can be created by calls of the form `new("StoichiometryMath", ...)`.

**Slots**

**math:** Object of class "expression" that evaluates to the stoichiometric coefficient.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[SBase](#)", directly.

**Methods**

**math** `signature(object = "StoichiometryMath")`: gets the `math` slot

**math<-** `signature(object = "StoichiometryMath")`: sets the `math` slot

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

---

TextGlyph-class      *SBML type "TextGlyph"*

---

**Description**

A run of text in an SBML layout.

**Instantiation**

Objects can be created by calls of the form `new("TextGlyph", ...)`.

**Slots**

**graphicalObject:** Object of class "character" identifying the [GraphicalObject](#) that this glyph labels (optional).

**text:** Object of class "character" containing the text shown by the glyph (mutually exclusive with **originOfText**).

**originOfText:** Object of class "character" identifying an SBML component whose name is used as the text (mutually exclusive with **text**).

**id:** Object of class "character" uniquely identifying this component.

**boundingBox:** Object of class "BoundingBox" describing the position and size of the graphical object.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[GraphicalObject](#)", directly. Class "[SBase](#)", by class "GraphicalObject", distance 2.

## Methods

**graphicalObject** signature(object = "TextGlyph"): gets the graphicalObject slot  
**graphicalObject<-** signature(object = "TextGlyph"): sets the graphicalObject slot  
**originOfText** signature(object = "TextGlyph"): gets the originOfText slot  
**originOfText<-** signature(object = "TextGlyph"): sets the originOfText slot  
**text** signature(x = "TextGlyph"): ...  
**text<-** signature(object = "TextGlyph"): sets the text slot

## Author(s)

Michael Lawrence

## References

<http://projects.villa-bosch.de/bcb/sbml>

---

Trigger-class

SBML Type "Trigger"

---

## Description

Expresses when an [Event](#) should be fired.

## Objects from the Class

Objects can be created by calls of the form new("Trigger", ...).

## Slots

**math:** Object of class "expression" that evaluates to TRUE when the event should be fired.  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

## Extends

Class "[SBase](#)", directly.

## Methods

**math** signature(domain = "Trigger"): gets the math slot.  
**math<-** signature(object = "Trigger"): sets the math slot.

**Note**

Requires libsbml >= 3.0

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

**See Also**

[Event](#), the parent of this element.

---

Unit-class

*SBML type "Unit"*

---

**Description**

A (possibly transformed) reference to a base UnitKind. The transformation is of the form: \$multiplier \* 10^scale \* x^exponent + offset\$.

**Instantiation**

Objects can be created by calls of the form new("Unit", ...).

**Slots**

**kind:** Object of class "character" identifying a an SBML UnitKind. For possible values see Table 2 in the SBML specification.

**exponent:** Object of class "integer" indicating the exponent to use in the transformation.

**unitScale:** Object of class "integer" indicating the order of magnitude of the scaling to use in the transformation.

**multiplier:** Object of class "numeric" indicating the factor to use for scaling in the transformation.

**offset:** Object of class "numeric" indicating the amount of constant shift in the transformation.

**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

**notes:** Object of class "character" containing user-readable XHTML notes about an element.

**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.

**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[SBase](#)", directly.

**Methods**

**exponent** `signature(object = "Unit")`: gets the exponent slot  
**exponent<-** `signature(object = "Unit")`: sets the exponent slot  
**kind** `signature(object = "Unit")`: gets the kind slot  
**kind<-** `signature(object = "Unit")`: sets the kind slot  
**multiplier** `signature(object = "Unit")`: gets the multiplier slot  
**multiplier<-** `signature(object = "Unit")`: sets the multiplier slot  
**offset** `signature(object = "Unit")`: gets the offset slot  
**offset<-** `signature(object = "Unit")`: sets the offset slot  
**unitScale** `signature(x = "Unit")`: ...  
**unitScale<-** `signature(object = "Unit")`: sets the unitScale slot

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

---

UnitDefinition-class    SBML type "*UnitDefinition*"

---

**Description**

Associates one or more [Units](#) with an ID and name.

**Instantiation**

Objects can be created by calls of the form `new("UnitDefinition", ...)`.

**Slots**

**id:** Object of class "character" uniquely identifying this component.  
**name:** Object of class "character" naming this component.  
**units:** Object of class "list" containing equivalent [Units](#) that are all associated with the same ID and name.  
**metaId:** Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.  
**notes:** Object of class "character" containing user-readable XHTML notes about an element.  
**annotation:** Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.  
**cvTerms:** Object of class "list" containing instances of [CVTerm](#) associated with this element.  
**sboTerm:** Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

**Extends**

Class "[SBase](#)", directly.

**Methods**

**id** `signature(object = "UnitDefinition")`: gets the id slot  
**id<-** `signature(object = "UnitDefinition")`: sets the id slot  
**name** `signature(object = "UnitDefinition")`: gets the name slot  
**name<-** `signature(object = "UnitDefinition")`: sets the name slot  
**units** `signature(object = "UnitDefinition")`: gets the units slot  
**units<-** `signature(object = "UnitDefinition")`: sets the units slot

**Author(s)**

Michael Lawrence

**References**

<http://sbml.org/documents/>

# Index

\* **IO**  
    SBML import, 41

\* **classes**  
    AlgebraicRule-class, 3  
    AssignmentRule-class, 4  
    BoundingBox-class, 5  
    Compartment-class, 6  
    CompartmentGlyph-class, 7  
    CompartmentType-class, 8  
    CompartmentVolumeRule-class, 9  
    Constraint-class, 10  
    CubicBezier-class, 11  
    Curve-class, 12  
    CVTerm-class, 13  
    Delay-class, 14  
    describe, 15  
    Dimensions-class, 15  
    Event-class, 16  
    EventAssignment-class, 18  
    Experiment-class, 19  
    FunctionDefinition-class, 20  
    GraphicalObject-class, 21  
    InitialAssignment-class, 22  
    KineticLaw-class, 23  
    Layout-class, 24  
    LineSegment-class, 25  
    Model-class, 27  
    ModelCreator-class, 29  
    ModelHistory-class, 30  
    ModifierSpeciesReference-class, 31  
    Parameter-class, 32  
    ParameterRule-class, 33  
    Point-class, 34  
    RateRule-class, 35  
    Reaction-class, 36  
    ReactionGlyph-class, 37  
    Rule-class, 39  
    SBase-class, 40  
    SBML-class, 42  
    SBMLDocument-class, 43  
    SBMLProblem-class, 45  
    SBMLProblems-class, 45  
    SimpleSpeciesReference-class, 46

    SOSDesign-class, 47  
    SOSExperiment-class, 48  
    SOSProtocol-class, 50  
    SOSResult-class, 51  
    SOSSubject-class, 52  
    Species-class, 53  
    SpeciesConcentrationRule-class, 55  
    SpeciesGlyph-class, 56  
    SpeciesReference-class, 57  
    SpeciesReferenceGlyph-class, 58  
    SpeciesType-class, 59  
    StoichiometryMath-class, 60  
    TextGlyph-class, 61  
    Trigger-class, 62  
    Unit-class, 63  
    UnitDefinition-class, 64

\* **math**  
    math, 26  
    .condition, SBMLProblem-method  
        (SBMLProblem-class), 45  
    .throw, SBMLError-method  
        (SBMLProblem-class), 45  
    .throw, SBMLFatal-method  
        (SBMLProblem-class), 45  
    .throw, SBMLInfo-method  
        (SBMLProblem-class), 45  
    .throw, SBMLProblems-method  
        (SBMLProblems-class), 45  
    .throw, SBMLWarning-method  
        (SBMLProblem-class), 45

    acot (math), 26  
    acoth (math), 26  
    acsc (math), 26  
    acsch (math), 26  
    additionalGraphicalObjects  
        (Layout-class), 24  
    additionalGraphicalObjects, Layout-method  
        (Layout-class), 24  
    additionalGraphicalObjects<--  
        (Layout-class), 24  
    additionalGraphicalObjects<-, Layout-method  
        (Layout-class), 24  
    AlgebraicRule-class, 3

annotation (SBase-class), 40  
annotation, SBase-method (SBase-class), 40  
annotation<- (SBase-class), 40  
annotation<-, SBase-method (SBase-class), 40  
array, 48  
as.character.SBML (SBML-class), 42  
as.character.SBMLDocument (SBMLDocument-class), 43  
as.ts, 49  
as.ts, SOSResult-method (SOSResult-class), 51  
asec (math), 26  
asech (math), 26  
AssignmentRule, 9, 23, 33, 55  
AssignmentRule-class, 4  
  
basePoint1 (CubicBezier-class), 11  
basePoint1, CubicBezier-method (CubicBezier-class), 11  
basePoint1<- (CubicBezier-class), 11  
basePoint1<-, CubicBezier-method (CubicBezier-class), 11  
basePoint2 (CubicBezier-class), 11  
basePoint2, CubicBezier-method (CubicBezier-class), 11  
basePoint2<- (CubicBezier-class), 11  
basePoint2<-, CubicBezier-method (CubicBezier-class), 11  
biologicalQualifierType (CVTerm-class), 13  
biologicalQualifierType, CVTerm-method (CVTerm-class), 13  
biologicalQualifierType<- (CVTerm-class), 13  
biologicalQualifierType<-, CVTerm-method (CVTerm-class), 13  
boundaryCondition (Species-class), 53  
boundaryCondition, Species-method (Species-class), 53  
boundaryCondition<- (Species-class), 53  
boundaryCondition<-, Species-method (Species-class), 53  
boundingBox (GraphicalObject-class), 21  
boundingBox, GraphicalObject-method (GraphicalObject-class), 21  
BoundingBox-class, 5  
boundingBox<- (GraphicalObject-class), 21  
boundingBox<-, GraphicalObject-method (GraphicalObject-class), 21  
charge (Species-class), 53  
charge, Species-method (Species-class), 53  
charge<- (Species-class), 53  
charge<-, Species-method (Species-class), 53  
coerce (SBML-class), 42  
coerce, SBML, graph-method (SBML-class), 42  
coerce, SBML, SBMLDocument-method (SBML-class), 42  
coerce, SBMLDocument, graph-method (SBMLDocument-class), 43  
coerce, SBMLDocument, SBML-method (SBMLDocument-class), 43  
Compartment, 4, 7–9, 18, 27, 35, 47, 51, 52  
compartment (Species-class), 53  
compartment, CompartmentGlyph-method (CompartmentGlyph-class), 7  
compartment, CompartmentVolumeRule-method (CompartmentVolumeRule-class), 9  
compartment, Species-method (Species-class), 53  
Compartment-class, 6  
compartment<- (Species-class), 53  
compartment<-, CompartmentGlyph-method (CompartmentGlyph-class), 7  
compartment<-, CompartmentVolumeRule-method (CompartmentVolumeRule-class), 9  
compartment<-, Species-method (Species-class), 53  
CompartmentGlyph, 24  
CompartmentGlyph-class, 7  
compartmentGlyphs (Layout-class), 24  
compartmentGlyphs, Layout-method (Layout-class), 24  
compartmentGlyphs<- (Layout-class), 24  
compartmentGlyphs<-, Layout-method (Layout-class), 24  
compartments (Model-class), 27  
compartments, Model-method (Model-class), 27  
compartments, SOSResult-method (SOSResult-class), 51  
compartments<- (Model-class), 27  
compartments<-, Model-method (Model-class), 27  
CompartmentType, 27  
CompartmentType-class, 8  
compartmentTypes (Model-class), 27

compartmentTypes,Model-method  
     (Model-class), 27  
 compartmentTypes<- (Model-class), 27  
 compartmentTypes<-,Model-method  
     (Model-class), 27  
 CompartmentVolumeRule-class, 9  
 condition, 45  
 constant (Species-class), 53  
 constant,Compartment-method  
     (Compartment-class), 6  
 constant,Parameter-method  
     (Parameter-class), 32  
 constant,Species-method  
     (Species-class), 53  
 constant<- (Species-class), 53  
 constant<-,Compartment-method  
     (Compartment-class), 6  
 constant<-,Parameter-method  
     (Parameter-class), 32  
 constant<-,Species-method  
     (Species-class), 53  
 Constraint, 27  
 Constraint-class, 10  
 constraints (Model-class), 27  
 constraints,Model-method (Model-class),  
     27  
 constraints<- (Model-class), 27  
 constraints<-,Model-method  
     (Model-class), 27  
 cot (math), 26  
 coth (math), 26  
 createdDate (ModelHistory-class), 30  
 createdDate,ModelHistory-method  
     (ModelHistory-class), 30  
 createdDate<- (ModelHistory-class), 30  
 createdDate<-,ModelHistory,character-method  
     (ModelHistory-class), 30  
 createdDate<-,ModelHistory,POSIXt-method  
     (ModelHistory-class), 30  
 creators (ModelHistory-class), 30  
 creators,ModelHistory-method  
     (ModelHistory-class), 30  
 creators<- (ModelHistory-class), 30  
 creators<-,ModelHistory-method  
     (ModelHistory-class), 30  
 csc (math), 26  
 csch (math), 26  
 CubicBezier-class, 11  
 Curve-class, 12  
 curveSegments (Curve-class), 12  
 curveSegments,Curve-method  
     (Curve-class), 12  
 curveSegments<- (Curve-class), 12  
 curveSegments<-,Curve-method  
     (Curve-class), 12  
 CVTerm, 3–12, 14, 16–18, 20–24, 26, 28,  
     31–36, 38–40, 42, 46, 53, 55–64  
 CVTerm-class, 13  
 cvTerms (SBase-class), 40  
 cvTerms,SBase-method (SBase-class), 40  
 cvTerms<- (SBase-class), 40  
 cvTerms<-,SBase-method (SBase-class), 40  
 Delay-class, 14  
 depth (Dimensions-class), 15  
 depth,Dimensions-method  
     (Dimensions-class), 15  
 depth<- (Dimensions-class), 15  
 depth<-,Dimensions-method  
     (Dimensions-class), 15  
 Describable, 52  
 Describable-class (describe), 15  
 describe, 15, 15  
 describe,AlgebraicRule-method  
     (describe), 15  
 describe,AssignmentRule-method  
     (describe), 15  
 describe,BoundingBox-method (describe),  
     15  
 describe,Compartment-method (describe),  
     15  
 describe,CompartmentGlyph-method  
     (describe), 15  
 describe,CompartmentType-method  
     (describe), 15  
 describe,CompartmentVolumeRule-method  
     (describe), 15  
 describe,Constraint-method (describe),  
     15  
 describe,CubicBezier-method (describe),  
     15  
 describe,Curve-method (describe), 15  
 describe,CVTerm-method (describe), 15  
 describe,Delay-method (describe), 15  
 describe,Dimensions-method (describe),  
     15  
 describe,Event-method (describe), 15  
 describe,EventAssignment-method  
     (describe), 15  
 describe,FunctionDefinition-method  
     (describe), 15  
 describe,GraphicalObject-method  
     (describe), 15  
 describe,InitialAssignment-method  
     (describe), 15

describe, KineticLaw-method (describe), 15  
describe, Layout-method (describe), 15  
describe, LineSegment-method (describe), 15  
describe, list-method (describe), 15  
describe, Model-method (describe), 15  
describe, ModelCreator-method (describe), 15  
describe, ModelHistory-method (describe), 15  
describe, Parameter-method (describe), 15  
describe, ParameterRule-method (describe), 15  
describe, Point-method (describe), 15  
describe, RateRule-method (describe), 15  
describe, Reaction-method (describe), 15  
describe, ReactionGlyph-method (describe), 15  
describe, SBML-method (describe), 15  
describe, SimpleSpeciesReference-method (describe), 15  
describe, Species-method (describe), 15  
describe, SpeciesConcentrationRule-method (describe), 15  
describe, SpeciesGlyph-method (describe), 15  
describe, SpeciesReference-method (describe), 15  
describe, SpeciesReferenceGlyph-method (describe), 15  
describe, SpeciesType-method (describe), 15  
describe, StoichiometryMath-method (describe), 15  
describe, TextGlyph-method (describe), 15  
describe, Trigger-method (describe), 15  
describe, Unit-method (describe), 15  
describe, UnitDefinition-method (describe), 15  
describe-methods (describe), 15  
design (Experiment-class), 19  
design, Experiment-method (Experiment-class), 19  
design<- (Experiment-class), 19  
design<-, Experiment-method (Experiment-class), 19  
dimensions (Layout-class), 24  
dimensions, BoundingBox-method (BoundingBox-class), 5  
dimensions, Layout-method (Layout-class), 24  
Dimensions-class, 15  
dimensions<- (Layout-class), 24  
dimensions<-, BoundingBox-method (BoundingBox-class), 5  
dimensions<-, Layout-method (Layout-class), 24  
email (ModelCreator-class), 29  
email, ModelCreator-method (ModelCreator-class), 29  
email<- (ModelCreator-class), 29  
email<-, ModelCreator-method (ModelCreator-class), 29  
end (LineSegment-class), 25  
end, LineSegment-method (LineSegment-class), 25  
end<- (LineSegment-class), 25  
end<-, LineSegment-method (LineSegment-class), 25  
errors (SBMLProblems-class), 45  
errors, SBMLProblems-method (SBMLProblems-class), 45  
Event, 14, 27, 48, 50, 62, 63  
Event-class, 16  
EventAssignment, 14, 17  
EventAssignment-class, 18  
eventAssignments (Event-class), 16  
eventAssignments, Event-method (Event-class), 16  
eventAssignments<- (Event-class), 16  
eventAssignments<-, Event-method (Event-class), 16  
eventDelay (Event-class), 16  
eventDelay, Event-method (Event-class), 16  
eventDelay<- (Event-class), 16  
eventDelay<-, Event-method (Event-class), 16  
events (Model-class), 27  
events, Model-method (Model-class), 27  
events<- (Model-class), 27  
events<-, Model-method (Model-class), 27  
Experiment, 48, 49  
Experiment-class, 19  
ExperimentDesign, 48  
ExperimentDesign-class (Experiment-class), 19  
ExperimentProtocol, 51  
ExperimentProtocol-class (Experiment-class), 19  
ExperimentResult, 51  
ExperimentResult-class (Experiment-class), 19

ExperimentSubject, 52  
 ExperimentSubject-class  
     (Experiment-class), 19  
 exponent (Unit-class), 63  
 exponent,Unit-method (Unit-class), 63  
 exponent<- (Unit-class), 63  
 exponent<-,Unit-method (Unit-class), 63  
  
 familyName (ModelCreator-class), 29  
 familyName,ModelCreator-method  
     (ModelCreator-class), 29  
 familyName<- (ModelCreator-class), 29  
 familyName<-,ModelCreator-method  
     (ModelCreator-class), 29  
 fast (Reaction-class), 36  
 fast,Reaction-method (Reaction-class),  
     36  
 fast<- (Reaction-class), 36  
 fast<-,Reaction-method  
     (Reaction-class), 36  
 fatals (SBMLProblems-class), 45  
 fatals,SBMLProblems-method  
     (SBMLProblems-class), 45  
 FunctionDefinition, 27  
 FunctionDefinition-class, 20  
 functionDefinitions (Model-class), 27  
 functionDefinitions,Model-method  
     (Model-class), 27  
 functionDefinitions<- (Model-class), 27  
 functionDefinitions<-,Model-method  
     (Model-class), 27  
  
 givenName (ModelCreator-class), 29  
 givenName,ModelCreator-method  
     (ModelCreator-class), 29  
 givenName<- (ModelCreator-class), 29  
 givenName<-,ModelCreator-method  
     (ModelCreator-class), 29  
 glyphCurve (ReactionGlyph-class), 37  
 glyphCurve,ReactionGlyph-method  
     (ReactionGlyph-class), 37  
 glyphCurve,SpeciesReferenceGlyph-method  
     (SpeciesReferenceGlyph-class),  
     58  
 glyphCurve<- (ReactionGlyph-class), 37  
 glyphCurve<-,ReactionGlyph-method  
     (ReactionGlyph-class), 37  
 glyphCurve<-,SpeciesReferenceGlyph-method  
     (SpeciesReferenceGlyph-class),  
     58  
 graph, 44  
 GraphicalObject, 7, 24, 38, 56, 58, 61  
 graphicalObject (TextGlyph-class), 61

graphicalObject,TextGlyph-method  
     (TextGlyph-class), 61  
 GraphicalObject-class, 21  
 graphicalObject<- (TextGlyph-class), 61  
 graphicalObject<-,TextGlyph-method  
     (TextGlyph-class), 61  
  
 hasOnlySubstanceUnits (Species-class),  
     53  
 hasOnlySubstanceUnits,Species-method  
     (Species-class), 53  
 hasOnlySubstanceUnits<-  
     (Species-class), 53  
 hasOnlySubstanceUnits<-,Species-method  
     (Species-class), 53  
 height (Dimensions-class), 15  
 height,Dimensions-method  
     (Dimensions-class), 15  
 height<- (Dimensions-class), 15  
 height<-,Dimensions-method  
     (Dimensions-class), 15  
  
 id (UnitDefinition-class), 64  
 id,BoundingBox-method  
     (BoundingBox-class), 5  
 id,Compartment-method  
     (Compartment-class), 6  
 id,CompartmentType-method  
     (CompartmentType-class), 8  
 id,Event-method (Event-class), 16  
 id,FunctionDefinition-method  
     (FunctionDefinition-class), 20  
 id,GraphicalObject-method  
     (GraphicalObject-class), 21  
 id,Layout-method (Layout-class), 24  
 id,Model-method (Model-class), 27  
 id,Parameter-method (Parameter-class),  
     32  
 id,Reaction-method (Reaction-class), 36  
 id,SimpleSpeciesReference-method  
     (SimpleSpeciesReference-class),  
     46  
 id,Species-method (Species-class), 53  
 id,SpeciesType-method  
     (SpeciesType-class), 59  
 id,UnitDefinition-method  
     (UnitDefinition-class), 64  
 id<- (UnitDefinition-class), 64  
 id<-,BoundingBox-method  
     (BoundingBox-class), 5  
 id<-,Compartment-method  
     (Compartment-class), 6

id<-, CompartmentType-method  
     (CompartmentType-class), 8  
 id<-, Event-method (Event-class), 16  
 id<-, FunctionDefinition-method  
     (FunctionDefinition-class), 20  
 id<-, GraphicalObject-method  
     (GraphicalObject-class), 21  
 id<-, Layout-method (Layout-class), 24  
 id<-, Model-method (Model-class), 27  
 id<-, Parameter-method  
     (Parameter-class), 32  
 id<-, Reaction-method (Reaction-class),  
     36  
 id<-, SimpleSpeciesReference-method  
     (SimpleSpeciesReference-class),  
     46  
 id<-, Species-method (Species-class), 53  
 id<-, SpeciesType-method  
     (SpeciesType-class), 59  
 id<-, UnitDefinition-method  
     (UnitDefinition-class), 64  
 infos (SBMLProblems-class), 45  
 infos, SBMLProblems-method  
     (SBMLProblems-class), 45  
 initialAmount (Species-class), 53  
 initialAmount, Species-method  
     (Species-class), 53  
 initialAmount<- (Species-class), 53  
 initialAmount<-, Species-method  
     (Species-class), 53  
 InitialAssignment, 28  
 InitialAssignment-class, 22  
 initialAssignments (Model-class), 27  
 initialAssignments, Model-method  
     (Model-class), 27  
 initialAssignments<- (Model-class), 27  
 initialAssignments<-, Model-method  
     (Model-class), 27  
 initialConcentration (Species-class), 53  
 initialConcentration, Species-method  
     (Species-class), 53  
 initialConcentration<- (Species-class),  
     53  
 initialConcentration<-, Species-method  
     (Species-class), 53  
  
 kind (Unit-class), 63  
 kind, Unit-method (Unit-class), 63  
 kind<- (Unit-class), 63  
 kind<-, Unit-method (Unit-class), 63  
 KineticLaw, 47, 48  
 KineticLaw (Reaction-class), 36  
  
 kineticLaw, Reaction-method  
     (Reaction-class), 36  
 KineticLaw-class, 23  
 kineticLaw<- (Reaction-class), 36  
 kineticLaw<-, Reaction-method  
     (Reaction-class), 36  
  
 Layout, 27  
 Layout-class, 24  
 layouts (Model-class), 27  
 layouts, Model-method (Model-class), 27  
 layouts<- (Model-class), 27  
 layouts<-, Model-method (Model-class), 27  
 level (SBML-class), 42  
 level, SBML-method (SBML-class), 42  
 level<- (SBML-class), 42  
 level<-, SBML-method (SBML-class), 42  
 LineSegment, 11, 12  
 LineSegment-class, 25  
  
 math, 26  
 math (KineticLaw-class), 23  
 math, Constraint-method  
     (Constraint-class), 10  
 math, Delay-method (Delay-class), 14  
 math, EventAssignment-method  
     (EventAssignment-class), 18  
 math, FunctionDefinition-method  
     (FunctionDefinition-class), 20  
 math, InitialAssignment-method  
     (InitialAssignment-class), 22  
 math, KineticLaw-method  
     (KineticLaw-class), 23  
 math, ParameterRule-method  
     (ParameterRule-class), 33  
 math, Rule-method (Rule-class), 39  
 math, StoichiometryMath-method  
     (StoichiometryMath-class), 60  
 math, Trigger-method (Trigger-class), 62  
 math<- (KineticLaw-class), 23  
 math<-, Constraint-method  
     (Constraint-class), 10  
 math<-, Delay-method (Delay-class), 14  
 math<-, EventAssignment-method  
     (EventAssignment-class), 18  
 math<-, FunctionDefinition-method  
     (FunctionDefinition-class), 20  
 math<-, InitialAssignment-method  
     (InitialAssignment-class), 22  
 math<-, KineticLaw-method  
     (KineticLaw-class), 23  
 math<-, ParameterRule-method  
     (ParameterRule-class), 33

math<-, Rule-method (Rule-class), 39  
 math<-, StoichiometryMath-method  
     (StoichiometryMath-class), 60  
 math<-, Trigger-method (Trigger-class),  
     62  
 matrix, 47, 48  
 message, 45  
 metaId (SBase-class), 40  
 metaId, SBase-method (SBase-class), 40  
 metaId<- (SBase-class), 40  
 metaId<-, SBase-method (SBase-class), 40  
 Model, 42, 49  
 model (SBML-class), 42  
 model, SBML-method (SBML-class), 42  
 Model-class, 27  
 model<- (SBML-class), 42  
 model<-, SBML-method (SBML-class), 42  
 ModelCreator, 30  
 ModelCreator-class, 29  
 ModelHistory, 28  
 modelHistory (Model-class), 27  
 modelHistory, Model-method  
     (Model-class), 27  
 ModelHistory-class, 30  
 modelHistory<- (Model-class), 27  
 modelHistory<-, Model-method  
     (Model-class), 27  
 modelQualifierType (CVTerm-class), 13  
 modelQualifierType, CVTerm-method  
     (CVTerm-class), 13  
 modelQualifierType<- (CVTerm-class), 13  
 modelQualifierType<-, CVTerm-method  
     (CVTerm-class), 13  
 modifiedDate (ModelHistory-class), 30  
 modifiedDate, ModelHistory-method  
     (ModelHistory-class), 30  
 modifiedDate<- (ModelHistory-class), 30  
 modifiedDate<-, ModelHistory, character-method  
     (ModelHistory-class), 30  
 modifiedDate<-, ModelHistory, POSIXt-method  
     (ModelHistory-class), 30  
 modifiedDate<-, ModelHistory-method  
     (ModelHistory-class), 30  
 modifiers (Reaction-class), 36  
 modifiers, Reaction-method  
     (Reaction-class), 36  
 modifiers<- (Reaction-class), 36  
 modifiers<-, Reaction-method  
     (Reaction-class), 36  
 ModifierSpeciesReference, 36  
 ModifierSpeciesReference-class, 31  
 msg (Constraint-class), 10  
 msg, Constraint-method  
     (Constraint-class), 10  
 msg<- (Constraint-class), 10  
 msg<-, Constraint-method  
     (Constraint-class), 10  
 multiplier (Unit-class), 63  
 multiplier, Unit-method (Unit-class), 63  
 multiplier<- (Unit-class), 63  
 multiplier<-, Unit-method (Unit-class),  
     63  
 name (UnitDefinition-class), 64  
 name, Compartment-method  
     (Compartment-class), 6  
 name, CompartmentType-method  
     (CompartmentType-class), 8  
 name, Event-method (Event-class), 16  
 name, FunctionDefinition-method  
     (FunctionDefinition-class), 20  
 name, Model-method (Model-class), 27  
 name, Parameter-method  
     (Parameter-class), 32  
 name, ParameterRule-method  
     (ParameterRule-class), 33  
 name, Reaction-method (Reaction-class),  
     36  
 name, Species-method (Species-class), 53  
 name, SpeciesType-method  
     (SpeciesType-class), 59  
 name, UnitDefinition-method  
     (UnitDefinition-class), 64  
 name<- (UnitDefinition-class), 64  
 name<-, Compartment-method  
     (Compartment-class), 6  
 name<-, CompartmentType-method  
     (CompartmentType-class), 8  
 name<-, Event-method (Event-class), 16  
 name<-, FunctionDefinition-method  
     (FunctionDefinition-class), 20  
 name<-, Model-method (Model-class), 27  
 name<-, Parameter-method  
     (Parameter-class), 32  
 name<-, ParameterRule-method  
     (ParameterRule-class), 33  
 name<-, Reaction-method  
     (Reaction-class), 36  
 name<-, Species-method (Species-class),  
     53  
 name<-, SpeciesType-method  
     (SpeciesType-class), 59  
 name<-, UnitDefinition-method  
     (UnitDefinition-class), 64  
 notes (SBase-class), 40

notes, SBase-method (SBase-class), 40  
notes<- (SBase-class), 40  
notes<-, SBase-method (SBase-class), 40

offset (Unit-class), 63  
offset, Unit-method (Unit-class), 63  
offset<- (Unit-class), 63  
offset<-, Unit-method (Unit-class), 63  
oldClass, 43  
OptionalCurve-class (Curve-class), 12  
OptionalDelay-class (Delay-class), 14  
OptionalKineticLaw-class  
    (KineticLaw-class), 23  
OptionalModelHistory-class  
    (ModelHistory-class), 30  
OptionalStoichiometryMath-class  
    (StoichiometryMath-class), 60  
organization (ModelCreator-class), 29  
organization, ModelCreator-method  
    (ModelCreator-class), 29  
organization<- (ModelCreator-class), 29  
organization<-, ModelCreator-method  
    (ModelCreator-class), 29  
originOfText (TextGlyph-class), 61  
originOfText, TextGlyph-method  
    (TextGlyph-class), 61  
originOfText<- (TextGlyph-class), 61  
originOfText<-, TextGlyph-method  
    (TextGlyph-class), 61  
outside (Compartment-class), 6  
outside, Compartment-method  
    (Compartment-class), 6  
outside<- (Compartment-class), 6  
outside<-, Compartment-method  
    (Compartment-class), 6

Parameter, 4, 18, 23, 27, 33, 35, 47, 48, 51, 52  
Parameter-class, 32  
ParameterRule-class, 33  
parameters (Model-class), 27  
parameters, KineticLaw-method  
    (KineticLaw-class), 23  
parameters, Model-method (Model-class),  
    27  
parameters, SOSResult-method  
    (SOSResult-class), 51  
parameters<- (Model-class), 27  
parameters<-, KineticLaw-method  
    (KineticLaw-class), 23  
parameters<-, Model-method  
    (Model-class), 27  
Point-class, 34  
position (BoundingBox-class), 5

position, BoundingBox-method  
    (BoundingBox-class), 5  
position<- (BoundingBox-class), 5  
position<-, BoundingBox-method  
    (BoundingBox-class), 5  
POSIXt, 30  
products (Reaction-class), 36  
products, Reaction-method  
    (Reaction-class), 36  
products<- (Reaction-class), 36  
products<-, Reaction-method  
    (Reaction-class), 36  
protocol (Experiment-class), 19  
protocol, Experiment-method  
    (Experiment-class), 19  
protocol<- (Experiment-class), 19  
protocol<-, Experiment-method  
    (Experiment-class), 19

qualifierType (CVTerm-class), 13  
qualifierType, CVTerm-method  
    (CVTerm-class), 13  
qualifierType<- (CVTerm-class), 13  
qualifierType<-, CVTerm-method  
    (CVTerm-class), 13

RateRule-class, 35  
reactants (Reaction-class), 36  
reactants, Reaction-method  
    (Reaction-class), 36  
reactants<- (Reaction-class), 36  
reactants<-, Reaction-method  
    (Reaction-class), 36  
Reaction, 23, 27, 31, 37, 38, 46, 51, 52, 57  
reaction (ReactionGlyph-class), 37  
reaction, ReactionGlyph-method  
    (ReactionGlyph-class), 37  
Reaction-class, 36  
reaction<- (ReactionGlyph-class), 37  
reaction<-, ReactionGlyph-method  
    (ReactionGlyph-class), 37  
ReactionGlyph, 24  
ReactionGlyph-class, 37  
reactionGlyphs (Layout-class), 24  
reactionGlyphs, Layout-method  
    (Layout-class), 24  
reactionGlyphs<- (Layout-class), 24  
reactionGlyphs<-, Layout-method  
    (Layout-class), 24  
reactions (Model-class), 27  
reactions, Model-method (Model-class), 27  
reactions, SOSDesign-method  
    (SOSDesign-class), 47

reactions, SOSResult-method  
     (SOSResult-class), 51  
 reactions<- (Model-class), 27  
 reactions<-, Experiment-method  
     (Experiment-class), 19  
 reactions<-, Model-method (Model-class),  
     27  
 reactions<-, SOSDesign-method  
     (SOSDesign-class), 47  
 resources (CVTerm-class), 13  
 resources, CVTerm-method (CVTerm-class),  
     13  
 resources<- (CVTerm-class), 13  
 resources<-, CVTerm-method  
     (CVTerm-class), 13  
 result (Experiment-class), 19  
 result, Experiment-method  
     (Experiment-class), 19  
 result<- (Experiment-class), 19  
 result<-, Experiment-method  
     (Experiment-class), 19  
 reversible (Reaction-class), 36  
 reversible, Reaction-method  
     (Reaction-class), 36  
 reversible<- (Reaction-class), 36  
 reversible<-, Reaction-method  
     (Reaction-class), 36  
 role (SpeciesReferenceGlyph-class), 58  
 role, SpeciesReferenceGlyph-method  
     (SpeciesReferenceGlyph-class),  
     58  
 role<- (SpeciesReferenceGlyph-class), 58  
 role<-, SpeciesReferenceGlyph-method  
     (SpeciesReferenceGlyph-class),  
     58  
 rsbml\_check, 43  
 rsbml\_check (SBMLDocument-class), 43  
 rsbml\_check, SBML-method (SBML-class), 42  
 rsbml\_check, SBMLDocument-method  
     (SBMLDocument-class), 43  
 rsbml\_doc (SBML-class), 42  
 rsbml\_doc, SBML-method (SBML-class), 42  
 rsbml\_dom (SBMLDocument-class), 43  
 rsbml\_dom, SBMLDocument-method  
     (SBMLDocument-class), 43  
 rsbml\_graph (SBMLDocument-class), 43  
 rsbml\_graph, Model-method  
     (SBMLDocument-class), 43  
 rsbml\_graph, SBML-method (SBML-class), 42  
 rsbml\_graph, SBMLDocument-method  
     (SBMLDocument-class), 43  
 rsbml\_problems, 46  
 rsbml\_problems (SBMLDocument-class), 43  
 rsbml\_problems, SBMLDocument-method  
     (SBMLDocument-class), 43  
 rsbml\_read (SBML import), 41  
 rsbml\_write (SBML-class), 42  
 rsbml\_write, SBML-method (SBML-class), 42  
 rsbml\_write, SBMLDocument-method  
     (SBMLDocument-class), 43  
 rsbml\_xml (SBML-class), 42  
 rsbml\_xml, SBML-method (SBML-class), 42  
 rsbml\_xml, SBMLDocument-method  
     (SBMLDocument-class), 43  
 Rule, 3, 4, 9, 27, 33, 35, 55  
 Rule-class, 39  
 rules (Model-class), 27  
 rules, Model-method (Model-class), 27  
 rules<- (Model-class), 27  
 rules<-, Model-method (Model-class), 27  
 SBase, 3–12, 14, 16–18, 20–24, 26, 28, 31–35,  
     37–39, 42, 46, 52, 54–62, 64, 65  
 SBase-class, 40  
 SBML, 41, 48, 52  
 SBML import, 41  
 SBML-class, 42  
 SBMLDocument, 41, 43, 49  
 SBMLDocument-class, 43  
 SBMLError, 45  
 SBMLError-class (SBMLProblem-class), 45  
 SBMLFatal, 45  
 SBMLFatal-class (SBMLProblem-class), 45  
 SBMLInfo, 45  
 SBMLInfo-class (SBMLProblem-class), 45  
 SBMLProblem, 46  
 SBMLProblem-class, 45  
 SBMLProblems, 45  
 SBMLProblems-class, 45  
 SBMLWarning, 45  
 SBMLWarning-class (SBMLProblem-class),  
     45  
 sboTerm (SBase-class), 40  
 sboTerm, SBase-method (SBase-class), 40  
 sboTerm<- (SBase-class), 40  
 sboTerm<-, SBase-method (SBase-class), 40  
 sec (math), 26  
 sech (math), 26  
 show, Describable-method (describe), 15  
 show, SBMLProblem-method  
     (SBMLProblem-class), 45  
 SimpleSpeciesReference, 31, 57  
 SimpleSpeciesReference-class, 46  
 simulate, 44, 50  
 simulate (SOSExperiment-class), 48

simulate, SBML-method (SBML-class), 42  
simulate, SBMLDocument-method (SBMLDocument-class), 43  
simulate, SOSExperiment-method (SOSExperiment-class), 48  
size (Compartment-class), 6  
size, Compartment-method (Compartment-class), 6  
size<- (Compartment-class), 6  
size<-, Compartment-method (Compartment-class), 6  
SOSDesign, 48, 49, 51  
SOSDesign-class, 47  
SOSExperiment, 19, 48, 51–53  
SOSExperiment-class, 48  
SOSProtocol, 44, 47–49  
SOSProtocol-class, 50  
SOSResult, 49  
SOSResult-class, 51  
SOSSubject, 48, 49  
SOSSubject-class, 52  
spatialDimensions (Compartment-class), 6  
spatialDimensions, Compartment-method (Compartment-class), 6  
spatialDimensions<- (Compartment-class), 6  
spatialDimensions<-, Compartment-method (Compartment-class), 6  
spatialSizeUnits (Species-class), 53  
spatialSizeUnits, Species-method (Species-class), 53  
spatialSizeUnits<- (Species-class), 53  
spatialSizeUnits<-, Species-method (Species-class), 53  
Species, 4, 6, 18, 27, 31, 35, 36, 46, 47, 51, 52, 55–60  
species (SpeciesGlyph-class), 56  
species, Model-method (Model-class), 27  
species, SimpleSpeciesReference-method (SimpleSpeciesReference-class), 46  
species, SOSResult-method (SOSResult-class), 51  
species, SpeciesConcentrationRule-method (SpeciesConcentrationRule-class), 55  
species, SpeciesGlyph-method (SpeciesGlyph-class), 56  
Species-class, 53  
species<- (SpeciesGlyph-class), 56  
species<-, Model-method (Model-class), 27  
species<-, SimpleSpeciesReference-method (SimpleSpeciesReference-class), 46  
species<-, SpeciesConcentrationRule-method (SpeciesConcentrationRule-class), 55  
species<-, SpeciesGlyph-method (SpeciesGlyph-class), 56  
SpeciesConcentrationRule-class, 55  
SpeciesGlyph, 24, 58  
speciesGlyph (SpeciesReferenceGlyph-class), 58  
speciesGlyph, SpeciesReferenceGlyph-method (SpeciesReferenceGlyph-class), 58  
SpeciesGlyph-class, 56  
speciesGlyph<- (SpeciesReferenceGlyph-class), 58  
speciesGlyph<-, SpeciesReferenceGlyph-method (SpeciesReferenceGlyph-class), 58  
speciesGlyphs (Layout-class), 24  
speciesGlyphs, Layout-method (Layout-class), 24  
speciesGlyphs<- (Layout-class), 24  
speciesGlyphs<-, Layout-method (Layout-class), 24  
SpeciesReference, 36, 38, 58, 60  
speciesReference (SpeciesReferenceGlyph-class), 58  
speciesReference, SpeciesReferenceGlyph-method (SpeciesReferenceGlyph-class), 58  
SpeciesReference-class, 57  
speciesReference<- (SpeciesReferenceGlyph-class), 58  
speciesReference<-, SpeciesReferenceGlyph-method (SpeciesReferenceGlyph-class), 58  
SpeciesReferenceGlyph, 38  
SpeciesReferenceGlyph-class, 58  
speciesReferenceGlyphs (ReactionGlyph-class), 37  
speciesReferenceGlyphs, ReactionGlyph-method (ReactionGlyph-class), 37  
speciesReferenceGlyphs<- (ReactionGlyph-class), 37  
speciesReferenceGlyphs<-, ReactionGlyph-method (ReactionGlyph-class), 37

SpeciesType, 27  
 SpeciesType-class, 59  
 speciesTypes (Model-class), 27  
 speciesTypes, Model-method  
     (Model-class), 27  
 speciesTypes<- (Model-class), 27  
 speciesTypes<-, Model-method  
     (Model-class), 27  
 start (LineSegment-class), 25  
 start, LineSegment-method  
     (LineSegment-class), 25  
 start<- (LineSegment-class), 25  
 start<-, LineSegment-method  
     (LineSegment-class), 25  
 stoichiometry (SpeciesReference-class), 57  
 stoichiometry, SpeciesReference-method  
     (SpeciesReference-class), 57  
 stoichiometry<-  
     (SpeciesReference-class), 57  
 stoichiometry<-, SpeciesReference-method  
     (SpeciesReference-class), 57  
 stoichiometryMath  
     (SpeciesReference-class), 57  
 stoichiometryMath, SpeciesReference-method  
     (SpeciesReference-class), 57  
 StoichiometryMath-class, 60  
 stoichiometryMath<-  
     (SpeciesReference-class), 57  
 stoichiometryMath<-, SpeciesReference-method  
     (SpeciesReference-class), 57  
 stoichiometryMatrix (Model-class), 27  
 stoichiometryMatrix, Model-method  
     (Model-class), 27  
 structure, 48  
 subject (Experiment-class), 19  
 subject, Experiment-method  
     (Experiment-class), 19  
 subject<- (Experiment-class), 19  
 subject<-, Experiment-method  
     (Experiment-class), 19  
 substanceUnits (KineticLaw-class), 23  
 substanceUnits, KineticLaw-method  
     (KineticLaw-class), 23  
 substanceUnits, Species-method  
     (Species-class), 53  
 substanceUnits<- (KineticLaw-class), 23  
 substanceUnits<-, KineticLaw-method  
     (KineticLaw-class), 23  
 substanceUnits<-, Species-method  
     (Species-class), 53  
 symbol (InitialAssignment-class), 22  
 symbol, InitialAssignment-method  
     (InitialAssignment-class), 22  
 symbol<- (InitialAssignment-class), 22  
 symbol<-, InitialAssignment-method  
     (InitialAssignment-class), 22  
 Sys.time, 30  
 text (TextGlyph-class), 61  
 text, TextGlyph-method  
     (TextGlyph-class), 61  
 text<- (TextGlyph-class), 61  
 text<-, TextGlyph-method  
     (TextGlyph-class), 61  
 TextGlyph, 24  
 TextGlyph-class, 61  
 textGlyphs (Layout-class), 24  
 textGlyphs, Layout-method  
     (Layout-class), 24  
 textGlyphs<- (Layout-class), 24  
 textGlyphs<-, Layout-method  
     (Layout-class), 24  
 timeUnits (KineticLaw-class), 23  
 timeUnits, Event-method (Event-class), 16  
 timeUnits, KineticLaw-method  
     (KineticLaw-class), 23  
 timeUnits<- (KineticLaw-class), 23  
 timeUnits<-, Event-method (Event-class), 16  
 timeUnits<-, KineticLaw-method  
     (KineticLaw-class), 23  
 Trigger, 14  
 trigger (Event-class), 16  
 trigger, Event-method (Event-class), 16  
 Trigger-class, 62  
 trigger<- (Event-class), 16  
 trigger<-, Event-method (Event-class), 16  
 type (AssignmentRule-class), 4  
 type, AssignmentRule-method  
     (AssignmentRule-class), 4  
 type, ParameterRule-method  
     (ParameterRule-class), 33  
 type<- (AssignmentRule-class), 4  
 type<-, AssignmentRule-method  
     (AssignmentRule-class), 4  
 type<-, ParameterRule-method  
     (ParameterRule-class), 33  
 Unit, 64  
 Unit-class, 63  
 UnitDefinition, 6, 27  
 UnitDefinition-class, 64  
 unitDefinitions (Model-class), 27

unitDefinitions,Model-method  
(Model-class), 27  
unitDefinitions<- (Model-class), 27  
unitDefinitions<-,Model-method  
(Model-class), 27  
units (UnitDefinition-class), 64  
units,Compartment-method  
(Compartment-class), 6  
units,Parameter-method  
(Parameter-class), 32  
units,ParameterRule-method  
(ParameterRule-class), 33  
units,Species-method (Species-class), 53  
units,UnitDefinition-method  
(UnitDefinition-class), 64  
units<- (UnitDefinition-class), 64  
units<-,Compartment-method  
(Compartment-class), 6  
units<-,Parameter-method  
(Parameter-class), 32  
units<-,ParameterRule-method  
(ParameterRule-class), 33  
units<-,Species-method (Species-class),  
53  
units<-,UnitDefinition-method  
(UnitDefinition-class), 64  
unitScale (Unit-class), 63  
unitScale,Unit-method (Unit-class), 63  
unitScale<- (Unit-class), 63  
unitScale<-,Unit-method (Unit-class), 63  
value (Parameter-class), 32  
value,Parameter-method  
(Parameter-class), 32  
value<- (Parameter-class), 32  
value<-,Parameter-method  
(Parameter-class), 32  
variable (RateRule-class), 35  
variable,AssignmentRule-method  
(AssignmentRule-class), 4  
variable,EventAssignment-method  
(EventAssignment-class), 18  
variable,ParameterRule-method  
(ParameterRule-class), 33  
variable,RateRule-method  
(RateRule-class), 35  
variable<- (RateRule-class), 35  
variable<-,AssignmentRule-method  
(AssignmentRule-class), 4  
variable<-,EventAssignment-method  
(EventAssignment-class), 18  
variable<-,ParameterRule-method  
(ParameterRule-class), 33  
variable<-,RateRule-method  
(RateRule-class), 35  
vector, 48  
ver (SBML-class), 42  
ver, SBML-method (SBML-class), 42  
ver<- (SBML-class), 42  
ver<-,SBML-method (SBML-class), 42  
warning, 45  
warns (SBMLProblems-class), 45  
warns,SBMLProblems-method  
(SBMLProblems-class), 45  
width (Dimensions-class), 15  
width,Dimensions-method  
(Dimensions-class), 15  
width<- (Dimensions-class), 15  
width<-,Dimensions-method  
(Dimensions-class), 15  
x (Point-class), 34  
x,Point-method (Point-class), 34  
x<- (Point-class), 34  
x<-,Point-method (Point-class), 34  
y (Point-class), 34  
y,Point-method (Point-class), 34  
y<- (Point-class), 34  
y<-,Point-method (Point-class), 34  
z (Point-class), 34  
z,Point-method (Point-class), 34  
z<- (Point-class), 34  
z<-,Point-method (Point-class), 34