

Package ‘ssviz’

January 20, 2026

Type Package

Title A small RNA-seq visualizer and analysis toolkit

Version 1.44.0

Date 2021-11-21

Author Diana Low

Maintainer Diana Low <lowdiana@gmail.com>

Description Small RNA sequencing viewer

License GPL-2

Depends R (>=

2.15.1),methods,Rsamtools,Biostrings,reshape,ggplot2,RColorBrewer,stats

biocViews ImmunoOncology,

Sequencing,RNASeq,Visualization,MultipleComparison,Genetics

Collate AllClasses.R AllGenerics.R helper.R

VignetteBuilder knitr

Suggests knitr

RoxygenNote 6.0.1

git_url <https://git.bioconductor.org/packages/ssviz>

git_branch RELEASE_3_22

git_last_commit e7f05f5

git_last_commit_date 2025-10-29

Repository Bioconductor 3.22

Date/Publication 2026-01-19

Contents

ssviz-package	2
counts	3
ctrlbam	3
getCountMatrix	3
getCountMatrix-methods	4
logicalORmissing-class	4
ntfreq	5
ntfreq-methods	5

pctrlbam	6
pingpong	6
pingpong-methods	7
plotDistro	7
plotDistro-methods	8
plotFreq	8
plotFreq-methods	9
plotPP	9
plotPP-methods	10
plotRegion	10
plotRegion-methods	11
ptreatbam	11
readBam	11
readBam-methods	12
treatbam	12
Index	13

ssviz-package	<i>ssviz</i>
---------------	--------------

Description

A package for short RNA seq visualization and quantification.

Details

Package: ssviz
 Type: Package
 Version: 0.99
 Date: 2014-05-08
 License: GPL-2

Author(s)

Diana H.P. Low Maintainer: Diana Low <dlow@imcb.a-star.edu.sg>

counts	<i>counts data</i>
--------	--------------------

Description

counts is an example total read count for bam reads

Usage

data(ssviz)

Source

internal

ctrlbam	<i>ctrlbam data</i>
---------	---------------------

Description

ctrlbam is an example control dataset from bam file read in with [readBam](#)

Usage

data(ssviz)

Source

internal

getCountMatrix	<i>getCountMatrix</i>
----------------	-----------------------

Description

returns the bam data.frame with an additional column counts. Only relevant if the fasta file used for mapping input was previously collapsed via fastx_toolkit to return a fasta read name in the format of readnumber-totalcounts

Usage

getCountMatrix(bam_file,pseudo=FALSE)

Arguments

- | | |
|----------|---|
| bam_file | An object of class DataFrame (from IRanges). Can be generated from readBam. |
| pseudo | Logical. If TRUE, assume the reads in the bam file does not have a count record and sets all counts to 1. |

Value

An object of class data.frame having the values from the original bam file with an additional 'count' column.

Author(s)

Diana H.P. Low

See Also

[readBam](#)

Examples

```
data(ssviz)
getCountMatrix(ctrlbam)
```

getCountMatrix-methods

getCountMatrix

Description

returns the bam data.frame with an additional column counts. Only relevant if the fasta file used for mapping input was previously collapsed via fastx_toolkit to return a fasta read name in the format of readnumber-totalcounts

Methods

signature(object="DataFrame") Returns an object of class data.frame having the values from the original bam file with an additional 'count' column.

logicalORmissing-class

Class "logicalORmissing"

Description

Class union of logical and missing object.

Author(s)

Diana H.P. Low

Examples

```
showClass("logicalORmissing")
```

ntfreq

*ntfreq***Description**

Calculates nucleotide frequency of reads in bam file

Usage

```
ntfreq(bam_file, ntlength, toRNA = TRUE, count_type = "total")
```

Arguments

<code>bam_file</code>	An object of class <code>data.frame</code> or <code>DataFrame</code>
<code>ntlength</code>	An integer specifying the length of the sequence to quantify
<code>toRNA</code>	A logical value on whether to translate the DNA sequence to RNA
<code>count_type</code>	A character string on how to count the nucleotides. Can be either "total" or "unique". If total is selected, the function will look for the <code>count</code> column and multiply the reads by its number of occurrence when calculating the frequency.

Value

Returns a `data.frame` of the frequency of nucleotides (either A/C/G/T or A/C/G/U) at each position up to the specified `ntlength`

Author(s)

Diana H.P. Low

Examples

```
data(ssviz)
freq<-ntfreq(pctrlbam,ntlength=10)
```

ntfreq-methods

*ntfreq***Description**

Calculates nucleotide frequency of reads in bam file

Methods

`ntfreq(bam_file, ntlength, toRNA = TRUE, count_type = "total")` Returns a data frame of nucleotide frequencies along length of sequence provided.

Author(s)

Diana H.P. Low

pctrlbam

pctrlbam data

Description

pctrlbam is an example control dataset from bam file read in with [readBam](#)

Usage

```
data(ssviz)
```

Source

internal

pingpong

pingpong

Description

piRNA ping-pong analysis of complementary sequences

Usage

```
pingpong(bam_file)
```

Arguments

bam_file An object of class data.frame or DataFrame

Details

The ping-pong mechanism is a proposed method for the amplification of primary piRNAs, which leads to the production of new primary piRNAs from their precursor transcripts, which eventually amplifies the pool of both primary and secondary piRNAs. This positive feedback loop is a secondary biogenesis mechanism that requires complementary transcripts to a pre-existing pool of piRNAs.

Value

This function returns a data.frame object with frequency of overlapping complementary piRNAs.

Author(s)

Diana H.P. Low

References

Brennecke J. et al. Cell 128, 1089-1103, March 23, 2007

Examples

```
data(ssviz)
pp<-pingpong(pctrlbam)
```

pingpong-methods	<i>pingpong</i>
------------------	-----------------

Description

piRNA ping-pong analysis of complementary sequences

Methods

pingpong(bam_file) Returns a data.frame object with frequency of overlapping complementary piRNAs.

Author(s)

Diana H.P. Low

plotDistro	<i>plotDistro</i>
------------	-------------------

Description

Plots distribution of reads in the bam file based on length, direction (strand) or location (rname)

Usage

```
plotDistro(bamlist, type = "qwidth", samplenames = NULL, unique = FALSE, ncounts = NULL, norm = FALSE)
```

Arguments

bamlist	An object of type list, giving a list of bam files. If you only have 1 file, use list(bam_file)
type	An object of type character. Can be qwidth, rname or strand. In theory, any column property existing in the bam file can be used, but these 3 would be most meaningful.
samplenames	Labels for the plot.
unique	Logical value to use unique reads (TRUE) or all reads (FALSE)
ncounts	Number of total counts in the bam file, used if unique is set to FALSE.
norm	Logical value to determine if plot will be normalised.
yname	y axis label.

Author(s)

Diana H.P. Low

Examples

```
data(ssviz)
plotDistro(list(ctrlbam))
```

plotDistro-methods	<i>plotDistro</i>
--------------------	-------------------

Description

Plots distribution of reads in the bam file based on length, direction (strand) or location (rname)

Methods

```
plotDistro(bamlist, type = "qwidth", samplenames = NULL, unique = FALSE, ncounts = 1e+06, norm = FALSE,
Returns a distribution plot.
```

Author(s)

Diana H.P. Low

plotFreq	<i>plotFreq</i>
----------	-----------------

Description

Plots nucleotide frequency generated by [ntfreq](#)

Usage

```
plotFreq(freqvector, percentage = TRUE)
```

Arguments

- freqvector data.frame object generated by [ntfreq](#)
- percentage Logical value to represent y-axis as percentage or frequency.

Author(s)

Diana H.P. Low

See Also

[ntfreq](#)

Examples

```
data(ssviz)
freq<-ntfreq(pctrlbam,ntlength=10)
plotFreq(freq)
```

plotFreq-methods	<i>plotFreq</i>
------------------	-----------------

Description

Plots nucleotide frequency generated by [ntfreq](#)

Methods

plotFreq(freqvector, percentage = TRUE) Returns a frequency bar plot.

Author(s)

Diana H.P. Low

plotPP	<i>plotPP</i>
--------	---------------

Description

Plots the ping-pong frequency of piRNA amplification

Usage

```
plotPP(pout, samplenames = NULL)
```

Arguments

pout	An object of type data.frame generated by pingpong
samplenames	An object of type character for sample labels.

Author(s)

Diana H.P. Low

References

Brennecke J. et al. Cell 128, 1089-1103, March 23, 2007

See Also

[pingpong](#)

Examples

```
data(ssviz)
pp<-pingpong(pctrlbam)
plotPP(list(pp))
```

plotPP-methods	<i>plotPP</i>
----------------	---------------

Description

Plots the ping-pong frequency of piRNA amplification

Methods

plotPP(pout, samplenames = NULL) Returns the pingpong amplification plot.

Author(s)

Diana H.P. Low

plotRegion	<i>plotRegion</i>
------------	-------------------

Description

Plots the read density given a chromosome region.

Usage

```
plotRegion(bamlist, region, howsmooth = 2, ncounts = NULL, samplenames = NULL)
```

Arguments

bamlist	An object of type list, giving a list of bam files. If you only have 1 file, use list(bam_file)
region	An object of type character defining the region to plot. Eg. chr1:1000-2000
howsmooth	Numeric value controlling smoothness of the plot.
ncounts	Total number of reads for plot normalization.
samplenames	Sample names

Value

Returns the x and y components of the region's reads and plots the density.

Author(s)

Diana H.P. Low

Examples

```
data(ssviz)
region<-'chr1:3015526-3080526'
plotRegion(list(ctrlbam), region=region)
```

plotRegion-methods	<i>plotRegion</i>
--------------------	-------------------

Description

Plots the read density given a chromosome region.

Methods

`plotRegion(bamlist, region, howsmooth = 2, ncounts = NULL, samplenames = NULL)` Returns the x and y components of the region's reads and plots the density.

Author(s)

Diana H.P. Low

ptreatbam	<i>ptreatbam data</i>
-----------	-----------------------

Description

ptreatbam is an example treatment dataset from bam file read in with [readBam](#)

Usage

`data(ssviz)`

Source

internal

readBam	<i>readBam</i>
---------	----------------

Description

Reads a bam file through RSamtools, and converts it into a data frame of class `DataFrame`

Usage

`readBam(file_name, tags = character(0))`

Arguments

<code>file_name</code>	Character string of bam file location
<code>tags</code>	Bam tags to import into the data frame. By default it only takes the standard values if none are given.

Details

This function formalizes what had been described in the RSamtools documentation and makes it easier to compute the downstream functions in this package.

Value

Returns the bam file contents in a readable dataframe format.

Author(s)

Diana H.P. Low

References

RSamtools package

Examples

```
bam.files <- dir(system.file("extdata", package = "ssviz"), full = TRUE, patt = "bam$")
ctrlbam <- readBam(bam.files[1])
```

readBam-methods	<i>readBam</i>
-----------------	----------------

Description

Reads a bam file through RSamtools, and converts it into a data frame of class DataFrame

Methods

`readBam(bam_file, tags = character(0))` Returns the bam file contents in a readable dataframe format.

Author(s)

Diana H.P. Low

treatbam	<i>treatbam data</i>
----------	----------------------

Description

treatbam is an example treatment dataset from bam file read in with [readBam](#)

Usage

```
data(ssviz)
```

Source

internal

Index

- * **classes**
 - logicalORmissing-class, 4
- * **datasets**
 - counts, 3
 - ctrlbam, 3
 - pctrlbam, 6
 - ptreatbam, 11
 - treatbam, 12
- * **methods**
 - ntfreq-methods, 5
 - pingpong-methods, 7
 - plotDistro-methods, 8
 - plotFreq-methods, 9
 - plotPP-methods, 10
 - plotRegion-methods, 11
 - readBam-methods, 12
- * **package**
 - ssviz-package, 2

counts, 3

ctrlbam, 3

getCountMatrix, 3

getCountMatrix, DataFrame-method
(getCountMatrix-methods), 4

getCountMatrix-methods, 4

logicalORmissing-class, 4

ntfreq, 5, 8, 9

ntfreq, DataFrame, numeric-method
(ntfreq-methods), 5

ntfreq-methods, 5

pctrlbam, 6

pingpong, 6, 9

pingpong, DataFrame-method
(pingpong-methods), 7

pingpong-methods, 7

plotDistro, 7

plotDistro, list-method
(plotDistro-methods), 8

plotDistro-methods, 8

plotFreq, 8

plotFreq, data.frame, logicalORmissing-method
(plotFreq-methods), 9

plotFreq-methods, 9

plotPP, 9

plotPP, list-method (plotPP-methods), 10

plotPP-methods, 10

plotRegion, 10

plotRegion, list, character-method
(plotRegion-methods), 11

plotRegion-methods, 11

ptreatbam, 11

readBam, 3, 4, 6, 11, 11, 12

readBam, character-method
(readBam-methods), 12

readBam-methods, 12

ssviz (ssviz-package), 2

ssviz-package, 2

treatbam, 12