

Package ‘MBAmethyl’

January 24, 2026

Type Package

Title Model-based analysis of DNA methylation data

Version 1.45.0

Date 2014-10-03

Author Tao Wang, Mengjie Chen

Maintainer Tao Wang <tao.wang.tw376@yale.edu>

Description This package provides a function for reconstructing DNA methylation values from raw measurements. It iteratively implements the group fused lars to smooth related-by-location methylation values and the constrained least squares to remove probe affinity effect across multiple sequences.

Depends R (>= 2.15)

License Artistic-2.0

biocViews DNAMethylation, MethylationArray

git_url <https://git.bioconductor.org/packages/MBAmethyl>

git_branch devel

git_last_commit a70414d

git_last_commit_date 2025-10-29

Repository Bioconductor 3.23

Date/Publication 2026-01-23

Contents

MBAmethyl-package	2
MBAmethyl	3
Index	5

Description

This package provides functions for reconstructing DNA methylation values from raw measurements. It utilizes both the information from biological replicates and neighboring probes by explicitly modeling the probe-specific effect and encouraging the neighboring similarity by a group fused lasso penalty.

Details

Package: MBAmethyl
 Type: Package
 Version: 0.99.0
 Date: 2014-08-24
 License: Artistic-2.0

Author(s)

Tao Wang, Mengjie Chen

Maintainer: Tao Wang <tao.wang.tw376@yale.edu>

References

~~ Literature or other references for background information ~~

Examples

```
p <- 80
n <- 40
K <- 2
k <- K - 1
cp <- numeric()
L <- c(0, floor(p / K) * (1 : k), p)
cp <- floor(p / K) * (1 : k) + 1

## phi0: probe effects; theta0: true methylation values; part: partition of probe indices
phi0 <- runif(p, 0.5, 2.0)
theta0 <- matrix(0, p, n)
part <- list()

for (s in 1 : K) {
  part[[s]] <- (L[s] + 1) : L[s + 1]
```

```

    phi0[part[[s]]] <- phi0[part[[s]]] / sqrt(mean(phi0[part[[s]]]^2))
  }

  theta0[part[[1]], ] <- rep(1, length(part[[1]]))
  theta0[part[[2]], ] <- rep(1, length(part[[2]]))

  error <- matrix(runif(p * n, 0, 0.1), p, n)
  Y <- theta0 * phi0 + error
  fit <- MBAmethyl(Y, steps = 10)

```

MBAmethyl

*Model-based analysis of DNA methylation data***Description**

This function reconstructs DNA methylation values from raw measurements. It iteratively implements the group fused lars to smooth related-by-location methylation values and the constrained least squares to remove probe affinity effect across multiple sequences. It also contains a criterion-based method (AIC or BIC) for selecting the tuning parameter.

Usage

```
MBAmethyl(Y, wts = .defaultWeights(nrow(Y)), steps = min(dim(Y)) - 1)
```

Arguments

<code>Y</code>	An observed matrix ($p \times n$) of methylation values (beta values); p is the number of probes and n is the number of samples;
<code>wts</code>	A pre-specified vector of weights. By default, we use the probe index-dependent weight scheme, $\text{wts}_i = \sqrt{p / i / (p - i)}$ for $i = 1, \dots, p$;
<code>steps</code>	Limit the number of steps taken. One can use this option to perform early stopping.

Value

<code>ans.aic</code>	A list corresponds to the AIC, containing estimated beta values, estimated probed effects, estimated change-point locations, residual sum of squares, and degree of freedom.
<code>ans.bic</code>	A list corresponds to the BIC, containing estimated beta values, estimated probed effects, estimated change-point locations, residual sum of squares, and degree of freedom.

Author(s)

Tao Wang, Mengjie Chen

References

paper under review

Examples

```
p <- 80
n <- 40
K <- 2
k <- K - 1
cp <- numeric()
L <- c(0, floor(p / K) * (1 : k), p)
cp <- floor(p / K) * (1 : k) + 1

## phi0: probe effects; theta0: true methylation values; part: partition of probe indices
phi0 <- runif(p, 0.5, 2.0)
theta0 <- matrix(0, p, n)
part <- list()

for (s in 1 : K) {
  part[[s]] <- (L[s] + 1) : L[s + 1]
  phi0[part[[s]]] <- phi0[part[[s]]] / sqrt(mean(phi0[part[[s]]]^2))
}

theta0[part[[1]], ] <- rep(1, length(part[[1]]))
theta0[part[[2]], ] <- rep(1, length(part[[2]]))

error <- matrix(runif(p * n, 0, 0.1), p, n)
Y <- theta0 * phi0 + error
fit <- MBAmethyl(Y, steps = 10)
```

Index

- * **methylation**

- MBAmethyl, [3](#)

- * **package**

- MBAmethyl-package, [2](#)

MBAmethyl, [3](#)

MBAmethyl-package, [2](#)