

Package ‘enrichplot’

January 23, 2026

Title Visualization of Functional Enrichment Result

Version 1.31.4

Description The 'enrichplot' package implements several visualization methods for interpreting functional enrichment results obtained from ORA or GSEA analysis.

It is mainly designed to work with the 'clusterProfiler' package suite. All the visualization methods are developed based on 'ggplot2' graphics.

Depends R (>= 4.2.0)

Imports aplot (>= 0.2.1), DOSE, dplyr, enrichit, ggfun (>= 0.1.7), ggnewscale, ggplot2 (>= 3.5.0), ggrepel (>= 0.9.0), ggtangle (>= 0.0.9), ggtree, GOSemSim (>= 2.37.2), graphics, grid, igraph, methods, purrr, RColorBrewer, reshape2, rlang, scatterpie, stats, tidydr, utils, yulab.utils (>= 0.2.2)

Suggests AnnotationDbi, clusterProfiler, europepmc, ggarchery, ggforce, ggHoriPlot, ggplotify, gggridges, ggstar, ggtreeExtra, ggupset, glue, grDevices, gridExtra, gson, org.Hs.eg.db, quarto, scales, tibble, tidyr

VignetteBuilder quarto

License Artistic-2.0

URL <https://yulab-smu.top/contribution-knowledge-mining/>

BugReports <https://github.com/GuangchuangYu/enrichplot/issues>

biocViews Annotation, GeneSetEnrichment, GO, KEGG, Pathways, Software, Visualization

Encoding UTF-8

RoxygenNote 7.3.3

git_url <https://git.bioconductor.org/packages/enrichplot>

git_branch devel

git_last_commit 8bb8e48

git_last_commit_date 2026-01-18

Repository Bioconductor 3.23

Date/Publication 2026-01-23

Author Guangchuang Yu [aut, cre] (ORCID:
<https://orcid.org/0000-0002-6485-8781>),
 Chun-Hui Gao [ctb] (ORCID: <https://orcid.org/0000-0002-1445-7939>)
Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Contents

enrichplot-package	3
as.data.frame.compareClusterResult	3
autofacet	4
barplot.enrichResult	4
cnetplot.enrichResult	5
color_palette	8
dotplot	8
dotplot2	12
emapplot	13
enrichplot_point_shape	15
fortify.compareClusterResult	16
geom_gsea_gene	17
get_enrichplot_color	18
ggtable	18
goplot	19
gseadist	20
gseaplot	21
gseaplot2	22
gsearank	23
gsInfo	24
heatplot	24
hplot	26
pairwise_termsim	26
plotting.clusterProfile	28
pmcplot	29
reexports	29
ridgeplot	30
set_enrichplot_color	31
ssplot	32
treeplot	34
upsetplot	37
volplot	38

Index	40
--------------	-----------

enrichplot-package	<i>enrichplot: Visualization of Functional Enrichment Result</i>
--------------------	--

Description

The 'enrichplot' package implements several visualization methods for interpreting functional enrichment results obtained from ORA or GSEA analysis. It is mainly designed to work with the 'clusterProfiler' package suite. All the visualization methods are developed based on 'ggplot2' graphics.

Author(s)

Maintainer: Guangchuang Yu <guangchuangyu@gmail.com> ([ORCID](#))

Other contributors:

- Chun-Hui Gao <gaospecial@gmail.com> ([ORCID](#)) [contributor]

See Also

Useful links:

- <https://yulab-smu.top/contribution-knowledge-mining/>
- Report bugs at <https://github.com/GuangchuangYu/enrichplot/issues>

as.data.frame.compareClusterResult	<i>Convert compareClusterResult to data frame</i>
------------------------------------	---

Description

Convert compareClusterResult to data frame

Usage

```
## S3 method for class 'compareClusterResult'  
as.data.frame(x, ...)
```

Arguments

x	compareClusterResult object
...	additional parameters

Value

data frame

autofacet

Plotting utility functions for enrichplot package

Description

This file contains plotting and visualization helper functions for enrichplot. Automatically split barplot or dotplot into several facets.

Usage

```
autofacet(by = "row", scales = "free", levels = NULL)
```

Arguments

by	one of 'row' or 'column'
scales	whether 'fixed' or 'free'
levels	set facet levels

Value

a ggplot object

barplot.enrichResult *barplot*

Description

Barplot of enrichResult

Usage

```
## S3 method for class 'enrichResult'
barplot(
  height,
  x = "Count",
  color = "p.adjust",
  showCategory = 8,
  font.size = 12,
  title = "",
  label_format = 30,
  ...
)
```

Arguments

height	enrichResult object
x	one of 'Count' and 'GeneRatio'
color	one of 'pvalue', 'p.adjust' and 'qvalue'
showCategory	number of categories to display or a vector of terms.
font.size	font size
title	plot title
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels. by default wraps names longer than 30 characters
...	additional parameters

Details

Barplot of enrichResult

Value

ggplot object

Examples

```
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
barplot(x)
# use `showCategory` to select the displayed terms. It can be a number of a vector of terms.
barplot(x, showCategory = 10)
categories <- c("urinary bladder cancer", "bronchiolitis obliterans",
               "aortic aneurysm", "esophageal cancer")
barplot(x, showCategory = categories)
```

cnetplot.enrichResult *Category-Gene-Network Plot*

Description

Category-gene-network plot

Usage

```
## S3 method for class 'enrichResult'
cnetplot(
  x,
  layout = igraph::layout_with_kk,
  showCategory = 5,
  color_category = "#E5C494",
  size_category = 1,
  color_item = "#B3B3B3",
  size_item = 1,
  color_edge = "grey",
  size_edge = 0.5,
  categorySizeBy = ~itemNum,
  node_label = "all",
  foldChange = NULL,
  fc_threshold = NULL,
  highlight = "none",
  highlight_alpha = 0.3,
  ...
)

## S3 method for class 'gseaResult'
cnetplot(
  x,
  layout = igraph::layout_with_kk,
  showCategory = 5,
  color_category = "#E5C494",
  size_category = 1,
  color_item = "#B3B3B3",
  size_item = 1,
  color_edge = "grey",
  size_edge = 0.5,
  categorySizeBy = ~itemNum,
  node_label = "all",
  foldChange = NULL,
  fc_threshold = NULL,
  highlight = "none",
  highlight_alpha = 0.3,
  ...
)

## S3 method for class 'compareClusterResult'
cnetplot(
  x,
  layout = igraph::layout_with_kk,
  showCategory = 5,
  color_category = "#E5C494",
  size_category = 1,
```

```

    color_item = "#B3B3B3",
    size_item = 1,
    color_edge = "grey",
    size_edge = 0.5,
    categorySizeBy = NULL,
    node_label = "all",
    foldChange = NULL,
    fc_threshold = NULL,
    highlight = "none",
    highlight_alpha = 0.3,
    pie = "equal",
    ...
)

```

Arguments

x	input object
layout	network layout
showCategory	number of categories to display or a vector of terms.
color_category	color of category nodes
size_category	relative size of the category nodes
color_item	color of item nodes
size_item	relative size of the item nodes (e.g., genes)
color_edge	color of edge
size_edge	relative size of edge
categorySizeBy	method of category size, one of "itemNum" (default), "pvalue", "p.adjust", "qvalue" or a numeric vector
node_label	one of 'all', 'none', 'category', 'item', 'exclusive' or 'share'. 'exclusive' labels genes that uniquely belong to categories; 'share' labels genes that are shared between categories.
foldChange	numeric values to color the item (e.g., fold change of gene expression values)
fc_threshold	threshold for filtering genes by absolute fold change (e.g., fc_threshold = 1 keeps only genes with foldChange > 1).
highlight	selected categories to be highlighted
highlight_alpha	transparency value for non-highlighted items
...	additional parameters
pie	one of 'equal' or 'Count' to set the slice ratio of the pies

See Also

[cnetplot][ggtangle::cnetplot]

color_palette	Create color palette for continuous data
---------------	--

Description

Create color palette for continuous data

Usage

```
color_palette(colors)
```

Arguments

colors colors of length ≥ 2

Value

color vector

Author(s)

guangchuang yu

Examples

```
color_palette(c("red", "yellow", "green"))
```

dotplot	<i>dotplot</i>
---------	----------------

Description

Dot plot for enrichment result

Usage

```
dotplot(object, ...)
```

```
## S4 method for signature 'enrichResult'
```

```
dotplot(  
  object,  
  x = "GeneRatio",  
  color = "p.adjust",  
  showCategory = 10,  
  size = NULL,  
  split = NULL,
```

```
    font.size = 12,
    title = "",
    orderBy = "x",
    label_format = 30,
    ...
)

## S4 method for signature 'gseaResult'
dotplot(
  object,
  x = "GeneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  ...
)

## S4 method for signature 'compareClusterResult'
dotplot(
  object,
  x = "Cluster",
  color = "p.adjust",
  showCategory = 5,
  split = NULL,
  font.size = 12,
  title = "",
  by = "geneRatio",
  size = NULL,
  includeAll = TRUE,
  label_format = 30,
  ...
)

## S4 method for signature 'enrichResultList'
dotplot(
  object,
  x = "GeneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
```

```
    orderBy = "x",
    label_format = 30,
    ...
)

## S4 method for signature 'gseaResultList'
dotplot(
  object,
  x = "GeneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  ...
)

dotplot.enrichResult(
  object,
  x = "geneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  decreasing = TRUE
)

dotplot.compareClusterResult(
  object,
  x = "Cluster",
  colorBy = "p.adjust",
  showCategory = 5,
  by = "geneRatio",
  size = "geneRatio",
  split = NULL,
  includeAll = TRUE,
  font.size = 12,
  title = "",
  label_format = 30,
  group = FALSE,
  shape = FALSE,
```

```

    facet = NULL,
    strip_width = 15
  )

```

Arguments

<code>object</code>	compareClusterResult object
<code>...</code>	additional parameters.
<code>x</code>	variable for x-axis, one of 'GeneRatio' and 'Count'
<code>color</code>	variable used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'
<code>showCategory</code>	number of categories to display or a vector of terms.
<code>size</code>	variable used to scale the sizes of categories, one of "geneRatio", "Percentage" and "count"
<code>split</code>	apply 'showCategory' to each category specified by the 'split', e.g., "ONTOLOGY", "category" and "intersect". Default is NULL and do nothing
<code>font.size</code>	font size
<code>title</code>	figure title
<code>orderBy</code>	The order of the Y-axis
<code>label_format</code>	a numeric value sets wrap length, alternatively a custom function to format axis labels. by default wraps names longer than 30 characters
<code>by</code>	one of "geneRatio", "Percentage" and "count"
<code>includeAll</code>	logical value
<code>decreasing</code>	logical. Should the orderBy order be increasing or decreasing?
<code>colorBy</code>	variable used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'
<code>group</code>	a logical value, whether to connect the nodes of the same group with wires.
<code>shape</code>	a logical value, whether to use nodes of different shapes to distinguish the group it belongs to
<code>facet</code>	apply 'facet_grid' to the plot by specified variable, e.g., "ONTOLOGY", "category" and "intersect".
<code>strip_width</code>	width of strip text (facet label).

Value

plot.

Author(s)

Guangchuang Yu

Examples

```
## Not run:
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
dotplot(x)
# use `showCategory` to select the displayed terms. It can be a number or a vector of terms.
dotplot(x, showCategory = 10)
categories <- c("pre-malignant neoplasm", "intestinal disease",
               "breast ductal carcinoma", "non-small cell lung carcinoma")
dotplot(x, showCategory = categories)
# It can also graph compareClusterResult
data(gcSample)
library(clusterProfiler)
library(DOSE)
library(org.Hs.eg.db)
data(gcSample)
xx <- compareCluster(gcSample, fun="enrichGO", OrgDb="org.Hs.eg.db")
xx2 <- pairwise_termsim(xx)
library(ggstar)
dotplot(xx2)
dotplot(xx2, shape = TRUE)
dotplot(xx2, group = TRUE)
dotplot(xx2, x = "GeneRatio", group = TRUE, size = "count")

## End(Not run)
```

dotplot2

dotplot2

Description

compare two clusters in the compareClusterResult object

Usage

```
dotplot2(object, x = "FoldEnrichment", vars = NULL, label = "auto", ...)
```

Arguments

object	a compareClusterResult object
x	selected variable to visualize in x-axis
vars	selected Clusters to be compared, only length of two is supported
label	to label the Clusters in the plot, should be a named vector
...	additional parameters passed to dotplot

Value

a ggplot object

Author(s)

Guangchuang Yu

emapplot	<i>emapplot</i>
----------	-----------------

Description

Enrichment Map for enrichment result of over-representation test or gene set enrichment analysis

Usage

```
emapplot(x, ...)  
  
## S4 method for signature 'enrichResult'  
emapplot(x, showCategory = 30, ...)  
  
## S4 method for signature 'gseaResult'  
emapplot(x, showCategory = 30, ...)  
  
## S4 method for signature 'compareClusterResult'  
emapplot(x, showCategory = 30, ...)  
  
emapplot_internal(  
  x,  
  layout = igraph::layout_with_kk,  
  showCategory = 30,  
  color = "p.adjust",  
  size_category = 1,  
  min_edge = 0.2,  
  color_edge = "grey",  
  size_edge = 0.5,  
  node_label = "category",  
  node_label_size = 5,  
  pie = "equal",  
  label_format = 30,  
  clusterFunction = stats::kmeans,  
  nWords = 4,  
  nCluster = NULL  
)
```

Arguments

<code>x</code>	Enrichment result.
<code>...</code>	Additional parameters
<code>showCategory</code>	number of categories to display or a vector of terms.
<code>layout</code>	igraph layout
<code>color</code>	Variable used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'.
<code>size_category</code>	relative size of the categories
<code>min_edge</code>	The minimum similarity threshold for whether two nodes are connected, should be between 0 and 1, default value is 0.2.
<code>color_edge</code>	color of the network edge
<code>size_edge</code>	relative size of edge width
<code>node_label</code>	Select which labels to display, one of 'category', 'group', 'all' and 'none'.
<code>node_label_size</code>	size of node label, default is 5.
<code>pie</code>	one of 'equal' or 'Count' to set the slice ratio of the pies
<code>label_format</code>	a numeric value sets wrap length, alternatively a custom function to format axis labels.
<code>clusterFunction</code>	function of Clustering method, such as 'stats::kmeans' (the default), 'cluster::clara', 'cluster::fanny' or 'cluster::pam'.
<code>nWords</code>	Numeric, the number of words in the cluster tags, the default value is 4.
<code>nCluster</code>	Numeric, the number of clusters, the default value is square root of the number of nodes.

Details

This function visualizes gene sets as a network (i.e. enrichment map). Mutually overlapping gene sets tend to cluster together, making it easier for interpretation. When the similarity between terms meets a certain threshold (default is 0.2, adjusted by parameter 'min_edge'), there will be edges between terms. The stronger the similarity, the shorter and thicker the edges. The similarity between terms is obtained by the function 'pairwise_termsim'. Details of the similarity calculation can be found in its documentation: [pairwise_termsim](#).

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
## Not run:
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
x2 <- pairwise_termsim(x)
emapplot(x2)
# use `layout` to change the layout of map
emapplot(x2, layout = "star")
# use `showCategory` to select the displayed terms. It can be a number or a vector of terms.
emapplot(x2, showCategory = 10)
categories <- c("pre-malignant neoplasm", "intestinal disease",
               "breast ductal carcinoma")
emapplot(x2, showCategory = categories)

# It can also graph compareClusterResult
library(clusterProfiler)
library(DOSE)
library(org.Hs.eg.db)
data(gcSample)
xx <- compareCluster(gcSample, fun="enrichGO", OrgDb="org.Hs.eg.db")
xx2 <- pairwise_termsim(xx)
emapplot(xx2)

## End(Not run)
```

enrichplot_point_shape

Predefined color palettes

Description

Predefined color palettes

Usage

enrichplot_point_shape

Format

An object of class `numeric` of length 1.

fortify.compareClusterResult
fortify

Description

convert compareClusterResult to a data.frame that ready for plot
convert enrichResult object for ggplot2

Usage

```
## S3 method for class 'compareClusterResult'
fortify(
  model,
  data,
  showCategory = 5,
  by = "geneRatio",
  split = NULL,
  includeAll = TRUE,
  ...
)

## S3 method for class 'enrichResult'
fortify(
  model,
  data,
  showCategory = 5,
  by = "Count",
  order = FALSE,
  drop = FALSE,
  split = NULL,
  ...
)
```

Arguments

model	'enrichResult' or 'compareClusterResult' object
data	not use here
showCategory	Category numbers to show
by	one of Count and GeneRatio
split	separate result by 'split' variable
includeAll	logical
...	additional parameter
order	logical
drop	logical

Value

data.frame
data.frame

Author(s)

Guangchuang Yu

geom_gsea_gene	<i>geom_gsea_gene</i>
----------------	-----------------------

Description

label genes in running score plot

Usage

```
geom_gsea_gene(  
  genes,  
  mapping = NULL,  
  geom = ggplot2::geom_text,  
  ...,  
  geneSet = NULL  
)
```

Arguments

- genes selected genes to be labeled
- mapping aesthetic mapping, default is NULL
- geom geometric layer to plot the gene labels, default is geom_text
- ... additional parameters passed to the 'geom'
- geneSet choose which gene set(s) to be label if the plot contains multiple gene sets

Value

ggplot object

Author(s)

Guangchuang Yu

get_enrichplot_color	<i>Color utility functions for enrichplot package</i>
----------------------	---

Description

This file contains all color-related helper functions Get default enrichplot colors

Usage

```
get_enrichplot_color(n = 2)
```

Arguments

n number of colors (2 or 3)

Value

color vector

ggtable	<i>ggtable</i>
---------	----------------

Description

plot table

Usage

```
ggtable(d, p = NULL)
```

Arguments

d data frame
p ggplot object to extract color to color rownames(d), optional

Value

ggplot object

Author(s)

guangchuang yu

*goplot**goplot*

Description

Plot induced GO DAG of significant terms

Usage

```
goplot(  
  x,  
  showCategory = 10,  
  color = "p.adjust",  
  layout = "sugiyama",  
  geom = "text",  
  ...  
)  
  
## S4 method for signature 'enrichResult'  
goplot(  
  x,  
  showCategory = 10,  
  color = "p.adjust",  
  layout = igraph::layout_with_sugiyama,  
  geom = "text",  
  ...  
)  
  
## S4 method for signature 'gseaResult'  
goplot(  
  x,  
  showCategory = 10,  
  color = "p.adjust",  
  layout = igraph::layout_with_sugiyama,  
  geom = "text",  
  ...  
)
```

Arguments

x	enrichment result.
showCategory	number of enriched terms to display
color	variable used to color enriched terms, e.g. pvalue, p.adjust or qvalue
layout	layout of the map
geom	label geom, one of 'label' or 'text'
...	additional parameters.

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
## Not run:
library(clusterProfiler)
data(geneList, package = "DOSE")
de <- names(geneList)[1:100]
yy <- enrichGO(de, 'org.Hs.eg.db', ont="BP", pvalueCutoff=0.01)
goplot(yy)
goplot(yy, showCategory = 5)

## End(Not run)
```

<i>gseadist</i>	<i>gseadist</i>
-----------------	-----------------

Description

plot logFC distribution of selected gene sets

Usage

```
gseadist(x, IDs, type = "density")
```

Arguments

x	GSEA result
IDs	gene set IDs
type	one of 'density' or 'boxplot'

Value

distribution plot

Author(s)

Guangchuang Yu

*gseaplot**gseaplot*

Description

Visualize GSEA analysis results

Usage

```
gseaplot(x, geneSetID, by = "all", title = "", ...)
```

```
## S4 method for signature 'gseaResult'
```

```
gseaplot(  
  x,  
  geneSetID,  
  by = "all",  
  title = "",  
  color = "black",  
  color.line = "green",  
  color.vline = "#FA5860",  
  ...  
)
```

```
gseaplot.gseaResult(  
  x,  
  geneSetID,  
  by = "all",  
  title = "",  
  color = "black",  
  color.line = "green",  
  color.vline = "#FA5860",  
  ...  
)
```

Arguments

x	gseaResult object
geneSetID	geneSet ID
by	one of "runningScore" or "position"
title	plot title
...	additional parameters
color	color of line segments
color.line	color of running enrichment score line
color.vline	color of vertical line indicating the maximum/minimal running enrichment score

Details

Plotting function for gseaResult

Value

ggplot2 object

ggplot2 object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
x <- gseD0(geneList)
gseaplot(x, geneSetID=1)
```

`gseaplot2`

gseaplot2

Description

GSEA plot that mimic the plot generated by broad institute's GSEA software

Usage

```
gseaplot2(
  x,
  geneSetID,
  title = "",
  color = "green",
  base_size = 11,
  rel_heights = c(1.5, 0.5, 1),
  subplots = 1:3,
  pvalue_table = FALSE,
  pvalue_table_columns = c("pvalue", "p.adjust"),
  pvalue_table_rownames = "Description",
  ES_geom = "line"
)
```

Arguments

x	gseaResult object
geneSetID	gene set ID
title	plot title
color	color of running enrichment score line
base_size	base font size
rel_heights	relative heights of subplots
subplots	which subplots to be displayed
pvalue_table	whether add pvalue table
pvalue_table_columns	selected columns to be plotted in the 'pvalue_table'
pvalue_table_rownames	selected column as the rownames of the 'pvalue_table'. If set to NULL, no rownames will be displayed.
ES_geom	geom for plotting running enrichment score, one of 'line' or 'dot'

Value

plot

Author(s)

Guangchuang Yu

gsearank

gsearank

Description

plot ranked list of genes with running enrichment score as bar height

Usage

```
gsearank(x, geneSetID, title = "", output = "plot")
```

Arguments

x	gseaResult object
geneSetID	gene set ID
title	plot title
output	one of 'plot' or 'table' (for exporting data)

Value

ggplot object

Author(s)

Guangchuang Yu

gsInfo	<i>gsInfo</i>
--------	---------------

Description

extract gsea result of selected geneSet

Usage

```
gsInfo(object, geneSetID)
```

Arguments

object	gseaResult object
geneSetID	gene set ID

Value

data.frame

Author(s)

Guangchuang Yu

heatplot	<i>heatplot</i>
----------	-----------------

Description

Heatmap-like plot for functional classification

Usage

```

heatplot(x, showCategory = 30, ...)

## S4 method for signature 'enrichResult'
heatplot(x, showCategory = 30, ...)

## S4 method for signature 'gseaResult'
heatplot(x, showCategory = 30, ...)

heatplot.enrichResult(
  x,
  showCategory = 30,
  showTop = NULL,
  symbol = "rect",
  foldChange = NULL,
  pvalue = NULL,
  label_format = 30
)

```

Arguments

x	enrichment result.
showCategory	number of enriched terms to display
...	Additional parameters
showTop	number of top genes ranked by ‘abs(foldChange) * frequency’ to be shown in the heatmap, default NULL means all genes are shown
symbol	symbol of the nodes, one of "rect" (the default) or "dot"
foldChange	fold change.
pvalue	pvalue of genes
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels. by default wraps names longer than 30 characters

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```

library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
heatplot(x)

```

hplot	<i>hplot</i>
-------	--------------

Description

Horizontal plot for GSEA result

Usage

```
hplot(x, geneSetID)
```

Arguments

x	gseaResult object
geneSetID	gene set ID

Value

horizontal plot

Author(s)

Guangchuang Yu

pairwise_termsim	<i>pairwise_termsim</i>
------------------	-------------------------

Description

Get the similarity matrix

Usage

```
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = NULL)

## S4 method for signature 'enrichResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = NULL)

## S4 method for signature 'gseaResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = NULL)

## S4 method for signature 'compareClusterResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = NULL)

pairwise_termsim.enrichResult(
```

```

    x,
    method = "JC",
    semData = NULL,
    showCategory = NULL
  )

pairwise_termsim.compareClusterResult(
  x,
  method = "JC",
  semData = NULL,
  showCategory = NULL
)

```

Arguments

<code>x</code>	enrichment result.
<code>method</code>	method of calculating the similarity between nodes, one of "Resnik", "Lin", "Rel", "Jiang", "Wang", and "JC" (Jaccard similarity coefficient) methods.
<code>semData</code>	'GOSemSimDATA' object, can be obtained through 'GOSemSim::godata'.
<code>showCategory</code>	number of enriched terms to be calculated. The default value is the number of enriched terms, or 200 if the number of enriched terms exceeds 200.

Details

This function adds a similarity matrix to the termsim slot of the enrichment result. Users can use the 'method' parameter to select the method of calculating the similarity. The Jaccard correlation coefficient (JC) is used by default, and it applies to all situations. When users want to calculate the correlation between GO terms or DO terms, they can also choose "Resnik", "Lin", "Rel" or "Jiang" (they are semantic similarity calculation methods from the 'GOSemSim' package), and at this time, the user needs to provide the 'semData' parameter, which can be obtained through [godata](#).

Examples

```

## Not run:
library(clusterProfiler)
library(org.Hs.eg.db)
library(enrichplot)
library(GOSemSim)
library(DOSE)
data(geneList)
gene <- names(geneList)[abs(geneList) > 2]
ego <- enrichGO(gene = gene,
  universe      = names(geneList),
  OrgDb         = org.Hs.eg.db,
  ont           = "BP",
  pAdjustMethod = "BH",
  pvalueCutoff  = 0.01,
  qvalueCutoff  = 0.05,
  readable      = TRUE)
d <- godata('org.Hs.eg.db', ont="BP")

```

```
ego2 <- pairwise_termsim(ego, method="Wang", semData = d)
emapplot(ego2)
emapplot_cluster(ego2)

## End(Not run)
```

plotting.clusterProfile

Internal plot function for plotting compareClusterResult

Description

Internal plot function for plotting compareClusterResult

Usage

```
plotting.clusterProfile(
  clProf.reshape.df,
  x = ~Cluster,
  type = "dot",
  colorBy = "p.adjust",
  by = "geneRatio",
  title = "",
  font.size = 12
)
```

Arguments

clProf.reshape.df	data frame of compareCluster result
x	x variable
type	one of dot and bar
colorBy	one of pvalue or p.adjust
by	one of percentage and count
title	graph title
font.size	graph font size

Value

ggplot object

Author(s)

Guangchuang Yu <https://yulab-smu.top>

`pmcplot`*pmcplot*

Description

PubMed Central Trend plot

Usage

```
pmcplot(query, period, proportion = TRUE)
```

Arguments

<code>query</code>	query terms
<code>period</code>	period of query in the unit of year
<code>proportion</code>	If TRUE, use <code>query_hits/all_hits</code> , otherwise use <code>query_hits</code> .

Value

ggplot object

Author(s)

Guangchuang Yu

`reexports`*Objects exported from other packages*

Description

These objects are imported from other packages. Follow the links below to see their documentation.

aplot [plot_list](#)

DOSE [theme_dose](#)

enrichit [geneID](#), [geneInCategory](#), [gseaScores](#)

ggplot2 [facet_grid](#), [ggtitle](#)

ggtangle [cnetplot](#), [geom_cnet_label](#)

ridgeplot

ridgeplot

Description

Ridgeline plot for GSEA result

Usage

```
ridgeplot(
  x,
  showCategory = 30,
  fill = "p.adjust",
  core_enrichment = TRUE,
  label_format = 30,
  ...
)

## S4 method for signature 'gseaResult'
ridgeplot(
  x,
  showCategory = 30,
  fill = "p.adjust",
  core_enrichment = TRUE,
  label_format = 30,
  ...
)

ridgeplot.gseaResult(
  x,
  showCategory = 30,
  fill = "p.adjust",
  core_enrichment = TRUE,
  label_format = 30,
  orderBy = "NES",
  decreasing = FALSE
)
```

Arguments

<code>x</code>	<code>gseaResult</code> object
<code>showCategory</code>	number of categories to display or a vector of terms.
<code>fill</code>	one of "pvalue", "p.adjust", "qvalue"
<code>core_enrichment</code>	whether to use only core_enriched genes

label_format	a numeric value setting the wrap length, alternatively a custom function to format axis labels.
...	additional parameters.
orderBy	The order of the Y-axis
decreasing	logical. Should the orderBy order be increasing or decreasing?

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
x <- gseD0(geneList)
ridgeplot(x)
```

set_enrichplot_color *Helper function to set color scale for enrichplot*

Description

Helper function to set color scale for enrichplot

Usage

```
set_enrichplot_color(
  colors = get_enrichplot_color(2),
  type = "color",
  name = NULL,
  .fun = NULL,
  reverse = TRUE,
  transform = "identity",
  ...
)
```

Arguments

colors	user provided color vector
type	one of 'color', 'colour' or 'fill'
name	name of the color legend

.fun	force to use user provided color scale function
reverse	whether reverse the color scheme
transform	transform the color scale
...	additional parameters

Value

a color scale

Author(s)

Guangchuang Yu

ssplot

ssplot

Description

Similarity Space Plot for enrichment analysis

Usage

```
ssplot(x, ...)

## S4 method for signature 'enrichResult'
ssplot(x, showCategory = 30, ...)

## S4 method for signature 'gseaResult'
ssplot(x, showCategory = 30, ...)

## S4 method for signature 'compareClusterResult'
ssplot(x, showCategory = 30, ...)

ssplot.enrichResult(
  x,
  showCategory = 30,
  drfun = NULL,
  dr.params = list(),
  node_label = "group",
  ...
)

ssplot.compareClusterResult(
  x,
  showCategory = 30,
  pie = "equal",
```

```

drfun = NULL,
dr.params = list(),
node_label = "group",
...
)

```

Arguments

x	Enrichment result.
...	additional parameters
	Additional parameters can refer to the following parameters:
	• layout igraph layout function for node positioning • color Variable used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'. • size_category relative size of the categories • min_edge The minimum similarity threshold for whether two nodes are connected, should be between 0 and 1, default value is 0.2. • color_edge color of the network edge • size_edge relative size of edge width. • node_label Select which labels to display, one of 'category', 'group', 'all' and 'none'. • node_label_size size of node label, default is 5. • pie one of 'equal' or 'Count' to set the slice ratio of the pies (for 'compareClusterResult' only). • label_format a numeric value sets wrap length, alternatively a custom function to format axis labels. • clusterFunction function of Clustering method, such as 'stats::kmeans' (the default), 'cluster::clara', 'cluster::fanny' or 'cluster::pam'. • nWords Numeric, the number of words in the cluster tags, the default value is 4. • nCluster Numeric, the number of clusters, the default value is square root of the number of nodes.
	Additional parameters can refer to the 'emapplot' function: emapplot .
showCategory	number of categories to display or a vector of terms.
drfun	The function used for dimension reduction, e.g. 'stats::cmdscale' (the default), 'vegan::metaMDS', or 'ape::pcoa'.
dr.params	list, the parameters of 'tidydr::dr'.
node_label	Select which labels to display, one of 'category', 'group', 'all' and 'none'.
pie	one of 'equal' or 'Count' to set the slice ratio of the pies

Details

Creates 2D visualization of enrichment results using dimension reduction techniques to show relationships between terms based on similarity.

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
## Not run:
library(clusterProfiler)
library(org.Hs.eg.db)
library(enrichplot)
library(GOSemSim)
library(DOSE)
data(geneList)
gene <- names(geneList)[abs(geneList) > 2]
ego <- enrichGO(gene = gene,
  universe      = names(geneList),
  OrgDb         = org.Hs.eg.db,
  ont           = "BP",
  pAdjustMethod = "BH",
  pvalueCutoff  = 0.01,
  qvalueCutoff  = 0.05,
  readable      = TRUE)
d <- godata('org.Hs.eg.db', ont="BP")
ego2 <- pairwise_termsim(ego, method = "Wang", semData = d)
ssplot(ego2)

## End(Not run)
```

treeplot

treeplot

Description

Functional grouping tree diagram for enrichment result of over-representation test or gene set enrichment analysis.

Creates hierarchical tree visualization of enriched terms based on similarity

Usage

```
treeplot(x, ...)
```

S4 method for signature 'enrichResult'

```
treeplot(x, ...)
```

S4 method for signature 'gseaResult'

```

treeplot(x, ...)

## S4 method for signature 'compareClusterResult'
treeplot(x, ...)

treeplot_internal(
  x,
  showCategory = 30,
  color = "p.adjust",
  size_var = c("Count", "setSize"),
  nCluster = 5,
  cluster_method = "ward.D",
  label_format = 30,
  fontsize_tiplab = 4,
  fontsize_cladelab = 4,
  group_color = NULL,
  extend = 0.3,
  hilight = TRUE,
  align = "both",
  hexpand = 0.1,
  tiplab_offset = 0.2,
  cladelab_offset = 1
)

```

Arguments

x	enrichment result.
...	additional parameters
showCategory	number of enriched terms to display
color	variable to color nodes, e.g. 'p.adjust', 'pvalue', or 'qvalue'
size_var	variable for node size, e.g. 'Count' (for enrichResult) or 'setSize' (for gseaResult)
nCluster	number of clusters for tree cutting
cluster_method	hierarchical clustering method
label_format	wrap length for labels or custom formatting function
fontsize_tiplab	font size for tip labels
fontsize_cladelab	font size for clade labels
group_color	vector of colors for groups
extend	extend length for clade labels
hilight	whether to highlight clades
align	alignment for highlight rectangles
hexpand	expand x limits by amount of xrange * hexpand

tiplab_offset offset for tip labels
 cladelab_offset
 offset for clade labels

Details

This function visualizes gene sets as a tree. Gene sets with high similarity tend to cluster together, making it easier for interpretation.

Value

ggplot object
 ggplot2 object representing the tree plot

Examples

```
## Not run:
library(clusterProfiler)
library(org.Hs.eg.db)
library(enrichplot)
library(GOsemSim)
library(ggplot2)
library(DOSE)
data(geneList)
gene <- names(geneList)[abs(geneList) > 2]
ego <- enrichGO(gene = gene,
  universe = names(geneList),
  OrgDb = org.Hs.eg.db,
  ont = "BP",
  pAdjustMethod = "BH",
  pvalueCutoff = 0.01,
  qvalueCutoff = 0.05,
  readable = TRUE)
d <- godata('org.Hs.eg.db', ont="BP")
ego2 <- pairwise_termsim(ego, method = "Wang", semData = d)
treeplot(ego2, showCategory = 30)
# use `highlight = FALSE` to remove ggtree::geom_highlight() layer.
treeplot(ego2, showCategory = 30, highlight = FALSE)
# use `offset` parameter to adjust the distance of bar and tree.
treeplot(ego2, showCategory = 30, highlight = FALSE, offset = rel(1.5))
# use `offset_tiplab` parameter to adjust the distance of nodes and branches.
treeplot(ego2, showCategory = 30, highlight = FALSE, offset_tiplab = rel(1.5))
keep <- rownames(ego2@termsim)[c(1:10, 16:20)]
keep
treeplot(ego2, showCategory = keep)
treeplot(ego2, showCategory = 20,
  group_color = c("#999999", "#E69F00", "#56B4E9", "#009E73", "#F0E442"))
# It can also graph compareClusterResult
data(gcSample)
xx <- compareCluster(gcSample, fun="enrichKEGG",
  organism="hsa", pvalueCutoff=0.05)
xx <- pairwise_termsim(xx)
```

```
treeplot(xx)

# use `geneClusterPanel` to change the gene cluster panel.
treeplot(xx, geneClusterPanel = "dotplot")

treeplot(xx, geneClusterPanel = "pie")

## End(Not run)
```

upsetplot

upsetplot method

Description

upsetplot method generics
Upsetplot

Usage

```
upsetplot(x, ...)
```

S4 method for signature 'enrichResult'

```
upsetplot(x, n = 10, ...)
```

S4 method for signature 'gseaResult'

```
upsetplot(x, n = 10, ...)
```

Arguments

x	object
...	additional parameters
n	number of categories to be plotted

Value

plot

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
upsetplot(x, 8)
```

`volplot`*volplot*

Description

Volcano plot for enrichment result

Usage

```
volplot(  
  x,  
  color = "zScore",  
  xintercept = 1,  
  yintercept = 2,  
  showCategory = 5,  
  label_format = 30,  
  ...  
)  
  
## S4 method for signature 'enrichResult'  
volplot(  
  x,  
  color = "zScore",  
  xintercept = 1,  
  yintercept = 2,  
  showCategory = 5,  
  label_format = 30,  
  ...  
)  
  
volplot.enrichResult(  
  x,  
  color = "zScore",  
  xintercept = 1,  
  yintercept = 2,  
  showCategory = 5,  
  label_format = 30,  
  font.size = 12,  
  size = 5  
)
```

Arguments

<code>x</code>	enrichment result.
<code>color</code>	selected variable to color the dots
<code>xintercept</code>	value to set x-intercept

yintercept	value to set y-intercept
showCategory	number of most significant enriched terms or selected terms to display determined by the variable selected to color the dots
label_format	a numeric value setting the wrap length, alternatively a custom function to format axis labels.
...	Additional parameters
font.size	font size for 'theme_dose()'
size	font size to label selected categories specified by showCategory

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
volplot(x)
```

Index

- * **datasets**
 - enrichplot_point_shape, 15
- * **internal**
 - enrichplot-package, 3
 - reexports, 29
- as.data.frame.compareClusterResult, 3
- autofacet, 4
- barplot.enrichResult, 4
- cnetplot, 29
- cnetplot(reexports), 29
- cnetplot.compareClusterResult(cnetplot.enrichResult), 5
- cnetplot.enrichResult, 5
- cnetplot.gseaResult(cnetplot.enrichResult), 5
- color_palette, 8
- dotplot, 8
- dotplot,compareClusterResult,ANY-method(dotplot), 8
- dotplot,compareClusterResult-method(dotplot), 8
- dotplot,enrichResult-method(dotplot), 8
- dotplot,enrichResultList,ANY-method(dotplot), 8
- dotplot,enrichResultList-method(dotplot), 8
- dotplot,gseaResult-method(dotplot), 8
- dotplot,gseaResultList,ANY-method(dotplot), 8
- dotplot,gseaResultList-method(dotplot), 8
- dotplot.compareClusterResult(dotplot), 8
- dotplot.enrichResult(dotplot), 8
- dotplot2, 12
- emapplot, 13, 33
- emapplot,compareClusterResult-method(emapplot), 13
- emapplot,enrichResult-method(emapplot), 13
- emapplot,gseaResult-method(emapplot), 13
- emapplot_internal(emapplot), 13
- enrichplot(enrichplot-package), 3
- enrichplot-package, 3
- enrichplot_point_shape, 15
- facet_grid, 29
- facet_grid(reexports), 29
- fortify.compareClusterResult, 16
- fortify.enrichResult(fortify.compareClusterResult), 16
- geneID, 29
- geneID(reexports), 29
- geneInCategory, 29
- geneInCategory(reexports), 29
- geom_cnet_label, 29
- geom_cnet_label(reexports), 29
- geom_gsea_gene, 17
- get_enrichplot_color, 18
- ggtable, 18
- ggtitle, 29
- ggtitle(reexports), 29
- godata, 27
- goplot, 19
- goplot,enrichResult-method(goplot), 19
- goplot,gseaResult-method(goplot), 19
- gseadist, 20
- gseaplot, 21
- gseaplot,gseaResult-method(gseaplot), 21
- gseaplot.gseaResult(gseaplot), 21
- gseaplot2, 22
- gsearank, 23

gseaScores, 29
gseaScores (reexports), 29
gsInfo, 24

heatmap, 24
heatmap, enrichResult-method
 (heatmap), 24
heatmap, gseaResult-method (heatmap),
 24
heatmap.enrichResult (heatmap), 24
hplot, 26

pairwise_termsim, 14, 26
pairwise_termsim, compareClusterResult-method
 (pairwise_termsim), 26
pairwise_termsim, enrichResult-method
 (pairwise_termsim), 26
pairwise_termsim, gseaResult-method
 (pairwise_termsim), 26
pairwise_termsim.compareClusterResult
 (pairwise_termsim), 26
pairwise_termsim.enrichResult
 (pairwise_termsim), 26
plot_list, 29
plot_list (reexports), 29
plotting.clusterProfile, 28
pmcplot, 29

reexports, 29
ridgeplot, 30
ridgeplot, gseaResult-method
 (ridgeplot), 30
ridgeplot.gseaResult (ridgeplot), 30

set_enrichplot_color, 31
ssplot, 32
ssplot, compareClusterResult-method
 (ssplot), 32
ssplot, enrichResult-method (ssplot), 32
ssplot, gseaResult-method (ssplot), 32
ssplot.compareClusterResult (ssplot), 32
ssplot.enrichResult (ssplot), 32

theme_dose, 29
theme_dose (reexports), 29
treeplot, 34
treeplot, compareClusterResult-method
 (treeplot), 34
treeplot, enrichResult-method
 (treeplot), 34
treeplot, gseaResult-method (treeplot),
 34
treeplot_internal (treeplot), 34

upsetplot, 37
upsetplot, enrichResult, ANY-method
 (upsetplot), 37
upsetplot, enrichResult-method
 (upsetplot), 37
upsetplot, gseaResult (upsetplot), 37
upsetplot, gseaResult-method
 (upsetplot), 37

volplot, 38
volplot, enrichResult-method (volplot),
 38
volplot.enrichResult (volplot), 38