

Package ‘iSEEhex’

January 24, 2026

Title iSEE extension for summarising data points in hexagonal bins

Version 1.13.0

Date 2024-20-01

Description This package provides panels summarising data points in hexagonal bins for ‘iSEE’. It is part of ‘iSEEu’, the iSEE universe of panels that extend the ‘iSEE’ package.

License Artistic-2.0

URL <https://github.com/iSEE/iSEEhex>

BugReports <https://support.bioconductor.org/t/iSEEhex>

biocViews Software, Infrastructure

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Depends SummarizedExperiment, iSEE

Imports ggplot2, hexbin, methods, shiny

Suggests BiocStyle, covr, knitr, RefManageR, rmarkdown, sessioninfo, testthat (>= 3.0.0), scRNAseq, scater

Config/testthat/edition 3

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/iSEEhex>

git_branch devel

git_last_commit 2ce63cf

git_last_commit_date 2025-10-29

Repository Bioconductor 3.23

Date/Publication 2026-01-23

Author Kevin Rue-Albrecht [aut, cre] (ORCID:
<<https://orcid.org/0000-0003-3899-3872>>),
Charlotte Soneson [aut] (ORCID:

<<https://orcid.org/0000-0003-3833-2169>>),
 Federico Marini [aut] (ORCID: <<https://orcid.org/0000-0003-3252-7758>>),
 Aaron Lun [aut] (ORCID: <<https://orcid.org/0000-0002-3564-4813>>)

Maintainer Kevin Rue-Albrecht <kevinrue67@gmail.com>

Contents

iSEHex-pkg	2
ReducedDimensionHexPlot-class	3
Index	5

iSEHex-pkg	<i>iSEHex: iSEE extension for summarising data points in hexagonal bins</i>
------------	---

Description

iSEHex is a package that provides panels summarising data points in hexagonal bins for iSEE.

Author(s)

Kevin Rue-Albrecht <kevin.rue-albrecht@kennedy.ox.ac.uk>

Charlotte Soneson <charlottesoneson@gmail.com>

Federico Marini <marinif@uni-mainz.de>

Aaron Lun <infinite.monkeys.with.keyboards@gmail.com>

See Also

Useful links:

- <https://github.com/iSEE/iSEHex>
- Report bugs at <https://support.bioconductor.org/t/iSEHex>

ReducedDimensionHexPlot-class

The ReducedDimensionHexPlot class

Description

The ReducedDimensionHexPlot is a [ReducedDimensionPlot](#) subclass that is dedicated to creating a reduced dimension plot summarising data points in hexagonal bins.

Slot overview

The following slots control the parameters used in the visualization:

- `BinResolution`, a numeric positive scalar specifying the number of hexagonal bins in both vertical and horizontal directions. Defaults to 100.

In addition, this class inherits all slots from its parent [ReducedDimensionPlot](#), [ColumnDotPlot](#), [DotPlot](#) and [Panel](#) classes.

Constructor

`ReducedDimensionHexPlot(...)` creates an instance of a `ReducedDimensionHexPlot` class, where any slot and its value can be passed to `...` as a named argument.

Supported methods

In the following code snippets, `x` is an instance of a [ReducedDimensionHexPlot](#) class. Refer to the documentation for each method for more details on the remaining arguments.

For defining the interface:

- `.panelColor(x)` will return the specified default color for this panel class.
- `.fullName(x)` will return "Hexagonal reduced dimension plot".
- `.hideInterface(x, field)` will return TRUE for `field="Downsample"` as downsampling is not applicable to this panel that summarizes all data points in each hexagonal bin; otherwise this function will call the [ReducedDimensionPlot](#) method.
- `.defineVisualShapeInterface(x)` will return NULL for this panel, as the shape aesthetic is not applicable to this panel that does not display individual data points.
- `.defineVisualSizeInterface(x)` overrides the equivalent method inherited from all parents classes and will return instead an HTML tag definition that contains a user input controlling the number of hexagonal bins in both vertical and horizontal directions.
- `.defineVisualOtherInterface(x)` will return NULL, as there are no additional visual parameters for this panel.
- `.allowableColorByDataChoices(x, se)` will return a character vector with the names of all continuous fields in `colData(se)`, where `se` is the input [SummarizedExperiment](#) object.

For monitoring reactive expressions:

- `.createObservers(x, se, input, session, pObjects, rObjects)` sets up observers for all new slots described above, as well as in the parent classes via the `ReducedDimensionPlot` method.

For creating the plot:

- `.generateDotPlot(x, envir)` will return a list with plot, a `ggplot2::ggplot()` object; and commands, a character vector of commands to produce that object when evaluated inside `envir`.

For documentation:

- `.definePanelTour(x)` returns an data.frame containing the steps of a panel-specific tour.
- `.getDotPlotColorHelp(x, color_choices)` returns a function that generates an **rintrojs** tour for the color choice UI.

Author(s)

Kevin Rue-Albrecht

See Also

`ReducedDimensionPlot`, for the base class.

Examples

```
library(scRNAseq)

# Example data ----
sce <- ReprocessedAllenData(assays="tophat_counts")
class(sce)

library(scater)
sce <- logNormCounts(sce, exprs_values="tophat_counts")

sce <- runPCA(sce, ncomponents=4)
sce <- runTSNE(sce)
rowData(sce)$ave_count <- rowMeans(assay(sce, "tophat_counts"))
rowData(sce)$n_cells <- rowSums(assay(sce, "tophat_counts") > 0)

# launch the app itself ----

if (interactive()) {
  iSEE(sce, initial=list(
    ReducedDimensionHexPlot(BinResolution=50),
    ReducedDimensionPlot()
  ))
}
```

Index

* **internal**
 iSEEhex-pkg, 2
 .allowableColorByDataChoices, 3
 .allowableColorByDataChoices, ReducedDimensionHexPlot-method
 (ReducedDimensionHexPlot-class), 3
 .createObservers, 4
 .createObservers, ReducedDimensionHexPlot-method
 (ReducedDimensionHexPlot-class), 3
 .definePanelTour, 4
 .definePanelTour, ReducedDimensionHexPlot-method
 (ReducedDimensionHexPlot-class), 3
 .defineVisualOtherInterface, 3
 .defineVisualOtherInterface, ReducedDimensionHexPlot-method
 (ReducedDimensionHexPlot-class), 3
 .defineVisualShapeInterface, 3
 .defineVisualShapeInterface, ReducedDimensionHexPlot-method
 (ReducedDimensionHexPlot-class), 3
 .defineVisualSizeInterface, 3
 .defineVisualSizeInterface, ReducedDimensionHexPlot-method
 (ReducedDimensionHexPlot-class), 3
 .fullName, 3
 .fullName, ReducedDimensionHexPlot-method
 (ReducedDimensionHexPlot-class), 3
 .generateDotPlot, 4
 .generateDotPlot, ReducedDimensionHexPlot-method
 (ReducedDimensionHexPlot-class), 3
 .getDotPlotColorHelp, 4
 .getDotPlotColorHelp, ReducedDimensionHexPlot-method
 (ReducedDimensionHexPlot-class), 3
 .hideInterface, 3
 .hideInterface, ReducedDimensionHexPlot-method
 (ReducedDimensionHexPlot-class), 3
 panelColor, 3
 .panelColor, ReducedDimensionHexPlot-method
 (ReducedDimensionHexPlot-class), 3
 colData(se), 3
 ColumnDotPlot, 3
 DotPlot, 3
 ggplot2::ggplot(), 4
 initialize, ReducedDimensionHexPlot-method
 (ReducedDimensionHexPlot-class), 3
 iSEEhex (iSEEhex-pkg), 2
 iSEEhex-package (iSEEhex-pkg), 2
 iSEEhex-pkg, 2
 Panel, 3
 ReducedDimensionHexPlot, 3
 ReducedDimensionHexPlot
 (ReducedDimensionHexPlot-class), 3
 ReducedDimensionHexPlot-class, 3
 ReducedDimensionPlot, 3, 4
 SummarizedExperiment, 3