

Package ‘HiCaptuRe’

May 26, 2026

Type Package

Title HiCaptuRe: Manipulating and integrating Capture Hi-C data

Version 1.3.0

URL <https://github.com/LaureTomas/HiCaptuRe>

Description Capture Hi-C is a set of techniques that enable the detection of genomic interactions involving regions of interest, known as baits. By focusing on selected loci, these approaches reduce sequencing costs while maintaining high resolution at the level of restriction fragments. Hi-CaptuRe provides tools to import, annotate, manipulate, and export Capture Hi-C data. The package accounts for the specific structure of bait–otherEnd interactions, facilitates integration with other omics datasets, and enables comparison across samples and conditions.

BugReports <https://github.com/LaureTomas/HiCaptuRe/issues>

License GPL-3

Encoding UTF-8

LazyData false

Depends R (>= 4.5.0)

Imports Biostrings, BSgenome, cli, data.table, dplyr, GenomeInfoDb, GenomicInteractions, GenomicRanges, InteractionSet, ggplot2, ggpubr, ggVennDiagram, gplots, igraph, IRanges, memoise, methods, S4Vectors, stringr, tibble, tidyr, UpSetR, utils

RoxygenNote 7.3.2

Suggests BSgenome.Hsapiens.NCBI.GRCh38, knitr, rmarkdown, DT, testthat, BiocStyle, kableExtra

biocViews Epigenetics, HiC, Sequencing, DataImport, Software

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/HiCaptuRe>

git_branch devel

git_last_commit 5fa64f9

git_last_commit_date 2026-04-28

Repository Bioconductor 3.24

Date/Publication 2026-05-25

Author Laureano Tomas-Daza [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-6127-1694>>)

Maintainer Laureano Tomas-Daza <lauretomas@gmail.com>

Contents

HiCaptuRe-package	2
.annotate_BOE	3
annotate_interactions	3
constants	4
digest_genome	4
distance_summary	5
export_interactions	6
getters	7
HiCaptuRe-class	8
interactionsByBaits	8
interactionsByRegions	9
intersect_interactions	10
load_interactions	10
peakmatrix2list	11
plot_distance_summary	12
setters	12
Index	14

HiCaptuRe-package	<i>HiCaptuRe: HiCaptuRe: Manipulating and integrating Capture Hi-C data</i>
-------------------	---

Description

Capture Hi-C is a set of techniques that enable the detection of genomic interactions involving regions of interest, known as baits. By focusing on selected loci, these approaches reduce sequencing costs while maintaining high resolution at the level of restriction fragments. HiCaptuRe provides tools to import, annotate, manipulate, and export Capture Hi-C data. The package accounts for the specific structure of bait–otherEnd interactions, facilitates integration with other omics datasets, and enables comparison across samples and conditions.

Author(s)

Maintainer: Laureano Tomas-Daza <lauretomas@gmail.com> ([ORCID](#))

See Also

Useful links:

- <https://github.com/LaureTomas/HiCaptuRe>
- Report bugs at <https://github.com/LaureTomas/HiCaptuRe/issues>

.annotate_BOE *Annotates interactions into B_B or B_OE*

Description

This internal function annotate a HiCaptuRe object based on the presence or not of annotation in a given restriction fragment

Usage

```
.annotate_BOE(interactions)
```

Arguments

interactions HiCaptuRe object from [load_interactions](#)

Value

HiCaptuRe object with the column int updated

annotate_interactions *Annotates HiCaptuRe object from load_interactions*

Description

This function annotate a HiCaptuRe object from load_interactions, based on a given annotations file

Usage

```
annotate_interactions(interactions, annotation, ...)
```

Arguments

interactions HiCaptuRe object from [load_interactions](#)
annotation full path to annotations file or a dataframe with 5 columns: chr, start, end, fragmentID, annotation
... additional parameters for fread

Value

HiCaptuRe object annotated, with columns bait_1 and bait_2 substituted based on the given annotation

Examples

```
annotation <- system.file("extdata", "annotation_example.txt", package = "HiCaptuRe")  
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")  
interactions <- load_interactions(ibed1, select_chr = "19")  
interactions <- annotate_interactions(interactions = interactions, annotation = annotation)
```

constants	<i>Column name constants for format detection and export</i>
-----------	--

Description

‘.IBED_COLS’ and ‘.PEAKMATRIX_COLS’ store canonical column names for ibed and peakmatrix formats. These are used in both ‘.detect_format()’ and export functions to avoid repetition and ensure consistency between import and export.

Usage

```
.IBED_COLS
```

Format

An object of class character of length 10.

digest_genome	<i>Digest genome for a specific restriction enzyme</i>
---------------	--

Description

This function takes a genome installed and generates its digest for a given restriction enzyme

Usage

```
digest_genome(
  genome = "GRCh38",
  RE_name = "HindIII",
  motif = NULL,
  cut_position = NULL,
  select_chr = c(seq_len(22), "X", "Y"),
  PAR_mask = TRUE,
  PAR_file = NULL,
  ...
)
```

Arguments

genome	character with the name of the genome version
RE_name	name of the restriction enzyme
motif	recognition motif of the restriction enzyme
cut_position	cut position of the restriction enzyme inside the motif
select_chr	a character vector containing the specific chromosomes to used from this genome, if NULL all chromosomes will be used
PAR_mask	a logical value where the Y chromosome should exclude the Pseudoautosomal Regions (PAR) or not
PAR_file	a full path to a file containing the coordinates of Y chromosome PAR with at least 3 columns with header: seqnames, start, end
...	extra arguments for read.table

Value

list object with 2 elements: a dataframe with the digested genome, and a the parameters used for the digestion.

Note

The package provides for a PAR coordinates file only for Homo sapiens for the genome version 38

The package provides the motives and cut positions for several restriction enzymes (HindIII, MboI, DpnII, EcoRI, BamHI)

Examples

```
digest <- digest_genome(genome = "GRCh38", RE_name = "HindIII", select_chr = "19")
```

distance_summary	<i>Computes the number of interactions by distance</i>
------------------	--

Description

This function computes the number of interactions by distance for a given GenomicInteractions object

Usage

```
distance_summary(interactions, breaks = seq(0, 10^6, 10^5), sample = "sample")
```

Arguments

interactions	GenomicInteractions object from load_interactions
breaks	vector with breaks for split distances
sample	character variable with the name of the sample

Value

list with 2 tables: short_int_dist_table and long_int_dist_table, with the number of short interactions and long interactions respectively

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")
interactions1 <- load_interactions(ibed1, select_chr = "19")
df <- distance_summary(interactions = interactions1)
```

export_interactions *Export interactions in the desired output format*

Description

This function exports interactions in different formats

Usage

```
export_interactions(  
  interactions,  
  file,  
  format = "ibed",  
  over.write = FALSE,  
  cutoff = 5,  
  parameters = FALSE  
)
```

Arguments

interactions	GenomicInteractions object from load_interactions
file	full path to desired output file (ibed, peakmatrix, washU, washUold, cytoscape, bedpe)
format	type of output format (ibed, peakmatrix, washU, washUold, cytoscape, bedpe, seqmonk)
over.write	TRUE/FALSE to over write the output file
cutoff	Chicago score cutoff to export interactions
parameters	TRUE/FALSE to also export the parameters of the given object

Value

tibble object with the ibed table and save it in the desired output file

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")  
interactions <- load_interactions(ibed1, select_chr = "19")  
export_interactions(interactions = interactions, file = tempfile(), format = "ibed", over.write = TRUE)
```

getters

Internal functions to access data held in a HiCaptuRe object.

Description

Use these functions to access data stored in each of the slots of a HiCapture object.

Usage

```
getParameters(x)

## S4 method for signature 'HiCaptuRe'
getParameters(x)

getByBaits(x)

## S4 method for signature 'HiCaptuRe'
getByBaits(x)

getByRegions(x)

## S4 method for signature 'HiCaptuRe'
getByRegions(x)
```

Arguments

x A HiCaptuRe object

Value

getParameters(x) A named list of named vectors with all parameters used.

getByBaits(x) A list of tibbles with bait-centric summaries.

getByRegions(x) A list of ‘GRanges’ with region-centric summaries.

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")
interactions <- load_interactions(ibed1, select_chr = "19")
getParameters(interactions)

baits <- c("ENST00000332235", "ENST00000516525")
interactions_baits <- interactionsByBaits(interactions = interactions, baits = baits)
getByBaits(interactions_baits)

regions <- GenomicRanges::GRanges(seqnames = 19, ranges = IRanges::IRanges(start = c(500000, 1000000), end = c(
interactions_regions <- interactionsByRegions(interactions = interactions, regions = regions)
getByRegions(interactions_regions)
```

HiCaptuRe-class	<i>HiCaptuRe Class</i>
-----------------	------------------------

Description

A S4 class to represent interactions between genomic regions

Slots

parameters List of parameters used to create the object and subsequence analysis

ByBaits List of Baits used by [interactionsByBaits](#).

ByRegions List of Regions used by [interactionsByRegions](#)

Note

This class contains a [GenomicInteractions](#) object inside therefore all methods available to it can be used. This type of object should be created through the function [load_interactions](#)

interactionsByBaits	<i>Filters HiCaptuRe object by baits</i>
---------------------	--

Description

This function filters a HiCaptuRe object from `load_interactions` by a set of given bait(s)

Usage

```
interactionsByBaits(interactions, baits, sep = ",", invert = FALSE)
```

Arguments

interactions a HiCaptuRe object

baits character vector containing bait names

sep character separating baits names when several baits in same fragment

invert TRUE/FALSE if need those interactions that do NOT contain the given baits

Value

The returned object includes a filtered set of interactions and updates the ByBaits slot with a tibble summarizing bait-wise interaction statistics (number of interactions, other ends, etc.). Baits that are not present in the interaction data will have empty statistics.

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")
interactions <- load_interactions(ibed1, select_chr = "19")
baits <- c("ENST00000332235", "ENST00000516525")
interactions_baits <- interactionsByBaits(interactions = interactions, baits = baits)
```

interactionsByRegions *Filters HiCaptuRe object by overlapping regions*

Description

This function filters a HiCaptuRe object from load_interactions by overlapping regions

Usage

```
interactionsByRegions(  
  interactions,  
  regions,  
  chr = NULL,  
  start = NULL,  
  end = NULL,  
  invert = FALSE  
)
```

Arguments

interactions	HiCaptuRe object
regions	full path to regions file (bed format) or a GRanges object
chr	column name of chromosome values
start	column name of start positions
end	column name of end positions
invert	TRUE/FALSE if need those interactions that do NOT overlaps with any regions

Value

HiCaptuRe object filtered by regions, by default with additional columns regarding overlap on each node. If invert=T no additional columns. And an additional slot ByRegions with region-centric statistics

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")  
interactions <- load_interactions(ibed1, select_chr = "19")  
regions <- GenomicRanges::GRanges(seqnames = 19, ranges = IRanges::IRanges(start = c(500000, 1000000), end = c(500000, 1000000)))  
interactions_regions <- interactionsByRegions(interactions = interactions, regions = regions)
```

intersect_interactions

Computes the intersect between a list of interactions objects

Description

This function computes all the possible intersects for a given list of HiCaptuRe objects

Usage

```
intersect_interactions(interactions_list, distance.boxplot = FALSE, ...)
```

Arguments

`interactions_list` list of HiCaptuRe objects from [load_interactions](#)

`distance.boxplot` logical, by default FALSE, plot a boxplot of log10 distance of each intersection in the upset plot

`...` extra arguments for UpSetR

Value

A list with:

intersections A named list of intersected HiCaptuRe objects

upset An UpSetR plot

venn A ggVennDiagram plot (NULL if > 7 sets)

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")
interactions1 <- load_interactions(ibed1, select_chr = "19")
ibed2 <- system.file("extdata", "ibed2_example.zip", package = "HiCaptuRe")
interactions2 <- load_interactions(ibed2, select_chr = "19")
interactions_list <- list(ibed1 = interactions1, ibed2 = interactions2)
intersection <- intersect_interactions(interactions_list = interactions_list)
```

load_interactions

Loads interaction file into GenomicInteractions Object

Description

This function loads interaction files from Chicago R package into a GenomicInteractions Object, and remove possible duplicated interactions

Usage

```
load_interactions(file, sep = "\t", ...)
```

Arguments

file full path to the interaction file (seqmonk, ibed, washU)
sep separator to read the file
... arguments to pass to [digest_genome](#)

Value

HiCaptuRe object

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")  
interactions <- load_interactions(ibed1, select_chr = "19")
```

peakmatrix2list *Creates a list of HiCaptuRe objects based on a peakmatrix*

Description

This function creates a list of HiCaptuRe objects separating all the samples included on a peakmatrix.

Usage

```
peakmatrix2list(peakmatrix, cutoff = 5)
```

Arguments

peakmatrix HiCaptuRe object of a peakmatrix
cutoff Chicago score cut-off to filter interactions

Value

A named list of HiCaptuRe objects, each corresponding to a sample (inferred from CS_* columns in the peakmatrix).

Examples

```
peakmatrix <- system.file("extdata", "peakmatrix_example.zip", package = "HiCaptuRe")  
interactions <- load_interactions(peakmatrix, select_chr = "19")  
interactions_list <- peakmatrix2list(peakmatrix = interactions)
```

`plot_distance_summary` *Generate the plot based on distance output*

Description

This function plots the distances by different approaches for the output of `distance_summary`

Usage

```
plot_distance_summary(distances, type_of_value = "absolute")
```

Arguments

`distances` dataframes output from `distance_summary`
`type_of_value` an element from: `absolute`, `by_int_type`, `by_total`

Details

The `type_of_value` argument could be: `Absolute`: plots the Absolute number of interactions. `By_int_type`: plots the number of interactions divided by the total number of interactions of each type. `By_total`: plots the number of interactions divided by the total number of interactions

Value

list with the plots

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")
interactions1 <- load_interactions(ibed1, select_chr = "19")
df <- distance_summary(interactions = interactions1)
plots <- plot_distance_summary(distances = df)
```

setters

Functions to set data held in a HiCaptuRe object.

Description

Use these functions to set data stored in each of the slots of a HiCapture object.

Usage

```
.setParameters(x, y)

## S4 method for signature 'HiCaptuRe,list'
.setParameters(x, y)

.setByBaits(x, y)
```

```
## S4 method for signature 'HiCaptuRe,list'  
.setByBaits(x, y)  
  
.setByRegions(x, y)  
  
## S4 method for signature 'HiCaptuRe,list'  
.setByRegions(x, y)
```

Arguments

x	A HiCaptuRe object
y	Data to add (parameters, tibble with bait-centric information or GRanges with region-centric)

Value

A HiCaptuRe object

Index

- * **internal**
 - .annotate_BOE, 3
 - constants, 4
 - HiCaptuRe-package, 2
 - setters, 12
 - .IBED_COLS (constants), 4
 - .annotate_BOE, 3
 - .setByBaits (setters), 12
 - .setByBaits, HiCaptuRe, list-method (setters), 12
 - .setByRegions (setters), 12
 - .setByRegions, HiCaptuRe, list-method (setters), 12
 - .setParameters (setters), 12
 - .setParameters, HiCaptuRe, list-method (setters), 12
- annotate_interactions, 3
- constants, 4
- digest_genome, 4, 11
- distance_summary, 5, 12
- export_interactions, 6
- GenomicInteractions, 8
- getByBaits (getters), 7
- getByBaits, HiCaptuRe-method (getters), 7
- getByRegions (getters), 7
- getByRegions, HiCaptuRe-method (getters), 7
- getParameters (getters), 7
- getParameters, HiCaptuRe-method (getters), 7
- getters, 7
- HiCaptuRe (HiCaptuRe-package), 2
- HiCaptuRe-class, 8
- HiCaptuRe-package, 2
- interactionsByBaits, 8, 8
- interactionsByRegions, 8, 9
- intersect_interactions, 10
- load_interactions, 3, 5, 6, 8, 10, 10
- peakmatrix2list, 11
- plot_distance_summary, 12
- setters, 12