

# Package ‘SiPSiC’

May 26, 2026

**Type** Package

**Title** Calculate Pathway Scores for Each Cell in scRNA-Seq Data

**Version** 1.13.0

**Date** 2022-12-29

**Description** Infer biological pathway activity of cells from single-cell RNA-sequencing data by calculating a pathway score for each cell (pathway genes are specified by the user). It is recommended to have the data in Transcripts-Per-Million (TPM) or Counts-Per-Million (CPM) units for best results. Scores may change when adding cells to or removing cells off the data. SiPSiC stands for Single Pathway analysis in Single Cells.

**License** file LICENSE

**URL** <https://www.genome.org/cgi/doi/10.1101/gr.278431.123>

**biocViews** Software, DifferentialExpression, GeneSetEnrichment, BiomedicalInformatics, CellBiology, Transcriptomics, RNASeq, SingleCell, Transcription, Sequencing, ImmunoOncology, DataImport

**Depends** Matrix, SingleCellExperiment

**Suggests** knitr, rmarkdown, BiocStyle

**VignetteBuilder** knitr

**BugReports** <https://github.com/DanielDavis12/SiPSiC/issues>

**git\_url** <https://git.bioconductor.org/packages/SiPSiC>

**git\_branch** devel

**git\_last\_commit** ee7c072

**git\_last\_commit\_date** 2026-04-28

**Repository** Bioconductor 3.24

**Date/Publication** 2026-05-25

**Author** Daniel Davis [aut, cre] (ORCID:  
<<https://orcid.org/0000-0001-7863-1521>>),  
Yotam Drier [aut]

**Maintainer** Daniel Davis <DanielDavis000@gmail.com>

## Contents

SiPSiC-package . . . . .	2
getPathwayScores . . . . .	2
normalizeCountsForGene . . . . .	3

**Index****5**

---

SiPSiC-package	<i>Calculate Pathway Scores for Each Cell in scRNA-Seq Data</i>
----------------	---

---

**Description**

Infer biological pathway activity of cells from single-cell RNA-sequencing data by calculating a pathway score for each cell (pathway genes are specified by the user). It is recommended to have the data in Transcripts-Per-Million (TPM) or Counts-Per-Million (CPM) units for best results. Scores may change when adding cells to or removing cells off the data. SiPSiC stands for Single Pathway analysis in Single Cells.

**Details**

Use this package to calculate per-cell scores for a biological pathway of your choice, from single-cell RNA-seq data. Transcripts-Per-Million (TPM) or Counts-Per-Million (CPM) units of the data are recommended for best results.

**Author(s)**

Daniel Davis, Yotam Drier. Maintainer: Daniel Davis

**References**

<https://medicine.ekmd.huji.ac.il/en/research/yotamd/Pages/default.aspx>

**See Also**

[getPathwayScores](#)

---

getPathwayScores	<i>Calculate Pathway Scores for all Cells in a scRNA-Seq Data</i>
------------------	---

---

**Description**

Calculate a pathway score for each cell included in the input scRNA-seq data, using the cell's transcription level of the pathway's genes.

**Usage**

```
getPathwayScores(dataMatrix, pathwayGenes, percentForNormalization)
```

**Arguments**

a list of three items:

- `dataMatrix` a matrix whose rows and columns represent genes and cells, respectively, containing the scRNA-seq data; Counts-Per-Million (CPM) or Transcripts-Per-Million (TPM) units should be used for best results. The matrix should be of type sparse matrix (`dgCMatrx`), otherwise errors might be raised.
- `pathwayGenes` a character vector of the gene names of which the relevant biological pathway consists.
- `percentForNormalization`  
The percent of top cells for each gene whose median is used to normalize the gene's expression values (5 by default).

**Value**

- `pathwayScores` an array (type double) of the pathway score of each cell in the input `dataMatrix`, less than two of the pathway genes are found in the data, in which case NA is returned.
- `index` a numeric array of the row indices in the `dataMatrix` where genes of the pathway were found.

**Author(s)**

Daniel Davis, Yotam Drier

**References**

<https://medicine.ekmd.huji.ac.il/en/research/yotamd/Pages/default.aspx>

**Examples**

```
library(SiPSiC)
geneCountsMatrix <- matrix(rpois(16, lambda = 10), ncol = 4, nrow = 4)
geneCountsMatrix <- as(geneCountsMatrix, "dgCMatrx")
rownames(geneCountsMatrix) <- c("Gene1", "Gene2", "Gene3", "Gene4")
colnames(geneCountsMatrix) <- c("Cell1", "Cell2", "Cell3", "Cell4")
assayData <- SingleCellExperiment(assays = list(counts = geneCountsMatrix))
pathwayGenesList <- c("Gene1", "Gene2", "Gene4")
percentForNormalization <- 7
scoresAndIndices <- getPathwayScores(counts(assayData), pathwayGenesList, percentForNormalization)
pathwayScoresOfCells <- scoresAndIndices$pathwayScores
pathwayGeneIndices <- scoresAndIndices$index
```

---

normalizeCountsForGene

*Gene counts normalization*

---

**Description**

Get the counts of a single gene normalized by the median of the top 5 percent cells, unless it's zero; In this case, the counts are all divided by the maximum value across all cells. If all counts are zeros, they are returned untouched.

**Usage**

```
normalizeCountsForGene(expressionValues, percentForNormalization)
```

**Arguments**

expressionValues

An array of type double, containing the counts (in any units, e.g. CPM or TPM) of a single gene across different cells.

percentForNormalization

The percent of top cells for each gene whose median is used to normalized the gene's expression values.

**Value**

An array (type double) of the normalized input counts.

**Author(s)**

Daniel Davis, Yotam Drier

# Index

`getPathwayScores`, [2](#), [2](#)

`normalizeCountsForGene`, [3](#)

SiPSiC (SiPSiC-package), [2](#)

SiPSiC-package, [2](#)