

Package ‘VennDetail’

May 26, 2026

Type Package

Title Comprehensive Visualization and Analysis of Multi-Set Intersections

Version 1.29.0

Date 2025-07-01

Description A comprehensive package for visualizing multi-set intersections and extracting detailed subset information. VennDetail generates high-resolution visualizations including traditional Venn diagrams, Venn-pie plots, and UpSet-style plots. It provides functions to extract and combine subset details with user datasets in various formats. The package is particularly useful for bioinformatics applications but can be used for any multi-set analysis.

License GPL-2

Encoding UTF-8

LazyData true

Depends R (>= 4.0.0)

Imports dplyr, DT, ggplot2, grid, gridExtra, magrittr, methods, patchwork, plotly, purrr, rlang, shiny, stats, tibble, tidyr, htmlwidgets, utils

Suggests knitr, rmarkdown, testthat (>= 3.0.0), markdown, RColorBrewer, rstudioapi

VignetteBuilder knitr

URL <https://github.com/guokai8/VennDetail>

BugReports <https://github.com/guokai8/VennDetail/issues>

Roxygen list(roclets = c("`namespace", "`rd"))

RoxygenNote 7.3.3

biocViews DataRepresentation, GraphAndNetwork, Visualization, Software

git_url <https://git.bioconductor.org/packages/VennDetail>

git_branch devel

git_last_commit 352913d

git_last_commit_date 2026-04-28

Repository Bioconductor 3.24

Date/Publication 2026-05-25

Author Kai Guo [aut, cre],
 Brett McGregor [aut],
 James Porter [aut],
 Junguk Hur [aut]

Maintainer Kai Guo <guokai8@gmail.com>

Contents

VennDetail-package	3
.add_colnames	4
.findOverlap	5
.make.table	5
.vennDiagram	6
as.data.frame.Venn	7
compareVenn	7
create_interactive_vennpie	8
detail	9
dim.Venn	10
dplot	10
getFeature	11
getSet	13
head.Venn	14
loadVenn	15
make.subset	15
makeContent.upset_grob	16
make_subset	16
make_truth_table	17
merge.Venn	18
names.Venn	18
newVenn	19
plot.Venn	20
print.upset_grob	25
result	26
rowjoin	27
saveVenn	28
setcolor	28
show Venn	29
summary.Venn	30
T2DM	30
upsetPlot	31
upsetPlot,Venn-method	34
upset_plot	37
Venn-class	40
vennApp	41
venndetail	42
vennDiagram	43
vennDiagram,Venn-method	44
vennEnrichment	46
vennpie	47
vennpie,Venn-method	48
vennStats	49

vennStats,Venn-method	50
[.Venn	51
\$.Venn	52

Index	53
--------------	-----------

VennDetail-package	<i>VennDetail: Comprehensive Visualization and Analysis of Multi-Set Intersections</i>
--------------------	--

Description

A comprehensive package for visualizing multi-set intersections and extracting detailed subset information. VennDetail generates high-resolution visualizations including traditional Venn diagrams, Venn-pie plots, and UpSet-style plots. It provides functions to extract and combine subset details with user datasets in various formats.

Details

The VennDetail package offers several powerful visualization and analysis tools:

Visualization methods:

- Traditional Venn diagram (for 2-5 sets)
- VennPie visualization (useful for more than 5 sets)
- UpSet plot (matrix-based visualization)
- Bar plot (simple visualization of subset sizes)

Key features:

- Extraction of elements in any subset combination
- Combining subset information with user-supplied data frames
- Statistical analysis of set intersections
- Enrichment analysis for set members
- Interactive visualizations
- High-resolution figure export
- Shiny app for interactive exploration

Getting Started

To create a Venn object for analysis:

```
““ # Create sample datasets A <- sample(1:100, 40, replace = FALSE) B <- sample(1:100, 60,
replace = FALSE) C <- sample(1:100, 40, replace = FALSE)
# Create a Venn object res <- venndetail(list(A = A, B = B, C = C)) ““
```

Visualization

```
““ # Traditional Venn diagram vennDiagram(res)
# VennPie visualization vennpie(res)
# UpSet plot upsetPlot(res)
# Bar plot dplot(res, order = TRUE)
# Generic plot function with type selection plot(res, type = "venn") ““
```

Data Extraction

```
““ # Extract elements shared by all sets shared <- getSet(res, "Shared")
# Extract elements unique to set A unique_to_A <- getSet(res, "A") ““
```

Statistical Analysis

```
““ # Test for significance of overlaps stats <- vennStats(res) ““
```

Author(s)

Kai Guo, Brett McGregor

See Also

Useful links:

- <https://github.com/guokai8/VennDetail>
- Report bugs at <https://github.com/guokai8/VennDetail/issues>

.add_colnames *Give first colname as RowNxyz*

Description

Give first colname as RowNxyz

Usage

```
.add_colnames(x)
```

Arguments

x data frame

Value

return data frame with the first colnames change to "RowNxyz"

.findOverlap *Find overlap between sets in a list*

Description

Find overlap between sets in a list

Usage

```
.findOverlap(setlist, xlim = c(0, 1), ylim = c(0, 1))
```

Arguments

setlist list of character vectors.
xlim vector with 2 numbers, x axis limits for the venn diagram.
ylim vector with 2 numbers, y axis limits for the venn diagram.

Value

list with 2 items: a data.frame with information about the groups (sizes, coordinates, etc.), and a data.frame containing the x and y coordinates for the venn diagram

.make.table *make table for venndetail modified from make.truth.table (VennDiagram)*

Description

make table for venndetail modified from make.truth.table (VennDiagram)

Usage

```
.make.table(x)
```

Arguments

x A list with input groups

Value

A data frame with logical vector columns and $2^{\text{length}(x)} - 1$ rows.

Author(s)

Kai Guo

 .vennDiagram

Create a standalone Venn diagram

Description

This function creates a standalone Venn diagram for 2-5 sets

Usage

```
.vennDiagram(
  setlist,
  title = NULL,
  colors = NULL,
  alpha = 0.4,
  showNumbers = TRUE,
  numberSize = 4,
  numberColor = "black",
  labelSize = 4,
  labelColor = "black",
  borderCol = FALSE,
  fillCol = TRUE,
  fixedCoords = TRUE,
  xlim = c(0, 1),
  ylim = c(0, 1)
)
```

Arguments

setlist	A named list of character vectors, each representing a set
title	Optional title for the plot
colors	Vector of colors for the sets. If NULL, default colors will be used
alpha	Transparency level for the circles (0-1)
showNumbers	Logical, whether to show counts and percentages in each region
numberSize	Size of the count labels
numberColor	Color of the count labels
labelSize	Size of the set labels
labelColor	Color of the set labels
borderCol	Logical, whether to color the borders of circles
fillCol	Logical, whether to fill circles with colors
fixedCoords	Logical, whether to use fixed coordinates
xlim	Vector with 2 numbers, x axis limits for the venn diagram
ylim	Vector with 2 numbers, y axis limits for the venn diagram

Value

A ggplot object

Author(s)

Kai Guo

as.data.frame.Venn *Utility functions for VennDetail package*

Description

Internal utility functions for the VennDetail package
Converts a Venn object to a data frame for easier manipulation

Usage

```
## S3 method for class 'Venn'  
as.data.frame(x, ...)
```

Arguments

x A Venn object
... Additional arguments (not used)

Value

A data frame with subset information

Author(s)

Kai Guo

Examples

```
# Create a Venn object  
A <- sample(1:100, 40, replace = FALSE)  
B <- sample(1:100, 60, replace = FALSE)  
res <- vennndetail(list(A = A, B = B))  
  
# Convert to data frame  
df <- as.data.frame(res)  
head(df)
```

compareVenn *Compare two Venn objects*

Description

Compares two Venn objects and returns a list of differences

Usage

```
compareVenn(x, y, what = c("groups", "subsets", "all"))
```

Arguments

x	First Venn object
y	Second Venn object
what	What to compare: "groups" (default), "subsets", or "all"

Value

A list with differences between the objects

Author(s)

Kai Guo

Examples

```
# Create two Venn objects
A1 <- sample(1:100, 40, replace = FALSE)
B1 <- sample(1:100, 60, replace = FALSE)
res1 <- venndetail(list(A = A1, B = B1))

A2 <- sample(1:100, 45, replace = FALSE)
B2 <- sample(1:100, 55, replace = FALSE)
res2 <- venndetail(list(A = A2, B = B2))

# Compare the objects
compareVenn(res1, res2)
```

create_interactive_vennpie

Create an interactive vennpie chart with plotly

Description

Creates a simple pie chart visualization for interactive exploration of set intersections

Usage

```
create_interactive_vennpie(  
  object,  
  subset = NULL,  
  any = NULL,  
  color = NULL,  
  revcolor = "lightgrey",  
  title = NULL  
)
```

Arguments

object	A Venn object
subset	Character vector of subset names to highlight
any	Highlight subsets shared by exactly this many sets
color	Optional vector of colors for the subsets
revcolor	Color for non-highlighted subsets
title	Optional plot title

Value

A plotly object

Author(s)

Kai Guo

detail

Get subset details from a Venn object

Description

Returns a named numeric vector with counts for each subset

The objective of this function is to summarize the overlaps across groups identified by `venndetail` without creating diagram.

Usage

```
detail(object)
```

```
## S4 method for signature 'Venn'  
detail(object)
```

Arguments

object	A Venn object
--------	---------------

Value

A named numeric vector with counts for each subset

Author(s)

Kai Guo

Examples

```

A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
res <- vennndetail(list(A = A, B = B, C = C))
detail(res)
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
res <- vennndetail(list(A = A, B = B, C = C))
detail(res)

```

dim.Venn	<i>Get dimensions of a Venn object</i>
----------	--

Description

Returns the dimensions of the result slot in a Venn object.

Usage

```

## S3 method for class 'Venn'
dim(x)

```

Arguments

x Venn object

Value

Integer vector of length 2 (rows, columns)

dplot	<i>Create a bar plot of subset counts</i>
-------	---

Description

Creates a bar plot showing counts for each subset

Usage

```

dplot(
  object,
  order = FALSE,
  textsize = 5,
  color = NULL,
  theme = ggplot2::theme_light(),
  title = NULL,
  xlabel = NULL,
  ylabel = NULL
)

```

```
)

## S4 method for signature 'Venn'
dplot(object, order = FALSE, textsize = 5)
```

Arguments

object	Venn object
order	Boolean indicating whether to sort the bar (default: FALSE).
textsize	Numeric vector giving the text size above the bar.
color	Optional vector of colors for the bars
theme	The ggplot2 theme to use. Default: theme_light
title	Optional plot title
xlabel	Optional x-axis label
ylabel	Optional y-axis label

Value

A ggplot2 object

Author(s)

Kai Guo

Examples

```
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
res <- vennetail(list(A = A, B = B, C = C))
dplot(res, order = TRUE, textsize = 3)
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
res <- vennetail(list(A = A, B = B, C = C))
dplot(res, order = TRUE, textsize = 3)
```

getFeature

Extract feature data for specific subsets

Description

Combines subset information with user-supplied data frames

GetFeature allows users to extract subsets from venn object into a table format along with accompanying information from the data frames provided in the rlist argument

Usage

```

getFeature(
  object,
  subset,
  rlist,
  userowname = TRUE,
  gind = NULL,
  sep = "_",
  wide = FALSE
)

## S4 method for signature 'Venn'
getFeature(
  object,
  subset,
  rlist,
  userowname = TRUE,
  gind = NULL,
  sep = "_",
  wide = FALSE
)

```

Arguments

object	Venn object
subset	Character vector giving the names of the user-defined subset to extract
rlist	List of user-supplied data frames to combine with <code>venndetail</code> result
userowname	Boolean indicating whether to use row names to join data frames or not (default: TRUE)
gind	Column name or index of each user-supplied data.frame to use to join data frames(valid only when <code>userowname=FALSE</code>)
sep	Character string used to separate the terms when concatenating group names into new separation character for new column names in the resulting data frame
wide	Boolean indicating whether to use wide format(default:FALSE)

Value

A data.frame combining subset information with user data
 data.frame with subsets information and details from the user supplied data frame

Author(s)

Kai Guo

Examples

```

A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
dA <- data.frame(A = A, "FC" = rnorm(40))
dB <- data.frame(B = B, "FC" = rnorm(60))

```

```

dC <- data.frame(C = C, "FC" = rnorm(40))
res <- vennDetail(list(A = A, B = B, C = C))
features <- getFeature(res, subset = "Shared",
                      rlist = list(dA, dB, dC),
                      userowname = FALSE,
                      gind = rep(1, 3))
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
dA <- data.frame(A = A, "FC" = rnorm(40))
dB <- data.frame(B = B, "FC" = rnorm(60))
dC <- data.frame(C = C, "FC" = rnorm(40))
res <- vennDetail(list(A = A, B = B, C = C))
rhs <- getFeature(res, subset = "Shared", rlist = list(dA, dB, dC),
                 userowname= FALSE, gind = rep(1, 3))

```

getSet

Extract specific subsets from a Venn object

Description

Extracts elements from specified subsets

getSet function provides a way to extract subsets from vennDetail object

Usage

```
getSet(object, subset = NULL, min = 0, wide = FALSE)
```

```
## S4 method for signature 'Venn'
```

```
getSet(object, subset = NULL, min = 0, wide = FALSE)
```

Arguments

object	Venn object
subset	Character vector giving the subset names
min	The minimum number of input groups that a subset must belong to e.g. min = 2 will only report those subsets with elements shared by 2 or more input groups.
wide	Boolean indicating return wide format (default: FALSE).

Value

A data.frame with elements from the specified subsets

Specific subset information

Author(s)

Kai Guo

Examples

```

A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
res <- vennndetail(list(A = A, B = B, C = C))
# Get elements unique to set A
unique_to_A <- getSet(res, "A")
# Get elements shared by all sets
shared <- getSet(res, "Shared")
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
res <- vennndetail(list(A = A, B = B, C = C))
getSet(res, "A")

```

head.Venn

Return the first or last parts of a Venn object

Description

Methods to extract the first or last parts of a Venn object's result slot.

Usage

```
## S3 method for class 'Venn'
head(x, n = 6L, ...)
```

```
## S3 method for class 'Venn'
tail(x, n = 6L, ...)
```

Arguments

x	Venn object
n	number of rows to display
...	other arguments ignored (for compatibility with generic)

Value

A data.frame with the first n rows

A data.frame with the last n rows

loadVenn	<i>Load a Venn object from a file</i>
----------	---------------------------------------

Description

Loads a Venn object from an RDS file

Usage

```
loadVenn(file)
```

Arguments

file	File name to load from
------	------------------------

Value

A Venn object

Author(s)

Kai Guo

Examples

```
## Not run:  
# Load a saved Venn object  
res <- loadVenn("my_venn.rds")  
  
# Plot the loaded object  
plot(res)  
  
## End(Not run)
```

make.subset	<i>Get subset from list of input groups</i>
-------------	---

Description

Get subset from list of input groups

Usage

```
make.subset(x, sep = "_")
```

Arguments

x	A list with input groups
sep	symbol character used when concatenating group names into subset names

Value

A list of subsets. The names on the list are the subset names and the list elements are the subset details.

Author(s)

Kai Guo

Examples

```
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
x <- list(A = A, B = B, C = C)
out <- make_subset(x)
```

makeContent.upset_grob

Draw method for upset_grob objects

Description

Internal method to draw upset_grob using grid viewports

Usage

```
## S3 method for class 'upset_grob'
makeContent(x)
```

Arguments

x An upset_grob object

Value

Draws the upset plot

make_subset

Create subsets from a list of sets

Description

Identifies all possible intersections between sets and returns a list of subsets

Usage

```
make_subset(x, sep = "_")
```

Arguments

x A list of vectors
sep Character used to separate set names in subset labels

Value

A named list where each element contains the unique items in that subset

Author(s)

Kai Guo

Examples

```
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
x <- list(A = A, B = B, C = C)
subsets <- make_subset(x)
lengths(subsets) # Number of elements in each subset
```

make_truth_table *Create a truth table for set combinations*

Description

Creates a logical matrix representing all possible combinations of sets

Usage

```
make_truth_table(x)
```

Arguments

x A list of vectors

Value

A data frame with logical columns for each set and rows for each combination

Author(s)

Kai Guo

merge.Venn	<i>Merge two or more venndetail obejcts</i>
------------	---

Description

Merge will combine multiple venn diagrams to allow comparison between multiple groups

Usage

```
## S3 method for class 'Venn'
merge(x, y, ignore.case = FALSE, useupper = TRUE, plot = FALSE, ...)
```

Arguments

x	Venn object
y	Venn object
ignore.case	Boolean indicating whether to ignore case of group names (default: FALSE)
useupper	Boolean indicating whether to use uppercases for group names (default: TRUE)
plot	Boolean indicating whether to plot figure or not (default: FALSE)
...	arguments for venndetail

Value

venn object

Examples

```
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
res1 <- venndetail(list(A = A, B = B))
res2 <- venndetail(list(A = A, C = C))
res <- merge(res1, res2)
```

names.Venn	<i>Extract subset names from a Venn object</i>
------------	--

Description

Returns the names of all subsets in a Venn object

Usage

```
## S3 method for class 'Venn'
names(x)
```

Arguments

x	A Venn object
---	---------------

Value

A character vector of subset names

Author(s)

Kai Guo

Examples

```
# Create a Venn object
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
res <- venndetail(list(A = A, B = B))

# Get subset names
names(res)
```

newVenn

Create a new Venn object

Description

Constructor function for creating Venn objects with validation

Usage

```
newVenn(
  input,
  raw,
  sep = "_",
  GroupNames,
  result,
  detail,
  wide,
  metadata = list()
)
```

Arguments

input	A list of input sets
raw	A named vector with counts
sep	The separator character
GroupNames	Names of the input groups
result	The result data.frame
detail	The detail vector
wide	The wide-format data.frame
metadata	Additional metadata (optional)

Value

A new Venn object

Author(s)

Kai Guo

Examples

```
## Not run:
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
raw <- c(A = 40, B = 60)
groups <- c("A", "B")
# Create a new Venn object manually (normally done by venndetail function)
venn_obj <- newVenn(input = list(A = A, B = B), raw = raw,
                   GroupNames = groups, ...)

## End(Not run)
```

plot.Venn

Plot a Venn object

Description

Unified plotting function for Venn objects that supports multiple visualization types

Usage

```
## S3 method for class 'Venn'
plot(
  x,
  type = "venn",
  title = NULL,
  interactive = FALSE,
  filename = NULL,
  width = 8,
  height = 6,
  dpi = 300,
  fill = NULL,
  alpha = 0.5,
  labels = TRUE,
  counts = TRUE,
  showNumbers = TRUE,
  numberSize = 4,
  numberColor = "black",
  labelSize = 4,
  labelColor = "black",
  borderCol = FALSE,
  fillCol = TRUE,
  fixedCoords = TRUE,
  xlim = c(0, 1),
```

```
ylim = c(0, 1),
show_percentages = TRUE,
show_unique_only = FALSE,
scaled = FALSE,
subset = NULL,
top = 31,
min = 0,
color = NULL,
revcolor = "lightgrey",
any = NULL,
show.number = TRUE,
show.x = TRUE,
sep = "_",
log = FALSE,
base = NULL,
percentage = FALSE,
nintersects = 40,
min_size = 1,
sets_bar_color = NULL,
main_bar_color = "steelblue",
point_size = 3,
line_size = 1,
show_numbers = TRUE,
sort_intersections_by = "freq",
sort_sets_by = "size",
sort_sets_decreasing = TRUE,
custom_sets_order = NULL,
sort_intersections_decreasing = TRUE,
custom_intersections_order = NULL,
intersection_color = "black",
highlight_intersections = NULL,
highlight_color = "darkorange",
empty_point_size = 1.5,
bar_width = 0.7,
text_angle = 0,
text_size = 10,
set_label_size = 3,
intersection_label_size = 3,
point_outline_color = "black",
point_stroke = 0.3,
set_size_show_values = TRUE,
intersection_size_show_values = TRUE,
show_empty_intersections = FALSE,
show_set_labels = TRUE,
plot_margin = 0.5,
height_ratio = 0.7,
width_ratio = 0.3,
bar_offset = -0.01,
set_text_size = 10,
intersection_title = "Intersection Size",
set_size_title = "Set Size",
matrix_point_shape = 21,
```

```

number_color_threshold = 0.75,
number_colors = c(on_bar = "black", off_bar = "black"),
theme_params = list(background_color = "white", grid_color = "grey92", axis_text_color
  = "black", use_grid = TRUE, border_color = NA),
return_data = FALSE,
order = FALSE,
textsize = 5,
theme = ggplot2::theme_light(),
xlabel = NULL,
ylabel = NULL,
...
)

```

Arguments

x	A Venn object
type	Type of plot: "venn" (traditional Venn diagram), "vennpie" (pie-chart style), "upset" (UpSet plot), or "bar" (bar plot of subset sizes)
title	Optional plot title
interactive	Logical: create an interactive plot? Default: FALSE
filename	Optional file name to save the plot
width	Width of the saved plot (default: 8)
height	Height of the saved plot (default: 6)
dpi	Resolution in dots per inch (default: 300)
fill	Colors for filling the circles (venn)
alpha	Transparency level (0-1), default: 0.5 (venn)
labels	Logical: show set labels? Default: TRUE (venn)
counts	Logical: show counts? Default: TRUE (venn)
showNumbers	Logical: show counts and percentages? Default: TRUE (venn)
numberSize	Size of count labels, default: 4 (venn)
numberColor	Color of count labels, default: "black" (venn)
labelSize	Size of set labels, default: 4 (venn)
labelColor	Color of set labels, default: "black" (venn)
borderCol	Logical: color borders? Default: FALSE (venn)
fillCol	Logical: fill circles? Default: TRUE (venn)
fixedCoords	Logical: fixed coordinates? Default: TRUE (venn)
xlim	X axis limits, default: c(0, 1) (venn)
ylim	Y axis limits, default: c(0, 1) (venn)
show_percentages	Logical: show percentages? Default: TRUE (venn)
show_unique_only	Logical: show unique only? Default: FALSE (venn)
scaled	Logical: scale circles? Default: FALSE (venn)
subset	Character vector of subsets to highlight (vennpie)
top	Maximum subsets to display, default: 31 (vennpie)

min	Minimum set membership, default: 0 (vennpie/getSet)
color	Colors for subsets (vennpie/bar)
revcolor	Color for non-highlighted, default: "lightgrey" (vennpie)
any	Highlight subsets shared by this many sets (vennpie)
show.number	Logical: show counts? Default: TRUE (vennpie)
show.x	Logical: show labels? Default: TRUE (vennpie)
sep	Character separator, default: "_" (vennpie)
log	Logical: use log scale? Default: FALSE (vennpie)
base	Base for log transformation (vennpie)
percentage	Logical: show percentages? Default: FALSE (vennpie)
nintersects	Maximum intersections, default: 40 (upset)
min_size	Minimum intersection size, default: 1 (upset)
sets_bar_color	Colors for set size bars (upset)
main_bar_color	Color for intersection bars, default: "steelblue" (upset)
point_size	Size of matrix points, default: 3 (upset)
line_size	Width of matrix lines, default: 1 (upset)
show_numbers	Logical: show bar counts? Default: TRUE (upset)
sort_intersections_by	Sort method: "freq", "degree", or "custom" (upset)
sort_sets_by	Sort method: "size", "name", or "custom" (upset)
sort_sets_decreasing	Logical: decreasing order? Default: TRUE (upset)
custom_sets_order	Custom set order (upset)
sort_intersections_decreasing	Logical: decreasing? Default: TRUE (upset)
custom_intersections_order	Custom intersection order (upset)
intersection_color	Color for dots/lines, default: "black" (upset)
highlight_intersections	IDs to highlight (upset)
highlight_color	Highlight color, default: "darkorange" (upset)
empty_point_size	Empty point size, default: 1.5 (upset)
bar_width	Bar width (0-1), default: 0.7 (upset)
text_angle	Text angle, default: 0 (upset)
text_size	Text size, default: 10 (upset)
set_label_size	Set label size, default: 3 (upset)
intersection_label_size	Intersection label size, default: 3 (upset)
point_outline_color	Point outline color, default: "black" (upset)

```

point_stroke    Point outline width, default: 0.3 (upset)
set_size_show_values
                Show set values? Default: TRUE (upset)
intersection_size_show_values
                Show intersection values? Default: TRUE (upset)
show_empty_intersections
                Show empty? Default: FALSE (upset)
show_set_labels
                Show set labels? Default: TRUE (upset)
plot_margin    Margin in cm, default: 0.5 (upset)
height_ratio   Matrix height ratio, default: 0.7 (upset)
width_ratio    Set size width ratio, default: 0.3 (upset)
bar_offset     Bar offset, default: -0.01 (upset)
set_text_size  Set label size, default: 10 (upset)
intersection_title
                Intersection title (upset)
set_size_title Set size title (upset)
matrix_point_shape
                Point shape, default: 21 (upset)
number_color_threshold
                Color threshold, default: 0.75 (upset)
number_colors  Label colors vector (upset)
theme_params   Theme parameters list (upset)
return_data    Return data? Default: FALSE (upset)
order          Logical: order bars? Default: FALSE (bar)
textsize       Text size, default: 5 (bar)
theme          ggplot2 theme (bar)
xlabel         X-axis label (bar)
ylabel         Y-axis label (bar)
...           Additional arguments passed to the specific plotting function

```

Value

A ggplot2 or plotly object

Author(s)

Kai Guo

Examples

```

# Create a Venn object
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
res <- vennndetail(list(A = A, B = B, C = C))

# Traditional Venn diagram

```

```

plot(res, type = "venn")

# Venn diagram with custom colors and transparency
plot(res, type = "venn", fill = c("red", "blue", "green"), alpha = 0.3)

# Venn-pie visualization
plot(res, type = "vennpie")

# Venn-pie with highlighted subsets
plot(res, type = "vennpie", any = 2, log = TRUE)

# UpSet plot
plot(res, type = "upset")

# UpSet plot with custom sorting and highlighting
plot(res, type = "upset",
      sort_sets_by = "size",
      highlight_intersections = c(1, 2),
      highlight_color = "red")

# Bar plot of subset sizes
plot(res, type = "bar")

# Ordered bar plot with larger text
plot(res, type = "bar", order = TRUE, textsize = 8)

# Save plot to file (not run during check)
## Not run:
plot(res, type = "venn", filename = "my_venn.png", width = 10, height = 8)

## End(Not run)

# Create interactive plot
if(interactive()) {
  plot(res, type = "venn", interactive = TRUE)
}

```

```
print.upset_grob      Print method for upset_grob objects
```

Description

Print method for upset_grob objects

Usage

```
## S3 method for class 'upset_grob'
print(x, ...)
```

Arguments

x	An upset_grob object
...	Additional arguments (ignored)

Value

Invisibly returns the input object

result	<i>Extract results from a Venn object</i>
--------	---

Description

Retrieves results from a Venn object in long or wide format

Result will return output in a table format including the contents of the subsets included in the `venndetail` object

Usage

```
result(object, wide = FALSE)

## S4 method for signature 'Venn'
result(object, wide = FALSE)
```

Arguments

object	A Venn object
wide	Logical: should results be returned in wide format? Default: FALSE

Value

A `data.frame` containing subset information

Author(s)

Kai Guo

Examples

```
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
res <- venndetail(list(A = A, B = B, C = C))
# Get results in long format
result_long <- result(res)
# Get results in wide format
result_wide <- result(res, wide = TRUE)
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
res <- venndetail(list(A = A, B = B, C = C))
result <- result(res)
```

rowjoin	<i>Join data.frames by row names or specified columns</i>
---------	---

Description

Joins two data.frames using various join methods
join two dataframes by rownames

Usage

```
rowjoin(x, y, fun = "full_join", by = NULL)

## S4 method for signature 'data.frame,data.frame'
rowjoin(x, y, fun = "full_join")
```

Arguments

x	data.frame x
y	data.frame y
fun	Different join format: left_join, full_join, right_join (default:full_join)
by	Optional vector of column names to join by

Value

A joined data.frame
dataframe with join results

Author(s)

Kai Guo

Examples

```
library(dplyr)
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
dA <- data.frame(A = A, "FC" = rnorm(40))
dB <- data.frame(B = B, "FC" = rnorm(60))
rownames(dA) <- A
rownames(dB) <- B
# Full join by row names
result <- rowjoin(dA, dB)
# Left join by row names
result <- rowjoin(dA, dB, fun = "left_join")
library(dplyr)
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
dA <- data.frame(A = A, "FC" = rnorm(40))
dB <- data.frame(B = B, "FC" = rnorm(60))
rownames(dA) <- A
rownames(dB) <- B
rowjoin(dA, dB)
```

saveVenn	<i>Save a Venn object to a file</i>
----------	-------------------------------------

Description

Saves a Venn object to an RDS file for later use

Usage

```
saveVenn(object, file)
```

Arguments

object	A Venn object
file	File name to save to

Value

The file name (invisibly)

Author(s)

Kai Guo

Examples

```
## Not run:  
# Create a Venn object  
A <- sample(1:100, 40, replace = FALSE)  
B <- sample(1:100, 60, replace = FALSE)  
res <- vennDetail(list(A = A, B = B))  
  
# Save to a file  
saveVenn(res, "my_venn.rds")  
  
## End(Not run)
```

setcolor	<i>return colors with given a vector</i>
----------	--

Description

Setcolor will provide a list of color vectors based on the number used as an input.

Usage

```
setcolor(n, palette = "default")
```

Arguments

n Number of colors needed
palette Type of palette: "default", "categorical", "sequential", or "diverging"

Value

color vector

Author(s)

Kai Guo

Examples

```
mycol <- setcolor(10)
mycol
```

show Venn

Show the summary of venn object

Description

This function provides a summary of the venn object, including a full results and subsets as well as an summary information.

Usage

```
## S4 method for signature 'Venn'
show(object)
```

Arguments

object venn object

Value

summary information for the venn object

Author(s)

Kai Guo

Examples

```
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
res <- vennetail(list(A = A, B = B, C = C))
show(res)
```

summary.Venn	<i>Give summary information of Venn object</i>
--------------	--

Description

print the summary information of Venn object

Usage

```
## S3 method for class 'Venn'
summary(object, ...)
```

Arguments

object	Venn object
...	other arguments ignored (for compatibility with generic)

Value

summary information

Examples

```
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
res <- vennDetail(list(A = A, B = B, C = C))
summary(res)
```

T2DM

T2DM Dataset

Description

T2DM data are differential expression genes (DEGs) with annotation from the publication by Hinder et al.

T2DM data are differential expression genes (DEGs) with annotation from the publication by Hinder et al. The data contains three DEG sets from three different tissues (Cortex,SCN,Glom). DEGs were determined by using Cuffdiff with a false discovery rate (FDR) < 0.05 between groups with or without pioglitazone treatment.

Usage

T2DM

T2DM

Format

A list of data frames with five columns each

A list of data frame with five columns individually:

Entrez Entrez gene IDs

Symbol HGNC symbols

Annotation Gene function

log2FC log2 Fold Change

FDR False Discovery Rate

Examples

T2DM

upsetPlot

Create an UpSet plot

Description

Creates an UpSet plot to visualize set intersections

Usage

```
upsetPlot(  
  object,  
  nintersects = 40,  
  min_size = 1,  
  sets_bar_color = NULL,  
  main_bar_color = "steelblue",  
  point_size = 3,  
  line_size = 1,  
  show_numbers = TRUE,  
  sort_intersections_by = "freq",  
  sort_sets_by = "size",  
  sort_sets_decreasing = TRUE,  
  custom_sets_order = NULL,  
  sort_intersections_decreasing = TRUE,  
  custom_intersections_order = NULL,  
  intersection_color = "black",  
  highlight_intersections = NULL,  
  highlight_color = "darkorange",  
  empty_point_size = 1.5,  
  bar_width = 0.7,  
  text_angle = 0,  
  text_size = 10,  
  set_label_size = 3,  
  intersection_label_size = 3,  
  point_outline_color = "black",  
  point_stroke = 0.3,  
)
```

```

set_size_show_values = TRUE,
intersection_size_show_values = TRUE,
show_empty_intersections = FALSE,
show_set_labels = TRUE,
plot_margin = 0.5,
height_ratio = 0.7,
width_ratio = 0.3,
bar_offset = -0.01,
set_text_size = 10,
intersection_title = "Intersection Size",
set_size_title = "Set Size",
matrix_point_shape = 21,
number_color_threshold = 0.75,
number_colors = c(on_bar = "black", off_bar = "black"),
theme_params = list(background_color = "white", grid_color = "grey92", axis_text_color
  = "black", use_grid = TRUE, border_color = NA),
title = NULL,
interactive = FALSE,
return_data = FALSE,
...
)

```

Arguments

object	A Venn object
nintersects	Maximum number of intersections to show
min_size	Minimum intersection size to include (default: 1)
sets_bar_color	Colors for the set size bars
main_bar_color	Color for the intersection size bars
point_size	Size of points in the matrix
line_size	Width of lines in the matrix
show_numbers	Logical: show counts on bars?
sort_intersections_by	How to sort intersections
sort_sets_by	How to sort sets
sort_sets_decreasing	Whether to sort sets in decreasing order
custom_sets_order	Custom order for sets if sort_sets_by="custom"
sort_intersections_decreasing	Whether to sort intersections in decreasing order
custom_intersections_order	Custom order for intersections
intersection_color	Color for intersection dots and lines
highlight_intersections	Vector of intersection IDs to highlight
highlight_color	Color for highlighted intersections

empty_point_size	Size of empty points in the matrix
bar_width	Width of bars
text_angle	Angle for text labels
text_size	Size of text in the plot
set_label_size	Size of set size labels
intersection_label_size	Size of intersection size labels
point_outline_color	Color for the outline of points
point_stroke	Width of point outline
set_size_show_values	Whether to show set size values
intersection_size_show_values	Whether to show intersection size values
show_empty_intersections	Whether to show empty intersections
show_set_labels	Whether to show set labels
plot_margin	Margin around the plots in cm
height_ratio	Ratio of matrix to total height
width_ratio	Ratio of set size to total width
bar_offset	Horizontal offset for top bars
set_text_size	Size of set labels
intersection_title	Title for the intersection size plot
set_size_title	Title for the set size plot
matrix_point_shape	Shape of the dots in the matrix
number_color_threshold	Fraction of max value for label color switch
number_colors	Colors for labels on/off bars
theme_params	Theme parameters for customization
title	Optional plot title
interactive	Create interactive plot?
return_data	Whether to return the data along with the plot
...	Additional arguments passed to internal functions

Value

A ggplot object or a combined grid layout

Author(s)

Kai Guo

Examples

```
# Basic example
sets <- list(
  "Set A" = c(1:100),
  "Set B" = c(30:120),
  "Set C" = c(20:50, 90:110),
  "Set D" = c(10:40, 80:120)
)
ven <- venndetail(sets)
upsetPlot(ven, bar_offset = -0.02)

# With highlighting
upsetPlot(ven,
  highlight_intersections = c(1, 2),
  highlight_color = "darkorange",
  bar_offset = -0.02)
```

upsetPlot, Venn-method *Create an UpSet plot for a Venn object*

Description

Creates an UpSet plot to visualize set intersections

Usage

```
## S4 method for signature 'Venn'
upsetPlot(
  object,
  nintersects = 40,
  min_size = 1,
  sets_bar_color = NULL,
  main_bar_color = "steelblue",
  point_size = 3,
  line_size = 1,
  show_numbers = TRUE,
  sort_intersections_by = "freq",
  sort_sets_by = "size",
  sort_sets_decreasing = TRUE,
  custom_sets_order = NULL,
  sort_intersections_decreasing = TRUE,
  custom_intersections_order = NULL,
  intersection_color = "black",
  highlight_intersections = NULL,
  highlight_color = "darkorange",
  empty_point_size = 1.5,
  bar_width = 0.7,
  text_angle = 0,
  text_size = 10,
  set_label_size = 3,
  intersection_label_size = 3,
```

```

point_outline_color = "black",
point_stroke = 0.3,
set_size_show_values = TRUE,
intersection_size_show_values = TRUE,
show_empty_intersections = FALSE,
show_set_labels = TRUE,
plot_margin = 0.5,
height_ratio = 0.7,
width_ratio = 0.3,
bar_offset = -0.01,
set_text_size = 10,
intersection_title = "Intersection Size",
set_size_title = "Set Size",
matrix_point_shape = 21,
number_color_threshold = 0.75,
number_colors = c(on_bar = "black", off_bar = "black"),
theme_params = list(background_color = "white", grid_color = "grey92", axis_text_color
  = "black", use_grid = TRUE, border_color = NA),
title = NULL,
interactive = FALSE,
return_data = FALSE
)

```

Arguments

object	A Venn object
nintersects	Maximum number of intersections to show (default: 40)
min_size	Minimum intersection size to include (default: 1)
sets_bar_color	Colors for the set size bars (default: NULL for auto-generate)
main_bar_color	Color for the intersection size bars (default: "steelblue")
point_size	Size of points in the matrix (default: 3)
line_size	Width of lines in the matrix (default: 1)
show_numbers	Logical: show counts on bars? (default: TRUE)
sort_intersections_by	How to sort intersections: "freq" (default), "degree"
sort_sets_by	How to sort sets: "size" (default), "name"
sort_sets_decreasing	Whether to sort sets in decreasing order (default: TRUE)
custom_sets_order	Custom order for sets if sort_sets_by="custom"
sort_intersections_decreasing	Whether to sort intersections in decreasing order (default: TRUE)
custom_intersections_order	Custom order for intersections if sort_intersections_by="custom"
intersection_color	Color for intersection dots and lines (default: "black")
highlight_intersections	Vector of intersection IDs to highlight (default: NULL)

highlight_color	Color for highlighted intersections (default: "darkorange")
empty_point_size	Size of empty points in the matrix (default: 1.5)
bar_width	Width of bars (0-1 scale) (default: 0.7)
text_angle	Angle for text labels (default: 0)
text_size	Size of text in the plot (default: 10)
set_label_size	Size of set size labels (default: 3)
intersection_label_size	Size of intersection size labels (default: 3)
point_outline_color	Color for the outline of points (default: "black")
point_stroke	Width of point outline (default: 0.3)
set_size_show_values	Whether to show set size values (default: TRUE)
intersection_size_show_values	Whether to show intersection size values (default: TRUE)
show_empty_intersections	Whether to show empty intersections (default: FALSE)
show_set_labels	Whether to show set labels (default: TRUE)
plot_margin	Margin around the plots in cm (default: 0.5)
height_ratio	Ratio of matrix to total height (default: 0.7)
width_ratio	Ratio of set size to total width (default: 0.3)
bar_offset	Horizontal offset for top bars to improve alignment (default: 0)
set_text_size	Size of set labels (default: 10)
intersection_title	Title for the intersection size plot (default: "Intersection Size")
set_size_title	Title for the set size plot (default: "Set Size")
matrix_point_shape	Shape of the dots in the matrix (21=filled circle) (default: 21)
number_color_threshold	Fraction of max value where number color switches (default: 0.75)
number_colors	Named vector with colors for labels on/off bars (default: c(on_bar="white", off_bar="black"))
theme_params	List of theme parameters for customization (default: list of defaults)
title	Optional plot title
interactive	Logical: create interactive plot? (default: FALSE)
return_data	Whether to return the data along with the plot (default: FALSE)

Value

A ggplot object or a combined grid layout

Author(s)

Kai Guo

Examples

```
# Basic example
sets <- list(
  "Set A" = c(1:100),
  "Set B" = c(30:120),
  "Set C" = c(20:50, 90:110),
  "Set D" = c(10:40, 80:120)
)
ven <- venndetail(sets)
upsetPlot(ven, bar_offset = -0.02)

# With highlighting
upsetPlot(ven,
  highlight_intersections = c(1, 2),
  highlight_color = "darkorange",
  bar_offset = -0.02)
```

upset_plot

Create an UpSet plot for set intersection visualization

Description

Creates a custom UpSet plot showing the intersections between sets. It displays the size of each intersection and the sets involved in each intersection.

Usage

```
upset_plot(
  data_list,
  sets = NULL,
  min_intersection_size = 1,
  max_sets_display = NULL,
  sort_sets_by = "size",
  sort_sets_decreasing = TRUE,
  custom_sets_order = NULL,
  sort_intersections_by = "freq",
  sort_intersections_decreasing = TRUE,
  custom_intersections_order = NULL,
  intersection_color = "black",
  main_bar_color = "steelblue",
  sets_bar_colors = NULL,
  highlight_intersections = NULL,
  highlight_color = "darkorange",
  point_outline_color = "black",
  filled_point_size = 2,
  empty_point_size = 1.5,
  line_size = 0.5,
  bar_width = 0.6,
  point_stroke = 0.3,
  text_angle = 0,
  text_size = 10,
```

```

set_text_size = 10,
set_label_size = 3,
intersection_label_size = 3,
intersection_title = "Intersection Size",
set_size_title = "Set Size",
matrix_point_shape = 21,
set_size_show_values = TRUE,
intersection_size_show_values = TRUE,
show_empty_intersections = FALSE,
show_set_labels = TRUE,
show_numbers_on_bars = TRUE,
number_color_threshold = 0.75,
number_colors = c(on_bar = "black", off_bar = "black"),
plot_margin = 0.5,
height_ratio = 0.5,
width_ratio = 0.3,
bar_offset = -0.01,
theme_params = list(background_color = "white", grid_color = "grey92", axis_text_color
  = "black", use_grid = TRUE, border_color = NA),
return_data = FALSE
)

```

Arguments

<code>data_list</code>	A named list of vectors, each containing elements in a set
<code>sets</code>	Optional vector of set names to include (default: all sets in <code>data_list</code>)
<code>min_intersection_size</code>	Minimum intersection size to include (default: 1)
<code>max_sets_display</code>	Maximum number of sets to display (default: all)
<code>sort_sets_by</code>	How to sort the sets: "size", "name", or "custom" (default: "size")
<code>sort_sets_decreasing</code>	Whether to sort sets in decreasing order (default: TRUE)
<code>custom_sets_order</code>	Custom order for sets if <code>sort_sets_by="custom"</code>
<code>sort_intersections_by</code>	How to sort intersections: "freq", "degree", or "custom" (default: "freq")
<code>sort_intersections_decreasing</code>	Whether to sort intersections in decreasing order (default: TRUE)
<code>custom_intersections_order</code>	Custom order for intersections if <code>sort_intersections_by="custom"</code>
<code>intersection_color</code>	Color for intersection dots and lines (default: "black")
<code>main_bar_color</code>	Color for the intersection size bars (default: "steelblue")
<code>sets_bar_colors</code>	Named vector of colors for each set (default: auto-generated)
<code>highlight_intersections</code>	Vector of intersection IDs to highlight (default: NULL)
<code>highlight_color</code>	Color for highlighted intersections (default: "#FF5500")

point_outline_color	Color for the outline of points (default: "black")
filled_point_size	Size of filled points in the matrix (default: 2)
empty_point_size	Size of empty points in the matrix (default: 1.5)
line_size	Width of connecting lines (default: 0.5)
bar_width	Width of bars (0-1 scale) (default: 0.7)
point_stroke	Width of point outline (default: 0.3)
text_angle	Angle for text labels (default: 0)
text_size	Size of text in the plot (default: 10)
set_text_size	Size of set labels (default: 10)
set_label_size	Size of set size labels (default: 3)
intersection_label_size	Size of intersection size labels (default: 3)
intersection_title	Title for the intersection size plot (default: "Intersection Size")
set_size_title	Title for the set size plot (default: "Set Size")
matrix_point_shape	Shape of the dots in the matrix (21=filled circle) (default: 21)
set_size_show_values	Whether to show set size values (default: TRUE)
intersection_size_show_values	Whether to show intersection size values (default: TRUE)
show_empty_intersections	Whether to show empty intersections (default: FALSE)
show_set_labels	Whether to show set labels (default: TRUE)
show_numbers_on_bars	Logical, whether to display counts on bars (default: TRUE)
number_color_threshold	Fraction of max value where number color switches (default: 0.75)
number_colors	Named vector with colors for labels on/off bars (default: c(on_bar="white", off_bar="black"))
plot_margin	Margin around the plots in cm (default: 0.5)
height_ratio	Ratio of matrix to total height (default: 0.7)
width_ratio	Ratio of set size to total width (default: 0.3)
bar_offset	Horizontal offset for top bars to improve alignment (default: 0)
theme_params	List of theme parameters for customization (default: list of defaults)
return_data	Whether to return the data along with the plot (default: FALSE)

Value

If `return_data=FALSE`, returns the patchwork plot object. If `return_data=TRUE`, returns a list containing the plot and component data.

Author(s)

Kai Guo

Examples

```

# Basic example
sets <- list(
  "Set A" = c(1:100),
  "Set B" = c(30:120),
  "Set C" = c(20:50, 90:110),
  "Set D" = c(10:40, 80:120)
)
upset_plot(sets)

# With highlighting
upset_plot(sets,
  highlight_intersections = c(1, 2),
  highlight_color = "darkorange",
  bar_offset = -0.02)

# Custom colors
set_colors <- c("Set A" = "blue", "Set B" = "green",
  "Set C" = "orange", "Set D" = "purple")
upset_plot(sets, sets_bar_colors = set_colors,
  main_bar_color = "darkblue")

```

Venn-class

Venn Class

Description

S4 class to store and manage set intersection data and visualizations

Slots

input A list containing the original input datasets

raw A named vector with counts of elements in each input set

sep The character used to separate set names in subset labels

GroupNames A character vector of input group names

result A data.frame containing subset information (subset name and elements)

detail A named vector with counts of elements in each subset

wide A data.frame with subset information in wide format for easier analysis

metadata A list to store additional metadata about the analysis

Author(s)

Kai Guo

Examples

```
## Not run:
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
venn_obj <- venn_detail(list(A = A, B = B, C = C))
# Access the detail slot
venn_obj@detail

## End(Not run)
```

vennApp

Create an interactive Venn diagram app

Description

Creates a Shiny app for interactive exploration of Venn diagrams

Usage

```
vennApp(object, launch = TRUE, ...)
```

Arguments

object	A Venn object
launch	Launch the app immediately? Default: TRUE
...	Additional arguments passed to shiny::runApp

Value

A Shiny app object (invisibly)

Author(s)

Kai Guo

Examples

```
## Not run:
# Create a Venn object
A <- sample(1:100, 40, replace = FALSE)
B <- sample(1:100, 60, replace = FALSE)
C <- sample(1:100, 40, replace = FALSE)
res <- venn_detail(list(A = A, B = B, C = C))

# Launch interactive app
vennApp(res)

## End(Not run)
```

`venndetail`*Create a Venn object for set analysis*

Description

Extracts shared and unique elements from multiple sets and creates a Venn object for analysis and visualization

Usage

```
venndetail(  
  x,  
  sep = "_",  
  abbr = FALSE,  
  minlength = 3,  
  abbr.method = "both.sides",  
  verbose = FALSE  
)
```

Arguments

<code>x</code>	A list of vectors with group names
<code>sep</code>	Symbol character used when concatenating group names into subset names (default: `_'`)
<code>abbr</code>	Logical: abbreviate subset names? Default: FALSE
<code>minlength</code>	Minimal length for abbreviated subset names. Default: 3
<code>abbr.method</code>	Method for abbreviation: "both.sides", "left.sides", or "right.sides"
<code>verbose</code>	Logical: show progress messages? Default: FALSE

Value

A Venn object

Author(s)

Kai Guo

Examples

```
# Create a Venn object with three sets  
A <- sample(1:100, 40, replace = FALSE)  
B <- sample(1:100, 60, replace = FALSE)  
C <- sample(1:100, 40, replace = FALSE)  
res <- venndetail(list(A = A, B = B, C = C))  
  
# Examine the results  
summary(res)  
  
# Plot the results  
plot(res, type = "venn")
```

```
# With abbreviated set names
sets <- list(
  LongNameGroup1 = sample(1:100, 40),
  LongNameGroup2 = sample(1:100, 50),
  LongNameGroup3 = sample(1:100, 45)
)
res <- vennDetail(sets, abbr = TRUE, minlength = 4)
```

vennDiagram

Create a Venn diagram

Description

Creates a traditional Venn diagram for 2-5 sets

Usage

```
vennDiagram(
  object,
  fill = NULL,
  alpha = 0.5,
  labels = TRUE,
  counts = TRUE,
  showNumbers = TRUE,
  numberSize = 4,
  numberColor = "black",
  labelSize = 4,
  labelColor = "black",
  borderCol = FALSE,
  fillCol = TRUE,
  fixedCoords = TRUE,
  xlim = c(0, 1),
  ylim = c(0, 1),
  show_percentages = TRUE,
  show_unique_only = FALSE,
  scaled = FALSE,
  title = NULL,
  interactive = FALSE,
  ...
)
```

Arguments

object	A Venn object
fill	Colors for filling the circles
alpha	Transparency level for the circles (0-1)
labels	Logical: show set labels? (default: TRUE)
counts	Logical: show counts? (default: TRUE)
showNumbers	Logical: whether to show counts and percentages in each region
numberSize	Size of the count labels

numberColor	Color of the count labels
labelSize	Size of the set labels
labelColor	Color of the set labels
borderCol	Logical: whether to color the borders of circles
fillCol	Logical: whether to fill circles with colors
fixedCoords	Logical: whether to use fixed coordinates
xlim	Vector with 2 numbers, x axis limits for the venn diagram
ylim	Vector with 2 numbers, y axis limits for the venn diagram
show_percentages	Logical: show percentages alongside counts? (default: TRUE)
show_unique_only	Logical: show counts only for unique elements? (default: FALSE)
scaled	Logical: scale circles by set size? (default: FALSE)
title	Optional plot title
interactive	Logical: create interactive plot? (default: FALSE)
...	Additional arguments passed to ggplot2 functions

Value

A ggplot2 or plotly object

Author(s)

Kai Guo

vennDiagram, Venn-method

Create a traditional Venn diagram

Description

Creates a traditional Venn diagram for 2-5 sets

Usage

```
## S4 method for signature 'Venn'
vennDiagram(
  object,
  fill = NULL,
  alpha = 0.5,
  labels = TRUE,
  counts = TRUE,
  showNumbers = TRUE,
  numberSize = 4,
  numberColor = "black",
  labelSize = 4,
  labelColor = "black",
```

```

borderCol = FALSE,
fillCol = TRUE,
fixedCoords = TRUE,
xlim = c(0, 1),
ylim = c(0, 1),
show_percentages = TRUE,
show_unique_only = FALSE,
scaled = FALSE,
title = NULL,
interactive = FALSE,
...
)

```

Arguments

object	A Venn object
fill	Colors for filling the circles
alpha	Transparency level for the circles (0-1)
labels	Logical: show set labels? (default: TRUE)
counts	Logical: show counts? (default: TRUE)
showNumbers	Logical: whether to show counts and percentages in each region
numberSize	Size of the count labels
numberColor	Color of the count labels
labelSize	Size of the set labels
labelColor	Color of the set labels
borderCol	Logical: whether to color the borders of circles
fillCol	Logical: whether to fill circles with colors
fixedCoords	Logical: whether to use fixed coordinates
xlim	Vector with 2 numbers, x axis limits for the venn diagram
ylim	Vector with 2 numbers, y axis limits for the venn diagram
show_percentages	Logical: show percentages alongside counts? (default: TRUE)
show_unique_only	Logical: show counts only for unique elements? (default: FALSE)
scaled	Logical: scale circles by set size? (default: FALSE)
title	Optional plot title
interactive	Logical: create interactive plot? (default: FALSE)
...	Additional arguments passed to ggplot2 functions

Value

A ggplot2 or plotly object

Author(s)

Kai Guo

`vennEnrichment`*Perform enrichment analysis on set intersections*

Description

Performs enrichment analysis to identify overrepresented categories in set intersections

Usage

```
vennEnrichment(  
  object,  
  annotation,  
  id_col,  
  category_col,  
  subsets = NULL,  
  min_overlap = 3,  
  adjust.method = "BH",  
  sig_threshold = 0.05  
)
```

Arguments

<code>object</code>	A Venn object
<code>annotation</code>	A data frame with annotation data (e.g., Gene Ontology terms)
<code>id_col</code>	Column in the annotation data frame containing identifiers matching elements in the Venn object
<code>category_col</code>	Column in the annotation data frame containing category information
<code>subsets</code>	Character vector of subset names to analyze (default: NULL, all subsets)
<code>min_overlap</code>	Minimum number of elements a category must share with a subset (default: 3)
<code>adjust.method</code>	Method for multiple testing correction (default: "BH")
<code>sig_threshold</code>	Significance threshold for p-values (default: 0.05)

Value

A data.frame with enrichment analysis results

Author(s)

Kai Guo

Examples

```
# Create a Venn object with gene sets  
A <- sample(1:1000, 100, replace = FALSE)  
B <- sample(1:1000, 150, replace = FALSE)  
C <- sample(1:1000, 120, replace = FALSE)  
res <- vennDetail(list(A = A, B = B, C = C))  
  
# Create simulated annotation data  
gene_ids <- 1:1000
```

```
categories <- sample(c("Category1", "Category2", "Category3", "Category4"),
                    1000, replace = TRUE)
anno <- data.frame(GeneID = gene_ids, Category = categories)

# Perform enrichment analysis
enrichment <- vennEnrichment(res, anno, "GeneID", "Category")
```

vennpie

Create a Venn-pie visualization

Description

Creates a pie-chart-like visualization of set intersections

Usage

```
vennpie(
  object,
  subset = NULL,
  top = 31,
  min = 0,
  color = NULL,
  revcolor = "lightgrey",
  any = NULL,
  show.number = TRUE,
  show.x = TRUE,
  sep = "_",
  log = FALSE,
  base = NULL,
  percentage = FALSE,
  title = NULL,
  interactive = FALSE,
  ...
)
```

Arguments

object	A Venn object
subset	Character vector of subset names to highlight
top	Maximum number of subsets to display
min	Minimum number of sets an element must be in
color	Optional vector of colors for the subsets
revcolor	Color for non-highlighted subsets
any	Highlight subsets shared by exactly this many sets
show.number	Logical: show counts in labels?
show.x	Logical: show subset labels?
sep	Character separator for subset names
log	Logical: use log scale for counts?

base	Base for log transformation if log=TRUE
percentage	Logical: show percentages instead of counts?
title	Optional plot title
interactive	Logical: create interactive plot?
...	Additional arguments

Value

A ggplot2 or plotly object

Author(s)

Kai Guo

vennpie, Venn-method *Create a Venn-pie visualization*

Description

Creates a pie-chart-like visualization of set intersections, which is particularly useful for visualizing more than 5 sets

Usage

```
## S4 method for signature 'Venn'
vennpie(
  object,
  subset = NULL,
  top = 31,
  min = 0,
  color = NULL,
  revcolor = "lightgrey",
  any = NULL,
  show.number = TRUE,
  show.x = TRUE,
  sep = "_",
  log = FALSE,
  base = NULL,
  percentage = FALSE,
  title = NULL,
  interactive = FALSE,
  ...
)
```

Arguments

object	A Venn object
subset	Character vector of subset names to highlight
top	Maximum number of subsets to display. Default: 31

min	Minimum number of sets an element must be in. Default: 0
color	Optional vector of colors for the subsets
revcolor	Color for non-highlighted subsets. Default: "lightgrey"
any	Highlight subsets shared by exactly this many sets
show.number	Logical: show counts in labels? Default: TRUE
show.x	Logical: show subset labels? Default: TRUE
sep	Character separator for subset names
log	Logical: use log scale for counts? Default: FALSE
base	Base for log transformation if log=TRUE
percentage	Logical: show percentages instead of counts? Default: FALSE
title	Optional plot title
interactive	Logical: create interactive plot? Default: FALSE
...	Additional arguments

Value

A ggplot2 or plotly object

Author(s)

Kai Guo

vennStats	<i>Perform statistical tests on set intersections</i>
-----------	---

Description

Performs statistical tests to evaluate the significance of set intersections

Usage

```
vennStats(
  object,
  universe = NULL,
  method = c("hypergeometric", "permutation"),
  nperm = 1000,
  adjust.method = "BH",
  include_singles = FALSE
)
```

Arguments

object	A Venn object
universe	Size of the universe for hypergeometric test. Default: NULL (will use the union of all sets)
method	Statistical method to use: "hypergeometric" or "permutation". Default: "hypergeometric"

nperm Number of permutations if method="permutation". Default: 1000
 adjust.method Method for multiple testing correction. Default: "BH"
 include_singles Logical: include tests for single sets? Default: FALSE

Value

A data.frame with statistical test results

Author(s)

Kai Guo

Examples

```
A <- sample(1:1000, 100, replace = FALSE)
B <- sample(1:1000, 150, replace = FALSE)
C <- sample(1:1000, 120, replace = FALSE)
res <- vennDetail(list(A = A, B = B, C = C))
stats <- vennStats(res)
```

vennStats, Venn-method *Perform statistical tests on set intersections*

Description

Performs statistical tests to evaluate the significance of set intersections

Usage

```
## S4 method for signature 'Venn'
vennStats(
  object,
  universe = NULL,
  method = c("hypergeometric", "permutation"),
  nperm = 1000,
  adjust.method = "BH",
  include_singles = FALSE
)
```

Arguments

object A Venn object
 universe Size of the universe for hypergeometric test (default: NULL, will use the union of all sets)
 method Statistical method to use: "hypergeometric" or "permutation" (default: "hypergeometric")
 nperm Number of permutations if method="permutation" (default: 1000)
 adjust.method Method for multiple testing correction (default: "BH")
 include_singles Logical: include tests for single sets? (default: FALSE)

Value

A data.frame with statistical test results

Author(s)

Kai Guo

Examples

```
# Create a Venn object
A <- sample(1:1000, 100, replace = FALSE)
B <- sample(1:1000, 150, replace = FALSE)
C <- sample(1:1000, 120, replace = FALSE)
res <- venndetail(list(A = A, B = B, C = C))

# Perform statistical tests
stats <- vennStats(res)

# With custom universe size
stats <- vennStats(res, universe = 2000)

# Using permutation test
stats <- vennStats(res, method = "permutation", nperm = 500)
```

[.Venn

Subset a Venn object

Description

Extract elements from the result slot of a Venn object using bracket notation.

Usage

```
## S3 method for class 'Venn'
x[i, j]
```

Arguments

x	Venn object
i	Row indices
j	Column indices

Value

Subset of the result data.frame

\$.Venn	<i>Extract column from a Venn object</i>
---------	--

Description

Extract a column from the result slot of a Venn object using \$ notation.

Usage

```
## S3 method for class 'Venn'  
x$name
```

Arguments

x	Venn object
name	Column name to extract

Value

Vector containing the specified column

Index

- * **datasets**
 - T2DM, [30](#)
- * **internal**
 - .findOverlap, [5](#)
 - .vennDiagram, [6](#)
 - make_truth_table, [17](#)
 - makeContent.upset_grob, [16](#)
- * **package**
 - VennDetail-package, [3](#)
 - .add_colnames, [4](#)
 - .findOverlap, [5](#)
 - .make.table, [5](#)
 - .vennDiagram, [6](#)
 - [.Venn, [51](#)
 - \$.Venn, [52](#)
- as.data.frame.Venn, [7](#)
- compareVenn, [7](#)
- create_interactive_vennpie, [8](#)
- detail, [9](#)
- detail, Venn-method (detail), [9](#)
- dim.Venn, [10](#)
- dplot, [10](#)
- dplot, Venn-method (dplot), [10](#)
- getFeature, [11](#)
- getFeature, Venn-method (getFeature), [11](#)
- getSet, [13](#)
- getSet, Venn-method (getSet), [13](#)
- head.Venn, [14](#)
- loadVenn, [15](#)
- make_subset, [15](#)
- make_subset, [16](#)
- make_truth_table, [17](#)
- makeContent.upset_grob, [16](#)
- merge.Venn, [18](#)
- names.Venn, [18](#)
- newVenn, [19](#)
- plot.Venn, [20](#)
- print.upset_grob, [25](#)
- result, [26](#)
- result, Venn-method (result), [26](#)
- rowjoin, [27](#)
- rowjoin, data.frame, data.frame-method (rowjoin), [27](#)
- saveVenn, [28](#)
- setcolor, [28](#)
- show Venn, [29](#)
- show, Venn-method (show Venn), [29](#)
- summary.Venn, [30](#)
- T2DM, [30](#)
- tail.Venn (head.Venn), [14](#)
- upset_plot, [37](#)
- upsetPlot, [31](#)
- upsetPlot, Venn-method, [34](#)
- Venn-class, [40](#)
- vennApp, [41](#)
- VennDetail (VennDetail-package), [3](#)
- venndetail, [42](#)
- VennDetail-package, [3](#)
- vennDiagram, [43](#)
- vennDiagram, Venn-method, [44](#)
- vennEnrichment, [46](#)
- vennpie, [47](#)
- vennpie, Venn-method, [48](#)
- vennStats, [49](#)
- vennStats, Venn-method, [50](#)