

# Package ‘chimeraviz’

May 25, 2026

**Type** Package

**Title** Visualization tools for gene fusions

**Version** 1.39.0

**Description** chimeraviz manages data from fusion gene finders and provides useful visualization tools.

**License** Artistic-2.0

**LazyData** TRUE

**Imports** methods, grid, Rsamtools, GenomeInfoDb, GenomicAlignments, RColorBrewer, graphics, AnnotationDbi, RCircos, org.Hs.eg.db, org.Mm.eg.db, rmarkdown, graph, Rgraphviz, DT, plyr, dplyr, BiocStyle, checkmate, gtools, magick

**Depends** Biostrings, GenomicRanges, IRanges, Gviz, S4Vectors, ensemblDb, AnnotationFilter, data.table

**Suggests** testthat, roxygen2, devtools, knitr, lintr

**SystemRequirements** bowtie, samtools, and egrep are required for some functionalities

**RoxygenNote** 7.1.1

**VignetteBuilder** knitr

**biocViews** Infrastructure, Alignment

**Encoding** UTF-8

**URL** <https://github.com/stianlagstad/chimeraviz>

**BugReports** <https://github.com/stianlagstad/chimeraviz/issues>

**git\_url** <https://git.bioconductor.org/packages/chimeraviz>

**git\_branch** devel

**git\_last\_commit** 24c40c6

**git\_last\_commit\_date** 2026-04-28

**Repository** Bioconductor 3.24

**Date/Publication** 2026-05-25

**Author** Stian Lågstad [aut, cre],  
Sen Zhao [ctb],  
Andreas M. Hoff [ctb],  
Bjarne Johannessen [ctb],  
Ole Christian Lingjærde [ctb],  
Rolf Skotheim [ctb]

**Maintainer** Stian Lågstad <stianlagstad@gmail.com>

## Contents

|   |    |
|---|----|
| add_fusion_reads_alignment . . . . .                      | 3  |
| chimeraviz . . . . .                                      | 4  |
| chimeraviz-internals-fusions_to_gene_label_data . . . . . | 4  |
| chimeraviz-internals-fusions_to_link_data . . . . .       | 5  |
| chimeraviz-internals-scaleListToInterval . . . . .        | 5  |
| create_fusion_report . . . . .                            | 6  |
| decide_transcript_category . . . . .                      | 7  |
| downstream_partner_gene . . . . .                         | 8  |
| down_shift . . . . .                                      | 9  |
| fetch_reads_from_fastq . . . . .                          | 10 |
| Fusion-class . . . . .                                    | 11 |
| fusion_spanning_reads_count . . . . .                     | 11 |
| fusion_split_reads_count . . . . .                        | 12 |
| fusion_to_data_frame . . . . .                            | 13 |
| get_ensembl_ids . . . . .                                 | 13 |
| get_fusion_by_chromosome . . . . .                        | 14 |
| get_fusion_by_gene_name . . . . .                         | 15 |
| get_fusion_by_id . . . . .                                | 16 |
| get_transcripts_ensembl_db . . . . .                      | 16 |
| import_aeron . . . . .                                    | 17 |
| import_chimpipe . . . . .                                 | 18 |
| import_defuse . . . . .                                   | 19 |
| import_ericscript . . . . .                               | 20 |
| import_function_non_ucsc . . . . .                        | 20 |
| import_fusioncatcher . . . . .                            | 21 |
| import_fusionmap . . . . .                                | 21 |
| import_infusion . . . . .                                 | 22 |
| import_jaffa . . . . .                                    | 23 |
| import_oncofuse . . . . .                                 | 23 |
| import_prada . . . . .                                    | 24 |
| import_soapfuse . . . . .                                 | 25 |
| import_squid . . . . .                                    | 25 |
| import_starfusion . . . . .                               | 26 |
| PartnerGene-class . . . . .                               | 27 |
| partner_gene_ensembl_id . . . . .                         | 27 |
| partner_gene_junction_sequence . . . . .                  | 28 |
| plot_circle . . . . .                                     | 29 |
| plot_fusion . . . . .                                     | 30 |
| plot_fusion_reads . . . . .                               | 32 |
| plot_fusion_transcript . . . . .                          | 34 |
| plot_fusion_transcripts_graph . . . . .                   | 36 |
| plot_fusion_transcript_with_protein_domain . . . . .      | 37 |
| plot_transcripts . . . . .                                | 39 |
| raw_chimpipe . . . . .                                    | 41 |
| raw_cytobandhg19 . . . . .                                | 41 |
| raw_cytobandhg38 . . . . .                                | 41 |
| raw_defuse . . . . .                                      | 42 |
| raw_ericscript . . . . .                                  | 42 |

|  |    |
|--|----|
| raw_fusion5267proteindomains . . . . . | 43 |
| raw_fusion5267reads . . . . .          | 43 |
| raw_fusion5267readsBedGraph . . . . .  | 43 |
| raw_fusioncatcher . . . . .            | 44 |
| raw_fusionmap . . . . .                | 44 |
| raw_Homo_sapiens.GRCh37.74 . . . . .   | 44 |
| raw_infusion . . . . .                 | 45 |
| raw_jaffa . . . . .                    | 45 |
| raw_oncofuse . . . . .                 | 45 |
| raw_prada . . . . .                    | 45 |
| raw_soapfuse . . . . .                 | 46 |
| raw_starfusion . . . . .               | 46 |
| select_transcript . . . . .            | 46 |
| show,Fusion-method . . . . .           | 47 |
| show,PartnerGene-method . . . . .      | 48 |
| split_on_utr_and_add_feature . . . . . | 48 |
| upstream_partner_gene . . . . .        | 49 |
| write_fusion_reference . . . . .       | 50 |

**Index****52**


---

 add\_fusion\_reads\_alignment

*Add fusion reads alignment to fusion object*

---

**Description**

This function lets you add a fusion read alignment file to a fusion object. If you've mapped the reads supporting a fusion against the fusion junction sequence, and have the resulting bamfile, use this function to add the information (as a `Gviz::GAlignmentPairs` object) to the fusion object.

**Usage**

```
add_fusion_reads_alignment(fusion, bamfile)
```

**Arguments**

|         |  |
|---------|--|
| fusion  | The fusion object to add a genomic alignment to.                         |
| bamfile | The bam file containing the fusion reads plotted to the fusion sequence. |

**Value**

An updated fusion object with `fusion@fusion_reads_alignment` set.

**Examples**

```
# Load data
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 1)
# Find the specific fusion we have aligned reads for
```

```

fusion <- get_fusion_by_id(fusions, 5267)
# Get reference to the bamfile with the alignment data
bamfile5267 <- system.file(
  "extdata",
  "5267readsAligned.bam",
  package="chimeraviz")
# Add the bam file of aligned fusion reads to the fusion object
fusion <- add_fusion_reads_alignment(fusion, bamfile5267)

```

---

chimeraviz

*chimeraviz: A package for working with and visualizing fusion genes.*


---

### Description

chimeraviz manages data from fusion gene finders and provides useful visualization tools.

---

chimeraviz-internals-fusions\_to\_gene\_label\_data

*Create gene label data for RCircos from the given fusions.*


---

### Description

This function takes a list of Fusion objects and creates a data frame in the format that RCircos.Gene.Name.Plot() expects for gene label data.

### Usage

```
.fusions_to_gene_label_data(fusion_list)
```

### Arguments

fusion\_list     A list of Fusion objects.

### Value

A data frame with fusion gene label data compatible with RCircos.Gene.Name.Plot()

```

# @examples # Apparently examples shouldn't be set on private functions
defuse833ke <- system.file("extdata", "defuse_833ke_results.filtered.tsv", package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 3)
labelData <- chimeraviz::fusions_to_gene_label_data(fusions)
# This labelData can be used with RCircos.Gene.Connector.Plot() and RCircos.Gene.Name.Plot()

```

---

`chimeraviz-internals-fusions_to_link_data`*Create link data for RCircos from the given fusions.*

---

### Description

This function takes a list of Fusion objects and creates a data frame in the format that `RCircos::RCircos.Link.Plot()` expects for link data.

### Usage

```
.fusions_to_link_data(fusion_list, min_link_width = 1, max_link_widht = 10)
```

### Arguments

`fusion_list` A list of Fusion objects.  
`min_link_width` The minimum link line width. Default = 1  
`max_link_widht` The maximum link line width. Default = 10

### Value

A data frame with fusion link data compatible with `RCircos::RCircos.Link.Plot()`

```
# @examples # Apparently examples shouldn't be set on private functions defuse833ke <- system.file("extdata", "defuse_833ke_results.filtered.tsv", package="chimeraviz") fusions <- import_defuse(defuse833ke, "hg19", 3) linkData <- chimeraviz::.fusions_to_link_data(fusions) # This linkData can be used with RCircos::RCircos.Link.Plot()
```

---

`chimeraviz-internals-scaleListToInterval`*Scale a vector of numeric values to an interval.*

---

### Description

This function takes a vector of numeric values as well as an interval [`new_min`, `new_max`] that the numeric values will be scaled (normalized) to.

### Usage

```
.scale_list_to_interval(the_list, new_min, new_max)
```

### Arguments

`the_list` A vector of numeric values.  
`new_min` Minimum value for the new interval.  
`new_max` Maximum value for the new interval.

**Value**

A data frame with fusion link data compatible with `RCircos::RCircos.Link.Plot()`

```
# @examples # Apparently examples shouldn't be set on private functions list012 <- c(0,1,2)
.scale_list_to_interval(list012, 1, 3) # [1] 1 2 3
```

---

`create_fusion_report` *Create a Fusion Report*

---

**Description**

This function will create a html report with an overplot and a sortable, searchable table with the fusion data.

**Usage**

```
create_fusion_report(fusions, output_filename, quiet = TRUE)
```

**Arguments**

|                              |  |
|------------------------------|--|
| <code>fusions</code>         | A list of Fusion objects.  |
| <code>output_filename</code> | Output html-file filename.   |
| <code>quiet</code>           | Parameter passed to <code>rmarkdown::render()</code> to toggle its output. |

**Value**

Creates a html report with an overplot and a sortable, searchable table with the fusion data.

**Examples**

```
# Load data
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 3)
# Temporary file to store the report
random_filename <- paste0(
  paste0(sample(LETTERS, 5, replace = TRUE), collapse=''),
  ".png"
)
# Create report
create_fusion_report(fusions, random_filename)
# Delete the file
file.remove(random_filename)
```

---

`decide_transcript_category`*Retrieves transcripts for partner genes in a Fusion object using EnsemblDb*

---

### Description

This function will check where in the transcript (the GRanges object) the fusion breakpoint is located, and return either "exonBoundary", "withinExon", "withinIntron", or "intergenic".

### Usage

```
decide_transcript_category(gr, fusion)
```

### Arguments

`gr`                    The GRanges object containing the transcript to be checked.  
`fusion`                The fusion object used to check the transcript.

### Value

Either "exonBoundary", "withinExon", "withinIntron", or "intergenic" depending on where in the transcript the breakpoint hits.

### Examples

```
# Load fusion data and choose a fusion object:
defuseData <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuseData, "hg19", 1)
fusion <- get_fusion_by_id(fusions, 5267)
# Create edb object
edbSqliteFile <- system.file(
  "extdata",
  "Homo_sapiens.GRCh37.74.sqlite",
  package="chimeraviz")
edb <- ensemblDb::EnsDb(edbSqliteFile)
# Get all exons for all transcripts in the genes in the fusion transcript
allTranscripts <- ensemblDb::exonsBy(
  edb,
  filter = list(
    AnnotationFilter::GeneIdFilter(
      c(
        partner_gene_ensembl_id(upstream_partner_gene(fusion)),
        partner_gene_ensembl_id(downstream_partner_gene(fusion))))),
  columns = c(
    "gene_id",
    "gene_name",
    "tx_id",
    "tx_cds_seq_start",
    "tx_cds_seq_end",
```

```

    "exon_id"))
# Extract one of the GRanges objects
gr <- allTranscripts[[1]]
# Check where in the transcript the fusion breakpoint hits
decide_transcript_category(gr, fusion)
# "exonBoundary"
# Check another case
gr <- allTranscripts[[3]]
decide_transcript_category(gr, fusion)
# "withinIntron"

```

---

downstream\_partner\_gene

*Get the downstream fusion partner gene*

---

## Description

This getter retrieves the downstream PartnerGene object.

This sets the downstream PartnerGene object of a Fusion object

## Usage

```

downstream_partner_gene(x)

## S4 method for signature 'Fusion'
downstream_partner_gene(x)

downstream_partner_gene(object) <- value

## S4 replacement method for signature 'Fusion'
downstream_partner_gene(object) <- value

```

## Arguments

|        |   |
|--------|---|
| x      | The Fusion object you wish to retrieve the downstream PartnerGene object for. |
| object | The Fusion object you wish to set a new downstream PartnerGene object for.    |
| value  | The new PartnerGene object.   |

## Value

The downstream PartnerGene object.

## Examples

```

# Load data
defuseData <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuseData, "hg19", 1)
fusion <- fusions[[1]]

```

```
# Get the downstream fusion partner gene
downstream_partner_gene(fusion)

# Load data
defuseData <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuseData, "hg19", 1)
fusion <- fusions[[1]]
# Set the downstream PartnerGene object to be the same as the upstream
# PartnerGene object
downstream_partner_gene(fusion) <- upstream_partner_gene(fusion)
```

---

down\_shift

*Remove introns and shift exons leftward*

---

## Description

This function takes a GRanges object and moves each IRanges object within next to each other starting at 1. This effectively removes the introns from the GRanges object.

## Usage

```
down_shift(transcript)
```

## Arguments

transcript      The GRanges object to remove introns from.

## Value

A GRanges object with introns removed.

## Examples

```
# Create a simple GRanges object:
gr <- IRanges::IRanges(
  start = c(13, 40, 100),
  end = c(20, 53, 110))
# Downshift it and see the introns are removed:
down_shift(gr)
```

---

`fetch_reads_from_fastq`*Fetch reads from fastq files*

---

## Description

This function will fetch read sequences from fastq files and put them into new fastq files.

## Usage

```
fetch_reads_from_fastq(  
  reads,  
  fastq_file_in1,  
  fastq_file_in2,  
  fastq_file_out1,  
  fastq_file_out2  
)
```

## Arguments

|                              |   |
|------------------------------|---|
| <code>reads</code>           | List of read IDs that is to be fetched. |
| <code>fastq_file_in1</code>  | First fastq file to search in.          |
| <code>fastq_file_in2</code>  | Second fastq file to search in.         |
| <code>fastq_file_out1</code> | First fastq file with results.          |
| <code>fastq_file_out2</code> | Second fastq file with results.         |

## Details

Note: This function runs (read only) bash commands on your system. Therefore the function will only work on a unix system.

## Value

The files `fastqFileOut1` and `fastqFileOut2` populated with the specified reads.

## Examples

```
## Not run:  
# fastq files that has the supporting reads  
fastq1 <- system.file("extdata", "reads.1.fq", package="chimeraviz")  
fastq2 <- system.file("extdata", "reads.2.fq", package="chimeraviz")  
# Which read ids to extract  
reads <- c(  
  "13422259", "19375605", "29755061",  
  "31632876", "32141428", "33857245")  
# Extract the actual reads and put them in the tmp files "fastqFileOut1" and  
# "fastqFileOut2"  
fastqFileOut1 <- tempfile(pattern = "fq1", tmpdir = tmpdir())  
fastqFileOut2 <- tempfile(pattern = "fq2", tmpdir = tmpdir())
```

```

fetch_reads_from_fastq(reads, fastq1, fastq2,
    fastqFileOut1, fastqFileOut2)
# We now have the reads supporting fusion 5267 in the two files.

## End(Not run)

```

---

|              |   |
|--------------|---|
| Fusion-class | <i>An S4 class to represent a fusion event.</i> |
|--------------|---|

---

### Description

The Fusion class represents a fusion event, holding data imported from a fusion tool.

### Slots

**id** A unique id representing a fusion event. For deFuse data this will be the cluster id.  
**fusion\_tool** Name of the fusion tool.  
**genome\_version** Name of the genome used to map reads.  
**spanning\_reads\_count** The number of spanning reads supporting the fusion.  
**split\_reads\_count** The number of split reads supporting the fusion.  
**fusion\_reads\_alignment** A Gviz::AlignmentsTrack object holding the fusion reads aligned to the fusion sequence.  
**gene\_upstream** A PartnerGene object holding information of the upstream fusion partner gene.  
**gene\_downstream** A PartnerGene object holding information of the downstream fusion partner gene.  
**inframe** A logical value indicating whether or not the downstream fusion partner gene is inframe or not. Not all fusion-finders report this.  
**fusion\_tool\_specific\_data** A list that will hold fields of importance for a specific fusion finder. This field is used because many fusion-finders report important values that are hard to fit into a standardized format. Examples of values that are added to this list is probability from deFuse and EricScore from EricScript.

---

|                             |  |
|-----------------------------|--|
| fusion_spanning_reads_count | <i>Get the spanning reads count from a Fusion object</i> |
|-----------------------------|--|

---

### Description

This getter retrieves the spanning reads count from a Fusion object

### Usage

```

fusion_spanning_reads_count(x)

## S4 method for signature 'Fusion'
fusion_spanning_reads_count(x)

```

**Arguments**

x                    The Fusion object you wish to retrieve the spanning reads count for.

**Value**

The Fusion spanning reads count.

**Examples**

```
# Load data
defuseData <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuseData, "hg19", 1)
fusion <- fusions[[1]]
# Get the spanning reads count
fusion_spanning_reads_count(fusion)
```

---

fusion\_split\_reads\_count

*Get the split reads count from a Fusion object*

---

**Description**

This getter retrieves the split reads count from a Fusion object

**Usage**

```
fusion_split_reads_count(x)
```

```
## S4 method for signature 'Fusion'
fusion_split_reads_count(x)
```

**Arguments**

x                    The Fusion object you wish to retrieve the split reads count for.

**Value**

The Fusion split reads count.

**Examples**

```
# Load data
defuseData <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuseData, "hg19", 1)
fusion <- fusions[[1]]
# Get the split reads count
```

```
fusion_split_reads_count(fusion)
```

---

```
fusion_to_data_frame
```

*Coerce Fusion object to data.frame*

---

**Description**

This function is used in `create_fusion_report()` to convert Fusion objects to a `data.frame`-format.

**Usage**

```
fusion_to_data_frame(fusion)
```

**Arguments**

`fusion`            The Fusion object to coerce.

**Value**

A `data.frame` with the fusion object.

**See Also**

`create_fusion_report`

**Examples**

```
# Load data
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 1)
# Find the fusion object to create a data frame from
fusion <- get_fusion_by_id(fusions, 5267)
# Create the data frame
dfFusion <- fusion_to_data_frame(fusion)
```

---

```
get_ensembl_ids
```

*Get ensembl ids for a fusion object*

---

**Description**

This function will get the ensembl ids from the `org.Hs.eg.db/org.Mm.eg.db` package given the gene names of the fusion event.

**Usage**

```
get_ensembl_ids(fusion)
```

**Arguments**

fusion            The Fusion object we want to get ensembl ids for.

**Value**

The Fusion object with Ensembl ids set.

**Examples**

```
# Import the filtered defuse results
defuse833keFiltered <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833keFiltered, "hg19", 1)
# Get a specific fusion
fusion <- get_fusion_by_id(fusions, 5267)
# See the ensembl ids:
partner_gene_ensembl_id(upstream_partner_gene(fusion))
# [1] "ENSG00000180198"
partner_gene_ensembl_id(downstream_partner_gene(fusion))
# [1] "ENSG00000162639"
# Reset the fusion objects ensembl ids
partner_gene_ensembl_id(upstream_partner_gene(fusion)) <- ""
partner_gene_ensembl_id(downstream_partner_gene(fusion)) <- ""
# Get the ensembl ids
fusion <- get_ensembl_ids(fusion)
# See that we now have the same ensembl ids again:
partner_gene_ensembl_id(upstream_partner_gene(fusion))
# [1] "ENSG00000180198"
partner_gene_ensembl_id(downstream_partner_gene(fusion))
# [1] "ENSG00000162639"
```

---

get\_fusion\_by\_chromosome

*Find fusions that involves genes in the given chromosome.*

---

**Description**

Helper function to retrieve the Fusion objects that involves genes in the given chromosome name.

**Usage**

```
get_fusion_by_chromosome(fusion_list, chr)
```

**Arguments**

fusion\_list      A list of Fusion objects.  
chr                The chromosome name we're looking for fusions in.

**Value**

A list of Fusion objects.

**Examples**

```
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 1)
length(get_fusion_by_chromosome(fusions, "chr1"))
# [1] 1
```

---

get\_fusion\_by\_gene\_name

*Find fusions that includes the given gene.*

---

**Description**

Helper function to retrieve the Fusion objects that has geneName as one of the partner genes.

**Usage**

```
get_fusion_by_gene_name(fusion_list, gene_name)
```

**Arguments**

fusion\_list      A list of Fusion objects.  
gene\_name        The gene name we're looking for.

**Details**

Note: get\_fusion\_by\_gene\_name(fusionList, "MT") will match both MT-ND5 and MT-ND4.

**Value**

A list of Fusion objects.

**Examples**

```
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 1)
length(get_fusion_by_gene_name(fusions, "RCC1"))
# [1] 1
```

---

get\_fusion\_by\_id      *Find a specific fusion object in a list by id*

---

### Description

Helper function to retrieve the Fusion object with the given id.

### Usage

```
get_fusion_by_id(fusion_list, id)
```

### Arguments

fusion\_list      A list of Fusion objects.  
 id                The id (e.g. the cluster\_id from a deFuse run) we're looking for.

### Value

A Fusion object.

### Examples

```
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 1)
fusion <- get_fusion_by_id(fusions, 5267)
# This should be the Fusion object:
fusion
# [1] "Fusion object"
# [1] "id: 5267"
# [1] "Fusion tool: defuse"
# [1] "Genome version: hg19"
# [1] "Gene names: RCC1-HENMT1"
# [1] "Chromosomes: chr1-chr1"
# [1] "Strands: +,-"
```

---

get\_transcripts\_ensembl\_db  
*Retrieves transcripts for partner genes in a Fusion object using EnsemblDB*

---

### Description

This function will retrieve transcripts for both genes in a fusion. It will check all transcripts and decide for each transcript if the fusion breakpoint happens at 1) an exon boundary, 2) within an exon, or 3) within an intron. This is done because fusions happening at exon boundaries are more likely to produce biologically interesting gene products. The function returns an updated Fusion object, where the fusion@gene\_upstream@transcriptsX slots are set with transcript information.

**Usage**

```
get_transcripts_ensembl_db(fusion, edb)
```

**Arguments**

fusion            The fusion object to find transcripts for.  
 edb                The edb object used to fetch data from.

**Value**

An updated fusion object with transcript data stored.

**Examples**

```
# Load fusion data and choose a fusion object:
defuseData <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuseData, "hg19", 1)
fusion <- get_fusion_by_id(fusions, 5267)
# Create edb object
edbSqliteFile <- system.file(
  "extdata",
  "Homo_sapiens.GRCh37.74.sqlite",
  package="chimeraviz")
edb <- ensemblDb::EnsDb(edbSqliteFile)
# Add transcripts data to fusion object
fusion <- get_transcripts_ensembl_db(fusion, edb)
# The transcripts are now accessible through fusion@gene_upstream@transcripts and
# fusion@gene_downstream@transcripts .
```

---

 import\_aeron

---

*Import results from an Aeron run into a list of Fusion objects.*


---

**Description**

A function that imports the results from an Aeron run into a list of Fusion objects.

**Usage**

```
import_aeron(
  filename_fusion_support,
  filename_fusion_transcript,
  genome_version,
  limit
)
```

**Arguments**

filename\_fusion\_support  
 Filename for the Aeron result file fusion\_support.txt.

filename\_fusion\_transcript  
 Filename for the Aeron result file fusion\_transcripts.txt.

genome\_version Which genome was used in mapping (hg19, hg38, etc.).

limit A limit on how many lines to read.

**Details**

Note that the strands and breakpoint positions are not included in the result files from Aeron. These have to be retrieved manually, using the ensembl identifiers (which are included in the result files, and will be available in the Fusion objects after importing).

**Value**

A list of Fusion objects.

**Examples**

```
aeronfusionsupportfile <- system.file(
  "extdata",
  "aeron_fusion_support.txt",
  package="chimeraviz")
aeronfusiontranscriptfile <- system.file(
  "extdata",
  "aeron_fusion_transcripts.fa",
  package="chimeraviz")
fusions <- import_aeron(
  aeronfusionsupportfile,
  aeronfusiontranscriptfile,
  "hg19",
  3)
# This should import a list of 3 fusions described in Fusion objects.
```

---

import\_chimpipe

*Import results from a ChimPipe run into a list of Fusion objects.*

---

**Description**

A function that imports the results from a ChimPipe run, typically from a chimericJunctions.txt file, into a list of Fusion objects.

**Usage**

```
import_chimpipe(filename, genome_version, limit)
```

**Arguments**

filename Filename for the ChimPipe results.

genome\_version Which genome was used in mapping (hg19, hg38, etc.).

limit A limit on how many lines to read.

**Value**

A list of Fusion objects.

**Examples**

```
chimpipelinefile <- system.file(
  "extdata",
  "chimericJunctions_MCF-7.txt",
  package="chimeraviz")
fusions <- import_chimpipeline(chimpipelinefile, "hg19", 3)
# This should import a list of 3 fusions described in Fusion objects.
```

---

|               |  |
|---------------|--|
| import_defuse | <i>Import results from a deFuse run into a list of Fusion objects.</i> |
|---------------|--|

---

**Description**

A function that imports the results from a deFuse run, typically from a results.filtered.tsv file, into a list of Fusion objects.

**Usage**

```
import_defuse(filename, genome_version, limit)
```

**Arguments**

|                |  |
|----------------|--|
| filename       | Filename for the deFuse results .tsv file.           |
| genome_version | Which genome was used in mapping (hg19, hg38, etc.). |
| limit          | A limit on how many lines to read.                   |

**Value**

A list of Fusion objects.

**Examples**

```
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 3)
# This should import a list of 3 fusions described in Fusion objects.
```

---

import\_ericscript      *Import results from a EricScript run into a list of Fusion objects.*

---

### Description

A function that imports the results from a EricScript run into a list of Fusion objects.

### Usage

```
import_ericscript(filename, genome_version, limit)
```

### Arguments

filename              Filename for the EricScript results file.  
genome\_version      Which genome was used in mapping (hg19, hg38, etc.).  
limit                  A limit on how many lines to read.

### Value

A list of Fusion objects.

### Examples

```
ericscriptData <- system.file(
  "extdata",
  "ericscript_SRR1657556.results.total.tsv",
  package = "chimeraviz")
fusions <- import_ericscript(ericscriptData, "hg19", 3)
# This should import a list of 3 fusions described in Fusion objects.
```

---

import\_function\_non\_ucsc  
*Alternative import function for Gviz::AlignmentsTrack*

---

### Description

This alternative import function for use with Gviz::AlignmentsTrack imports a bamfile with non-UCSC chromosome names.

### Usage

```
import_function_non_ucsc(file, selection)
```

### Arguments

file                  The bamfile.  
selection              Which regions to get from the bamfile.

### Value

A GRanges object with coverage data for the selection.

---

import\_fusioncatcher    *Import results from a Fusioncatcher run into a list of Fusion objects.*

---

### Description

A function that imports the results from a Fusioncatcher run, typically from a final-list-candidate-fusion-genes.txt file, into a list of Fusion objects.

### Usage

```
import_fusioncatcher(filename, genome_version, limit)
```

### Arguments

filename            Filename for the Fusioncatcher final-list-candidate-fusion-genes.txt results file.  
genome\_version    Which genome was used in mapping (hg19, hg38, etc.).  
limit              A limit on how many lines to read.

### Value

A list of Fusion objects.

### Examples

```
fusioncatcher833ke <- system.file(  
  "extdata",  
  "fusioncatcher_833ke_final-list-candidate-fusion-genes.txt",  
  package = "chimeraviz")  
fusions <- import_fusioncatcher(fusioncatcher833ke, "hg38", 3)  
# This should import a list of 3 fusions described in Fusion objects.
```

---

import\_fusionmap        *Import results from a FusionMap run into a list of Fusion objects.*

---

### Description

A function that imports the results from a FusionMap run, typically from a InputFastq.FusionReport.txt file, into a list of Fusion objects.

### Usage

```
import_fusionmap(filename, genome_version, limit)
```

### Arguments

filename            Filename for the FusionMap PairedEndFusionReport.txt results file.  
genome\_version    Which genome was used in mapping (hg19, hg38, etc.).  
limit              A limit on how many lines to read.

**Value**

A list of Fusion objects.

**Examples**

```
fusionmapData <- system.file(
  "extdata",
  "FusionMap_01_TestDataset_InputFastq.FusionReport.txt",
  package = "chimeraviz")
fusions <- import_fusionmap(fusionmapData, "hg19", 3)
# This should import a list of 3 fusions described in Fusion objects.
```

---

|                 |   |
|-----------------|---|
| import_infusion | <i>Import results from an InFusion run into a list of Fusion objects.</i> |
|-----------------|---|

---

**Description**

A function that imports the results from an InFusion run into a list of Fusion objects.

**Usage**

```
import_infusion(filename, genome_version, limit)
```

**Arguments**

|                |  |
|----------------|--|
| filename       | Filename for the jaffa_results.csv file.             |
| genome_version | Which genome was used in mapping (hg19, hg38, etc.). |
| limit          | A limit on how many lines to read.                   |

**Value**

A list of Fusion objects.

**Examples**

```
infusionData <- system.file(
  "extdata",
  "infusion_fusions.txt",
  package = "chimeraviz")
fusions <- import_infusion(infusionData, "hg19", 3)
# This should import a list of 3 fusions described in Fusion objects.
```

---

|              |   |
|--------------|---|
| import_jaffa | <i>Import results from a JAFFA run into a list of Fusion objects.</i> |
|--------------|---|

---

**Description**

A function that imports the results from a JAFFA run, typically from a jaffa\_results.csv file, into a list of Fusion objects.

**Usage**

```
import_jaffa(filename, genome_version, limit)
```

**Arguments**

filename       Filename for the jaffa\_results.csv file.  
genome\_version Which genome was used in mapping (hg19, hg38, etc.).  
limit           A limit on how many lines to read.

**Value**

A list of Fusion objects.

**Examples**

```
jaffaData <- system.file(  
  "extdata",  
  "jaffa_results.csv",  
  package = "chimeraviz")  
fusions <- import_jaffa(jaffaData, "hg19", 3)  
# This should import a list of 3 fusions described in Fusion objects.
```

---

|                 |  |
|-----------------|--|
| import_oncofuse | <i>Import results from a oncofuse run into a list of Fusion objects.</i> |
|-----------------|--|

---

**Description**

A function that imports the results from a oncofuse run, typically from a results.filtered.tsv file, into a list of Fusion objects.

**Usage**

```
import_oncofuse(filename, genome_version, limit)
```

**Arguments**

filename       Filename for the oncofuse results .tsv file.  
genome\_version Which genome was used in mapping (hg19, hg38, etc.).  
limit           A limit on how many lines to read.

## Details

This import function was contributed by Lavinia G, ref <https://github.com/stianlagstad/chimeraviz/issues/47#issuecomment409773158>

## Value

A list of Fusion objects.

## Examples

```
oncofuse833ke <- system.file(
  "extdata",
  "oncofuse.outfile",
  package="chimeraviz")
fusions <- import_oncofuse(oncofuse833ke, "hg19", 3)
# This should import a list of 3 fusions described in Fusion objects.
```

---

import\_prada

*Import results from a PRADA run into a list of Fusion objects.*

---

## Description

A function that imports the results from a PRADA run into a list of Fusion objects.

## Usage

```
import_prada(filename, genome_version, limit)
```

## Arguments

`filename`           Filename for the PRADA results file.  
`genome_version`   Which genome was used in mapping (hg19, hg38, etc.).  
`limit`             A limit on how many lines to read.

## Value

A list of Fusion objects.

## Examples

```
pradaData <- system.file(
  "extdata",
  "PRADA.acc.fusion.fq.TAF.tsv",
  package = "chimeraviz")
fusions <- import_prada(pradaData, "hg19", 3)
# This should import a list of 3 fusions described in Fusion objects.
```

---

|                 |  |
|-----------------|--|
| import_soapfuse | <i>Import results from a SOAPfuse run into a list of Fusion objects.</i> |
|-----------------|--|

---

**Description**

A function that imports the results from a SOAPfuse run, typically from a final.Fusion.specific.for.genes file, into a list of Fusion objects.

**Usage**

```
import_soapfuse(filename, genome_version, limit)
```

**Arguments**

|                |   |
|----------------|---|
| filename       | Filename for the SOAPfuse final-list-candidate-fusion-genes.txt results file. |
| genome_version | Which genome was used in mapping (hg19, hg38, etc.).                          |
| limit          | A limit on how many lines to read.  |

**Value**

A list of Fusion objects.

**Examples**

```
soapfuse833ke <- system.file(
  "extdata",
  "soapfuse_833ke_final.Fusion.specific.for.genes",
  package = "chimeraviz")
fusions <- import_soapfuse(soapfuse833ke, "hg19", 3)
# This should import a list of 3 fusions described in Fusion objects.
```

---

|              |   |
|--------------|---|
| import_squid | <i>Import results from a SQUID run into a list of Fusion objects.</i> |
|--------------|---|

---

**Description**

A function that imports the results from a SQUID run into a list of Fusion objects.

**Usage**

```
import_squid(filename, genome_version, limit)
```

**Arguments**

|                |  |
|----------------|--|
| filename       | Filename for the SQUID results.                      |
| genome_version | Which genome was used in mapping (hg19, hg38, etc.). |
| limit          | A limit on how many lines to read.                   |

**Value**

A list of Fusion objects.

**Examples**

```
squidfile <- system.file(
  "extdata",
  "squid_hcc1954_sv.txt",
  package="chimeraviz")
fusions <- import_squid(squidfile, "hg19", 3)
# This should import a list of 3 fusions described in Fusion objects.
```

---

|                   |   |
|-------------------|---|
| import_starfusion | <i>Import results from a STAR-Fusion run into a list of Fusion objects.</i> |
|-------------------|---|

---

**Description**

A function that imports the results from a STAR-Fusion run, typically from a star-fusion.fusion\_candidates.final.abridged file, into a list of Fusion objects.

**Usage**

```
import_starfusion(filename, genome_version, limit)
```

**Arguments**

|                |   |
|----------------|---|
| filename       | Filename for the STAR-Fusion star-fusion.fusion_candidates.final.abridged results file. |
| genome_version | Which genome was used in mapping (hg19, hg38, etc.).                                    |
| limit          | A limit on how many lines to read.  |

**Value**

A list of Fusion objects.

**Examples**

```
starfusionData <- system.file(
  "extdata",
  "star-fusion.fusion_candidates.final.abridged.txt",
  package = "chimeraviz")
fusions <- import_starfusion(starfusionData, "hg19", 3)
# This should import a list of 3 fusions described in Fusion objects.
```

---

PartnerGene-class      *An S4 class to represent a gene partner in a fusion*

---

### Description

The PartnerGene class represents one of the genes in a fusion event.

### Slots

name Character containing name of the gene.  
ensembl\_id Character containing ensembl id for the gene.  
chromosome Character containing chromosome name.  
breakpoint Numeric containing the fusion breakpoint.  
strand Character containing gene strand.  
junction\_sequence Biostrings::DNASTring containing the sequence right before/after the fusion breakpoint.  
transcripts GenomicRanges::GRangesList containing three GenomicRanges::Granges() objects, one for each "transcript type". The transcript types are: 1) Transcripts where the fusion breakpoint hits an exon boundary, 2) transcripts where the fusion breakpoint is within an exon, 3) transcripts where the fusion breakpoint is within an intron.

---

partner\_gene\_ensembl\_id  
*Get the Ensembl ID from a PartnerGene object*

---

### Description

This getter retrieves the Ensembl ID from a PartnerGene object  
This sets the Ensembl ID of a PartnerGene object.

### Usage

```
partner_gene_ensembl_id(x)

## S4 method for signature 'PartnerGene'
partner_gene_ensembl_id(x)

partner_gene_ensembl_id(object) <- value

## S4 replacement method for signature 'PartnerGene'
partner_gene_ensembl_id(object) <- value
```

### Arguments

x                    The PartnerGene object you wish to retrieve the Ensembl ID for.  
object                The PartnerGene object you wish to set a new Ensembl ID for.  
value                 The new Ensembl ID.

**Value**

The upstream fusion partner gene Ensembl ID.

**Examples**

```
# Load data
defuseData <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuseData, "hg19", 1)
fusion <- fusions[[1]]
# Get the Ensembl ID from the upstream fusion partner gene
partner_gene_ensembl_id(upstream_partner_gene(fusion))

# Load data
defuseData <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuseData, "hg19", 1)
fusion <- fusions[[1]]
# Set the downstream PartnerGene object to be the same as the upstream
# PartnerGene object
partner_gene_ensembl_id(upstream_partner_gene(fusion)) <- "test"
```

---

`partner_gene_junction_sequence`

*Get the junction sequence from a PartnerGene object*

---

**Description**

This getter retrieves the junction sequence from a PartnerGene object

**Usage**

```
partner_gene_junction_sequence(x)

## S4 method for signature 'PartnerGene'
partner_gene_junction_sequence(x)
```

**Arguments**

`x` The PartnerGene object you wish to retrieve the junction sequence for.

**Value**

The upstream fusion partner gene junction sequence.

## Examples

```
# Load data
defuseData <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuseData, "hg19", 1)
fusion <- fusions[[1]]
# Get the junction sequence from the upstream fusion partner gene
partner_gene_junction_sequence(upstream_partner_gene(fusion))
```

---

|             |   |
|-------------|---|
| plot_circle | <i>Create a circle plot of the given fusions.</i> |
|-------------|---|

---

## Description

This function takes a list of Fusion objects and creates a circle plot indicating which chromosomes the fusion genes in the list consists of.

## Usage

```
plot_circle(fusion_list)
```

## Arguments

fusion\_list      A list of Fusion objects.

## Details

Note that only a limited number of gene names can be shown in the circle plot due to the limited resolution of the plot. RCircos will automatically limit the number of gene names shown if there are too many.

## Value

Creates a circle plot.

## Examples

```
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 3)
# Temporary file to store the plot
pngFilename <- tempfile(
  pattern = "circlePlot",
  fileext = ".png",
  tmpdir = tempdir())
# Open device
png(pngFilename, width = 1000, height = 750)
# Plot!
```

```
plot_circle(fusions)
# Close device
dev.off()
```

---

|             |  |
|-------------|--|
| plot_fusion | <i>Plot a fusion event with transcripts, coverage and ideograms.</i> |
|-------------|--|

---

## Description

This function creates a plot with information about transcripts, coverage, location and more.

## Usage

```
plot_fusion(
  fusion,
  edb = NULL,
  bamfile = NULL,
  which_transcripts = "exonBoundary",
  ylim = c(0, 1000),
  non_ucsc = TRUE,
  reduce_transcripts = FALSE,
  bedgraphfile = NULL
)
```

```
plot_fusion_separate(
  fusion,
  edb,
  bamfile = NULL,
  which_transcripts = "exonBoundary",
  ylim = c(0, 1000),
  non_ucsc = TRUE,
  reduce_transcripts = FALSE,
  bedgraphfile = NULL
)
```

```
plot_fusion_together(
  fusion,
  edb,
  bamfile = NULL,
  which_transcripts = "exonBoundary",
  ylim = c(0, 1000),
  non_ucsc = TRUE,
  reduce_transcripts = FALSE,
  bedgraphfile = NULL
)
```

## Arguments

|        |   |
|--------|---|
| fusion | The Fusion object to plot.                            |
| edb    | The ensemblDb object that will be used to fetch data. |

|                    |  |
|--------------------|--|
| bamfile            | The bamfile with RNA-seq data.   |
| which_transcripts  | This character vector decides which transcripts are to be plotted. Can be "exonBoundary", "withinExon", "withinIntron", "intergenic", or a character vector with specific transcript ids. Default value is "exonBoundary".           |
| ylim               | Limits for the coverage y-axis.  |
| non_ucsc           | Boolean indicating whether or not the bamfile used has UCSC- styled chromosome names (i.e. with the "chr" prefix). Setting this to true lets you use a bamfile with chromosome names like "1" and "X", instead of "chr1" and "chrX". |
| reduce_transcripts | Boolean indicating whether or not to reduce all transcripts into a single transcript for each partner gene.  |
| bedgraphfile       | A bedGraph file to use instead of the bamfile to plot coverage.  |

### Details

plot\_fusion() will dispatch to either plot\_fusion\_separate() or plot\_fusion\_together(). plot\_fusion\_separate() will plot the fusion gene partners in separate graphs shown next to each other, while plot\_fusion\_together() will plot the fusion gene partners in the same graph with the same x-axis. plot\_fusion() will dispatch to plot\_fusion\_together() if the fusion gene partners are on the same strand, same chromosome and are close together ( $\leq 50,000$  bp apart).

### Value

Creates a fusion plot.

### Examples

```
# Load data and example fusion event
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 1)
fusion <- get_fusion_by_id(fusions, 5267)
# Load edb
edbSqliteFile <- system.file(
  "extdata",
  "Homo_sapiens.GRCh37.74.sqlite",
  package="chimeraviz")
edb <- ensemblDb::EnsDb(edbSqliteFile)
# bamfile with reads in the regions of this fusion event
bamfile5267 <- system.file(
  "extdata",
  "fusion5267and11759reads.bam",
  package="chimeraviz")
# Temporary file to store the plot
pngFilename <- tempfile(
  pattern = "fusionPlot",
  fileext = ".png",
  tmpdir = tempdir())
# Open device
png(pngFilename, width = 1000, height = 750)
# Plot!
```

```

plot_fusion(
  fusion = fusion,
  bamfile = bamfile5267,
  edb = edb,
  non_ucsc = TRUE)
# Close device
dev.off()

# Example using a .bedGraph file instead of a .bam file:
# Load data and example fusion event
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 1)
fusion <- get_fusion_by_id(fusions, 5267)
# Load edb
edbSqliteFile <- system.file(
  "extdata",
  "Homo_sapiens.GRCh37.74.sqlite",
  package="chimeraviz")
edb <- ensemblDb::EnsDb(edbSqliteFile)
# bedgraphfile with coverage data from the regions of this fusion event
bedgraphfile <- system.file(
  "extdata",
  "fusion5267and11759reads.bedGraph",
  package="chimeraviz")
# Temporary file to store the plot
pngFilename <- tempfile(
  pattern = "fusionPlot",
  fileext = ".png",
  tmpdir = tempdir())
# Open device
png(pngFilename, width = 1000, height = 750)
# Plot!
plot_fusion(
  fusion = fusion,
  bedgraphfile = bedgraphfile,
  edb = edb,
  non_ucsc = TRUE)
# Close device
dev.off()

```

---

plot\_fusion\_reads      *Create a plot of the reads supporting the given fusion.*

---

### Description

This function takes a Fusion object and plots the reads supporting the fusion on top of the fusion sequence (fusion@junction\_sequence), provided that add\_fusion\_reads\_alignment() has been run earlier in order to add fusion reads alignment data to the fusion object.

### Usage

```
plot_fusion_reads(fusion, show_all_nucleotides = TRUE, nucleotide_amount = 10)
```

**Arguments**

`fusion`            The Fusion object to plot.

`show_all_nucleotides`  
                     Boolean indicating whether or not to show all nucleotides. If FALSE, then only `nucleotide_amount` amount of nucleotides will be shown on each end of the fusion junction. If TRUE, then the whole fusion junction sequence will be shown.

`nucleotide_amount`  
                     The number of nucleotides to show on each end of the fusion junction sequence. Defaults to 10. Only applicable if `show_all_nucleotides` is set to TRUE.

**Details**

Note that the package used for plotting, Gviz, is strict on chromosome names. If the plot produced doesn't show the reads, the problem might be solved by naming the fusion sequence "chrNA".

**Value**

Creates a fusion reads plot.

**See Also**

`add_fusion_reads_alignment`

**Examples**

```
# Load data
defuseData <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuseData, "hg19", 1)
# Find the specific fusion we have aligned reads for
fusion <- get_fusion_by_id(fusions, 5267)
bamfile <- system.file(
  "extdata",
  "5267readsAligned.bam",
  package="chimeraviz")
# Add the bam file of aligned fusion reads to the fusion object
fusion <- add_fusion_reads_alignment(fusion, bamfile)
# Temporary file to store the plot
pngFilename <- tempfile(
  pattern = "fusionPlot",
  fileext = ".png",
  tmpdir = tempdir())
# Calculate image size based on supporting reads and length of junction
# sequence.
imageWidth <- (nchar(partner_gene_junction_sequence(upstream_partner_gene(fusion))) +
  nchar(partner_gene_junction_sequence(downstream_partner_gene(fusion)))) * 15
imageHeight <- (fusion_split_reads_count(fusion)+fusion_spanning_reads_count(fusion)) * 20
# Open device
png(pngFilename, width = imageWidth, height = imageHeight)
# Now we can plot
plot_fusion_reads(fusion)
# Close device
dev.off()
```

---

`plot_fusion_transcript`*Plot possible fusion transcripts based on annotation.*

---

## Description

This function takes a fusion object and an ensemblDb object and plots the reduced version of the fusion transcript. This transcript consist of the "mashed together" version of all possible fusion transcripts based on known annotations. If a bamfile is specified, the fusion transcript will be plotted with coverage information.

## Usage

```
plot_fusion_transcript(  
  fusion,  
  edb = NULL,  
  bamfile = NULL,  
  which_transcripts = "exonBoundary",  
  bedgraphfile = NULL  
)
```

## Arguments

|                                |  |
|--------------------------------|--|
| <code>fusion</code>            | The Fusion object to plot.   |
| <code>edb</code>               | The edb object that will be used to fetch data.  |
| <code>bamfile</code>           | The bamfile with RNA-seq data.   |
| <code>which_transcripts</code> | This character vector decides which transcripts are to be plotted. Can be "exonBoundary", "withinExon", "withinIntron", "intergenic", or a character vector with specific transcript ids. Default value is "exonBoundary". |
| <code>bedgraphfile</code>      | A bedGraph file to use instead of the bamfile to plot coverage.  |

## Details

Note that the transcript database used (the edb object) must have the same seqnames as any bamfile used. Otherwise the coverage data will be wrong.

## Value

Creates a fusion transcript plot.

## Examples

```
# Load data and example fusion event  
defuse833ke <- system.file(  
  "extdata",  
  "defuse_833ke_results.filtered.tsv",  
  package="chimeraviz")  
fusions <- import_defuse(defuse833ke, "hg19", 1)
```

```
fusion <- get_fusion_by_id(fusions, 5267)
# Load edb
edbSqliteFile <- system.file(
  "extdata",
  "Homo_sapiens.GRCh37.74.sqlite",
  package="chimeraviz")
edb <- ensemblDb::EnsDb(edbSqliteFile)
# bamfile with reads in the regions of this fusion event
bamfile5267 <- system.file(
  "extdata",
  "fusion5267and11759reads.bam",
  package="chimeraviz")
# Temporary file to store the plot
pngFilename <- tempfile(
  pattern = "fusionPlot",
  fileext = ".png",
  tmpdir = tmpdir())
# Open device
png(pngFilename, width = 500, height = 500)
# Plot!
plot_fusion_transcript(
  fusion = fusion,
  bamfile = bamfile5267,
  edb = edb)
# Close device
dev.off()

# Example using a .bedGraph file instead of a .bam file:
# Load data and example fusion event
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 1)
fusion <- get_fusion_by_id(fusions, 5267)
# Load edb
edbSqliteFile <- system.file(
  "extdata",
  "Homo_sapiens.GRCh37.74.sqlite",
  package="chimeraviz")
edb <- ensemblDb::EnsDb(edbSqliteFile)
# bedgraphfile with coverage data from the regions of this fusion event
bedgraphfile <- system.file(
  "extdata",
  "fusion5267and11759reads.bedGraph",
  package="chimeraviz")
# Temporary file to store the plot
pngFilename <- tempfile(
  pattern = "fusionPlot",
  fileext = ".png",
  tmpdir = tmpdir())
# Open device
png(pngFilename, width = 500, height = 500)
# Plot!
plot_fusion_transcript(
  fusion = fusion,
  bamfile = bamfile5267,
```

```

    edb = edb)
# Close device
dev.off()

```

---

```

plot_fusion_transcripts_graph
    Graph plot of possible fusion transcripts.

```

---

## Description

This function takes a fusion object and a TranscriptDb object and plots a graph showing the possible fusion transcripts.

## Usage

```

plot_fusion_transcripts_graph(
  fusion,
  edb = NULL,
  which_transcripts = "exonBoundary",
  rankdir = "TB"
)

```

## Arguments

|                   |  |
|-------------------|--|
| fusion            | The Fusion object to plot.   |
| edb               | The edb object that will be used to fetch data.  |
| which_transcripts | This character vector decides which transcripts are to be plotted. Can be "exonBoundary", "withinExon", "withinIntron", "intergenic", or a character vector with specific transcript ids. Default value is "exonBoundary". |
| rankdir           | Choose whether the graph should be plotted from left to right ("LR"), or from top to bottom ("TB"). This parameter is given to Rgraphviz::plot().  |

## Value

Creates a fusion transcripts graph plot.

## Examples

```

# Load data and example fusion event
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 1)
fusion <- get_fusion_by_id(fusions, 5267)
# Load edb
edbSqliteFile <- system.file(
  "extdata",
  "Homo_sapiens.GRCh37.74.sqlite",
  package="chimeraviz")

```

```

edb <- ensemblDb::EnsDb(edbSqliteFile)
# Temporary file to store the plot
pngFilename <- tempfile(
  pattern = "fusionPlot",
  fileext = ".png",
  tmpdir = tmpdir())
# Open device
png(pngFilename, width = 500, height = 500)
# Plot!
plot_fusion_transcripts_graph(
  fusion = fusion,
  edb = edb)
# Close device
dev.off()

```

---

```
plot_fusion_transcript_with_protein_domain
```

*Plot a specific fusion transcript with protein domain annotations*

---

## Description

This function takes a fusion object, an ensemblDb object, a bedfile with protein domain data and two specific transcript ids. The function plots the specific fusion transcript along with annotations of protein domains. If a bamfile is specified, the fusion transcript will be plotted with coverage information.

## Usage

```

plot_fusion_transcript_with_protein_domain(
  fusion,
  edb = NULL,
  bamfile = NULL,
  bedfile = NULL,
  gene_upstream_transcript = "",
  gene_downstream_transcript = "",
  plot_downstream_protein_domains_if_fusion_is_out_of_frame = FALSE
)

```

## Arguments

|   |   |
|---|---|
| fusion  | The Fusion object to plot.  |
| edb   | The edb object that will be used to fetch data.   |
| bamfile   | The bamfile with RNA-seq data.  |
| bedfile   | The bedfile with protein domain data.   |
| gene_upstream_transcript                                  | The transcript id for the upstream gene.  |
| gene_downstream_transcript                                | The transcript id for the downstream gene.  |
| plot_downstream_protein_domains_if_fusion_is_out_of_frame | Setting this to true makes the function plot protein domains in the downstream gene even though the fusion is out of frame. |

**Details**

Note that the transcript database used (the edb object) must have the same seqnames as any bamfile used. Otherwise the coverage data will be wrong.

**Value**

Creates a fusion transcript plot with annotations of protein domains.

**Examples**

```
# Load data and example fusion event
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 1)
fusion <- get_fusion_by_id(fusions, 5267)
# Select transcripts
gene_upstream_transcript <- "ENST00000434290"
gene_downstream_transcript <- "ENST00000370031"
# Load edb
edbSqliteFile <- system.file(
  "extdata",
  "Homo_sapiens.GRCh37.74.sqlite",
  package="chimeraviz")
edb <- ensemblDb::EnsDb(edbSqliteFile)
# bamfile with reads in the regions of this fusion event
bamfile5267 <- system.file(
  "extdata",
  "fusion5267and11759reads.bam",
  package="chimeraviz")
# bedfile with protein domains for the transcripts in this example
bedfile <- system.file(
  "extdata",
  "protein_domains_5267.bed",
  package="chimeraviz")
# Temporary file to store the plot
pngFilename <- tempfile(
  pattern = "fusionPlot",
  fileext = ".png",
  tmpdir = tempdir())
# Open device
png(pngFilename, width = 500, height = 500)
# Plot!
plot_fusion_transcript_with_protein_domain(
  fusion = fusion,
  edb = edb,
  bamfile = bamfile5267,
  bedfile = bedfile,
  gene_upstream_transcript = gene_upstream_transcript,
  gene_downstream_transcript = gene_downstream_transcript,
  plot_downstream_protein_domains_if_fusion_is_out_of_frame = TRUE)
# Close device
dev.off()
```

---

|                  |  |
|------------------|--|
| plot_transcripts | <i>Plot transcripts for each partner gene in a fusion event.</i> |
|------------------|--|

---

### Description

This function takes a fusion object and an ensemblDb object and plots transcripts for both genes, showing which parts of each genes are included in the fusion event. If the bamfile parameter is set, then the coverage is plotted beneath the transcripts.

### Usage

```
plot_transcripts(
  fusion,
  edb = NULL,
  bamfile = NULL,
  which_transcripts = "exonBoundary",
  non_ucsc = TRUE,
  ylim = c(0, 1000),
  reduce_transcripts = FALSE,
  bedgraphfile = NULL
)
```

### Arguments

|                    |  |
|--------------------|--|
| fusion             | The Fusion object to plot.   |
| edb                | The edb object that will be used to fetch data.  |
| bamfile            | The bamfile with RNA-seq data.   |
| which_transcripts  | This character vector decides which transcripts are to be plotted. Can be "exonBoundary", "withinExon", "withinIntron", "intergenic", or a character vector with specific transcript ids. Default value is "exonBoundary".           |
| non_ucsc           | Boolean indicating whether or not the bamfile used has UCSC- styled chromosome names (i.e. with the "chr" prefix). Setting this to true lets you use a bamfile with chromosome names like "1" and "X", instead of "chr1" and "chrX". |
| ylim               | Limits for the coverage y-axis.  |
| reduce_transcripts | Boolean indicating whether or not to reduce all transcripts into a single transcript for each partner gene.  |
| bedgraphfile       | A bedGraph file to use instead of the bamfile to plot coverage.  |

### Value

Creates a fusion transcripts plot.

### Examples

```
# Load data and example fusion event
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
```

```

    package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 1)
fusion <- get_fusion_by_id(fusions, 5267)
# Load edb
edbSqliteFile <- system.file(
  "extdata",
  "Homo_sapiens.GRCh37.74.sqlite",
  package="chimeraviz")
edb <- ensemblDb::EnsDb(edbSqliteFile)
# bamfile with reads in the regions of this fusion event
bamfile5267 <- system.file(
  "extdata",
  "fusion5267and11759reads.bam",
  package="chimeraviz")
# Temporary file to store the plot
pngFilename <- tempfile(
  pattern = "fusionPlot",
  fileext = ".png",
  tmpdir = tmpdir())
# Open device
png(pngFilename, width = 500, height = 500)
# Plot!
plot_transcripts(
  fusion = fusion,
  edb = edb,
  bamfile = bamfile5267,
  non_ucsc = TRUE)
# Close device
dev.off()

# Example using a .bedGraph file instead of a .bam file:
# Load data and example fusion event
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 1)
fusion <- get_fusion_by_id(fusions, 5267)
# Load edb
edbSqliteFile <- system.file(
  "extdata",
  "Homo_sapiens.GRCh37.74.sqlite",
  package="chimeraviz")
edb <- ensemblDb::EnsDb(edbSqliteFile)
# bedgraphfile with coverage data from the regions of this fusion event
bedgraphfile <- system.file(
  "extdata",
  "fusion5267and11759reads.bedGraph",
  package="chimeraviz")
# Temporary file to store the plot
pngFilename <- tempfile(
  pattern = "fusionPlot",
  fileext = ".png",
  tmpdir = tmpdir())
# Open device
png(pngFilename, width = 500, height = 500)
# Plot!

```

```

plot_transcripts(
  fusion = fusion,
  edb = edb,
  bedgraphfile = bedgraphfile,
  non_ucsc = TRUE)
# Close device
dev.off()

```

---

|              |                      |
|--------------|----------------------|
| raw_chimpipe | <i>ChimPipe data</i> |
|--------------|----------------------|

---

### Description

Documentation for the ChimPipe example data.

Documentation for the SQUID example data.

### chimericJunctions\_MCF-7.txt

This is example data from the ChimPipe tutorial all-in-one package located at <https://chimpipe.readthedocs.io/en/latest/tutorial/all-in-one-package> It was downloaded March 10th 2020

### squid\_hcc1954\_sv.txt

This is example data for SQUID provided on GitHub here: <https://github.com/Kingsford-Group/squid/issues/20#issuecomment598888472> It was downloaded March 17th 2020

---

|                  |                                  |
|------------------|----------------------------------|
| raw_cytobandhg19 | <i>Cytoband information HG19</i> |
|------------------|----------------------------------|

---

### Description

Cytoband information for the HG19 assembly from UCSC. Downloaded from <http://hgdownload.cse.ucsc.edu/goldenpath>

### UCSC.HG19.Human.CytoBandIdeogram.txt

This data is used with RCircos in `plot_circle()`.

---

|                  |                                   |
|------------------|-----------------------------------|
| raw_cytobandhg38 | <i>Cytoband information HG138</i> |
|------------------|-----------------------------------|

---

### Description

Cytoband information for the HG38 assembly from UCSC. Downloaded from <http://hgdownload.cse.ucsc.edu/goldenpath>

### Details

All `_alt` or `_random` entries has been manually removed, as has the `chrM` entry.

### UCSC.HG38.Human.CytoBandIdeogram.txt

This data is used with RCircos in `plot_circle()`.

---

|            |                    |
|------------|--------------------|
| raw_defuse | <i>deFuse data</i> |
|------------|--------------------|

---

### Description

Documentation for the deFuse example data.

#### **defuse\_833ke\_results.filtered.tsv**

This file has the results from a run of deFuse-0.7.0 on the 833ke cell line. The program was ran with the standard configuration, but with the parameter `span_count_threshold=5` instead of the standard 3. The resulting `results.filtered.tsv` file was then manually filtered to only include 17 fusion events in the interest of saving computing time for tests and examples. The original results contained 171 fusion events.

#### **reads\_supporting\_defuse\_fusion\_5267.\*.fq**

These two files, `reads_supporting_defuse_fusion_5267.1.fq` and `reads_supporting_defuse_fusion_5267.2.fq`, contains the reads that support the fusion event with `cluster_id 5267`.

#### **5267readsAligned.bam**

The bamfile `5267readsAligned.bam` and the `5267readsAligned.bam.bai` index file contains the reads supporting the fusion event with `cluster_id 5267` aligned to the fusion sequence. It is used with `plot_fusion_reads()`.

---

|                |                        |
|----------------|------------------------|
| raw_ericscript | <i>EricScript data</i> |
|----------------|------------------------|

---

### Description

Documentation for the EricScript example data.

#### **ericscript\_SRR1657556.results.total.tsv**

This is example data thankfully provided by EricScript author Matteo Benelli.

---

raw\_fusion5267proteindomains  
*protein\_domains\_5267 bed file*

---

### Description

Documentation for the protein\_domains\_5267.bed file containing protein domains for the genes in the fusion with cluster\_id=5267.

### protein\_domains\_5267.bed

This file is an excerpt from a larger file that we created by: - downloading domain name annotation from Pfam database (PfamA version 31) and domain region annotation from Ensembl database through BioMart API - switching the domain coordinates in the protein level to these in transcript level.

---

raw\_fusion5267reads *Fusion5267and11759 bamfile*

---

### Description

Documentation for the fusion5267and11759reads.bam file containing reads mapped to the region where the genes in the fusions with cluster\_id=5267 and cluster\_id=11759 is.

### fusion5267and11759reads.bam

This file is the result of running these commands:

```
samtools view -b original_bamfile.bam "1:28831455-28866812" "1:109189912-109205148" "12:8608225-8677832" > fusion5267and11759reads.bam samtools index fusion5267and11759reads.bam fusion5267and11759reads.b
```

where we extract the reads mapping to the region where we know the fusions with cluster\_id=5267 and cluster\_id=11759 from the deFuse example data is.

The original\_bamfile.bam is from a study of the 833KE cell line by Andreas M. Hoff et al., documented in the paper [Identification of Novel Fusion Genes in Testicular Germ Cell Tumors](<http://cancerres.aacrjournals.org>).

---

raw\_fusion5267readsBedGraph  
*Fusion5267and11759 bedGraph file*

---

### Description

Documentation for the fusion5267and11759reads.bedGraph file containing read count data from the regions of the fusion event with cluster\_id=5267.

### fusion5267and11759reads.bedGraph

This file is the result of running this command:

```
bedtools genomecov -ibam fusion5267and11759reads.bam -bg > fusion5267and11759reads.bam.bedGraph
```

fusion5267and11759reads.bam has its own documentation entry for how it was created.

---

raw\_fusioncatcher      *Fusioncatcher data*

---

### Description

Documentation for the Fusioncatcher example data.

#### fusioncatcher\_833ke\_final-list-candidate-fusion-genes.txt

This file has the results from a run of Fusioncatcher-0.99.3e on the 833ke cell line. The program was ran with the standard configuration file and with the parameters "-p 8 -z -keep-preliminary".

---

raw\_fusionmap      *FusionMap data*

---

### Description

Documentation for the FusionMap example data.

#### FusionMap\_01\_TestDataset\_InputFastq.FusionReport.txt

This is example data provided with the FusionMap version released 2015-03-31.

---

raw\_Homo\_sapiens.GRCh37.74  
                                  *Homo\_sapiens.GRCh37.74\_subset.gtf*

---

### Description

Homo\_sapiens.GRCh37.74\_subset.gtf

#### Homo\_sapiens.GRCh37.74\_subset.gtf

The Homo\_sapiens.GRCh37.74.gtf file is a subset version of the Ensembl Homo\_sapiens.GRCh37.74.gtf file, located here: [ftp://ftp.ensembl.org/pub/release-74/gtf/homo\\_sapiens](ftp://ftp.ensembl.org/pub/release-74/gtf/homo_sapiens). This gtf file contains transcripts for the partner genes in two of the fusion transcripts from the deFuse example data provided with this package: The fusion transcript with cluster\_id=5267, and the fusion transcript with cluster\_id=11759.

The file is the result of running this command:

```
# grep "ENST00000373831\|ENST00000373832\|ENST00000373833\|ENST00000398958\|ENST00000411533\|ENST00000411534" Homo_sapiens.GRCh37.74.gtf > Homo_sapiens.GRCh37.74_subset.gtf
```

The transcript names given in the command above are all transcripts available for the genes CLEC6A, CLEC4D, HENMT1, and RCC1 in Ensembl version 74.

#### Homo\_sapiens.GRCh37.74.sqlite

The Homo\_sapiens.GRCh37.74.sqlite file is the sqlite database that the EnsemblDb package creates from the corresponding gtf file. It was created using this command:

```
# ensDbFromGtf( # gtf = "Homo_sapiens.GRCh37.74_subset.gtf", # organism = "Homo_sapiens", # genomeVersion = "GRCh37", # version = 74)
```

---

|              |                      |
|--------------|----------------------|
| raw_infusion | <i>InFusion data</i> |
|--------------|----------------------|

---

**Description**

Documentation for the InFusion example data.

**infusion\_fusions.txt**

This is example data from the InFusion getting started page located at <https://bitbucket.org/kokonech/infusion/wiki/GettingStarted>

---

|           |                   |
|-----------|-------------------|
| raw_jaffa | <i>JAFFA data</i> |
|-----------|-------------------|

---

**Description**

Documentation for the JAFFA example data.

**jaffa\_results.csv**

This is example data from the described JAFFA example run documented at <https://github.com/Oshlack/JAFFA/wiki/Example>

---

|              |                      |
|--------------|----------------------|
| raw_oncofuse | <i>oncofuse data</i> |
|--------------|----------------------|

---

**Description**

Documentation for the oncofuse example data.

**oncofuse.outfile**

The example output from oncofuse was kindly provided by Lavinia G here: <https://github.com/stianlagstad/chimeraviz/issues/409773158>

---

|           |                   |
|-----------|-------------------|
| raw_prada | <i>PRADA data</i> |
|-----------|-------------------|

---

**Description**

Documentation for the PRADA example data.

**PRADA.acc.fusion.fq.TAF.tsv**

This is example data thankfully provided by PRADA authors Siyuan Zheng and Roeland Verhaak.

---

|              |                      |
|--------------|----------------------|
| raw_soapfuse | <i>SOAPfuse data</i> |
|--------------|----------------------|

---

**Description**

Documentation for the SOAPfuse example data.

**soapfuse\_833ke\_final.Fusion.specific.for.genes**

This file has the results from a run of soapfuse-1.26 on the 833ke cell line. The program was ran with the standard configuration file.

---

|                |                         |
|----------------|-------------------------|
| raw_starfusion | <i>STAR-Fusion data</i> |
|----------------|-------------------------|

---

**Description**

Documentation for the STAR-Fusion example data.

**star-fusion.fusion\_candidates.final.abridged.txt**

This example data was retrieved from the STAR-Fusion github page June 2.nd 2017.

---

|                   |   |
|-------------------|---|
| select_transcript | <i>Select which transcript to use (for plotting) for a GenePartner object</i> |
|-------------------|---|

---

**Description**

This function takes a GenePartner object and creates a transcript data.frame with transcript information, including only the transcripts given by the parameter which\_transcripts

**Usage**

```
select_transcript(gene_partner, which_transcripts = "exonBoundary")
```

**Arguments**

gene\_partner The GenePartner object to select a transcript for.

which\_transcripts

This character vector decides which transcripts are to be plotted. Can be "exonBoundary", "withinExon", "withinIntron", "intergenic", or a character vector with specific transcript ids. Default value is "exonBoundary".

**Details**

select\_transcript() selects which transcript to create by this prioritization:

1. Exon boundary transcripts.
2. Within exon transcripts.
3. Within intron transcripts.
4. Intergenic transcripts.

**Value**

A data.frame with transcript data.

**Examples**

```
# Load data and example fusion event
defuse833ke <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833ke, "hg19", 1)
fusion <- get_fusion_by_id(fusions, 5267)
# Load edb
edbSqliteFile <- system.file(
  "extdata",
  "Homo_sapiens.GRCh37.74.sqlite",
  package="chimeraviz")
edb <- ensemblDb::EnsDb(edbSqliteFile)
# Get transcripts
fusion <- get_transcripts_ensembl_db(fusion, edb)
# Select transcript
transcriptsA <- select_transcript(upstream_partner_gene(fusion))
```

---

show,Fusion-method      *Show method for the Fusion class.*

---

**Description**

Show method for the Fusion class.

**Usage**

```
## S4 method for signature 'Fusion'
show(object)
```

**Arguments**

object            A Fusion object

**Value**

Shows information about a Fusion object.

---

show,PartnerGene-method

*Show method for the PartnerGene class.*

---

### Description

Show method for the PartnerGene class.

### Usage

```
## S4 method for signature 'PartnerGene'  
show(object)
```

### Arguments

object            A PartnerGene object

### Value

Shows information about a PartnerGene object.

---

split\_on\_utr\_and\_add\_feature

*Split GRanges object based on cds*

---

### Description

This function will look for ranges (exons) in the GRanges object that has the coding DNA sequence starting or stopping within it. If found, these exons are split, and each exon in the GRanges object will be tagged as either "protein\_coding", "5utr", or "3utr". The returned GRanges object will have feature values set in mcols(gr)\$feature reflecting this.

### Usage

```
split_on_utr_and_add_feature(gr)
```

### Arguments

gr                The GRanges object we want to split and tag with feature info.

### Value

An updated GRanges object with feature values set.

**Examples**

```

# Load fusion data and choose a fusion object:
defuseData <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuseData, "hg19", 1)
fusion <- get_fusion_by_id(fusions, 5267)
# Create edb object
edbSqliteFile <- system.file(
  "extdata",
  "Homo_sapiens.GRCh37.74.sqlite",
  package="chimeraviz")
edb <- ensemblDb::EnsDb(edbSqliteFile)
# Get all exons for all transcripts in the genes in the fusion transcript
allTranscripts <- ensemblDb::exonsBy(
  edb,
  filter = list(
    AnnotationFilter::GeneIdFilter(
      c(
        partner_gene_ensembl_id(upstream_partner_gene(fusion)),
        partner_gene_ensembl_id(downstream_partner_gene(fusion))))),
  columns = c(
    "gene_id",
    "gene_name",
    "tx_id",
    "tx_cds_seq_start",
    "tx_cds_seq_end",
    "exon_id"))
# Extract one of the GRanges objects
gr <- allTranscripts[[1]]
# Check how many ranges there are here
length(gr)
# Should be 9 ranges
# Split the ranges containing the cds start/stop positions and add feature
# values:
gr <- split_on_utr_and_add_feature(gr)
# Check the length again
length(gr)
# Should be 11 now, as the range containing the cds_start position and the
# range containing the cds_stop position has been split into separate ranges

```

---

upstream\_partner\_gene *Get the upstream fusion partner gene*

---

**Description**

This getter retrieves the upstream PartnerGene object.

This sets the upstream PartnerGene object of a Fusion object

## Usage

```
upstream_partner_gene(x)

## S4 method for signature 'Fusion'
upstream_partner_gene(x)

upstream_partner_gene(object) <- value

## S4 replacement method for signature 'Fusion'
upstream_partner_gene(object) <- value
```

## Arguments

|        |   |
|--------|---|
| x      | The Fusion object you wish to retrieve the upstream PartnerGene object for. |
| object | The Fusion object you wish to set a new upstream PartnerGene object for.    |
| value  | The new PartnerGene object.   |

## Value

The upstream PartnerGene object.

## Examples

```
# Load data
defuseData <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuseData, "hg19", 1)
fusion <- fusions[[1]]
# Get the upstream fusion partner gene
upstream_partner_gene(fusion)

# Load data
defuseData <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuseData, "hg19", 1)
fusion <- fusions[[1]]
# Set the upstream PartnerGene object to be the same as the downstream
# PartnerGene object
upstream_partner_gene(fusion) <- downstream_partner_gene(fusion)
```

---

write\_fusion\_reference

*Write fusion junction sequence to a fasta file*

---

## Description

This function will write the fusion sequence to a fasta file, using `Biostring::writeXStringSet()`.

**Usage**

```
write_fusion_reference(fusion, filename)
```

**Arguments**

|          |  |
|----------|--|
| fusion   | The Fusion object we want to create a fasta file from. |
| filename | The filename to write to.                              |

**Value**

Writes the fusion junction sequence to the given filename.

**Examples**

```
# Import the filtered defuse results
defuse833keFiltered <- system.file(
  "extdata",
  "defuse_833ke_results.filtered.tsv",
  package="chimeraviz")
fusions <- import_defuse(defuse833keFiltered, "hg19", 1)
# Get a specific fusion
fusion <- get_fusion_by_id(fusions, 5267)
# Create temporary file to hold the fusion sequence
fastaFileOut <- tempfile(pattern = "fusionSequence", tmpdir = tempdir())
# Write fusion sequence to file
write_fusion_reference(fusion, fastaFileOut)
```

# Index

.fusions\_to\_gene\_label\_data  
    (chimeraviz-internals-fusions\_to\_gene\_label\_data), 4  
.fusions\_to\_link\_data  
    (chimeraviz-internals-fusions\_to\_link\_data), 5  
.scale\_list\_to\_interval  
    (chimeraviz-internals-scaleListToInterval), 5  
add\_fusion\_reads\_alignment, 3  
chimeraviz, 4  
chimeraviz-internals-fusions\_to\_gene\_label\_data, 4  
chimeraviz-internals-fusions\_to\_link\_data, 5  
chimeraviz-internals-scaleListToInterval, 5  
create\_fusion\_report, 6  
decide\_transcript\_category, 7  
down\_shift, 9  
downstream\_partner\_gene, 8  
downstream\_partner\_gene, Fusion-method  
    (downstream\_partner\_gene), 8  
downstream\_partner\_gene<-  
    (downstream\_partner\_gene), 8  
downstream\_partner\_gene<-, Fusion-method  
    (downstream\_partner\_gene), 8  
fetch\_reads\_from\_fastq, 10  
Fusion (Fusion-class), 11  
Fusion-class, 11  
fusion\_spanning\_reads\_count, 11  
fusion\_spanning\_reads\_count, Fusion-method  
    (fusion\_spanning\_reads\_count), 11  
fusion\_split\_reads\_count, 12  
fusion\_split\_reads\_count, Fusion-method  
    (fusion\_split\_reads\_count), 12  
fusion\_to\_data\_frame, 13  
get\_ensembl\_ids, 13  
get\_fusion\_by\_chromosome, 14  
get\_fusion\_by\_gene\_name, 15  
get\_fusion\_by\_id, 16  
get\_transcripts\_ensembl\_db, 16  
import\_aeron, 17  
import\_chimpipe, 18  
import\_defuse, 19  
import\_ericscript, 20  
import\_function\_non\_ucsc, 20  
import\_fusioncatcher, 21  
import\_fusionmap, 21  
import\_infusion, 22  
import\_jaffa, 23  
import\_oncofuse, 23  
import\_prada, 24  
import\_soapfuse, 25  
import\_squid, 25  
import\_starfusion, 26  
partner\_gene\_ensembl\_id, 27  
partner\_gene\_ensembl\_id, PartnerGene-method  
    (partner\_gene\_ensembl\_id), 27  
partner\_gene\_ensembl\_id<-  
    (partner\_gene\_ensembl\_id), 27  
partner\_gene\_ensembl\_id<-, PartnerGene-method  
    (partner\_gene\_ensembl\_id), 27  
partner\_gene\_junction\_sequence, 28  
partner\_gene\_junction\_sequence, PartnerGene-method  
    (partner\_gene\_junction\_sequence), 28  
PartnerGene (PartnerGene-class), 27  
PartnerGene-class, 27  
plot\_circle, 29  
plot\_fusion, 30  
plot\_fusion\_reads, 32  
plot\_fusion\_separate (plot\_fusion), 30  
plot\_fusion\_together (plot\_fusion), 30  
plot\_fusion\_transcript, 34  
plot\_fusion\_transcript\_with\_protein\_domain, 37  
plot\_fusion\_transcripts\_graph, 36  
plot\_transcripts, 39  
raw\_chimpipe, 41

raw\_cytobandhg19, 41  
raw\_cytobandhg38, 41  
raw\_defuse, 42  
raw\_ericscript, 42  
raw\_fusion5267proteindomains, 43  
raw\_fusion5267reads, 43  
raw\_fusion5267readsBedGraph, 43  
raw\_fusioncatcher, 44  
raw\_fusionmap, 44  
raw\_Homo\_sapiens.GRCh37.74, 44  
raw\_infusion, 45  
raw\_jaffa, 45  
raw\_oncofuse, 45  
raw\_prada, 45  
raw\_soapfuse, 46  
raw\_starfusion, 46  
  
select\_transcript, 46  
show, Fusion-method, 47  
show, PartnerGene-method, 48  
split\_on\_utr\_and\_add\_feature, 48  
  
upstream\_partner\_gene, 49  
upstream\_partner\_gene, Fusion-method  
    (upstream\_partner\_gene), 49  
upstream\_partner\_gene<-  
    (upstream\_partner\_gene), 49  
upstream\_partner\_gene<- , Fusion-method  
    (upstream\_partner\_gene), 49  
  
write\_fusion\_reference, 50