

# Package ‘goSorensen’

May 26, 2026

**Type** Package

**Title** Statistical inference based on the Sorensen-Dice dissimilarity and the Gene Ontology (GO)

**Version** 1.15.0

**Description** This package implements inferential methods to compare gene lists in terms of their biological meaning as expressed in the GO. The compared gene lists are characterized by cross-tabulation frequency tables of enriched GO items. Dissimilarity between gene lists is evaluated using the Sorensen-Dice index.

The fundamental guiding principle is that two gene lists are taken as similar if they share a great proportion of common enriched GO items.

**URL** <https://github.com/pablof1988/goSorensen>

**BugReports** <https://github.com/pablof1988/goSorensen/issues>

**Depends** R (>= 4.6)

**Imports** clusterProfiler, goProfiles, parallel, stats, stringr, withr

**Suggests** BiocManager, BiocStyle, knitr, rmarkdown, org.At.tair.db, org.Ag.eg.db, org.Bt.eg.db, org.Ce.eg.db, org.Cf.eg.db, org.Dm.eg.db, org.Dr.eg.db, org.EcSakai.eg.db, org.EcK12.eg.db, org.Gg.eg.db, org.Mm.eg.db, org.Mmu.eg.db, org.Rn.eg.db, org.Sc.sgd.db, org.Ss.eg.db, org.Pt.eg.db, org.Xl.eg.db, GO.db, ggplot2, ggrepel, DT, magick, AnnotationDbi, org.Hs.eg.db

**VignetteBuilder** knitr

**License** GPL-3

**Encoding** UTF-8

**LazyData** false

**NeedsCompilation** no

**biocViews** Annotation, GO, GeneSetEnrichment, Software, Microarray, Pathways, GeneExpression, MultipleComparison, GraphAndNetwork, Reactome, Clustering, KEGG

**Config/roxygen2/version** 8.0.0

**git\_url** <https://git.bioconductor.org/packages/goSorensen>

**git\_branch** devel

**git\_last\_commit** 2d4ad98

**git\_last\_commit\_date** 2026-05-12

**Repository** Bioconductor 3.24

**Date/Publication** 2026-05-25

**Author** Pablo Flores [aut, cre] (ORCID:

<<https://orcid.org/0000-0002-7156-8547>>),

Jordi Ocana [aut, ctb] (ORCID: <<https://orcid.org/0000-0002-4736-6996>>),

Alex Mantilla [aut, ctb] (ORCID:

<<https://orcid.org/0000-0001-7047-7072>>),

Alexandre Sanchez-Pla [ctb] (ORCID:

<<https://orcid.org/0000-0002-8673-7737>>),

Miquel Salicru [ctb] (ORCID: <<https://orcid.org/0000-0001-9644-5626>>)

**Maintainer** Pablo Flores <p\_flores@epoch.edu.ec>

## Contents

allBuildEnrichTable . . . . .	3
allContTabs . . . . .	5
allContTabsNoLevel . . . . .	5
allDissMatrx . . . . .	6
allDissMatrxNoLevel . . . . .	7
allEqTests . . . . .	7
allEqTestsNoLevel . . . . .	8
allEqTests_boot . . . . .	8
allEqTests_bootNoLevel . . . . .	9
allEquivTestSorensen . . . . .	10
allHclustThreshold . . . . .	12
allOncoGeneLists . . . . .	13
allSorenThreshold . . . . .	14
boot.tStat . . . . .	16
buildEnrichTable . . . . .	17
cont_all_BP . . . . .	20
cont_all_BP4 . . . . .	21
cont_atlas.sanger_BP . . . . .	22
cont_atlas.sanger_BP4 . . . . .	22
dissMatrx_BP . . . . .	23
dissMatrx_BP4 . . . . .	23
dSorensen . . . . .	24
duppSorensen . . . . .	26
enrichedIn . . . . .	30
enrichedInBP . . . . .	33
enrichedInBP4 . . . . .	34
eqTest_all_BP . . . . .	34
eqTest_all_BP4 . . . . .	35
eqTest_atlas.sanger_BP . . . . .	36
eqTest_atlas.sanger_BP4 . . . . .	36
equivTestSorensen . . . . .	37
fullEnrichedInBP . . . . .	40
fullEnrichedInBP4 . . . . .	41
getDissimilarity . . . . .	42
getEffNboot . . . . .	43
getNboot . . . . .	46
getPvalue . . . . .	48

getSE . . . . .	50
getTable . . . . .	51
getUpper . . . . .	53
gosorensen . . . . .	54
hclustThreshold . . . . .	56
nice2x2Table . . . . .	57
pbtGeneLists . . . . .	59
pruneClusts . . . . .	60
seSorensen . . . . .	60
sorenThreshold . . . . .	63
upgrade . . . . .	65

<b>Index</b>	<b>67</b>
--------------	-----------

---

allBuildEnrichTable	<i>Iterate buildEnrichTable along the specified GO ontologies and GO levels</i>
---------------------	---

---

## Description

Iterate buildEnrichTable along the specified GO ontologies and GO levels

## Usage

```
allBuildEnrichTable(
  x,
  geneUniverse,
  orgPackg,
  check.table = TRUE,
  ontos = c("BP", "CC", "MF"),
  GOLevels = GOLevels,
  keyType = "ENTREZID",
  storeEnrichedIn = TRUE,
  trace = TRUE,
  ...
)
```

## Arguments

x	object of class "list". Each of its elements must be a "character" vector of gene identifiers (e.g., ENTREZ). Then all pairwise contingency tables of joint enrichment are built between these gene lists, iterating the process for all specified GO ontologies and GO levels.
geneUniverse	character vector containing the universe of genes from where gene lists have been extracted. This vector must be obtained from the annotation package declared in orgPackg. For more details, refer to vignette <a href="#">goSorensen_Introduction</a> .
orgPackg	A string with the name of the genomic annotation package corresponding to a specific species to be analysed, which must be previously installed and activated. For more details, refer to vignette <a href="#">goSorensen_Introduction</a> .
check.table	Boolean. If TRUE (default), all resulting tables are checked by means of function nice2x2Table.

ontos	"character", GO ontologies to analyse. Defaults to <code>c("BP", "CC", "MF")</code> .
GOLevels	Integer vector of GO levels to analyze inside each selected ontology. If NULL, contingency tables are built without restricting the analysis to specific GO levels.
keyType	Character string specifying the type of gene identifier used in the input, such as "ENTREZID" or "SYMBOL".
storeEnrichedIn	logical, for each ontology and level under study, the matrix of enriched (GO terms) x (gene lists) TRUE/FALSE values, must be stored in the result?
trace	Logical. If TRUE (default), the (usually very time consuming) process of function <code>allBuildEnrichTable</code> is traced along the specified GO ontologies and levels.
...	extra parameters for function <code>buildEnrichTable</code> .

### Value

An object of class "allTableList". It is a list with as many components as GO ontologies have been analyzed.

If `GOLevels` is not NULL, each ontology component is itself a list with as many components as GO levels have been analyzed. Each of these elements is an object generated by `buildEnrichTable.list()`, that is, an object of class "tableList" containing all pairwise contingency tables of mutual enrichment between the gene lists in argument `x`.

If `GOLevels = NULL`, each ontology component is directly an object of class "tableList", containing all pairwise contingency tables of mutual enrichment between the gene lists in argument `x`, without GO level restriction.

The result also includes the attribute `GOLevels`, which stores the GO levels used in the analysis, or NULL when no GO level restriction was applied.

### Examples

```
## The following example is highly time-consuming and is therefore not run
## automatically during R CMD check.

## Not run:
## i) Obtaining ENTREZ identifiers for the gene universe of humans:
library(org.Hs.eg.db)
humanEntrezIDs <- keys(org.Hs.eg.db, keytype = "ENTREZID")

## ii) Gene lists to be explored for analysis:
data(allOncogeneLists)

# iii) Calculation of all joint enrichment contingency matrices directly from
# the gene lists across GO levels 3 to 10 for the BP, CC, and MF ontologies.
allContTabs <- allBuildEnrichTable(allOncogeneLists,
  geneUniverse = humanEntrezIDs,
  orgPackg = "org.Hs.eg.db",
  ontos = c("BP", "CC", "MF"),
  GOLevels = 3:10
)
allContTabs

## End(Not run)

# Since running this example may take several minutes, the result has been
```

```
# pre-computed and is accessible as the following:
data(allContTabs)
allContTabs
# This shortcut applies only to this example; for your own gene-list data,
# the computation must be performed explicitly.

# For a complete overview of this function's use, see the section 3 of the
# vignette "Introduction to goSorensen". You can do this by consulting the
# general package documentation or by directly running the following code in
# the R console:
# vignette("goSorensen_Introduction", package = "goSorensen")
```

---

allContTabs	<i>Example of the output produced by the function allBuildEnrichTable.</i>
-------------	--

---

### Description

This object contains all the enrichment contingency tables to compare all possible pairs of lists from [allOncoGeneLists](#) across GO-Levels 3 to 10, and for the ontologies BP, CC, and MF.

### Usage

```
data(allContTabs)
```

### Format

An exclusive object from goSorensen of the class "allTableList"

### Details

The attribute `enriched` is present in each element of this output, meaning that there is an enrichment matrix, similar to the one obtained with the function `enrichedIn`, for each ontology and GO-Level contained in this object. The attribute `enriched` is present in each element of this output, meaning that there is an enrichment matrix, similar to the one obtained with the function `enrichedIn`, for each ontology and GO-Level contained in this object.

Consider this object only as an illustrative example, which is valid exclusively for the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

allContTabsNoLevel	<i>Example of the output produced by the function allBuildEnrichTable.</i>
--------------------	--

---

### Description

This object contains all the enrichment contingency tables to compare all possible pairs of lists from [allOncoGeneLists](#) without GO-Levels restriction, and for the ontologies BP, CC, and MF.

**Usage**

```
data(allContTabsNoLevel)
```

**Format**

An exclusive object from goSorensen of the class "allTableList"

**Details**

The attribute `enriched` is present in each element of this output, meaning that there is an enrichment matrix, similar to the one obtained with the function `enrichedIn`, for each ontology contained in this object.

Consider this object only as an illustrative example, which is valid exclusively for the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

allDissMatrx	<i>Example of the output produced by the function <code>allSorenThreshold</code>. It contains the dissimilarity matrices for GO levels from 3 to 10 across the ontologies BP, CC and MF.</i>
--------------	--

---

**Description**

This object contains the matrices of dissimilarities between the 7 lists from `allOncoGeneLists`, computed based on the irrelevance threshold that makes them equivalent for GO levels from 3 to 10 across the ontologies BP, CC and MF.

**Usage**

```
data("allDissMatrx")
```

**Format**

An object of class "dist"

**Details**

Equivalence tests were computed based on the normal distribution (`boot = TRUE` by default) and using a confidence level `conf.level = 0.95`.

Consider this object only as an illustrative example, which is valid exclusively for the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

allDissMatrxNoLevel	<i>Example of the output produced by the function allSorenThreshold. It contains the dissimilarity matrices without GO-Level restriction across the ontologies BP, CC and MF.</i>
---------------------	---

---

### Description

This object contains the matrices of dissimilarities between the 7 lists from `allOncoGeneLists`, computed based on the irrelevance threshold that makes them equivalent without GO-Level restriction across the ontologies BP, CC and MF.

### Usage

```
data("allDissMatrxNoLevel")
```

### Format

An object of class "dist"

### Details

Equivalence tests were computed based on the normal distribution (boot = TRUE by default) and using a confidence level `conf.level = 0.95`. Equivalence tests were computed based on the normal distribution (boot = TRUE by default) and using a confidence level `conf.level = 0.95`.

Consider this object only as an illustrative example, which is valid exclusively for the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

allEqTests	<i>Example of the output produced by the function allEquivTestSorensen using the normal asymptotic distribution.</i>
------------	--

---

### Description

This object contains all the outputs for the equivalence tests to compare all possible pairs of lists from `allOncoGeneLists` across GO-Levels 3 to 10, and for the ontologies BP, CC, and MF, using the normal asymptotic distribution.

### Usage

```
data(allEqTests)
```

### Format

An exclusive object from `goSorensen` of the class "AllEquivSDhtest"

**Details**

The parameters considered to execute these tests are: irrelevance limit  $d0 = 0.4444$  and confidence level `conf.level = 0.95`.

Consider this object only as an illustrative example, which is valid exclusively for the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

allEqTestsNoLevel	<i>Example of the output produced by the function allEquivTestSorensen using the normal asymptotic distribution.</i>
-------------------	--

---

**Description**

This object contains all the outputs for the equivalence tests to compare all possible pairs of lists from [allOncoGeneLists](#) without GO-Level restriction, and for the ontologies BP, CC, and MF, using the normal asymptotic distribution.

**Usage**

```
data(allEqTestsNoLevel)
```

**Format**

An exclusive object from goSorensen of the class "AllEquivSDhtest"

**Details**

The parameters considered to execute these tests are: irrelevance limit  $d0 = 0.4444$  and confidence level `conf.level = 0.95`.

Consider this object only as an illustrative example, which is valid exclusively for the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

allEqTests_boot	<i>Example of the output produced by the function allEquivTestSorensen using the approximated bootstrap distribution.</i>
-----------------	---

---

**Description**

This object contains all the outputs for the equivalence tests to compare all possible pairs of lists from [allOncoGeneLists](#) across GO-Levels 3 to 10, and for the ontologies BP, CC, and MF, using the approximated bootstrap distribution.

**Usage**

```
data(allEqTests_boot)
```

**Format**

An exclusive object from goSorensen of the class "AllEquivSDhtest"

**Details**

The parameters considered to execute these tests are: irrelevance limit  $d0 = 0.4444$  and confidence level `conf.level = 0.95`.

Consider this object only as an illustrative example, which is valid exclusively for the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

allEqTests\_bootNoLevel

*Example of the output produced by the function allEquivTestSorensen using the approximated bootstrap distribution.*

---

**Description**

This object contains all the outputs for the equivalence tests to compare all possible pairs of lists from [allOncoGeneLists](#) without GO-Level restriction, and for the ontologies BP, CC, and MF, using the approximated bootstrap distribution.

**Usage**

```
data(allEqTests_bootNoLevel)
```

**Format**

An exclusive object from goSorensen of the class "AllEquivSDhtest"

**Details**

The parameters considered to execute these tests are: irrelevance limit  $d0 = 0.4444$  and confidence level `conf.level = 0.95`.

Consider this object only as an illustrative example, which is valid exclusively for the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

allEquivTestSorensen *Iterate equivTestSorensen along the specified GO ontologies and GO levels*

---

### Description

Iterate equivTestSorensen along the specified GO ontologies and GO levels

### Usage

```
allEquivTestSorensen(x, ...)

## S3 method for class 'list'
allEquivTestSorensen(
  x,
  d0 = 1/(1 + 1.25),
  conf.level = 0.95,
  boot = FALSE,
  nboot = 10000,
  check.table = TRUE,
  ontos = c("BP", "CC", "MF"),
  GOLevels = GOLevels,
  trace = TRUE,
  ...
)

## S3 method for class 'allTableList'
allEquivTestSorensen(
  x,
  d0 = 1/(1 + 1.25),
  conf.level = 0.95,
  boot = FALSE,
  nboot = 10000,
  check.table = TRUE,
  ontos,
  GOLevels,
  trace = TRUE,
  ...
)
```

### Arguments

x	either an object of class "list" or an object of class "allTableList". In the first case, each of its elements must be a "character" vector of gene identifiers (e.g., ENTREZ).
...	extra parameters for function buildEnrichTable.
d0	equivalence threshold for the Sorensen-Dice dissimilarity, d. The null hypothesis states that $d \geq d_0$ , i.e., inequivalence between the compared gene lists and the alternative that $d < d_0$ , i.e., equivalence or dissimilarity irrelevance (up to a level $d_0$ ).

conf.level	confidence level of the one-sided confidence interval, a value between 0 and 1.
boot	boolean. If TRUE, the confidence interval and the test p-value are computed by means of a bootstrap approach instead of the asymptotic normal approach. Defaults to FALSE.
nboot	numeric, number of initially planned bootstrap replicates. Ignored if boot == FALSE. Defaults to 10000.
check.table	Boolean. If TRUE (default), argument x is checked to adequately represent a 2x2 contingency table (or an aggregate of them) or gene lists producing a correct table. This checking is performed by means of function nice2x2Table.
ontos	"character", GO ontologies to analyse. Defaults to c("BP", "CC", "MF").
GOlevels	Integer vector of GO levels to analyze inside each selected ontology. If NULL, equivalence tests are performed without restricting the analysis to specific GO levels.
trace	Logical. If TRUE (default), the (usually very time consuming) process of function allEquivTestSorensen is traced along the specified GO ontologies and levels.

### Value

An object of class "AllEquivSDhtest". It is a list with as many components as GO ontologies have been analyzed.

If GOlevels is not NULL, each ontology component is itself a list with as many components as GO levels have been analyzed. Each of these elements is an object generated by equivTestSorensen.list() or equivTestSorensen.tableList(), that is, an object of class "equivSDhtestList" containing pairwise comparisons between gene lists.

If GOlevels = NULL, each ontology component is directly an object of class "equivSDhtestList", containing all pairwise equivalence tests between the gene lists in argument x, without GO level restriction.

### Methods (by class)

- allEquivTestSorensen(list): S3 method for class "list"
- allEquivTestSorensen(allTableList): S3 method for class "allTableList"

### Examples

```
## The following example is highly time-consuming and is therefore not run
## automatically during R CMD check.

## Not run:
## i) Obtaining ENTREZ identifiers for the gene universe of humans:
library(org.Hs.eg.db)
humanEntrezIDs <- keys(org.Hs.eg.db, keytype = "ENTREZID")

## ii) Gene lists to be explored for analysis:
data(allOncoGeneLists)

# iii) Calculation of equivalence tests for all joint enrichment contingency
# tables across GO levels 3 to 10 for the BP, CC, and MF ontologies
allEqTests <- allEquivTestSorensen(allOncoGeneLists,
  geneUniverse = humanEntrezIDs,
  orgPackg = "org.Hs.eg.db",
```

```

ontos = c("BP", "CC", "MF"),
GOLevels = 3:10,
d0 = 0.4444,
conf.level = 0.95
)
allEqTests

## End(Not run)

# Since running this example may take several minutes, the result has been
# pre-computed and is accessible as the following:
data(allEqTests)
allEqTests
# This shortcut applies only to this example; for your own gene-list data,
# the computation must be performed explicitly.

# For a complete overview of this function's use, see the section 4 of the
# vignette "Introduction to goSorensen". You can do this by consulting the
# general package documentation or by directly running the following code in
# the R console:
# vignette("goSorensen_Introduction", package = "goSorensen")

```

---

allHclustThreshold	<i>Iterate hclustThreshold along the specified GO ontologies and GO levels</i>
--------------------	--

---

## Description

Iterate hclustThreshold along the specified GO ontologies and GO levels

## Usage

```
allHclustThreshold(x, ontos, GOLevels, trace = TRUE, ...)
```

## Arguments

x	an object of class "distList".
ontos	"character", GO ontologies to iterate. Defaults to the ontologies in 'x'.
GOLevels	"integer", GO levels to iterate inside each one of these GO ontologies.
trace	Logical. If TRUE (default), the process is traced along the specified GO ontologies and levels.
...	extra parameters for function hclustThreshold.

## Value

An object of class "equivClustSorensenList" descending from "iterEquivClust" which itself descends from class "list". It is a list with as many components as GO ontologies have been specified. Each of these elements is itself a list with as many components as GO levels have been specified. Finally, the elements of these lists are objects of class "equivClustSorensen", descending from "equivClust" which itself descends from "hclust".

**Examples**

```

# The following example requires calculating all dissimilarity matrices at
# the 3:10 levels and BP, CC, and MF ontologies for visualization purposes.
# Because this process is computationally intensive and can take a
# considerable amount of time, the example is not run automatically during
# the R CMD check.
## Not run:
## i) Obtaining ENTREZ identifiers for the gene universe of humans:
library(org.Hs.eg.db)
humanEntrezIDs <- keys(org.Hs.eg.db, keytype = "ENTREZID")

## ii) Gene lists to be explored for analysis:
data(allOncoGeneLists)

# iii) Compute the thresholded dissimilarity matrices for the BP, CC, and MF
# ontologies across all GO levels, specifically from level 3 to level 10.
allDissMatrx <- allSorenThreshold(allOncoGeneLists,
  geneUniverse = humanEntrezIDs,
  orgPackg = "org.Hs.eg.db",
  ontos = c("BP", "CC", "MF"),
  GOLevels = 3:10,
  trace = FALSE
)
allDissMatrx

## End(Not run)

# Since running this example may take several minutes, the result has been
# pre-computed and is accessible as the following:
data(allDissMatrx)
allDissMatrx
# This shortcut applies only to this example; for your own gene-list data,
# the computation must be performed explicitly.

# The hclusts object stores all hierarchical clustering results for each
# ontology and GO level calculated from the allDissMatrx object. Any of these
# clustering results can be visualized. For example:
all.clust.threshold <- allHclustThreshold(allDissMatrx)
plot(all.clust.threshold$BP$`level 4`)
plot(all.clust.threshold$CC$`level 5`)
plot(all.clust.threshold$MF$`level 6`)

```

---

allOncoGeneLists	<i>7 gene lists possibly related with cancer</i>
------------------	--

---

**Description**

An object of class "list" of length 7. Each one of its elements is a "character" vector of gene identifiers (e.g., ENTREZ). Only gene lists of length almost 100 were taken from their source web. Take these lists just as an illustrative example, they are not automatically updated.

**Usage**

```
data(allOncoGeneLists)
```

**Format**

An object of class "list" of length 7. Each one of its elements is a "character" vector of ENTREZ gene identifiers .

**Source**

<http://www.bushmanlab.org/links/genelists>

---

allSorenThreshold	<i>Iterate sorenThreshold along the specified GO ontologies and GO levels</i>
-------------------	---

---

**Description**

Iterate sorenThreshold along the specified GO ontologies and GO levels

**Usage**

```
allSorenThreshold(x, ...)  
  
## S3 method for class 'list'  
allSorenThreshold(  
  x,  
  geneUniverse,  
  orgPackg,  
  boot = FALSE,  
  nboot = 10000,  
  boot.seed = 6551,  
  ontos = c("BP", "CC", "MF"),  
  GOLevels = seq.int(3, 10),  
  trace = TRUE,  
  alpha = 0.05,  
  precis = 0.001,  
  ...  
)  
  
## S3 method for class 'allTableList'  
allSorenThreshold(  
  x,  
  boot = FALSE,  
  nboot = 10000,  
  boot.seed = 6551,  
  ontos,  
  GOLevels,  
  trace = TRUE,  
  alpha = 0.05,  
  precis = 0.001,  
  ...  
)
```

**Arguments**

x	either an object of class "list" or an object of class "allTableList". In the first case, each of its elements must be a "character" vector of gene identifiers (e.g., ENTREZ). In the second case, the object corresponds to all contingency tables of joint enrichment along one or more GO ontologies and one or more GO levels.
...	extra parameters for function buildEnrichTable.
geneUniverse	character vector containing the universe of genes from where gene lists have been extracted. This vector must be obtained from the annotation package declared in orgPackg. For more details see <a href="#">README File</a> .
orgPackg	A string with the name of the genomic annotation package corresponding to a specific species to be analyzed, which must be previously installed and activated. For more details see <a href="#">README File</a> .
boot	boolean. If TRUE, the confidence intervals and the test p-values are computed by means of a bootstrap approach instead of the asymptotic normal approach. Defaults to FALSE.
nboot	numeric, number of initially planned bootstrap replicates. Ignored if boot == FALSE. Defaults to 10000.
boot.seed	starting random seed for all bootstrap iterations. Defaults to 6551. see the details section
ontos	"character", GO ontologies to analyse.
GOLevels	"integer", GO levels to analyse inside each one of these GO ontologies.
trace	Logical. If TRUE (default), the (usually very time consuming) process is traced along the specified GO ontologies and levels.
alpha	simultaneous nominal significance level for the equivalence tests to be repeatedly performed, defaults to 0.05
precis	numerical precision in the iterative search of the equivalence threshold dissimilarities,

**Value**

An object of class "distList". It is a list with as many components as GO ontologies have been analysed. Each of these elements is itself a list with as many components as GO levels have been analysed. Finally, the elements of these lists are objects of class "dist" with the Sorensen-Dice equivalence threshold dissimilarity.

**Methods (by class)**

- allSorenThreshold(list): S3 method for class "list"
- allSorenThreshold(allTableList): S3 method for class "allTableList"

**Examples**

```
## The following example is highly time-consuming and is therefore not run
## automatically during R CMD check.

## Not run:
## i) Obtaining ENTREZ identifiers for the gene universe of humans:
library(org.Hs.eg.db)
humanEntrezIDs <- keys(org.Hs.eg.db, keytype = "ENTREZID")
```

```

## ii) Gene lists to be explored for analysis:
data(allOncogeneLists)

# iii) # Calculation of all dissimilarity matrices derived from joint
# enrichment contingency tables across GO levels 3 to 10 for the BP, CC, and
# MF ontologies:
allDissMatrx <- allSorenThreshold(allOncogeneLists,
  geneUniverse = humanEntrezIDs,
  orgPackg = "org.Hs.eg.db",
  ontos = c("BP", "CC", "MF"),
  GOLevels = 3:10,
  trace = FALSE
)
allDissMatrx

## End(Not run)

# Since running this example may take several minutes, the result has been
# pre-computed and is accessible as the following:
data(allDissMatrx)
allDissMatrx
# This shortcut applies only to this example; for your own gene-list data,
# the computation must be performed explicitly.

# For a complete overview of this function's use, see the section 2 of the
# vignette "Working with the Irrelevance-threshold Matrix of Dissimilarities"
# You can do this by consulting the general package documentation or by
# directly running the following code in the R console:
# vignette("Dissimilarities_Matrix", package = "goSorensen")

```

---

boot.tStat

*Studentized Sorensen-Dice dissimilarity statistic*


---

## Description

Efficient computation of the studentized statistic  $(\hat{dis} - dis) / \hat{se}$  where 'dis' stands for the "population" value of the Sorensen-Dice dissimilarity, ' $\hat{dis}$ ' for its estimated value and ' $\hat{se}$ ' for the estimate of the standard error of ' $\hat{dis}$ '. Internally used in bootstrap computations.

## Usage

```
boot.tStat(xBoot, dis)
```

## Arguments

xBoot	either an object of class "table", "matrix" or "numeric" representing a 2x2 contingency table of joint enrichment.
dis	the "known" value of the population dissimilarity.

## Details

This function is repeatedly evaluated during bootstrap iterations. Given a contingency table 'x' of mutual enrichment (the "true" dataset):

$$\begin{array}{cc} n_{11} & n_{10} \\ n_{01} & n_{00}, \end{array}$$

summarizing the status of mutual presence of enrichment in two gene lists, where the subindex '11' corresponds to those GO terms enriched in both lists, '01' to terms enriched in the second list but not in the first one, '10' to terms enriched in the first list but not enriched in the second one and '00' to those GO terms non enriched in both gene lists, i.e., to the double negatives.

A typical bootstrap iteration consists in repeatedly generating four frequencies from a multinomial of parameters  $size = \sum(n_{ij})$ ,  $i, j = 1, 0$  and probabilities  $(n_{11}/size, n_{10}/size, n_{01}/size, n_{00}/size)$ . The argument 'xBoot' corresponds to each one of these bootstrap resamples (indiferently represented in form of a 2x2 "table" or "matrix" or as a numeric vector) In each bootstrap iteration, the value of the "true" known 'dis' is the dissimilarity which was computed from 'x' (a constant, known value in the full iteration) and the values of '^dis' and '^se' are internally computed from the bootstrap data 'xBoot'.

## Value

A numeric value, the result of computing  $(\hat{dis} - dis) / \hat{se}$ .

---

<code>buildEnrichTable</code>	<i>Create enrichment contingency tables from gene lists</i>
-------------------------------	---

---

## Description

Generic function to build 2x2 enrichment contingency tables from gene lists, or all pairwise contingency tables for a "list" of gene lists.

## Usage

```
buildEnrichTable(x, ...)

## Default S3 method:
buildEnrichTable(
  x,
  y,
  listNames = c("gene.list1", "gene.list2"),
  check.table = TRUE,
  geneUniverse,
  orgPackg,
  onto,
  GOLevel = NULL,
  storeEnrichedIn = TRUE,
  pAdjustMeth = "BH",
  pvalCutoff = 0.01,
  qvalCutoff = 0.05,
  keyType = "ENTREZID",
```

```

parallel = FALSE,
nOfCores = 1,
...
)

## S3 method for class 'list'
buildEnrichTable(
  x,
  check.table = TRUE,
  geneUniverse,
  orgPackg,
  onto,
  GOlevel = NULL,
  storeEnrichedIn = TRUE,
  pAdjustMeth = "BH",
  pvalCutoff = 0.01,
  qvalCutoff = 0.05,
  keyType = "ENTREZID",
  parallel = FALSE,
  nOfCores = min(parallel::detectCores() - 1, length(x) - 1),
  ...
)

```

### Arguments

x	A list of gene lists (each element must be a character vector of gene identifiers).
...	Additional parameters for internal use (not used for the moment)
y	An object of class "character" (or coercable to "character") representing a vector of gene identifiers (e.g., ENTREZ).
listNames	a character(2) with the gene lists names originating the cross-tabulated enrichment frequencies. Only in the "character" or default interface.
check.table	Logical The resulting table must be checked. Defaults to TRUE.
geneUniverse	character vector containing the universe of genes from where gene lists have been extracted. This vector must be obtained from the annotation package declared in orgPackg. For more details, refer to vignette <a href="#">goSorensen_Introduction</a> .
orgPackg	A string with the name of the genomic annotation package corresponding to a specific species to be analysed, which must be previously installed and activated. For more details, refer to vignette <a href="#">goSorensen_Introduction</a> .
onto	string describing the ontology. Either "BP", "MF" or "CC".
GOlevel	Integer specifying the GO level to analyze. If NULL, the analysis is performed without restricting GO terms to a specific level.
storeEnrichedIn	logical, the matrix of enriched (GO terms) x (gene lists) TRUE/FALSE values, must be stored in the result? See the details section
pAdjustMeth	string describing the adjust method, either "BH", "BY" or "Bonf", defaults to 'BH'.
pvalCutoff	adjusted pvalue cutoff on enrichment tests to report
qvalCutoff	qvalue cutoff on enrichment tests to report as significant. Tests must pass i) pvalueCutoff on unadjusted pvalues, ii) pvalueCutoff on adjusted pvalues and iii) qvalueCutoff on qvalues to be reported

keyType	keyType Character string specifying the type of gene identifier used in the input, such as "ENTREZID" or "SYMBOL".
parallel	Logical. Defaults to FALSE but put it at TRUE for parallel computation.
nOfCores	Number of cores for parallel computations. Only in "list" interface.

## Details

Specific methods are implemented for different input classes.

If the argument `storeEnrichedIn` is TRUE (the default value), the result of `buildEnrichTable()` includes an additional attribute `enriched` with a matrix of TRUE/FALSE values. Each row indicates whether a given GO term is enriched or not in each one of the gene lists (columns). To save space, only GO terms enriched in at least one of the gene lists are included in this matrix.

Also, to avoid redundancies and save space, the result of `buildEnrichTable.list()` (an object of class "tableList", which is itself an aggregate of 2x2 contingency tables of class "table") has the attribute `enriched`, but its table members do not have this attribute.

The default value of argument `parallel` is FALSE, and you may consider the trade-off between the time spent initializing parallelization and the possible time gain from parallel execution. Although it is difficult to establish a general guideline, parallelization is usually worthwhile only when analyzing many gene lists, on the order of 30 or more, although this depends on the computer and the application.

## Value

See method-specific documentation.

in the "character" interface, an object of class "table". It represents a 2x2 contingency table, the cross-tabulation of the enriched GO terms in two gene lists: "Number of enriched GO terms in list 1 (TRUE, FALSE)" x "Number of enriched Go terms in list 2 (TRUE, FALSE)". In the "list" interface, the result is an object of class "tableList" with all pairwise tables. Class "tableList" corresponds to objects representing all mutual enrichment contingency tables generated in a pairwise fashion: Given gene lists (i.e. "character" vectors of gene identifiers)  $l_1, l_2, \dots, l_k$ , an object of class "tableList" is a list of lists of contingency tables  $t(i,j)$  generated from each pair of gene lists  $i$  and  $j$ , with the following structure:

$l_2$

$l_2 l_1 t(2,1)$

$l_3$

$l_3 l_1 t(3,1), l_3 l_2 t(3,2)$

...

$l_k$

$l_k l_1 t(k,1), l_k l_2 t(k,2), \dots, l_k l_{(k-1)} t(K,k-1)$

An object of class "tableList" containing all pairwise enrichment contingency tables.

## Methods (by class)

- `buildEnrichTable(default)`: Creates a 2x2 enrichment contingency table from two gene lists
- `buildEnrichTable(list)`: Builds all pairwise enrichment contingency tables from a list of gene lists

## Examples

```
## The following example is highly time-consuming and is therefore not run
## automatically during R CMD check.

## Not run:
## i) Obtaining ENTREZ identifiers for the gene universe of humans:
library(org.Hs.eg.db)
humanEntrezIDs <- keys(org.Hs.eg.db, keytype = "ENTREZID")

## ii) Gene lists to be explored for analysis:
data(allOncogeneLists)

# iii) Calculation of the joint enrichment matrix directly from gene lists at
# the GO 4 level and the BP ontology.:
cont_all_BP4 <- buildEnrichTable(allOncogeneLists,
  geneUniverse = humanEntrezIDs,
  orgPackg = "org.Hs.eg.db",
  onto = "BP",
  GOLevel = 4
)
cont_all_BP4

## End(Not run)

# Since running this example may take several minutes, the result has been
# pre-computed and is accessible as the following:
data(cont_all_BP4)
cont_all_BP4
# This shortcut applies only to this example; for your own gene-list data,
# the computation must be performed explicitly.

# For a complete overview of this function's use, see the section 3 of the
# vignette "Introduction to goSorensen". You can do this by consulting the
# general package documentation or by directly running the following code in
# the R console:
# vignette("goSorensen_Introduction", package = "goSorensen")
```

---

cont\_all\_BP

*Example of the output produced by the function buildEnrichTable. It contains the enrichment contingency tables for all the lists from allOncogeneLists for ontology BP without GO-Level restriction.*

---

## Description

Given 7 lists contained in allOncogeneLists, this object contains the  $7(6)/2 = 21$  possible enrichment contingency tables to compare all possible pairs of lists. Each contingency 2x2 table contains the number of joint enriched GO terms (TRUE-TRUE); the number of GO terms enriched only in one list but not in the other one (FALSE-TRUE and TRUE-FALSE); and the number of GO terms not enriched in either of the two lists.

An important attribute of this object is enriched, which contains the enrichment matrix obtained using the function `enrichedIn`. Actually, the contingency tables in this object are derived from cross-frequency tables created between pairs of lists, which are located as columns in this enrichment matrix.

**Usage**

```
data(cont_all_BP)
```

**Format**

An exclusive object from goSorensen of the class "tableList"

**Details**

Consider this object only as an illustrative example, which is valid exclusively for the data [allOncogeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

cont\_all\_BP4

*Example of the output produced by the function buildEnrichTable. It contains the enrichment contingency tables for all the lists from allOncogeneLists at level 4 of ontology BP.*

---

**Description**

Given 7 lists contained in [allOncogeneLists](#), this object contains the  $7(6)/2 = 21$  possible enrichment contingency tables to compare all possible pairs of lists. Each contingency 2x2 table contains the number of joint enriched GO terms (TRUE-TRUE); the number of GO terms enriched only in one list but not in the other one (FALSE-TRUE and TRUE-FALSE); and the number of GO terms not enriched in either of the two lists.

An important attribute of this object is `enriched`, which contains the enrichment matrix obtained using the function [enrichedIn](#). Actually, the contingency tables in this object are derived from cross-frequency tables created between pairs of lists, which are located as columns in this enrichment matrix.

**Usage**

```
data(cont_all_BP4)
```

**Format**

An exclusive object from goSorensen of the class "tableList"

**Details**

Consider this object only as an illustrative example, which is valid exclusively for the data [allOncogeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

cont\_atlas.sanger\_BP *Example of the output produced by the function buildEnrichTable. It contains the enrichment contingency table for two lists for ontology BP without GO-Level restriction.*

---

### Description

A contingency 2x2 table with the number of joint enriched GO terms (TRUE-TRUE); the number of GO terms enriched only in one list but not in the other one (FALSE-TRUE and TRUE-FALSE); and the number of GO terms not enriched in either of the two lists.

### Usage

```
data(cont_atlas.sanger_BP)
```

### Format

An object of class "table"

### Details

Consider this object only as an illustrative example, which is valid exclusively for the lists atlas and sanger from the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

cont\_atlas.sanger\_BP4 *Example of the output produced by the function buildEnrichTable. It contains the enrichment contingency table for two lists at level 4 of ontology BP.*

---

### Description

A contingency 2x2 table with the number of joint enriched GO terms (TRUE-TRUE); the number of GO terms enriched only in one list but not in the other one (FALSE-TRUE and TRUE-FALSE); and the number of GO terms not enriched in either of the two lists.

### Usage

```
data(cont_atlas.sanger_BP4)
```

### Format

An object of class "table"

### Details

Consider this object only as an illustrative example, which is valid exclusively for the lists atlas and sanger from the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

dissMatrx_BP	<i>Example of the output produced by the function <code>sorenThreshold</code>. It contains the dissimilarity matrix for the ontology BP without GO-Level restriction.</i>
--------------	---

---

### Description

This object contains the matrix of dissimilarities between the 7 lists from `allOncoGeneLists`, computed based on the irrelevance threshold that makes them equivalent for the ontology BP without GO-Level restriction.

### Usage

```
data("dissMatrx_BP")
```

### Format

An object of class "dist"

### Details

Equivalence tests were computed based on the normal distribution (`boot = TRUE` by default) and using a confidence level `conf.level = 0.95`.

Consider this object only as an illustrative example, which is valid exclusively for the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

dissMatrx_BP4	<i>Example of the output produced by the function <code>sorenThreshold</code>. It contains the dissimilarity matrix at GO level 4, for the ontology BP.</i>
---------------	---

---

### Description

This object contains the matrix of dissimilarities between the 7 lists from `allOncoGeneLists`, computed based on the irrelevance threshold that makes them equivalent at GO level 4, for the ontology BP.

### Usage

```
data("dissMatrx_BP4")
```

### Format

An object of class "dist"

## Details

Equivalence tests were computed based on the normal distribution (`boot = TRUE` by default) and using a confidence level `conf.level = 0.95`.

Consider this object only as an illustrative example, which is valid exclusively for the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

dSorensen

*Computation of the Sorensen-Dice dissimilarity*

---

## Description

Computation of the Sorensen-Dice dissimilarity

## Usage

```
dSorensen(x, ...)

## S3 method for class 'table'
dSorensen(x, check.table = TRUE, ...)

## S3 method for class 'matrix'
dSorensen(x, check.table = TRUE, ...)

## S3 method for class 'numeric'
dSorensen(x, check.table = TRUE, ...)

## S3 method for class 'character'
dSorensen(x, y, check.table = TRUE, ...)

## S3 method for class 'list'
dSorensen(x, check.table = TRUE, ...)

## S3 method for class 'tableList'
dSorensen(x, check.table = TRUE, ...)
```

## Arguments

<code>x</code>	either an object of class "table", "matrix" or "numeric" representing a 2x2 contingency table, or a "character" vector (a set of gene identifiers) or "list" or "tableList" object. See the details section for more information.
<code>...</code>	extra parameters for function <code>buildEnrichTable</code> .
<code>check.table</code>	Boolean. If <code>TRUE</code> (default), argument <code>x</code> is checked to adequately represent a 2x2 contingency table, by means of function <code>nice2x2Table</code> .
<code>y</code>	an object of class "character" representing a vector of valid gene identifiers (e.g., ENTREZ).

## Details

Given a 2x2 arrangement of frequencies (either implemented as a "table", a "matrix" or a "numeric" object):

$$\begin{array}{cc} n_{11} & n_{10} \\ n_{01} & n_{00}, \end{array}$$

this function computes the Sorensen-Dice dissimilarity

$$\frac{n_{10} + n_{01}}{2n_{11} + n_{10} + n_{01}}.$$

The subindex '11' corresponds to those GO terms enriched in both lists, '01' to terms enriched in the second list but not in the first one, 10' to terms enriched in the first list but not enriched in the second one and '00' corresponds to those GO terms non enriched in both gene lists, i.e., to the double negatives, a value which is ignored in the computations.

In the "numeric" interface, if `length(x) >= 3`, the values are interpreted as  $(n_{11}, n_{01}, n_{10}, n_{00})$ , always in this order and discarding extra values if necessary. The result is correct, regardless the frequencies being absolute or relative.

If `x` is an object of class "character", then `x` (and `y`) must represent two "character" vectors of valid gene identifiers (e.g., ENTREZ). Then the dissimilarity between lists `x` and `y` is computed, after internally summarizing them as a 2x2 contingency table of joint enrichment. This last operation is performed by function `buildEnrichTable` and "valid gene identifiers (e.g., ENTREZ)" stands for the coherency of these gene identifiers with the arguments `geneUniverse` and `orgPackg` of `buildEnrichTable`, passed by the ellipsis argument `...` in `dSorensen`.

If `x` is an object of class "list", the argument must be a list of "character" vectors, each one representing a gene list (character identifiers). Then, all pairwise dissimilarities between these gene lists are computed.

If `x` is an object of class "tableList", the Sorensen-Dice dissimilarity is computed over each one of these tables. Given `k` gene lists (i.e. "character" vectors of gene identifiers) `l1`, `l2`, ..., `lk`, an object of class "tableList" (typically constructed by a call to function `buildEnrichTable`) is a list of lists of contingency tables  $t(i,j)$  generated from each pair of gene lists `i` and `j`, with the following structure:

```
$l2
$l2$l1$t(2,1)
$l3
$l3$l1$t(3,1), $l3$l2$t(3,2)
...
$lk
$lk$l1$t(k,1), $lk$l2$t(k,2), ..., $lk$l(k-1)t(k,k-1)
```

## Value

In the "table", "matrix", "numeric" and "character" interfaces, the value of the Sorensen-Dice dissimilarity. In the "list" and "tableList" interfaces, the symmetric matrix of all pairwise Sorensen-Dice dissimilarities.

**Methods (by class)**

- dSorensen(table): S3 method for class "table"
- dSorensen(matrix): S3 method for class "matrix"
- dSorensen(numeric): S3 method for class "numeric"
- dSorensen(character): S3 method for class "character"
- dSorensen(list): S3 method for class "list"
- dSorensen(tableList): S3 method for class "tableList"

**See Also**

[buildEnrichTable](#) for constructing contingency tables of mutual enrichment, [nice2x2Table](#) for checking contingency tables validity, [seSorensen](#) for computing the standard error of the dissimilarity, [duppSorensen](#) for the upper limit of a one-sided confidence interval of the dissimilarity, [equivTestSorensen](#) for an equivalence test.

**Examples**

```
# Sorensen-Dice dissimilarity from scratch, directly from two gene lists:

# Manually define a 2 x 2 enrichment contingency table
contTable <- as.table(matrix(c(127, 19, 159, 3018),
  nrow = 2,
  dimnames = list(
    "Enriched in List 1" = c(TRUE, FALSE),
    "Enriched in List 2" = c(TRUE, FALSE)
  )
))
contTable

# Calculation of the dissimilarity value using the joint enrichment
# contingency matrix
dSorensen(contTable)
```

---

duppSorensen	<i>Upper limit of a one-sided confidence interval (0, dUpp] for the Sorensen-Dice dissimilarity</i>
--------------	---

---

**Description**

Upper limit of a one-sided confidence interval (0, dUpp] for the Sorensen-Dice dissimilarity

**Usage**

```
duppSorensen(x, ...)

## S3 method for class 'table'
duppSorensen(
  x,
  dis = dSorensen.table(x, check.table = FALSE),
  se = seSorensen.table(x, check.table = FALSE),
```

```
    conf.level = 0.95,
    z.conf.level = qnorm(1 - conf.level),
    boot = FALSE,
    nboot = 10000,
    check.table = TRUE,
    ...
)

## S3 method for class 'matrix'
duppSorensen(
  x,
  dis = dSorensen.matrix(x, check.table = FALSE),
  se = seSorensen.matrix(x, check.table = FALSE),
  conf.level = 0.95,
  z.conf.level = qnorm(1 - conf.level),
  boot = FALSE,
  nboot = 10000,
  check.table = TRUE,
  ...
)

## S3 method for class 'numeric'
duppSorensen(
  x,
  dis = dSorensen.numeric(x, check.table = FALSE),
  se = seSorensen.numeric(x, check.table = FALSE),
  conf.level = 0.95,
  z.conf.level = qnorm(1 - conf.level),
  boot = FALSE,
  nboot = 10000,
  check.table = TRUE,
  ...
)

## S3 method for class 'character'
duppSorensen(
  x,
  y,
  conf.level = 0.95,
  boot = FALSE,
  nboot = 10000,
  check.table = TRUE,
  ...
)

## S3 method for class 'list'
duppSorensen(
  x,
  conf.level = 0.95,
  boot = FALSE,
  nboot = 10000,
  check.table = TRUE,
```

```

    ...
)

## S3 method for class 'tableList'
duppSorensen(
  x,
  conf.level = 0.95,
  boot = FALSE,
  nboot = 10000,
  check.table = TRUE,
  ...
)

```

### Arguments

<code>x</code>	either an object of class "table", "matrix" or "numeric" representing a 2x2 contingency table, or a "character" (a set of gene identifiers) or "list" or "tableList" object. See the details section for more information.
<code>...</code>	additional arguments for function <code>buildEnrichTable</code> .
<code>dis</code>	Sorensen-Dice dissimilarity value. Only required to speed computations if this value is known in advance.
<code>se</code>	standard error estimate of the sample dissimilarity. Only required to speed computations if this value is known in advance.
<code>conf.level</code>	confidence level of the one-sided confidence interval, a numeric value between 0 and 1.
<code>z.conf.level</code>	standard normal (or bootstrap, see arguments below) distribution quantile at the $1 - \text{conf.level}$ value. Only required to speed computations if this value is known in advance. Then, the argument <code>conf.level</code> is ignored.
<code>boot</code>	boolean. If TRUE, <code>z.conf.level</code> is computed by means of a bootstrap approach instead of the asymptotic normal approach. Defaults to FALSE.
<code>nboot</code>	numeric, number of initially planned bootstrap replicates. Ignored if <code>boot == FALSE</code> . Defaults to 10000.
<code>check.table</code>	Boolean. If TRUE (default), argument <code>x</code> is checked to adequately represent a 2x2 contingency table. This checking is performed by means of function <code>nice2x2Table</code> .
<code>y</code>	an object of class "character" representing a vector of gene identifiers (e.g., ENTREZ).

### Details

This function computes the upper limit of a one-sided confidence interval for the Sorensen-Dice dissimilarity, given a 2x2 arrangement of frequencies (either implemented as a "table", a "matrix" or a "numeric" object):

$$\begin{matrix} n_{11} & n_{10} \\ n_{01} & n_{00}, \end{matrix}$$

The subindex '11' corresponds to those GO terms enriched in both lists, '01' to terms enriched in the second list but not in the first one, '10' to terms enriched in the first list but not enriched in the

second one and '00' corresponds to those GO terms non enriched in both gene lists, i.e., to the double negatives, a value which is ignored in the computations, except if `boot == TRUE`.

In the "numeric" interface, if `length(x) >= 4`, the values are interpreted as  $(n_{11}, n_{01}, n_{10}, n_{00})$ , always in this order and discarding extra values if necessary.

Arguments `dis`, `se` and `z.conf.level` are not required. If known in advance (e.g., as a consequence of previous computations with the same data), providing its value may speed the computations.

By default, `z.conf.level` corresponds to the  $1 - \text{conf.level}$  quantile of a standard normal  $N(0,1)$  distribution, as the studentized statistic  $(\hat{d} - d) / \hat{se}$  is asymptotically  $N(0,1)$ . In the studentized statistic,  $d$  stands for the "true" Sorensen-Dice dissimilarity,  $\hat{d}$  to its sample estimate and  $\hat{se}$  for the estimate of its standard error. In fact, the normal is its limiting distribution but, for finite samples, the true sampling distribution may present departures from normality (mainly with some inflation in the left tail). The bootstrap method provides a better approximation to the true sampling distribution. In the bootstrap approach, `nboot` new bootstrap contingency tables are generated from a multinomial distribution with parameters `size = n = n11 + n01 + n10 + n00` and probabilities  $(n_{11}/n, n_{01}/n, n_{10}/n, n_{00}/n)$ . Sometimes, some of these generated tables may present so low frequencies of enrichment that make them unable for Sorensen-Dice computations. As a consequence, the number of effective bootstrap samples may be lower than the number of initially planned bootstrap samples `nboot`. Computing in advance the value of argument `z.conf.level` may be a way to cope with these departures from normality, by means of a more adequate quantile function. Alternatively, if `boot == TRUE`, a bootstrap quantile is internally computed.

If `x` is an object of class "character", then `x` (and `y`) must represent two "character" vectors of valid gene identifiers (e.g., ENTREZ). Then the confidence interval for the dissimilarity between lists `x` and `y` is computed, after internally summarizing them as a 2x2 contingency table of joint enrichment. This last operation is performed by function `buildEnrichTable` and "valid gene identifiers (e.g., ENTREZ)" stands for the coherency of these gene identifiers with the arguments `geneUniverse` and `orgPackg` of `buildEnrichTable`, passed by the ellipsis argument `...` in `dUppSorensen`.

In the "list" interface, the argument must be a list of "character" vectors, each one representing a gene list (character identifiers). Then, all pairwise upper limits of the dissimilarity between these gene lists are computed.

In the "tableList" interface, the upper limits are computed over each one of these tables. Given gene lists (i.e. "character" vectors of gene identifiers) `l1`, `l2`, ..., `lk`, an object of class "tableList" (typically constructed by a call to function `buildEnrichTable`) is a list of lists of contingency tables `t(i,j)` generated from each pair of gene lists `i` and `j`, with the following structure:

```
$l2
$l2$l1$t(2,1)
$l3
$l3$l1$t(3,1), $l3$l2$t(3,2)
...
$lk
$lk$l1$t(k,1), $lk$l2$t(k,2), ..., $lk$l(k-1)t(k,k-1)
```

## Value

In the "table", "matrix", "numeric" and "character" interfaces, the value of the Upper limit of the confidence interval for the Sorensen-Dice dissimilarity. When `boot == TRUE`, this result also has an extra attribute: "eff.nboot" which corresponds to the number of effective bootstrap replicats, see the details section. In the "list" and "tableList" interfaces, the result is the symmetric matrix of all pairwise upper limits.

**Methods (by class)**

- `duppSorensen(table)`: S3 method for class "table"
- `duppSorensen(matrix)`: S3 method for class "matrix"
- `duppSorensen(numeric)`: S3 method for class "numeric"
- `duppSorensen(character)`: S3 method for class "character"
- `duppSorensen(list)`: S3 method for class "list"
- `duppSorensen(tableList)`: S3 method for class "tableList"

**See Also**

[buildEnrichTable](#) for constructing contingency tables of mutual enrichment, [nice2x2Table](#) for checking contingency tables validity, [dSorensen](#) for computing the Sorensen-Dice dissimilarity, [seSorensen](#) for computing the standard error of the dissimilarity, [equivTestSorensen](#) for an equivalence test.

**Examples**

```
# Computing the Upper confidence limit:

# Manually define a 2 x 2 enrichment contingency table
contTable <- as.table(matrix(c(127, 19, 159, 3018),
  nrow = 2,
  dimnames = list(
    "Enriched in List 1" = c(TRUE, FALSE),
    "Enriched in List 2" = c(TRUE, FALSE)
  )
))
contTable

# Calculation of the Upper Confidence Limit Using the Joint Enrichment
# Contingency Matrix
duppSorensen(contTable)
```

---

enrichedIn

*This function builds a cross-tabulation of enriched (TRUE) and non-enriched (FALSE) GO terms vs. gene lists*

---

**Description**

This function builds a cross-tabulation of enriched (TRUE) and non-enriched (FALSE) GO terms vs. gene lists

**Usage**

```
enrichedIn(x, ...)

## Default S3 method:
enrichedIn(
  x,
  geneUniverse,
```

```

    orgPackg,
    onto,
    GOLevel,
    pAdjustMeth = "BH",
    pvalCutoff = 0.01,
    qvalCutoff = 0.05,
    parallel = FALSE,
    nOfCores = 1,
    onlyEnriched = TRUE,
    keyType = "ENTREZID",
    ...
)

```

### Arguments

x	Either an object of class "character" (or coercible to "character") or "list". In the "character" interface, these values should represent Entrez gene identifiers (or, more generally, feature identifiers). In the "list" interface, each element of the list must be a character vector of identifiers.
...	Additional parameters passed to internal method implementations.
geneUniverse	Character vector containing the universe of genes from which the gene lists were extracted. This vector must be obtained from the annotation package declared in orgPackg. For more details, refer to vignette <a href="#">goSorensen_Introduction</a> .
orgPackg	A string with the name of the genomic annotation package corresponding to a specific species to be analyzed, which must be previously installed and activated. For more details, refer to vignette <a href="#">goSorensen_Introduction</a> .
onto	string describing the ontology. Belongs to c('BP', 'MF', 'CC')
GOLevel	Integer GO level to analyze within the selected ontology. If NULL, the analysis is performed without restricting the enrichment computation to a specific GO level.
pAdjustMeth	string describing the adjust method. Belongs to c('BH', 'BY', 'Bonf')
pvalCutoff	adjusted pvalue cutoff on enrichment tests to report
qvalCutoff	qvalue cutoff on enrichment tests to report as significant. Tests must pass i) pvalueCutoff on unadjusted pvalues, ii) pvalueCutoff on adjusted pvalues and iii) qvalueCutoff on qvalues to be reported
parallel	Logical. Only in "list" interface. Defaults to FALSE, put it at TRUE for parallel computation
nOfCores	Number of cores for parallel computations. Only in "list" interface
onlyEnriched	logical. If TRUE (the default), the returned result only contains those GO terms enriched in almost one of the gene lists
keyType	Character string giving the type of gene identifier used in x, such as "ENTREZID" or "SYMBOL".

### Details

When the function argument `onlyEnriched` is `FALSE`, commonly the result is a sparse but very large object. This function is primarily designed for internal use of function `buildEnrichTable`, with argument `onlyEnriched` always put at its default `TRUE` value. Then calls to `enrichedIn` result in much more compact objects, in general.

Argument `parallel` only applies to interface "list". Its default value is "FALSE" and you may consider the trade of between the time spent in initializing parallelization and the possible time gain when parallelizing. It is difficult to establish a general guideline, but parallelizing is only worthwhile when analyzing many gene lists, on the order of 30 or more, although it depends a lot on each processor.

```
AnnotationDbi::select(org.Hs.eg.db, ...)
```

## Value

In the "character" interface, a length `k` vector of TRUE/FALSE values corresponding to enrichment or not of the GO terms at level 'GOLevel' in ontology 'onto'. If 'onlyEnriched' is FALSE, `k` corresponds to the total number of these GO terms. If 'onlyEnriched' is TRUE (default), `k` is the number of enriched GO terms (and then all values in the resulting vector are TRUE). In the "list" interface, a logical matrix of TRUE/FALSE values indicating enrichment or not, with `k` rows and `s` columns. `s` is the number of gene lists (the length of list 'x'). If 'onlyEnriched' is FALSE, `k` corresponds to the total number of GO terms at level 'GOLevel' in ontology 'onto'. If 'onlyEnriched' is TRUE (default), the resulting matrix only contains the `k` rows corresponding to GO terms enriched in at least one of these `s` gene lists. In both interfaces ("character" or "list"), the result also has an attribute (`nTerms`) with the total number of GO terms at level 'GOLevel' in ontology 'onto'.

## Methods (by class)

- `enrichedIn(default)`: S3 default method

## Examples

```
## The following example is highly time-consuming and is therefore not run
## automatically during R CMD check.

## Not run:
## i) Obtaining ENTREZ identifiers for the gene universe of humans:
library(org.Hs.eg.db)
humanEntrezIDs <- keys(org.Hs.eg.db, keytype = "ENTREZID")

## ii) Gene lists to be explored for analysis:
data(allOncoGeneLists)

# iii) Computing the threshold enrichment matrix directly from gene lists at
# GO level 4 and BP ontology:
enrichedInBP4 <- enrichedIn(allOncoGeneLists,
  geneUniverse = humanEntrezIDs,
  orgPackg = "org.Hs.eg.db",
  onto = "BP",
  GOLevel = 4
)
enrichedInBP4

## End(Not run)

# Since running this example may take several minutes, the result has been
# pre-computed and is accessible as the following:
data(enrichedInBP4)
enrichedInBP4
# This shortcut applies only to this example; for your own gene-list data,
# the computation must be performed explicitly.
```

```
# For a complete overview of this function's use, see the section 2 of the
# vignette 'Introduction to goSorensen'. You can do this by consulting the
# general package documentation or by directly running the following code in
# the R console:
# vignette("goSorensen_Introduction", package = "goSorensen")
```

---

enrichedInBP	<i>Example of the output produced by the function enrichedIn. It contains exclusively GO terms enriched in at least one list of allOncoGeneLists, ontology BP, without GO-Level restriction.</i>
--------------	--

---

## Description

A matrix with columns representing the gene lists from [allOncoGeneLists](#), and rows with GO terms in the BP ontology.

This matrix comprises logical values, with TRUE indicating that the associated GO term is enriched in the respective list, and FALSE indicating that the GO term is not enriched.

This matrix represents the output of the `enrichedIn` function with the argument `onlyEnriched = TRUE` (default), displaying exclusively the GO terms enriched in at least one list (only rows with at least one TRUE).

## Usage

```
data(enrichedInBP)
```

## Format

An object of class "matrix" "array"

## Details

The attribute `nTerms` of this matrix represents the total number of terms evaluated in the BP ontology. The difference between `nTerms` and the rows of this matrix indicates the number of non-enriched GO terms across all columns (i.e., rows filled with FALSE).

Please, consider this object as an illustrative example only, which is valid exclusively for the [allOncoGeneLists](#) data contained in this package. Note that gene lists, GO terms and Bioconductor may change over time. The current version of these results was generated with Bioconductor version 3.20.

---

enrichedInBP4	<i>Example of the output produced by the function <code>enrichedIn</code>. It contains exclusively GO terms enriched in at least one list of <code>allOncoGeneLists</code>, ontology BP, GO-Level 4.</i>
---------------	--

---

### Description

A matrix with columns representing the gene lists from `allOncoGeneLists`, and rows with GO terms in the BP ontology at GO-Level 4.

This matrix comprises logit values, with TRUE indicating that the associated GO term is enriched in the respective list, and FALSE indicating that the GO term is not enriched.

This matrix represents the output of the `enrichedIn` function with the argument `onlyEnriched = TRUE` (default), displaying exclusively the GO terms enriched in at least one list (only rows with at least one TRUE).

### Usage

```
data(enrichedInBP4)
```

### Format

An object of class "matrix" "array"

### Details

The attribute `nTerms` of this matrix represents the total number of terms evaluated in the BP ontology at GO-Level 4. The difference between `nTerms` and the rows of this matrix indicates the number of non-enriched GO terms across all columns (i.e., rows filled with FALSE).

Please, consider this object as an illustrative example only, which is valid exclusively for the `allOncoGeneLists` data contained in this package. Note that gene lists, GO terms and Bioconductor may change over time. The current version of these results was generated with Bioconductor version 3.20.

---

eqTest_all_BP	<i>Example of the output produced by the function <code>equivTestSorensen</code>. It contains all the possible equivalence tests for the lists from <code>allOncoGeneLists</code> in ontology BP without GO-Level restriction.</i>
---------------	--

---

### Description

From the seven lists contained in `allOncoGeneLists`, this object contains the  $7(6)/2 = 21$  possible outputs for the equivalence tests to compare all possible pairs of lists, using the normal asymptotic distribution.

### Usage

```
data(eqTest_all_BP)
```

**Format**

An exclusive object from goSorensen of the class "equivSDhstestList"

**Details**

The parameters considered to execute these tests are: irrelevance limit  $d0 = 0.4444$  and confidence level `conf.level = 0.95`.

Consider this object only as an illustrative example, which is valid exclusively for the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

eqTest\_all\_BP4

*Example of the output produced by the function equivTestSorensen. It contains all the possible equivalence tests for the lists from allOncoGeneLists at level 4 of ontology BP.*

---

**Description**

From the seven lists contained in `allOncoGeneLists`, this object contains the  $7(6)/2 = 21$  possible outputs for the equivalence tests to compare all possible pairs of lists, using the normal asymptotic distribution.

**Usage**

```
data(eqTest_all_BP4)
```

**Format**

An exclusive object from goSorensen of the class "equivSDhstestList"

**Details**

The parameters considered to execute these tests are: irrelevance limit  $d0 = 0.4444$  and confidence level `conf.level = 0.95`.

Consider this object only as an illustrative example, which is valid exclusively for the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

eqTest\_atlas.sanger\_BP

*Example of the output produced by the function equivTestSorensen. It contains the equivalence test for comparing two lists in ontology BP without GO-Level restriction.*

---

### Description

The output of an equivalence test to detect biological similarity between the lists atlas and sanger from allOncoGeneLists, based on the normal asymptotic distribution.

### Usage

```
data(eqTest_atlas.sanger_BP)
```

### Format

An exclusive object from goSorensen of the class "equivSDhtest"

### Details

The parameters considered to execute this test are: irrelevance limit  $d0 = 0.4444$  and confidence level `conf.level = 0.95`.

Consider this object only as an illustrative example, which is valid exclusively for the lists atlas and sanger from the data [allOncoGeneLists](#) contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

eqTest\_atlas.sanger\_BP4

*Example of the output produced by the function equivTestSorensen. It contains the equivalence test for comparing two lists at level 4 of ontology BP.*

---

### Description

The output of an equivalence test to detect biological similarity between the lists atlas and sanger from allOncoGeneLists, based on the normal asymptotic distribution.

### Usage

```
data(eqTest_atlas.sanger_BP4)
```

### Format

An exclusive object from 'goSorensen' of the class "equivSDhtest"

## Details

The parameters considered to execute this test are: irrelevance limit  $d_0 = 0.4444$  and confidence level `conf.level = 0.95`.

Consider this object only as an illustrative example, which is valid exclusively for the lists atlas and sanger from the data `allOncoGeneLists` contained in this package. Note that gene lists, GO terms, and Bioconductor may change over time. The current version of these results were generated with Bioconductor version 3.20.

---

equivTestSorensen	<i>Equivalence test based on the Sorensen-Dice dissimilarity</i>
-------------------	--

---

## Description

Equivalence test based on the Sorensen-Dice dissimilarity, computed either by an asymptotic normal approach or by a bootstrap approach.

## Usage

```
equivTestSorensen(x, ...)

## S3 method for class 'character'
equivTestSorensen(
  x,
  y,
  d0 = 1/(1 + 1.25),
  conf.level = 0.95,
  boot = FALSE,
  nboot = 10000,
  check.table = TRUE,
  ...
)
```

## Arguments

<code>x</code>	either an object of class "table", "matrix", "numeric", "character", "list" or "tableList". See the details section for more information.
<code>...</code>	extra parameters for function <code>buildEnrichTable</code> .
<code>y</code>	an object of class "character" representing a list of gene identifiers (e.g., ENTREZ).
<code>d0</code>	equivalence threshold for the Sorensen-Dice dissimilarity, $d$ . The null hypothesis states that $d \geq d_0$ , i.e., inequivalence between the compared gene lists and the alternative that $d < d_0$ , i.e., equivalence or dissimilarity irrelevance (up to a level $d_0$ ).
<code>conf.level</code>	confidence level of the one-sided confidence interval, a value between 0 and 1.
<code>boot</code>	boolean. If TRUE, the confidence interval and the test p-value are computed by means of a bootstrap approach instead of the asymptotic normal approach. Defaults to FALSE.
<code>nboot</code>	numeric, number of initially planned bootstrap replicates. Ignored if <code>boot == FALSE</code> . Defaults to 10000.

`check.table` Boolean. If TRUE (default), argument `x` is checked to adequately represent a 2x2 contingency table (or an aggregate of them) or gene lists producing a correct table. This checking is performed by means of function `nice2x2Table`.

## Details

This function computes either the normal asymptotic or the bootstrap equivalence test based on the Sorensen-Dice dissimilarity, given a 2x2 arrangement of frequencies (either implemented as a "table", a "matrix" or a "numeric" object):

$$\begin{array}{cc} n_{11} & n_{10} \\ n_{01} & n_{00}, \end{array}$$

The subindex '11' corresponds to those GO terms enriched in both lists, '01' to terms enriched in the second list but not in the first one, '10' to terms enriched in the first list but not enriched in the second one and '00' corresponds to those GO terms non enriched in both gene lists, i.e., to the double negatives, a value which is ignored in the computations.

In the "numeric" interface, if `length(x) >= 4`, the values are interpreted as  $(n_{11}, n_{01}, n_{10}, n_{00})$ , always in this order and discarding extra values if necessary.

If `x` is an object of class "character", then `x` (and `y`) must represent two "character" vectors of valid gene identifiers (e.g., ENTREZ). Then the equivalence test is performed between `x` and `y`, after internally summarizing them as a 2x2 contingency table of joint enrichment. This last operation is performed by function `buildEnrichTable` and "valid gene identifiers (e.g., ENTREZ)" stands for the coherency of these gene identifiers with the arguments `geneUniverse` and `orgPackg` of `buildEnrichTable`, passed by the ellipsis argument `...` in `equivTestSorensen`.

If `x` is an object of class "list", each of its elements must be a "character" vector of gene identifiers (e.g., ENTREZ). Then all pairwise equivalence tests are performed between these gene lists.

Class "tableList" corresponds to objects representing all mutual enrichment contingency tables generated in a pairwise fashion: Given gene lists `l1`, `l2`, ..., `lk`, an object of class "tableList" (typically constructed by a call to function `buildEnrichTable`) is a list of lists of contingency tables `tij` generated from each pair of gene lists `i` and `j`, with the following structure:

\$l2

\$l2\$l1\$t21

\$l3

\$l3\$l1\$t31, \$l3\$l2\$t32

...

\$lk\$l1\$tk1, \$lk\$l2\$tk2, ..., \$lk\$l(k-1)\$tk(k-1)

If `x` is an object of class "tableList", the test is performed over each one of these tables.

The test is based on the fact that the studentized statistic  $(\hat{d} - d) / \hat{se}$  is approximately distributed as a standard normal.  $\hat{d}$  stands for the sample Sorensen-Dice dissimilarity,  $d$  for its true (unknown) value and  $\hat{se}$  for the estimate of its standard error. This result is asymptotically correct, but the true distribution of the studentized statistic is not exactly normal for finite samples, with a heavier left tail than expected under the Gaussian model, which may produce some type I error inflation. The bootstrap method provides a better approximation to this distribution. In the bootstrap approach, `nboot` new bootstrap contingency tables are generated from a multinomial distribution with parameters  $size = n = (n_{11} + n_{01} + n_{10} + n_{00})$  and probabilities  $(n_{11}/n, n_{01}/n, n_{10}/n, n_{00}/n)$ . Sometimes, some of these generated tables may present so low frequencies of enrichment that make them unable for Sorensen-Dice computations. As a consequence, the number of effective bootstrap samples may be lower than the number of initially planned ones, `nboot`, but our simulation studies

concluded that this makes the test more conservative, less prone to reject a truly false null hypothesis of inequivalence, but in any case protects from inflating the type I error.

In a bootstrap test result, use `getNboot` to access the number of initially planned bootstrap replicates and `getEffNboot` to access the number of finally effective bootstrap replicates.

## Value

See method-specific documentation.

For all interfaces (except for the "list" and "tableList" interfaces), the result is a list of class "equivSDhstest" which inherits from "hstest", with the following components:

**statistic** The value of the studentized statistic  $(dSorensen(x) - d0)/seSorensen(x)$ .

**p.value** The p-value of the test.

**conf.int** The one-sided confidence interval  $(0, dUpp]$ .

**estimate** The Sorensen dissimilarity estimate,  $dSorensen(x)$ .

**null.value** The value of  $d0$ .

**stderr** The standard error of the Sorensen dissimilarity estimate,  $seSorensen(x)$ , used as denominator in the studentized statistic.

**alternative** A character string describing the alternative hypothesis.

**method** A character string describing the test.

**data.name** A character string giving the names of the data.

**enrichTab** The 2x2 contingency table of joint enrichment on which the test was based.

For the "list" and "tableList" interfaces, the result is an object of class "equivSDhstestList", a list of all pairwise comparisons, each one being an object of class "equivSDhstest".

## Methods (by class)

- `equivTestSorensen(character)`: S3 default method.

## See Also

[nice2x2Table](#) for checking and reformatting data, [dSorensen](#) for computing the Sorensen-Dice dissimilarity, [seSorensen](#) for computing the standard error of the dissimilarity, [duppSorensen](#) for the upper limit of a one-sided confidence interval of the dissimilarity. [getTable](#), [getPvalue](#), [getUpper](#), [getSE](#), [getNboot](#) and [getEffNboot](#) for accessing specific fields in the result of these testing functions. [update](#) for updating the result of these testing functions with alternative equivalence limits, confidence levels or to convert a normal result in a bootstrap result or the reverse.

## Examples

```
## The following example is highly time-consuming and is therefore not run
## automatically during R CMD check.
```

```
## Not run:
```

```
## i) Obtaining ENTREZ identifiers for the gene universe of humans:
library(org.Hs.eg.db)
humanEntrezIDs <- keys(org.Hs.eg.db, keytype = "ENTREZID")
```

```
## ii) Gene lists to be explored for analysis:
data(allOncogeneLists)
```

```

# iii) Calculation of Calculation of the equivalence test of all joint
# enrichment contingency tables obtained from the BP ontology at the GO 4
# level.
eqTest_all_BP4 <- equivTestSorensen(allOncoGeneLists,
  geneUniverse = humanEntrezIDs,
  orgPackg = "org.Hs.eg.db",
  onto = "BP",
  GOLevel = 4,
  d0 = 0.4444,
  conf.level = 0.95
)
eqTest_all_BP4

## End(Not run)

# Since running this example may take several minutes, the result has been
# pre-computed and is accessible as the following:
data(eqTest_all_BP4)
eqTest_all_BP4
# This shortcut applies only to this example; for your own gene-list data,
# the computation must be performed explicitly.

# For a complete overview of this function's use, see the section 4 of the
# vignette "Introduction to goSorensen". You can do this by consulting the
# general package documentation or by directly running the following code in
# the R console:
# vignette("goSorensen_Introduction", package = "goSorensen")

```

---

fullEnrichedInBP	<i>Example of the output produced by the function enrichedIn. It contains all the GO terms enriched or not-enriched in the lists of allOncoGeneLists, ontology BP, without GO-Level restriction.</i>
------------------	--

---

## Description

A matrix with columns representing the gene lists from [allOncoGeneLists](#), and rows with GO terms in the BP ontology.

This matrix comprises logical values, with TRUE indicating that the associated GO term is enriched in the respective list, and FALSE indicating that the GO term is not enriched.

This matrix represents the output of the [enrichedIn](#) function with the argument `onlyEnriched = FALSE`. The rows of this matrix display all the GO terms involved in the BP ontology.

## Usage

```
data(fullEnrichedInBP)
```

## Format

An object of class "matrix" "array"

**Details**

The attribute `nTerms` indicates the total number of GO terms evaluated in the BP ontology. For this particular case, `nTerms` matches with the number of rows of the matrix.

Please, consider this object as an illustrative example only, which is valid exclusively for the [allOncoGeneLists](#) data contained in this package. Please note that gene lists, GO terms and Bioconductor may change over time. The current version of these results was generated with Bioconductor version 3.20.

---

<code>fullEnrichedInBP4</code>	<i>Example of the output produced by the function <code>enrichedIn</code>. It contains all the GO terms enriched or not-enriched in the lists of <code>allOncoGeneLists</code>, ontology BP, GO-Level 4.</i>
--------------------------------	--

---

**Description**

A matrix with columns representing the gene lists from [allOncoGeneLists](#), and rows with GO terms in the BP ontology at GO-Level 4.

This matrix comprises logit values, with TRUE indicating that the associated GO term is enriched in the respective list, and FALSE indicating that the GO term is not enriched.

This matrix represents the output of the `enrichedIn` function with the argument `onlyEnriched = FALSE`. The rows of this matrix display all the GO terms involved in the BP ontology at GO-Level 4.

**Usage**

```
data(fullEnrichedInBP4)
```

**Format**

An object of class "matrix" "array"

**Details**

The attribute `nTerms` indicates the total number of GO terms evaluated in the BP ontology, GO-Level 4. For this particular case, `nTerms` matches with the number of rows of the matrix

Please, consider this object as an illustrative example only, which is valid exclusively for the [allOncoGeneLists](#) data contained in this package. Please note that gene lists, GO terms and Bioconductor may change over time. The current version of these results was generated with Bioconductor version 3.20.

---

getDissimilarity	<i>Access to the estimated Sorensen-Dice dissimilarity in one or more e quivalence test results</i>
------------------	---

---

### Description

Given objects representing the result(s) of one or more equivalence tests (classes "equivSDhtest", "equivSDhtestList" or "allEquivSDtest", i.e., the result of functions 'equivTestSorensen' and 'allEquivTestSorensen') this function returns the estimated dissimilarities in the tests.

### Usage

```
getDissimilarity(x, ...)

## S3 method for class 'equivSDhtest'
getDissimilarity(x, ...)

## S3 method for class 'equivSDhtestList'
getDissimilarity(x, simplify = TRUE, ...)

## S3 method for class 'AllEquivSDhtest'
getDissimilarity(x, onto, GOlevel, listNames, simplify = TRUE, ...)
```

### Arguments

x	an object of class "equivSDhtest" or "equivSDhtestList" or "allEquivSDtest".
...	Additional parameters.
simplify	logical, if TRUE the result is simplified, e.g., returning a vector instead of a matrix.
onto	character, a vector with one or more of "BP", "CC" or "MF", ontologies to access.
GOlevel	numeric or character, a vector with one or more GO levels to access. See the details section and the examples.
listNames	character(2), the names of a pair of gene lists.

### Details

Argument `GOlevel` can be of class "character" or "numeric". In the first case, the GO levels must be specified like "level 6" or `c("level 4", "level 5", "level 6")` In the second case ("numeric"), the GO levels must be specified like `6` or `seq.int(4, 6)`.

### Value

When `x` is an object of class "equivSDhtest" (i.e., the result of a single equivalence test), the returned value is a single numeric value, the Sorensen-Dice dissimilarity. For an object of class "equivSDhtestList" (i.e. all pairwise tests for a set of gene lists), if `simplify = TRUE` (the default), the resulting value is a vector with the dissimilarities in all those tests, or the symmetric matrix of all dissimilarities if `simplify = FALSE`. If `x` is an object of class "allEquivSDtest" (i.e., the test iterated along GO ontologies and levels), the preceding result is returned in the form of a list along the ontologies, levels and pairs of gene lists specified by the arguments `onto`, `GOlevel` and `listNames` (or all present in `x` for missing arguments).

**Methods (by class)**

- getDissimilarity(equivSDhtest): S3 method for class "equivSDhtest"
- getDissimilarity(equivSDhtestList): S3 method for class "equivSDhtestList"
- getDissimilarity(AllEquivSDhtest): S3 method for class "AllEquivSDhtest"

**Examples**

```
# Manually define a 2 x 2 enrichment contingency table
contTable <- as.table(matrix(c(127, 19, 159, 3018),
  nrow = 2,
  dimnames = list(
    "Enriched in List 1" = c(TRUE, FALSE),
    "Enriched in List 2" = c(TRUE, FALSE)
  )
))
contTable

# Compute the Sorensen equivalence test from the contingency table.
# The result is an object of class "equivSDhtest".
equivalenceTest <- equivTestSorensen(contTable)
equivalenceTest

# Extract the Sorensen dissimilarity value from the equivalence test object
getDissimilarity(equivalenceTest)
```

---

getEffNboot

*Access to the number of effective bootstrap replicates in one or more equivalence test results (only for their bootstrap version)*

---

**Description**

Given objects representing the result(s) of one or more equivalence tests (classes "equivSDhtest", "equivSDhtestList" or "allEquivSDhtest", i.e., the result of functions 'equivTestSorensen' and 'allEquivTestSorensen'), this function returns the number of effective bootstrap replicates. Obviously, this only applies to calls of these functions with the parameter boot = TRUE, otherwise it returns a NA value. See the details section for further explanation.

**Usage**

```
getEffNboot(x, ...)

## S3 method for class 'equivSDhtest'
getEffNboot(x, ...)

## S3 method for class 'equivSDhtestList'
getEffNboot(x, simplify = TRUE, ...)

## S3 method for class 'AllEquivSDhtest'
getEffNboot(x, onto, GOLevel, listNames, simplify = TRUE, ...)
```

**Arguments**

<code>x</code>	an object of class "equivSDhtest" or "equivSDhtestList" or "allEquivSDtest".
<code>...</code>	Additional parameters.
<code>simplify</code>	logical, if TRUE the result is simplified, e.g., returning a vector instead of a matrix.
<code>onto</code>	character, a vector with one or more of "BP", "CC" or "MF", ontologies to access.
<code>GOlevel</code>	numeric or character, a vector with one or more GO levels to access. See the details section and the examples.
<code>listNames</code>	character(2), the names of a pair of gene lists.

**Details**

In the bootstrap version of the equivalence test, resampling is performed generating new bootstrap contingency tables from a multinomial distribution based on the "real", observed, frequencies of mutual enrichment. In some bootstrap resamples, the generated contingency table of mutual enrichment may have very low frequencies of enrichment, which makes it unable for Sorensen-Dice computations. Then, the number of effective bootstrap resamples may be lower than those initially planned. To get the number of initially planned bootstrap resamples use function `getNboot`.

Argument `GOlevel` can be of class "character" or "numeric". In the first case, the GO levels must be specified like "level 6" or `c("level 4", "level 5", "level 6")` In the second case ("numeric"), the GO levels must be specified like `6` or `seq.int(4, 6)`.

**Value**

When `x` is an object of class "equivSDhtest" (i.e., the result of a single equivalence test), the returned value is a single numeric value, the number of effective bootstrap replicates, or NA if bootstrapping has not been performed. For an object of class "equivSDhtestList" (i.e. all pairwise tests for a set of gene lists), if `simplify = TRUE` (the default), the resulting value is a vector with the number of effective bootstrap replicates in all those tests, or the symmetric matrix of all these values if `simplify = FALSE`. If `x` is an object of class "allEquivSDtest" (i.e., the test iterated along GO ontologies and levels), the preceding result is returned in the form of a list along the ontologies, levels and pairs of gene lists specified by the arguments `onto`, `GOlevel` and `listNames` (or all present in `x` for missing arguments).

**Methods (by class)**

- `getEffNboot(equivSDhtest)`: S3 method for class "equivSDhtest"
- `getEffNboot(equivSDhtestList)`: S3 method for class "equivSDhtestList"
- `getEffNboot(AllEquivSDhtest)`: S3 method for class "AllEquivSDhtest"

**See Also**

[getNboot](#)

**Examples**

```
# Dataset 'allOncoGeneLists' contains the result of the equivalence test between gene lists
# 'sanger' and 'atlas', at level 4 of the BP ontology:
data(eqTest_atlas.sanger_BP4)
eqTest_atlas.sanger_BP4
```

```

class(eqTest_atlas.sanger_BP4)
# This may correspond to the result of code like:
# eqTest_atlas.sanger_BP4 <- equivTestSorensen(
#   allOncoGeneLists[["sanger"]], allOncoGeneLists[["atlas"]],
#   geneUniverse = humanEntrezIDs, orgPackg = "org.Hs.eg.db",
#   onto = "BP", GOLevel = 4, listNames = c("sanger", "atlas"))
#
# (But results may vary according to GO updating)

# Not a bootstrap test, first upgrade to a bootstrap test:
boot.sanger_atlas.BP.4 <- upgrade(eqTest_atlas.sanger_BP4, boot = TRUE)

# getEffNboot(eqTest_atlas.sanger_BP4)
getEffNboot(boot.sanger_atlas.BP.4)
getNboot(boot.sanger_atlas.BP.4)

# All pairwise equivalence tests at level 4 of the BP ontology
data(eqTest_all_BP4)
?eqTest_all_BP4
class(eqTest_all_BP4)
# This may correspond to a call like:
# eqTest_all_BP4 <- equivTestSorensen(allOncoGeneLists,
#   geneUniverse = humanEntrezIDs, orgPackg = "org.Hs.eg.db",
#   onto = "BP", GOLevel = 4)
boot.BP.4 <- upgrade(eqTest_all_BP4, boot = TRUE)
getEffNboot(eqTest_all_BP4)
getEffNboot(boot.BP.4)
getNboot(boot.BP.4)
getEffNboot(boot.BP.4, simplify = FALSE)

# Bootstrap equivalence test iterated over all GO ontologies and levels 3 to 10.
# data(allEqTests)
# ?allEqTests
# class(allEqTests)
# This may correspond to code like:
# (By default, the tests are iterated over all GO ontologies and for levels 3 to 10)
# allEqTests <- allEquivTestSorensen(allOncoGeneLists,
#   geneUniverse = humanEntrezIDs,
#   orgPackg = "org.Hs.eg.db",
#   boot = TRUE)
# boot.allEqTests <- upgrade(allEqTests, boot = TRUE)
# Number of effective bootstrap replicates for all tests:
# getEffNboot(boot.allEqTests)
# getEffNboot(boot.allEqTests, simplify = FALSE)

# Number of effective bootstrap replicates for specific GO ontologies, levels or pairs
# of gene lists:
# getEffNboot(boot.allEqTests, GOLevel = "level 6")
# getEffNboot(boot.allEqTests, GOLevel = 6)
# getEffNboot(boot.allEqTests, GOLevel = seq.int(4,6))
# getEffNboot(boot.allEqTests, GOLevel = "level 6", simplify = FALSE)
# getEffNboot(boot.allEqTests, GOLevel = "level 6", listNames = c("waldman", "sanger"))
# getEffNboot(boot.allEqTests, GOLevel = seq.int(4,6), onto = "BP")
# getEffNboot(boot.allEqTests, GOLevel = seq.int(4,6), onto = "BP", simplify = FALSE)
# getEffNboot(boot.allEqTests, GOLevel = "level 6", onto = "BP",
#   listNames = c("atlas", "sanger"))
# getEffNboot(boot.allEqTests$BP$`level 4`)

```

---

getNboot	<i>Access to the number of initially planned bootstrap replicates in one or more equivalence test results (only in their bootstrap version)</i>
----------	---

---

### Description

Given objects representing the result(s) of one or more equivalence tests (classes "equivSDhtest", "equivSDhtestList" or "allEquivSDtest", i.e., the result of functions 'equivTestSorensen' and 'allEquivTestSorensen' with the parameter boot = TRUE), this function returns the number of initially planned bootstrap replicates in these equivalence tests, which may be greater than the number of finally effective or valid bootstrap replicates. See the details section for more information on this.

### Usage

```
getNboot(x, ...)
```

```
## S3 method for class 'equivSDhtest'
getNboot(x, ...)
```

```
## S3 method for class 'equivSDhtestList'
getNboot(x, simplify = TRUE, ...)
```

```
## S3 method for class 'AllEquivSDhtest'
getNboot(x, onto, GOlevel, listNames, simplify = TRUE, ...)
```

### Arguments

x	an object of class "equivSDhtest" or "equivSDhtestList" or "allEquivSDtest".
...	Additional parameters.
simplify	logical, if TRUE the result is simplified, e.g., returning a vector instead of a matrix.
onto	character, a vector with one or more of "BP", "CC" or "MF", ontologies to access.
GOlevel	numeric or character, a vector with one or more GO levels to access. See the details section and the examples.
listNames	character(2), the names of a pair of gene lists.

### Details

In the bootstrap version of the equivalence test, resampling is performed generating new bootstrap contingency tables from a multinomial distribution based on the "real", observed, frequencies of mutual enrichment. In some bootstrap iterations, the generated contingency table of mutual enrichment may have very low frequencies of enrichment, which makes it unable for Sorensen-Dice computations. Then, the number of effective bootstrap resamples may be lower than those initially planned. To get the number of effective bootstrap resamples use function getEffNboot.

Argument GOlevel can be of class "character" or "numeric". In the first case, the GO levels must be specified like "level 6" or c("level 4", "level 5", "level 6") In the second case ("numeric"), the GO levels must be specified like 6 or seq.int(4, 6).

**Value**

When `x` is an object of class "equivSDhtest" (i.e., the result of a single equivalence test), the returned value is a single numeric value, the number of initially planned bootstrap replicates, or NA if bootstrapping has not been performed. For an object of class "equivSDhtestList" (i.e. all pairwise tests for a set of gene lists), if `simplify = TRUE` (the default), the resulting value is a vector with the number of initially bootstrap replicates in all those tests, or the symmetric matrix of all these values if `simplify = FALSE`. If `x` is an object of class "allEquivSDhtest" (i.e., the test iterated along GO ontologies and levels), the preceding result is returned in the form of a list along the ontologies, levels and pairs of gene lists specified by the arguments `onto`, `GOlevel` and `listNames` (or all present in `x` for missing arguments).

**Methods (by class)**

- `getNboot(equivSDhtest)`: S3 method for class "equivSDhtest"
- `getNboot(equivSDhtestList)`: S3 method for class "equivSDhtestList"
- `getNboot(AllEquivSDhtest)`: S3 method for class "AllEquivSDhtest"

**See Also**

[getEffNboot](#)

**Examples**

```
# Dataset 'allOncoGeneLists' contains the result of the equivalence test between gene lists
# 'sanger' and 'atlas', at level 4 of the BP ontology:
data(eqTest_atlas.sanger_BP4)
eqTest_atlas.sanger_BP4
class(eqTest_atlas.sanger_BP4)
# This may correspond to the result of code like:
# eqTest_atlas.sanger_BP4 <- equivTestSorensen(
#   allOncoGeneLists[["sanger"]], allOncoGeneLists[["atlas"]],
#   geneUniverse = humanEntrezIDs, orgPackg = "org.Hs.eg.db",
#   onto = "BP", GOlevel = 4, listNames = c("sanger", "atlas"))
#
# (But results may vary according to GO updating)

# Not a bootstrap test, first upgrade to a bootstrap test:
boot.eqTest_atlas.sanger_BP4 <- upgrade(eqTest_atlas.sanger_BP4, boot = TRUE)

getNboot(eqTest_atlas.sanger_BP4)
getNboot(boot.eqTest_atlas.sanger_BP4)

# All pairwise equivalence tests at level 4 of the BP ontology
data(eqTest_all_BP4)
?eqTest_all_BP4
class(eqTest_all_BP4)
# This may correspond to a call like:
# eqTest_all_BP4 <- equivTestSorensen(allOncoGeneLists,
#   geneUniverse = humanEntrezIDs, orgPackg = "org.Hs.eg.db",
#   onto = "BP", GOlevel = 4)
boot.eqTest_all_BP4 <- upgrade(eqTest_all_BP4, boot = TRUE)
getNboot(eqTest_all_BP4)
getNboot(boot.eqTest_all_BP4)
getNboot(boot.eqTest_all_BP4, simplify = FALSE)
```

```

# Bootstrap equivalence test iterated over all GO ontologies and levels 3 to 10.
# data(allEqTests)
# ?allEqTests
# class(allEqTests)
# This may correspond to code like:
# (By default, the tests are iterated over all GO ontologies and for levels 3 to 10)
# allEqTests <- allEquivTestSorensen(allOncoGeneLists,
#                                   geneUniverse = humanEntrezIDs,
#                                   orgPackg = "org.Hs.eg.db",
#                                   boot = TRUE)
# boot.allEqTests <- upgrade(allEqTests, boot = TRUE)
# All numbers of bootstrap replicates:
# getNboot(boot.allEqTests)
# getNboot(boot.allEqTests, simplify = FALSE)

# Number of bootstrap replicates for specific GO ontologies, levels or pairs of gene lists:
# getNboot(boot.allEqTests, GOLevel = "level 6")
# getNboot(boot.allEqTests, GOLevel = 6)
# getNboot(boot.allEqTests, GOLevel = seq.int(4,6))
# getNboot(boot.allEqTests, GOLevel = "level 6", simplify = FALSE)
# getNboot(boot.allEqTests, GOLevel = "level 6", listNames = c("atlas", "sanger"))
# getNboot(boot.allEqTests, GOLevel = seq.int(4,6), onto = "BP")
# getNboot(boot.allEqTests, GOLevel = seq.int(4,6), onto = "BP", simplify = FALSE)
# getNboot(boot.allEqTests, GOLevel = "level 6", onto = "BP",
#           listNames = c("waldman", "sanger"))
# getNboot(boot.allEqTests$BP$`level 4`)

```

---

getPvalue

*Access to the p-value of one or more equivalence test results*

---

## Description

Given objects representing the result(s) of one or more equivalence tests (classes "equivSDhtest", "equivSDhtestList" or "allEquivSDtest", i.e., the result of functions 'equivTestSorensen' and 'allEquivTestSorensen') this function returns the p-values of the tests.

## Usage

```
getPvalue(x, ...)
```

```
## S3 method for class 'equivSDhtest'
```

```
getPvalue(x, ...)
```

```
## S3 method for class 'equivSDhtestList'
```

```
getPvalue(x, simplify = TRUE, ...)
```

```
## S3 method for class 'AllEquivSDhtest'
```

```
getPvalue(x, onto, GOLevel, listNames, simplify = TRUE, ...)
```

## Arguments

x an object of class "equivSDhtest" or "equivSDhtestList" or "allEquivSDtest".

...	Additional parameters.
simplify	logical, if TRUE the result is simplified, e.g., returning a vector instead of a matrix.
onto	character, a vector with one or more of "BP", "CC" or "MF", ontologies to access.
GOlevel	numeric or character, a vector with one or more GO levels to access. See the details section and the examples.
listNames	character(2), the names of a pair of gene lists.

### Details

Argument `GOlevel` can be of class "character" or "numeric". In the first case, the GO levels must be specified like "level 6" or `c("level 4", "level 5", "level 6")`. In the second case ("numeric"), the GO levels must be specified like `6` or `seq.int(4, 6)`.

### Value

When `x` is an object of class "equivSDhtest" (i.e., the result of a single equivalence test), the returned value is a single numeric value, the test p-value. For an object of class "equivSDhtestList" (i.e. all pairwise tests for a set of gene lists), if `simplify = TRUE` (the default), the resulting value is a vector with the p-values in all those tests, or the symmetric matrix of all p-values if `simplify = FALSE`. If `x` is an object of class "allEquivSDhtest" (i.e., the test iterated along GO ontologies and levels), the preceding result is returned in the form of a list along the ontologies, levels and pairs of gene lists specified by the arguments `onto`, `GOlevel` and `listNames` (or all present in `x` for missing arguments).

### Methods (by class)

- `getPvalue(equivSDhtest)`: S3 method for class "equivSDhtest"
- `getPvalue(equivSDhtestList)`: S3 method for class "equivSDhtestList"
- `getPvalue(AllEquivSDhtest)`: S3 method for class "AllEquivSDhtest"

### Examples

```
# Manually define a 2 x 2 enrichment contingency table
contTable <- as.table(matrix(c(127, 19, 159, 3018),
  nrow = 2,
  dimnames = list(
    "Enriched in List 1" = c(TRUE, FALSE),
    "Enriched in List 2" = c(TRUE, FALSE)
  )
))
contTable

# Compute the Sorensen equivalence test from the contingency table.
# The result is an object of class "equivSDhtest".
equivalenceTest <- equivTestSorensen(contTable)
equivalenceTest

# Extract the pvalue from the equivalence test object
getPvalue(equivalenceTest)
```

---

getSE	<i>Access to the estimated standard error of the sample Sorensen-Dice dissimilarity in one or more equivalence test results</i>
-------	---

---

### Description

Given objects representing the result(s) of one or more equivalence tests (classes "equivSDhtest", "equivSDhtestList" or "allEquivSDtest", i.e., the result of functions 'equivTestSorensen' and 'allEquivTestSorensen') this function returns the estimated standard errors of the sample dissimilarities in the tests.

### Usage

```
getSE(x, ...)

## S3 method for class 'equivSDhtest'
getSE(x, ...)

## S3 method for class 'equivSDhtestList'
getSE(x, simplify = TRUE, ...)

## S3 method for class 'AllEquivSDhtest'
getSE(x, onto, GOLevel, listNames, simplify = TRUE, ...)
```

### Arguments

x	an object of class "equivSDhtest" or "equivSDhtestList" or "allEquivSDtest".
...	additional parameters.
simplify	logical, if TRUE the result is simplified, e.g., returning a vector instead of a matrix.
onto	character, a vector with one or more of "BP", "CC" or "MF", ontologies to access.
GOLevel	numeric or character, a vector with one or more GO levels to access. See the details section and the examples.
listNames	character(2), the names of a pair of gene lists.

### Details

Argument `GOLevel` can be of class "character" or "numeric". In the first case, the GO levels must be specified like "level 6" or `c("level 4", "level 5", "level 6")` In the second case ("numeric"), the GO levels must be specified like `6` or `seq.int(4,6)`.

### Value

When `x` is an object of class "equivSDhtest" (i.e., the result of a single equivalence test), the returned value is a single numeric value, the standard error of the Sorensen-Dice dissimilarity estimate. For an object of class "equivSDhtestList" (i.e. all pairwise tests for a set of gene lists), if `simplify = TRUE` (the default), the resulting value is a vector with the dissimilarity standard errors in all those tests, or the symmetric matrix of all these values if `simplify = FALSE`. If `x` is an object of class "allEquivSDtest" (i.e., the test iterated along GO ontologies and levels), the preceding result is

returned in the form of a list along the ontologies, levels and pairs of gene lists specified by the arguments `onto`, `GOlevel` and `listNames` (or all present in `x` for missing arguments).

### Methods (by class)

- `getSE(equivSDhtest)`: S3 method for class "equivSDhtest"
- `getSE(equivSDhtestList)`: S3 method for class "equivSDhtestList"
- `getSE(AllEquivSDhtest)`: S3 method for class "AllEquivSDhtest"

### Examples

```
# Manually define a 2 x 2 enrichment contingency table
contTable <- as.table(matrix(c(127, 19, 159, 3018),
  nrow = 2,
  dimnames = list(
    "Enriched in List 1" = c(TRUE, FALSE),
    "Enriched in List 2" = c(TRUE, FALSE)
  )
))
contTable

# Compute the Sorensen equivalence test from the contingency table.
# The result is an object of class "equivSDhtest".
equivalenceTest <- equivTestSorensen(contTable)
equivalenceTest

# Extract the standard error value from the equivalence test object
getSE(equivalenceTest)
```

---

getTable	<i>Access to the contingency table of mutual enrichment of one or more equivalence test results</i>
----------	---

---

### Description

Given objects representing the result(s) of one or more equivalence tests (classes "equivSDhtest", "equivSDhtestList" or "allEquivSDhtest", i.e., the result of functions 'equivTestSorensen' and 'allEquivTestSorensen') this function returns the contingency tables from which the tests were performed.

### Usage

```
getTable(x, ...)
```

## S3 method for class 'equivSDhtest'

```
getTable(x, ...)
```

## S3 method for class 'equivSDhtestList'

```
getTable(x, ...)
```

## S3 method for class 'AllEquivSDhtest'

```
getTable(x, onto, GOlevel, listNames, ...)
```

**Arguments**

x	an object of class "equivSDhstest" or "equivSDhstestList" or "allEquivSDtest".
...	Additional parameters.
onto	character, a vector with one or more of "BP", "CC" or "MF", ontologies to access.
GOlevel	numeric or character, a vector with one or more GO levels to access. See the details section and the examples.
listNames	character(2), the names of a pair of gene lists.

**Details**

Argument `GOlevel` can be of class "character" or "numeric". In the first case, the GO levels must be specified like "level 6" or `c("level 4", "level 5", "level 6")`. In the second case ("numeric"), the GO levels must be specified like `6` or `4:6`.

**Value**

An object of class "table", the 2x2 enrichment contingency table of mutual enrichment in two gene lists, built to perform the equivalence test based on the Sorensen-Dice dissimilarity.

When `x` is an object of class "equivSDhstest" (i.e., the result of a single equivalence test), the returned value is an object of class "table", the 2x2 enrichment contingency table of mutual enrichment in two gene lists, built to perform the equivalence test based on the Sorensen-Dice dissimilarity. For an object of class "equivSDhstestList" (i.e. all pairwise tests for a set of gene lists), the resulting value is a list with all the tables built in all those tests. If `x` is an object of class "allEquivSDtest" (i.e., the test iterated along GO ontologies and levels), the preceding result is returned as a list along the ontologies, levels and pairs of gene lists specified by the arguments `onto`, `GOlevel` and `listNames` (or all ontologies, levels or pairs of gene lists present in `x` if one or more of these arguments are missing).

**Methods (by class)**

- `getTable(equivSDhstest)`: S3 method for class "equivSDhstest"
- `getTable(equivSDhstestList)`: S3 method for class "equivSDhstestList"
- `getTable(AllEquivSDhstest)`: S3 method for class "AllEquivSDhstest"

**Examples**

```
# Manually define a 2 x 2 enrichment contingency table
contTable <- as.table(matrix(c(127, 19, 159, 3018),
  nrow = 2,
  dimnames = list(
    "Enriched in List 1" = c(TRUE, FALSE),
    "Enriched in List 2" = c(TRUE, FALSE)
  )
))
contTable

# Compute the Sorensen equivalence test from the contingency table.
# The result is an object of class "equivSDhstest".
equivalenceTest <- equivTestSorensen(contTable)
equivalenceTest
```

```
# Access the enrichment contingency table
getTable(equivalenceTest)
```

---

getUpper	<i>Access to the upper limit of the one-sided confidence intervals for the Sorensen-Dice dissimilarity in one or more equivalence test results</i>
----------	--

---

### Description

Given objects representing the result(s) of one or more equivalence tests (classes "equivSDhtest", "equivSDhtestList" or "allEquivSDtest", i.e., the result of functions 'equivTestSorensen' and 'allEquivTestSorensen') this function returns the upper limits of the one-sided confidence intervals [0, dU] for the Sorensen-Dice dissimilarity.

### Usage

```
getUpper(x, ...)
```

```
## S3 method for class 'equivSDhtest'
getUpper(x, ...)
```

```
## S3 method for class 'equivSDhtestList'
getUpper(x, simplify = TRUE, ...)
```

```
## S3 method for class 'AllEquivSDhtest'
getUpper(x, onto, GOLevel, listNames, simplify = TRUE, ...)
```

### Arguments

x	an object of class "equivSDhtest" or "equivSDhtestList" or "allEquivSDtest".
...	Additional parameters.
simplify	logical, if TRUE the result is simplified, e.g., returning a vector instead of a matrix.
onto	character, a vector with one or more of "BP", "CC" or "MF", ontologies to access.
GOLevel	numeric or character, a vector with one or more GO levels to access. See the details section and the examples.
listNames	character(2), the names of a pair of gene lists.

### Details

Argument GOLevel can be of class "character" or "numeric". In the first case, the GO levels must be specified like "level 6" or c("level 4", "level 5", "level 6") In the second case ("numeric"), the GO levels must be specified like 6 or seq.int(4, 6).

**Value**

A numeric value, the upper limit of the one-sided confidence interval for the Sorensen-Dice dissimilarity.

When `x` is an object of class "equivSDhtest" (i.e., the result of a single equivalence test), the returned value is a single numeric value, the upper limit of the one-sided confidence interval for the Sorensen-Dice dissimilarity. For an object of class "equivSDhtestList" (i.e. all pairwise tests for a set of gene lists), if `simplify = TRUE` (the default), the resulting value is a vector with the upper limit of the one-sided confidence intervals in all those tests, or the symmetric matrix of all these values if `simplify = FALSE`. If `x` is an object of class "allEquivSDhtest" (i.e., the test iterated along GO ontologies and levels), the preceding result is returned in the form of a list along the ontologies, levels and pairs of gene lists specified by the arguments `onto`, `GOlevel` and `listNames` (or all present in `x` for missing arguments).

**Methods (by class)**

- `getUpper(equivSDhtest)`: S3 method for class "equivSDhtest"
- `getUpper(equivSDhtestList)`: S3 method for class "equivSDhtestList"
- `getUpper(AllEquivSDhtest)`: S3 method for class "AllEquivSDhtest"

**Examples**

```
# Manually define a 2 x 2 enrichment contingency table
contTable <- as.table(matrix(c(127, 19, 159, 3018),
  nrow = 2,
  dimnames = list(
    "Enriched in List 1" = c(TRUE, FALSE),
    "Enriched in List 2" = c(TRUE, FALSE)
  )
))
contTable

# Compute the Sorensen equivalence test from the contingency table.
# The result is an object of class "equivSDhtest".
equivalenceTest <- equivTestSorensen(contTable)
equivalenceTest

# Extract the upper limit of the one-sided confidence intervals value from
# the equivalence test object
getUpper(equivalenceTest)
```

---

gosorensen

*gosorensen: A package for making inference on gene lists based on the Sorensen-Dice dissimilarity*

---

**Description**

Given two lists of genes, and a set of Gene Ontology (GO) items (e.g., all GO items in a given level of a given GO ontology) one may explore some aspects of their biological meaning by constructing a 2x2 contingency table, the cross-tabulation of: number of these GO items non-enriched in both gene lists (`n00`), items enriched in the first list but not in the second one (`n10`), items non-enriched

in the first list but enriched in the second (n10) and items enriched in both lists (n11). Then, one may express the degree of similarity or dissimilarity between the two lists by means of an appropriate index computed on these frequency tables of concordance or non-concordance in GO items enrichment. In our opinion, an appropriate index is the Sorensen-Dice index which ignores the double negatives n00: if the total number of candidate GO items under consideration grows (e.g., all items in a deep level of an ontology) likely n00 will also grow artificially. On the other hand, intuitively the degree of similarity between both lists must be directly related to the degree of concordance in the enrichment, n11.

## Details

gosorensen package provides the following functions:

- enrichedIn** Build a cross-tabulation of enriched and non-enriched GO terms vs. gene lists
- buildEnrichTable** Build an enrichment contingency table from two or more gene lists
- allBuildEnrichTable** Iterate 'buildEnrichTable' along the specified GO ontologies and GO levels
- nice2x2Table** Check for validity an enrichment contingency table
- dSorensen** Compute the Sorensen-Dice dissimilarity
- seSorensen** Standard error estimate of the sample Sorensen-Dice dissimilarity
- duppSorensen** Upper limit of a one-sided confidence interval (0,dUpp] for the population dissimilarity
- equivTestSorensen** Equivalence test between two gene lists, based on the Sorensen-Dice dissimilarity
- allEquivTestSorensen** Iterate equivTestSorensen along GO ontologies and GO levels
- getDissimilarity, getPvalue, getSE, getTable, getUpper, getNboot, getEffNboot** Accessor functions to some fields of an equivalence test result
- upgrade** Updating the result of an equivalence test, e.g., changing the equivalence limit
- sorenThreshold** For a given level (2, 3, ...) in a GO ontology (BP, MF or CC), compute the equivalence threshold dissimilarity matrix.
- allSorenThreshold** Iterate 'sorenThreshold' along the specified GO ontologies and GO levels.
- hclustThreshold** From a Sorensen-Dice threshold dissimilarity matrix, generate an object of class "hclust"
- allHclustThreshold** Iterate 'hclustThreshold' along the specified GO ontologies and GO levels
- pruneClusts** Remove all NULL or unrepresentable as a dendrogram "equivClustSorensen" elements in an object of class "equivClustSorensenList"

All these functions are generic, adequate for different (S3) classes representing the before cited GO term enrichment cross-tabulations.

## Author(s)

**Maintainer:** Pablo Flores <p\_flores@epoch.edu.ec> ([ORCID](#))

Authors:

- Pablo Flores <p\_flores@epoch.edu.ec> ([ORCID](#))
- Jordi Ocana ([ORCID](#)) [contributor]
- Alex Mantilla ([ORCID](#)) [contributor]

Other contributors:

- Alexandre Sanchez-Pla ([ORCID](#)) [contributor]
- Miquel Salicru ([ORCID](#)) [contributor]

**See Also**

Useful links:

- <https://github.com/pablof1988/goSorensen>
- Report bugs at <https://github.com/pablof1988/goSorensen/issues>

---

hclustThreshold	<i>From a Sorensen-Dice threshold dissimilarity matrix, generate an object of class "hclust"</i>
-----------------	--

---

**Description**

From a Sorensen-Dice threshold dissimilarity matrix, generate an object of class "hclust"

**Usage**

```
hclustThreshold(
  x,
  onTheFlyDev = NULL,
  method = "complete",
  jobName = paste("Equivalence cluster", method, sep = "_"),
  ylab = "Sorensen equivalence threshold\n          dissimilarity",
  ...
)
```

**Arguments**

x	an object of class "dist" with the Sorensen-Dice equivalence threshold dissimilarities matrix
onTheFlyDev	character, name of the graphical device where to immediately display the resulting diagram. The appropriate names depend on the operating system. Defaults to NULL and then nothing is displayed
method	character, one of the admissible methods in function hclust. Defaults to "complete"
jobName	character, main plot name, defaults to paste("Equivalence cluster", onto, ontoLevel, method, sep = "_")
ylab	character, label of the vertical axis of the plot, defaults to "Sorensen equivalence threshold dissimilarity"
...	additional arguments to hclust

**Value**

An object of class equivClustSorensen, descending from class hclust

**Examples**

```

# The following example requires the computation of the dissimilarity matrix
# for visualization purposes. Since this process is computationally intensive
# and may take a considerable amount of time, the example is not executed
# automatically during R CMD check

## Not run:
## i) Obtaining ENTREZ identifiers for the gene universe of humans:
library(org.Hs.eg.db)
humanEntrezIDs <- keys(org.Hs.eg.db, keytype = "ENTREZID")

## ii) Gene lists to be explored for analysis:
data(allOncogeneLists)

# iii) Computing the threshold dissimilarity matrix directly from gene lists
# at GO level 4 and BP ontology:
dissMatrx_BP4 <- sorenThreshold(allOncogeneLists,
  geneUniverse = humanEntrezIDs,
  orgPackg = "org.Hs.eg.db",
  onto = "BP",
  GOLevel = 4,
  trace = FALSE
)
dissMatrx_BP4

## End(Not run)

# Since running this example may take several minutes, the result has been
# pre-computed and is accessible as the following:
data(dissMatrx_BP4)
dissMatrx_BP4
# This shortcut applies only to this example; for your own gene-list data,
# the computation must be performed explicitly.

# Visualization of the hierarchical clustering results based on the
# dissimilarity matrix and irrelevance threshold values.
clust.threshold <- hclustThreshold(dissMatrx_BP4)
plot(clust.threshold)

```

---

nice2x2Table

*Checks for validity data representing an enrichment contingency table generated from two gene lists*

---

**Description**

Checks for validity data representing an enrichment contingency table generated from two gene lists

**Usage**

```

nice2x2Table(x)

## S3 method for class 'table'
nice2x2Table(x)

```

```
## S3 method for class 'matrix'
nice2x2Table(x)

## S3 method for class 'numeric'
nice2x2Table(x)
```

### Arguments

x either an object of class "table", "matrix" or "numeric".

### Details

In the "table" and "matrix" interfaces, the input parameter x must correspond to a two-dimensional array:

$$\begin{array}{cc} n_{11} & n_{10} \\ n_{01} & n_{00}, \end{array}$$

These values are interpreted (always in this order) as n11: number of GO terms enriched in both lists, n01: GO terms enriched in the second list but not in the first one, n10: terms not enriched in the second list but enriched in the first one and double negatives, n00. The double negatives n00 are ignored in many computations concerning the Sorensen-Dice index.

In the "numeric" interface, the input x must correspond to a numeric of length 3 or more, in the same order as before.

### Value

boolean, TRUE if x nicely represents a 2x2 contingency table interpretable as the cross-tabulation of the enriched GO terms in two gene lists: "Number of enriched terms in list 1 (TRUE, FALSE)" x "Number of enriched terms in list 2 (TRUE, FALSE)". In this function, "nicely representing a 2x2 contingency table" is interpreted in terms of computing the Sorensen-Dice dissimilarity and associated statistics. Otherwise the execution is interrupted.

### Methods (by class)

- nice2x2Table(table): S3 method for class "table"
- nice2x2Table(matrix): S3 method for class "matrix"
- nice2x2Table(numeric): S3 method for class "numeric"

### Examples

```
conti <- as.table(matrix(c(27, 36, 12, 501, 43, 15, 0, 0, 0),
  nrow = 3, ncol = 3,
  dimnames = list(
    c("a1", "a2", "a3"),
    c("b1", "b2", "b3")
  )
))
tryCatch(nice2x2Table(conti), error = function(e) {
  return(e)
})
conti2 <- conti[1, seq.int(1, min(2, ncol(conti))), drop = FALSE]
```

```
conti2
tryCatch(nice2x2Table(conti2), error = function(e) {
  return(e)
})

conti3 <- matrix(c(12, 210), ncol = 2, nrow = 1)
conti3
tryCatch(nice2x2Table(conti3), error = function(e) {
  return(e)
})

conti4 <- c(32, 21, 81, 1439)
nice2x2Table(conti4)
conti4.mat <- matrix(conti4, nrow = 2)
conti4.mat
conti5 <- c(32, 21, 81)
nice2x2Table(conti5)

conti6 <- c(-12, 21, 8)
tryCatch(nice2x2Table(conti6), error = function(e) {
  return(e)
})

conti7 <- c(0, 0, 0, 32)
tryCatch(nice2x2Table(conti7), error = function(e) {
  return(e)
})
```

---

pbtGeneLists

*14 gene lists possibly related with kidney transplant rejection*

---

### Description

An object of class "list" of length 14. A non up-to-date subset of the University of Alberta pathogenesis-based transcripts sets (PBTs) that were generated by using Affymetrix Microarrays. Take them just as an illustrative example.

### Usage

```
data(pbtGeneLists)
```

### Format

An object of class "list" of length 5. Each one of its elements is a "character" vector of ENTREZ gene identifiers.

### Source

<https://www.ualberta.ca/medicine/institutes-centres-groups/atagc/research/gene-lists.html>

---

pruneClusts	<i>Remove all NULL or unrepresentable as a dendrogram "equivClustSorensen" elements in an object of class "equivClustSorensenList"</i>
-------------	--

---

### Description

Remove all NULL or unrepresentable as a dendrogram "equivClustSorensen" elements in an object of class "equivClustSorensenList"

### Usage

```
pruneClusts(x)
```

### Arguments

x	An object of class "equivClustSorensenList" descending from "iterEquivClust" which itself descends from class "list". See the details section.
---	--

### Details

"equivClustSorensenList" objects are lists whose components are one or more of BP, CC or MF, the GO ontologies. Each of these elements is itself a list whose elements correspond to GO levels. Finally, the elements of these lists are objects of class "equivClustSorensen", descending from "equivClust" which itself descends from "hclust".

### Value

An object of class "equivClustSorensenList".

---

seSorensen	<i>Standard error of the sample Sorensen-Dice dissimilarity, asymptotic approach</i>
------------	--

---

### Description

Standard error of the sample Sorensen-Dice dissimilarity, asymptotic approach

### Usage

```
seSorensen(x, ...)

## S3 method for class 'table'
seSorensen(x, check.table = TRUE, ...)

## S3 method for class 'matrix'
seSorensen(x, check.table = TRUE, ...)

## S3 method for class 'numeric'
seSorensen(x, check.table = TRUE, ...)
```

```
## S3 method for class 'character'
seSorensen(x, y, check.table = TRUE, ...)

## S3 method for class 'list'
seSorensen(x, check.table = TRUE, ...)

## S3 method for class 'tableList'
seSorensen(x, check.table = TRUE, ...)
```

### Arguments

**x** either an object of class "table", "matrix" or "numeric" representing a 2x2 contingency table, or a "character" (a set of gene identifiers) or "list" or "tableList" object. See the details section for more information.

**...** extra parameters for function `buildEnrichTable`.

**check.table** Boolean. If TRUE (default), argument `x` is checked to adequately represent a 2x2 contingency table. This checking is performed by means of function `nice2x2Table`.

**y** an object of class "character" representing a vector of gene identifiers (e.g., ENTREZ).

### Details

This function computes the standard error estimate of the sample Sorensen-Dice dissimilarity, given a 2x2 arrangement of frequencies (either implemented as a "table", a "matrix" or a "numeric" object):

$$\begin{array}{cc} n_{11} & n_{10} \\ n_{01} & n_{00}, \end{array}$$

The subindex '11' corresponds to those GO terms enriched in both lists, '01' to terms enriched in the second list but not in the first one, '10' to terms enriched in the first list but not enriched in the second one and '00' corresponds to those GO terms non enriched in both gene lists, i.e., to the double negatives, a value which is ignored in the computations.

In the "numeric" interface, if `length(x) >= 3`, the values are interpreted as  $(n_{11}, n_{01}, n_{10})$ , always in this order.

If `x` is an object of class "character", then `x` (and `y`) must represent two "character" vectors of valid gene identifiers (e.g., ENTREZ). Then the standard error for the dissimilarity between lists `x` and `y` is computed, after internally summarizing them as a 2x2 contingency table of joint enrichment. This last operation is performed by function `buildEnrichTable` and "valid gene identifiers (e.g., ENTREZ)" stands for the coherency of these gene identifiers with the arguments `geneUniverse` and `orgPackg` of `buildEnrichTable`, passed by the ellipsis argument `...` in `seSorensen`.

In the "list" interface, the argument must be a list of "character" vectors, each one representing a gene list (character identifiers). Then, all pairwise standard errors of the dissimilarity between these gene lists are computed.

If `x` is an object of class "tableList", the standard error of the Sorensen-Dice dissimilarity estimate is computed over each one of these tables. Given `k` gene lists (i.e. "character" vectors of gene identifiers) `l1, l2, ..., lk`, an object of class "tableList" (typically constructed by a call to function `buildEnrichTable`) is a list of lists of contingency tables  $t(i,j)$  generated from each pair of gene lists `i` and `j`, with the following structure:

```

$12
$12$11$t(2,1)
$13
$13$11$t(3,1), $13$12$t(3,2)
...
$1k
$1k$11$t(k,1), $1k$12$t(k,2), ..., $1k$1(k-1)t(k,k-1)

```

### Value

In the "table", "matrix", "numeric" and "character" interfaces, the value of the standard error of the Sorensen-Dice dissimilarity estimate. In the "list" and "tableList" interfaces, the symmetric matrix of all standard error dissimilarity estimates.

### Methods (by class)

- seSorensen(table): S3 method for class "table"
- seSorensen(matrix): S3 method for class "matrix"
- seSorensen(numeric): S3 method for class "numeric"
- seSorensen(character): S3 method for class "character"
- seSorensen(list): S3 method for class "list"
- seSorensen(tableList): S3 method for class "tableList"

### See Also

[buildEnrichTable](#) for constructing contingency tables of mutual enrichment, [nice2x2Table](#) for checking the validity of enrichment contingency tables, [dSorensen](#) for computing the Sorensen-Dice dissimilarity, [duppSorensen](#) for the upper limit of a one-sided confidence interval of the dissimilarity, [equivTestSorensen](#) for an equivalence test.

### Examples

```

# Manually define a 2 x 2 enrichment contingency table
contTable <- as.table(matrix(c(127, 19, 159, 3018),
  nrow = 2,
  dimnames = list(
    "Enriched in List 1" = c(TRUE, FALSE),
    "Enriched in List 2" = c(TRUE, FALSE)
  )
))
contTable

# Calculation of the standard error using the joint enrichment contingency
# matrix
seSorensen(contTable)

```

---

sorenThreshold	<i>For a given level (2, 3, ...) in a GO ontology (BP, MF or CC), compute the equivalence threshold dissimilarity matrix.</i>
----------------	---

---

### Description

For a given level (2, 3, ...) in a GO ontology (BP, MF or CC), compute the equivalence threshold dissimilarity matrix.

### Usage

```
sorenThreshold(x, ...)
```

```
## S3 method for class 'list'
sorenThreshold(
  x,
  onto,
  GOLevel,
  geneUniverse,
  orgPackg,
  boot = FALSE,
  nboot = 10000,
  boot.seed = 6551,
  trace = TRUE,
  alpha = 0.05,
  precis = 0.001,
  ...
)
```

```
## S3 method for class 'tableList'
sorenThreshold(
  x,
  boot = FALSE,
  nboot = 10000,
  boot.seed = 6551,
  trace = TRUE,
  alpha = 0.05,
  precis = 0.001,
  ...
)
```

### Arguments

x	either an object of class "list" or class "tableList". See the details section for more information.
...	additional arguments to buildEnrichTable
onto	character, GO ontology ("BP", "MF" or "CC") under consideration
GOLevel	integer (2, 3, ...) level of a GO ontology where the GO profiles are built

geneUniverse	character vector containing the universe of genes from where geneLists have been extracted. This vector must be extracted from the annotation package declared in orgPackg. For more details see <a href="#">README File</a> .
orgPackg	A string with the name of the genomic annotation package corresponding to a specific species to be analyzed, which must be previously installed and activated. For more details see <a href="#">README File</a> .
boot	boolean. If TRUE, the p-values are computed by means of a bootstrap approach instead of the asymptotic normal approach. Defaults to FALSE.
nboot	numeric, number of initially planned bootstrap replicates. Ignored if boot == FALSE. Defaults to 10000
boot.seed	starting random seed for all bootstrap iterations. Defaults to 6551. see the details section
trace	boolean, the full process must be traced? Defaults to TRUE
alpha	simultaneous nominal significance level for the equivalence tests to be repeatedly performed, defaults to 0.05
precis	numerical precision in the iterative search of the equivalence threshold dissimilarities, defaults to 0.001

## Details

If  $x$  is an object of class "list", each of its elements must be a "character" vector of gene identifiers (e.g., ENTREZ). Then all pairwise threshold dissimilarities between these gene lists are obtained.

Class "tableList" corresponds to objects representing all mutual enrichment contingency tables generated in a pairwise fashion: Given gene lists  $l_1, l_2, \dots, l_k$ , an object of class "tableList" (typically constructed by a call to function `buildEnrichTable`) is a list of lists of contingency tables  $t_{ij}$  generated from each pair of gene lists  $i$  and  $j$ , with the following structure:

```

$12
$12$11$t21
$13
$13$11$t31, $13$12$t32
...
$1k$11$t1k, $1k$12$t1k, ..., $1k$1(k-1)t1(k-1)

```

If  $x$  is an object of class "tableList", the threshold dissimilarity is obtained over each one of these tables.

If `boot == TRUE`, all series of `nboot` bootstrap replicates start from the same random seed, provided by the argument `boot.seed`, except if `boot == NULL`.

Do not confuse the resulting threshold dissimilarity matrix with the Sorensen-Dice dissimilarities computed in each equivalence test.

The dimension of the resulting matrix may be less than the number of original gene lists being compared, as the process may not converge for some pairs of gene lists.

## Value

An object of class "dist", the equivalence threshold dissimilarity matrix based on the Sorensen-Dice dissimilarity.

**Methods (by class)**

- `sorenThreshold(list)`: S3 method for class "list"
- `sorenThreshold(tableList)`: S3 method for class "tableList"

**Examples**

```
## The following example is highly time-consuming and is therefore not run
## automatically during R CMD check.

## Not run:
## i) Obtaining ENTREZ identifiers for the gene universe of humans:
library(org.Hs.eg.db)
humanEntrezIDs <- keys(org.Hs.eg.db, keytype = "ENTREZID")

## ii) Gene lists to be explored for analysis:
data(allOncoGeneLists)

# iii) Computing the threshold dissimilarity matrix directly from gene lists at
# GO level 4 and BP ontology:
dissMatrx_BP4 <- sorenThreshold(allOncoGeneLists,
  geneUniverse = humanEntrezIDs,
  orgPackg = "org.Hs.eg.db",
  onto = "BP",
  GOLevel = 4,
  trace = FALSE
)
dissMatrx_BP4

## End(Not run)

# Since running this example may take several minutes, the result has been
# pre-computed and is accessible as the following:
data(dissMatrx_BP4)
dissMatrx_BP4
# This shortcut applies only to this example; for your own gene-list data,
# the computation must be performed explicitly.

# For a complete overview of this function's use, see the section 2 of the
# vignette "Working with the Irrelevance-threshold Matrix of Dissimilarities"
# You can do this by consulting the general package documentation or by
# directly running the following code in the R console:
# vignette("Dissimilarities_Matrix", package = "goSorensen")
```

---

 upgrade

---

*Update the result of a Sorensen-Dice equivalence test.*


---

**Description**

Recompute the test (or tests) from an object of class "equivSDhtest", "equivSDhtestList" or "AllEquivSDhtest" (i.e., the output of functions "equivTestSorensen" or "allEquivTestSorensen"). Using the same table or tables of enrichment frequencies in 'x', obtain again the result of the equivalence test for new values of any of the parameters `d0` or `conf.level` or `boot` or `nboot` or `check.table`.

**Usage**

```

upgrade(x, ...)

## S3 method for class 'equivSDhtest'
upgrade(x, ...)

## S3 method for class 'equivSDhtestList'
upgrade(x, ...)

## S3 method for class 'AllEquivSDhtest'
upgrade(x, ...)

```

**Arguments**

x                    an object of class "equivSDhtest", "equivSDhtestList" or "AllEquivSDhtest".

...                   any valid parameters for function "equivTestSorensen" for its interface "table", to recompute the test(s) according to these parameters.

**Value**

An object of the same class than x.

**Methods (by class)**

- upgrade(equivSDhtest): S3 method for class "equivSDhtest"
- upgrade(equivSDhtestList): S3 method for class "equivSDhtestList"
- upgrade(AllEquivSDhtest): S3 method for class "allEquivSDhtest"

**Examples**

```

# Manually define a 2 x 2 enrichment contingency table
contTable <- as.table(matrix(c(127, 19, 159, 3018),
  nrow = 2,
  dimnames = list(
    "Enriched in List 1" = c(TRUE, FALSE),
    "Enriched in List 2" = c(TRUE, FALSE)
  )
))
contTable

# Compute the Sorensen equivalence test from the contingency table.
# The result is an object of class "equivSDhtest".
equivalenceTest <- equivTestSorensen(contTable)
equivalenceTest

# Access the equivalence test results.
upgrade(equivalenceTest)

```

# Index

## \* datasets

- allContTabs, 5
  - allContTabsNoLevel, 5
  - allDissMatrx, 6
  - allDissMatrxNoLevel, 7
  - allEqTests, 7
  - allEqTests\_boot, 8
  - allEqTests\_bootNoLevel, 9
  - allEqTestsNoLevel, 8
  - allOncoGeneLists, 13
  - cont\_all\_BP, 20
  - cont\_all\_BP4, 21
  - cont\_atlas.sanger\_BP, 22
  - cont\_atlas.sanger\_BP4, 22
  - dissMatrx\_BP, 23
  - dissMatrx\_BP4, 23
  - dSorensen, 24, 30, 39, 62
  - duppSorensen, 26, 26, 39, 62
  - enrichedIn, 20, 21, 30, 33, 34, 40, 41
  - enrichedInBP, 33
  - enrichedInBP4, 34
  - eqTest\_all\_BP, 34
  - eqTest\_all\_BP4, 35
  - eqTest\_atlas.sanger\_BP, 36
  - eqTest\_atlas.sanger\_BP4, 36
  - fullEnrichedInBP, 40
  - fullEnrichedInBP4, 41
  - pbtGeneLists, 59
- 
- allBuildEnrichTable, 3
  - allContTabs, 5
  - allContTabsNoLevel, 5
  - allDissMatrx, 6
  - allDissMatrxNoLevel, 7
  - allEqTests, 7
  - allEqTests\_boot, 8
  - allEqTests\_bootNoLevel, 9
  - allEqTestsNoLevel, 8
  - allEquivTestSorensen, 10
  - allHclustThreshold, 12
  - allOncoGeneLists, 5–9, 13, 21–24, 33–37, 40, 41
  - allSorenThreshold, 14
- 
- boot.tStat, 16
  - buildEnrichTable, 17, 25, 26, 29, 30, 38, 61, 62, 64
  - cont\_all\_BP, 20
  - cont\_all\_BP4, 21
  - cont\_atlas.sanger\_BP, 22
  - cont\_atlas.sanger\_BP4, 22
  - dissMatrx\_BP, 23
  - dissMatrx\_BP4, 23
  - dSorensen, 24, 30, 39, 62
  - duppSorensen, 26, 26, 39, 62
  - enrichedIn, 20, 21, 30, 33, 34, 40, 41
  - enrichedInBP, 33
  - enrichedInBP4, 34
  - eqTest\_all\_BP, 34
  - eqTest\_all\_BP4, 35
  - eqTest\_atlas.sanger\_BP, 36
  - eqTest\_atlas.sanger\_BP4, 36
  - equivTestSorensen, 26, 30, 37, 62
  - fullEnrichedInBP, 40
  - fullEnrichedInBP4, 41
  - getDissimilarity, 42
  - getEffNboot, 39, 43, 47
  - getNboot, 39, 44, 46
  - getPvalue, 39, 48
  - getSE, 39, 50
  - getTable, 39, 51
  - getUpper, 39, 53
  - goSorensen (gosorensen), 54
  - gosorensen, 54
  - goSorensen-package (gosorensen), 54
  - hclustThreshold, 56
  - nice2x2Table, 26, 30, 39, 57, 62
  - pbtGeneLists, 59
  - pruneClusts, 60
  - seSorensen, 26, 30, 39, 60
  - sorenThreshold, 63
  - update, 39
  - upgrade, 65