

Package ‘igvShiny’

May 26, 2026

Title igvShiny: a wrapper of Integrative Genomics Viewer (IGV - an interactive tool for visualization and exploration integrated genomic data)

Version 1.9.3

Date 2024-08-29

Description This package is a wrapper of Integrative Genomics Viewer (IGV). It comprises an htmlwidget version of IGV. It can be used as a module in Shiny apps.

URL <https://github.com/gladkia/igvShiny>,
<https://gladkia.github.io/igvShiny/>

BugReports <https://github.com/gladkia/igvShiny/issues>

Depends GenomicRanges, methods, shiny

Imports BiocGenerics, checkmate, futile.logger, GenomeInfoDbData, htmlwidgets, httr, jsonlite, randomcoloR, utils

Suggests BiocStyle, GenomicAlignments, knitr, Rsamtools, rtracklayer, testthat, shinytest2, VariantAnnotation

biocViews Software, ShinyApps, Sequencing, Coverage

License MIT + file LICENSE

Encoding UTF-8

Collate 'constants.R' 'genomeSpec.R' 'GWASTrack.R' 'igvShiny.R' 'packages.R' 'utils.R' 'zzz.R'

RoxygenNote 7.3.1

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/igvShiny>

git_branch devel

git_last_commit c955a3e

git_last_commit_date 2026-05-01

Repository Bioconductor 3.24

Date/Publication 2026-05-25

Author Paul Shannon [aut],
Arkadiusz Gladki [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-7059-6378>>),
Karolina Scigocka [aut]

Maintainer Arkadiusz Gladki <gladki.arkadiusz@gmail.com>

Contents

.sanitizeAndMergeOptions	2
display,GWASTrack-method	3
getUrl,GWASTrack-method	3
get_basic_genomes	4
get_cas_genomes	5
get_css_genomes	5
get_tracks_dir	6
GWASTrack-class	6
igvShiny	8
igvShinyOutput	9
loadBamTrackFromLocalData	9
loadBamTrackFromURL	10
loadBedGraphTrack	11
loadBedGraphTrackFromURL	12
loadBedTrack	13
loadCramTrackFromURL	14
loadGFF3TrackFromLocalData	15
loadGFF3TrackFromURL	17
loadGwasTrack	18
loadSegTrack	19
loadVcfTrack	20
parseAndValidateGenomeSpec	21
removeTracksByName	22
removeUserAddedTracks	23
renderIgvShiny	23
showGenomicRegion	24
Index	26

.sanitizeAndMergeOptions

Sanitize and merge track configuration options

Description

Sanitize and merge track configuration options

Usage

```
.sanitizeAndMergeOptions(baseOptions, userOptions)
```

Arguments

baseOptions A list of default options set by the R function.
 userOptions A list of options provided by the user via trackConfig.

Value

A merged and sanitized list of options ready to be sent to JavaScript.

display,GWASTrack-method

display the already constructed and configured track

Description

display the already constructed and configured track

Usage

```
## S4 method for signature 'GWASTrack'  
display(obj, session, id, deleteTracksOfSameName = TRUE)
```

Arguments

obj	An object of class GWASTrack
session	a Shiny session object
id	character the identifier of the target igv object in the browser
deleteTracksOfSameName	logical to avoid duplications in track names

Value

nothing

Examples

```
library(igvShiny)  
demo_app_file <-  
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")  
if (interactive()) {  
  shiny::runApp(demo_app_file)  
}
```

getUrl,GWASTrack-method

the url of the gwas table

Description

the url of the gwas table

Usage

```
## S4 method for signature 'GWASTrack'  
getUrl(obj)
```

Arguments

obj An object of class GWASTrack

Value

character

Examples

```
file <-  
  # a local gwas file  
  system.file(package = "igvShiny", "extdata", "gwas-5k.tsv.gz")  
tbl.gwas <- read.table(file,  
                      sep = "\t",  
                      header = TRUE,  
                      quote = "")  
  
track <-  
  GWASTrack(  
    "gwas 5k",  
    tbl.gwas,  
    chrom.col = 12,  
    pos.col = 13,  
    pval.col = 28  
  )  
getUrl(track)
```

get_basic_genomes *get_basic_genomes*

Description

a helper function for basic genomes, obtains the genome codes (e.g. 'hg38')

Usage

```
get_basic_genomes()
```

Value

an list of short genome codes, e.g., "hg38", "dm6"

Examples

```
bs <- get_basic_genomes()
```

get_cas_genomes *get_cas_genomes*

Description

a helper function for common always available stock genomes, obtains the genome codes (e.g. 'hg38')

Usage

```
get_cas_genomes()
```

Value

an list of short genome codes, e.g., "hg38", "dm6"

Examples

```
cas <- get_cas_genomes()
```

get_css_genomes *get_css_genomes*

Description

a helper function for mostly internal use, obtains the genome codes (e.g. 'hg38') supported by igv.js

Usage

```
get_css_genomes(test = FALSE)
```

Arguments

test logical(1) defaults to FALSE

Value

an list of short genome codes, e.g., "hg38", "dm6", "tair10"

Examples

```
css <- get_css_genomes(test = TRUE)
```

<code>get_tracks_dir</code>	<i>get_tracks_dir</i> Get the directory where tracks are stored. The directory can be defined with environmental variable. If not defined the default is a directory called "tracks" in the temp directory. We need a local directory to write files - for instance, a vcf file representing a genomic region of interest. We then tell shiny about that directory, so that shiny's built-in http server can serve up files we write there, ultimately consumed by igv.js
-----------------------------	---

Description

`get_tracks_dir` Get the directory where tracks are stored. The directory can be defined with environmental variable. If not defined the default is a directory called "tracks" in the temp directory. We need a local directory to write files - for instance, a vcf file representing a genomic region of interest. We then tell shiny about that directory, so that shiny's built-in http server can serve up files we write there, ultimately consumed by igv.js

Usage

```
get_tracks_dir(env_var = "TRACKS_DIR")
```

Arguments

`env_var` The name of the environmental variable to use.

Value

string with the path to the tracks directory.

Examples

```
gtd <- get_tracks_dir(env_var = "TRACKS_DIR")
```

<code>GWASTrack-class</code>	<i>Constructor for GWASTrack</i>
------------------------------	----------------------------------

Description

GWASTrack creates an IGV manhattan track from GWAS data

Usage

```
GWASTrack(
  trackName,
  data,
  chrom.col,
  pos.col,
  pval.col,
  trackHeight = 50,
```

```

    autoscale = TRUE,
    minY = 0,
    maxY = 30
  )

```

Arguments

trackName	A character string, used as track label by igv, we recommend unique names per track.
data	a data.frame or a url pointing to one, whose structure is described by chrom.col, pos.col, pval.col
chrom.col	numeric, the column number of the chromosome column
pos.col	numeric, the column number of the position column
pval.col	numeric, the column number of the GWAS pvalue column
trackHeight	numeric in pixels
autoscale	logical
minY	numeric for explicit (non-auto) scaling
maxY	numeric for explicit (non-auto) scaling

Value

A GWASTrack object

Examples

```

file <-
  # a local gwas file
  system.file(package = "igvShiny", "extdata", "gwas-5k.tsv.gz")
tbl.gwas <- read.table(file,
                      sep = "\t",
                      header = TRUE,
                      quote = "")

dim(tbl.gwas)
track <-
  GWASTrack(
    "gwas 5k",
    tbl.gwas,
    chrom.col = 12,
    pos.col = 13,
    pval.col = 28
  )
getUrl(track)

url <- "https://gladki.pl/igvShiny/gwas_sample.tsv.gz"
track <- GWASTrack(
  "remote url gwas",
  url,
  chrom.col = 3,
  pos.col = 4,
  pval.col = 10,
  autoscale = FALSE,
  minY = 0,
  maxY = 300,

```

```

    trackHeight = 100
  )
  getUrl(track)

```

 igvShiny

Create an igvShiny instance

Description

This function is called in the server function of your shiny app

Usage

```

igvShiny(
  genomeOptions,
  width = NULL,
  height = NULL,
  elementId = NULL,
  displayMode = "squished",
  tracks = list()
)

```

Arguments

genomeOptions	a list with these fields: genomeName, initialLocus, annotation, dataMode, fasta, fastaIndex, stockGenome, validated
width	a character string, standard css notations, either e.g., "1000px" or "95%"
height	a character string, needs to be an explicit pixel measure, e.g., "800px"
elementId	a character string, the html element id within which igv is created
displayMode	a character string, default "SQUISHED".
tracks	a list of track specifications to be created and displayed at startup

Value

the created widget

Examples

```

library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}

```

igvShinyOutput	<i>create the UI for the widget</i>
----------------	-------------------------------------

Description

This function is called in the ui function of your shiny app

Usage

```
igvShinyOutput(outputId, width = "100%", height = NULL)
```

Arguments

outputId	a character string, specifies the html element id
width	a character string, standard css notations, either e.g., "1000px" or "95%", "100%" by default
height	a character string, needs to be an explicit pixel measure, e.g., "800px", "400px" by default

Value

the created widget's html

Examples

```
io <- igvShinyOutput("igvOut")
```

loadBamTrackFromLocalData	<i>load GenomicAlignments data as an igv.js alignment track</i>
---------------------------	---

Description

load GenomicAlignments data as an igv.js alignment track

Usage

```
loadBamTrackFromLocalData(  
  session,  
  id,  
  trackName,  
  data,  
  deleteTracksOfSameName = TRUE,  
  displayMode = "EXPANDED",  
  trackConfig = list()  
)
```

Arguments

session	an environment or list, provided and managed by shiny
id	character string, the html element id of this widget instance
trackName	character string
data	GenomicAlignments object
deleteTracksOfSameName	logical, default TRUE
displayMode	character string, possible values are "EXPANDED"(default), "SQUISHED" or "COLLAPSED"
trackConfig	a named list of additional igv.js track configuration options.

Value

nothing

Examples

```
library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}
```

loadBamTrackFromURL *load a bam track which, with index, is served up by http*

Description

load a remote bam track

Usage

```
loadBamTrackFromURL(
  session,
  id,
  trackName,
  bamURL,
  indexURL,
  deleteTracksOfSameName = TRUE,
  displayMode = "EXPANDED",
  showAllBases = FALSE,
  trackConfig = list()
)
```

Arguments

session	an environment or list, provided and managed by shiny
id	character string, the html element id of this widget instance
trackName	character string
bamURL	character string http url for the bam file, typically very large
indexURL	character string http url for the bam file index, typically small
deleteTracksOfSameName	logical, default TRUE
displayMode	character string, possible values are "EXPANDED"(default), "SQUISHED" or "COLLAPSED"
showAllBases	logical, show all bases in the alignment, default FALSE
trackConfig	a named list of additional igv.js track configuration options.

Value

nothing

Examples

```
library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}
```

loadBedGraphTrack *load a scored genome annotation track provided as a data.frame*

Description

load a genome annotation track provided as a data.frame

Usage

```
loadBedGraphTrack(
  session,
  id,
  trackName,
  tbl,
  color = "gray",
  trackHeight = 30,
  autoscale,
  autoscaleGroup = -1,
  min = NA_real_,
  max = NA_real_,
  deleteTracksOfSameName = TRUE,
  quiet = TRUE,
  trackConfig = list()
)
```

Arguments

session	an environment or list, provided and managed by shiny
id	character string, the html element id of this widget instance
trackName	character string
tbl	data.frame, with at least "chrom" "start" "end" "score" columns
color	character string, a legal CSS color, or "random", "gray" by default
trackHeight	an integer, 30 (pixels) by default
autoscale	logical
autoscaleGroup	numeric(1) defaults to -1
min	numeric, consulted when autoscale is FALSE
max	numeric, consulted when autoscale is FALSE
deleteTracksOfSameName	logical, default TRUE
quiet	logical, default TRUE, controls verbosity
trackConfig	a named list of additional igv.js track configuration options.

Value

nothing

Examples

```
library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}
```

loadBedGraphTrackFromURL

load a bedgraph track from a URL

Description

load a bedgraph track provided as a data.frame

Usage

```
loadBedGraphTrackFromURL(
  session,
  id,
  trackName,
  url,
  color = "gray",
  trackHeight = 30,
  autoscale = TRUE,
```

```

    min = 0,
    max = 1,
    autoscaleGroup = -1,
    deleteTracksOfSameName = TRUE,
    quiet = TRUE,
    trackConfig = list()
  )

```

Arguments

session	an environment or list, provided and managed by shiny
id	character string, the html element id of this widget instance
trackName	character string
url	character
color	character string, a legal CSS color, or "random", "gray" by default
trackHeight	an integer, 30 (pixels) by default
autoscale	logical
min	numeric, consulted when autoscale is FALSE
max	numeric, consulted when autoscale is FALSE
autoscaleGroup	numeric(1) defaults to -1
deleteTracksOfSameName	logical(1) defaults to TRUE
quiet	logical, default TRUE, controls verbosity
trackConfig	a named list of additional igv.js track configuration options.

Value

nothing

Examples

```

library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}

```

loadBedTrack

load a bed track provided as a data.frame

Description

load a bed track provided as a data.frame

Usage

```
loadBedTrack(
  session,
  id,
  trackName,
  tbl,
  color = "",
  trackHeight = 50,
  deleteTracksOfSameName = TRUE,
  quiet = TRUE,
  trackConfig = list()
)
```

Arguments

session	an environment or list, provided and managed by shiny
id	character string, the html element id of this widget instance
trackName	character string
tbl	data.frame, with at least "chrom" "start" "end" columns
color	character string, a legal CSS color, or "random", "gray" by default
trackHeight	an integer, 50 (pixels) by default
deleteTracksOfSameName	logical, default TRUE
quiet	logical, default TRUE, controls verbosity
trackConfig	a named list of additional igv.js track configuration options.

Value

nothing

Examples

```
library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}
```

loadCramTrackFromURL *load a cram track which, with index, is served up by http*

Description

load a remote cram track

Usage

```
loadCramTrackFromURL(  
  session,  
  id,  
  trackName,  
  cramURL,  
  indexURL,  
  deleteTracksOfSameName = TRUE,  
  trackConfig = list()  
)
```

Arguments

session	an environment or list, provided and managed by shiny
id	character string, the html element id of this widget instance
trackName	character string
cramURL	character string http url for the bam file, typically very large
indexURL	character string http url for the bam file index, typically small
deleteTracksOfSameName	logical, default TRUE
trackConfig	a named list of additional igv.js track configuration options.

Value

nothing

Examples

```
library(igvShiny)  
demo_app_file <-  
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")  
if (interactive()) {  
  shiny::runApp(demo_app_file)  
}
```

loadGFF3TrackFromLocalData

load a GFF3 track defined by local data

Description

load a local GFF3 track file

Usage

```
loadGFF3TrackFromLocalData(
  session,
  id,
  trackName,
  tbl.gff3,
  color = "gray",
  colorTable,
  colorByAttribute,
  displayMode,
  trackHeight = 50,
  visibilityWindow,
  deleteTracksOfSameName = TRUE,
  trackConfig = list()
)
```

Arguments

session	an environment or list, provided and managed by shiny
id	character string, the html element id of this widget instance
trackName	character string
tbl.gff3	data.frame in standard 9-column GFF3 format
color	character #RGB or a recognized color name. ignored if colorTable and colorByAttribute provided
colorTable	list, mapping a gff3 attribute, typically biotype, to a color
colorByAttribute	character, name of a gff3 attribute in column 9, typically "biotype"
displayMode	character, "EXPANDED", "SQUISHED" or "COLLAPSED"
trackHeight	numeric defaults to 50
visibilityWindow	numeric, Maximum window size in base pairs for which indexed annotations or variants are displayed
deleteTracksOfSameName	logical, default TRUE
trackConfig	a named list of additional igv.js track configuration options.

Value

nothing

Examples

```
library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo-GFF3.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}
```

loadGFF3TrackFromURL *load a GFF3 track which, with index, is served up by http*

Description

load a remote GFF3 track

Usage

```
loadGFF3TrackFromURL(
  session,
  id,
  trackName,
  gff3URL,
  indexURL,
  color = "gray",
  colorTable,
  colorByAttribute,
  displayMode,
  trackHeight = 50,
  visibilityWindow,
  deleteTracksOfSameName = TRUE,
  trackConfig = list()
)
```

Arguments

session	an environment or list, provided and managed by shiny
id	character string, the html element id of this widget instance
trackName	character string
gff3URL	character string http url for the bam file, typically very large
indexURL	character string http url for the bam file index, typically small
color	character #RGB or a recognized color name. ignored if colorTable and colorByAttribute provided
colorTable	list, mapping a gff3 attribute, typically biotype, to a color
colorByAttribute	character, name of a gff3 attribute in column 9, typically "biotype"
displayMode	character, "EXPANDED", "SQUISHED" or "COLLAPSED"
trackHeight	numeric defaults to 50
visibilityWindow	numeric, Maximum window size in base pairs for which indexed annotations or variants are displayed
deleteTracksOfSameName	logical, default TRUE
trackConfig	a named list of additional igv.js track configuration options.

Value

nothing

Examples

```
library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo-GFF3.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}
```

loadGwasTrack	<i>load a GWAS (genome-wide association study) track provided as a data.frame</i>
---------------	---

Description

load a GWAS (genome-wide association study) track provided as a data.frame

Usage

```
loadGwasTrack(
  session,
  id,
  trackName,
  tbl.gwas,
  ymin = 0,
  ymax = 35,
  deleteTracksOfSameName = TRUE,
  trackConfig = list()
)
```

Arguments

session	an environment or list, provided and managed by shiny
id	character string, the html element id of this widget instance
trackName	character string
tbl.gwas	data.frame, with at least "chrom" "start" "end" columns
ymin	numeric defaults to 0
ymax	numeric defaults to 35
deleteTracksOfSameName	logical, default TRUE
trackConfig	a named list of additional igv.js track configuration options.

Value

nothing

Examples

```
library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}
```

loadSegTrack

load a seg track provided as a data.frame

Description

load a SEG track provided as a data.frame. igv "displays segmented data as a blue-to-red heatmap where the data range is -1.5 to 1.5... The segmented data file format is the output of the Circular Binary Segmentation algorithm (Olshen et al., 2004)".

Usage

```
loadSegTrack(
  session,
  id,
  trackName,
  tbl,
  deleteTracksOfSameName = TRUE,
  trackConfig = list()
)
```

Arguments

session	an environment or list, provided and managed by shiny
id	character string, the html element id of this widget instance
trackName	character string
tbl	data.frame, with at least "chrom" "start" "end" "score" columns
deleteTracksOfSameName	logical, default TRUE
trackConfig	a named list of additional igv.js track configuration options.

Value

nothing

Examples

```
library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}
```

loadVcfTrack	<i>load a VCF (variant) track provided as a Bioconductor VariantAnnotation object</i>
--------------	---

Description

load a VCF (variant) track provided as a Bioconductor VariantAnnotation object

Usage

```
loadVcfTrack(  
  session,  
  id,  
  trackName,  
  vcfData,  
  deleteTracksOfSameName = TRUE,  
  trackConfig = list()  
)
```

Arguments

session	an environment or list, provided and managed by shiny
id	character string, the html element id of this widget instance
trackName	character string
vcfData	VariantAnnotation object
deleteTracksOfSameName	logical, default TRUE
trackConfig	a named list of additional igv.js track configuration options.

Value

nothing

Examples

```
library(igvShiny)  
demo_app_file <-  
  system.file(package = "igvShiny", "demos", "igvShinyDemo-withVCF.R")  
if (interactive()) {  
  shiny::runApp(demo_app_file)  
}
```

```
parseAndValidateGenomeSpec  
  parseAndValidateGenomeSpec
```

Description

a helper function for internal use by the igvShiny constructor, but possible also of use to those building an igvShiny app, to test their genome specification for validity

Usage

```
parseAndValidateGenomeSpec(  
  genomeName,  
  initialLocus = "all",  
  stockGenome = TRUE,  
  dataMode = NA,  
  fasta = NA,  
  fastaIndex = NA,  
  genomeAnnotation = NA  
)
```

Arguments

genomeName	character usually one short code of a supported ("stock") genome (e.g., "hg38") or for a user-supplied custom genome, the name you wish to use
initialLocus	character default "all", otherwise "chrN:start-end" or a recognized gene symbol
stockGenome	logical default TRUE
dataMode	character either "stock", "localFile" or "http"
fasta	character when supplying a custom (non-stock) genome, either a file path or a URL
fastaIndex	character when supplying a custom (non-stock) genome, either a file path or a URL, essential for all but the very small custom genomes.
genomeAnnotation	character when supplying a custom (non-stock) genome, a file path or URL pointing to a genome annotation file in a gff3 format

Value

an options list directly usable by igvApp.js, and thus igv.js

See Also

[get_css_genomes()] for stock genomes we support.

Examples

```

genomeSpec <-
  parseAndValidateGenomeSpec("hg38", "APOE") # the simplest case
base.url <-
  "https://gladki.pl/igvr/testFiles/sarsGenome"
fasta.file <-
  sprintf("%s/%s", base.url, "Sars_cov_2.ASM985889v3.dna.toplevel.fa")
fastaIndex.file <-
  sprintf("%s/%s",
    base.url,
    "Sars_cov_2.ASM985889v3.dna.toplevel.fa.fai")
annotation.file <-
  sprintf("%s/%s", base.url, "Sars_cov_2.ASM985889v3.101.gff3")
custom.genome.title <- "SARS-CoV-2"
genomeOptions <-
  parseAndValidateGenomeSpec(
    genomeName = custom.genome.title,
    initialLocus = "all",
    stockGenome = FALSE,
    dataMode = "http",
    fasta = fasta.file,
    fastaIndex = fastaIndex.file,
    genomeAnnotation = annotation.file
  )

```

removeTracksByName	<i>remove tracks from the browser</i>
--------------------	---------------------------------------

Description

delete tracks on the browser

Usage

```
removeTracksByName(session, id, trackNames)
```

Arguments

session	an environment or list, provided and managed by shiny
id	character string, the html element id of this widget instance
trackNames	a vector of character strings

Value

nothing

Examples

```
library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}
```

removeUserAddedTracks *remove only those tracks explicitly added by your app*

Description

remove only those tracks explicitly added by your app. stock tracks (i.e., #' Refseq Genes) remain

Usage

```
removeUserAddedTracks(session, id)
```

Arguments

session an environment or list, provided and managed by shiny
id character string, the html element id of this widget instance

Value

nothing

Examples

```
library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}
```

renderIgvShiny *draw the igv genome browser element*

Description

This function is called in the server function of your shiny app

Usage

```
renderIgvShiny(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

expr	an expression that generates an HTML widget
env	the environment in which to evaluate expr
quoted	logical flag indicating if expr a quoted expression

Value

an output or render function that enables the use of the widget within Shiny applications

Examples

```
library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}
```

showGenomicRegion *focus igv on a region*

Description

zoom in or out to show the nominated region, by chromosome locus or gene symbol
 return the current region displayed by your igv instance

Usage

```
showGenomicRegion(session, id, region)

getGenomicRegion(session, id)
```

Arguments

session	an environment or list, provided and managed by shiny
id	character string, the html element id of this widget instance
region	a character string, either e.g. "chr5:92,221,640-92,236,523" or "MEF2C"

Value

a character string of format "chrom:start-end"

Examples

```
library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}
```

```
library(igvShiny)
demo_app_file <-
  system.file(package = "igvShiny", "demos", "igvShinyDemo.R")
if (interactive()) {
  shiny::runApp(demo_app_file)
}
```

Index

- * **GWASTrack_class**
 - display, GWASTrack-method, 3
 - getUrl, GWASTrack-method, 3
 - GWASTrack-class, 6
 - * **igvShiny**
 - .sanitizeAndMergeOptions, 2
 - igvShiny, 8
 - igvShinyOutput, 9
 - parseAndValidateGenomeSpec, 21
 - removeTracksByName, 22
 - removeUserAddedTracks, 23
 - renderIgvShiny, 23
 - showGenomicRegion, 24
 - * **track_loaders**
 - loadBamTrackFromLocalData, 9
 - loadBamTrackFromURL, 10
 - loadBedGraphTrack, 11
 - loadBedGraphTrackFromURL, 12
 - loadBedTrack, 13
 - loadCramTrackFromURL, 14
 - loadGFF3TrackFromLocalData, 15
 - loadGFF3TrackFromURL, 17
 - loadGwasTrack, 18
 - loadSegTrack, 19
 - loadVcfTrack, 20
 - * **utils**
 - get_basic_genomes, 4
 - get_cas_genomes, 5
 - get_css_genomes, 5
 - get_tracks_dir, 6
 - .GWASTrack (GWASTrack-class), 6
 - .sanitizeAndMergeOptions, 2
- display (display, GWASTrack-method), 3
- display, GWASTrack-method, 3
- get_basic_genomes, 4
- get_cas_genomes, 5
- get_css_genomes, 5
- get_tracks_dir, 6
- getGenomicRegion (showGenomicRegion), 24
- getUrl (getUrl, GWASTrack-method), 3
- getUrl, GWASTrack-method, 3
- GWASTrack (GWASTrack-class), 6
- GWASTrack-class, 6
- igvShiny, 8
- igvShinyOutput, 9
- loadBamTrackFromLocalData, 9
- loadBamTrackFromURL, 10
- loadBedGraphTrack, 11
- loadBedGraphTrackFromURL, 12
- loadBedTrack, 13
- loadCramTrackFromURL, 14
- loadGenomeAnnotationTrack
(loadBedGraphTrack), 11
- loadGFF3TrackFromLocalData, 15
- loadGFF3TrackFromURL, 17
- loadGwasTrack, 18
- loadSEGTrack (loadSegTrack), 19
- loadSegTrack, 19
- loadVcfTrack, 20
- parseAndValidateGenomeSpec, 21
- removeTracksByName, 22
- removeUserAddedTracks, 23
- renderIgvShiny, 23
- showGenomicRegion, 24