

Package ‘PhenStat’

October 12, 2016

Type Package

Title Statistical analysis of phenotypic data

Version 2.6.0

Date 2016-04-27

Author Natalja Kurbatova, Natasha Karp, Jeremy Mason

Maintainer Natasha Karp <nk3@sanger.ac.uk>

Depends R (>= 2.3.0)

Imports methods, car, nlme, nortest, MASS, logistf

Suggests RUnit, BiocGenerics

Description Package contains methods for statistical analysis of phenotypic data.

License file LICENSE

NeedsCompilation no

R topics documented:

| | |
|---|----|
| analysedDataset | 3 |
| analysedDatasetPhenList | 3 |
| analysedSubset | 4 |
| analysisResults | 4 |
| batchIn | 4 |
| boxplotResidualBatch | 5 |
| boxplotSexGenotype | 6 |
| boxplotSexGenotypeBatch | 7 |
| boxplotSexGenotypeBatchAdjusted | 8 |
| boxplotSexGenotypeResult | 9 |
| boxplotSexGenotypeWeightBatchAdjusted | 10 |
| categoricalBarplot | 11 |
| checkDataset | 12 |
| classificationTag | 14 |
| comparison | 15 |
| dataset | 15 |
| finalLRModel | 16 |

| | |
|---|----|
| finalModel | 17 |
| finalTFModel | 18 |
| FisherExactTest | 20 |
| generateGraphs | 21 |
| getColumn | 22 |
| getColumnBatchAdjusted | 22 |
| getColumnView | 22 |
| getColumnWeightBatchAdjusted | 23 |
| getCountMatrices | 23 |
| getDataset | 23 |
| getGenotypeEffect | 23 |
| getMatrix | 24 |
| getPercentageMatrix | 24 |
| getStat | 24 |
| getVariable | 24 |
| getVariables | 25 |
| hemiGenotype | 25 |
| JSONOutput | 25 |
| LRDataset | 26 |
| matrixCount | 27 |
| method | 28 |
| methodText | 28 |
| multipleBatches | 28 |
| noSexes | 28 |
| parameters | 29 |
| parserOutputSummary | 29 |
| parserOutputSummaryLR | 30 |
| parserOutputTFSummary | 31 |
| PhenList | 32 |
| PhenList-class | 34 |
| PhenTestResult | 36 |
| PhenTestResult-class | 38 |
| plotResidualPredicted | 41 |
| pvalue | 42 |
| qqplotGenotype | 42 |
| qqplotRandomEffects | 43 |
| qqplotRotatedResiduals | 44 |
| recommendMethod | 45 |
| refGenotype | 46 |
| RRTest | 46 |
| scatterplotGenotypeWeight | 48 |
| scatterplotGenotypeWeightResult | 49 |
| scatterplotSexGenotypeBatch | 50 |
| scatterplotSexGenotypeBatchResult | 51 |
| setBatch | 53 |
| setGenotype | 53 |
| setMissingValue | 53 |
| setSex | 53 |

analysedDataset 3

| | |
|--------------------------------|----|
| setWeight | 54 |
| startLRModel | 54 |
| startModel | 55 |
| startTFModel | 57 |
| subsetText | 59 |
| summaryOutput | 59 |
| testDataset | 61 |
| testFinalLRModel | 63 |
| testFinalModel | 64 |
| testGenotype | 65 |
| TFDataset | 65 |
| transformation | 66 |
| transformationJSON | 66 |
| transformationText | 67 |
| vectorOutput | 67 |
| vectorOutputMatrices | 68 |
| weightIn | 69 |

Index 70

analysedDataset *Method "analysedDataset"*

Description

Method *analysedDataset* returns subset of the original dataset that was analysed

Methods

signature(obj = "PhenTestResult")

analysedDatasetPhenList
Method "analysedDatasetPhenList"

Description

Method *analysedDatasetPhenList* returns subset of the original dataset that will be analysed

Methods

signature(obj = "PhenList")

| | |
|----------------|--------------------------------|
| analysedSubset | <i>Method "analysedSubset"</i> |
|----------------|--------------------------------|

Description

Method analysedSubset returns name of the subset that was analysed by RR or FE frameworks

Methods

signature(obj = "htestPhenStat")

| | |
|-----------------|---------------------------------|
| analysisResults | <i>Method "analysisResults"</i> |
|-----------------|---------------------------------|

Description

Method analysisResults returns analysis results

Methods

signature(obj = "PhenTestResult")

| | |
|---------|-------------------------|
| batchIn | <i>Method "batchIn"</i> |
|---------|-------------------------|

Description

Method batchIn returns TRUE/FALSE values depending on the batch column presence/absence in the dataset

Methods

signature(obj = "PhenList")

signature(obj = "PhenTestResult")

boxplotResidualBatch *Method "boxplotResidualBatch"*

Description

Graph function for the Mixed Model framework's results. Creates a box plot with residue versus batch split by genotype.

Usage

```
boxplotResidualBatch(phenTestResult, outputMessages=TRUE)
```

Arguments

phenTestResult instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument

outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#) and [PhenTestResult](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
result <- testDataset(test,
  depVariable="Lean.Mass")
boxplotResidualBatch(result)
```

boxplotSexGenotype *Method "boxplotSexGenotype"*

Description

Graph function for the phenotypic dataset. Creates a box plot split by sex and genotype.

Usage

```
boxplotSexGenotype(phenList, depVariable=NULL, graphingName=NULL, outputMessages=TRUE)
```

Arguments

| | |
|----------------|---|
| phenList | instance of the PhenList class; mandatory argument |
| depVariable | a character string defining the dependent variable of interest; mandatory argument |
| graphingName | a character string defining the name to be used on the graph for the dependent variable; mandatory argument |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE |

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
# box plot for dataset with two sexes: males and females
boxplotSexGenotype(test,
  depVariable="Bone.Mineral.Content",
  graphingName="BMC")

file <- system.file("extdata", "test4.csv", package="PhenStat")
```

```
test_1sex <- PhenList(dataset=read.csv(file),
  testGenotype="Mysm1/+")
# box plot for females only dataset
boxplotSexGenotype(test_1sex,
  depVariable="Lean.Mass",
  graphingName="Lean Mass (g)")
```

boxplotSexGenotypeBatch

Method "boxplotSexGenotypeBatch"

Description

NB! Function is deprecated, please use scatterplotSexGenotypeBatch function instead. Graph function for the phenotypic dataset. Creates a box plot split by sex, genotype and batch.

Note: the batches are not ordered with time but allow assessment of how the treatment groups lie relative to the normal control variation.

Usage

```
boxplotSexGenotypeBatch(phenList, depVariable=NULL, graphingName=NULL, outputMessages=TRUE)
```

Arguments

| | |
|----------------|---|
| phenList | instance of the PhenList class; mandatory argument |
| depVariable | a character string defining the dependent variable of interest; mandatory argument |
| graphingName | a character string defining the name to be used on the graph for the dependent variable; mandatory argument |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE |

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```

file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
# box plot for dataset with two sexes: males and females
boxplotSexGenotypeBatch(test,
  depVariable="Bone.Mineral.Content",
  graphingName="BMC" )

file <- system.file("extdata", "test4.csv", package="PhenStat")
test_1sex <- PhenList(dataset=read.csv(file),
  testGenotype="Mysm1/+")
# box plot for females only dataset
boxplotSexGenotypeBatch(test_1sex,depVariable="Lean.Mass",
  graphingName="Lean Mass")

```

boxplotSexGenotypeBatchAdjusted

Method "boxplotSexGenotypeBatchAdjusted"

Description

Graph function for the phenotypic dataset. Creates a box plot split by sex and genotype after accounting for batch.

Usage

```
boxplotSexGenotypeBatchAdjusted(phenList,depVariable=NULL,graphingName=NULL,outputMessages=TRUE)
```

Arguments

| | |
|----------------|---|
| phenList | instance of the PhenList class; mandatory argument |
| depVariable | a character string defining the dependent variable of interest; mandatory argument |
| graphingName | a character string defining the name to be used on the graph for the dependent variable; mandatory argument |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE |

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also[PhenList](#)**Examples**

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
# box plot for dataset with two sexes: males and females
boxplotSexGenotypeBatchAdjusted(test,
  depVariable="Bone.Mineral.Content",
  graphingName="BMC" )
```

`boxplotSexGenotypeResult`*Method "boxplotSexGenotypeResult"*

Description

Graph function for the phenotypic dataset. Creates a box plot split by sex and genotype. Is based on PhenTestResult object.

Usage

```
boxplotSexGenotypeResult(phenTestResult, graphingName=NULL, outputMessages=TRUE)
```

Arguments

`phenTestResult` instance of the [PhenTestResult](#) class; mandatory argument
`graphingName` a character string defining the name to be used on the graph for the dependent variable; mandatory argument
`outputMessages` flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also[PhenList](#)

Examples

```

file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
result <- testDataset(test,
  depVariable="Lean.Mass")
# box plot for dataset with two sexes: males and females
boxplotSexGenotypeResult(result,
  graphingName="BMC")

file <- system.file("extdata", "test4.csv", package="PhenStat")
test_1sex <- PhenList(dataset=read.csv(file),
  testGenotype="Mysm1/+")
result_1sex <- testDataset(test_1sex,
  depVariable="Lean.Mass")
# box plot for females only dataset
boxplotSexGenotypeResult(result_1sex,
  graphingName="Lean Mass (g)")

```

boxplotSexGenotypeWeightBatchAdjusted

Method "boxplotSexGenotypeWeightBatchAdjusted"

Description

Graph function for the phenotypic dataset. Creates a box plot split by sex and genotype after accounting for batch and weight.

Usage

```
boxplotSexGenotypeWeightBatchAdjusted(phenList, depVariable=NULL, graphingName=NULL, outputMessages)
```

Arguments

| | |
|----------------|---|
| phenList | instance of the PhenList class; mandatory argument |
| depVariable | a character string defining the dependent variable of interest; mandatory argument |
| graphingName | a character string defining the name to be used on the graph for the dependent variable; mandatory argument |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE |

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
                 testGenotype="Sparc/Sparc")
# box plot for dataset with two sexes: males and females
boxplotSexGenotypeWeightBatchAdjusted(test,
    depVariable="Bone.Mineral.Content",
    graphingName="BMC" )
```

categoricalBarplot *Method "categoricalBarplot"*

Description

Graph function for the Fisher Exact Test framework's results. Creates stacked bar plot(s) to compare proportions seen in a categorical variable between different genotypes. Graphs are created for all data and also for each sex individually.

Usage

```
categoricalBarplot(phenTestResult, outputMessages=TRUE)
```

Arguments

phenTestResult instance of the [PhenTestResult](#) class that comes from the function testDataset; mandatory argument

outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Aff3/Aff3")
result <- testDataset(test,
  depVariable="Thoracic.Processes",
  method="FE")
categoricalBarplot(result)
```

checkDataset

Method "checkDataset"

Description

Checks dataset for the minimum required info:

1. Column names should present
2. Genotype column should present
3. Sex column should present
4. Two data points for each Genotype/Sex combination
5. Number of Genotype levels should be 2
6. Number of Sex levels should be 1 or 2
7. Sex levels have to be "Female" and/or "Male"
8. Records with reference genotype should be in the dataset
9. Records with test genotype should be in the dataset

Perform the following additional checks:

- presence of Weight column,
- presence of Batch column (Assay.Date).

Warning given in case of missed data indicating that you can only fit a glm or to use MM equation "withoutWeight".

Function [checkDataset](#) is called from [PhenList](#) function.

Usage

```
checkDataset(dataset, testGenotype, refGenotype="+/+",
             outputMessages=TRUE, dataset.clean=TRUE)
```

Arguments

| | |
|----------------|---|
| dataset | data frame created from file or from another source; mandatory argument |
| testGenotype | defines the test genotype to be compared to the reference genotype; mandatory argument |
| refGenotype | defines the reference genotype; assigned default value is "+/+" |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; assigned default value is TRUE |
| dataset.clean | flag: "FALSE" value for no modification of the dataset; "TRUE" value to clean dataset if needed; assigned default value is TRUE |

Value

Returns an instance of the [PhenList](#) class.

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#)

Examples

```
# "checkDataset" is called internally from "PhenList" function
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
                 testGenotype="Sparc/Sparc")
```

classificationTag *Method "classificationTag"*

Description

Returns a classification tag to assign a sexual dimorphism assessment of the phenotypic change.

Usage

```
classificationTag(phenTestResult, userMode = "summaryOutput",
                 phenotypeThreshold = 0.01, outputMessages=TRUE)
```

Arguments

| | |
|--------------------|--|
| phenTestResult | instance of the PhenTestResult class that comes from the function testDataset ; mandatory argument |
| userMode | flag: "vectorOutput" a sexual dimorphic classification is assigned with a proviso of later assessing the overall statistical significance; "summaryOutput" the phenotypeThreshold is used to assess the overall statistical significance and then if significant the sexual dimorphic classification determined; defaults to summaryOutput |
| phenotypeThreshold | a numerical value defining the threshold to use in classificationTag in determining whether the genotype effect is classed as significant or not; default value 0.01 |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages ; default value TRUE |

Value

Returns a classification tag to assign a sexual dimorphism assessment of the phenotypic change.

If you are working interactively with the data, the argument "userMode" set to the value "summaryOutput" will use the "phenotypeThreshold" argument's value to assess statistical significance of the genotype effect and if significant then assign a sexual dimorphic classification. Alternatively, if the "userMode" set to the value "vectorMode", a sexual dimorphic classification will be returned with the MM framework where later you can globally assess whether the variable had a significant genotype effect. With the FE framework and the vectorMode, a NA is returned as the type of the effect cannot be assessed without assessing the statistical significance of the genotype effect.

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
result <- testDataset(test,
  depVariable="Lean.Mass")
classificationTag(result,
  userMode="summaryOutput",
  phenotypeThreshold=0.001)
classificationTag(result,
  userMode="vectorOutput")
```

comparison

Method "comparison"

Description

Method comparison returns name of the comparison that was performed by RR framework: "High vs Normal/Low" or "Low vs Normal/High"

Methods

signature(obj = "hctestPhenStat")

dataset

Method "dataset"

Description

Method dataset returns data frame stored in the object

Methods

signature(obj = "PhenList")

| | |
|--------------|-----------------------|
| finalLRModel | Method "finalLRModel" |
|--------------|-----------------------|

Description

This is an internal function run within LR framework. It completes the final stage of the LR framework, which builds the final model and estimates effects. As an internal function, it doesn't include extensive error testing of inputs. Please use cautiously if calling directly.

Works with [PhenTestResult](#) object created by [startLRModel](#) function. The creation of LR final model is based on the significance of different fixed effects, depVariable and equation values stored in [PhenTestResult](#) object.

Usage

```
finalLRModel(phenTestResult, outputMessages = TRUE)
```

Arguments

`phenTestResult` instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument

`outputMessages` flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

Value

Returns results stored in instance of the [PhenTestResult](#) class

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#) and [testDataset](#)

Examples

```

file <- system.file("extdata", "testLR.csv", package="PhenStat")
testLR <- PhenList(dataset=read.csv(file),
  testGenotype="Mock")
testLR2 <- LRDataset(testLR, "V2")

# when "testDataset" function's argument "callAll" is set to FALSE
# only "startLRModel" function is called - the first step of LR framework
resultLR <- testDataset(testLR2,
  depVariable="V2",
  callAll=FALSE,
  method="LR")
# print out formula that has been created
analysisResults(resultLR)$model.formula.genotype
# print out batch effect's significance
analysisResults(resultLR)$model.effect.batch
resultLR <- finalLRModel(resultLR)

```

| | |
|------------|----------------------------|
| finalModel | <i>Method "finalModel"</i> |
|------------|----------------------------|

Description

This is an internal function run within MM framework. It completes the final stage of the MM framework, which builds the final model and estimates effects. As an internal function, it doesn't include extensive error testing of inputs. Please use cautiously if calling directly.

Works with [PhenTestResult](#) object created by [startModel](#) function. The creation of MM final model is based on the significance of different fixed effects, depVariable and equation values stored in [PhenTestResult](#) object.

Usage

```
finalModel(phenTestResult, outputMessages = TRUE)
```

Arguments

`phenTestResult` instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument

`outputMessages` flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

Value

Returns results stored in instance of the [PhenTestResult](#) class

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#) and [testDataset](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
# when "testDataset" function's argument "callAll" is set to FALSE
# only "startModel" function is called - the first step of MM framework
result <- testDataset(test,
  depVariable="Lean.Mass",
  equation="withoutWeight",
  callAll=FALSE)
# print out formula that has been created
# result$model.formula.genotype
# print out batch effect's significance
# result$model.effect.batch
# change the model
# result <- testDataset(test,
#   depVariable="Lean.Mass",
#   equation="withWeight",
#   callAll=FALSE)
# print out new formula
#result$model.formula.genotype
# run the final model fitting when statisfied with the model
result <- finalModel(result)
```

finalTFModel

Method "finalTFModel"

Description

This is an internal function run within TF framework. It completes the final stage of the TF framework, which builds the final model and estimates effects. As an internal function, it doesn't include extensive error testing of inputs. Please use cautiously if calling directly.

Works with [PhenTestResult](#) object created by [startTFModel](#) function. The creation of TF final model is based on the significance of different fixed effects, depVariable and equation values stored in [PhenTestResult](#) object.

Usage

```
finalTFModel(phenTestResult, outputMessages = TRUE)
```

Arguments

phenTestResult instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument

outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

Value

Returns results stored in instance of the [PhenTestResult](#) class

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* **7**(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#) and [testDataset](#)

Examples

```
file <- system.file("extdata", "test7_TFE.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
                testGenotype="het",
                refGenotype = "WT",
                dataset.colname.sex="sex",
                dataset.colname.genotype="Genotype",
                dataset.values.female="f",
                dataset.values.male= "m",
                dataset.colname.weight="body.weight",
                dataset.colname.batch="Date_of_procedure_start")

test_TF <- TFDataset(test,depVariable="Cholesterol")

# when "testDataset" function's argument "callAll" is set to FALSE
# only "startTFModel" function is called - the first step of TFE framework
result <- testDataset(test_TF,
                     depVariable="Cholesterol",
                     callAll=FALSE,
                     method="TF")
```

```
# print out formula that has been created
analysisResults(result)$model.formula.genotype
# print out batch effect's significance
analysisResults(result)$model.effect.batch
result <- finalTFModel(result)
```

FisherExactTest *Method "FisherExactTest"*

Description

The main function of the Fisher Exact Test framework. Creates n times 2 matrices with record counts, where n rows represent dependent variable levels and two columns represent genotype levels. Performs Fisher Exact Tests on calculated count matrices.

Three matrices can be created and three tests can be potentially perform depending on the dataset:

- all records together regardless the sex values - combined dataset,
- records where sex value is "Male" (if such exists) - males only dataset,
- records where sex value is "Female" (if such exists) - females only dataset.

Together with count matrices creates percentage matrices, calculates effect sizes and statistics for count matrices. Performs Fisher Exact Tests.

The results (matrices, statistics and Fisher Exact Test outputs) are stored in [PhenTestResult](#) object.

The function is called from "testDataset" function when "method" argument is set to "FE" meaning "Fisher Exact Test".

Usage

```
FisherExactTest(phenList, depVariable, outputMessages=TRUE)
```

Arguments

| | |
|----------------|---|
| phenList | instance of the PhenList class; mandatory argument |
| depVariable | a character string defining the dependent variable of interest; mandatory argument |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE |

Value

Returns results stored in instance of the [PhenTestResult](#) class

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#)

Examples

```
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Aff3/Aff3")
# "FisherExactTest" function is called from "testDataset" function.
result <- testDataset(test,depVariable="Thoracic.Processes",method="FE")
# Fisher Exact Test results can be printed out using function "summaryOutput"
summaryOutput(result)
```

generateGraphs

Method "generateGraphs"

Description

Function generates graphs for the Mixed Model and Time as Fixed Effect frameworks' results and stores generated graphs in the defined directory.

Usage

```
generateGraphs(phenTestResult, dir,
  graphingName=NULL, type="Xlib")
```

Arguments

| | |
|----------------|---|
| phenTestResult | instance of the PhenTestResult class that comes from the function testDataset ; mandatory argument |
| dir | directory where to store generated graphs; mandatory argument |
| graphingName | a character string defining the name to be used on the graph for the dependent variable; defaults to NULL then the depVariable name will be plotted |
| type | character string, one of "Xlib" or "quartz" (some OS X builds) or "cairo", or "window", or "cairo-png"; mandatory argument |

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#)

| | |
|-----------|---------------------------|
| getColumn | <i>Method "getColumn"</i> |
|-----------|---------------------------|

Description

Method getColumn returns column of interest

Methods

signature(obj = "PhenList")

| | |
|------------------------|--|
| getColumnBatchAdjusted | <i>Method "getColumnBatchAdjusted"</i> |
|------------------------|--|

Description

Method getColumnBatchAdjusted returns column of interest adjusted for batch

Methods

signature(obj = "PhenList")

| | |
|---------------|-------------------------------|
| getColumnView | <i>Method "getColumnView"</i> |
|---------------|-------------------------------|

Description

Method getColumnView returns RR or FE frameworks results in a column format

Methods

signature(obj = "hstestPhenStat")

getColumnWeightBatchAdjusted
Method "getColumnWeightBatchAdjusted"

Description

Method getColumnWeightBatchAdjusted returns column of interest adjusted for weight and batch

Methods

signature(obj = "PhenList")

getCountMatrices *Method "getCountMatrices"*

Description

Method getCountMatrices returns count matrices for FE and RR frameworks

Methods

signature(obj = "PhenTestResult")

getDataset *Method "getDataset"*

Description

Method getDataset returns data frame stored in the object

Methods

signature(obj = "PhenList")

getGenotypeEffect *Method "getGenotypeEffect"*

Description

Method getGenotypeEffect returns genotype effect and standard error for the linear regression frameworks

Methods

signature(obj = "PhenTestResult")

| | |
|-----------|---------------------------|
| getMatrix | <i>Method "getMatrix"</i> |
|-----------|---------------------------|

Description

Method getMatrix returns RR or FE frameworks results in a matrix format

Methods

signature(obj = "hstestPhenStat")

| | |
|---------------------|-------------------------------------|
| getPercentageMatrix | <i>Method "getPercentageMatrix"</i> |
|---------------------|-------------------------------------|

Description

Method getPercentageMatrix returns percentage matrix calculated out of counts

Methods

signature(obj = "hstestPhenStat")

| | |
|---------|-------------------------|
| getStat | <i>Method "getStat"</i> |
|---------|-------------------------|

Description

Method getStat returns simple statistics about variables in the dataset

Methods

signature(obj = "PhenList")

| | |
|-------------|-----------------------------|
| getVariable | <i>Method "getVariable"</i> |
|-------------|-----------------------------|

Description

Method getVariable returns dependent variable name

Methods

signature(obj = "PhenTestResult")

| | |
|--------------|------------------------------|
| getVariables | <i>Method "getVariables"</i> |
|--------------|------------------------------|

Description

Method getVariables returns names of variables in the dataset

Methods

signature(obj = "PhenList")

| | |
|--------------|------------------------------|
| hemiGenotype | <i>Method "hemiGenotype"</i> |
|--------------|------------------------------|

Description

Method hemiGenotype returns hemi genotype if defined

Methods

signature(obj = "PhenList")

signature(obj = "PhenTestResult")

| | |
|------------|----------------------------|
| JSONOutput | <i>Method "JSONOutput"</i> |
|------------|----------------------------|

Description

Wrapper for the model fitting results. Returns model fitting and testing results in a JSON format. Assumes that modelling results are stored in the [PhenTestResult](#) object (output from function [testDataset](#)).

Usage

```
JSONOutput(phenTestResult, phenotypeThreshold = 0.01)
```

Arguments

phenTestResult instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument

phenotypeThreshold a numerical value defining the threshold to use in classificationTag; default value 0.01

Value

Returns a vector with model fitting results in JSON format: model output summary and other values

Author(s)

Natalja Kurbatova

See Also

[PhenTestResult](#)

Examples

```
# Mixed Model framework
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
result <- testDataset(test,
  depVariable="Lean.Mass")
JSONOutput(result)

# Fishe Exact Test framework
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test2 <- PhenList(dataset=read.csv(file),
  testGenotype="Aff3/Aff3")
result2 <- testDataset(test2,
  depVariable="Thoracic.Processes",
  method="FE")
JSONOutput(result2)
```

LRDataset

Method "LRDataset"

Description

Prepares dataset for the LR framework - maps values of dependent variable to 0/1, where 1 is modeled.

Usage

```
LRDataset(phenList = NULL, depVariable = NULL, abnormalValues =
  c("abnormal", "Abnormal", "TRUE", "deviant"),
  outputMessages = TRUE)
```

Arguments

- phenList instance of the [PhenList](#) class; mandatory argument
- depVariable a character string defining the dependent variable of interest; mandatory argument
- abnormalValues a list of abnormal values that will be mapped to 0; mandatory argument
- outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

Value

Returns dataset suitable for LR framework, where provided abnormal values are mapped to 1 and all other values of dependent variable are assumed to be normal and are mapped to 0.

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* **7**(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

Examples

```
file <- system.file("extdata", "testLR.csv", package="PhenStat")
testLR <- PhenList(dataset=read.csv(file),
                  testGenotype="Mock")
testLR2 <- LRDataset(testLR, "V2")
```

matrixCount

Method "matrixCount"

Description

Method `matrixCount` returns matrix of counts that was created by RR or FE framework.

Methods

`signature(obj = "hstestPhenStat")`

| | |
|--------|------------------------|
| method | <i>Method "method"</i> |
|--------|------------------------|

Description

Method method returns method abbreviation, for example: "RR", "MM".

Methods

signature(obj = "PhenTestResult")

| | |
|------------|----------------------------|
| methodText | <i>Method "methodText"</i> |
|------------|----------------------------|

Description

Method methodText returns method's name, for example: "Reference Range Plus", "Linear Mixed Model".

Methods

signature(obj = "PhenTestResult")

| | |
|-----------------|---------------------------------|
| multipleBatches | <i>Method "multipleBatches"</i> |
|-----------------|---------------------------------|

Description

Method multipleBatches returns TRUE if there are multiple batches in the dataset, FALSE otherwise

Methods

signature(obj = "PhenList")

| | |
|---------|-------------------------|
| noSexes | <i>Method "noSexes"</i> |
|---------|-------------------------|

Description

Method noSexes returns number of sex levels: 1/2

Methods

signature(obj = "PhenList")
signature(obj = "PhenTestResult")

| | |
|------------|----------------------------|
| parameters | <i>Method "parameters"</i> |
|------------|----------------------------|

Description

Method parameters returns parameters specific for applied method/dataset combination

Methods

signature(obj = "PhenTestResult")

| | |
|---------------------|-------------------------------------|
| parserOutputSummary | <i>Method "parserOutputSummary"</i> |
|---------------------|-------------------------------------|

Description

Parsers model output summary and returns it in readable named vector format

Usage

```
parserOutputSummary(linearRegressionOutput)
```

Arguments

linearRegressionOutput
linear regression output that comes from the MM methods; mandatory argument

Value

Returns a named vector with linear regression model output summary results

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
result <- testDataset(test,
  depVariable="Lean.Mass")
linearRegressionOutput <- analysisResults(result)
parserOutputSummary(linearRegressionOutput)
```

parserOutputSummaryLR *Method "parserOutputSummaryLR"*

Description

Parsers model output summary and returns it in readable named vector format

Usage

```
parserOutputSummaryLR(linearRegressionOutput)
```

Arguments

linearRegressionOutput
linear regression output that comes from the MM methods; mandatory argument

Value

Returns a named vector with logistic regression model output summary results

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#)

Examples

```
file <- system.file("extdata", "testLR.csv", package="PhenStat")
testLR <- PhenList(dataset=read.csv(file),
  testGenotype="Mock")
testLR2 <- LRDataset(testLR, "V2")
resultLR <- testDataset(testLR2,
  depVariable="V2",
  method="LR")
linearRegressionOutput <- analysisResults(resultLR)
parserOutputSummaryLR(linearRegressionOutput)
```

parserOutputTFSummary *Method "parserOutputTFSummary"*

Description

Parsers model output summary from TF framework and returns it in readable named vector format

Usage

```
parserOutputTFSummary(linearRegressionOutput)
```

Arguments

linearRegressionOutput
linear regression output that comes from the TF method; mandatory argument

Value

Returns a named vector with model output summary results

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#)

Examples

```
file <- system.file("extdata", "test6_RR.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="0xr1/0xr1")
result <- testDataset(test,
  depVariable="Ca",
  method="TF",
  dataPointsThreshold=2)
linearRegressionOutput <- analysisResults(result)
parserOutputTFSummary(linearRegressionOutput)
```

 PhenList

Method "PhenList"

Description

Function to create data object from the data frame.

In addition to dependent variable column (the variable of interest) mandatory columns that should present in the data frame are "Genotype" and "Sex". The "Assay.Date" column is used to model "Batch" effect if not specified differently. "Weight" column is used to model body weight effect.

Function creates [PhenList](#) object, checks data integrity, renames columns when requested, provides simple statistics about dataset.

Returns an instance of the [PhenList](#) object created from the data file.

Dataset is cleaned to ensure there is a maximum two sex levels and there are exactly two levels for genotype. Data cleaning can be switched off by defining the argument "dataset.clean" as FALSE.

Usage

```
PhenList(dataset, testGenotype, refGenotype="+/+", hemiGenotype=NULL,
  outputMessages=TRUE, dataset.clean=TRUE,
  dataset.colname.batch=NULL, dataset.colname.genotype=NULL,
  dataset.colname.sex=NULL, dataset.colname.weight=NULL,
  dataset.values.missingValue=" ", dataset.values.male=NULL,
  dataset.values.female=NULL)
```

Arguments

| | |
|--------------|--|
| dataset | data frame created from file or from another source; mandatory argument |
| testGenotype | defines the test genotype to be compared to the reference genotype; mandatory argument |
| refGenotype | defines the reference genotype; assigned default value is "+/+" |
| hemiGenotype | defines the genotype value for hemizygous that will be changed to test genotype value |

outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; assigned default value is TRUE

dataset.clean flag: "FALSE" value for no modification of the dataset; "TRUE" value to clean dataset if needed; assigned default value is TRUE

dataset.colname.batch
column name within dataset for the batch effect

dataset.colname.genotype
column name within dataset for the genotype info

dataset.colname.sex
column name within dataset for the sex info

dataset.colname.weight
column name within dataset for the weight info

dataset.values.missingValue
value used as missing value in the dataset

dataset.values.male
value used to label "males" in the dataset

dataset.values.female
value used to label "females" in the dataset

Value

Returns an instance of the [PhenList](#) class.

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")

file <- system.file("extdata", "test2.csv", package="PhenStat")
test2 <- PhenList(dataset=read.csv(file),
  testGenotype="Arid4a/Arid4a",
  refGenotype="+/+",
  hemiGenotype="Arid4a/+",
```

```

dataset.colname.weight="Weight.Value")

file <- system.file("extdata", "test3.csv", package="PhenStat")
test3 <- PhenList(dataset=read.csv(file),
  dataset.clean=TRUE,
  dataset.values.female=1,
  dataset.values.male=2,
  testGenotype="Mysm1/+")

```

PhenList-class

Class "PhenList"

Description

A list-based S4 class for storing phenotypic data. Helps to support data integrity checks and statistics calculation. The PhenList object can be created by using function [PhenList](#).

Explore PhenList object

PhenList object instance contains the following slots:

1. "datasetPL" where cleaned and checked dataset is stored: `getDataset(phenList)`
2. "testGenotype" where the genotype level to test is stored: `testGenotype(phenList)`
3. "refGenotype" where reference genotype value is stored with default value set to "+/+":
`refGenotype(phenList)`
4. "hemiGenotype" if defined contains the genotype value for hemizygous: `hemiGenotype(phenList)`
6. "dataset.clean" flag value is stored, see [PhenList](#) for more details:
`phenList@dataset.clean`
7. "dataset.colname" if defined contains dataset column names that have been renamed:
 - `phenList@dataset.colname.batch` column name for batch values
 - `phenList@dataset.colname.genotype` column name for genotype values
 - `phenList@dataset.colname.sex` column name for sex values
 - `phenList@dataset.colname.weight` column name for weight values
8. "dataset.values" if defined contains dataset values that have been changed during dataset cleaning process:
 - `phenList@dataset.values.missingValue` value used as missing value in the original dataset
 - `phenList@dataset.values.male` value used to label "males" in the original dataset
 - `phenList@dataset.values.female` value used to label "females" in the original dataset

Slots

datasetPL: Object of class "data.frame" ~~ dataset to work with
refGenotype: Object of class "character" ~~ reference genotype
testGenotype: Object of class "character" ~~ test genotype
hemiGenotype: Object of class "character" ~~ hemi genotype
dataset.colname.batch: Object of class "character" ~~ column name for batch values
dataset.colname.genotype: Object of class "character" ~~ column name for genotype values
dataset.colname.sex: Object of class "character" ~~ column name for sex values
dataset.colname.weight: Object of class "character" ~~ column name for weight values
dataset.values.missingValue: Object of class "character" ~~ value used as missing value in the original dataset
dataset.values.male: Object of class "character" ~~ value used to label "males" in the original dataset
dataset.values.female: Object of class "character" ~~ value used to label "females" in the original dataset
dataset.clean: Object of class "logical" ~~ flag value is stored
datasetUNF: Object of class "data.frame" ~~ unfiltered dataset

Methods

getDataset (accessor): Returns dataset
refGenotype (accessor): Returns reference genotype
testGenotype (accessor): Returns test genotype
hemiGenotype (accessor): Returns hemi genotype if specified
getColumn Returns specified column if exists
getColumnBatchAdjusted Returns specified column adjusted for batch effect
getColumnWeightBatchAdjusted Returns specified column adjusted for batch and weight effects
getStat Returns simple dataset statistics
getVariables Returns dataset column names
batchIn Returns TRUE if the batch is in the dataset, FALSE otherwise
weightIn Returns TRUE if the weight is in the dataset, FALSE otherwise
multipleBatches Returns TRUE if the batches are variable in the dataset, FALSE otherwise
noSexes Returns number of sexes in the dataset
setBatch Sets the batch column - change the column names
setGenotype Sets the genotype column - change the column names
setMissingValue Sets the missing value
setSex Sets the sex column - change the column names
setWeight Sets the weight column - change the column names

Author(s)

Natalja Kurbatova

See Also[PhenList](#)**Examples**

```

file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
class(test)

file <- system.file("extdata", "test2.csv", package="PhenStat")
test2 <- PhenList(dataset=read.csv(file),
  testGenotype="Arid4a/Arid4a",
  refGenotype="+/+",
  hemiGenotype="Arid4a/+",
  dataset.colname.weight="Weight.Value")
getStat(test2)
testGenotype(test2)
refGenotype(test2)
hemiGenotype(test2)

```

PhenTestResult

*Method "PhenTestResult"***Description**

Creates [PhenTestResult](#) object based on test results or model building results. Internal function for the package. Not build for users to directly call.

Usage

```

PhenTestResult(model.output=NULL, model.dataset=NULL,
  depVariable=NULL,
  refGenotype=NULL,
  equation="withWeight",
  method="MM", model.effect.batch=NULL,
  model.effect.variance=NULL, model.effect.sex=NULL,
  model.effect.interaction=NULL, model.output.interaction=NULL,
  model.effect.weight=NULL, numberSexes=NULL, pThreshold=0.05,
  model.formula.null=NULL, model.formula.genotype=NULL,
  model.output.genotype.nulltest.pVal=NULL,
  model.output.quality=NULL, model.output.summary=NULL,
  model.output.averageRefGenotype = NULL,
  model.output.percentageChanges = NULL)

```

Arguments

| | |
|--|--|
| <code>model.output</code> | representing the model fit gls object or lme object |
| <code>model.dataset</code> | dataset used for modeling |
| <code>depVariable</code> | depending variable in the model |
| <code>refGenotype</code> | reference genotype in the model |
| <code>equation</code> | possible values: "withWeight" to include weight effect into model, "withoutWeight" to exclude weight effect from the model |
| <code>method</code> | possible values: "MM" to work with Mixed Model framework, "FE" to work with Fisher Exact Test framework |
| <code>model.effect.batch</code> | Result of the test for batch effect significance |
| <code>model.effect.variance</code> | Result of the test for residual variance effect |
| <code>model.effect.sex</code> | Result of the test for sex effect significance |
| <code>model.effect.weight</code> | Result of the test for weight effect significance |
| <code>model.effect.interaction</code> | Result of the test for genotype by sex interaction significance |
| <code>model.output.interaction</code> | Interaction test result: p-value |
| <code>numberSexes</code> | number of possible sex values in the dataset |
| <code>pThreshold</code> | p-value threshold used to evaluate the effect significance, default value 0.05 |
| <code>model.formula.null</code> | formula for the model without genotype effect |
| <code>model.formula.genotype</code> | formula for the model with genotype effect |
| <code>model.output.genotype.nulltest.pVal</code> | Genotype test results: p-value |
| <code>model.output.quality</code> | vector that contains diagnostic test output for mixed model quality of fit |
| <code>model.output.summary</code> | named vector that contains summary of the model output |
| <code>model.output.averageRefGenotype</code> | named vector that contains mean values calculated for reference genotype records |
| <code>model.output.percentageChanges</code> | named vector that contains percentage changes values per sex |

Value

Returns an instance of the [PhenTestResult](#) class.

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
# "testDataset" function calls "PhenTestResult" function internally
result <- testDataset(test,
  equation="withoutWeight",
  depVariable="Lean.Mass")
class(result)
```

PhenTestResult-class *Class "PhenTestResult"*

Description

A list-based S4 class for storing of model fitting results and other information like dependent variable, method used to build a model, etc. Helps to support operations needed for model fitting process and modelling/testing results storage. In the package PhenTestResult object is created by function [testDataset](#).

Explore PhenTestResult object

PhenTestResults object instance contains the following slots:

1. "analysedDataset" contains subdataset that was used for the modelling/testing:

`analysedDataset(phenTestResult)`

2. "depVariable" contains dependent variable that was tested: `getVariable(phenTestResult)`

3. "refGenotype" contains reference genotype which is usually is wildtype: `refGenotype(phenTestResult)`

4. "testGenotype" contains test genotype: `testGenotype(phenTestResult)`

5. "method" contains method name that was used for modelling/testing: `method(phenTestResult)`

6. "transformationRequired" contains TRUE/FALSE value indicating transformation of dependent variable:

`transformationText(phenTestResult)` or `phenTestResult@transformationRequired`

7. "lambdaValue" contains lambda value for the Box-Cox transformation:

transformationText(phenTestResult) or phenTestResult\$lambdaValue

8. "scaleShift" contains the value of scale shift for Box-Cox transformation:

transformationText(phenTestResult) or phenTestResult@scaleShift

9. "transformationCode" contains the code of transformation. Possible values:

0 - transformation is not applicable (methods "FE", "RR", "LR") or switched off by user
 1 - transformation is not needed (1 is within the 95% CI)
 2 - log transformation
 3 - power transformation
 4 - transformation is not performed since optimal lambda value is not found ($-5 < \lambda < 5$)

transformationText(phenTestResult) or phenTestResult@transformationCode

10. "parameters" contains the parameters used during method application, e.g. pThreshold for MM and TF:

parameters(phenTestResult)

11. Modelling/testing results are stored in the sections "analysisResults": analysisResults(phenTestResult)

The contents of the analysisResults slot depend on framework that was used.

The results of MM and TF frameworks: 1. Equation used during linear modeling: analysisResults(phenTestResult)\$equation

2. Batch effect significance: analysisResults(phenTestResult)\$model.effect.batch

3. Variance equality: analysisResults(phenTestResult)\$model.effect.variance

4. Weight effect significance: analysisResults(phenTestResult)\$model.effect.weight

5. Sex effect significance: analysisResults(phenTestResult)\$model.effect.interaction

6. Evidence of sex effect (p-value): analysisResults(phenTestResult)\$model.output.interaction

7. Evidence of genotype effect (p-value): analysisResults(phenTestResult)\$model.output.genotype.nulltest.pvalue

8. Formula for the final genotype model: analysisResults(phenTestResult)\$model.formula.genotype

9. Formula for the final null model: analysisResults(phenTestResult)\$model.formula.null

10. Model fitting output: analysisResults(phenTestResult)\$model.output

11. Model fitting summary: summary(analysisResults(phenTestResult)\$model.output)\$tTable

The results of FE and RR frameworks are stored as a list of htestPhenStat S4 objects: analysisResults(phenTestResult)[c("FE", "RR")]

Each one htestPhenStat object contains:

1. Output of Fisher Exact Test: pvalue(analysisResults(phenTestResult)[[1]]).

2. Effect size: ES(analysisResults(phenTestResult)[[1]]).

3. Name of the table analysed (all, males, females): analysedSubset(analysisResults(phenTestResult)[[1]]).

4. Comparison, used for RR only (High vs Normal/Low, Low vs High/Normal): comparison(analysisResults(phenTestResult)[[1]]).

5. Matrix of counts: matrixCount(analysisResults(phenTestResult)[[1]]).

Slots

analysedDataset: Object of class "data.frame" ~~ analysed dataset

transformationRequired: Object of class "logical" ~~ flag indicating was or not transformation performed

lambdaValue: Object of class "numeric" ~~ Box-Cox transform lambda value

scaleShift: Object of class "numeric" ~~ Box-Cox transform scale shift

transformationCode: Object of class "numeric" ~~ code explaining the transformation output
 depVariable: Object of class "character" ~~ dependent variable
 refGenotype: Object of class "character" ~~ reference genotype
 testGenotype: Object of class "character" ~~ test genotype
 method: Object of class "character" ~~ analysis method
 parameters: Object of class "matrix" ~~ parameters of method
 analysisResults: Object of class "list" ~~ results of the analysis

Methods

getVariable (accessor): Returns dependent variable
refGenotype (accessor): Returns reference genotype
testGenotype (accessor): Returns test genotype
method (accessor): Returns method used
methodText (accessor): Returns full name of the method used
parameters (accessor): Returns parameteres used during the method application
analysisResults (accessor): Returns analysis results depending on method
analysedDataset (accessor): Returns analysed dataset
transformationText (accessor): Returns the info about transformation
batchIn Returns TRUE if the batch is in the dataset, FALSE otherwise
weightIn Returns TRUE if the weight is in the dataset, FALSE otherwise
noSexes Returns number of sexes in the dataset
show Prints out the PhenTestResult object
getCountMatrices Returns count matrices if they are present (for methods "FE" and "RR"), NULL otherwise.

Author(s)

Natalja Kurbatova

Examples

```

# Mixed Model framework
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
result <- testDataset(test,
  equation="withoutWeight",
  depVariable="Bone.Area")
getVariable(result)
method(result)
# Batch effect is significant
analysisResults(result)$model.effect.batch
# Variance homogeneosity

```

```

analysisResults(result)$model.effect.variance
# Weight effect is significant
analysisResults(result)$model.effect.weight
# Sex effect is significant
analysisResults(result)$model.effect.interaction
# Sex effect p-value - the result of the test
analysisResults(result)$model.output.interaction
# Genotype effect p-value
analysisResults(result)$model.output.genotype.nulltest.pVal
# Final model formula with genotype
analysisResults(result)$model.formula.genotype
# Final model formula without genotype
analysisResults(result)$model.formula.null
# Final model fitting output
# result$model.output
# Final model fitting summary
# summary(result$model.output)$tTable

# Fisher Exact Test framework
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Aff3/Aff3")
result <- testDataset(test,
  depVariable="Thoracic.Processes",
  method="FE")
getVariable(result)
method(result)
for (i in seq_along(analysisResults(result))) {
  val <- analysisResults(result)[[i]]
  val
}

```

plotResidualPredicted *Method "plotResidualPredicted"*

Description

Graph function for the Mixed Model framework's results. Creates predicted versus residual values plots split by genotype.

Usage

```
plotResidualPredicted(phenTestResult, outputMessages=TRUE)
```

Arguments

phenTestResult instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument

outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#) and [PhenTestResult](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
result <- testDataset(test,
  depVariable="Lean.Mass")
plotResidualPredicted(result)
```

| | |
|--------|------------------------|
| pvalue | <i>Method "pvalue"</i> |
|--------|------------------------|

Description

Method pvalue returns p-value that was calculate by RR or FE framework.

Methods

```
signature(obj = "hctestPhenStat")
```

| | |
|----------------|--------------------------------|
| qqplotGenotype | <i>Method "qqplotGenotype"</i> |
|----------------|--------------------------------|

Description

Graph function for the Mixed Model framework's results. Creates a Q-Q plot of residuals for each genotype.

Usage

```
qqplotGenotype(phenTestResult, outputMessages=TRUE)
```

Arguments

- phenTestResult instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument
- outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* **7**(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#) and [PhenTestResult](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
result <- testDataset(test,
  depVariable="Lean.Mass")
qqplotGenotype(result)
```

qqplotRandomEffects *Method "qqplotRandomEffects"*

Description

Graph function for the Mixed Model framework's results. Creates a Q-Q plot of blups (best linear unbiased predictions).

Usage

```
qqplotRandomEffects(phenTestResult, outputMessages=TRUE)
```

Arguments

- phenTestResult instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument
- outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#) and [PhenTestResult](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
                 testGenotype="Sparc/Sparc")
result <- testDataset(test,
                      depVariable="Lean.Mass")
qqplotRandomEffects(result)
```

qqplotRotatedResiduals

Method "qqplotRotatedResiduals"

Description

Graph function for the Mixed Model framework's results. Creates a Q-Q plot of rotated residuals.

Usage

```
qqplotRotatedResiduals(phenTestResult, outputMessages=TRUE)
```

Arguments

`phenTestResult` instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument

`outputMessages` flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- Houseman, E. A., Ryan, L. M., Coull, B. A. (2004): Cholesky residuals for assessing normal errors in a linear model with correlated outcomes. *Journal of the American Statistical Association* 99:466: pg 383-394. Doi 10.1198
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#) and [PhenTestResult](#)

Examples

```
file <- system.file("extdata", "test2.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  dataset.colname.weight="Weight.Value",
  testGenotype="Arid4a/Arid4a",
  hemiGenotype="Arid4a/+")
result <- testDataset(test,
  depVariable="C1")
qqplotRotatedResiduals(result)
```

| | |
|-----------------|---------------------------------|
| recommendMethod | <i>Method "recommendMethod"</i> |
|-----------------|---------------------------------|

Description

Checks the dependent variable and dataset to make choose the appropriate statistical method. Returns the method or the list of methods that are appropriate for statistical analysis.

Usage

```
recommendMethod(phenList=NULL, depVariable=NULL, outputMessages=TRUE)
```

Arguments

| | |
|----------------|---|
| phenList | instance of the PhenList class; mandatory argument |
| depVariable | a character string defining the dependent variable of interest; mandatory argument |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE |

Value

Returns the method or the list of methods that are appropriate for statistical analysis.

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
                 testGenotype="Sparc/Sparc")
recommendMethod(test, "Lean.Mass")
```

| | |
|-------------|-----------------------------|
| refGenotype | <i>Method "refGenotype"</i> |
|-------------|-----------------------------|

Description

Method refGenotype returns reference genotype

Methods

```
signature(obj = "PhenList")
signature(obj = "PhenTestResult")
```

| | |
|--------|------------------------|
| RRTest | <i>Method "RRTest"</i> |
|--------|------------------------|

Description

This is an internal function run within RR framework. It performs Reference Ranges Plus test and after that Fisher Exact test on calculated count matrices. As an internal function, it doesn't include extensive error testing of inputs. Please use cautiously if calling directly.

Works with [PhenList](#) object created by [PhenList](#) function.

Usage

```
RRTest(phenList, depVariable, outputMessages=TRUE, naturalVariation=95, controlPointsThreshold=60)
```

Arguments

| | |
|------------------------|---|
| phenList | instance of the PhenList class; mandatory argument |
| depVariable | a character string defining the dependent variable of interest; mandatory argument |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE |
| naturalVariation | number defining the natural variation range in percents for normal values; default value 95 |
| controlPointsThreshold | number defining how many control points is needed to perform RR plus method; default value 60 |

Value

Returns results stored in instance of the [PhenTestResult](#) class

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#) and [testDataset](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
                 testGenotype="Sparc/Sparc")
# "RRTest" function is called from "testDataset" function
result <- testDataset(test,
                     depVariable="Lean.Mass",
                     method="RR")
# RR test results can be printed out using function "summaryOutput"
summaryOutput(result)
```

scatterplotGenotypeWeight

Method "scatterplotGenotypeWeight"

Description

Graph function for the phenotypic dataset. Creates a scatter plot body weight versus dependent variable.

Both a regression line and a loess line (locally weighted line) is fitted for each genotype.

Usage

```
scatterplotGenotypeWeight(phenList, depVariable=NULL, graphingName=NULL, outputMessages=TRUE)
```

Arguments

| | |
|----------------|---|
| phenList | instance of the PhenList class; mandatory argument |
| depVariable | a character string defining the dependent variable of interest; mandatory argument |
| graphingName | a character string defining the name to be used on the graph for the dependent variable; mandatory argument |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE |

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
scatterplotGenotypeWeight(test,
  depVariable="Bone.Mineral.Content",
  graphingName="BMC" )
```

```
file <- system.file("extdata", "test4.csv", package="PhenStat")
test_1sex <- PhenList(dataset=read.csv(file),
  testGenotype="Mysm1/+")
scatterplotGenotypeWeight(test_1sex,
  depVariable="Lean.Mass",
  graphingName="Lean Mass")
```

scatterplotGenotypeWeightResult

Method "scatterplotGenotypeWeightResult"

Description

Graph function for the phenotypic dataset. Creates a scatter plot body weight versus dependent variable. It is based on PhenTestResult object. Both a regression line and a loess line (locally weighted line) is fitted for each genotype.

Usage

```
scatterplotGenotypeWeightResult(phenTestResult, graphingName=NULL, outputMessages=TRUE)
```

Arguments

phenTestResult instance of the [PhenTestResult](#) class; mandatory argument

graphingName a character string defining the name to be used on the graph for the dependent variable; mandatory argument

outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```

file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
result <- testDataset(test,
  depVariable="Lean.Mass")
scatterplotGenotypeWeightResult(result,
  graphingName="BMC" )
file <- system.file("extdata", "test4.csv", package="PhenStat")
test_1sex <- PhenList(dataset=read.csv(file),
  testGenotype="Mysm1/+")
result_1sex <- testDataset(test_1sex,
  depVariable="Lean.Mass")
scatterplotGenotypeWeightResult(result_1sex,
  graphingName="Lean Mass")

```

scatterplotSexGenotypeBatch

Method "scatterplotSexGenotypeBatch"

Description

Graph function for the phenotypic dataset. Creates a scatterplot split by sex, genotype and batch. refGenotype data points are shown in black and the testGenotype data points are shown in red.

Note: the batches are not ordered with time but allow assessment of how the testGenotype data lie relative to the variation within the refGenotype data.

Usage

```
scatterplotSexGenotypeBatch(phenList,depVariable=NULL,graphingName=NULL,outputMessages=TRUE)
```

Arguments

| | |
|----------------|---|
| phenList | instance of the PhenList class; mandatory argument |
| depVariable | a character string defining the dependent variable of interest; mandatory argument |
| graphingName | a character string defining the name to be used on the graph for the dependent variable; mandatory argument |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE |

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
# box plot for dataset with two sexes: males and females
scatterplotSexGenotypeBatch(test,
  depVariable="Bone.Mineral.Content",
  graphingName="BMC" )

file <- system.file("extdata", "test4.csv", package="PhenStat")
test_1sex <- PhenList(dataset=read.csv(file),
  testGenotype="Mysm1/+")
# box plot for females only dataset
scatterplotSexGenotypeBatch(test_1sex, depVariable="Lean.Mass",
  graphingName="Lean Mass")
```

scatterplotSexGenotypeBatchResult

Method "scatterplotSexGenotypeBatchResult"

Description

Graph function for the phenotypic dataset. Creates a scatterplot split by sex, genotype and batch. refGenotype data points are shown in black and the testGenotype data points are shown in red. It is based on PhenTestResult object.

Note: the batches are not ordered with time but allow assessment of how the testGenotype data lie relative to the variation within the refGenotype data.

Usage

```
scatterplotSexGenotypeBatchResult(phenTestResult, graphingName=NULL, outputMessages=TRUE)
```

Arguments

- phenTestResult instance of the [PhenTestResult](#) class; mandatory argument
- graphingName a character string defining the name to be used on the graph for the dependent variable; mandatory argument
- outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
result <- testDataset(test,
  depVariable="Lean.Mass")
# box plot for dataset with two sexes: males and females
scatterplotSexGenotypeBatchResult(result,
  graphingName="BMC" )

file <- system.file("extdata", "test4.csv", package="PhenStat")
test_1sex <- PhenList(dataset=read.csv(file),
  testGenotype="Mysm1/+")
result_1sex <- testDataset(test_1sex,
  depVariable="Lean.Mass")
# box plot for females only dataset
scatterplotSexGenotypeBatchResult(result_1sex,
  graphingName="Lean Mass")
```

| | |
|----------|--------------------------|
| setBatch | <i>Method "setBatch"</i> |
|----------|--------------------------|

Description

Method setBatch sets batch column in the dataset

Methods

signature(obj = "PhenList")

| | |
|-------------|-----------------------------|
| setGenotype | <i>Method "setGenotype"</i> |
|-------------|-----------------------------|

Description

Method setGenotype sets genotype column in the dataset

Methods

signature(obj = "PhenList")

| | |
|-----------------|---------------------------------|
| setMissingValue | <i>Method "setMissingValue"</i> |
|-----------------|---------------------------------|

Description

Method setMissingValue sets missing value in the dataset

Methods

signature(obj = "PhenList")

| | |
|--------|------------------------|
| setSex | <i>Method "setSex"</i> |
|--------|------------------------|

Description

Method setSex sets sex column in the dataset

Methods

signature(obj = "PhenList")

| | |
|-----------|---------------------------|
| setWeight | <i>Method "setWeight"</i> |
|-----------|---------------------------|

Description

Method setWeight sets weight column in the dataset

Methods

signature(obj = "PhenList")

| | |
|--------------|------------------------------|
| startLRModel | <i>Method "startLRModel"</i> |
|--------------|------------------------------|

Description

This is an internal function run within LR framework. It completes the testing stage of which effects are significant. As an internal function, it doesn't include extensive error testing of inputs. Please use cautiously if calling directly.

It creates start model and modify it after testing of different hypothesis.

The tested effects are:

-batch effect (TRUE if batch variation is significant, FALSE if not), though it is never used in final LR model;

-interaction effect (TRUE if genotype by sex interaction is significant),

-sex effect (TRUE if sex is significant),

-weight effect and variance effect are not tested and used in LR model.

Usage

```
startLRModel(phenList, depVariable, outputMessages=TRUE, pThreshold=0.05)
```

Arguments

| | |
|----------------|--|
| phenList | instance of the PhenList class; mandatory argument |
| depVariable | a character string defining the dependent variable of interest; mandatory argument |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages ; default value TRUE |
| pThreshold | a numerical value for the p-value threshold used to determine which fixed effects to keep in the model, default value 0.05 |

Value

Returns results stored in instance of the [PhenTestResult](#) class

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```
file <- system.file("extdata", "testLR.csv", package="PhenStat")
testLR <- PhenList(dataset=read.csv(file),
                  testGenotype="Mock")
testLR2 <- LRDataset(testLR, "V2")

# when "testDataset" function's argument "callAll" is set to FALSE
# only "startLRModel" function is called - the first step of LR framework
resultLR <- testDataset(testLR2,
                       depVariable="V2",
                       callAll=FALSE,
                       method="LR")
# print out formula that has been created
analysisResults(resultLR)$model.formula.genotype
# print out batch effect's significance
analysisResults(resultLR)$model.effect.batch
```

startModel

Method "startModel"

Description

This is an internal function run within MM framework. It completes the testing stage of which effects are significant. As an internal function, it doesn't include extensive error testing of inputs. Please use cautiously if calling directly.

It creates start model and modify it after testing of different hypothesis (the model fixed effects).

The model random effects are:

-batch effect (TRUE if batch variation is significant, FALSE if not)

The model fixed effects are:

- variance effect (TRUE if residual variances for genotype groups are homogeneous and FALSE if they are heterogeneous),
- interaction effect (TRUE if genotype by sex interaction is significant),
- sex effect (TRUE if sex is significant),
- weight effect (TRUE if weight is significant).

If user would like to assign other TRUE/FALSE values to the fixed effects of the model then he or she has to define keepList argument which is vector of TRUE/FALSE values.

If user has defined model fixed effects (keepList argument) then function prints out calculated and user defined effects (only when outputMessages argument is set to TRUE), checks user defined effects for consistency (for instance, if there are no "Weight" column in the dataset then weight effect can't be assigned to TRUE, etc.) and modifies start model according to user defined effects.

As the result PhenTestResult object that contains calculated or user defined model fixed effects and MM start model is created.

Usage

```
startModel(phenList, depVariable,
           equation="withWeight", outputMessages=TRUE,
           pThreshold=0.05, keepList=NULL)
```

Arguments

| | |
|----------------|---|
| phenList | instance of the PhenList class; mandatory argument |
| depVariable | a character string defining the dependent variable of interest; mandatory argument |
| equation | a character string defining the equation to use. Possible values "withWeight" (default),"withoutWeight" |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages ; default value TRUE |
| pThreshold | a numerical value for the p-value threshold used to determine which fixed effects to keep in the model, default value 0.05 |
| keepList | a logical vector defining the significance of different model effects: keep_batch, keep_equalvar, keep_weight, keep_sex, keep_interaction; default value NULL |

Value

Returns results stored in instance of the [PhenTestResult](#) class

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
# when "testDataset" function's argument "callAll" is set to FALSE
# only "startModel" function is called - the first step of MM framework
result <- testDataset(test,
  depVariable="Lean.Mass",
  callAll=FALSE)
# print out formula that has been created
analysisResults(result)$model.formula.genotype
# print out batch effect's significance
analysisResults(result)$model.effect.batch
# change the model
result <- testDataset(test,
  depVariable="Lean.Mass",
  equation="withWeight",
  callAll=FALSE)
# print out new formula
analysisResults(result)$model.formula.genotype
```

startTFModel

Method "startTFModel"

Description

This is an internal function run within TF framework. It completes the testing stage of which effects are significant. As an internal function, it doesn't include extensive error testing of inputs. Please use cautiously if calling directly.

It creates start model and modify it after testing of different hypothesis.

The tested fixed effects are:

- batch effect (TRUE if batch variation is significant, FALSE if not),
- variance effect (TRUE if residual variances for genotype groups are homogeneous and FALSE if they are heterogeneous),
- interaction effect (TRUE if genotype by sex interaction is significant),

- sex effect (TRUE if sex is significant),
- weight effect (TRUE if weight is significant).

Usage

```
startTFModel(phenList, depVariable,  
             equation="withWeight", outputMessages=TRUE,  
             pThreshold=0.05, keepList=NULL)
```

Arguments

| | |
|----------------|---|
| phenList | instance of the PhenList class; mandatory argument |
| depVariable | a character string defining the dependent variable of interest; mandatory argument |
| equation | a character string defining the equation to use. Possible values "withWeight" (default),"withoutWeight" |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages ; default value TRUE |
| pThreshold | a numerical value for the p-value threshold used to determine which fixed effects to keep in the model, default value 0.05 |
| keepList | a logical vector defining the significance of different model effects: keep_batch, keep_equalvar, keep_weight, keep_sex, keep_interaction; default value NULL |

Value

Returns results stored in instance of the [PhenTestResult](#) class

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```

file <- system.file("extdata", "test7_TFE.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
                testGenotype="het",
                refGenotype = "WT",
                dataset.colname.sex="sex",
                dataset.colname.genotype="Genotype",
                dataset.values.female="f",
                dataset.values.male= "m",
                dataset.colname.weight="body.weight",
                dataset.colname.batch="Date_of_procedure_start")

test_TF <- TFDataset(test,depVariable="Cholesterol")

# when "testDataset" function's argument "callAll" is set to FALSE
# only "startTFModel" function is called - the first step of TFE framework
result <- testDataset(test_TF,
                    depVariable="Cholesterol",
                    callAll=FALSE,
                    method="TF")
# print out formula that has been created
analysisResults(result)$model.formula.genotype
# print out batch effect's significance
analysisResults(result)$model.effect.batch

```

subsetText

*Method "subsetText"***Description**

Method subsetText returns full name of subset that was analysed by RR or FE framework: Males only, Females only, All.

Methods

```
signature(obj = "htestPhenStat")
```

summaryOutput

*Method "summaryOutput"***Description**

Wrapper for the model fitting results. Returns model fitting and testing results in a user friendly format.

Usage

```
summaryOutput(phenTestResult, phenotypeThreshold = 0.01)
```

Arguments

`phenTestResult` instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument

`phenotypeThreshold`
a numerical value defining the threshold to use in `classificationTag`; default value 0.01

Value

Returns model fitting results in a text format for the screen

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#)

Examples

```
# Mixed Model framework
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
result <- testDataset(test,
  depVariable="Lean.Mass")
summaryOutput(result)

# Fishe Exact Test framework
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test2 <- PhenList(dataset=read.csv(file),
  testGenotype="Aff3/Aff3")
result2 <- testDataset(test2,
  depVariable="Thoracic.Processes",
  method="FE")
summaryOutput(result2)
```

| | |
|-------------|-----------------------------|
| testDataset | <i>Method "testDataset"</i> |
|-------------|-----------------------------|

Description

Statistical analysis manager function in PhenStat package.

Firstly, it performs the checks for dependent variable in the dataset. Some checks are generic, some depends on selected statistical framework/method.

Secondly, if checks are passed it runs the stages of selected framework to analyse dependent variable.

For instance, runs startModel and finalModel for the MM framework if the argument "callAll" is set to TRUE. If framework contains only one stage like in Fisher Exact Test case then runs that one stage regardless "callAll" value.

Usage

```
testDataset(phenList=NULL, depVariable=NULL,
            equation="withWeight", outputMessages=TRUE,
            pThreshold=0.05, method="MM", callAll=TRUE, keepList=NULL, dataPointsThreshold=4,
            RR_naturalVariation=95,RR_controlPointsThreshold=60,transformValues=FALSE,useUnfiltered=F)
```

Arguments

| | |
|---------------------|---|
| phenList | instance of the PhenList class; mandatory argument |
| depVariable | a character string defining the dependent variable of interest; mandatory argument |
| equation | a character string defining the equation to use. Possible values "withWeight" (default), "withoutWeight" |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE |
| pThreshold | a numerical value for the p-value threshold used to determine which fixed effects to keep in the model, default value 0.05 |
| method | a character string ("MM", "FE" or "RR") defining the method to use for model building; default value "MM" for mixed model |
| callAll | flag: "FALSE" value to run only the first stage of the selected framework; "TRUE" value (default) to run all stages of framework one after another |
| keepList | a logical vector defining the significance of different model effects: keep_batch, keep_equalvar, keep_weight, keep_sex, keep_interaction; default value NULL |
| dataPointsThreshold | threshold for the number of data points in the MM framework; default value is 4 ; minimal value is 2 |
| RR_naturalVariation | threshold for the variation ranges in the RR framework; default value is 95 ; minimal value is 60 |

RR_controlPointsThreshold
 threshold for the number of control data points in the RR framework ; default value is 60; minimal value is 40

transformValues
 flag: "FALSE" value to suppress transformation; "TRUE" value to perform transformation if needed; default value FALSE

useUnfiltered
 flag: "FALSE" value to use filtered dataset; "TRUE" value to use unfiltered dataset; default value FALSE

Value

Returns results stored in instance of the [PhenTestResult](#) class

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```
# Mixed Model framework
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
result <- testDataset(test,
  depVariable="Lean.Mass")
# print out formula that has been created
analysisResults(result)$model.formula.genotype
summaryOutput(result)

# Mixed Model framework with user defined effects
user_defined_effects <- c(keep_batch=TRUE,
  keep_equalvar=TRUE,
  keep_weight=TRUE,
  keep_sex=TRUE,
  keep_interaction=TRUE)
result3 <- testDataset(test,
  depVariable="Lean.Mass",
  keepList=user_defined_effects)
# print out formula that has been created
analysisResults(result3)$model.formula.genotype
```

```
summaryOutput(result3)

# Fisher Exact Test framework
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test2 <- PhenList(dataset=read.csv(file),
  testGenotype="Aff3/Aff3")
result2 <- testDataset(test2,
  depVariable="Thoracic.Processes",
  method="FE")
summaryOutput(result2)
```

| | |
|------------------|----------------------------------|
| testFinalLRModel | <i>Method "testFinalLRModel"</i> |
|------------------|----------------------------------|

Description

Performs diagnostic tests for Logistic Regression model quality of fit. There are no arguments checks assuming that function is called internally from the "finalLRModel" function. Otherwise should be used with precaution.

Usage

```
testFinalLRModel(phenTestResult)
```

Arguments

phenTestResult instance of the [PhenTestResult](#) class that comes from the function testDataset ; mandatory argument

Value

Returns a vector with model fitting results

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#)

Examples

```
file <- system.file("extdata", "testLR.csv", package="PhenStat")
testLR <- PhenList(dataset=read.csv(file),
  testGenotype="Mock")
testLR2 <- LRDataset(testLR, "V2")
resultLR <- testDataset(testLR2,
  depVariable="V2",
  method="LR")
testFinalLRModel(resultLR)
```

| | |
|----------------|--------------------------------|
| testFinalModel | <i>Method "testFinalModel"</i> |
|----------------|--------------------------------|

Description

Performs diagnostic tests for Mixed Model quality of fit. There are no arguments checks assuming that function is called internally from the "finalModel" function. Otherwise should be used with precaution.

Usage

```
testFinalModel(phenTestResult)
```

Arguments

phenTestResult instance of the [PhenTestResult](#) class that comes from the function testDataset ; mandatory argument

Value

Returns a vector with model fitting results

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
result <- testDataset(test,
  depVariable="Lean.Mass")
testFinalModel(result)
```

| | |
|--------------|------------------------------|
| testGenotype | <i>Method "testGenotype"</i> |
|--------------|------------------------------|

Description

Method testGenotype returns test genotype

Methods

```
signature(obj = "PhenList")
signature(obj = "PhenTestResult")
```

| | |
|-----------|---------------------------|
| TFDataset | <i>Method "TFDataset"</i> |
|-----------|---------------------------|

Description

Removes of all non-concurrent batches from the dataset. Returns dataset suitable for TF framework or original dataset if data removal was not successful.

Usage

```
TFDataset(phenList, depVariable, outputMessages=TRUE, forDecisionTree = FALSE)
```

Arguments

| | |
|-----------------|---|
| phenList | instance of the PhenList class; mandatory argument |
| depVariable | a character string defining the dependent variable of interest; mandatory argument |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE |
| forDecisionTree | flag: "FALSE" value for normal procedure; "TRUE" value to indicate that is called form decisionTree function; default value FALSE |

Value

Returns dataset suitable for TF framework or original dataset if data removal was not successful.

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenList](#)

Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
                 testGenotype="Sparc/Sparc")
test2 <- TFDataset(test, "Lean.Mass")
```

| | |
|----------------|--------------------------------|
| transformation | <i>Method "transformation"</i> |
|----------------|--------------------------------|

Description

Method transformation returns transformation values: lamda=value, scaleShift=value

Methods

```
signature(obj = "PhenTestResult")
```

| | |
|--------------------|------------------------------------|
| transformationJSON | <i>Method "transformationJSON"</i> |
|--------------------|------------------------------------|

Description

Method transformationJSON returns transformation values as JSON string

Methods

```
signature(obj = "PhenTestResult")
```

| | |
|--------------------|------------------------------------|
| transformationText | <i>Method "transformationText"</i> |
|--------------------|------------------------------------|

Description

Method transformationText returns transformation values as one string

Methods

```
signature(obj = "PhenTestResult")
```

| | |
|--------------|------------------------------|
| vectorOutput | <i>Method "vectorOutput"</i> |
|--------------|------------------------------|

Description

Wrapper for the model fitting results. Returns model fitting and testing results in a vector format. Assumes that modelling results are stored in the [PhenTestResult](#) object (output from function [testDataset](#)).

Usage

```
vectorOutput(phenTestResult, phenotypeThreshold = 0.01)
```

Arguments

phenTestResult instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument

phenotypeThreshold
a numerical value defining the threshold to use in classificationTag; default value 0.01

Value

Returns a vector with model fitting results: model output summary and other values

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also[PhenTestResult](#)**Examples**

```
# Mixed Model framework
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Sparc/Sparc")
result <- testDataset(test,
  depVariable="Lean.Mass")
vectorOutput(result)

# Fishe Exact Test framework
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test2 <- PhenList(dataset=read.csv(file),
  testGenotype="Aff3/Aff3")
result2 <- testDataset(test2,
  depVariable="Thoracic.Processes",
  method="FE")
vectorOutput(result2)
```

vectorOutputMatrices *Method "vectorOutputMatrices"*

Description

Returns count matrices from Fisher Exact Test framework in a vector form.

Note: Maximal supported number of dependent variable levels is 10.

Usage

```
vectorOutputMatrices(phenTestResult, outputMessages=TRUE)
```

Arguments

`phenTestResult` instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument

`outputMessages` flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

Value

Returns a vector with count values.

Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

See Also

[PhenTestResult](#)

Examples

```
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file),
  testGenotype="Aff3/Aff3")
result <- testDataset(test,
  depVariable="Thoracic.Processes",
  method="FE")
vectorOutputMatrices(result)
```

weightIn

Method "weightIn"

Description

Returns TRUE if the weight is in the dataset, FALSE otherwise

Methods

signature(obj = "PhenList")

signature(obj = "PhenTestResult")

Index

- *Topic **other possible keyword(s)**
 - weightIn, [69](#)
- *Topic **classes**
 - PhenList-class, [34](#)
 - PhenTestResult-class, [38](#)
- *Topic **methods**
 - analysedDataset, [3](#)
 - analysedDatasetPhenList, [3](#)
 - analysedSubset, [4](#)
 - analysisResults, [4](#)
 - batchIn, [4](#)
 - comparison, [15](#)
 - dataset, [15](#)
 - getColumn, [22](#)
 - getColumnBatchAdjusted, [22](#)
 - getColumnView, [22](#)
 - getColumnWeightBatchAdjusted, [23](#)
 - getCountMatrices, [23](#)
 - getDataset, [23](#)
 - getGenotypeEffect, [23](#)
 - getMatrix, [24](#)
 - getPercentageMatrix, [24](#)
 - getStat, [24](#)
 - getVariable, [24](#)
 - getVariables, [25](#)
 - hemiGenotype, [25](#)
 - matrixCount, [27](#)
 - method, [28](#)
 - methodText, [28](#)
 - multipleBatches, [28](#)
 - noSexes, [28](#)
 - parameters, [29](#)
 - PhenList-class, [34](#)
 - PhenTestResult-class, [38](#)
 - pvalue, [42](#)
 - refGenotype, [46](#)
 - setBatch, [53](#)
 - setGenotype, [53](#)
 - setMissingValue, [53](#)
 - setSex, [53](#)
 - setWeight, [54](#)
 - subsetText, [59](#)
 - testGenotype, [65](#)
 - transformation, [66](#)
 - transformationJSON, [66](#)
 - transformationText, [67](#)
 - weightIn, [69](#)
- analysedDataset, [3](#)
- analysedDataset,PhenTestResult-method (PhenTestResult-class), [38](#)
- analysedDatasetPhenList, [3](#)
- analysedSubset, [4](#)
- analysisResults, [4](#)
- analysisResults,PhenTestResult-method (PhenTestResult-class), [38](#)
- batchIn, [4](#)
- batchIn,PhenList-method (batchIn), [4](#)
- batchIn,PhenTestResult-method (batchIn), [4](#)
- batchIn-methods (batchIn), [4](#)
- boxplotResidualBatch, [5](#)
- boxplotSexGenotype, [6](#)
- boxplotSexGenotypeBatch, [7](#)
- boxplotSexGenotypeBatchAdjusted, [8](#)
- boxplotSexGenotypeResult, [9](#)
- boxplotSexGenotypeWeightBatchAdjusted, [10](#)
- categoricalBarplot, [11](#)
- checkDataset, [12](#), [12](#)
- classificationTag, [14](#)
- comparison, [15](#)
- dataset, [15](#)
- dataset,PhenList-method (PhenList-class), [34](#)

- finalLRModel, 16
- finalModel, 17
- finalTFModel, 18
- FisherExactTest, 20

- generateGraphs, 21
- getColumn, 22
- getColumn,PhenList,character-method
(PhenList-class), 34
- getColumnBatchAdjusted, 22
- getColumnBatchAdjusted,PhenList,character-method
(PhenList-class), 34
- getColumnView, 22
- getColumnWeightBatchAdjusted, 23
- getColumnWeightBatchAdjusted,PhenList,character-method
(PhenList-class), 34
- getCountMatrices, 23
- getCountMatrices,PhenTestResult-method
(PhenTestResult-class), 38
- getDataset, 23
- getGenotypeEffect, 23
- getGenotypeEffect,PhenTestResult-method
(PhenTestResult-class), 38
- getMatrix, 24
- getPercentageMatrix, 24
- getStat, 24
- getStat,PhenList-method
(PhenList-class), 34
- getVariable, 24
- getVariable,PhenTestResult-method
(PhenTestResult-class), 38
- getVariables, 25
- getVariables,PhenList-method
(PhenList-class), 34

- hemiGenotype, 25
- hemiGenotype,PhenList-method
(PhenList-class), 34

- JSONOutput, 25

- LRDataset, 26

- matrixCount, 27
- method, 28
- method,PhenTestResult-method
(PhenTestResult-class), 38
- methodText, 28
- methodText,PhenTestResult-method
(PhenTestResult-class), 38

- multipleBatches, 28
- multipleBatches,PhenList-method
(PhenList-class), 34

- noSexes, 28
- noSexes,PhenList-method (noSexes), 28
- noSexes,PhenTestResult-method
(noSexes), 28

- parameters, 29
- parameters,PhenTestResult-method
(PhenTestResult-class), 38
- parserOutputSummary, 29
- parserOutputSummaryLR, 30
- parserOutputTFSummary, 31
- PhenList, 5–13, 20, 27, 32, 32, 33, 34, 36,
42–52, 54–58, 61, 62, 65, 66
- PhenList-class, 34
- PhenTestResult, 5, 9, 11, 13–22, 25, 26,
29–31, 36, 36, 37, 38, 41–45, 47, 49,
52, 55, 56, 58, 60, 62–64, 67–69
- PhenTestResult-class, 38
- plotResidualPredicted, 41
- pvalue, 42

- qqplotGenotype, 42
- qqplotRandomEffects, 43
- qqplotRotatedResiduals, 44

- recommendMethod, 45
- refGenotype, 46
- refGenotype,PhenList-method
(PhenList-class), 34
- refGenotype,PhenTestResult-method
(PhenTestResult-class), 38
- RRTest, 46

- scatterplotGenotypeWeight, 48
- scatterplotGenotypeWeightResult, 49
- scatterplotSexGenotypeBatch, 50
- scatterplotSexGenotypeBatchResult, 51
- setBatch, 53
- setBatch,PhenList,character-method
(PhenList-class), 34
- setGenotype, 53
- setGenotype,PhenList,character-method
(PhenList-class), 34
- setMissingValue, 53
- setMissingValue,PhenList,character-method
(PhenList-class), 34

setSex, [53](#)
setSex,PhenList,character-method
(PhenList-class), [34](#)
setWeight, [54](#)
setWeight,PhenList,character-method
(PhenList-class), [34](#)
show,PhenTestResult-method
(PhenTestResult-class), [38](#)
startLRModel, [16](#), [54](#)
startModel, [17](#), [55](#)
startTFModel, [18](#), [57](#)
subsetText, [59](#)
summaryOutput, [59](#)

testDataset, [5](#), [14](#), [16–19](#), [21](#), [25](#), [38](#), [41](#), [43](#),
[44](#), [47](#), [60](#), [61](#), [67](#), [68](#)
testFinalLRModel, [63](#)
testFinalModel, [64](#)
testGenotype, [65](#)
testGenotype,PhenList-method
(PhenList-class), [34](#)
testGenotype,PhenTestResult-method
(PhenTestResult-class), [38](#)
TFDataset, [65](#)
transformation, [66](#)
transformationJSON, [66](#)
transformationText, [67](#)
transformationText,PhenTestResult-method
(PhenTestResult-class), [38](#)

vectorOutput, [67](#)
vectorOutputMatrices, [68](#)

weightIn, [69](#)
weightIn,PhenList-method (weightIn), [69](#)
weightIn,PhenTestResult-method
(weightIn), [69](#)
weightIn-methods (weightIn), [69](#)