

Package ‘BioCor’

October 15, 2018

Title Functional similarities

Version 1.4.0

Author Lluís Revilla Sancho <lluis.revilla@gmail.com>

Maintainer Lluís Revilla Sancho <lluis.revilla@gmail.com>

Description Calculates functional similarities based on the pathways described on KEGG and REACTOME or in gene sets. These similarities can be calculated for pathways or gene sets, genes, or clusters and combined with other similarities. They can be used to improve networks, gene selection, testing relationships...

Depends R (>= 3.4.0)

License GPL-3 + file LICENSE

Encoding UTF-8

LazyData true

biocViews StatisticalMethod, Clustering, GeneExpression, Network, Pathways, NetworkEnrichment, SystemsBiology

Imports BiocParallel, Matrix, GSEABase

Suggests reactome.db, org.Hs.eg.db, WGCNA, methods, GOSemSim, testthat, knitr, rmarkdown, BiocStyle, airway, DESeq2, boot, targetscan.Hs.eg.db, Hmisc

BugReports <https://github.com/llrs/BioCor/issues>

URL <https://github.com/llrs/BioCor/>

VignetteBuilder knitr

RoxygenNote 6.0.1

git_url <https://git.bioconductor.org/packages/BioCor>

git_branch RELEASE_3_7

git_last_commit dc2ee5f

git_last_commit_date 2018-04-30

Date/Publication 2018-10-15

R topics documented:

BioCor-package	2
addSimilarities	3
AintoB	4
clusterGeneSim	5
clusterSim	6
combinadic	7
combineScores	8
combineSources	10
conversions	10
diceSim	11
duplicateIndices	12
geneSim	13
mclusterGeneSim	14
mclusterSim	15
mgeneSim	16
mpathSim	17
pathSim	19
removeDup	20
seq2mat	21
similarities	22
weighted	23
Index	25

 BioCor-package

BioCor: A package to calculate functional similarities

Description

Calculates a functional similarity measure between gene identifiers based on the pathways described on KEGG and REACTOME.

Important functions

[pathSim](#) Calculates the similarity between two pathways

[geneSim](#) Calculates the similarity (based on pathSim) between two genes

[clusterSim](#) Calculates the similarity between two clusters of genes by joining pathways of each gene.

[clusterGeneSim](#) Calculates the similarity between two clusters of genes by comparing the similarity between the genes of a cluster

[similarities](#) Allows to combine the value of matrices of similarities

[conversions](#) Two functions to convert similarity measures

[weighted](#) Functions provided to combine similarities

addSimilarities	<i>Additive integration of similarities</i>
-----------------	---

Description

Function that use the previously calculated similarities into a single similarity matrix.

Usage

```
addSimilarities(x, bio_mat, weights = c(0.5, 0.18, 0.1, 0.22))
```

Arguments

x	A matrix with the similarity of expression
bio_mat	A list of matrices of the same dimension as x.
weights	A numeric vector of weight to multiply each similarity

Details

The total weight can't be higher than 1 to prevent values above 1 but can be below 1. It uses `weighted.sum` with `abs = TRUE` internally.

Value

A square matrix of the same dimensions as the input matrices.

Author(s)

Lluís Revilla

See Also

[similarities](#), [weighted](#).

Examples

```
set.seed(100)
a <- seq2mat(LETTERS[1:5], rnorm(10))
b <- seq2mat(LETTERS[1:5], seq(from = 0.1, to = 1, by = 0.1))
sim <- list(b)
addSimilarities(a, sim, c(0.5, 0.5))
```

AintoB*Insert a matrix into another*

Description

Insert values from a matrix into another matrix based on the rownames and colnames replacing the values.

Usage

```
AintoB(A, B)
```

Arguments

A	A matrix to be inserted.
B	A matrix to insert in.

Details

If all the genes with pathway information are already calculated but you would like to use more genes when performing analysis. insert the once you have calculated on the matrix of genes.

Value

A matrix with the values of A in the matrix B.

Author(s)

Lluís Revilla

Examples

```
B <- matrix(ncol = 10, nrow = 10,
            dimnames = list(letters[1:10], letters[1:10]))
A <- matrix(c(1:15), byrow=TRUE, nrow=5,
            dimnames = list(letters[1:5], letters[1:3]))
AintoB(A, B)

# Mixed orders
colnames(A) <- c("c", "h", "e")
rownames(A) <- c("b", "a", "f", "c", "j")
AintoB(A, B)

# Missing columns or rows
colnames(A) <- c("d", "f", "k")
AintoB(A, B)
```

clusterGeneSim	<i>Similarity score between clusters of genes based on genes similarity</i>
----------------	---

Description

Looks for the similarity between genes of a group and then between each group's genes.

Usage

```
clusterGeneSim(cluster1, cluster2, info, method = c("max", "rcmax.avg"), ...)  
  
## S4 method for signature 'character,character,GeneSetCollection'  
clusterGeneSim(cluster1,  
  cluster2, info, method = c("max", "rcmax.avg"), ...)
```

Arguments

cluster1	A vector with genes.
cluster2	A vector with genes.
info	A list or a GeneSetCollection of genes and the pathways they are involved.
method	A vector with two or one argument to be passed to combineScores the first one is used to summarize the similarities of genes, the second one for clusters.
...	Other arguments passed to combineScores

Details

Differs with clusterSim that first each combination between genes is calculated, and with this values then the comparison between the two clusters is done. Thus applying combineScores twice, one at gene level and another one at cluster level.

Value

Returns a similarity score between the genes of the two clusters.

Methods (by class)

- cluster1 = character, cluster2 = character, info = GeneSetCollection: Calculates the gene similarities in a GeneSetCollection and combine them using [combineScoresPar](#)

Author(s)

Lluís Revilla

See Also

[mclusterGeneSim](#), [combineScores](#) and [clusterSim](#)

Examples

```

if (require("org.Hs.eg.db")) {
  #Extract the paths of all genes of org.Hs.eg.db from KEGG (last update in
  # data of June 31st 2011)
  genes.kegg <- as.list(org.Hs.egPATH)
  clusterGeneSim(c("18", "81", "10"), c("100", "10", "1"), genes.kegg)
  clusterGeneSim(c("18", "81", "10"), c("100", "10", "1"), genes.kegg,
                 c("avg", "avg"))
  clusterGeneSim(c("18", "81", "10"), c("100", "10", "1"), genes.kegg,
                 c("avg", "rcmax.avg"))
  (clus <- clusterGeneSim(c("18", "81", "10"), c("100", "10", "1"),
                        genes.kegg, "avg"))
  combineScores(clus, "rcmax.avg")
} else {
  warning('You need org.Hs.eg.db package for this example')
}

```

clusterSim	<i>Similarity score between clusters of genes based on pathways similarity</i>
------------	--

Description

Looks for the similarity between genes in groups

Usage

```
clusterSim(cluster1, cluster2, info, method = "max", ...)
```

```
## S4 method for signature 'character,character,GeneSetCollection'
clusterSim(cluster1, cluster2,
           info, method = "max", ...)
```

Arguments

cluster1, cluster2	A vector with genes.
info	A list or a GeneSetCollection of genes and the pathways they are involved.
method	one of c("avg", "max", "rcmax", "rcmax.avg", "BMA", "reciprocal"), see Details.
...	Other arguments passed to combineScores

Details

Once the pathways for each cluster are found they are combined using [combineScores](#).

Value

clusterSim returns a similarity score of the two clusters

Methods (by class)

- `cluster1 = character, cluster2 = character, info = GeneSetCollection`: Calculates all the similarities of the `GeneSetCollection` and combine them using [combineScoresPar](#)

Author(s)

Lluís Revilla

See Also

For a different approach see [clusterGeneSim](#), [combineScores](#) and [conversions](#)

Examples

```
if (require("org.Hs.eg.db")) {
  #Extract the paths of all genes of org.Hs.eg.db from KEGG (last update in
  # data of June 31st 2011)
  genes.kegg <- as.list(org.Hs.egPATH)
  clusterSim(c("9", "15", "10"), c("33", "19", "20"), genes.kegg)
  clusterSim(c("9", "15", "10"), c("33", "19", "20"), genes.kegg, NULL)
  clusterSim(c("9", "15", "10"), c("33", "19", "20"), genes.kegg, "avg")
} else {
  warning('You need org.Hs.eg.db package for this example')
}
```

combinadic

i-th combination of *n* elements taken from *r*

Description

Function similar to `combn` but for larger vectors. To avoid allocating a big vector with all the combinations each one can be computed with this function.

Usage

```
combinadic(n, r, i)
```

Arguments

<code>n</code>	Elements to extract the combination from
<code>r</code>	Number of elements per combination
<code>i</code>	<i>i</i> th combination

Value

The combination *i*th of the elements

Author(s)

Joshua Ulrich

References

[StackOverflow answer 4494469/2886003](#)

See Also

[combn](#)

Examples

```
#Output of all combinations
combn(LETTERS[1:5], 2)
# Output of the second combination
combinadic(LETTERS[1:5], 2, 2)
```

combineScores

Combining values

Description

Combine several similarities into one using several methods.

combineScoresPar performs multiple combineScores. It allows parallel computing using BiocParallel back-end.

Usage

```
combineScores(scores, method = c("max", "avg", "rcmax", "rcmax.avg", "BMA",
  "reciprocal"), round = FALSE, t = 0)

combineScoresPar(scores, method, subSets = NULL, BPPARAM = NULL, ...)
```

Arguments

scores	Matrix of scores to be combined
method	one of c("avg", "max", "rcmax", "rcmax.avg", "BMA", "reciprocal"), see Details.
round	Should the resulting value be rounded to the third digit?
t	Numeric value to filter scores below this value. Only used in the reciprocal method.
subSets	List of combinations as info in other functions.
BPPARAM	BiocParallel back-end parameters. By default (NULL) a for loop is used.
...	Other arguments passed to combineScores

Details

The input matrix can be a base matrix or a matrix from package Matrix. The methods return:

avg The average or mean value

max The max value

rcmax The max of the column means or row means

rcmax.avg The sum of the max values by rows and columns divided by the number of columns and rows

BMA The same as rcmax.avg

reciprocal The double of the sum of the reciprocal maximal similarities (above a threshold) divided by the number of elements. See equation 3 of the Tao *et al* 2007 article

Value

A numeric value as described in details.

Note

combineScores is a version of the function of the same name in package GOSemSim ([combineScores](#)) with optional rounding and some internal differences.

Author(s)

Lluís Revilla based on Guangchuang Yu

References

Ying Tao, Lee Sam, Jianrong Li, Carol Friedman, Yves A. Lussier; Information theory applied to the sparse gene ontology annotation network to predict novel gene function. *Bioinformatics* 2007; 23 (13): i529-i538. doi: 10.1093/bioinformatics/btm195

See Also

[register](#) in BiocParallel about the arguments accepted by BPPARAM

Examples

```
(d <- structure(c(0.4, 0.6, 0.222222222222222, 0.4, 0.4, 0, 0.25, 0.5,
  0.285714285714286), .Dim = c(3L, 3L),
  .Dimnames = list(c("a", "b", "c"), c("d", "e", "f"))))
e <- d
sapply(c("avg", "max", "rcmax", "rcmax.avg", "BMA", "reciprocal"),
  combineScores, scores = d)
d[1,2] <- NA
sapply(c("avg", "max", "rcmax", "rcmax.avg", "BMA", "reciprocal"),
  combineScores, scores = d)
colnames(e) <- rownames(e)
combineScoresPar(e, list(a= c("a", "b"), b = c("b", "c")),
  method = "max")
```

combineSources *Combine different sources of pathways*

Description

Given several sources of pathways with the same for the same id of the genes it merge them.

Usage

```
combineSources(...)
```

Arguments

... Lists of genes and their pathways.

Details

It assumes that the identifier of the genes are the same for both sources but if many aren't equal it issues a warning. Only unique pathways identifiers are returned.

Value

A single list with the pathways of each source on the same gene.

Examples

```
DB1 <- list(g1 = letters[6:8], g2 = letters[1:5], g3 = letters[4:7])
DB2 <- list(g1 = c("one", "two"), g2 = c("three", "four"),
           g3 = c("another", "two"))
combineSources(DB1, DB2)
combineSources(DB1, DB1)
DB3 <- list(g1 = c("one", "two"), g2 = c("three", "four"),
           g4 = c("five", "six", "seven"), g5 = c("another", "two"))
combineSources(DB1, DB3) # A warning is expected
```

conversions *Convert the similarities formats*

Description

Functions to convert the similarity coefficients between Jaccard and Dice. D2J is the opposite of J2D.

Usage

```
D2J(D)
```

```
J2D(J)
```

Arguments

D	Dice coefficient, as returned by diceSim , geneSim , clusterSim and clusterGeneSim
J	Jaccard coefficient

Value

A numeric value.

Author(s)

Lluís Revilla

Examples

```
D2J(0.5)
J2D(0.5)
D2J(J2D(0.5))
```

diceSim

Compare pathways

Description

Function to estimate how much two list of genes overlap by looking how much of the nodes are shared. Calculates the Dice similarity

Usage

```
diceSim(g1, g2)
```

Arguments

g1, g2 A character list with the names of the proteins in each pathway.

Details

It requires a vector of characters otherwise will return an NA.

Value

A score between 0 and 1 calculated as the double of the proteins shared by g1 and g2 divided by the number of genes in both groups.

Author(s)

Lluís Revilla

See Also

Used for [geneSim](#), see [conversions](#) help page to transform Dice score to Jaccard score.

Examples

```
genes.id2 <- c("52", "11342", "80895", "57654", "548953", "11586", "45985")
genes.id1 <- c("52", "11342", "80895", "57654", "58493", "1164", "1163",
"4150", "2130", "159")
diceSim(genes.id1, genes.id2)
diceSim(genes.id2, genes.id2)
```

duplicateIndices	<i>Finds the indices of the duplicated events of a vector</i>
------------------	---

Description

Finds the indices of duplicated elements in the vector given.

Usage

```
duplicateIndices(vec)
```

Arguments

vec Vector of identifiers presumably duplicated

Details

For each duplication it can return a list or if all the duplication events are of the same length it returns a matrix, where each column is duplicated.

Value

The format is determined by the `simplify2array`

Author(s)

Lluís Revilla

See Also

[removeDup](#)

Examples

```
duplicateIndices(c("52", "52", "53", "55")) # One repeated element
duplicateIndices(c("52", "52", "53", "55", "55")) # Repeated elements
duplicateIndices(c("52", "55", "53", "55", "52")) # Mixed repeated elements
```

`geneSim`*Similarity score genes based on pathways similarity*

Description

Given two genes, calculates the Dice similarity between each pathway which is combined to obtain a similarity between the genes.

Usage

```
geneSim(gene1, gene2, info, method = "max", ...)  
  
## S4 method for signature 'character,character,GeneSetCollection'  
geneSim(gene1, gene2, info,  
        method = "max", ...)
```

Arguments

<code>gene1, gene2</code>	Ids of the genes to calculate the similarity, to be found in genes.
<code>info</code>	A list or a <code>GeneSetCollection</code> of genes and the pathways they are involved.
<code>method</code>	one of <code>c("avg", "max", "rcmax", "rcmax.avg", "BMA", "reciprocal")</code> , see <code>Details</code> .
<code>...</code>	Other arguments passed to <code>combineScores</code>

Details

Given the information about the genes and their pathways, uses the ids of the genes to find the Dice similarity score for each pathway comparison between the genes. Later this similarities are combined using [combineScoresPar](#).

Value

The highest Dice score of all the combinations of pathways between the two ids compared if a method to combine scores is provided or NA if there isn't information for one gene. If an NA is returned this means that there isn't information available for any pathways for one of the genes. Otherwise a number between 0 and 1 (both included) is returned. Note that there isn't a negative value of similarity.

Methods (by class)

- `gene1 = character, gene2 = character, info = GeneSetCollection`: Calculates all the similarities of the `GeneSetCollection` and combine them using [combineScoresPar](#)

Author(s)

Lluís Revilla

See Also

[mgeneSim](#), [conversions](#) help page to transform Dice score to Jaccard score. For the method to combine the scores see [combineScoresPar](#).

Examples

```

if (require("org.Hs.eg.db") & require("reactome.db")) {
  # Extract the paths of all genes of org.Hs.eg.db from KEGG
  # (last update in data of June 31st 2011)
  genes.kegg <- as.list(org.Hs.egPATH)
  # Extracts the paths of all genes of org.Hs.eg.db from reactome
  genes.react <- as.list(reactomeEXTID2PATHID)
  geneSim("81", "18", genes.react)
  geneSim("81", "18", genes.kegg)
  geneSim("81", "18", genes.react, NULL)
  geneSim("81", "18", genes.kegg, NULL)
} else {
  warning('You need reactome.db and org.Hs.eg.db package for this example')
}

```

mclusterGeneSim

Similarity score between clusters of genes based on genes similarity

Description

Looks for the similarity between genes of a group and then between each group's genes.

Usage

```
mclusterGeneSim(clusters, info, method = c("max", "rcmax.avg"), ...)
```

```

## S4 method for signature 'list, GeneSetCollection'
mclusterGeneSim(clusters, info,
  method = c("max", "rcmax.avg"), ...)

```

Arguments

clusters	A list of clusters of genes to be found in id.
info	A list or a GeneSetCollection of genes and the pathways they are involved.
method	A vector with two or one argument to be passed to combineScores the first one is used to summarize the similarities of genes, the second one for clusters.
...	Other arguments passed to combineScores

Value

Returns a matrix with the similarity scores for each cluster comparison.

Methods (by class)

- clusters = list, info = GeneSetCollection: Calculates all the similarities of the GeneSetCollection and combine them using [combineScoresPar](#)

Author(s)

Lluís Revilla

See Also

[clusterGeneSim](#), [clusterSim](#) and [combineScores](#)

Examples

```
if (require("org.Hs.eg.db")) {
  genes.kegg <- as.list(org.Hs.egPATH)
  clusters <- list(cluster1 = c("18", "81", "10"),
                  cluster2 = c("100", "594", "836"),
                  cluster3 = c("18", "10", "83"))
  mclusterGeneSim(clusters, genes.kegg)
  mclusterGeneSim(clusters, genes.kegg, c("max", "avg"))
  mclusterGeneSim(clusters, genes.kegg, c("max", "BMA"))
} else {
  warning('You need org.Hs.eg.db package for this example')
}
```

mclusterSim	<i>Similarity score between clusters of genes based on pathways similarity</i>
-------------	--

Description

Looks for the similarity between genes in groups. Once the pathways for each cluster are found they are combined using `combineScores`.

Usage

```
mclusterSim(clusters, info, method = "max", ...)

## S4 method for signature 'list, GeneSetCollection'
mclusterSim(clusters, info, method = "max",
            ...)
```

Arguments

clusters	A list of clusters of genes to be found in id.
info	A list or a GeneSetCollection of genes and the pathways they are involved.
method	one of c("avg", "max", "rcmax", "rcmax.avg", "BMA", "reciprocal"), see Details.
...	Other arguments passed to combineScores

Value

mclusterSim returns a matrix with the similarity scores for each cluster comparison.

Methods (by class)

- clusters = list, info = GeneSetCollection: Calculates all the similarities of the GeneSetCollection and combine them using `combineScoresPar`

Author(s)

Lluís Revilla

See AlsoFor a different approach see [clusterGeneSim](#), [combineScores](#) and [conversions](#)**Examples**

```

if (require("org.Hs.eg.db")) {
  #Extract the paths of all genes of org.Hs.eg.db from KEGG (last update in
  # data of June 31st 2011)
  genes.kegg <- as.list(org.Hs.egPATH)

  clusters <- list(cluster1 = c("18", "81", "10"),
                  cluster2 = c("100", "10", "1"),
                  cluster3 = c("18", "10", "83"))
  mclusterSim(clusters, genes.kegg)
  mclusterSim(clusters, genes.kegg, "avg")
} else {
  warning('You need org.Hs.eg.db package for this example')
}

```

mgeneSim

*Similarity score genes based on pathways similarity***Description**

Given two genes, calculates the Dice similarity between each pathway which is combined to obtain a similarity between the genes.

Usage

```

mgeneSim(genes, info, method = "max", ...)

## S4 method for signature 'character, GeneSetCollection'
mgeneSim(genes, info, method = "max",
  ...)

## S4 method for signature 'missing, GeneSetCollection'
mgeneSim(genes, info, method = "max",
  ...)

```

Arguments

genes	A vector of genes.
info	A list or a GeneSetCollection of genes and the pathways they are involved.
method	one of c("avg", "max", "rcmax", "rcmax.avg", "BMA", "reciprocal"), see Details.
...	Other arguments passed to combineScores

Details

Given the information about the genes and their pathways, uses the ids of the genes to find the Dice similarity score for each pathway comparison between the genes. Later this similarities are combined using [combineScoresPar](#).

Value

mGeneSim returns the matrix of similarities between the genes in the vector

Methods (by class)

- genes = character, info = GeneSetCollection: Calculates all the similarities of the list and combine them using [combineScoresPar](#)
- genes = missing, info = GeneSetCollection: Calculates all the similarities of the list and combine them using [combineScoresPar](#)

Note

genes accept named characters and the output will use the names of the genes.

See Also

[geneSim](#), [conversions](#) help page to transform Dice score to Jaccard score. For the method to combine the scores see [combineScoresPar](#).

Examples

```
if (require("org.Hs.eg.db") & require("reactome.db")) {
  # Extract the paths of all genes of org.Hs.eg.db from KEGG
  # (last update in data of June 31st 2011)
  genes.kegg <- as.list(org.Hs.egPATH)
  # Extracts the paths of all genes of org.Hs.eg.db from reactome
  genes.react <- as.list(reactomeEXTID2PATHID)
  mGeneSim(c("81", "18", "10"), genes.react)
  mGeneSim(c("81", "18", "10"), genes.react, "avg")
  named_genes <- structure(c("81", "18", "10"),
    .Names = c("ACTN4", "ABAT", "NAT2"))
  mGeneSim(named_genes, genes.react, "max")
} else {
  warning('You need reactome.db and org.Hs.eg.db package for this example')
}
```

mPathSim

Calculates the Dice similarity between pathways

Description

Calculates the similarity between several pathways using dice similarity score. If one needs the matrix of similarities between pathways set the argument methods to NULL.

Usage

```

mpathSim(pathways, info, method = NULL, ...)

## S4 method for signature 'character, GeneSetCollection, ANY'
mpathSim(pathways, info,
  method = NULL, ...)

## S4 method for signature 'missing, GeneSetCollection, ANY'
mpathSim(pathways, info,
  method = NULL, ...)

## S4 method for signature 'missing, list, ANY'
mpathSim(pathways, info, method = NULL, ...)

## S4 method for signature 'missing, list, missing'
mpathSim(pathways, info, method = NULL, ...)

```

Arguments

pathways	Pathways to calculate the similarity for
info	A list of genes and the pathways they are involved or a GeneSetCollection object
method	To combine the scores of each pathway, one of c("avg", "max", "rcmax", "rcmax.avg", "BMA"), if NULL returns the matrix of similarities.
...	Other arguments passed to combineScoresPar

Value

The similarity between those pathways or all the similarities between each comparison.

Methods (by class)

- pathways = character, info = GeneSetCollection, method = ANY: Calculates the similarity between the provided pathways of the GeneSetCollection using combineScoresPar
- pathways = missing, info = GeneSetCollection, method = ANY: Calculates all the similarities of the GeneSetCollection and combine them using combineScoresPar
- pathways = missing, info = list, method = ANY: Calculates all the similarities of the list and combine them using combineScoresPar
- pathways = missing, info = list, method = missing: Calculates all the similarities of the list

Note

pathways accept named characters, and then the output will have the names

See Also

[pathSim](#) For single pairwise comparison. [conversions](#) To convert the Dice similarity to Jaccard similarity

Examples

```

if (require("reactome.db")){
  genes.react <- as.list(reactomeEXTID2PATHID)
  (pathways <- sample(unique(unlist(genes.react)), 10))
  mpathSim(pathways, genes.react, NULL)
  named_paths <- structure(
    c("R-HSA-112310", "R-HSA-112316", "R-HSA-112315"),
    .Names = c("Neurotransmitter Release Cycle",
               "Neuronal System",
               "Transmission across Chemical Synapses"))
  mpathSim(named_paths, genes.react, NULL)
} else {
  warning('You need reactome.db package for this example')
}

```

pathSim

Calculates the Dice similarity between pathways

Description

Calculates the similarity between pathways using dice similarity score. diceSim is used to calculate similarities between the two pathways.

Usage

```

pathSim(pathway1, pathway2, info)

## S4 method for signature 'character,character,GeneSetCollection'
pathSim(pathway1, pathway2,
        info)

```

Arguments

```

pathway1, pathway2
    A single pathway to calculate the similarity

info
    A list or a GeneSetCollection of genes and the pathways they are involved.

```

Value

The similarity between those pathways or all the similarities between each comparison.

Methods (by class)

- pathway1 = character, pathway2 = character, info = GeneSetCollection: Calculates all the similarities of a GeneSetCollection and combine them using combineScoresPar

Author(s)

Lluís Revilla

See Also

[conversions](#) help page to transform Dice score to Jaccard score. [mpathSim](#) for multiple pairwise comparison of pathways.

Examples

```
if (require("reactome.db")){
  # Extracts the paths of all genes of org.Hs.eg.db from reactome
  genes.react <- as.list(reactomeEXTID2PATHID)
  (paths <- sample(unique(unlist(genes.react)), 2))
  pathSim(paths[1], paths[2], genes.react)
} else {
  warning('You need reactome.db package for this example')
}
```

removeDup

*Remove duplicated rows and columns***Description**

Given the indices of the duplicated entries remove the columns and rows until just one is left, it keeps the duplicated with the highest absolute mean value.

Usage

```
removeDup(cor_mat, dupli)
```

Arguments

cor_mat	List of matrices
dupli	List of indices with duplicated entries

Value

A matrix with only one of the columns and rows duplicated

Author(s)

Lluís Revilla

See Also

[duplicateIndices](#) to obtain the list of indices with duplicated entries.

Examples

```
a <- seq2mat(c("52", "52", "53", "55"), runif(choose(4, 2)))
b <- seq2mat(c("52", "52", "53", "55"), runif(choose(4, 2)))
mat <- list("kegg" = a, "react" = b)
mat
dupli <- duplicateIndices(rownames(a))
remat <- removeDup(mat, dupli)
remat
```

seq2mat	<i>Transforms a vector to a symmetric matrix</i>
---------	--

Description

Fills a matrix of `ncol = length(x)` and `nrow = length(x)` with the values in `dat` and setting the diagonal to 1.

Usage

```
seq2mat(x, dat)
```

Arguments

<code>x</code>	names of columns and rows, used to define the size of the matrix
<code>dat</code>	Data to fill with the matrix with except the diagonal.

Details

`dat` should be at least `choose(length(x), 2)` of length. It assumes that the data provided comes from using the row and column id to obtain it.

Value

A square matrix with the diagonal set to 1 and `dat` on the upper and lower triangle with the columns ids and row ids from `x`.

Author(s)

Lluís Revilla

See Also

[upper.tri](#) and [lower.tri](#)

Examples

```
seq2mat(LETTERS[1:5], 1:10)
seq2mat(LETTERS[1:5], seq(from = 0.1, to = 1, by = 0.1))
```

`similarities`*Apply a function to a list of similarities*

Description

Function to join list of similarities by a function provided by the user.

Usage

```
similarities(sim, func, ...)
```

Arguments

<code>sim</code>	list of similarities to be joined. All similarities must have the same dimensions. The genes are assumed to be in the same order for all the matrices.
<code>func</code>	function to perform on those similarities: prod, sum... It should accept as many arguments as similarities matrices are provided, and should use numbers.
<code>...</code>	Other arguments passed to the function <code>func</code> . Usually <code>na.rm</code> or similar.

Value

A matrix of the size of the similarities

Note

It doesn't check that the columns and rows of the matrices are in the same order or are the same.

Author(s)

Lluís Revilla

See Also

[weighted](#) for functions that can be used, and [addSimilarities](#) for a wrapper to one of them

Examples

```
set.seed(100)
a <- seq2mat(LETTERS[1:5], rnorm(10))
b <- seq2mat(LETTERS[1:5], seq(from = 0.1, to = 1, by = 0.1))
sim <- list(b, a)
similarities(sim, weighted.prod, c(0.5, 0.5))
# Note the differences in the sign of some values
similarities(sim, weighted.sum, c(0.5, 0.5))
```

weighted	<i>Weighted operations</i>
----------	----------------------------

Description

Calculates the weighted sum or product of `x`. Each values should have its weight, otherwise it will throw an error.

Usage

```
weighted.sum(x, w, abs = TRUE)
```

```
weighted.prod(x, w)
```

Arguments

<code>x</code>	an object containing the values whose weighted operations is to be computed
<code>w</code>	a numerical vector of weights the same length as <code>x</code> giving the weights to use for elements of <code>x</code> .
<code>abs</code>	If any <code>x</code> is negative you want the result negative too?

Details

This functions are thought to be used with similarities. As some similarities might be positive and others negative the argument `abs` is provided for `weighted.sum`, assuming that only one similarity will be negative (usually the one coming from expression correlation).

Value

`weighted.sum` returns the sum of the product of `x*weights` removing all NA values. See parameter `abs` if there are any negative values.

`weighted.prod` returns the product of product of `x*weights` removing all NA values.

Author(s)

Lluís Revilla

See Also

[weighted.mean](#), [similarities](#) and [addSimilarities](#)

Examples

```
expr <- c(-0.2, 0.3, 0.5, 0.8, 0.1)
weighted.sum(expr, c(0.5, 0.2, 0.1, 0.1, 0.1))
weighted.sum(expr, c(0.5, 0.2, 0.1, 0.2, 0.1), FALSE)
weighted.sum(expr, c(0.4, 0.2, 0.1, 0.2, 0.1))
weighted.sum(expr, c(0.4, 0.2, 0.1, 0.2, 0.1), FALSE)
weighted.sum(expr, c(0.4, 0.2, 0, 0.2, 0.1))
weighted.sum(expr, c(0.5, 0.2, 0, 0.2, 0.1))
# Compared to weighted.prod:
weighted.prod(expr, c(0.5, 0.2, 0.1, 0.1, 0.1))
```

```
weighted.prod(expr, c(0.4, 0.2, 0.1, 0.2, 0.1))  
weighted.prod(expr, c(0.4, 0.2, 0, 0.2, 0.1))  
weighted.prod(expr, c(0.5, 0.2, 0, 0.2, 0.1))
```

Index

addSimilarities, [3](#), [22](#), [23](#)
AintoB, [4](#)

BioCor (BioCor-package), [2](#)
BioCor-package, [2](#)

clusterGeneSim, [2](#), [5](#), [7](#), [11](#), [15](#), [16](#)
clusterGeneSim, character, character, GeneSetCollection-method
(clusterGeneSim), [5](#)
clusterSim, [2](#), [5](#), [6](#), [11](#), [15](#)
clusterSim, character, character, GeneSetCollection-method
(clusterSim), [6](#)

combinadic, [7](#)
combineScores, [5–7](#), [8](#), [9](#), [15](#), [16](#)
combineScoresPar, [5](#), [7](#), [13–15](#), [17](#), [18](#)
combineScoresPar (combineScores), [8](#)
combineSources, [10](#)
combn, [8](#)
conversions, [2](#), [7](#), [10](#), [11](#), [13](#), [16–18](#), [20](#)

D2J (conversions), [10](#)
diceSim, [11](#), [11](#)
duplicateIndices, [12](#), [20](#)

geneSim, [2](#), [11](#), [13](#), [17](#)
geneSim, character, character, GeneSetCollection-method
(geneSim), [13](#)

J2D (conversions), [10](#)

lower.tri, [21](#)

mclusterGeneSim, [5](#), [14](#)
mclusterGeneSim, list, GeneSetCollection-method
(mclusterGeneSim), [14](#)
mclusterSim, [15](#)
mclusterSim, list, GeneSetCollection-method
(mclusterSim), [15](#)
mgeneSim, [13](#), [16](#)
mgeneSim, character, GeneSetCollection-method
(mgeneSim), [16](#)
mgeneSim, missing, GeneSetCollection-method
(mgeneSim), [16](#)
mpathSim, [17](#), [20](#)
mpathSim, character, GeneSetCollection, ANY-method
(mpathSim), [17](#)
mpathSim, missing, GeneSetCollection, ANY-method
(mpathSim), [17](#)
mpathSim, missing, list, ANY-method
(mpathSim), [17](#)
mpathSim, missing, list, missing-method
(mpathSim), [17](#)
pathSim, [2](#), [18](#), [19](#)
pathSim, character, character, GeneSetCollection-method
(pathSim), [19](#)

register, [9](#)
removeDup, [12](#), [20](#)

seq2mat, [21](#)
similarities, [2](#), [3](#), [22](#), [23](#)

upper.tri, [21](#)

weighted, [2](#), [3](#), [22](#), [23](#)
weighted.mean, [23](#)