

# Package ‘geneLenDataBase’

October 16, 2018

**Version** 1.16.0

**Date** 2016/04/09

**Title** Lengths of mRNA transcripts for a number of genomes

**Author** Matthew Young

**Maintainer** Nadia Davidson <nadia.davidson@mcri.edu.au>, Anthony Hawkins <anthony.hawkins@mcri.edu.au>

**Depends** R (>= 2.11.0)

**Imports** utils, rtracklayer, GenomicFeatures (>= 1.3.15)

**LazyLoad** yes

**Description** Length of mRNA transcripts for a number of genomes and gene ID formats, largely based on UCSC table browser

**biocViews** ExperimentData, Genome

**License** LGPL (>= 2)

**NeedsCompilation** no

**git\_url** <https://git.bioconductor.org/packages/geneLenDataBase>

**git\_branch** RELEASE\_3\_7

**git\_last\_commit** c2a8b23

**git\_last\_commit\_date** 2018-04-30

**Date/Publication** 2018-10-16

## R topics documented:

anoCar1.ensGene.LENGTH . . . . .	8
anoCar1.genscan.LENGTH . . . . .	9
anoCar1.xenoRefGene.LENGTH . . . . .	9
anoGam1.ensGene.LENGTH . . . . .	10
anoGam1.geneid.LENGTH . . . . .	10
anoGam1.genscan.LENGTH . . . . .	11
apiMel1.genscan.LENGTH . . . . .	11
apiMel2.ensGene.LENGTH . . . . .	12
apiMel2.geneid.LENGTH . . . . .	12
apiMel2.genscan.LENGTH . . . . .	13
aplCal1.xenoRefGene.LENGTH . . . . .	13
bosTau2.geneid.LENGTH . . . . .	14

bosTau2.geneSymbol.LENGTH . . . . .	14
bosTau2.genscan.LENGTH . . . . .	15
bosTau2.refGene.LENGTH . . . . .	15
bosTau2.sgpGene.LENGTH . . . . .	16
bosTau3.ensGene.LENGTH . . . . .	16
bosTau3.geneid.LENGTH . . . . .	17
bosTau3.geneSymbol.LENGTH . . . . .	17
bosTau3.genscan.LENGTH . . . . .	18
bosTau3.refGene.LENGTH . . . . .	18
bosTau3.sgpGene.LENGTH . . . . .	19
bosTau4.ensGene.LENGTH . . . . .	19
bosTau4.geneSymbol.LENGTH . . . . .	20
bosTau4.genscan.LENGTH . . . . .	20
bosTau4.nscanGene.LENGTH . . . . .	21
bosTau4.refGene.LENGTH . . . . .	21
braFlo1.xenoRefGene.LENGTH . . . . .	22
caeJap1.xenoRefGene.LENGTH . . . . .	22
caePb1.xenoRefGene.LENGTH . . . . .	23
caePb2.xenoRefGene.LENGTH . . . . .	23
caeRem2.xenoRefGene.LENGTH . . . . .	24
caeRem3.xenoRefGene.LENGTH . . . . .	24
calJac1.genscan.LENGTH . . . . .	25
calJac1.nscanGene.LENGTH . . . . .	25
calJac1.xenoRefGene.LENGTH . . . . .	26
canFam1.ensGene.LENGTH . . . . .	26
canFam1.geneSymbol.LENGTH . . . . .	27
canFam1.genscan.LENGTH . . . . .	27
canFam1.nscanGene.LENGTH . . . . .	28
canFam1.refGene.LENGTH . . . . .	28
canFam1.xenoRefGene.LENGTH . . . . .	29
canFam2.ensGene.LENGTH . . . . .	29
canFam2.geneSymbol.LENGTH . . . . .	30
canFam2.genscan.LENGTH . . . . .	30
canFam2.nscanGene.LENGTH . . . . .	31
canFam2.refGene.LENGTH . . . . .	31
canFam2.xenoRefGene.LENGTH . . . . .	32
cavPor3.ensGene.LENGTH . . . . .	32
cavPor3.genscan.LENGTH . . . . .	33
cavPor3.nscanGene.LENGTH . . . . .	33
cavPor3.xenoRefGene.LENGTH . . . . .	34
cb1.xenoRefGene.LENGTH . . . . .	34
cb3.xenoRefGene.LENGTH . . . . .	35
ce2.geneid.LENGTH . . . . .	35
ce2.geneSymbol.LENGTH . . . . .	36
ce2.refGene.LENGTH . . . . .	36
ce4.geneSymbol.LENGTH . . . . .	37
ce4.refGene.LENGTH . . . . .	37
ce4.xenoRefGene.LENGTH . . . . .	38
ce6.ensGene.LENGTH . . . . .	38
ce6.geneSymbol.LENGTH . . . . .	39
ce6.refGene.LENGTH . . . . .	39
ce6.xenoRefGene.LENGTH . . . . .	40

ci1.geneSymbol.LENGTH . . . . .	40
ci1.refGene.LENGTH . . . . .	41
ci1.xenoRefGene.LENGTH . . . . .	41
ci2.ensGene.LENGTH . . . . .	42
ci2.geneSymbol.LENGTH . . . . .	42
ci2.refGene.LENGTH . . . . .	43
ci2.xenoRefGene.LENGTH . . . . .	43
danRer3.ensGene.LENGTH . . . . .	44
danRer3.geneSymbol.LENGTH . . . . .	44
danRer3.refGene.LENGTH . . . . .	45
danRer4.ensGene.LENGTH . . . . .	45
danRer4.geneSymbol.LENGTH . . . . .	46
danRer4.genscan.LENGTH . . . . .	46
danRer4.nscanGene.LENGTH . . . . .	47
danRer4.refGene.LENGTH . . . . .	47
danRer5.ensGene.LENGTH . . . . .	48
danRer5.geneSymbol.LENGTH . . . . .	48
danRer5.refGene.LENGTH . . . . .	49
danRer5.vegaGene.LENGTH . . . . .	49
danRer5.vegaPseudoGene.LENGTH . . . . .	50
danRer6.ensGene.LENGTH . . . . .	50
danRer6.geneSymbol.LENGTH . . . . .	51
danRer6.refGene.LENGTH . . . . .	51
danRer6.xenoRefGene.LENGTH . . . . .	52
dm1.geneSymbol.LENGTH . . . . .	52
dm1.genscan.LENGTH . . . . .	53
dm1.refGene.LENGTH . . . . .	53
dm2.geneid.LENGTH . . . . .	54
dm2.geneSymbol.LENGTH . . . . .	54
dm2.genscan.LENGTH . . . . .	55
dm2.nscanGene.LENGTH . . . . .	55
dm2.refGene.LENGTH . . . . .	56
dm3.geneSymbol.LENGTH . . . . .	56
dm3.nscanPasaGene.LENGTH . . . . .	57
dm3.refGene.LENGTH . . . . .	57
dp2.genscan.LENGTH . . . . .	58
dp2.xenoRefGene.LENGTH . . . . .	58
dp3.geneid.LENGTH . . . . .	59
dp3.genscan.LENGTH . . . . .	59
dp3.xenoRefGene.LENGTH . . . . .	60
droAna1.geneid.LENGTH . . . . .	60
droAna1.genscan.LENGTH . . . . .	61
droAna1.xenoRefGene.LENGTH . . . . .	61
droAna2.genscan.LENGTH . . . . .	62
droAna2.xenoRefGene.LENGTH . . . . .	62
droEre1.genscan.LENGTH . . . . .	63
droEre1.xenoRefGene.LENGTH . . . . .	63
droGri1.genscan.LENGTH . . . . .	64
droGri1.xenoRefGene.LENGTH . . . . .	64
droMoj1.geneid.LENGTH . . . . .	65
droMoj1.genscan.LENGTH . . . . .	65
droMoj1.xenoRefGene.LENGTH . . . . .	66

droMoj2.genscan.LENGTH . . . . .	66
droMoj2.xenoRefGene.LENGTH . . . . .	67
droPer1.genscan.LENGTH . . . . .	67
droPer1.xenoRefGene.LENGTH . . . . .	68
droSec1.genscan.LENGTH . . . . .	68
droSec1.xenoRefGene.LENGTH . . . . .	69
droSim1.geneid.LENGTH . . . . .	69
droSim1.genscan.LENGTH . . . . .	70
droSim1.xenoRefGene.LENGTH . . . . .	70
droVir1.geneid.LENGTH . . . . .	71
droVir1.genscan.LENGTH . . . . .	71
droVir1.xenoRefGene.LENGTH . . . . .	72
droVir2.genscan.LENGTH . . . . .	72
droVir2.xenoRefGene.LENGTH . . . . .	73
droYak1.geneid.LENGTH . . . . .	73
droYak1.genscan.LENGTH . . . . .	74
droYak1.xenoRefGene.LENGTH . . . . .	74
droYak2.genscan.LENGTH . . . . .	75
droYak2.xenoRefGene.LENGTH . . . . .	75
equCab1.geneid.LENGTH . . . . .	76
equCab1.geneSymbol.LENGTH . . . . .	76
equCab1.nscanGene.LENGTH . . . . .	77
equCab1.refGene.LENGTH . . . . .	77
equCab1.sgpGene.LENGTH . . . . .	78
equCab2.ensGene.LENGTH . . . . .	78
equCab2.geneSymbol.LENGTH . . . . .	79
equCab2.nscanGene.LENGTH . . . . .	79
equCab2.refGene.LENGTH . . . . .	80
equCab2.xenoRefGene.LENGTH . . . . .	80
felCat3.ensGene.LENGTH . . . . .	81
felCat3.geneid.LENGTH . . . . .	81
felCat3.geneSymbol.LENGTH . . . . .	82
felCat3.genscan.LENGTH . . . . .	82
felCat3.nscanGene.LENGTH . . . . .	83
felCat3.refGene.LENGTH . . . . .	83
felCat3.sgpGene.LENGTH . . . . .	84
felCat3.xenoRefGene.LENGTH . . . . .	84
fr1.ensGene.LENGTH . . . . .	85
fr1.genscan.LENGTH . . . . .	85
fr2.ensGene.LENGTH . . . . .	86
galGal2.ensGene.LENGTH . . . . .	86
galGal2.geneid.LENGTH . . . . .	87
galGal2.geneSymbol.LENGTH . . . . .	87
galGal2.genscan.LENGTH . . . . .	88
galGal2.refGene.LENGTH . . . . .	88
galGal2.sgpGene.LENGTH . . . . .	89
galGal3.ensGene.LENGTH . . . . .	89
galGal3.geneSymbol.LENGTH . . . . .	90
galGal3.genscan.LENGTH . . . . .	90
galGal3.nscanGene.LENGTH . . . . .	91
galGal3.refGene.LENGTH . . . . .	91
galGal3.xenoRefGene.LENGTH . . . . .	92

gasAcu1.ensGene.LENGTH . . . . .	92
gasAcu1.nscanGene.LENGTH . . . . .	93
hg16.acembly.LENGTH . . . . .	93
hg16.ensGene.LENGTH . . . . .	94
hg16.exoniphy.LENGTH . . . . .	94
hg16.geneid.LENGTH . . . . .	95
hg16.geneSymbol.LENGTH . . . . .	95
hg16.genscan.LENGTH . . . . .	96
hg16.knownGene.LENGTH . . . . .	96
hg16.refGene.LENGTH . . . . .	97
hg16.sgpGene.LENGTH . . . . .	97
hg17.acembly.LENGTH . . . . .	98
hg17.acescan.LENGTH . . . . .	98
hg17.ccdsGene.LENGTH . . . . .	99
hg17.ensGene.LENGTH . . . . .	99
hg17.exoniphy.LENGTH . . . . .	100
hg17.geneid.LENGTH . . . . .	100
hg17.geneSymbol.LENGTH . . . . .	101
hg17.genscan.LENGTH . . . . .	101
hg17.knownGene.LENGTH . . . . .	102
hg17.refGene.LENGTH . . . . .	102
hg17.sgpGene.LENGTH . . . . .	103
hg17.vegaGene.LENGTH . . . . .	103
hg17.vegaPseudoGene.LENGTH . . . . .	104
hg17.xenoRefGene.LENGTH . . . . .	104
hg18.acembly.LENGTH . . . . .	105
hg18.acescan.LENGTH . . . . .	105
hg18.ccdsGene.LENGTH . . . . .	106
hg18.ensGene.LENGTH . . . . .	106
hg18.exoniphy.LENGTH . . . . .	107
hg18.geneid.LENGTH . . . . .	107
hg18.geneSymbol.LENGTH . . . . .	108
hg18.genscan.LENGTH . . . . .	108
hg18.knownGene.LENGTH . . . . .	109
hg18.knownGeneOld3.LENGTH . . . . .	109
hg18.refGene.LENGTH . . . . .	110
hg18.sgpGene.LENGTH . . . . .	110
hg18.sibGene.LENGTH . . . . .	111
hg18.xenoRefGene.LENGTH . . . . .	111
hg19.ccdsGene.LENGTH . . . . .	112
hg19.ensGene.LENGTH . . . . .	112
hg19.exoniphy.LENGTH . . . . .	113
hg19.geneSymbol.LENGTH . . . . .	113
hg19.knownGene.LENGTH . . . . .	114
hg19.nscanGene.LENGTH . . . . .	114
hg19.refGene.LENGTH . . . . .	115
hg19.xenoRefGene.LENGTH . . . . .	115
loxAfr3.xenoRefGene.LENGTH . . . . .	116
mm7.ensGene.LENGTH . . . . .	116
mm7.geneid.LENGTH . . . . .	117
mm7.geneSymbol.LENGTH . . . . .	117
mm7.genscan.LENGTH . . . . .	118

mm7.knownGene.LENGTH	118
mm7.refGene.LENGTH	119
mm7.sgpGene.LENGTH	119
mm7.xenoRefGene.LENGTH	120
mm8.ccdsGene.LENGTH	120
mm8.ensGene.LENGTH	121
mm8.geneid.LENGTH	121
mm8.geneSymbol.LENGTH	122
mm8.genscan.LENGTH	122
mm8.knownGene.LENGTH	123
mm8.nscanGene.LENGTH	123
mm8.refGene.LENGTH	124
mm8.sgpGene.LENGTH	124
mm8.sibGene.LENGTH	125
mm8.xenoRefGene.LENGTH	125
mm9.acembly.LENGTH	126
mm9.ccdsGene.LENGTH	126
mm9.ensGene.LENGTH	127
mm9.exoniphy.LENGTH	127
mm9.geneid.LENGTH	128
mm9.geneSymbol.LENGTH	128
mm9.genscan.LENGTH	129
mm9.knownGene.LENGTH	129
mm9.nscanGene.LENGTH	130
mm9.refGene.LENGTH	130
mm9.sgpGene.LENGTH	131
mm9.xenoRefGene.LENGTH	131
monDom1.genscan.LENGTH	132
monDom4.ensGene.LENGTH	132
monDom4.geneSymbol.LENGTH	133
monDom4.genscan.LENGTH	133
monDom4.nscanGene.LENGTH	134
monDom4.refGene.LENGTH	134
monDom4.xenoRefGene.LENGTH	135
monDom5.ensGene.LENGTH	135
monDom5.geneSymbol.LENGTH	136
monDom5.genscan.LENGTH	136
monDom5.nscanGene.LENGTH	137
monDom5.refGene.LENGTH	137
monDom5.xenoRefGene.LENGTH	138
ornAna1.ensGene.LENGTH	138
ornAna1.geneSymbol.LENGTH	139
ornAna1.refGene.LENGTH	139
ornAna1.xenoRefGene.LENGTH	140
oryLat2.ensGene.LENGTH	140
oryLat2.geneSymbol.LENGTH	141
oryLat2.refGene.LENGTH	141
oryLat2.xenoRefGene.LENGTH	142
panTro1.ensGene.LENGTH	142
panTro1.geneid.LENGTH	143
panTro1.genscan.LENGTH	143
panTro1.xenoRefGene.LENGTH	144

panTro2.ensGene.LENGTH . . . . .	144
panTro2.geneSymbol.LENGTH . . . . .	145
panTro2.genscan.LENGTH . . . . .	145
panTro2.nscanGene.LENGTH . . . . .	146
panTro2.refGene.LENGTH . . . . .	146
panTro2.xenoRefGene.LENGTH . . . . .	147
petMar1.xenoRefGene.LENGTH . . . . .	147
ponAbe2.ensGene.LENGTH . . . . .	148
ponAbe2.geneSymbol.LENGTH . . . . .	148
ponAbe2.genscan.LENGTH . . . . .	149
ponAbe2.nscanGene.LENGTH . . . . .	149
ponAbe2.refGene.LENGTH . . . . .	150
ponAbe2.xenoRefGene.LENGTH . . . . .	150
priPac1.xenoRefGene.LENGTH . . . . .	151
rheMac2.ensGene.LENGTH . . . . .	151
rheMac2.geneid.LENGTH . . . . .	152
rheMac2.geneSymbol.LENGTH . . . . .	152
rheMac2.nscanGene.LENGTH . . . . .	153
rheMac2.refGene.LENGTH . . . . .	153
rheMac2.sgpGene.LENGTH . . . . .	154
rheMac2.xenoRefGene.LENGTH . . . . .	154
rn3.ensGene.LENGTH . . . . .	155
rn3.geneid.LENGTH . . . . .	155
rn3.geneSymbol.LENGTH . . . . .	156
rn3.genscan.LENGTH . . . . .	156
rn3.knownGene.LENGTH . . . . .	157
rn3.nscanGene.LENGTH . . . . .	157
rn3.refGene.LENGTH . . . . .	158
rn3.sgpGene.LENGTH . . . . .	158
rn3.xenoRefGene.LENGTH . . . . .	159
rn4.ensGene.LENGTH . . . . .	159
rn4.geneid.LENGTH . . . . .	160
rn4.geneSymbol.LENGTH . . . . .	160
rn4.genscan.LENGTH . . . . .	161
rn4.knownGene.LENGTH . . . . .	161
rn4.nscanGene.LENGTH . . . . .	162
rn4.refGene.LENGTH . . . . .	162
rn4.sgpGene.LENGTH . . . . .	163
rn4.xenoRefGene.LENGTH . . . . .	163
sacCer1.ensGene.LENGTH . . . . .	164
sacCer2.ensGene.LENGTH . . . . .	164
strPur1.geneSymbol.LENGTH . . . . .	165
strPur1.genscan.LENGTH . . . . .	165
strPur1.refGene.LENGTH . . . . .	166
strPur1.xenoRefGene.LENGTH . . . . .	166
strPur2.geneSymbol.LENGTH . . . . .	167
strPur2.genscan.LENGTH . . . . .	167
strPur2.refGene.LENGTH . . . . .	168
strPur2.xenoRefGene.LENGTH . . . . .	168
supportedGeneIDs . . . . .	169
supportedGenomes . . . . .	169
taeGut1.ensGene.LENGTH . . . . .	170

taeGut1.geneSymbol.LENGTH . . . . .	170
taeGut1.genscan.LENGTH . . . . .	171
taeGut1.nscanGene.LENGTH . . . . .	171
taeGut1.refGene.LENGTH . . . . .	172
taeGut1.xenoRefGene.LENGTH . . . . .	172
tetNig1.ensGene.LENGTH . . . . .	173
tetNig1.geneid.LENGTH . . . . .	173
tetNig1.genscan.LENGTH . . . . .	174
tetNig1.nscanGene.LENGTH . . . . .	174
tetNig2.ensGene.LENGTH . . . . .	175
unfactor . . . . .	175
xenTro1.genscan.LENGTH . . . . .	176
xenTro2.ensGene.LENGTH . . . . .	176
xenTro2.geneSymbol.LENGTH . . . . .	177
xenTro2.genscan.LENGTH . . . . .	177
xenTro2.refGene.LENGTH . . . . .	178

**Index** **179**

---

anoCar1.ensGene.LENGTH

*Transcript length data for the organism anoCar*

---

### Description

anoCar1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(anoCar1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoCar1.ensGene.LENGTH)
head(anoCar1.ensGene.LENGTH)
```



---

```
anoCar1.genscan.LENGTH
```

*Transcript length data for the organism anoCar*

---

### Description

anoCar1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(anoCar1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoCar1.genscan.LENGTH)
head(anoCar1.genscan.LENGTH)
```

---

```
anoCar1.xenoRefGene.LENGTH
```

*Transcript length data for the organism anoCar*

---

### Description

anoCar1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(anoCar1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoCar1.xenoRefGene.LENGTH)
head(anoCar1.xenoRefGene.LENGTH)
```

---

```
anoGam1.ensGene.LENGTH
```

*Transcript length data for the organism anoGam*

---

### Description

anoGam1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(anoGam1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoGam1.ensGene.LENGTH)
head(anoGam1.ensGene.LENGTH)
```

---

```
anoGam1.geneid.LENGTH
```

*Transcript length data for the organism anoGam*

---

### Description

anoGam1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(anoGam1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoGam1.geneid.LENGTH)
head(anoGam1.geneid.LENGTH)
```

---

```
anoGam1.genscan.LENGTH
```

*Transcript length data for the organism anoGam*

---

### Description

anoGam1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(anoGam1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoGam1.genscan.LENGTH)
head(anoGam1.genscan.LENGTH)
```

---

```
apiMel1.genscan.LENGTH
```

*Transcript length data for the organism apiMel*

---

### Description

apiMel1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(apiMel1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(apiMel1.genscan.LENGTH)
head(apiMel1.genscan.LENGTH)
```

---

```
apiMel2.ensGene.LENGTH
```

*Transcript length data for the organism apiMel*

---

### Description

apiMel2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(apiMel2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(apiMel2.ensGene.LENGTH)
head(apiMel2.ensGene.LENGTH)
```

---

```
apiMel2.geneid.LENGTH
```

*Transcript length data for the organism apiMel*

---

### Description

apiMel2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(apiMel2, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(apiMel2.geneid.LENGTH)
head(apiMel2.geneid.LENGTH)
```

---

```
apiMel2.genscan.LENGTH
```

*Transcript length data for the organism apiMel*

---

### Description

apiMel2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(apiMel2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(apiMel2.genscan.LENGTH)
head(apiMel2.genscan.LENGTH)
```

---

```
aplCal1.xenoRefGene.LENGTH
```

*Transcript length data for the organism aplCal*

---

### Description

aplCal1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(aplCal1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(aplCal1.xenoRefGene.LENGTH)
head(aplCal1.xenoRefGene.LENGTH)
```

---

bosTau2.geneid.LENGTH *Transcript length data for the organism bosTau*

---

### Description

bosTau2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau2.geneid.LENGTH)
head(bosTau2.geneid.LENGTH)
```

---

bosTau2.geneSymbol.LENGTH  
*Transcript length data for the organism bosTau*

---

### Description

bosTau2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau2.geneSymbol.LENGTH)
head(bosTau2.geneSymbol.LENGTH)
```

---

`bosTau2.genscan.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau2.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau2.genscan.LENGTH)
head(bosTau2.genscan.LENGTH)
```

---

`bosTau2.refGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau2.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau2.refGene.LENGTH)
head(bosTau2.refGene.LENGTH)
```

---

```
bosTau2.sgpGene.LENGTH
```

*Transcript length data for the organism bosTau*

---

### Description

bosTau2.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau2.sgpGene.LENGTH)
head(bosTau2.sgpGene.LENGTH)
```

---

```
bosTau3.ensGene.LENGTH
```

*Transcript length data for the organism bosTau*

---

### Description

bosTau3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau3.ensGene.LENGTH)
head(bosTau3.ensGene.LENGTH)
```



---

bosTau3.geneid.LENGTH *Transcript length data for the organism bosTau*

---

### Description

bosTau3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau3.geneid.LENGTH)
head(bosTau3.geneid.LENGTH)
```

---

bosTau3.geneSymbol.LENGTH  
*Transcript length data for the organism bosTau*

---

### Description

bosTau3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau3.geneSymbol.LENGTH)
head(bosTau3.geneSymbol.LENGTH)
```

---

```
bosTau3.genscan.LENGTH
```

*Transcript length data for the organism bosTau*

---

### Description

bosTau3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau3.genscan.LENGTH)
head(bosTau3.genscan.LENGTH)
```

---

```
bosTau3.refGene.LENGTH
```

*Transcript length data for the organism bosTau*

---

### Description

bosTau3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau3.refGene.LENGTH)
head(bosTau3.refGene.LENGTH)
```

---

`bosTau3.sgpGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau3.sgpGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `sgpGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, sgpGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(bosTau3.sgpGene.LENGTH)
head(bosTau3.sgpGene.LENGTH)
```

---

`bosTau4.ensGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau4.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(bosTau4.ensGene.LENGTH)
head(bosTau4.ensGene.LENGTH)
```

---

```
bosTau4.geneSymbol.LENGTH
```

*Transcript length data for the organism bosTau*

---

### Description

bosTau4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau4.geneSymbol.LENGTH)
head(bosTau4.geneSymbol.LENGTH)
```

---

```
bosTau4.genscan.LENGTH
```

*Transcript length data for the organism bosTau*

---

### Description

bosTau4.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau4.genscan.LENGTH)
head(bosTau4.genscan.LENGTH)
```

---

```
bosTau4.nscanGene.LENGTH
```

*Transcript length data for the organism bosTau*

---

### Description

bosTau4.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau4.nscanGene.LENGTH)
head(bosTau4.nscanGene.LENGTH)
```

---

```
bosTau4.refGene.LENGTH
```

*Transcript length data for the organism bosTau*

---

### Description

bosTau4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau4.refGene.LENGTH)
head(bosTau4.refGene.LENGTH)
```

---

```
braFlo1.xenoRefGene.LENGTH
```

*Transcript length data for the organism braFlo*

---

### Description

braFlo1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(braFlo1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(braFlo1.xenoRefGene.LENGTH)
head(braFlo1.xenoRefGene.LENGTH)
```

---

```
caeJap1.xenoRefGene.LENGTH
```

*Transcript length data for the organism caeJap*

---

### Description

caeJap1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caeJap1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(caeJap1.xenoRefGene.LENGTH)
head(caeJap1.xenoRefGene.LENGTH)
```

---

```
caePb1.xenoRefGene.LENGTH
```

*Transcript length data for the organism caePb*

---

### Description

caePb1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caePb1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(caePb1.xenoRefGene.LENGTH)
head(caePb1.xenoRefGene.LENGTH)
```

---

```
caePb2.xenoRefGene.LENGTH
```

*Transcript length data for the organism caePb*

---

### Description

caePb2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caePb2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(caePb2.xenoRefGene.LENGTH)
head(caePb2.xenoRefGene.LENGTH)
```

---

```
caeRem2.xenoRefGene.LENGTH
```

*Transcript length data for the organism caeRem*

---

### Description

caeRem2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caeRem2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(caeRem2.xenoRefGene.LENGTH)
head(caeRem2.xenoRefGene.LENGTH)
```

---

```
caeRem3.xenoRefGene.LENGTH
```

*Transcript length data for the organism caeRem*

---

### Description

caeRem3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caeRem3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(caeRem3.xenoRefGene.LENGTH)
head(caeRem3.xenoRefGene.LENGTH)
```



---

`calJac1.genscan.LENGTH`*Transcript length data for the organism calJac*

---

**Description**

calJac1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(calJac1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(calJac1.genscan.LENGTH)
head(calJac1.genscan.LENGTH)
```

---

`calJac1.nscanGene.LENGTH`*Transcript length data for the organism calJac*

---

**Description**

calJac1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(calJac1, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(calJac1.nscanGene.LENGTH)
head(calJac1.nscanGene.LENGTH)
```

---

```
calJac1.xenoRefGene.LENGTH
```

*Transcript length data for the organism calJac*

---

### Description

calJac1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(calJac1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(calJac1.xenoRefGene.LENGTH)
head(calJac1.xenoRefGene.LENGTH)
```

---

```
canFam1.ensGene.LENGTH
```

*Transcript length data for the organism canFam*

---

### Description

canFam1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam1.ensGene.LENGTH)
head(canFam1.ensGene.LENGTH)
```

---

`canFam1.geneSymbol.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

`canFam1.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(canFam1.geneSymbol.LENGTH)
head(canFam1.geneSymbol.LENGTH)
```

---

`canFam1.genscan.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

`canFam1.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(canFam1.genscan.LENGTH)
head(canFam1.genscan.LENGTH)
```

---

canFam1.nscanGene.LENGTH

*Transcript length data for the organism canFam*

---

### Description

canFam1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam1.nscanGene.LENGTH)
head(canFam1.nscanGene.LENGTH)
```

---

canFam1.refGene.LENGTH

*Transcript length data for the organism canFam*

---

### Description

canFam1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam1.refGene.LENGTH)
head(canFam1.refGene.LENGTH)
```

---

```
canFam1.xenoRefGene.LENGTH
```

*Transcript length data for the organism canFam*

---

### Description

canFam1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam1.xenoRefGene.LENGTH)
head(canFam1.xenoRefGene.LENGTH)
```

---

```
canFam2.ensGene.LENGTH
```

*Transcript length data for the organism canFam*

---

### Description

canFam2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam2.ensGene.LENGTH)
head(canFam2.ensGene.LENGTH)
```

---

```
canFam2.geneSymbol.LENGTH
```

*Transcript length data for the organism canFam*

---

### Description

canFam2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam2.geneSymbol.LENGTH)
head(canFam2.geneSymbol.LENGTH)
```

---

```
canFam2.genscan.LENGTH
```

*Transcript length data for the organism canFam*

---

### Description

canFam2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam2.genscan.LENGTH)
head(canFam2.genscan.LENGTH)
```

---

`canFam2.nscanGene.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

canFam2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, nscanGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(canFam2.nscanGene.LENGTH)
head(canFam2.nscanGene.LENGTH)
```

---

`canFam2.refGene.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

canFam2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(canFam2.refGene.LENGTH)
head(canFam2.refGene.LENGTH)
```

---

```
canFam2.xenoRefGene.LENGTH
```

*Transcript length data for the organism canFam*

---

### Description

canFam2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam2.xenoRefGene.LENGTH)
head(canFam2.xenoRefGene.LENGTH)
```

---

```
cavPor3.ensGene.LENGTH
```

*Transcript length data for the organism cavPor*

---

### Description

cavPor3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(cavPor3.ensGene.LENGTH)
head(cavPor3.ensGene.LENGTH)
```



---

```
cavPor3.genscan.LENGTH
```

*Transcript length data for the organism cavPor*

---

### Description

cavPor3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(cavPor3.genscan.LENGTH)
head(cavPor3.genscan.LENGTH)
```

---

```
cavPor3.nscanGene.LENGTH
```

*Transcript length data for the organism cavPor*

---

### Description

cavPor3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(cavPor3.nscanGene.LENGTH)
head(cavPor3.nscanGene.LENGTH)
```

---

```
cavPor3.xenoRefGene.LENGTH
```

*Transcript length data for the organism cavPor*

---

### Description

cavPor3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(cavPor3.xenoRefGene.LENGTH)
head(cavPor3.xenoRefGene.LENGTH)
```

---

```
cb1.xenoRefGene.LENGTH
```

*Transcript length data for the organism cb*

---

### Description

cb1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(cb1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(cb1.xenoRefGene.LENGTH)
head(cb1.xenoRefGene.LENGTH)
```

---

`cb3.xenoRefGene.LENGTH`*Transcript length data for the organism cb*

---

**Description**

`cb3.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(cb3, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(cb3.xenoRefGene.LENGTH)
head(cb3.xenoRefGene.LENGTH)
```

---

`ce2.geneid.LENGTH`*Transcript length data for the organism ce*

---

**Description**

`ce2.geneid.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneid` table.

The data file was made by calling `downloadLengthFromUCSC(ce2, geneid)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ce2.geneid.LENGTH)
head(ce2.geneid.LENGTH)
```

---

ce2.geneSymbol1.LENGTH *Transcript length data for the organism ce*

---

### Description

ce2.geneSymbol1.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ce2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce2.geneSymbol1.LENGTH)
head(ce2.geneSymbol1.LENGTH)
```

---

ce2.refGene.LENGTH *Transcript length data for the organism ce*

---

### Description

ce2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ce2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce2.refGene.LENGTH)
head(ce2.refGene.LENGTH)
```

---

ce4.geneSymbol.LENGTH *Transcript length data for the organism ce*

---

### Description

ce4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ce4, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce4.geneSymbol.LENGTH)
head(ce4.geneSymbol.LENGTH)
```

---

ce4.refGene.LENGTH *Transcript length data for the organism ce*

---

### Description

ce4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ce4, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce4.refGene.LENGTH)
head(ce4.refGene.LENGTH)
```

---

```
ce4.xenoRefGene.LENGTH
```

*Transcript length data for the organism ce*

---

### Description

ce4.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ce4, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce4.xenoRefGene.LENGTH)
head(ce4.xenoRefGene.LENGTH)
```

---

```
ce6.ensGene.LENGTH
```

*Transcript length data for the organism ce*

---

### Description

ce6.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(ce6, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce6.ensGene.LENGTH)
head(ce6.ensGene.LENGTH)
```

---

ce6.geneSymbol.LENGTH *Transcript length data for the organism ce*

---

### Description

ce6.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ce6, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce6.geneSymbol.LENGTH)
head(ce6.geneSymbol.LENGTH)
```

---

ce6.refGene.LENGTH *Transcript length data for the organism ce*

---

### Description

ce6.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ce6, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce6.refGene.LENGTH)
head(ce6.refGene.LENGTH)
```

---

ce6.xenoRefGene.LENGTH

*Transcript length data for the organism ce*

---

### Description

ce6.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ce6, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce6.xenoRefGene.LENGTH)
head(ce6.xenoRefGene.LENGTH)
```

---

ci1.geneSymbol.LENGTH *Transcript length data for the organism ci*

---

### Description

ci1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ci1, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci1.geneSymbol.LENGTH)
head(ci1.geneSymbol.LENGTH)
```



---

ci1.refGene.LENGTH      *Transcript length data for the organism ci*

---

### Description

ci1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ci1, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci1.refGene.LENGTH)
head(ci1.refGene.LENGTH)
```

---

ci1.xenoRefGene.LENGTH      *Transcript length data for the organism ci*

---

### Description

ci1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ci1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci1.xenoRefGene.LENGTH)
head(ci1.xenoRefGene.LENGTH)
```

---

ci2.ensGene.LENGTH     *Transcript length data for the organism ci*

---

### Description

ci2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(ci2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci2.ensGene.LENGTH)
head(ci2.ensGene.LENGTH)
```

---

ci2.geneSymbol.LENGTH     *Transcript length data for the organism ci*

---

### Description

ci2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ci2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci2.geneSymbol.LENGTH)
head(ci2.geneSymbol.LENGTH)
```

---

ci2.refGene.LENGTH      *Transcript length data for the organism ci*

---

### Description

ci2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ci2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci2.refGene.LENGTH)
head(ci2.refGene.LENGTH)
```

---

ci2.xenoRefGene.LENGTH      *Transcript length data for the organism ci*

---

### Description

ci2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ci2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci2.xenoRefGene.LENGTH)
head(ci2.xenoRefGene.LENGTH)
```

---

danRer3.ensGene.LENGTH

*Transcript length data for the organism danRer*

---

### Description

danRer3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer3, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer3.ensGene.LENGTH)
head(danRer3.ensGene.LENGTH)
```

---

danRer3.geneSymbol.LENGTH

*Transcript length data for the organism danRer*

---

### Description

danRer3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(danRer3, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer3.geneSymbol.LENGTH)
head(danRer3.geneSymbol.LENGTH)
```

---

```
danRer3.refGene.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer3, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer3.refGene.LENGTH)
head(danRer3.refGene.LENGTH)
```

---

```
danRer4.ensGene.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer4.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer4.ensGene.LENGTH)
head(danRer4.ensGene.LENGTH)
```

---

```
danRer4.geneSymbol.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer4.geneSymbol.LENGTH)
head(danRer4.geneSymbol.LENGTH)
```

---

```
danRer4.genscan.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer4.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer4.genscan.LENGTH)
head(danRer4.genscan.LENGTH)
```

---

`danRer4.nscanGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer4.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, nscanGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(danRer4.nscanGene.LENGTH)
head(danRer4.nscanGene.LENGTH)
```

---

`danRer4.refGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(danRer4.refGene.LENGTH)
head(danRer4.refGene.LENGTH)
```

---

```
danRer5.ensGene.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer5.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer5.ensGene.LENGTH)
head(danRer5.ensGene.LENGTH)
```

---

```
danRer5.geneSymbol.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer5.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer5.geneSymbol.LENGTH)
head(danRer5.geneSymbol.LENGTH)
```



---

```
danRer5.refGene.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer5.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer5.refGene.LENGTH)
head(danRer5.refGene.LENGTH)
```

---

```
danRer5.vegaGene.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer5.vegaGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, vegaGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer5.vegaGene.LENGTH)
head(danRer5.vegaGene.LENGTH)
```

---

```
danRer5.vegaPseudoGene.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer5.vegaPseudoGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaPseudoGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, vegaPseudoGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer5.vegaPseudoGene.LENGTH)
head(danRer5.vegaPseudoGene.LENGTH)
```

---

```
danRer6.ensGene.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer6.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer6.ensGene.LENGTH)
head(danRer6.ensGene.LENGTH)
```

---

```
danRer6.geneSymbol.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer6.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer6.geneSymbol.LENGTH)
head(danRer6.geneSymbol.LENGTH)
```

---

```
danRer6.refGene.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer6.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer6.refGene.LENGTH)
head(danRer6.refGene.LENGTH)
```

---

```
danRer6.xenoRefGene.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer6.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer6.xenoRefGene.LENGTH)
head(danRer6.xenoRefGene.LENGTH)
```

---

```
dm1.geneSymbol.LENGTH
```

*Transcript length data for the organism dm*

---

### Description

dm1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(dm1, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm1.geneSymbol.LENGTH)
head(dm1.geneSymbol.LENGTH)
```

---

dm1.genscan.LENGTH      *Transcript length data for the organism dm*

---

### Description

dm1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dm1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm1.genscan.LENGTH)
head(dm1.genscan.LENGTH)
```

---

dm1.refGene.LENGTH      *Transcript length data for the organism dm*

---

### Description

dm1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(dm1, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm1.refGene.LENGTH)
head(dm1.refGene.LENGTH)
```

---

dm2.geneid.LENGTH      *Transcript length data for the organism dm*

---

### Description

dm2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(dm2, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.geneid.LENGTH)
head(dm2.geneid.LENGTH)
```

---

dm2.geneSymbol.LENGTH      *Transcript length data for the organism dm*

---

### Description

dm2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(dm2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.geneSymbol.LENGTH)
head(dm2.geneSymbol.LENGTH)
```

---

dm2.genscan.LENGTH     *Transcript length data for the organism dm*

---

### Description

dm2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dm2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.genscan.LENGTH)
head(dm2.genscan.LENGTH)
```

---

dm2.nscanGene.LENGTH     *Transcript length data for the organism dm*

---

### Description

dm2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(dm2, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.nscanGene.LENGTH)
head(dm2.nscanGene.LENGTH)
```

---

dm2.refGene.LENGTH     *Transcript length data for the organism dm*

---

### Description

dm2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(dm2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.refGene.LENGTH)
head(dm2.refGene.LENGTH)
```

---

dm3.geneSymbol.LENGTH     *Transcript length data for the organism dm*

---

### Description

dm3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(dm3, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm3.geneSymbol.LENGTH)
head(dm3.geneSymbol.LENGTH)
```



---

`dm3.nscanPasaGene.LENGTH`*Transcript length data for the organism dm*

---

**Description**

dm3.nscanPasaGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanPasaGene table.

The data file was made by calling `downloadLengthFromUCSC(dm3, nscanPasaGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(dm3.nscanPasaGene.LENGTH)
head(dm3.nscanPasaGene.LENGTH)
```

---

`dm3.refGene.LENGTH`*Transcript length data for the organism dm*

---

**Description**

dm3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(dm3, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(dm3.refGene.LENGTH)
head(dm3.refGene.LENGTH)
```

---

dp2.genscan.LENGTH      *Transcript length data for the organism dp*

---

### Description

dp2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dp2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dp2.genscan.LENGTH)
head(dp2.genscan.LENGTH)
```

---

dp2.xenoRefGene.LENGTH      *Transcript length data for the organism dp*

---

### Description

dp2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(dp2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dp2.xenoRefGene.LENGTH)
head(dp2.xenoRefGene.LENGTH)
```

---

dp3.geneid.LENGTH      *Transcript length data for the organism dp*

---

### Description

dp3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(dp3, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dp3.geneid.LENGTH)
head(dp3.geneid.LENGTH)
```

---

dp3.genscan.LENGTH      *Transcript length data for the organism dp*

---

### Description

dp3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dp3, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dp3.genscan.LENGTH)
head(dp3.genscan.LENGTH)
```

---

```
dp3.xenoRefGene.LENGTH
```

*Transcript length data for the organism dp*

---

### Description

dp3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(dp3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dp3.xenoRefGene.LENGTH)
head(dp3.xenoRefGene.LENGTH)
```

---

```
droAna1.geneid.LENGTH
```

*Transcript length data for the organism droAna*

---

### Description

droAna1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droAna1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droAna1.geneid.LENGTH)
head(droAna1.geneid.LENGTH)
```

---

```
droAna1.genscan.LENGTH
```

*Transcript length data for the organism droAna*

---

### Description

droAna1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droAna1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droAna1.genscan.LENGTH)
head(droAna1.genscan.LENGTH)
```

---

```
droAna1.xenoRefGene.LENGTH
```

*Transcript length data for the organism droAna*

---

### Description

droAna1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droAna1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droAna1.xenoRefGene.LENGTH)
head(droAna1.xenoRefGene.LENGTH)
```

---

```
droAna2.genscan.LENGTH
```

*Transcript length data for the organism droAna*

---

### Description

droAna2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droAna2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droAna2.genscan.LENGTH)
head(droAna2.genscan.LENGTH)
```

---

```
droAna2.xenoRefGene.LENGTH
```

*Transcript length data for the organism droAna*

---

### Description

droAna2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droAna2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droAna2.xenoRefGene.LENGTH)
head(droAna2.xenoRefGene.LENGTH)
```

---

```
droEre1.genscan.LENGTH
```

*Transcript length data for the organism droEre*

---

### Description

droEre1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droEre1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droEre1.genscan.LENGTH)
head(droEre1.genscan.LENGTH)
```

---

```
droEre1.xenoRefGene.LENGTH
```

*Transcript length data for the organism droEre*

---

### Description

droEre1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droEre1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droEre1.xenoRefGene.LENGTH)
head(droEre1.xenoRefGene.LENGTH)
```

---

```
droGri1.genscan.LENGTH
```

*Transcript length data for the organism droGri*

---

### Description

droGri1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droGri1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droGri1.genscan.LENGTH)
head(droGri1.genscan.LENGTH)
```

---

```
droGri1.xenoRefGene.LENGTH
```

*Transcript length data for the organism droGri*

---

### Description

droGri1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droGri1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droGri1.xenoRefGene.LENGTH)
head(droGri1.xenoRefGene.LENGTH)
```



---

droMoj1.geneid.LENGTH *Transcript length data for the organism droMoj*

---

### Description

droMoj1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droMoj1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droMoj1.geneid.LENGTH)
head(droMoj1.geneid.LENGTH)
```

---

droMoj1.genscan.LENGTH  
*Transcript length data for the organism droMoj*

---

### Description

droMoj1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droMoj1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droMoj1.genscan.LENGTH)
head(droMoj1.genscan.LENGTH)
```

---

```
droMoj1.xenoRefGene.LENGTH
```

*Transcript length data for the organism droMoj*

---

### Description

droMoj1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droMoj1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droMoj1.xenoRefGene.LENGTH)
head(droMoj1.xenoRefGene.LENGTH)
```

---

```
droMoj2.genscan.LENGTH
```

*Transcript length data for the organism droMoj*

---

### Description

droMoj2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droMoj2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droMoj2.genscan.LENGTH)
head(droMoj2.genscan.LENGTH)
```

---

```
droMoj2.xenoRefGene.LENGTH
```

*Transcript length data for the organism droMoj*

---

### Description

droMoj2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droMoj2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droMoj2.xenoRefGene.LENGTH)
head(droMoj2.xenoRefGene.LENGTH)
```

---

```
droPer1.genscan.LENGTH
```

*Transcript length data for the organism droPer*

---

### Description

droPer1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droPer1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droPer1.genscan.LENGTH)
head(droPer1.genscan.LENGTH)
```

---

```
droPer1.xenoRefGene.LENGTH
```

*Transcript length data for the organism droPer*

---

### Description

droPer1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droPer1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droPer1.xenoRefGene.LENGTH)
head(droPer1.xenoRefGene.LENGTH)
```

---

```
droSec1.genscan.LENGTH
```

*Transcript length data for the organism droSec*

---

### Description

droSec1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droSec1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droSec1.genscan.LENGTH)
head(droSec1.genscan.LENGTH)
```

---

```
droSec1.xenoRefGene.LENGTH
```

*Transcript length data for the organism droSec*

---

### Description

droSec1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droSec1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droSec1.xenoRefGene.LENGTH)
head(droSec1.xenoRefGene.LENGTH)
```

---

```
droSim1.geneid.LENGTH
```

*Transcript length data for the organism droSim*

---

### Description

droSim1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droSim1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droSim1.geneid.LENGTH)
head(droSim1.geneid.LENGTH)
```

---

```
droSim1.genscan.LENGTH
```

*Transcript length data for the organism droSim*

---

### Description

droSim1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droSim1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droSim1.genscan.LENGTH)
head(droSim1.genscan.LENGTH)
```

---

```
droSim1.xenoRefGene.LENGTH
```

*Transcript length data for the organism droSim*

---

### Description

droSim1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droSim1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droSim1.xenoRefGene.LENGTH)
head(droSim1.xenoRefGene.LENGTH)
```

---

droVir1.geneid.LENGTH *Transcript length data for the organism droVir*

---

### Description

droVir1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droVir1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droVir1.geneid.LENGTH)
head(droVir1.geneid.LENGTH)
```

---

droVir1.genscan.LENGTH  
*Transcript length data for the organism droVir*

---

### Description

droVir1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droVir1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droVir1.genscan.LENGTH)
head(droVir1.genscan.LENGTH)
```

---

```
droVir1.xenoRefGene.LENGTH
```

*Transcript length data for the organism droVir*

---

### Description

droVir1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droVir1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droVir1.xenoRefGene.LENGTH)
head(droVir1.xenoRefGene.LENGTH)
```

---

```
droVir2.genscan.LENGTH
```

*Transcript length data for the organism droVir*

---

### Description

droVir2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droVir2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droVir2.genscan.LENGTH)
head(droVir2.genscan.LENGTH)
```



---

`droVir2.xenoRefGene.LENGTH`*Transcript length data for the organism droVir*

---

**Description**

droVir2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droVir2, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(droVir2.xenoRefGene.LENGTH)
head(droVir2.xenoRefGene.LENGTH)
```

---

`droYak1.geneid.LENGTH` *Transcript length data for the organism droYak*

---

**Description**

droYak1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droYak1, geneid)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(droYak1.geneid.LENGTH)
head(droYak1.geneid.LENGTH)
```

---

```
droYak1.genscan.LENGTH
```

*Transcript length data for the organism droYak*

---

### Description

droYak1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droYak1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droYak1.genscan.LENGTH)
head(droYak1.genscan.LENGTH)
```

---

```
droYak1.xenoRefGene.LENGTH
```

*Transcript length data for the organism droYak*

---

### Description

droYak1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droYak1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droYak1.xenoRefGene.LENGTH)
head(droYak1.xenoRefGene.LENGTH)
```

---

```
droYak2.genscan.LENGTH
```

*Transcript length data for the organism droYak*

---

### Description

droYak2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droYak2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droYak2.genscan.LENGTH)
head(droYak2.genscan.LENGTH)
```

---

```
droYak2.xenoRefGene.LENGTH
```

*Transcript length data for the organism droYak*

---

### Description

droYak2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droYak2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droYak2.xenoRefGene.LENGTH)
head(droYak2.xenoRefGene.LENGTH)
```

---

equCab1.geneid.LENGTH *Transcript length data for the organism equCab*

---

### Description

equCab1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(equCab1.geneid.LENGTH)
head(equCab1.geneid.LENGTH)
```

---

equCab1.geneSymbol.LENGTH  
*Transcript length data for the organism equCab*

---

### Description

equCab1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(equCab1.geneSymbol.LENGTH)
head(equCab1.geneSymbol.LENGTH)
```

---

`equCab1.nscanGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

equCab1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab1.nscanGene.LENGTH)
head(equCab1.nscanGene.LENGTH)
```

---

`equCab1.refGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

equCab1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab1.refGene.LENGTH)
head(equCab1.refGene.LENGTH)
```

---

equCab1.sgpGene.LENGTH

*Transcript length data for the organism equCab*

---

### Description

equCab1.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(equCab1.sgpGene.LENGTH)
head(equCab1.sgpGene.LENGTH)
```

---

equCab2.ensGene.LENGTH

*Transcript length data for the organism equCab*

---

### Description

equCab2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(equCab2.ensGene.LENGTH)
head(equCab2.ensGene.LENGTH)
```

---

`equCab2.geneSymbol.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

`equCab2.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab2.geneSymbol.LENGTH)
head(equCab2.geneSymbol.LENGTH)
```

---

`equCab2.nscanGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

`equCab2.nscanGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `nscanGene` table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab2.nscanGene.LENGTH)
head(equCab2.nscanGene.LENGTH)
```

---

```
equCab2.refGene.LENGTH
```

*Transcript length data for the organism equCab*

---

### Description

equCab2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(equCab2.refGene.LENGTH)
head(equCab2.refGene.LENGTH)
```

---

```
equCab2.xenoRefGene.LENGTH
```

*Transcript length data for the organism equCab*

---

### Description

equCab2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(equCab2.xenoRefGene.LENGTH)
head(equCab2.xenoRefGene.LENGTH)
```



---

```
felCat3.ensGene.LENGTH
```

*Transcript length data for the organism felCat*

---

### Description

felCat3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(felCat3.ensGene.LENGTH)
head(felCat3.ensGene.LENGTH)
```

---

```
felCat3.geneid.LENGTH
```

*Transcript length data for the organism felCat*

---

### Description

felCat3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(felCat3.geneid.LENGTH)
head(felCat3.geneid.LENGTH)
```

```
felCat3.geneSymbol.LENGTH
```

*Transcript length data for the organism felCat*

---

### Description

felCat3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(felCat3.geneSymbol.LENGTH)
head(felCat3.geneSymbol.LENGTH)
```

---

```
felCat3.genscan.LENGTH
```

*Transcript length data for the organism felCat*

---

### Description

felCat3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(felCat3.genscan.LENGTH)
head(felCat3.genscan.LENGTH)
```

---

```
felCat3.nscanGene.LENGTH
```

*Transcript length data for the organism felCat*

---

### Description

felCat3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(felCat3.nscanGene.LENGTH)
head(felCat3.nscanGene.LENGTH)
```

---

```
felCat3.refGene.LENGTH
```

*Transcript length data for the organism felCat*

---

### Description

felCat3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(felCat3.refGene.LENGTH)
head(felCat3.refGene.LENGTH)
```

---

```
felCat3.sgpGene.LENGTH
```

*Transcript length data for the organism felCat*

---

### Description

felCat3.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(felCat3.sgpGene.LENGTH)
head(felCat3.sgpGene.LENGTH)
```

---

```
felCat3.xenoRefGene.LENGTH
```

*Transcript length data for the organism felCat*

---

### Description

felCat3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(felCat3.xenoRefGene.LENGTH)
head(felCat3.xenoRefGene.LENGTH)
```

---

fr1.ensGene.LENGTH      *Transcript length data for the organism fr*

---

### Description

fr1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(fr1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(fr1.ensGene.LENGTH)
head(fr1.ensGene.LENGTH)
```

---

fr1.genscan.LENGTH      *Transcript length data for the organism fr*

---

### Description

fr1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(fr1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(fr1.genscan.LENGTH)
head(fr1.genscan.LENGTH)
```

---

fr2.ensGene.LENGTH      *Transcript length data for the organism fr*

---

### Description

fr2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(fr2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(fr2.ensGene.LENGTH)
head(fr2.ensGene.LENGTH)
```

---

galGal2.ensGene.LENGTH      *Transcript length data for the organism galGal*

---

### Description

galGal2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal2.ensGene.LENGTH)
head(galGal2.ensGene.LENGTH)
```

---

galGal2.geneid.LENGTH *Transcript length data for the organism galGal*

---

### Description

galGal2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal2.geneid.LENGTH)
head(galGal2.geneid.LENGTH)
```

---

galGal2.geneSymbol.LENGTH  
*Transcript length data for the organism galGal*

---

### Description

galGal2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal2.geneSymbol.LENGTH)
head(galGal2.geneSymbol.LENGTH)
```

---

```
galGal2.genscan.LENGTH
```

*Transcript length data for the organism galGal*

---

### Description

galGal2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal2.genscan.LENGTH)
head(galGal2.genscan.LENGTH)
```

---

```
galGal2.refGene.LENGTH
```

*Transcript length data for the organism galGal*

---

### Description

galGal2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal2.refGene.LENGTH)
head(galGal2.refGene.LENGTH)
```



---

`galGal2.sgpGene.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal2.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, sgpGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(galGal2.sgpGene.LENGTH)
head(galGal2.sgpGene.LENGTH)
```

---

`galGal3.ensGene.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(galGal3.ensGene.LENGTH)
head(galGal3.ensGene.LENGTH)
```

---

```
galGal3.geneSymbol.LENGTH
```

*Transcript length data for the organism galGal*

---

### Description

galGal3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal3.geneSymbol.LENGTH)
head(galGal3.geneSymbol.LENGTH)
```

---

```
galGal3.genscan.LENGTH
```

*Transcript length data for the organism galGal*

---

### Description

galGal3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal3.genscan.LENGTH)
head(galGal3.genscan.LENGTH)
```

---

```
galGal3.nscanGene.LENGTH
```

*Transcript length data for the organism galGal*

---

### Description

galGal3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal3.nscanGene.LENGTH)
head(galGal3.nscanGene.LENGTH)
```

---

```
galGal3.refGene.LENGTH
```

*Transcript length data for the organism galGal*

---

### Description

galGal3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal3.refGene.LENGTH)
head(galGal3.refGene.LENGTH)
```

---

```
galGal3.xenoRefGene.LENGTH
```

*Transcript length data for the organism galGal*

---

### Description

galGal3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal3.xenoRefGene.LENGTH)
head(galGal3.xenoRefGene.LENGTH)
```

---

```
gasAcu1.ensGene.LENGTH
```

*Transcript length data for the organism gasAcu*

---

### Description

gasAcu1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(gasAcu1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(gasAcu1.ensGene.LENGTH)
head(gasAcu1.ensGene.LENGTH)
```

---

```
gasAcu1.nscanGene.LENGTH
```

*Transcript length data for the organism gasAcu*

---

### Description

gasAcu1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(gasAcu1, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(gasAcu1.nscanGene.LENGTH)
head(gasAcu1.nscanGene.LENGTH)
```

---

```
hg16.acembly.LENGTH
```

*Transcript length data for the organism hg*

---

### Description

hg16.acembly.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acembly table.

The data file was made by calling `downloadLengthFromUCSC(hg16, acembly)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.acembly.LENGTH)
head(hg16.acembly.LENGTH)
```

---

hg16.ensGene.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg16.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.ensGene.LENGTH)
head(hg16.ensGene.LENGTH)
```

---

hg16.exoniphy.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg16.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg16, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.exoniphy.LENGTH)
head(hg16.exoniphy.LENGTH)
```

---

hg16.geneid.LENGTH      *Transcript length data for the organism hg*

---

### Description

hg16.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(hg16, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.geneid.LENGTH)
head(hg16.geneid.LENGTH)
```

---

hg16.geneSymbol.LENGTH      *Transcript length data for the organism hg*

---

### Description

hg16.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg16, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.geneSymbol.LENGTH)
head(hg16.geneSymbol.LENGTH)
```

---

hg16.genscan.LENGTH *Transcript length data for the organism hg*

---

### Description

hg16.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(hg16, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.genscan.LENGTH)
head(hg16.genscan.LENGTH)
```

---

hg16.knownGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg16.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.knownGene.LENGTH)
head(hg16.knownGene.LENGTH)
```



---

hg16.refGene.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg16.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.refGene.LENGTH)
head(hg16.refGene.LENGTH)
```

---

hg16.sgpGene.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg16.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.sgpGene.LENGTH)
head(hg16.sgpGene.LENGTH)
```

---

hg17.acembly.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg17.acembly.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acembly table.

The data file was made by calling `downloadLengthFromUCSC(hg17, acembly)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.acembly.LENGTH)
head(hg17.acembly.LENGTH)
```

---

hg17.acescan.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg17.acescan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acescan table.

The data file was made by calling `downloadLengthFromUCSC(hg17, acescan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.acescan.LENGTH)
head(hg17.acescan.LENGTH)
```

---

hg17.ccdsGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg17.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, ccdsGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.ccdsGene.LENGTH)
head(hg17.ccdsGene.LENGTH)
```

---

hg17.ensGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg17.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.ensGene.LENGTH)
head(hg17.ensGene.LENGTH)
```

---

hg17.exoniphy.LENGTH *Transcript length data for the organism hg*

---

### Description

hg17.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg17, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.exoniphy.LENGTH)
head(hg17.exoniphy.LENGTH)
```

---

hg17.geneid.LENGTH *Transcript length data for the organism hg*

---

### Description

hg17.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(hg17, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.geneid.LENGTH)
head(hg17.geneid.LENGTH)
```

---

```
hg17.geneSymbol.LENGTH
```

*Transcript length data for the organism hg*

---

### Description

hg17.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg17, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.geneSymbol.LENGTH)
head(hg17.geneSymbol.LENGTH)
```

---

```
hg17.genscan.LENGTH
```

*Transcript length data for the organism hg*

---

### Description

hg17.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(hg17, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.genscan.LENGTH)
head(hg17.genscan.LENGTH)
```

---

hg17.knownGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg17.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.knownGene.LENGTH)
head(hg17.knownGene.LENGTH)
```

---

hg17.refGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg17.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.refGene.LENGTH)
head(hg17.refGene.LENGTH)
```

---

hg17.sgpGene.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg17.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.sgpGene.LENGTH)
head(hg17.sgpGene.LENGTH)
```

---

hg17.vegaGene.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg17.vegaGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, vegaGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.vegaGene.LENGTH)
head(hg17.vegaGene.LENGTH)
```

---

hg17.vegaPseudoGene.LENGTH

*Transcript length data for the organism hg*

---

### Description

hg17.vegaPseudoGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaPseudoGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, vegaPseudoGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.vegaPseudoGene.LENGTH)
head(hg17.vegaPseudoGene.LENGTH)
```

---

hg17.xenoRefGene.LENGTH

*Transcript length data for the organism hg*

---

### Description

hg17.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.xenoRefGene.LENGTH)
head(hg17.xenoRefGene.LENGTH)
```



---

hg18.acembly.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.acembly.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acembly table.

The data file was made by calling `downloadLengthFromUCSC(hg18, acembly)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.acembly.LENGTH)
head(hg18.acembly.LENGTH)
```

---

hg18.acescan.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.acescan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acescan table.

The data file was made by calling `downloadLengthFromUCSC(hg18, acescan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.acescan.LENGTH)
head(hg18.acescan.LENGTH)
```

---

hg18.ccdsGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg18.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, ccdsGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.ccdsGene.LENGTH)
head(hg18.ccdsGene.LENGTH)
```

---

hg18.ensGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg18.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.ensGene.LENGTH)
head(hg18.ensGene.LENGTH)
```

---

hg18.exoniphy.LENGTH *Transcript length data for the organism hg*

---

### Description

hg18.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg18, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.exoniphy.LENGTH)
head(hg18.exoniphy.LENGTH)
```

---

hg18.geneid.LENGTH *Transcript length data for the organism hg*

---

### Description

hg18.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(hg18, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.geneid.LENGTH)
head(hg18.geneid.LENGTH)
```

---

```
hg18.geneSymbol.LENGTH
```

*Transcript length data for the organism hg*

---

### Description

hg18.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg18, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.geneSymbol.LENGTH)
head(hg18.geneSymbol.LENGTH)
```

---

```
hg18.genscan.LENGTH
```

*Transcript length data for the organism hg*

---

### Description

hg18.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(hg18, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.genscan.LENGTH)
head(hg18.genscan.LENGTH)
```

---

hg18.knownGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg18.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.knownGene.LENGTH)
head(hg18.knownGene.LENGTH)
```

---

hg18.knownGeneOld3.LENGTH  
*Transcript length data for the organism hg*

---

### Description

hg18.knownGeneOld3.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGeneOld3 table.

The data file was made by calling `downloadLengthFromUCSC(hg18, knownGeneOld3)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.knownGeneOld3.LENGTH)
head(hg18.knownGeneOld3.LENGTH)
```

---

hg18.refGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.refGene.LENGTH)
head(hg18.refGene.LENGTH)
```

---

hg18.sgpGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.sgpGene.LENGTH)
head(hg18.sgpGene.LENGTH)
```

---

hg18.sibGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.sibGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sibGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, sibGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.sibGene.LENGTH)
head(hg18.sibGene.LENGTH)
```

---

hg18.xenoRefGene.LENGTH  
*Transcript length data for the organism hg*

---

### Description

hg18.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.xenoRefGene.LENGTH)
head(hg18.xenoRefGene.LENGTH)
```

---

hg19.ccdsGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg19.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, ccdsGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.ccdsGene.LENGTH)
head(hg19.ccdsGene.LENGTH)
```

---

hg19.ensGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg19.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.ensGene.LENGTH)
head(hg19.ensGene.LENGTH)
```



---

hg19.exoniphy.LENGTH *Transcript length data for the organism hg*

---

### Description

hg19.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg19, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.exoniphy.LENGTH)
head(hg19.exoniphy.LENGTH)
```

---

hg19.geneSymbol.LENGTH  
*Transcript length data for the organism hg*

---

### Description

hg19.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg19, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.geneSymbol.LENGTH)
head(hg19.geneSymbol.LENGTH)
```

---

hg19.knownGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg19.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.knownGene.LENGTH)
head(hg19.knownGene.LENGTH)
```

---

hg19.nscanGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg19.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.nscanGene.LENGTH)
head(hg19.nscanGene.LENGTH)
```

---

hg19.refGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg19.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.refGene.LENGTH)
head(hg19.refGene.LENGTH)
```

---

hg19.xenoRefGene.LENGTH  
*Transcript length data for the organism hg*

---

### Description

hg19.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.xenoRefGene.LENGTH)
head(hg19.xenoRefGene.LENGTH)
```

---

```
loxAfr3.xenoRefGene.LENGTH
```

*Transcript length data for the organism loxAfr*

---

### Description

loxAfr3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(loxAfr3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(loxAfr3.xenoRefGene.LENGTH)
head(loxAfr3.xenoRefGene.LENGTH)
```

---

```
mm7.ensGene.LENGTH
```

*Transcript length data for the organism mm*

---

### Description

mm7.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.ensGene.LENGTH)
head(mm7.ensGene.LENGTH)
```

---

mm7.geneid.LENGTH      *Transcript length data for the organism mm*

---

### Description

mm7.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(mm7, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.geneid.LENGTH)
head(mm7.geneid.LENGTH)
```

---

mm7.geneSymbol.LENGTH      *Transcript length data for the organism mm*

---

### Description

mm7.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(mm7, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.geneSymbol.LENGTH)
head(mm7.geneSymbol.LENGTH)
```

---

mm7.genscan.LENGTH     *Transcript length data for the organism mm*

---

### Description

mm7.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(mm7, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.genscan.LENGTH)
head(mm7.genscan.LENGTH)
```

---

mm7.knownGene.LENGTH     *Transcript length data for the organism mm*

---

### Description

mm7.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.knownGene.LENGTH)
head(mm7.knownGene.LENGTH)
```

---

mm7.refGene.LENGTH      *Transcript length data for the organism mm*

---

### Description

mm7.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.refGene.LENGTH)
head(mm7.refGene.LENGTH)
```

---

mm7.sgpGene.LENGTH      *Transcript length data for the organism mm*

---

### Description

mm7.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.sgpGene.LENGTH)
head(mm7.sgpGene.LENGTH)
```

---

mm7.xenoRefGene.LENGTH

*Transcript length data for the organism mm*

---

### Description

mm7.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.xenoRefGene.LENGTH)
head(mm7.xenoRefGene.LENGTH)
```

---

mm8.ccdsGene.LENGTH

*Transcript length data for the organism mm*

---

### Description

mm8.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, ccdsGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.ccdsGene.LENGTH)
head(mm8.ccdsGene.LENGTH)
```



---

mm8.ensGene.LENGTH      *Transcript length data for the organism mm*

---

### Description

mm8.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.ensGene.LENGTH)
head(mm8.ensGene.LENGTH)
```

---

mm8.geneid.LENGTH      *Transcript length data for the organism mm*

---

### Description

mm8.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(mm8, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.geneid.LENGTH)
head(mm8.geneid.LENGTH)
```

---

mm8.geneSymbol.LENGTH *Transcript length data for the organism mm*

---

### Description

mm8.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(mm8, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.geneSymbol.LENGTH)
head(mm8.geneSymbol.LENGTH)
```

---

mm8.genscan.LENGTH *Transcript length data for the organism mm*

---

### Description

mm8.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(mm8, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.genscan.LENGTH)
head(mm8.genscan.LENGTH)
```

---

mm8.knownGene.LENGTH *Transcript length data for the organism mm*

---

### Description

mm8.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.knownGene.LENGTH)
head(mm8.knownGene.LENGTH)
```

---

mm8.nscanGene.LENGTH *Transcript length data for the organism mm*

---

### Description

mm8.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.nscanGene.LENGTH)
head(mm8.nscanGene.LENGTH)
```

---

mm8.refGene.LENGTH      *Transcript length data for the organism mm*

---

### Description

mm8.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.refGene.LENGTH)
head(mm8.refGene.LENGTH)
```

---

mm8.sgpGene.LENGTH      *Transcript length data for the organism mm*

---

### Description

mm8.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.sgpGene.LENGTH)
head(mm8.sgpGene.LENGTH)
```

---

mm8.sibGene.LENGTH      *Transcript length data for the organism mm*

---

### Description

mm8.sibGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sibGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, sibGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.sibGene.LENGTH)
head(mm8.sibGene.LENGTH)
```

---

mm8.xenoRefGene.LENGTH      *Transcript length data for the organism mm*

---

### Description

mm8.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.xenoRefGene.LENGTH)
head(mm8.xenoRefGene.LENGTH)
```

---

mm9.acembly.LENGTH     *Transcript length data for the organism mm*

---

### Description

mm9.acembly.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acembly table.

The data file was made by calling `downloadLengthFromUCSC(mm9, acembly)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.acembly.LENGTH)
head(mm9.acembly.LENGTH)
```

---

mm9.ccdsGene.LENGTH     *Transcript length data for the organism mm*

---

### Description

mm9.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, ccdsGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.ccdsGene.LENGTH)
head(mm9.ccdsGene.LENGTH)
```

---

mm9.ensGene.LENGTH     *Transcript length data for the organism mm*

---

### Description

mm9.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.ensGene.LENGTH)
head(mm9.ensGene.LENGTH)
```

---

mm9.exoniphy.LENGTH     *Transcript length data for the organism mm*

---

### Description

mm9.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(mm9, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.exoniphy.LENGTH)
head(mm9.exoniphy.LENGTH)
```

---

mm9.geneid.LENGTH      *Transcript length data for the organism mm*

---

### Description

mm9.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(mm9, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.geneid.LENGTH)
head(mm9.geneid.LENGTH)
```

---

mm9.geneSymbol.LENGTH      *Transcript length data for the organism mm*

---

### Description

mm9.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(mm9, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.geneSymbol.LENGTH)
head(mm9.geneSymbol.LENGTH)
```



---

mm9.genscan.LENGTH     *Transcript length data for the organism mm*

---

### Description

mm9.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(mm9, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.genscan.LENGTH)
head(mm9.genscan.LENGTH)
```

---

mm9.knownGene.LENGTH     *Transcript length data for the organism mm*

---

### Description

mm9.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.knownGene.LENGTH)
head(mm9.knownGene.LENGTH)
```

---

mm9.nscanGene.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm9.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.nscanGene.LENGTH)
head(mm9.nscanGene.LENGTH)
```

---

mm9.refGene.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm9.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.refGene.LENGTH)
head(mm9.refGene.LENGTH)
```

---

mm9.sgpGene.LENGTH      *Transcript length data for the organism mm*

---

### Description

mm9.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.sgpGene.LENGTH)
head(mm9.sgpGene.LENGTH)
```

---

mm9.xenoRefGene.LENGTH      *Transcript length data for the organism mm*

---

### Description

mm9.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.xenoRefGene.LENGTH)
head(mm9.xenoRefGene.LENGTH)
```

---

```
monDom1.genscan.LENGTH
```

*Transcript length data for the organism monDom*

---

### Description

monDom1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(monDom1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom1.genscan.LENGTH)
head(monDom1.genscan.LENGTH)
```

---

```
monDom4.ensGene.LENGTH
```

*Transcript length data for the organism monDom*

---

### Description

monDom4.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom4.ensGene.LENGTH)
head(monDom4.ensGene.LENGTH)
```

---

```
monDom4.geneSymbol.LENGTH
```

*Transcript length data for the organism monDom*

---

### Description

monDom4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom4.geneSymbol.LENGTH)
head(monDom4.geneSymbol.LENGTH)
```

---

```
monDom4.genscan.LENGTH
```

*Transcript length data for the organism monDom*

---

### Description

monDom4.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom4.genscan.LENGTH)
head(monDom4.genscan.LENGTH)
```

---

monDom4.nscanGene.LENGTH

*Transcript length data for the organism monDom*

---

### Description

monDom4.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom4.nscanGene.LENGTH)
head(monDom4.nscanGene.LENGTH)
```

---

monDom4.refGene.LENGTH

*Transcript length data for the organism monDom*

---

### Description

monDom4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom4.refGene.LENGTH)
head(monDom4.refGene.LENGTH)
```

---

```
monDom4.xenoRefGene.LENGTH
```

*Transcript length data for the organism monDom*

---

### Description

monDom4.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom4.xenoRefGene.LENGTH)
head(monDom4.xenoRefGene.LENGTH)
```

---

```
monDom5.ensGene.LENGTH
```

*Transcript length data for the organism monDom*

---

### Description

monDom5.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom5.ensGene.LENGTH)
head(monDom5.ensGene.LENGTH)
```

---

```
monDom5.geneSymbol.LENGTH
```

*Transcript length data for the organism monDom*

---

### Description

monDom5.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom5.geneSymbol.LENGTH)
head(monDom5.geneSymbol.LENGTH)
```

---

```
monDom5.genscan.LENGTH
```

*Transcript length data for the organism monDom*

---

### Description

monDom5.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom5.genscan.LENGTH)
head(monDom5.genscan.LENGTH)
```



---

```
monDom5.nscanGene.LENGTH
```

*Transcript length data for the organism monDom*

---

### Description

monDom5.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom5.nscanGene.LENGTH)
head(monDom5.nscanGene.LENGTH)
```

---

```
monDom5.refGene.LENGTH
```

*Transcript length data for the organism monDom*

---

### Description

monDom5.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom5.refGene.LENGTH)
head(monDom5.refGene.LENGTH)
```

---

```
monDom5.xenoRefGene.LENGTH
```

*Transcript length data for the organism monDom*

---

### Description

monDom5.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom5.xenoRefGene.LENGTH)
head(monDom5.xenoRefGene.LENGTH)
```

---

```
ornAna1.ensGene.LENGTH
```

*Transcript length data for the organism ornAna*

---

### Description

ornAna1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ornAna1.ensGene.LENGTH)
head(ornAna1.ensGene.LENGTH)
```

---

```
ornAna1.geneSymbol.LENGTH
```

*Transcript length data for the organism ornAna*

---

### Description

ornAna1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ornAna1.geneSymbol.LENGTH)
head(ornAna1.geneSymbol.LENGTH)
```

---

```
ornAna1.refGene.LENGTH
```

*Transcript length data for the organism ornAna*

---

### Description

ornAna1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ornAna1.refGene.LENGTH)
head(ornAna1.refGene.LENGTH)
```

---

```
ornAna1.xenoRefGene.LENGTH
```

*Transcript length data for the organism ornAna*

---

### Description

ornAna1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ornAna1.xenoRefGene.LENGTH)
head(ornAna1.xenoRefGene.LENGTH)
```

---

```
oryLat2.ensGene.LENGTH
```

*Transcript length data for the organism oryLat*

---

### Description

oryLat2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(oryLat2.ensGene.LENGTH)
head(oryLat2.ensGene.LENGTH)
```

---

```
oryLat2.geneSymbol.LENGTH
```

*Transcript length data for the organism oryLat*

---

### Description

oryLat2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(oryLat2.geneSymbol.LENGTH)
head(oryLat2.geneSymbol.LENGTH)
```

---

```
oryLat2.refGene.LENGTH
```

*Transcript length data for the organism oryLat*

---

### Description

oryLat2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(oryLat2.refGene.LENGTH)
head(oryLat2.refGene.LENGTH)
```

---

```
oryLat2.xenoRefGene.LENGTH
```

*Transcript length data for the organism oryLat*

---

### Description

oryLat2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(oryLat2.xenoRefGene.LENGTH)
head(oryLat2.xenoRefGene.LENGTH)
```

---

```
panTro1.ensGene.LENGTH
```

*Transcript length data for the organism panTro*

---

### Description

panTro1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro1.ensGene.LENGTH)
head(panTro1.ensGene.LENGTH)
```

---

panTro1.geneid.LENGTH *Transcript length data for the organism panTro*

---

### Description

panTro1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro1.geneid.LENGTH)
head(panTro1.geneid.LENGTH)
```

---

panTro1.genscan.LENGTH  
*Transcript length data for the organism panTro*

---

### Description

panTro1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro1.genscan.LENGTH)
head(panTro1.genscan.LENGTH)
```

---

```
panTro1.xenoRefGene.LENGTH
```

*Transcript length data for the organism panTro*

---

### Description

panTro1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro1.xenoRefGene.LENGTH)
head(panTro1.xenoRefGene.LENGTH)
```

---

```
panTro2.ensGene.LENGTH
```

*Transcript length data for the organism panTro*

---

### Description

panTro2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro2.ensGene.LENGTH)
head(panTro2.ensGene.LENGTH)
```



---

```
panTro2.geneSymbol.LENGTH
```

*Transcript length data for the organism panTro*

---

### Description

panTro2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro2.geneSymbol.LENGTH)
head(panTro2.geneSymbol.LENGTH)
```

---

```
panTro2.genscan.LENGTH
```

*Transcript length data for the organism panTro*

---

### Description

panTro2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro2.genscan.LENGTH)
head(panTro2.genscan.LENGTH)
```

---

```
panTro2.nscanGene.LENGTH
```

*Transcript length data for the organism panTro*

---

### Description

panTro2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro2.nscanGene.LENGTH)
head(panTro2.nscanGene.LENGTH)
```

---

```
panTro2.refGene.LENGTH
```

*Transcript length data for the organism panTro*

---

### Description

panTro2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro2.refGene.LENGTH)
head(panTro2.refGene.LENGTH)
```

---

```
panTro2.xenoRefGene.LENGTH
```

*Transcript length data for the organism panTro*

---

### Description

panTro2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro2.xenoRefGene.LENGTH)
head(panTro2.xenoRefGene.LENGTH)
```

---

```
petMar1.xenoRefGene.LENGTH
```

*Transcript length data for the organism petMar*

---

### Description

petMar1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(petMar1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(petMar1.xenoRefGene.LENGTH)
head(petMar1.xenoRefGene.LENGTH)
```

---

```
ponAbe2.ensGene.LENGTH
```

*Transcript length data for the organism ponAbe*

---

### Description

ponAbe2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ponAbe2.ensGene.LENGTH)
head(ponAbe2.ensGene.LENGTH)
```

---

```
ponAbe2.geneSymbol.LENGTH
```

*Transcript length data for the organism ponAbe*

---

### Description

ponAbe2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ponAbe2.geneSymbol.LENGTH)
head(ponAbe2.geneSymbol.LENGTH)
```

---

```
ponAbe2.genscan.LENGTH
```

*Transcript length data for the organism ponAbe*

---

### Description

ponAbe2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ponAbe2.genscan.LENGTH)
head(ponAbe2.genscan.LENGTH)
```

---

```
ponAbe2.nscanGene.LENGTH
```

*Transcript length data for the organism ponAbe*

---

### Description

ponAbe2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ponAbe2.nscanGene.LENGTH)
head(ponAbe2.nscanGene.LENGTH)
```

---

```
ponAbe2.refGene.LENGTH
```

*Transcript length data for the organism ponAbe*

---

### Description

ponAbe2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ponAbe2.refGene.LENGTH)
head(ponAbe2.refGene.LENGTH)
```

---

```
ponAbe2.xenoRefGene.LENGTH
```

*Transcript length data for the organism ponAbe*

---

### Description

ponAbe2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ponAbe2.xenoRefGene.LENGTH)
head(ponAbe2.xenoRefGene.LENGTH)
```

---

```
priPac1.xenoRefGene.LENGTH
```

*Transcript length data for the organism priPac*

---

### Description

priPac1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(priPac1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(priPac1.xenoRefGene.LENGTH)
head(priPac1.xenoRefGene.LENGTH)
```

---

```
rheMac2.ensGene.LENGTH
```

*Transcript length data for the organism rheMac*

---

### Description

rheMac2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rheMac2.ensGene.LENGTH)
head(rheMac2.ensGene.LENGTH)
```

---

`rheMac2.geneid.LENGTH` *Transcript length data for the organism rheMac*

---

### Description

`rheMac2.geneid.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneid` table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rheMac2.geneid.LENGTH)
head(rheMac2.geneid.LENGTH)
```

---

`rheMac2.geneSymbol.LENGTH`  
*Transcript length data for the organism rheMac*

---

### Description

`rheMac2.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rheMac2.geneSymbol.LENGTH)
head(rheMac2.geneSymbol.LENGTH)
```



---

```
rheMac2.nscanGene.LENGTH
```

*Transcript length data for the organism rheMac*

---

### Description

rheMac2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rheMac2.nscanGene.LENGTH)
head(rheMac2.nscanGene.LENGTH)
```

---

```
rheMac2.refGene.LENGTH
```

*Transcript length data for the organism rheMac*

---

### Description

rheMac2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rheMac2.refGene.LENGTH)
head(rheMac2.refGene.LENGTH)
```

---

```
rheMac2.sgpGene.LENGTH
```

*Transcript length data for the organism rheMac*

---

### Description

rheMac2.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rheMac2.sgpGene.LENGTH)
head(rheMac2.sgpGene.LENGTH)
```

---

```
rheMac2.xenoRefGene.LENGTH
```

*Transcript length data for the organism rheMac*

---

### Description

rheMac2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rheMac2.xenoRefGene.LENGTH)
head(rheMac2.xenoRefGene.LENGTH)
```

---

rn3.ensGene.LENGTH      *Transcript length data for the organism rn*

---

### Description

rn3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.ensGene.LENGTH)
head(rn3.ensGene.LENGTH)
```

---

rn3.geneid.LENGTH      *Transcript length data for the organism rn*

---

### Description

rn3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(rn3, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.geneid.LENGTH)
head(rn3.geneid.LENGTH)
```

---

rn3.geneSymbol.LENGTH *Transcript length data for the organism rn*

---

### Description

rn3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(rn3, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.geneSymbol.LENGTH)
head(rn3.geneSymbol.LENGTH)
```

---

rn3.genscan.LENGTH *Transcript length data for the organism rn*

---

### Description

rn3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(rn3, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.genscan.LENGTH)
head(rn3.genscan.LENGTH)
```

---

rn3.knownGene.LENGTH *Transcript length data for the organism rn*

---

### Description

rn3.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.knownGene.LENGTH)
head(rn3.knownGene.LENGTH)
```

---

rn3.nscanGene.LENGTH *Transcript length data for the organism rn*

---

### Description

rn3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.nscanGene.LENGTH)
head(rn3.nscanGene.LENGTH)
```

---

rn3.refGene.LENGTH      *Transcript length data for the organism rn*

---

### Description

rn3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.refGene.LENGTH)
head(rn3.refGene.LENGTH)
```

---

rn3.sgpGene.LENGTH      *Transcript length data for the organism rn*

---

### Description

rn3.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.sgpGene.LENGTH)
head(rn3.sgpGene.LENGTH)
```

---

```
rn3.xenoRefGene.LENGTH
```

*Transcript length data for the organism rn*

---

### Description

rn3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.xenoRefGene.LENGTH)
head(rn3.xenoRefGene.LENGTH)
```

---

```
rn4.ensGene.LENGTH
```

*Transcript length data for the organism rn*

---

### Description

rn4.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.ensGene.LENGTH)
head(rn4.ensGene.LENGTH)
```

---

rn4.geneid.LENGTH      *Transcript length data for the organism rn*

---

### Description

rn4.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(rn4, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.geneid.LENGTH)
head(rn4.geneid.LENGTH)
```

---

rn4.geneSymbol.LENGTH      *Transcript length data for the organism rn*

---

### Description

rn4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(rn4, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.geneSymbol.LENGTH)
head(rn4.geneSymbol.LENGTH)
```



---

rn4.genscan.LENGTH     *Transcript length data for the organism rn*

---

### Description

rn4.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(rn4, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.genscan.LENGTH)
head(rn4.genscan.LENGTH)
```

---

rn4.knownGene.LENGTH     *Transcript length data for the organism rn*

---

### Description

rn4.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.knownGene.LENGTH)
head(rn4.knownGene.LENGTH)
```

---

rn4.nscanGene.LENGTH    *Transcript length data for the organism rn*

---

### Description

rn4.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.nscanGene.LENGTH)
head(rn4.nscanGene.LENGTH)
```

---

rn4.refGene.LENGTH    *Transcript length data for the organism rn*

---

### Description

rn4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.refGene.LENGTH)
head(rn4.refGene.LENGTH)
```

---

rn4.sgpGene.LENGTH      *Transcript length data for the organism rn*

---

### Description

rn4.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.sgpGene.LENGTH)
head(rn4.sgpGene.LENGTH)
```

---

rn4.xenoRefGene.LENGTH      *Transcript length data for the organism rn*

---

### Description

rn4.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.xenoRefGene.LENGTH)
head(rn4.xenoRefGene.LENGTH)
```

---

```
sacCer1.ensGene.LENGTH
```

*Transcript length data for the organism sacCer*

---

### Description

sacCer1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(sacCer1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(sacCer1.ensGene.LENGTH)
head(sacCer1.ensGene.LENGTH)
```

---

```
sacCer2.ensGene.LENGTH
```

*Transcript length data for the organism sacCer*

---

### Description

sacCer2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(sacCer2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(sacCer2.ensGene.LENGTH)
head(sacCer2.ensGene.LENGTH)
```

---

```
strPur1.geneSymbol.LENGTH
```

*Transcript length data for the organism strPur*

---

### Description

strPur1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(strPur1.geneSymbol.LENGTH)
head(strPur1.geneSymbol.LENGTH)
```

---

```
strPur1.genscan.LENGTH
```

*Transcript length data for the organism strPur*

---

### Description

strPur1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(strPur1.genscan.LENGTH)
head(strPur1.genscan.LENGTH)
```

---

```
strPur1.refGene.LENGTH
```

*Transcript length data for the organism strPur*

---

### Description

strPur1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(strPur1.refGene.LENGTH)
head(strPur1.refGene.LENGTH)
```

---

```
strPur1.xenoRefGene.LENGTH
```

*Transcript length data for the organism strPur*

---

### Description

strPur1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(strPur1.xenoRefGene.LENGTH)
head(strPur1.xenoRefGene.LENGTH)
```

---

```
strPur2.geneSymbol.LENGTH
```

*Transcript length data for the organism strPur*

---

### Description

strPur2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(strPur2.geneSymbol.LENGTH)
head(strPur2.geneSymbol.LENGTH)
```

---

```
strPur2.genscan.LENGTH
```

*Transcript length data for the organism strPur*

---

### Description

strPur2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(strPur2.genscan.LENGTH)
head(strPur2.genscan.LENGTH)
```

---

```
strPur2.refGene.LENGTH
```

*Transcript length data for the organism strPur*

---

### Description

strPur2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(strPur2.refGene.LENGTH)
head(strPur2.refGene.LENGTH)
```

---

```
strPur2.xenoRefGene.LENGTH
```

*Transcript length data for the organism strPur*

---

### Description

strPur2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(strPur2.xenoRefGene.LENGTH)
head(strPur2.xenoRefGene.LENGTH)
```



---

supportedGeneIDs	<i>Supported Gene IDs</i>
------------------	---------------------------

---

**Description**

Lists supported gene ID formats

**Usage**

```
supportedGeneIDs()
```

**Details**

Uses the supportedUCSCtables function from the GenomicFeatures package to obtain a list of gene ID formats available from the UCSC genome browser. The db column gives the gene ID formats which are provided to the id argument of various functions. The track and subtrack columns are the names of the UCSC track/subtrack from which information is fetched.

The GeneID column lists the "full name" of the gene ID format where available.

The final column, headed AvailableGenomes lists the genomes for which there is a local copy of the length information available for the gene ID format listed in the geneLenDataBase package.

**Value**

A data.frame containing supported gene ID formats.

**Author(s)**

Matthew D. Young <myoung@wehi.edu.au>

**Examples**

```
supportedGeneIDs()
```

---

supportedGenomes	<i>Supported Genomes</i>
------------------	--------------------------

---

**Description**

Lists supported genomes

**Usage**

```
supportedGenomes()
```

**Details**

Uses the ucscGenomes() function from the rtracklayer package to obtain a list of genomes available from the UCSC genome browser. The db column lists genomes as they are provided to the genome argument of various functions.

The final column, headed AvailableGeneIDs lists the gene ID formats for which there is a local copy of the length information available for the genome listed in the geneLenDataBase package.

**Value**

A data.frame containing supported genomes.

**Author(s)**

Matthew D. Young <myoung@wehi.edu.au>

**Examples**

```
supportedGenomes()
```

---

```
taeGut1.ensGene.LENGTH
```

*Transcript length data for the organism taeGut*

---

**Description**

taeGut1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(taeGut1.ensGene.LENGTH)
head(taeGut1.ensGene.LENGTH)
```

---

```
taeGut1.geneSymbol.LENGTH
```

*Transcript length data for the organism taeGut*

---

**Description**

taeGut1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(taeGut1.geneSymbol.LENGTH)
head(taeGut1.geneSymbol.LENGTH)
```

---

```
taeGut1.genscan.LENGTH
```

*Transcript length data for the organism taeGut*

---

**Description**

taeGut1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(taeGut1.genscan.LENGTH)
head(taeGut1.genscan.LENGTH)
```

---

```
taeGut1.nscanGene.LENGTH
```

*Transcript length data for the organism taeGut*

---

**Description**

taeGut1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, nscanGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(taeGut1.nscanGene.LENGTH)
head(taeGut1.nscanGene.LENGTH)
```

---

```
taeGut1.refGene.LENGTH
```

*Transcript length data for the organism taeGut*

---

### Description

taeGut1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(taeGut1.refGene.LENGTH)
head(taeGut1.refGene.LENGTH)
```

---

```
taeGut1.xenoRefGene.LENGTH
```

*Transcript length data for the organism taeGut*

---

### Description

taeGut1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(taeGut1.xenoRefGene.LENGTH)
head(taeGut1.xenoRefGene.LENGTH)
```

---

```
tetNig1.ensGene.LENGTH
```

*Transcript length data for the organism tetNig*

---

### Description

tetNig1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(tetNig1.ensGene.LENGTH)
head(tetNig1.ensGene.LENGTH)
```

---

```
tetNig1.geneid.LENGTH Transcript length data for the organism tetNig
```

---

### Description

tetNig1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(tetNig1.geneid.LENGTH)
head(tetNig1.geneid.LENGTH)
```

---

```
tetNig1.genscan.LENGTH
```

*Transcript length data for the organism tetNig*

---

### Description

tetNig1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(tetNig1.genscan.LENGTH)
head(tetNig1.genscan.LENGTH)
```

---

```
tetNig1.nscanGene.LENGTH
```

*Transcript length data for the organism tetNig*

---

### Description

tetNig1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(tetNig1.nscanGene.LENGTH)
head(tetNig1.nscanGene.LENGTH)
```

---

```
tetNig2.ensGene.LENGTH
```

*Transcript length data for the organism tetNig*

---

### Description

tetNig2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(tetNig2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(tetNig2.ensGene.LENGTH)
head(tetNig2.ensGene.LENGTH)
```

---

```
unfactor
```

*Purge factors*

---

### Description

Removes all factors from a variable in a sensible way.

### Usage

```
unfactor(var)
```

### Arguments

`var`                    The variable from which you want the factors removed.

### Details

As factors are their own type, to remove factors we must convert each level into another type. This is currently done using "typeless" behaviour: a factor is converted to a numeric vector if this can be done without inducing NAs, otherwise it is coerced using `as.character`. Currently supported types are: `/codefactor`, `/codedata.frame` and `/codelist`.

### Value

The variable with all factors converted to characters or numbers (see details).

### Author(s)

Matthew D. Young <[myoung@wehi.edu.au](mailto:myoung@wehi.edu.au)>

**Examples**

```
#A named factor
x <- factor(sample(1:6, 100, replace=TRUE))
names(x) <- paste("Roll.No", 1:100, sep='.')
x
unfactor(x)

#A data.frame
x <- data.frame(player <- c("Alice", "Bob", "Mary", "Fred"), score <- factor(c(9, 7, 8, 9)), stringsAsFactors=TRUE)
x$player
x$score
y <- unfactor(x)
y$player
y$score
```

---

xenTro1.genscan.LENGTH

*Transcript length data for the organism xenTro*

---

**Description**

xenTro1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(xenTro1, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(xenTro1.genscan.LENGTH)
head(xenTro1.genscan.LENGTH)
```

---

xenTro2.ensGene.LENGTH

*Transcript length data for the organism xenTro*

---

**Description**

xenTro2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, ensGene)` on the date on which the package was last updated.



**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(xenTro2.ensGene.LENGTH)
head(xenTro2.ensGene.LENGTH)
```

---

```
xenTro2.geneSymbol.LENGTH
```

*Transcript length data for the organism xenTro*

---

**Description**

xenTro2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(xenTro2.geneSymbol.LENGTH)
head(xenTro2.geneSymbol.LENGTH)
```

---

```
xenTro2.genscan.LENGTH
```

*Transcript length data for the organism xenTro*

---

**Description**

xenTro2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(xenTro2.genscan.LENGTH)
head(xenTro2.genscan.LENGTH)
```

---

`xenTro2.refGene.LENGTH`*Transcript length data for the organism xenTro*

---

**Description**

`xenTro2.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(xenTro2.refGene.LENGTH)
head(xenTro2.refGene.LENGTH)
```

# Index

## \*Topic **datasets**

anoCar1.ensGene.LENGTH, 8  
anoCar1.genscan.LENGTH, 9  
anoCar1.xenoRefGene.LENGTH, 9  
anoGam1.ensGene.LENGTH, 10  
anoGam1.geneid.LENGTH, 10  
anoGam1.genscan.LENGTH, 11  
apiMe11.genscan.LENGTH, 11  
apiMe12.ensGene.LENGTH, 12  
apiMe12.geneid.LENGTH, 12  
apiMe12.genscan.LENGTH, 13  
aplCa11.xenoRefGene.LENGTH, 13  
bosTau2.geneid.LENGTH, 14  
bosTau2.geneSymbol.LENGTH, 14  
bosTau2.genscan.LENGTH, 15  
bosTau2.refGene.LENGTH, 15  
bosTau2.sgpGene.LENGTH, 16  
bosTau3.ensGene.LENGTH, 16  
bosTau3.geneid.LENGTH, 17  
bosTau3.geneSymbol.LENGTH, 17  
bosTau3.genscan.LENGTH, 18  
bosTau3.refGene.LENGTH, 18  
bosTau3.sgpGene.LENGTH, 19  
bosTau4.ensGene.LENGTH, 19  
bosTau4.geneSymbol.LENGTH, 20  
bosTau4.genscan.LENGTH, 20  
bosTau4.nscanGene.LENGTH, 21  
bosTau4.refGene.LENGTH, 21  
braFlo1.xenoRefGene.LENGTH, 22  
caeJap1.xenoRefGene.LENGTH, 22  
caePb1.xenoRefGene.LENGTH, 23  
caePb2.xenoRefGene.LENGTH, 23  
caeRem2.xenoRefGene.LENGTH, 24  
caeRem3.xenoRefGene.LENGTH, 24  
calJac1.genscan.LENGTH, 25  
calJac1.nscanGene.LENGTH, 25  
calJac1.xenoRefGene.LENGTH, 26  
canFam1.ensGene.LENGTH, 26  
canFam1.geneSymbol.LENGTH, 27  
canFam1.genscan.LENGTH, 27  
canFam1.nscanGene.LENGTH, 28  
canFam1.refGene.LENGTH, 28  
canFam1.xenoRefGene.LENGTH, 29  
canFam2.ensGene.LENGTH, 29  
canFam2.geneSymbol.LENGTH, 30  
canFam2.genscan.LENGTH, 30  
canFam2.nscanGene.LENGTH, 31  
canFam2.refGene.LENGTH, 31  
canFam2.xenoRefGene.LENGTH, 32  
cavPor3.ensGene.LENGTH, 32  
cavPor3.genscan.LENGTH, 33  
cavPor3.nscanGene.LENGTH, 33  
cavPor3.xenoRefGene.LENGTH, 34  
cb1.xenoRefGene.LENGTH, 34  
cb3.xenoRefGene.LENGTH, 35  
ce2.geneid.LENGTH, 35  
ce2.geneSymbol.LENGTH, 36  
ce2.refGene.LENGTH, 36  
ce4.geneSymbol.LENGTH, 37  
ce4.refGene.LENGTH, 37  
ce4.xenoRefGene.LENGTH, 38  
ce6.ensGene.LENGTH, 38  
ce6.geneSymbol.LENGTH, 39  
ce6.refGene.LENGTH, 39  
ce6.xenoRefGene.LENGTH, 40  
ci1.geneSymbol.LENGTH, 40  
ci1.refGene.LENGTH, 41  
ci1.xenoRefGene.LENGTH, 41  
ci2.ensGene.LENGTH, 42  
ci2.geneSymbol.LENGTH, 42  
ci2.refGene.LENGTH, 43  
ci2.xenoRefGene.LENGTH, 43  
danRer3.ensGene.LENGTH, 44  
danRer3.geneSymbol.LENGTH, 44  
danRer3.refGene.LENGTH, 45  
danRer4.ensGene.LENGTH, 45  
danRer4.geneSymbol.LENGTH, 46  
danRer4.genscan.LENGTH, 46  
danRer4.nscanGene.LENGTH, 47  
danRer4.refGene.LENGTH, 47  
danRer5.ensGene.LENGTH, 48  
danRer5.geneSymbol.LENGTH, 48  
danRer5.refGene.LENGTH, 49  
danRer5.vegaGene.LENGTH, 49  
danRer5.vegaPseudoGene.LENGTH, 50  
danRer6.ensGene.LENGTH, 50

- danRer6.geneSymbol.LENGTH, 51  
 danRer6.refGene.LENGTH, 51  
 danRer6.xenoRefGene.LENGTH, 52  
 dm1.geneSymbol.LENGTH, 52  
 dm1.genscan.LENGTH, 53  
 dm1.refGene.LENGTH, 53  
 dm2.geneid.LENGTH, 54  
 dm2.geneSymbol.LENGTH, 54  
 dm2.genscan.LENGTH, 55  
 dm2.nscanGene.LENGTH, 55  
 dm2.refGene.LENGTH, 56  
 dm3.geneSymbol.LENGTH, 56  
 dm3.nscanPasaGene.LENGTH, 57  
 dm3.refGene.LENGTH, 57  
 dp2.genscan.LENGTH, 58  
 dp2.xenoRefGene.LENGTH, 58  
 dp3.geneid.LENGTH, 59  
 dp3.genscan.LENGTH, 59  
 dp3.xenoRefGene.LENGTH, 60  
 droAna1.geneid.LENGTH, 60  
 droAna1.genscan.LENGTH, 61  
 droAna1.xenoRefGene.LENGTH, 61  
 droAna2.genscan.LENGTH, 62  
 droAna2.xenoRefGene.LENGTH, 62  
 droEre1.genscan.LENGTH, 63  
 droEre1.xenoRefGene.LENGTH, 63  
 droGri1.genscan.LENGTH, 64  
 droGri1.xenoRefGene.LENGTH, 64  
 droMoj1.geneid.LENGTH, 65  
 droMoj1.genscan.LENGTH, 65  
 droMoj1.xenoRefGene.LENGTH, 66  
 droMoj2.genscan.LENGTH, 66  
 droMoj2.xenoRefGene.LENGTH, 67  
 droPer1.genscan.LENGTH, 67  
 droPer1.xenoRefGene.LENGTH, 68  
 droSec1.genscan.LENGTH, 68  
 droSec1.xenoRefGene.LENGTH, 69  
 droSim1.geneid.LENGTH, 69  
 droSim1.genscan.LENGTH, 70  
 droSim1.xenoRefGene.LENGTH, 70  
 droVir1.geneid.LENGTH, 71  
 droVir1.genscan.LENGTH, 71  
 droVir1.xenoRefGene.LENGTH, 72  
 droVir2.genscan.LENGTH, 72  
 droVir2.xenoRefGene.LENGTH, 73  
 droYak1.geneid.LENGTH, 73  
 droYak1.genscan.LENGTH, 74  
 droYak1.xenoRefGene.LENGTH, 74  
 droYak2.genscan.LENGTH, 75  
 droYak2.xenoRefGene.LENGTH, 75  
 equCab1.geneid.LENGTH, 76  
 equCab1.geneSymbol.LENGTH, 76  
 equCab1.nscanGene.LENGTH, 77  
 equCab1.refGene.LENGTH, 77  
 equCab1.sgpGene.LENGTH, 78  
 equCab2.ensGene.LENGTH, 78  
 equCab2.geneSymbol.LENGTH, 79  
 equCab2.nscanGene.LENGTH, 79  
 equCab2.refGene.LENGTH, 80  
 equCab2.xenoRefGene.LENGTH, 80  
 felCat3.ensGene.LENGTH, 81  
 felCat3.geneid.LENGTH, 81  
 felCat3.geneSymbol.LENGTH, 82  
 felCat3.genscan.LENGTH, 82  
 felCat3.nscanGene.LENGTH, 83  
 felCat3.refGene.LENGTH, 83  
 felCat3.sgpGene.LENGTH, 84  
 felCat3.xenoRefGene.LENGTH, 84  
 fr1.ensGene.LENGTH, 85  
 fr1.genscan.LENGTH, 85  
 fr2.ensGene.LENGTH, 86  
 galGal2.ensGene.LENGTH, 86  
 galGal2.geneid.LENGTH, 87  
 galGal2.geneSymbol.LENGTH, 87  
 galGal2.genscan.LENGTH, 88  
 galGal2.refGene.LENGTH, 88  
 galGal2.sgpGene.LENGTH, 89  
 galGal3.ensGene.LENGTH, 89  
 galGal3.geneSymbol.LENGTH, 90  
 galGal3.genscan.LENGTH, 90  
 galGal3.nscanGene.LENGTH, 91  
 galGal3.refGene.LENGTH, 91  
 galGal3.xenoRefGene.LENGTH, 92  
 gasAcu1.ensGene.LENGTH, 92  
 gasAcu1.nscanGene.LENGTH, 93  
 hg16.acembly.LENGTH, 93  
 hg16.ensGene.LENGTH, 94  
 hg16.exoniphy.LENGTH, 94  
 hg16.geneid.LENGTH, 95  
 hg16.geneSymbol.LENGTH, 95  
 hg16.genscan.LENGTH, 96  
 hg16.knownGene.LENGTH, 96  
 hg16.refGene.LENGTH, 97  
 hg16.sgpGene.LENGTH, 97  
 hg17.acembly.LENGTH, 98  
 hg17.acescan.LENGTH, 98  
 hg17.ccdsGene.LENGTH, 99  
 hg17.ensGene.LENGTH, 99  
 hg17.exoniphy.LENGTH, 100  
 hg17.geneid.LENGTH, 100  
 hg17.geneSymbol.LENGTH, 101  
 hg17.genscan.LENGTH, 101  
 hg17.knownGene.LENGTH, 102  
 hg17.refGene.LENGTH, 102

hg17.sgpGene.LENGTH, 103  
hg17.vegaGene.LENGTH, 103  
hg17.vegaPseudoGene.LENGTH, 104  
hg17.xenoRefGene.LENGTH, 104  
hg18.acembly.LENGTH, 105  
hg18.acescan.LENGTH, 105  
hg18.ccdsGene.LENGTH, 106  
hg18.ensGene.LENGTH, 106  
hg18.exoniphy.LENGTH, 107  
hg18.geneid.LENGTH, 107  
hg18.geneSymbol.LENGTH, 108  
hg18.genscan.LENGTH, 108  
hg18.knownGene.LENGTH, 109  
hg18.knownGeneOld3.LENGTH, 109  
hg18.refGene.LENGTH, 110  
hg18.sgpGene.LENGTH, 110  
hg18.sibGene.LENGTH, 111  
hg18.xenoRefGene.LENGTH, 111  
hg19.ccdsGene.LENGTH, 112  
hg19.ensGene.LENGTH, 112  
hg19.exoniphy.LENGTH, 113  
hg19.geneSymbol.LENGTH, 113  
hg19.knownGene.LENGTH, 114  
hg19.nscanGene.LENGTH, 114  
hg19.refGene.LENGTH, 115  
hg19.xenoRefGene.LENGTH, 115  
loxAfr3.xenoRefGene.LENGTH, 116  
mm7.ensGene.LENGTH, 116  
mm7.geneid.LENGTH, 117  
mm7.geneSymbol.LENGTH, 117  
mm7.genscan.LENGTH, 118  
mm7.knownGene.LENGTH, 118  
mm7.refGene.LENGTH, 119  
mm7.sgpGene.LENGTH, 119  
mm7.xenoRefGene.LENGTH, 120  
mm8.ccdsGene.LENGTH, 120  
mm8.ensGene.LENGTH, 121  
mm8.geneid.LENGTH, 121  
mm8.geneSymbol.LENGTH, 122  
mm8.genscan.LENGTH, 122  
mm8.knownGene.LENGTH, 123  
mm8.nscanGene.LENGTH, 123  
mm8.refGene.LENGTH, 124  
mm8.sgpGene.LENGTH, 124  
mm8.sibGene.LENGTH, 125  
mm8.xenoRefGene.LENGTH, 125  
mm9.acembly.LENGTH, 126  
mm9.ccdsGene.LENGTH, 126  
mm9.ensGene.LENGTH, 127  
mm9.exoniphy.LENGTH, 127  
mm9.geneid.LENGTH, 128  
mm9.geneSymbol.LENGTH, 128  
mm9.genscan.LENGTH, 129  
mm9.knownGene.LENGTH, 129  
mm9.nscanGene.LENGTH, 130  
mm9.refGene.LENGTH, 130  
mm9.sgpGene.LENGTH, 131  
mm9.xenoRefGene.LENGTH, 131  
monDom1.genscan.LENGTH, 132  
monDom4.ensGene.LENGTH, 132  
monDom4.geneSymbol.LENGTH, 133  
monDom4.genscan.LENGTH, 133  
monDom4.nscanGene.LENGTH, 134  
monDom4.refGene.LENGTH, 134  
monDom4.xenoRefGene.LENGTH, 135  
monDom5.ensGene.LENGTH, 135  
monDom5.geneSymbol.LENGTH, 136  
monDom5.genscan.LENGTH, 136  
monDom5.nscanGene.LENGTH, 137  
monDom5.refGene.LENGTH, 137  
monDom5.xenoRefGene.LENGTH, 138  
ornAna1.ensGene.LENGTH, 138  
ornAna1.geneSymbol.LENGTH, 139  
ornAna1.refGene.LENGTH, 139  
ornAna1.xenoRefGene.LENGTH, 140  
oryLat2.ensGene.LENGTH, 140  
oryLat2.geneSymbol.LENGTH, 141  
oryLat2.refGene.LENGTH, 141  
oryLat2.xenoRefGene.LENGTH, 142  
panTro1.ensGene.LENGTH, 142  
panTro1.geneid.LENGTH, 143  
panTro1.genscan.LENGTH, 143  
panTro1.xenoRefGene.LENGTH, 144  
panTro2.ensGene.LENGTH, 144  
panTro2.geneSymbol.LENGTH, 145  
panTro2.genscan.LENGTH, 145  
panTro2.nscanGene.LENGTH, 146  
panTro2.refGene.LENGTH, 146  
panTro2.xenoRefGene.LENGTH, 147  
petMar1.xenoRefGene.LENGTH, 147  
ponAbe2.ensGene.LENGTH, 148  
ponAbe2.geneSymbol.LENGTH, 148  
ponAbe2.genscan.LENGTH, 149  
ponAbe2.nscanGene.LENGTH, 149  
ponAbe2.refGene.LENGTH, 150  
ponAbe2.xenoRefGene.LENGTH, 150  
priPac1.xenoRefGene.LENGTH, 151  
rheMac2.ensGene.LENGTH, 151  
rheMac2.geneid.LENGTH, 152  
rheMac2.geneSymbol.LENGTH, 152  
rheMac2.nscanGene.LENGTH, 153  
rheMac2.refGene.LENGTH, 153  
rheMac2.sgpGene.LENGTH, 154  
rheMac2.xenoRefGene.LENGTH, 154

- rn3.ensGene.LENGTH, 155  
 rn3.geneid.LENGTH, 155  
 rn3.geneSymbol.LENGTH, 156  
 rn3.genscan.LENGTH, 156  
 rn3.knownGene.LENGTH, 157  
 rn3.nscanGene.LENGTH, 157  
 rn3.refGene.LENGTH, 158  
 rn3.sgpGene.LENGTH, 158  
 rn3.xenoRefGene.LENGTH, 159  
 rn4.ensGene.LENGTH, 159  
 rn4.geneid.LENGTH, 160  
 rn4.geneSymbol.LENGTH, 160  
 rn4.genscan.LENGTH, 161  
 rn4.knownGene.LENGTH, 161  
 rn4.nscanGene.LENGTH, 162  
 rn4.refGene.LENGTH, 162  
 rn4.sgpGene.LENGTH, 163  
 rn4.xenoRefGene.LENGTH, 163  
 sacCer1.ensGene.LENGTH, 164  
 sacCer2.ensGene.LENGTH, 164  
 strPur1.geneSymbol.LENGTH, 165  
 strPur1.genscan.LENGTH, 165  
 strPur1.refGene.LENGTH, 166  
 strPur1.xenoRefGene.LENGTH, 166  
 strPur2.geneSymbol.LENGTH, 167  
 strPur2.genscan.LENGTH, 167  
 strPur2.refGene.LENGTH, 168  
 strPur2.xenoRefGene.LENGTH, 168  
 taeGut1.ensGene.LENGTH, 170  
 taeGut1.geneSymbol.LENGTH, 170  
 taeGut1.genscan.LENGTH, 171  
 taeGut1.nscanGene.LENGTH, 171  
 taeGut1.refGene.LENGTH, 172  
 taeGut1.xenoRefGene.LENGTH, 172  
 tetNig1.ensGene.LENGTH, 173  
 tetNig1.geneid.LENGTH, 173  
 tetNig1.genscan.LENGTH, 174  
 tetNig1.nscanGene.LENGTH, 174  
 tetNig2.ensGene.LENGTH, 175  
 xenTro1.genscan.LENGTH, 176  
 xenTro2.ensGene.LENGTH, 176  
 xenTro2.geneSymbol.LENGTH, 177  
 xenTro2.genscan.LENGTH, 177  
 xenTro2.refGene.LENGTH, 178
- anoCar1.ensGene.LENGTH, 8  
 anoCar1.genscan.LENGTH, 9  
 anoCar1.xenoRefGene.LENGTH, 9  
 anoGam1.ensGene.LENGTH, 10  
 anoGam1.geneid.LENGTH, 10  
 anoGam1.genscan.LENGTH, 11  
 apiMel1.genscan.LENGTH, 11  
 apiMel2.ensGene.LENGTH, 12  
 apiMel2.geneid.LENGTH, 12  
 apiMel2.genscan.LENGTH, 13  
 aplCa11.xenoRefGene.LENGTH, 13
- bosTau2.geneid.LENGTH, 14  
 bosTau2.geneSymbol.LENGTH, 14  
 bosTau2.genscan.LENGTH, 15  
 bosTau2.refGene.LENGTH, 15  
 bosTau2.sgpGene.LENGTH, 16  
 bosTau3.ensGene.LENGTH, 16  
 bosTau3.geneid.LENGTH, 17  
 bosTau3.geneSymbol.LENGTH, 17  
 bosTau3.genscan.LENGTH, 18  
 bosTau3.refGene.LENGTH, 18  
 bosTau3.sgpGene.LENGTH, 19  
 bosTau4.ensGene.LENGTH, 19  
 bosTau4.geneSymbol.LENGTH, 20  
 bosTau4.genscan.LENGTH, 20  
 bosTau4.nscanGene.LENGTH, 21  
 bosTau4.refGene.LENGTH, 21  
 braFlo1.xenoRefGene.LENGTH, 22
- caeJap1.xenoRefGene.LENGTH, 22  
 caePb1.xenoRefGene.LENGTH, 23  
 caePb2.xenoRefGene.LENGTH, 23  
 caeRem2.xenoRefGene.LENGTH, 24  
 caeRem3.xenoRefGene.LENGTH, 24  
 calJac1.genscan.LENGTH, 25  
 calJac1.nscanGene.LENGTH, 25  
 calJac1.xenoRefGene.LENGTH, 26  
 canFam1.ensGene.LENGTH, 26  
 canFam1.geneSymbol.LENGTH, 27  
 canFam1.genscan.LENGTH, 27  
 canFam1.nscanGene.LENGTH, 28  
 canFam1.refGene.LENGTH, 28  
 canFam1.xenoRefGene.LENGTH, 29  
 canFam2.ensGene.LENGTH, 29  
 canFam2.geneSymbol.LENGTH, 30  
 canFam2.genscan.LENGTH, 30  
 canFam2.nscanGene.LENGTH, 31  
 canFam2.refGene.LENGTH, 31  
 canFam2.xenoRefGene.LENGTH, 32  
 cavPor3.ensGene.LENGTH, 32  
 cavPor3.genscan.LENGTH, 33  
 cavPor3.nscanGene.LENGTH, 33  
 cavPor3.xenoRefGene.LENGTH, 34  
 cb1.xenoRefGene.LENGTH, 34  
 cb3.xenoRefGene.LENGTH, 35  
 ce2.geneid.LENGTH, 35  
 ce2.geneSymbol.LENGTH, 36  
 ce2.refGene.LENGTH, 36  
 ce4.geneSymbol.LENGTH, 37  
 ce4.refGene.LENGTH, 37

- ce4.xenoRefGene.LENGTH, 38  
 ce6.ensGene.LENGTH, 38  
 ce6.geneSymbol.LENGTH, 39  
 ce6.refGene.LENGTH, 39  
 ce6.xenoRefGene.LENGTH, 40  
 ci1.geneSymbol.LENGTH, 40  
 ci1.refGene.LENGTH, 41  
 ci1.xenoRefGene.LENGTH, 41  
 ci2.ensGene.LENGTH, 42  
 ci2.geneSymbol.LENGTH, 42  
 ci2.refGene.LENGTH, 43  
 ci2.xenoRefGene.LENGTH, 43  
  
 danRer3.ensGene.LENGTH, 44  
 danRer3.geneSymbol.LENGTH, 44  
 danRer3.refGene.LENGTH, 45  
 danRer4.ensGene.LENGTH, 45  
 danRer4.geneSymbol.LENGTH, 46  
 danRer4.genscan.LENGTH, 46  
 danRer4.nscanGene.LENGTH, 47  
 danRer4.refGene.LENGTH, 47  
 danRer5.ensGene.LENGTH, 48  
 danRer5.geneSymbol.LENGTH, 48  
 danRer5.refGene.LENGTH, 49  
 danRer5.vegaGene.LENGTH, 49  
 danRer5.vegaPseudoGene.LENGTH, 50  
 danRer6.ensGene.LENGTH, 50  
 danRer6.geneSymbol.LENGTH, 51  
 danRer6.refGene.LENGTH, 51  
 danRer6.xenoRefGene.LENGTH, 52  
 dm1.geneSymbol.LENGTH, 52  
 dm1.genscan.LENGTH, 53  
 dm1.refGene.LENGTH, 53  
 dm2.geneid.LENGTH, 54  
 dm2.geneSymbol.LENGTH, 54  
 dm2.genscan.LENGTH, 55  
 dm2.nscanGene.LENGTH, 55  
 dm2.refGene.LENGTH, 56  
 dm3.geneSymbol.LENGTH, 56  
 dm3.nscanPasaGene.LENGTH, 57  
 dm3.refGene.LENGTH, 57  
 downloadLengthFromUCSC, 8–168, 170–178  
 dp2.genscan.LENGTH, 58  
 dp2.xenoRefGene.LENGTH, 58  
 dp3.geneid.LENGTH, 59  
 dp3.genscan.LENGTH, 59  
 dp3.xenoRefGene.LENGTH, 60  
 droAna1.geneid.LENGTH, 60  
 droAna1.genscan.LENGTH, 61  
 droAna1.xenoRefGene.LENGTH, 61  
 droAna2.genscan.LENGTH, 62  
 droAna2.xenoRefGene.LENGTH, 62  
 droEre1.genscan.LENGTH, 63  
 droEre1.xenoRefGene.LENGTH, 63  
 droGr11.genscan.LENGTH, 64  
 droGr11.xenoRefGene.LENGTH, 64  
 droMoj1.geneid.LENGTH, 65  
 droMoj1.genscan.LENGTH, 65  
 droMoj1.xenoRefGene.LENGTH, 66  
 droMoj2.genscan.LENGTH, 66  
 droMoj2.xenoRefGene.LENGTH, 67  
 droPer1.genscan.LENGTH, 67  
 droPer1.xenoRefGene.LENGTH, 68  
 droSec1.genscan.LENGTH, 68  
 droSec1.xenoRefGene.LENGTH, 69  
 droSim1.geneid.LENGTH, 69  
 droSim1.genscan.LENGTH, 70  
 droSim1.xenoRefGene.LENGTH, 70  
 droVir1.geneid.LENGTH, 71  
 droVir1.genscan.LENGTH, 71  
 droVir1.xenoRefGene.LENGTH, 72  
 droVir2.genscan.LENGTH, 72  
 droVir2.xenoRefGene.LENGTH, 73  
 droYak1.geneid.LENGTH, 73  
 droYak1.genscan.LENGTH, 74  
 droYak1.xenoRefGene.LENGTH, 74  
 droYak2.genscan.LENGTH, 75  
 droYak2.xenoRefGene.LENGTH, 75  
  
 equCab1.geneid.LENGTH, 76  
 equCab1.geneSymbol.LENGTH, 76  
 equCab1.nscanGene.LENGTH, 77  
 equCab1.refGene.LENGTH, 77  
 equCab1.sgpGene.LENGTH, 78  
 equCab2.ensGene.LENGTH, 78  
 equCab2.geneSymbol.LENGTH, 79  
 equCab2.nscanGene.LENGTH, 79  
 equCab2.refGene.LENGTH, 80  
 equCab2.xenoRefGene.LENGTH, 80  
  
 felCat3.ensGene.LENGTH, 81  
 felCat3.geneid.LENGTH, 81  
 felCat3.geneSymbol.LENGTH, 82  
 felCat3.genscan.LENGTH, 82  
 felCat3.nscanGene.LENGTH, 83  
 felCat3.refGene.LENGTH, 83  
 felCat3.sgpGene.LENGTH, 84  
 felCat3.xenoRefGene.LENGTH, 84  
 fr1.ensGene.LENGTH, 85  
 fr1.genscan.LENGTH, 85  
 fr2.ensGene.LENGTH, 86  
  
 galGal2.ensGene.LENGTH, 86  
 galGal2.geneid.LENGTH, 87  
 galGal2.geneSymbol.LENGTH, 87  
 galGal2.genscan.LENGTH, 88



- galGal2.refGene.LENGTH, 88
- galGal2.sgpGene.LENGTH, 89
- galGal3.ensGene.LENGTH, 89
- galGal3.geneSymbol.LENGTH, 90
- galGal3.genscan.LENGTH, 90
- galGal3.nscanGene.LENGTH, 91
- galGal3.refGene.LENGTH, 91
- galGal3.xenoRefGene.LENGTH, 92
- gasAcu1.ensGene.LENGTH, 92
- gasAcu1.nscanGene.LENGTH, 93
  
- hg16.acembly.LENGTH, 93
- hg16.ensGene.LENGTH, 94
- hg16.exoniphy.LENGTH, 94
- hg16.geneid.LENGTH, 95
- hg16.geneSymbol.LENGTH, 95
- hg16.genscan.LENGTH, 96
- hg16.knownGene.LENGTH, 96
- hg16.refGene.LENGTH, 97
- hg16.sgpGene.LENGTH, 97
- hg17.acembly.LENGTH, 98
- hg17.acescan.LENGTH, 98
- hg17.ccdsGene.LENGTH, 99
- hg17.ensGene.LENGTH, 99
- hg17.exoniphy.LENGTH, 100
- hg17.geneid.LENGTH, 100
- hg17.geneSymbol.LENGTH, 101
- hg17.genscan.LENGTH, 101
- hg17.knownGene.LENGTH, 102
- hg17.refGene.LENGTH, 102
- hg17.sgpGene.LENGTH, 103
- hg17.vegaGene.LENGTH, 103
- hg17.vegaPseudoGene.LENGTH, 104
- hg17.xenoRefGene.LENGTH, 104
- hg18.acembly.LENGTH, 105
- hg18.acescan.LENGTH, 105
- hg18.ccdsGene.LENGTH, 106
- hg18.ensGene.LENGTH, 106
- hg18.exoniphy.LENGTH, 107
- hg18.geneid.LENGTH, 107
- hg18.geneSymbol.LENGTH, 108
- hg18.genscan.LENGTH, 108
- hg18.knownGene.LENGTH, 109
- hg18.knownGeneOld3.LENGTH, 109
- hg18.refGene.LENGTH, 110
- hg18.sgpGene.LENGTH, 110
- hg18.sibGene.LENGTH, 111
- hg18.xenoRefGene.LENGTH, 111
- hg19.ccdsGene.LENGTH, 112
- hg19.ensGene.LENGTH, 112
- hg19.exoniphy.LENGTH, 113
- hg19.geneSymbol.LENGTH, 113
- hg19.knownGene.LENGTH, 114
  
- hg19.nscanGene.LENGTH, 114
- hg19.refGene.LENGTH, 115
- hg19.xenoRefGene.LENGTH, 115
  
- loxAfr3.xenoRefGene.LENGTH, 116
  
- mm7.ensGene.LENGTH, 116
- mm7.geneid.LENGTH, 117
- mm7.geneSymbol.LENGTH, 117
- mm7.genscan.LENGTH, 118
- mm7.knownGene.LENGTH, 118
- mm7.refGene.LENGTH, 119
- mm7.sgpGene.LENGTH, 119
- mm7.xenoRefGene.LENGTH, 120
- mm8.ccdsGene.LENGTH, 120
- mm8.ensGene.LENGTH, 121
- mm8.geneid.LENGTH, 121
- mm8.geneSymbol.LENGTH, 122
- mm8.genscan.LENGTH, 122
- mm8.knownGene.LENGTH, 123
- mm8.nscanGene.LENGTH, 123
- mm8.refGene.LENGTH, 124
- mm8.sgpGene.LENGTH, 124
- mm8.sibGene.LENGTH, 125
- mm8.xenoRefGene.LENGTH, 125
- mm9.acembly.LENGTH, 126
- mm9.ccdsGene.LENGTH, 126
- mm9.ensGene.LENGTH, 127
- mm9.exoniphy.LENGTH, 127
- mm9.geneid.LENGTH, 128
- mm9.geneSymbol.LENGTH, 128
- mm9.genscan.LENGTH, 129
- mm9.knownGene.LENGTH, 129
- mm9.nscanGene.LENGTH, 130
- mm9.refGene.LENGTH, 130
- mm9.sgpGene.LENGTH, 131
- mm9.xenoRefGene.LENGTH, 131
- monDom1.genscan.LENGTH, 132
- monDom4.ensGene.LENGTH, 132
- monDom4.geneSymbol.LENGTH, 133
- monDom4.genscan.LENGTH, 133
- monDom4.nscanGene.LENGTH, 134
- monDom4.refGene.LENGTH, 134
- monDom4.xenoRefGene.LENGTH, 135
- monDom5.ensGene.LENGTH, 135
- monDom5.geneSymbol.LENGTH, 136
- monDom5.genscan.LENGTH, 136
- monDom5.nscanGene.LENGTH, 137
- monDom5.refGene.LENGTH, 137
- monDom5.xenoRefGene.LENGTH, 138
  
- ornAna1.ensGene.LENGTH, 138
- ornAna1.geneSymbol.LENGTH, 139



- ornAna1.refGene.LENGTH, 139
- ornAna1.xenoRefGene.LENGTH, 140
- oryLat2.ensGene.LENGTH, 140
- oryLat2.geneSymbol.LENGTH, 141
- oryLat2.refGene.LENGTH, 141
- oryLat2.xenoRefGene.LENGTH, 142
  
- panTro1.ensGene.LENGTH, 142
- panTro1.geneid.LENGTH, 143
- panTro1.genscan.LENGTH, 143
- panTro1.xenoRefGene.LENGTH, 144
- panTro2.ensGene.LENGTH, 144
- panTro2.geneSymbol.LENGTH, 145
- panTro2.genscan.LENGTH, 145
- panTro2.nscanGene.LENGTH, 146
- panTro2.refGene.LENGTH, 146
- panTro2.xenoRefGene.LENGTH, 147
- petMar1.xenoRefGene.LENGTH, 147
- ponAbe2.ensGene.LENGTH, 148
- ponAbe2.geneSymbol.LENGTH, 148
- ponAbe2.genscan.LENGTH, 149
- ponAbe2.nscanGene.LENGTH, 149
- ponAbe2.refGene.LENGTH, 150
- ponAbe2.xenoRefGene.LENGTH, 150
- priPac1.xenoRefGene.LENGTH, 151
  
- rheMac2.ensGene.LENGTH, 151
- rheMac2.geneid.LENGTH, 152
- rheMac2.geneSymbol.LENGTH, 152
- rheMac2.nscanGene.LENGTH, 153
- rheMac2.refGene.LENGTH, 153
- rheMac2.sgpGene.LENGTH, 154
- rheMac2.xenoRefGene.LENGTH, 154
- rn3.ensGene.LENGTH, 155
- rn3.geneid.LENGTH, 155
- rn3.geneSymbol.LENGTH, 156
- rn3.genscan.LENGTH, 156
- rn3.knownGene.LENGTH, 157
- rn3.nscanGene.LENGTH, 157
- rn3.refGene.LENGTH, 158
- rn3.sgpGene.LENGTH, 158
- rn3.xenoRefGene.LENGTH, 159
- rn4.ensGene.LENGTH, 159
- rn4.geneid.LENGTH, 160
- rn4.geneSymbol.LENGTH, 160
- rn4.genscan.LENGTH, 161
- rn4.knownGene.LENGTH, 161
- rn4.nscanGene.LENGTH, 162
- rn4.refGene.LENGTH, 162
- rn4.sgpGene.LENGTH, 163
- rn4.xenoRefGene.LENGTH, 163
  
- sacCer1.ensGene.LENGTH, 164
  
- sacCer2.ensGene.LENGTH, 164
- strPur1.geneSymbol.LENGTH, 165
- strPur1.genscan.LENGTH, 165
- strPur1.refGene.LENGTH, 166
- strPur1.xenoRefGene.LENGTH, 166
- strPur2.geneSymbol.LENGTH, 167
- strPur2.genscan.LENGTH, 167
- strPur2.refGene.LENGTH, 168
- strPur2.xenoRefGene.LENGTH, 168
- supportedGeneIDs, 169
- supportedGenomes, 169
  
- taeGut1.ensGene.LENGTH, 170
- taeGut1.geneSymbol.LENGTH, 170
- taeGut1.genscan.LENGTH, 171
- taeGut1.nscanGene.LENGTH, 171
- taeGut1.refGene.LENGTH, 172
- taeGut1.xenoRefGene.LENGTH, 172
- tetNig1.ensGene.LENGTH, 173
- tetNig1.geneid.LENGTH, 173
- tetNig1.genscan.LENGTH, 174
- tetNig1.nscanGene.LENGTH, 174
- tetNig2.ensGene.LENGTH, 175
  
- unfactor, 175
  
- xenTro1.genscan.LENGTH, 176
- xenTro2.ensGene.LENGTH, 176
- xenTro2.geneSymbol.LENGTH, 177
- xenTro2.genscan.LENGTH, 177
- xenTro2.refGene.LENGTH, 178